Q ¸ `

RG-S3760E 2Ï ë x 6

RGOS 10.4(3b19)

(Ä â

Jä K5%4°©2000-2012

Jä K5%4°(Ý È J ±+- Í ` ž Ä â,X Ô Û ý Ä

þ k Jä K5%4°,X :M6AŒ Ã Ë) Ž á k ¹ Ï) • ã ê 6 ã Í ` Y,X Ï)F¼ ÚE¯>
á Ã ,) Ã Û Ñ Ã Â Ã ô • Ã5ïA¥ ä J ªAÁ?Ô Ã Ú J <F¼ êF¼ Ú*ü b î*üEè Ä

Ã Ã Ã

Ã Ã Ã Ã

RGNOS® Ã Ã Ã

Ã FÑ Jä K5%4°,X"¼ ` Û È á k Ó f Ä

!B÷ Ä â

` Y • q B)„ Ý µ C 0 È+ b { •(4{ ê J ª s ´ È J Y • Ý Ã6Ñ ¬ È ÄJä
K5%4° ±+- ü"u Ý Ï)Eî-¹ ê5Ù ¤/ ,X ™ ‰ ß Í ` Y •E¯> Â ,X ý Ä

` ™ 0  S*ü Û Ð ÈJä K5%4° ü4ê m  ` Ê Æ o ±A• J Y • š.B ÃM4 È J á
.B ± ` Y • ` <"u ÝJíAÃ êF+$ã È ` ,X Ý µ C 3 á X ä Ï) â/ ê k/ ,X ™
± Ä

T Õ

Jä K5%4° l •5%0- Öhttp://www.ruijie.com.cn/ Ä

| Ã ¹ ü l5% 9‹ k Ô „X { • T C m Ã{ • Lp s ´ žKÂNl Ú d Ã{ •,X h *ü?· ‡ • ÃEC Ê 4{C m1 1 Ä

Jä K5%4° ü4“ v á Öhttp://webchat.ruijie.com.cn Ä

| Ã ¹ ü ¹ 0 ¹ ½8:30 7Ç .6 &• ÈÆîE› ü4“ v á 9‹ k µ C |A¶ ÃE°/ßA×A© fLp Ã EC Ê4È x1 T Õ Ä ´LÔ ßEQ v 0Ã È Ã ¹ G Ê þ Ò Ã ¥L Ê È • “ ¿ K Ä

Jä K5%4°E°/ß T Õ — Öhttp://www.ruijie.com.cn/service.aspx Ä

Jä K5%4°E°/ß T Õ — Ã ¹ Ý,X v ¤ o LÔ?U,X T } `?· ‡ • Ä Í b v F ,X { •,X]>™ ÃEC Ê,XG!5B ¹ ž J W,X5%4° û6Ñ,XKÂNl È v á u —FÑ Ú ¤ oE™Eó,X T Õ Ä

7 h24 ã Ê T á u&Á4“ Ö4008-111-000

Jä K5%4° T AŽ / Ö http://support.ruijie.com.cn

Jä K5%4° T Õ â ¡O\ µ1… Öservice@ruijie.com.cn

‚Ì GC m

` á/Ä	AÈ â

` Ÿ4¡ Z { • ü s6Ñ `(=)Ú Þ•ÞX@ lÚÝQ@$0DT3‰ž B ÿPÑ,XK+ 4!0Ã yš@{Vô]>Ì€ { •]>™ `

5XLMLHV"
VKRZWDUWFKDWVWDUWWHUPLQOVHUYLFH

ØÕXÐ,X}¡CÈVG5Byß¥XQa” ><”ip address” È
ýÆÐ

5XLMLHFRQJILD"
$‰&'3DGGUHVV
GKFS,3GGUHVVYLD'+&3
5XLMLHFRQJILSDGGUHVV

EGÊ **ip address**
S*ÛHOHEg9ßÑA
S*ü **show aliases**

ËG5B_Ð ß¥’5B<G5BßS*Qdef-route” ><TAxCÃA’5B”ip route 0.0.0.0 0.0.0.0 192.168.1.1”Ö

5XLMLHFRQJXUHWHUPLQO
5XLMLHFRQJDOLDVFRQJGHIURXWHLSURXWH
5XLMLHFRQJGHIURXWH"
GHIURXWH LSURXWH
5XLMLHFRQJHQ
5XLMLHVKRZOLDVHVFRQJ
JOREOHFRQJXUHPRGHDOLDV
GHIURXWHLSURXWH

ÏÎGQ

Q	EÄ
show aliases	¡A’5B

ËGÄß

1.2 privilege

?U6QX> LßÃG5BßS*ü **privilege**
no EÑMßQ6AxÄ
privilege *mode* [**all**] {**level** *level* **| reset**} *command-string*
no privilege *mode* [**all**] [**level** *level*] *command-string*

ÐAß

Ð	EÄ
mode	?U\XQX CLI Q
all	ûQXßXLß{ÿ
level *level*	ûßXE> L{ßÿX8È 0-15
reset	QX> L6TAx4{ÿ
command-string	**?UQú**

ĭ5,Õ5BĐ -

ë Ð <G5Bã

Ï5*Ð ß</ÊÚ¼ **privilege** ÐÇ X CLI ÐK+æXA ÐÇ

DGÐÐG5Bã*ü **privilege ?** CLI Ð

ã	Aã
config	<G5Bã
exec	(Mã
interface	yG5Bã
ip-dhcp-pool	DHCP ¼G5Bã
keychain	KeyChain G5Bã
keychain-key	KeyChain-key G5Bã
time-range	Time-Range G5Bã

ĬG5B_Đ ßÐ’5B CLI 4{ÿ 1 ,X¸"test" Ð’5B> reload ÇXLÐ’Ú

```
5XLMLHFRQJHQEOHVHFUHWOHYHOWHVW
5XLMLHFRQJSULYLOHJHH[HFOHYHOUHORDG
```

8Ê*ä{ÿ 1 E9 CLI + M6æ*ü reload Ç

```
5XLMLHUHORDG"
/,1(5HDVRQRUUHORDG
FU!
```

Vp?UÚ reload ,X<FÐÑ4{ÿ 1 ,X*Ð*ü all GK+Ö

```
5XLMLHFRQJSULYLOHJHH[HFOOOHYHOUHORDG
```

8Ê*ä{ÿ 1 E9 CLI + M6æ*ü reload ,X<FÇ

```
5XLMLHUHORDG"
/,1(5HDVRQRUUHORDG
DWUHORDGDWDVSHFLILFWLPHGDWH
FDQHOFDQHOSHQLQUHORDGVFKHPH
LQHORDGDIWHUDWLPHLQWHUYDO
```

ÏÎGÐ

Ç	Ð Ä
enable secret	**A5B** CLI 4{ÿX¸

ĬGÄæ -

1.3 show aliases

?U/,ÝXÐMnÐÐ EXEC ß*ü **show aliases** Ç

show aliases [*mode*]

ÐAæ

Ð	Ð Ä

mode	

Ъ,Õ5BÐ	-
	EXEC ã
Ъ*Ð	VpùÉg9ÐXÐ'5BÄ
Ü5B_Ð	EXEC ÐKÐ

```
5XLMLHVKRDOLDVHVH[HF
H[HFPRGHDOLDV
KKHOS
SSLQ
VVKRZ
XXQHXJ
XQQHXJ
```

ÏÜÐ	EÄ
alias	A'5BÐ

2

2.1 banner login

?UG5B,O)ÑlÇÀËG5Bâ Ç **banner login**ÄUÐÑlÇ55Bti

no banner login Ö

banner login *c message c*

ÐAê	Ð	Ä
	c	*ÇXÚh0ÀÊ50ú*
	message	*ÄÉÇÉQnÊ*

Ï5,Õ5BÐ -

Ïç (M*ã

Ï*ê ÔGÄ8ECÊsÊKÛ@ÊsÄalendar Á@Ês++4PE|ÈSsÄ'ÔKÁ¡X™
¾6ÕÍDÊ
Vp2Ï¾XECÊs`@ÊsÄÊbECÊsÈ'X4ÈÔUÊEAÉCÊs
B,XÊè@ÊsÄ

ÏG5B_Ð S*ÙÑCÊs,XÊè@ÊsÄ
5XLMLHFORFNXSGDWHFDOHQDU

ÏÎGÇ

Ç	ÊÄ
-	-

ÏGÄè -

2.6 disable

(MÈUL¹ÙX4{èÊ (M*Ç **disableÄ**
disable [*privilege-level*]

ÐAè

Ð	ÊÄ
privilege-level	L$4{

Ï5,Õ5BÐ -

Ïç (M*ã

Ï*ê S*ÄÇM*ãÊÎ¹ptL$4{Ê$4{LÛ,X
L$4{Ä

disable

Ï5B_Ð M6,X/_G5BA'Û$4{L14{Ö
5XLMLHGLVDEOH

ÏÎGÇ

Ç	ÊÄ
enable	ÎÊ9(M*ê,Ò)È4{ÿÄ

ÏGÄè -

2.7 enable

?UE9(M*ÀÊ BE†G5BQ **enable**Ä

enable

ÐAÀ

Ð	Ä
-	-

Ö,Õ5BÐ -

Ð -

Ö*Ð -

G5B_Ð -

ÎGÐ

Q	Ä
-	-

GÄÀ -

2.8 enable password

?UG5BÀ4{ýXÊ <G5BQ **enable password**ÄÐ no 8Ô4{ýX·

Ä

enable password [**level** *level*] {*password* | [**0** | **7**] *encrypted-password*}

no enable password [**level** *level*]

ÐAÀ

Ð	Ä	
Password	*E9(M	EXEC G5B,X;
Level	*ýX4{ý	
0|7	;Xt2O_È	tÈ 7 1T)tš
encrypted-password	[	

Ö,Õ5BÐ -

Ð <G5Bã

Ö*Ð

EÑNOEg9t2O_ÀÀIC+A'tÊ;XÊÔUEg9t2O_Ä

ýÑVÖ

ÑOý 1 26 ß+Þ++0Ä

M6ÀÑNÈÑ9ÄÊSX0N0;XÊÀ4

EXEC

ËG5B_Ð	M6,X/_A’5B; pw10Ö	
	5XLMLHFRQJHQEOHSDVVZRUGSZ	
ÏÎGÐ	Ç	ÆÄ
	enable secret	A’5B]<,X;

ËGÄè -.002 Tc 0.0042 Tw 7.[(pw)23g32780323g32( )Tj5.197.4.754 g.9/TT0 1 T1007 -Tw 7.1

2.10 enable service

?UêÐKÂ¸XáäSSH Server/Telnet Server/Web Server/Snmp AgentÊ5BÃ

Ѕ*Ò **enable service** Ö

enable service { **ssh-server** | **telnet-server** | **web-server** | **snmp-agent**}

ÐAê

Ð	Ë Ä		
ssh-server	**ê**	SSH Server Èêé	IPv4 ` IPv6 á
telnet-server	**êÍ**	Telnet Server Èêé	IPv4 ` IPv6 á
web-server [http | https | all]	**êÍ**		

	Ð	Ë Ä
	enable	**6** **enable password** ê **enable secret** Ò5B **>** AxA **O** 15 4{ ,XÄ¼TAxG*ü enable AxAÄ
	local	**6** username Ò5B,X*ê> AxA È*MO4¥ 15 4{LÄ

Ö,Õ5BÐ 2¼TAxG*ü enable AxAÄ

Ëê <G5Bã

Ö*ô AÇA'5B Web ,O)AxAÄ*ü **no ip http authentication** Ò5BÄxÄ

Ö5B_Ð MI6,X/_È'5B Web ,O)Ê*ü local AxAÄ
5XLMLHFRQJLSKWWSDXWKHQWLFDWLRQRFDO

ÏÎGÒ

Ò	Ë Ä
enable service	**6**

ÖÄÈ -

2.15 ip http port

?UA'5BHTTP á,X0Ê5BÄ*ü **ip http port** Ò

ip http port *number*

ÖÐÈ

Ð	Ë Ä
number	*A* HTTP Server 0ÃAx 80Ä

Ö,Õ5BÐ TAx 80Ä

Ëê <G5Bã

Ö*ô AÇA'5B HTTP á,X0Ã*ü **no ip http port** ÓÃ5BÄxÄ

Ö5B_Ð MI6,X/_È'5B HTTP á0Ã 8080Ö
5XLMLHFRQJLSKWWSSRUW

ÏÎGÒ

Ò	Ë Ä
enable service	**6**

ÖÄÈ -

2.16 ip http secure-port

?UA'5BHTTPS á,X0ÃG5BBÃ*ü **ip http secure-port Ò**

ip http secure-port *number*

ÐAà

Ð	ÆÄ
number	*AB* HTTPS Server 0ÃAx 443Ä

5,Ò5BÐ TAx 443Ä

ð <G5Bã

Ã*Ð AÇÐA'5B HTTPS á,X0Ã*ü **no ip http secure-port ÒÃ5BxÄ**

Ò5B_Ð MI6,X/_È'5B HTTPS á0Ã 4443Ö

5XLMLHFRQJLSKWWSVHFXUHSRUW

ÎÒÐ

Ò	ÆÄ
enable service	**ÐÑ**
show web-server status	*/* web á<(Ã

ÒÄà -

2.17 ip telnet source-interface

?UÛýÞX IP 0 Telnet E,X0Ã5BÃ*ü **ip telnet source-interface Ò**

ip telnet source-interface *interface-name*

ÐAà

Ð	ÆÄ

ð	Q	Ë Ä
	telnet	¸ Ô Telnet á<Ä

Ï GÄ è -

2.18 lock

?U 40 Ã'5B Ô Ê X È Ë EXEC ð Q **lockÄ**
lock

Ï Ð A è

Ð	Ë Ä
-	-

Ï ,Õ 5B Ð -

Ï ð (M*ã

Ï S*Ô 4E Ë A'5B Ê X ð ÿ A ¡ X Ê 0 Ã M6 Ł 6 A K Ê Ë PxJ Õ e
0 Ã M6Ö

1 Ô Ë g9 **lock** ¿ Ì Ë g9 ×

1 & Ë g9 Ê 0 Ã g9 Ì ¿ BAxEg9,X Ì ¿ 8
Ì È/Locked Q ×

?U Ç Ë 9 40 Ê Ô UEg9A'5B,X Ê

?U 40 Ã * 1 0 Ã s6 Ł Ô UE Ë ü line G5B **lockable** X line Þ
Õ 0 Ã X(M Ä

Ï G5B_Ð M6,X/_J Õ Ã M6Ö

```
5XLMLHFRQJOLQHORFNDEOH
5XLMLHFRQJOLQHQ
5XLMLHORFN
3DVVZRUGSDVVZRUG!
$DLQDVVZRUG!
/RFNHG
Ï G5B_VnA9Ð/RINè
```

2.19 lockable

?UÕõ*ü **lock** line G5Bß **lockable**
lock **no** 5
lockable
no lockable

ÐAß	Ð	Ä
	-	-

Ь,Õ5BÐ -

line G5Bã

A lock EXEC **lock**

M6,X/_ Xs6 5XLMLHFRQJOLQHFRQROH
5XLMLHFRQJOLQHORFNDEOH
5XLMLHFRQJOLQHQR
5XLMLHORFN
3DVVZRUGSDVVZRUG!
3DLQSDVVZRUG!
/RFNHG
3DVVZRUGSDVVZRUG!

ÎG	Q	Ä
	lock	Õ

G -

2.20 login

ü AAA GK X 1T),X,O) yG5BQ **login**
X **no** 6 D)
login
no login

ÐAß	Ð	Ä
	-	-

Ь,Õ5BÐ -

é line G5Bã

Ï*Ê Vpù'ý AAA]<áÈ,O)AxAÊ1T),XÞÄG,XÛ VTY ê
console yG5B,XÄ

ÏG5B_Ð ÑM6,X/_ù VTY Ð’5B,O)ÞÄ
5XLMLHFRQJXUDDDDDDDDRGHO
5XLMLHFRQJOLQHYW\
5XLMLHFRQJOLQHSDVVZRUGUPDWHVW
5XLMLHFRQJOLQHORJLQ

ÏÎGÐ

Ç	ÆÄ
password	**G5B** line 4ÇÃO);

ÏGÄÈ -

2.21 login authentication

ü AAA ÎXÈ)AxAÑOG*ü AAA á9E> AxAÈ*ÄÇ6(,O)AxAÈ<Ä
AÇX no 6È8,O)AxAÈ<Ä

login authentication {**default** | *list-name*}

no login authentication {**default** | *list-name*}

ÏÐAÈ

Ð	ÆÄ
default	*ÆxXAxAÈ*
list-name	*ÆÈ*

Ï,Õ5BÐ -

éÐ line G5Bã

Ï*Ê Vp*ü AAA]<áÈ,O)AxAÊ*ü,XÈ<E> AxAÄ

ÏG5B_Ð

ÏGÄê -

2.25 privilege mode

?ÉLI Ê

ÐAê	Ð	Ä
	-	-

Ï,Õ5BÐ ?ÉLI Ê

ê ?ÉLI Ê

Ï*Ô ?ÉLI Ê

Ï5B_Ð ?ÉLI Ê

ÎGÐ	Ð	Ä
	-	-

ÏGÄê -

2.26 prompt

?UA’5B2Ï¾X ÐèG5Bê Ð **prompt** ÄU ê5Bü **no prompt** Ð

prompt *string*

ÐAê	Ð	Ä
	string	Ð 32 þ0ú

Ï,Õ5BÐ -

ê <G5Bã

Ï*Ô Vp4üÉ5B Ð Ï ÐÚc-2Ï X Ð

0Ú EXEC

Ï5B_Ð M6,X/_Ú5B Ð ú RGOSÖ

```
5XLMLHFRQJSURPSW5*26
5XLMLHFRQJHQ
5*26
```

ÏĈĢĐ

Ç	ÉÄ
-	-

ĞÄåè -

2.27 reload

?UGÆ'ĐÏ4ÈÉ (M*ðÇ **reload**Ä

reload [*text* | **in** [*hh:*] *mm* [*text*] | **at** *hh:mm* [*month day year*] [*text*] | **cancel**]

ĐÄåè

Ð	ÉÄ
text	ØsÉ-255 þ8V
in [*hh:*] *mm*	ûÈhæè 24 ý
at *hh:mm*	ûXÐÏ
month	ÃÖæ 3 Ñlar
day	æ 1 31
year	ÆÄ993-2035 åÑ*ú
cancel	Æuæ

Ğ,Ğ5BÐ -

ðÇ (M*ã

Ğ*ûÐ S*ÀåÑA'ûÙ,XÐÊ> 1u)ÆÙ

ĞŠ5B_Đ MÙ6,X/_ûÙ 10 ÚŁĞ¿Ï4ÖÖ

```
5XLMLHUHORDGLQ
5RXWHUZOOUHORDGLQHFRQV
```

ĪĈĢĐ

Ç	ÉÄ
-	-

ĞÄåè -

2.28 service password-encryption

?UÉ> tèÉË service password-encryption ÈÝQX no 6ñ,ÑÐÉ 4ðXñðÉÄ

service password-encryption

ĐÄåè

Ð	ÉÄ
-	-

2.30 show clock

2.35 show this

?U¡Ä¼ÃXG5BÇÈÍ6> Ç **show thisÄ**

show this

ÐAê	Ð	ÆÄ
	-	-

Ö,Õ5BÐ ´

êÇ yã

Ö*Ûê S*ÄãXG5BÇÄ

Ö5B_Ð ÍÍ6,X/_¡ß interface fastEthernet 0/1 ßXG5BÇÄ

```
5XLMLHFRQJLJ9HUIDFHIDVW(WKHUQHW
5XLMLHFRQJI)DVW(WKHUQHWVKRZKLV
%XLOGLQFRQJXUDWLRQ

VDYHGWUHHOLQHSHSRLQWRSRLQW
VDYHGWUHPVWSRUWSULRULW\

HQG
5XLMLHFRQJI)DVW(WKHUQHW
```

ÏÎGÇ

Ç	ÆÄ
-	-

ÖÄê 10.4(3b19) (Ãýê*ü show this ÇWÂS*ü show this Ç

2.36 show startup-config

?U¡Ç¦ü NVRAMÄÍ2çîc,¦|<Å'ÎXG5BÆÈ (M*ÇÇ **show startup-configÄ**

show startup-config

ÐAê	Ð	ÆÄ
	-	-

ê ,|ü NVRAMÄ¼2ûc,¸|<Å'ÎXG5BG startup-config A'|Ê ,XG5BÄ
startup-config ÎX±bA'Ù5B Flash ,XTÁxG5B[Êconfig.text ,XG5BÄ

ÏG5B_Ð -

ÎÌGÐ

Ò	ÊÄ
-	-

ÏGÄê -

2.37 show version

?U¦Ò2Ï³XÇÃMê **show version Ö**
show version [**devices | slots**]

ÐÄê

Ð	ÊÄ
devices	***ÐÌÂÇ***
slots	***ÐÌÑ***

Ï – D A È

2.38 show web-server status

?U¹ Web áG5BQ¿(ÕË Q **show web-server statusÄ**

show web-server status

ËDAè

Þ	ÆÄ
-	-

Ë5,Õ5BÐ -

è Q (M*ã

Ë*Ô -

ËG5B_Ð / Web áG5BQ¿(Õ

```
5XLMLHVKRZEVHUYHUVWDWXV
KWWSVHUYHUVWDWXVHQEOHG
KWWSVHUYHUSRUW
KWWSVVHUYHUVWDWXVHQEOHG
KWWSVVHUYHUSRUW
```

ÏÎGÐ

Q	ÆÄ
-	-

ËGÄè -

2.39 speed

?UG5B40ÃºÃ'ÛXEÐ[ÈCÕ5BÈ Q **speed** *speed*

Sú **no speed Ø Q**

speed *speed*

ËDAè

Þ	ÆÄ
Speed	0ÃÝÛ6Ê bpsÁ> yÈÑgEÐ[A'5B 9600Ã 19200Ã 38400Ã57600 Ã 115200 ,XÐ[,ÕXEÐ[9600Ä

Ë5,Õ5BÐ 5,ÕXEÐ[9600

è Q <G5Bã

Ë*Ô S*AQ'5B40ÃºÃ'ÛXEÀÆÐ[Ä

ËG5B_Ð M6,X/_ÉÐ[A'5B 57600 bpsÖ

```
é
é
```

ÏÎGĐ

Ç	Ë Ä
-	-

ÏGÄê -

2.40 telnet

?U,O)Ê Telnet á<È EXEC(ÄMê*ü **telnet** Ę>ÒÄ

telnet *host* [*port*] [*I***source** {**ip** *A.B.C.D* **| ipv6** *X:X:X::X* **| interface** *interface-name}*]

ÐAê

Ð	Ë Ä
Host	Telnet á<,X IPV4 Ã IPV6 ê
Port	Telnet á<,X TCP 0Ë Ax 23
/source	*ô* Telnet v0Ã*¡X IP ê
ip *A.B.C.D*	*ô* Telnet v0Ã*¡X IPV4
ipv6 *X:X:X::X*	*ô* Telnet v0Ã*¡X IPV6
interface *interface-name*	*ô* Telnet v0Ã*¡X

ï,Õ5BÐ -

ę (Mã

Ï*ô A Ç,O)Ê telnet á<Ä

Ï5B_Đ _ 1 6,X_È telnet ,X,ÂXA'Û IPV4 192.168.1.1 Ã*TÄx Gi 0/1È

ôA¶X VRF CÁ>< vpn1

```
5XLMLHWHOHQWVRXUFHLQWHUIDFHJLJDELW(WKHUQWYUIYSQ
```

_ 2 6,X_ telnet ,X,ÂXA'Û IPV6 2AAA:BBBB::CCCC

```
5XLMLHWHOHQWV$%%%%&&&&
```

ÏÎGĐ

Ç	Ë Ä
ip telnet source-interface	ô IP 0 Telnet E ,X
show sessions	Ę E! Telnet Ô,ŸXÎA±
exit	EÊ

ÏGÄê **-**

2.41 username

?UA'5B*Ë <G5BĘ **username**Ä

username *name*{**nopassword**|**password**{*password* | [**0|7**]*encrypted-password* }}

username *name* **privilege** *privilege-level*

no username *name*

ÐAð	Ð	ÐÄ
	name	ð
	password	ð
	0|7	ð tð 7 1T)tš
	encrypted-password	ð
	privilege-level	ð

Ð,Õ5BÐ -

ðÐ <G5Bã

Ð*ðÐ AðÐ0*ÐBgðAxAÐ*Ä

7

7

7

ÐG5B_Ð ð6,X/_G5Bðð4ð*4ð 15 4{Ö

5XLMLHFRQJXVHUQPHWHVWSULYLOHJHSDVVZRUGSZ

ÎÐGÐ Ð ÐÄlogin locel

Ï*Ô	Ô*ô[Ê×ÇL$
Ï5B_Ð	Ñ6,X/_G5B*ü test K[ÊÃXAïmLÏÔ 5XLMLHFRQJXVHUQPHWHVSHUPLVVLRQZ Ñ6,X/_G5B/U6*ü test [ÊÑÖ 5XLMLHFRQJXVHUQPHWHVSHUPLVVLRQOO Ñ6,X/_G5B*ü test L8Z config.text [ÊW[ÊKÃmÃLÔ 5XLMLHFRQJXVHUQPHWHVSHUPLVVLRQRQJWH[W 5XLMLHFRQJXVHUQPHWHVSHUPLVVLRQZ

ÏÎGÇ	Ç	ÉÄ
	-	-

ÏGÄÔ	-

2.43 username reject rlogin

?UL$ïïE/ÇÖ)Ï TELNET/SSH/HTTP 1ÔÉ <G5BÇ **username reject rloginÄ**

username *name* **reject rlogin**

no username *name* **reject rlogin**

ÐAÔ	Ð	ÉÄ
	name	ñ

ï,Õ5BÐ	-

Ç	<G5Bã

Ï*Ô	AÇ[L$ïïE/ÇÖ)ÈG5BZÏÈ> E/ÇÖ)2Ô*ñ ñÑE/ÄKÂ

Ï5B_Ð	Ñ6,X/_L$È> E/ÇÖ)Ö 5XLMLHFRQJXVHUQPHWHVWUHMHFWUORJLQ

ÏÎGÇ	Ç	ÉÄ
	login local	**E>AxA•**

ÏGÄÔ	-

2.44 write

ÍÏ¼ïG5BÄunning-config æÅ5BÄ

write [**memory** | **network** | **terminal**]

ÐAåè

Ð	ÆÄ
memory	*Íïèm9* NVRAMÈèa **copy running-config startup-configÄ**
network	*Íïè±* TFTP á<Èèa **copy running-config tftpÄ**
terminal	*Íïè Èèa* **show running-configÄ**

Ï¿ÕG5BÐ -

ïð (M*ã

Ï*ðÐ AÇ¢ïbJS¨XS*ïæÅxÃ±-ð*ïS*Ä

ÏG5B_Ð _ 1ïð¥)Ä'ïÍ¼ïG5BÖ

```
5XLMLHØLWH
%XLOGLQFRQJXUDWLRQ
>2.@
```

ÎÏGÐ

Ç	ÆÄ
copy	**ÁÛG5ÞÊ>ã**
show running-config	**ßÍ¼ïG5B**

ÏGÄåè **-**

3 LINE

3.1 access-class

A'5B Line ß*¡X ACLÄ¥Kâ¢Ø¾ü **access-class** { *access-list-number* | *access-list-name* } { **in | out** } Œ5B Line ß¡XA'K Â è<Ä5*ü **no access-class** { *access-list-number* | *access-list-name* } {**in | out**} ¥Ð LINE ß¡X ACL G5BÄ

access-class { *access-list-number* | *access-list-name* } {**in | out**}

no access-class { *access-list-number* | *access-list-name* } {**in | out**}

ÐAÐ	Ð	EÄ c c | access(Li)-3(n)(out)]TJ/TT0 4 50 Tc 0.94 0 Td(

console	{·
tty	ø
vty	≤40áÇÊÖ telnet/ssh Eý
First-line	**?UE9X** first-line 4Ë
Last-line	**?UE9X** last-line 4Ë

ï5,Õ5BÐ -

ïÐ <G5Bã

Ï*Ô LINE ã

ïG5B_Ð E9 LINE VTY 1 3 ,X LINE ð

5XLMLHFRQJOLQHYW\

ÏÎGÐ

Ç	ÊÄ
-	-

ïGÄè -

3.3 line vty

AçÐÑ*¡X VTY EýD,ÂÊAÇX no ÐÑ*¡X VTY E²yD,Â

line vty *line-number*

no line vty *line-number*

ÏÐAè

Ð	ÊÄ
line-number	VTY EýD,Â

ï5,Õ5BÐ 5,ÐX VTY EýD,Â 5ÈË 0--4Ä

ïÐ <G5Bã

Ï*Ô LÔUrt5ÑX VTY EýD,Ñ*5ÇÄ

ïG5B_Ð _ 1ÐX VTY EýD,Â 20Ëu VTY 4ÈÈ 0—19Ä

5XLMLHFRQJOLQHYW\

_ 2ÐX VTY EýD,Â 10Ëu VTY 4ÈÈ 0—9Ä

5XLMLHFRQJRQOLQHYW\

ÏÎGÇ

Ç	ÊÄ
-	-

默认级别	-

3.4 transport input

命令功能

配置Line用户支持的协议类型。

transport input命令用来配置Line用户支持的协议类型。

default transport input命令用来恢复Line用户支持的协议类型为缺省值。

命令格式

transport input {**all | ssh | telnet | none**}

default transport input

参数说明

参数	说明
all	支持SSH和Telnet协议
ssh	支持SSH协议
telnet	支持Telnet协议
none	不支持任何协议

缺省配置

缺省情况下，TTY用户支持的协议类型为NONE，即不支持任何协议。

default transp8 0_0 1 Tf

4 UPGRADE

4.1 upgrade system

LÔUE> 2ï¼{ÊMß*ü **upgrade system ÊÇ·Ä**

upgrade system [*filename*]

ÐAß	Ð	Ë Ä
	filename	2ï¼{[ßÐÃË

Ь,ÕЬBÐ -

ÊÐ (Mã

Б*Ð ÷ AÇÏ¼E> 4{Ä

:DLWLQRULPDJHLQWDOOHG&RPSOHWH
6ORW0$1LQWDOOHG
6ORW6OLPDJHVKDYHEHHQQWDOOHG

Q	EÄ
-	-

5

5.1 cd

A’5B[Ë¼³XÐÃÄ

cd [*filesystem:*][*directory*]

ËÐÀè

Ð	ÉÄ
filesystem	û,X[Ë¼ÄÐ‰OÜ
directory	û,X,Â

Ëõ,Õ5BÐ 5,Ø Flash ,X,Â

Ëð (Mã

Ës*û **cd Ë¼ÃÃ¼ËÃÃ¼èÐÃÃ**

/ ð2¼³XÐÃÂU¦2¼ÐÃÈ*ü **pwd Ø**

ËG5B_Ð _ 1ÔÃA’5B usb0 ,X,Â

5XLMLHFGXVE

_ 2ÔÃA’5B sd 5,X,Â

5XLMLHFGVG

ÏÐÑ

Ñ	ÉÄ
pwd	**/[ÊÃ**

ËÄè -

5.2 copy

¢,ÂËÈ

copy *source-url destination-url*

ËÐè

Ð	ÉÄ
source-url	**[Ê** URLè[ÊÐÑ° /ØXÄ
destination-url	**Ê** URLè[ÊÐÑ/ØXÄ

Ëõ,Õ5BÐ -

Ëð (Mã

Ï*Ô S*ü copy ÔÇ[ïÏ«ÈXÏÏ5%4ê<KÈX[ÊgÄ

(Mn[Ê4¾X URL ¼Ô

¼Ô	Aê
flash:	flash ,|ïÏ«¼ÔÊÑ*Ä URL ê*¼Ô ,XÊ,Õ</ flashÏÊÂ'[ÔX|/ÇFÑu flash Ä
tftp:	TFTP 5%4ê<
xmodem:	S*ü xmodem Âê%4Â'[Ê

ÏÐAê

Ð	Ë Ä
recursive	**ì Ô Uô8M20N Â**
url	?Uô8,X[Ê X urlÄ

Ï5,Õ5BÐ -

Ïê (Mã

Ï*Ð ô8 url ô5B,X[ÆÇ8,|ÏÐX[Ê URL ÑO flash:/ usb0:/È usb1:/ slave:/,XÐ url ôÆÊ</ô8[Ë4ÐX[Ê

Ï5B_Ð _ 1ô8¦ÂX tmpfile [Ê

5XLMLHGHOHWHWPSILOH

_ 2Ö ô8$ÐX rgos.bin.bak [Ê

5XLMLHGHOHWHVODYHUJRVELQDN

_ 3ô8 sd 5ÐX aaa.bin [Ê

5XLMLHGHOHWHVGDDDELQ

_ 4ô8 flash ÐXÔ20N,Â aaa

5XLMLHGHOHWHUHFXUVLYHDDD

ÎÏGÐ

Ï5B_Đ

```
_ 1Ø$HÂX[Ê
5XLMLHGLUVODYH
LUHFWRUIVODYH
0RGH/LQ6L]H07LPH1DPH

UJRVELQ
FRQJWH[W
FIJW[W

)LOHV7RDOVL]H%WHVLUHFWRULHV
7RWDOEWHV0%LQKLVGHYLFHEWHV0%DYDLODEOH
_ 2ÐÂX[ÊXC
5XLMLHGLU
LUHFWRUIWHPS
0RGH/LQ6L]H07LPH1DPH

DGDW

)LOHV7RDOVL]H%WHVLUHFWRULHV
7RWDOEWHV0%LQKLVGHYLFHEWHV0%DYDLODEOH
```

ÏÎGĐ

Ç	Ë
pwd	**/C**
cd	**A5[Ê4C**

Ï GÄ

-

5.5 mkdir

Î

mkdir *directory*

Ï Đ

Đ	Ë
directory	*Ø*

Ï,Õ5BĐ

-

Ï

(Mã

Ï*Ð

Eg9?UÎX,Ø(Ø

flash:/backup/temp flash:/backup
flash:/bakcup flash:/backup/temp

Ï5B_Ð _ 1ØÃ test ,Â Ö
5XLMLHPNGLUWHVW
_ 2Ö sd 5,ÃÂ test2
5XLMLHPNGLUVGWHVW

ÏÎGÐ

Ò	Ë
rmdir	**ô8Â**
pwd	**/[Ê¼CÃ**

ÏÄÀè -

5.6 pwd

/ÐCÃ
pwd

ÐAè

Ð	Ë
-	-

ï,Õ5BÐ -

Ð -

Ï*Ð /ØX[Ê¼CÃÄ

Ï5B_Ð _ 1Ø6,X/_ÐCÃÇÄ
5XLMLHSØ
IODVK

ÏÎGÐ

Ò	Ë
cd	**è[Ê¼CÃ**

ÏÄÀè -

5.7 rename

/|Ù,X[êÊ
rename *url1 url2*

ÏÐAÐ

Ð	Ë.Ä
url1	>ñ¸,X8[Ê URL
url2	,Â[ÊÃ¸QPl—~G8Ðr0tHn%GÐ·Ð8r0tHn%"bq'.U8uPyÐ8uPyÐÐh<Ð;Ö5M

6

6.1 archive

ÔÌ,7ä archive ÔÅ5BÄå*ÄÄÒX no EÝM6äAÊ5BåX}ẅ5B5,ÕŠ
Õ

archive

no archive

ÐÄÅÐ

Ð	ŁÄ
-	-

Ï5,Õẅ5BÐ -

ÐÒ <G5Bã

ŠS*Ð archive ÒÌ,7G5BÄ

?UEẗMã end Ò*ÏK CTRL+CÄ

?UE²<G5Bã exit ÃÒ

Ïẅ5B_Ð _ 1ÔÌ,7G5Bã

```
5XLMLHFRQ ÌJXUHWHUPLQ O
(Q WHUFRQÌJXUDWLRQ RPPDQGVRQ HSHUOLQH(QGZLWK&17/=
5XLMLHFRQÌJDUFKLYH
```

ÏÏGÒ

Q	ŁÄ
-	-

ÏGÄÐ -

6.2 hidekeys

/UÔG5BÁÇÕÄÃ*ÄÄÒX no EÝMAÇ5BÁÇÕÄ

hidekeys

no hidekeys

ÐÄÅÐ

Ð	ŁÄ
-	-

Ï5,Õ5BÐ 5,ÑÀÇ5BÁÇÕÄ



,71ku)Ó5Bã

Ï*Ð -

Ï5B_Ð _ 1ÐÏ6Ï5B¼ÕÄ

ÏGÄð -

6.4 logging enable

Ô5B66ÑÑ*ÀÇX no EÝMMGKÁ5B66Ñ

logging enable

no logging enable

ÐAð

Ï*Ð -

ÏG5B_Ð _ 1ÐG5B¼-,X5,Ä<Ð 50Ä

```
5XLMLHFRQJXUHWHUPLQO
(QWHUFRQJXUDWLRQRPPDQGVRQSHUOLQH(QGZK&17/=
5XLMLHFRQJDUFKLYH
5XLMLHFRQJDUFKLYHORJFRQJ
5XLMLHFRQJDUFKLYHORJFRQJORJJLQVL]H
```

ÌÏGÐ

Ð	ÐÄ
archive	**E9,7G5B**
log config	**E9,7¼u)Ï5B**

ÏÄÐ -

6.6 notify syslog

AÆÏG5BÐî¡ÏCE0Ã<*Ã*ÄÐX no EÝM/U6ÆÏG5BÐî¡µ

CE0Ã<Ä

notify syslog

no notify syslog

ÐÄÐ

Ð	ÐÄ
-	-

Ï,ÏG5BÐ 5,Ã6ÆÏG5BÐî¡ÏCE0Ã<Ä

Ð 7¼u)Ï5Bã

Ï*Ð -

ÏG5B_Ð _ 1ÐÆÏG5BÐî¡ÏCE0Ã<Ä

```
5XLMLHFRQJXUHWHUPLQO
(QWHUFRQJXUDWLRQRPPDQGVRQSHUOLQH(QGZK&17/=
5XLMLHFRQJDUFKLYH
5XLMLHFRQJDUFKLYHORJFRQJ
5XLMLHFRQJDUFKLYHORJFRQJRWLIVVORJ
```

ÌÏGÐ

Ð	ÐÄ
archive	E9,7G5Bã
log config	E9,7¼u)Ï5Bã
logging enable	Ï5Bê6Ñ

ÏGÄê -

6.7 show archive log config

/G5B5,ÊÄ

show archive log config {{**all** | *start-num* [*end-num*]} [**provisioning** | **contenttype** [**plaintext**]] | **statistics**}

ÐAê

user@line

{*ÁG5BB5,Â*ÀCÍÆ¼S,X
Æ¼6,X 15~+0Æ¼b,Ê9þ,2Æ

G²¯4 ”r T!»‘Z±ÓRÌ!¼¤¼.Å€

7 CPU-LOG

7.1 cpu-log

?UG5B CPU ÿÿ[Ç?₩KŁ$ Ê*ü **cpu-logÄ**

cpu-log *log-limit low_num high_num*

ÐAÈ

Ð	ÆÄ
log-limit	8ÈXQú
low_num	CPU ÿÿ[Ç?₩KŁ$
high_num	CPU ÿÿ[Ç?₱KŁ$

Ï,Õ5BÐ TA×ÆPKŁ$ 100%ÈŁ$ 90%Ä

Ê

<G5Bã

Ï*Ô

S*ÆÊ5B CPU ÿÿ[Ç?₱KŁÈPU ÿÿ[CÝÞKŁ$XÆÊÕ

CÈ CPU ÿÿ[ÇÞ?₱KŁÊ ÆÇ× CPU ÿÿ[Þ?₩KŁ$ ÆÕ

Ç, Eî CPU ÿÿ[ÆÈÇ¼ CPU ÿÿ[PÞPKŁÇ5KŁÊ

EÕ

G5B_Ð M6,X/_Ú CPU ÿÿ[Ç?₩KŁG5B 70%È CPU ÿÿ[Ç?₱KŁG5B 80%Ä

UXLMLHFRQJFSXORJORJOLPLW

8¹ CPU ÿÿ[Pþ 80%ÚVÇÖ

2FW<6&+(&.&38B86,1*B5$(B/2*&38XWLOL]DWLRQDWHLRQPLQWHUFRQ RFFXSLHGPRVW&38XWLOL]DWLRQDWH

8¹ CPU ÿÿ[Þ 70%ÚVÇÖ

2FW<6&+(&.&38B86,1*B5$(B/2*&38XWLOL]DWLRQDWHLRQPLQWHUFRQ RFFXSLHGPRVW&38XWLOL]DWLRQDWH LVNWLPHU

2FW6<6&+(&.&38B86,1*B5$(B/2*7KH&38XWLOL]DWLRQDWLRKDVEHHQHFHDVHG

ÏÊÐ

Ð	ÆÄ
-	-

G**Ä**È -

7.2 show cpu

?U¡ÐÏ³ CPU ÿÿ[ÇÈÆË (M*Ê **show cpuÄ**

show cpu

ÐAÐ

Ð	ÆÄ
-	-

Ъ,Õ5BÐ -

```
PVWSBHYHVW
*953B(9(17
UOGSBWDVN
UHUSBWDVN
UHXSBHYHVWBKDVOHU
WSSBWDVN
LSWLPHU
UWDGYG
WHVW
WHVW
7DUSWLPH
JUDBDUS
7WFSWLPHU
HIBUHV
HIBUFYBPVJ
HIBLERRVLVWHVWBGDHPRQ
LSBWXEOBUFYBSNW
UHVW
WXQW
HIBUFYBPVJ
HIBLERRVLVWHVWBGDHPRQ
LPLG
VPG
ULSG
ULSQG
RVSIG
RVSIG
EJSG
SLPG
SLPG
SGPG
GYPUSG
YWBFREFW
DDDBWDVN
7ORJWUDS
GKFSF
VWSBUHFYBWDVN
WSBWDVN
VODBGHDPRQ
WUDFNBGDHPRQ
SEUBJXDUG
YUUSG
SVSG
LJVSG
```

```
FRDBUHFY
FRBRSHU
FRBPDF
UDGLXVBWDVN
WDFBDFFWBWDVN
WDFBWDVN
GKFSGBWDVN
GKFSVBWDVN
GKFSSLQBWDVN
GKFSFBWDVN
XDUWBGHEXJBILOHBWDVN
VVSBLQWBWDVN
UOBOLVWHQ
LNOBPVJBRSHUDWHBWKUHDG
EFP3&
EFP/;
EFP/;
EFP&175
EFP7;
EFP*6$7;
EFP/,1.
EFP5;
PQSNWBUFYBWKUHDG
PQSNWBUHFFOHBWKUHDG
VWDFNBWDVN
VWDFNBGLVFBWDVN
UHGXBVEBWDVN
FRQGLVDWFKBWDVN
GHYSUEBWDVN
UGSBVQBWKUHDG
UGSBUFYBWKUHDG
UGSBVORWBFKDQHBWKUHDG
GDWDSNWBUFYBWKUHDG
NHHSDOLYHBOLQBBQWLI\
UHUSBPVJBUHFYBWKUHDG
LSBVFDBJXDUGBWDVN
VVSBLSPFBKLWBWDVN
VVSBLSPFBWUDSBWDVN
KBHUUBVQBWDVN
UHUSBSDFNHWBVHQBWDVN
LGOHBYODBSURFBWKUHDG
FPLFBSDXVHBGHWHFW
VWDWBJHWBDQBVHQ
UOBFRQ
```

LGOH

+‰	Aè
No	cË
5Sec	
1Min	
5Min	

8

8.1 memory-lack exit-policy

AÇ'5BY,E' lower 4 OSPFÃRIPÃPIM-SM 1Ä

memory-lack exit-policy { **ospf** | **pim-sm** | **rip**}

no memory-lack exit-policy

Ð	**Ä**	
ospf|pim-sm|rip	OSPF ê PIM ê RIPÄ	
no	x> Ä	

5,Ð5BÐ

<G5Bã

Y,E' lower 4 **show memory** lower 4 È

-

Ç	**Ä**
show memory	/Y,Ç

-

8.2 show memory

-	-

Ï,Õ5BÐ -

Ï Ð (M*ã

Ï*Ð S*ÀÐÏ¹XY,(Õ,S*Ï³X(¾Ú,GÏ³X
0NKÆEDÕNKÆ,EG£,ÈÇÄ

Ï5B_Ð ¾M6,X/_> **show memory pool**

```
5XLMLHVKRZ0HPRU\
6\VWHP0HPRU6WDWLVWLF
)UHHSDJHV
0WHUPDUNVPLQRU0UORZ0LJK
6\VWHP7RWDO0HPRU0%&XUUHQ)UHH0HPRU\%
8VHG5DWH
```

¾M6ë<,XÇÙ¾Õ

ÃÝ,NIÐÕNKÆ,NI 4k ÃXY,0NKÃ

Y,´4È<Ø,´4“XÄ

´4“	AÈ
min	Y,U0ÃÈXYE¤ È'8´4È*õ +Ã¤ Ä
lower	Y,ÇÈ'8´4ÃA7¾ÃÇÝ ,ÆÃ,X{¬ß **memory-lack exit-policy**
low	Y,ÇÈ'8´4ÈÃÁÉ9 OVERFLOW Ç ¬Ä
high	Y,>È´4È</2Ï¹Y,>ÈÃA'ÔÃÁ© ¢ OVERFLOW

2Ï¹Y,DÃÝ,DÈ,S*Ù[Ä

ÎÇÐ	Ç	Æ
	-	-

ÏÄÈ -

8.3 show memory protocols

AÇÔÃÁ,4*Ù,Ø‰

9 POE

9.1 poe enable

G5B0ÃXE/ß+6ÑÄ

poe enable

no poe enable

ËÐÀÈ

Ð	ÆÄ
-	-

Ë,Õ5BÐ -

Ëº yG5Bã

Ë*Ê EÆºG5BÈ6Ñ GKÁÃXE/ß+6Ñ

ËG5B_Ð

5XLMLHFRQJLI

5XLMLHFRQJLISRHHQEOH

5XLMLHFRQJLIQSRHHQEOH

5XLMLHFRQJLI

ÌGº

º	ÆÄ
-	-

ËGÄÈ -

9.2 poe mode

A'5B2Ï¾Xo+1u)Ê

poe mode auto

poe mode energy-saving

poe mode energy-static

ËÐÀÈ

Ð	ÆÄ	
auto	**A5Ê1uÍÀã**	POE A'ÌXTAxã
energy-saving	**A5Ê1uÍÑã**	POE A'ÌXÆã
energy-saving	**A5Ê1uÍ-Êã**	POE A'ÌXÆã

Ë,Õ5BÐ auto

Ïð <G5Bã

Ï*Ð ÿ VÐ'5B2Ï¡³XTAxo+1u)ðÑ

ÏG5B_Ð A'5B! POE 2Ï¡³Xo+1u)ðV6ðÑ

```
5XLMLHFRQJXUH
5XLMLHFRQJSRHPRGHHQUJVDYLQ
5XLMLHFRQJHQ
```

ÏÎGÐ

Ç	ÐÄ
-	-

ÏGÄð S3760E-P V1.x (PoE x6Ñ-Õ+1u)ðÑ

9.3 poe disconnect-mode mode

A'5B2Ï¡³Xyzðä

poe disconnect-mode *mode*

ÏÐAð

Ð	ÐÄ
mode	*AB,Xyzð*ac | dc}

Ï,Õ5BÐ dc

Ïð <G5Bã

Ï*Ð ÿ VÐ'5B2Ï¡³Xyzðä

ÏG5B_Ð A'5B! POE 2Ï¡³Xyzðã ac

```
5XLMLHFRQJXUH
5XLMLHFRQJSRHGLVFRQFWPRGHDF
5XLMLHFRQJHQ
```

ÏÎGÐ

Ç	ÐÄ
-	-

ÏGÄð -

9.4 poe power-off time-range name

A'5B0ÃXnÊ+s6ÃÑ

poe power-off time-range *name*

no poe power-off time-range

ÏĈĠĘĐ	Ą	ĖÄ
	-	-

ĠÄâê -

9.6 poe legacy

A’5Byŵ2ĕJ PD Ps6Ñ

poe legacy

no poe legacy

ĐAâê	Đ	ĖÄ
	-	-

ƀ,Õ5BĐ -

ĘĐ yG5Bã

Ƽ*Ð EĖĘĄG5BĖ6ŏĠKÁÃX PoE M2Ðâ

ĠƀB_Đ 0Ã fa 0/1 ,XM2Ðã

5XLMLHFRQJLQWHUIDFH)DVW(WKHUQHW

5XLMLHFRQJLISRHOHJDF\

ÏĈĠĘĐ	Ą	ĖÄ
	-	-

ĠÄâê -

9.7 poe max-power

A’5B2Ï¾XĐ[Ä

poe max-power *int*

no poe max-power

ĐAâê	Đ	ĖÄ
	int	ĐĘ WĖĖ0-30>
		Õ 802.3af ,X2ÏĐĖĖ0-15.4>

ƀ,Õ5BĐ -

ĘĐ yG5Bã

S*Ð	EEQG5BÈA'5B0ÃXÔ)[Ä	
G5B_Ð	A'5B0Ã Fa 0/1 ,XÔ)[	20W
	5XLMLHFRQJLQWHUIDFH)DVW(WKHUQHW	
	5XLMLHFRQJLISRHPD[SRZHU	

ÏGÐ

Q	[redacted]Ä
-	

GÄè -

929.4 p61D3982CBE280C309E0CE4D2 [redacted] 3D58.254232CF]538.38 677 0.48 0

A'5B24³X³X³X³X³X³X³X³X³T#uÈÐXdž [redacted] Xp@jBè-fD,xuVVgyÂuaÐ

ѣ,Õ5BÐ	2Ї¦X±-s)[TAx	0%
Ð	<G5Bã	

9.11 poe warning-power

A’5B2Ï¾Xs)[A:¼Ä

poe warnig-power *int*

ÐAÐ	Ð	ÐÄ
	int	**A:s]RÐ**0-99>

Ð,ÕÐBÐ 99

```
5XLMLHFRQJSRHSWLILFDWLRQRQURHQEOH
5XLMLHFRQJHQ
5XLMLHØLWH
```

ÏĈĢĘ

Ę	Ä
-	-

ĞÄê -

9.13 poe pd-description

A’5B0Ã¾X PD Ł0áÄ

poe pd-description *pd-name*

no poe pd-description

ÐAê

Ð	Ä	
pd-name	PD Ł0áÈ+0ĐSÕ	32 þ0Á

ĥ,Ğ5BÐ -

ĐĘ yG5Bã

Ĕ*Đ A’5B RFC3621 pethPsePortType ,XÈD Ł0Á

ĞĘ5B_Ð _VÈ’5B FastEthernet 0/1 y¡X PD Ł0ú

```
5XLMLHFRQJXUH
5XLMLHFRQJLQWHUIDFH)DVW(WKHUQHW
5XLMLHFRQJLISRHSGGHVFULSWLRQS
5XLMLHFRQJLIHQ
```

ÏĈĢĘ

Ę	Ä
-	-

ĞÄê -

9.14 poe class-lldp enable

A’5B2Ï¾X LLDP `ðÚ[s6Ñ

poe class-lldp enable

no poe class-lldp enable

ÐAê

Ð	Ä

-	-

Ъ,Õ5BÐ -

Ð <G5Bã

Ъ*Ð A’5B2Ï¾X LLDP `ðsõÑ

7URXEOHFDXVH1RÐ
3ULRULWFULWLFDO
/HJDFRII
3RÐURIIWLPHUDQH1$
3RÐUPDQJHPQDXWR

ÎĈĢÐ		
	Ð	ÐÄ
	-	-

ĞÄð -

9.16 show poe interfaces

¦ÑÃX PoE (Õ5BÄ

show poe interfaces status

show poe interfaces configuration

ĐAð

Đ	ÐÄ	
status	/Ý	PoE 0ÃX(Õ
configuration	/Ý	PoE 0ÃXG5BÐ

Ð,Õ5BĐ -

Ð (M*ã

Ð*Ð ÑÃX POE (Õ5B

Ğ5B_Đ

5XLMLHVKRSRHLQWHUIDFHVVWDWXV
,QWHUIDFH3RÐU3RÐU&UU$J3HDN&UU7URXEOH33RUW
&RQURO6WDWXV3RÐU3RÐU3RÐU&UUHQW&DVH&ODVV9ROWDJH

)DQEOHRQP$
)DQEOHRQP$
)DQEOHRQP$
)DQEOHRII:::P$$
)DQEOHRQP$
)DQEOHRQP$
)DQEOHRQP$
)DQEOHRQP$
)DQEOHRQP$
)DQEOHRQP$
)DQEOHRQP$
)DQEOHRII:::P$$
)DQEOHRQP$
)DQEOHRQP$

```
)DHQEOHRII:::P$$
)DHQEOHRII:::P$$
)DHQEOHRII:::P$$
)DHQEOHRII:::P$$
)DHQEOHRII:::P$$
)DHQEOHRII:::P$$
)DHQEOHRII:::P$$
)DHQEOHRII:::P$$
)DHQEOHRII:::P$$
)DHQEOHRII:::P$$

5XLMLHVKRZRHLQWHUIDFHVFRQJXUDWLRQ
,QWHUIDFH3RUW3RUW3RUW0D[$ORF3RUW3RUW3RUWURII
&RQWURO6WDWXV3RUW3RUW3ULRULW\HJDF7LPHUDQH

)DHQEOHRQ$$FULWLFDORII1$
)DHQEOHRQ$$FULWLFDORII1$
)DHQEOHRQ$$FULWLFDORII1$
)DHQEOHRII1$$FULWLFDORII1$
)DHQEOHRQ$$FULWLFDORII1$
)DHQEOHRQ$$KLJKRII1$
)DHQEOHRQ$$KLJKRII1$
)DHQEOHRQ$$KLJKRII1$
)DHQEOHRQ$$KLJKRII1$
)DHQEOHRQ$$KLJKRII1$
)DHQEOHRQ$$KLJKRII1$
)DHQEOHRII1$$KLJKRII1$
)DHQEOHRQ$$ORZRII1$
)DHQEOHRQ$$ORZRII1$
)DHQEOHRII1$$ORZRII1$
)DHQEOHRII1$$ORZRII1$
)DHQEOHRII1$$ORZRII1$
)DHQEOHRII1$$ORZRII1$
)DHQEOHRII1$$ORZRII1$
)DHQEOHRII1$$ORZRII1$
)DHQEOHRII1$$ORZRII1$
)DHQEOHRII1$$ORZRII1$
)DHQEOHRII1$$ORZRII1$
)DHQEOHRII1$$ORZRII1$
```

ÏĜĢ

Ą	ĘÄ
-	-

ĞĜÄ

-

9.17 show poe powersupply

¦ß POE 2Ï¼³Xo+(Ð

show poe powersupply

ÐAð

Ð	Ð£Ä
-	-

Ъ,ÕЪBÐ -

Ð (M*ã

Ъ*Ð ÷ Ð POE 2Ï¼³Xo+(Õ

ÜЪB_Ð

```
6(3VKRZSRHSRÆUVXSSO\
HYLFHPHPEHU
3RÆUPDQJHPHQWDXWR
36(WRWDOSRÆU:
36(WRWDOSRÆUFRQXPSWLRQ
36(WRWDOUHDLQSRÆU:
36(SHDNSRÆU                                    :
36(DYHUDJHSRÆU:
36(SRÆUHGSRUW
36(GLVFRQFWPRGH'&
36(UHVHUYHSRÆU
```

ÎÜÐ

Q	Ð£Ä
-	-

10

10.1 clear logging

?UÈ8Y,4¢XG¢ÆÈM*ð AÇÐ

clear logging

ÐAð	Ð	Æ
	-	-

Ö,Õ5BÐ -

Ð (M*ã

Ö*Ð AÇ8Y,4¢[YÁÑ8¥[,X4ÃuÇÄ

Ö5B_Ð MI6/_È8Y,4¢[YÄ

5XLMLHFOHDUORJJLÇ

ÎGÐ

Ç	Æ
logging on	Ê
show logging	¢[
logging buffered	ÁA¥¢

ÖÄð -

10.2 logging buffered

?UA'5BA)Ç,XY,4ÐÖÇÁÆG5B> AÇÐ

AÇ no 6ÁU6Y,4Ç)ÇÄÇ default 6Á,4Çá

5,Õ

logging buffered [*buffer-size*] [*level*]

no logging buffered

default logging buffered

Ö,Õ5BÐ 4ţA×ß'Â’ÎO_Ý6Ö
—×6TA× 1M Bytes×
Ö.×6TA× 256K Bytes×
y9×6TA× 128K Bytes×
JA’ÛA× 4K Bytes×
ß,XÛ6û 7Ä

Ëß <G5Bã

Ö*Ô Y,4ţNKÈ)ß*¡XÈpûßXY,>mßXß¢Ú²ZÄU¡Ý
,4ţXß¢ÈË*(M*ß **show logging**Ä
Y,4ţXß¢ÊXÈ’Ûß)(M*ß **clear logging**ßX
ß8ß?UCCß¢ÈÈAÚ}= FLASH 6ÈÕ Syslog ServerÄ
ß¢Ú 8 ß{Ä< 1Õ

GK+	14{	ÈÄ
Emergencies	0	2ßÃÑE¤
Alerts	1	LÔU0ÖG³7,XKÑl
Critical	2	G?U‰
Errors	3	JÁß¢
warnings	4	A:ß¢
Notifications	5	BE?O_È¢LÔUG¦¼G?Uß¢
informational	6	AÈß¢
Debugging	7	AÁß¢

CÈ{ß¢P6 0 4{ÿXß¢Ô4{ÿXß¢Ä
ÔAß¢ß¢4{ÈbÔA5Bß¢{ß¢Ú

Ö5B_Ð M6/_A’5BÁXÆÿ 6 Ô 6

10.3 logging console

?UA'5BA{ÐXÇ4{ÀËG5BÐ AÄÇX no 6ÃU6ü
{Ðy[Ä
logging console [*level*]
no logging console

ÐAÐ	Ð	ÐÄ

level

Ï5B_Ð 5XLMLHFRQJORJJLQJFRXQW

Ï Ñ	Ä
show logging count	**Ø**
show logging	**5**

Ï -

10.5 logging facility

?UA’5B ,XA G5B A x(23) Ä

logging facility *facility-type*

no logging facility

Ð

18 (local2)	Local use
19 (local3)	Local use
20 (local4)	Local use
21 (local5)	Local use
22 (local6)	Local use
23 (local7)	Local use

TAxA'(Ûocal7)23 Ä

Ï5B_Đ MI6,XA'5B Syslog A'Û kernelÖ

5XLMLHFRQJORJJLQDFLOLW\NHUQ

ÏGĐ

Ọ	Ä
logging console	A'5BAĐXĐ4{ÿ

ÏGÄè -

10.6 logging file flash

?UÚ FLASH ÈËG5BèA FLASH A),«

ÇÈ*AÇX no 6Ä

logging file flash:*filename* [*max-file-size*] [*level*]

no logging file

ÏDAè

Đ	Ä
filename	txt 2O_Ä
max-file-size	128K 6M bytesÈ,Đ 128KÄ
level	FLASH ,X4{ÿ 6Ä«b« 1Ä

ï,Õ5BĐ FLASH Ä

Ïè <G5Bã

Ï*Đ Vpù Syslog Server<5×%4Eg
y FLASH Ä
txtÈ5B Ä

FLASH FLASH FLASH logging file flash

Ï5B_Đ MI6/_A), FLASH È trace.txtÈ 128KÈ4{ÿ 6Ä

5XLMLHFRQJORJJLQLOHIODVKWUDFH

ÏĈĢĐ

Ǫ	ƐÄ
logging on	**Ĝ**

Đ	Ä
-	-

Ь,Õ5BĐ AĢÄ’Ä

Ä Ę <G5Bã

Ь*Ð ĢÃ Console 0kÃ VTY 0kÐÃ,ãXA’Ð,4Ã
FLASHÃSyslog Server ÄĢÈpGKÐĢÁ,È
L8Ð4{ 1 ,X LogÄ

Ġ5B_Đ MI6,X/_Ä’ĢKĢÖ
5XLMLHFRQJRORJJLQRQ

ÏĠĘĐ

Ę	Ä
logging buffered	**Á Ä**
logging	**Á 4-** Syslog Server
logging file flash:	**Á Ä** FLASH Þ
logging console	**Ä Ð 4{ÿ**
logging monitor	**Ä** VTY 0k{V telnet 0k) ,X 4{ÿ
logging trap	**Ä Ð** Syslog Server ,X 4{ÿ

ĠÄĘ -

10.9 logging rate-limit

?UĢ[L$6Ã Ä AEgÎXĢÄĖG5Bã AĘUGKÁ
E[L$6ÃĖ*AĘX no 6Ä
logging rate-limit {*number* | **all** *number* | **console** {*number* | **all** *number*}} [**except** [*severity*]]
no logging rate-limit

ĐAĘ

Đ	Ä
number	1—10000
all	0—7 4{
console	
except	error(3) 1b error 4{ X E[{
severity	0—7

Ь,Õ5BĐ 5, E[{Ä

Ä Ę <G5Bã

ê 8ÇQ4¾;XÇCEgÃ*8ÇÃ5GÇ,XÇCEgÃ

ÜG5B_Đ A'5BÆ¡sYA¡ÇXÇÔ debugÅ 10 5Ê warning Ê4{Ç>{
Ö
5XLMLHFRQJORJJLQUDWHOLPLWDOO H[FHSWZUQV

ÎÎGÇ

Ç	ÆÄ
show logging count	Ê4Ç
show logging	Ç5Ç4Ç

ÜGÄê -

10.10 logging server

?UÁ)û,X syslog serverÈËG5BÃ*AÇU8 syslog server ë<,X
û,X syslog serverÈË*AÇX no 6Ä
logging server {*ip-address* [**vrf** *vrf-name*] | **ipv6** *ipv6-address*}
no logging server {*ip-address* [**vrf** *vrf-name*] | **ipv6** *ipv6-address*}

ÐAê

Đ	ÆÄ
ip-address	*yÇX* IP
vrf-name	*ûÇX* VRFXPN CÃE@¥<Å_
ipv6-address	*ûyÇX* IPV6

Ü5,Õ5BĐ TAxÅ syslog server ¥Ç

Ç <G5Bã

Ü*Đ AÇûÔ Syslog server 9yA'ÇXÇÃG5BE' 5 þ Syslog ServerÄ
CÇG5B,XÝ Syslog ServerÄ

ÜG5B_Đ _ 1Ç6,X/_ûÔ 202.101.11.1 ,X syslog serverÖ
5XLMLHFRQJORJJLQVHUYHU
_ 2Ç6,X/_ûÔ IPV6 AAAA:BBBB::FFFF
5XLMLHFRQJORJJLQVHUYHULSY$%%%%))))

ÎÎGÇ

Ç	ÆÄ
logging on	Ô
show logging	Ç[ÈG5B
logging trap	**A5** syslog server ,XÇ4{ÿ

ÜGÄê -

10.11 logging source interface

?UA'5B¥[,X¤yÀËG5B¤ AÖQX no 6¤¥[,X¤yA'5BÄ

logging source interface *interface-type interface-number*

no logging source interface

ÏDA¤Ð

Ð	ÆÄ
interface-type	*y2O*
interface-number	*y¤*

Ï5,Õ5BÐ -

Ï¤Ð <G5Bã

Ï*Ð TAx¤ Syslog Server ,X¥[¤ IP y[ÆÕ,X IP ÆC Cu)Ð*A¥[,X¤ IP ¤h¥,X IP È1u)ÚÆÊÔ A¤¿ÐÕ,X¥[¤A'5BA¤y¤5B IP È y[¤ IP y[ÆÕ,X IP Ä

Ï5B_Ð M6,X/_û Loopback 0 ,X Syslog y[,X¤Ö

5XLMLHFRQJORJJLQVRXUFHLQWHUIDFHORRSEDFN

ÏGÐ

Q	ÆÄ
logging	**¤4-** Syslog Server

ÏGA¤Ð -

10.12 logging source ip| ipv6

?UA'5B¥[,X¤ IP ÀËG5B¤ AÖQX no 6¤¥[,X¤ IP A'5BÄ

logging source {**ip** *ip-address* | **ipv6** *ipv6-address*}

no logging source [**ip** | **ipv6**]

ÏDA¤Ð

Ð	ÆÄ	
ip-address	*û*	IPV4 Æ¥Õ[,X¤ IPV4
ipv6-address	*û*	IPV6 Æ¥Õ[,X¤ IPV6

Ï5,Õ5BÐ -

Ï¤Ð <G5Bã

ê TA×xèÆÕ- Syslog Server ,X¼[ê IP y[Æ¥Õ,X IP ÆÆC€þu
)Ê*Á¥Ó,Xê IP îhþ IP È1u)ÍÆÆÂ¥
Á«ÆÕ,X¼[ÈA'Þ5BA¹ IP ¼[ê IP y[Æ¥Õ
¡X IP Ä

Ï5B_Đ MI6,X/_ô 192.168.1.1 Syslog y[,Xê Ö
5XLMLHFRQJORJJLQVRXUFHLS

ÎGÐ Ç

10.14 logging trap

?UA'5BA¥Ê¢Õ· syslog Server ,XÊ¢4{ÊÀ¥ËG5BÊ¡ AÊÇÇX no 6ã

/U6½ý[¥Ê¢Õ· syslog ServerÄ

logging trap [*level*]

no logging trap

ÐAÊê	Ð	ÉÄ
	level	½X¡Ê¢ÊSÐÄG ¢ÊAÄÀ¥Ë 1Ä

ï5,Õ5BÐ Informational(6)

ïÊ <G5Bã

ïS*Ê ?Uý½¥Ê¢Õ· syslog ServerÈj?US*ïG5BÇ logging G5B syslog Server¡ü

logging trap ÊÊ¢Õ¡X¢Ê4{½Ä

ÉÉ› **show logging** Ê5ÈÐ4?AuÄ

ïG5B_Ð MÍ6,X_G5B½{ý 6 ,X¡Ê¢Õ· 202.101.11.22 ,X syslog ServerÖ

5XLMLHFRQJORJJLQ

5XLMLHFRQJORJJLQWUDSLQRUPDWLRQO

ÎGÇ	Ç	ÉÄ
	logging on	Ê
	logging	½¥- Syslog Server
	show logging	¥[ÈG5Ð

ïGÄê -

10.15 more flash

?U¡Ä)¡ FLASH [¥ÈÀÊM*ê AÇ

more flash:*filename*

ÐAÊê	Ð	ÉÄ
	filename	[ê

ï5,Õ5BÐ -

ïÊ (M*ã

ïS*Ê ¡ FLASH [ÊÊ/f2/" È/f3/' ,X[ÄÇÇÊ

Ï

ÏG5B_Đ M6/_¦ FLASH [ÊXÔ
5XLMLHPRUHIODVKIORJW[W
ORRNXSILOHLQVKHH[WHQGHGIODVKIORJW[W
5XLMLH5HORDGUHTXHVWHGEGPLQVWUDWRU5HORDG5HDVRQHORDG
FRPPDQ

ÏGÇ	Ç	ÉÄ
	logging file flash:	**ÇÁ** FLASH Þ

ÏGÄè -

10.16 service private-syslog

?UÉÍHÁXèËG5Bã AÄX no 6Ý
,XèG*TAx,Xã> /Ä
service private-syslog
no service private-syslog

ÐAè

Ð	ÉÄ
-	-

Ï,Õ5BÐ ÇG*TAxã> /Ä

Ç <G5Bã

Ï*Ô TAxÈM6,XÇ/VÖ
*timestamp: %facility-severity-mnemonic: description
q ÖÈ %ãÇ}ÁÇ Á
_May 31 23:25:21: %SYS-5-CONFIG_I: Conf igured from console by console

8Ã6ÑÔM6,XÇ/VÖ
timestamp facility-severity-mnemonic: description
q ÖÈ ãÇ}ÁÇ Á
_May 31 23:31:28 SYS-5-CONFIG_I: Configured from console by console
JÃAxÈXÊÑÃXÈM6Ô
Ç ÑM6ÇÁ

ÏG5B_Đ M6/_G5BÉÍHÁÝ
5XLMLHFRQJVHUYLFHSULYDWHVORJ

ÏGÇ	Ç	ÉÄ
	logging on	Ö

service timestamps	**Ê**

ËGÄê -

10.17 service sequence-numbers

?UÊtÆÊG5Bê AÐX no 6Ê,XcÄ

service sequence-numbers

no service sequence-numbers

ËAê

Ð	ÄÄ
-	-

Ë,Õ5BÐ Ê

Ëê <G5Bã

Ë*Ð L8ÊtÊÈÊÃtÆÊ 1 ÊÊ

Ñ2ÆFÊÝÊXÑNcÄ

ËG5B_Ð Ê6/_G5BÊtÆÐ

5XLMLHFRQJVHUYLFHVHTXHQHXQPEHUV

ÌÎGÐ

Ð	ÄÄ
logging on	**Ê**
service timestamps	**Ê**

ËGÄê -

10.18 service standard-syslog

?UÉHÊ RFC3164 n,XÈÊG5Bê AÐX

no 6Ê RFC3164 n,XÈG*TAx,XÈ> /Ä

service standard-syslog

no service standard-syslog

Ð	ÄÄ
-	

ê TAxÐÊÔ6,XÇC/VÖ
*timestamp: %facility-severity-mnemonic: description
q ÖÊ %ãÇ}ÆÇ Æ
_Ø May 31 23:25:21: %SYS-5-CONFIG_I: Conf igured from console by console

8Ê6ÃÔ6,XÇC/VÖ
timestamp %facility-severity-mnemonic: description
q ÖÊ% ãÇ}ÆÇ Æ
_Ø May 31 23:31:28 %SYS-5-CONFIG_I: Configured from console by console
JÊAxÆXÇÊÊKÊÔ6Ê Ã
Ê6Ê

ÖG5B_Ð Ô6/_G5BÉÚHÊ
5XLMLHFRQJVHUYLFHVWDQDUGVORJ

ÏÎGÇ

Ç	ÐÄ
logging on	Ê
service timestamps	ÆÊ

ÖGÄÊ -

10.19 service sysname

?UÆCtÐ2Ï4ÃÊËG5BÊ AÉÇX no 6ÊÆ,X2Ï
4ÃÄ
service sysname
no service sysname

ÐÄÊ

Ð	ÐÄ
-	-

Ö,Õ5BÐ ÆCtÐ2Ï4ÃÄ

Ê <G5BÃ

Ö*Ð EÐ8ÊÇL0UÈÆCtÐ2Ï4ÃÄ

ÖG5B_Ð Ô6/_G5BÆCtÐ2Ï4ÃÊ
0DU6<6&21),*&RQJXUHGIURPFRQROHEFRQROH
5XLMLHFRQJWHUPLQO
(QWHUFRQJXUDWLRQRPPDQGVRQHSHUOLQH(QGZK&17/=
5XLMLHFRQJVHUYLFHVVQPH
5XLMLHFRQJHQ
0DU66<6&21),*&RQJXUHGIURPFRQROHEFRQROH

ÏÎGÐ	[redacted]ÉÄ
	show logging	**/Ê5Þ3ÆÐ**

ÏGÄÐ -

10.20 service timestamps

?UÐtÐÐÀËG5BÐ AÐÐX no 6Ð

ÐÐÄefault 66Ð,XÐÐAxÄ

service timestamps [*message-type* [**uptime** | **datetime** [**msec** | **year** ÐS,GpNÐÐÐHbbèP0ÐQGÎ FÐ

10.21 show logging

?U¦G5B,XÐÃ?AuµCÈ,4¢¥[ÈËM*ä AÇ

Syslog logging	ê©Ô enabled,GKÁ disabled
Console logging	D{ß,X4{è¢Au
Monitor logging	Dü VTY 0kß,X4{è¢Au
Buffer logging	A)¥,4ß,X4{è¢Au
Standard format	ê
Timestamp debug messages	Debug ¿Ê
Timestamp log messages	Log ¿Ê
Sequence-number log messages	cÔ
Sysname log messages	¿t2¼
Count log messages	¼Aus6Ñ
Trap logging	¥Ô Syslog Server ¿,X4{è¢Au
Log Buffer	A)¥,4ß¥[

ÏÇÐ

Ò	Ä
logging on	ê
clear logging	84

ÏÄê -

10.22 show logging count

?U¡2¼ß{*ô D Ð XÊ4Au¿Ê(Mê AÒ
Ä
show logging count

ÐAê

Ð	Ä
-	-

Ï,Õ5BÐ -

Ò (Mã

Ï*Ð Z*¼[4Aus6ÑÔUG5Bè **logging count** Ò **show logging count**
ñ
E› **show logging** Ò4Aus6Ð

Ï5B_Ð M6/_> **show logging count** Ò Ö
5XLMLHVKRØRJJLQFRXQW
0RGXOH1DPH0HVVDJH1DPH6HY2FFXU/DVW7LPH
6<6&21),*B,
-XO
6<6727$

ñ	Q	ÆÄ
	logging count	-Aus6Ñ

11

11.1 fan force enable

G5BN¡X0ÈQX no 6ã5,Õ5BÄ

fan force enable

no fan force enable

ï¨ÐAÈð

Ð	ÆÄ
-	-

ï¿,Õ5BÐ 7¦ßã

ï¨Ð config ã

ï¨S*Ð AÇG5BÄ

no fan force enble	**show running-config**

ï¨G5B_Ð G5BN¡X0ã

5XLMLHFRQJ

(QWHUFRQJXUDWLRRPPDQVRSHUOLQ(QZK&17/=

5XLMLHFRQJIDRUFHHQEOH

ÏÎGÐ

Q	ÆÄ
show fans	**N GC Ä**

ï¨GÄÈð AÐ' S3760E V2.x A'Ð

11.2 show fans

¡N¡X0Ð

show fans

ï¨ÐAÈð

Ð	ÆÄ
-	-

ï¿,Õ5BÐ -

ê	(Mã	
Ï*Ð	bÐXNÐE@EáÏXA'ÐSpeed	ãN/A"
Ï5B_Ð	_ ÐÐ¢Ð0ÐÖ	
	5XLMLHVKRÐDÐ HYLFH)DÐWDWH0RGH6SHHGUSP	

¶

¶

¶

Ø‰ÝÏÖ

+‰	Aê
Dev	C{¡XA’ûÊ
Slot	C{¡XÞ

Temperature Slot	¼ó,XÑ
State	Ä'¼(Õ
Current(C)	Ä'¼

ÏĈĢĘ

Ą	Ł Ä
-	-

ĠÄâ -

12 Warm Reload & Upgrade

12.1 reload warm

reload warm

reload [**warm**] [*text* | **in** [*hh:*] *mm* [*text*] | **at** *hh:mm* [*month day* | *day month*] [*text*] | **cancel**]

warm	warm reload
text	1-255
in [*hh:*] *mm*	24
at *hh:mm*	
month	3
day	1 31
cancel	

-

<

SMNG reload

Warm Reload

```
5XLMLHUHORDGDUP
3URFHVVHGZWKUHORDG
-XQ65(/2'KHGHYLFHLVUHORDGLQJXHWRWKHHIHXWLRQFRPPDQUHORDG
6VWHPZOOSHUIRUPDUPUHORDG
```

copy tftp ` reload warm

```
5XLMLHFRSWIWSUJRVELQDVKUJRVELQ
FHVVLQWIWSUJRVELQ
6VWHPLVUXQGHIUDJPHQWSOHDVHZLWWLQ
3UHVV&WUO&WRTXLW
7UDQVPLVVLRQVKGILOHOHQWKEWHV
```

```
8SWLPHV
_ 2Warm Reload
Warm Reload
5XLMLHVKROGUPUHORDG
:DUP5HORDGFRQILJXUDWLRQWDWH
:DUPUHORDGLVHQDEOHG
0D[UHORDGFRXQW
0LQXSWLPHV
:DUP5HORDGUXQQLQJVWDWH
:DUP5HORDGLVRSHQQVDYHG
_ 3Warm Reload
Warm Reload
5XLMLHVKROGUPUHORDG
:DUP5HORDGFRQILJXUDWLRQWDWH
:DUPUHORDGLVGLVDEOHG
0D[UHORDGFRXQW
0LQXSWLPHV
:DUP5HORDGUXQQLQJVWDWH
:DUP5HORDGLVFORVH
_ 4Warm Reload
Warm Reload
5XLMLHVKROGUPUHORDG
:DUPUHORDGFRQILJXUDWLRQWDWH
:DUPUHORDGLVHQDEOHG
0D[UHORDGFRXQW
0LQXSWLPHV
:DUPUHORDGUXQQLQJVWDWH
:DUPUHORDGLVDYDLODEOH
:DUPUHORDGFRXQW
8SWLPHV

6ORWUPUHORDGUXQQLQJVWDWH
6ORW
:DUPUHORDGLVDYDLODEOH
:DUPUHORDGFRXQW
8SWLPHV
```

+‰	A
max reload count	G5B,X GKÈ4É Warm Reload ,X DÄ
min uptime	G5B,X 2ÄCK0n E›X KÈhÄ Warm Reload G O4£
warm reload count	X Warm Reload ,X DÄ
uptime	2ÄG5B KÈhÄ

ÏGQ

Q	EÄ
warm-reload {enable | count *number*] | **uptime** *minutes*}	**A5B** Warm Reload s6Ñ

reload warm	Warm Reload/Upgrade
reset warm module *slot*	Warm Reload
show warm-reload	Warm Reload

13 SRM

13.1 cpu

ü srm-policy GЂBЂЀE› **cpu Ð9** owner-cpu GЂBЂÄ **cpu**

ÐAÐ	Ð	ЄÄ
	-	-

Ï5B_Ð _ 1ÖG5Bþ rgos_group ,XC‡S*5ÙÏ snmpd ï#Ê1*¡¼1*+9Ä

```
5XLMLHFRQJXUHWHUPLQO
5XLMLHFRQJUHVRXFHPDQJHU
5XLMLHFRQJVUPXVHUJURXSUJRVBJURXS
5RXWHUFRQJUHVJURXSLQWDQHVQSG
```

ÎÏGÐ

Ç	Ë Ä
resource manager	**E9** srm G5Bã

Ï ÄÊ **-**

13.3 memory

ü srm-policy G5BÈE› **memory** Ç9 owner-memory G5BÊ

memory

Ð Ê

Ð	Ë Ä
-	-

Ï,Ï5BÐ -

Ê Srm-policy G5Bã

Ï*Ê -

Ï5B_Ð _ 1Ö srm-policy G5BÈE› memory Ç9 owner-memory G5BÊ

```
5XLMLHFRQJVUPSROLFPHPRU\
5XLMLHFRQJRQUPHPRU\
```

ÎÏGÐ

Ç	Ë Ä
resource manager	**E9** srm G5Bã
policy policy-name [**global**]	**Ê19E9** srm-policy G5Bã

Ï ÄÊ **-**

13.4 policy

ü srm G5BÈE› **policy Ç5Ê19E9** srm-policy G5BÊ

policy *policy-name* [**global**]

no policy *policy-name*

ÏÐAê

Ð	Ë
policy-name	policy-nameÖ*+9ÁÄ
global	**µ¼Z** global ÐÈ</EÐ,¥1*+9È</E- Ô¥1*+9Ä
no	**ô8¥19Ä**

Ï,Õ5BÐ -

ê srm G5Bã

Ï*Ð -

ÏG5B_Ð _ 1Ö5BÁÄ rgos_policy ,X<,¥1*+9Ä

```
5XLMLHFRQJUHVRXFHPDQJHU
5XLMLHFRQJVUPSROLFUJRVBSROLFJOREDO
5XLMLHFRQJVUPSROLF\
```

_ 2Ö5BÁÄ rgos_policy ,X*¡¥1*+9Ä

```
5XLMLHFRQJUHVRXFHPDQJHU
5XLMLHFRQJVUPSROLFUJRVBSROLF\
5XLMLHFRQJVUPSROLF\
```

ÎGÐ

Ð	Ë
resource manager	**E9** srm G5Bã

ÏGÄê -

13.5 policy policy-name

ü config-res-group G5BÈE› **policy** *policy-name* G¥Á

policy *policy-name*

no policy *policy-name*

ÐAê

Ð	Ë
policy-name	¥Á
no	**ô84¥19Ä**

Ï,Õ5BÐ -

ê srm G5Bã

Ï*Ð -

ÏG5B_Ð _ 1ÖG5Bê rgos_group ,X4Ð snmpd ¥4Ð1*+9Ä

```
5XLMLHFRQJXUHWHUPLQO
5XLMLHFRQJUHVRXUFHPDQJHU
5XLMLHFRQJVUPXVHUJURXSUJRVBJURXS
5RXWHUFRQJUHVJURXSLQWDQHVPSG
5RXWHUFRQJUHVJURXSSROLFUJRVBSROLF\
```

ÏĈGĘ

Ą	ĘÄ
resource manager	**Ę9** srm GƀBã

ĞGÄà

-

13.6 resource manager

ëŒ9 srm GƀBÄ

resource manager [**slot** *slot-id* [**subsystem** *subsystem-id*]]

ËÐAà

Ð	ĘÄ
slot *slot-id*	ûº?UGƀB,XS5Ä
subsystem *subsystem-id*	²Ä#ßÈ 0-1þ show version /Ć,X cpu idÄ

Ëƀ,ÕƀBÐ

-

Ëę

<ã

ËƧ*Ð

-

ĞGƀB_Ð

_Ë9 srm GƀBã

```
5XLMLHFRQJUHVRXUFHPDQJHU
5XLMLHFRQJVUP
```

ÏĈGĘ

Ą	ĘÄ
-	-

ĞGÄà

-

13.7 rising

ü owner-memory ê owner-cpu GƀBÈĘ› **rising Ąƀ4Ä**

{**critical | major | minor**} **rising** rising-waterline-value [**interval** interval-value] [**falling** falling-waterline-value [**interval** interval-value]]

no {**critical | major | minor**}

ËÐAà

Ð	ĘÄ

rising	rising ‴4“
rising-waterline-value	rising ‴4ĵ¸RĐ 1~100
interval-value	ĵĐ 5Đ 86400Ż4
falling	falling ‴4“
falling-waterline-value	falling ¾É 1 100è falling value N¥O rising value
no	ô84“

Ï,Õ5BÐ -

ĵĐ owner-memory ê owner-cpu G5Bã

Ï*Đ

major rising minor rising critical rising major rising

Ï5B_Đ _ 1Ö5B critical ‴4“

```
5XLMLHFRQJVUPSROLFLPHPRU\
5XLMLHFRQJRØUPHPRUFULWLFDOULVLQDOOLQWHUYDO
```

ÏÎGĵ

Ą	ĘÄ
resource manager	**E9** srm G5Bã
policy policy-name [global]	**Î** policy JE9 srm-policy G5Bã
memory	**E9** owner-memory G5Bã
cpu	**E9** owner-cpu G5Bã

ÏGÄĐ -

13.8 show resource database

/ SRM DBgÇÈ8Ý5ÇÈ8S*4ÇÈ8S*5ÇÄ

show resource database [**slot** *slot-id* [**subsystem** *subsystem-id*]]

ÏÐAĐ

Đ	ĘÄ
slot *slot-id*	ô?U/,XS5
subsystem *subsystem-id*	8Ï4 0-1ĵ show version /Ç,X cpu id

Ï,Õ5BÐ -

ĵĐ <ã

Ï*Đ -

Ï5B_Đ _ 1ÇX SRM DBgÇ

```
5XLMLHVKRZHVRXUFHGDWDEDVH
5HVRXUFH2ZQHUV,'

&SX                                                    [
0HPRU\                                                [
5HVRXUFH8VHUV,'          3ULRULW\

.WLPHU                                                 [          3527B76.
WWLPHU                                                 [     3B76.
SULQNBWDVN          [          3B76.B76
ZLWTXHXHBSURFHVV[   3527B76.
WDVNOHWBWDVN     [3527B76.
FPLFBSDXVHBGHWHFW[   3527B76.
LGOH          [     ,/(
NHYHQWV  [     3527B76.
VHSG  [     3527B76.
VHSBWUDSG     [D     3B76.
PWGEORFN     [E     3527B76.
JFBWDVN     [F     3527B76.
&RQWH[W  [G     3527B76.
NVZSG          [H     3527B76.
0RUH—
```

+‰	A
Resource Owners	C
ID	
Resource User Groups	C
Resource Users	C
Priority	PROT_TASK HAPP_TASK_TS APP_TASK APP_TASK_TS IDLE:0NK

-	-

-

13.9 show resource notification

/ SRM

show resource notification owner {**all | cpu | memory**}

Ð

Runtime(ms)	E▹ ÊÆÄ
5Sec	C¢S*5Ù 5 /¼*ü cpu C¢,X,RÚ
1Min	C¢S*5Ù 1 Ú54*ü cpu C¢,X,RÚ
5Min	C¢S*5Ù 5 Ú54*ü cpu C¢,X,RÚ

ÏĈĢĘ

Ę	ĘÄ
-	-

ĠÄâ -

13.11 show resource policy

/ SRM ,¼1*+9Ä

show resource policy {**all |** *policy-name*} [**slot** *slot-id* [**subsystem** *subsystem-id*]]

ĐAâ

Đ	ĘÄ
all	**Ý9**
policy-name	*K1Á*
slot *slot-id*	Ù?U/,XS5
subsystem *subsystem-id*	2ÝÆÆ< 0-1Ù5 show version /Ä,X cpu id

Ъ,Ø5BĐ -

Ę <ã

Ъ*Ê -

Ġ5B_Đ _ 1ÙX SRM 1*+9Ä

```
5XLMLHVKRWHVRXUFHSROLFLDOO
SROLF\1DPHURVBJOREDOBSROLF\

7\SH*OREDO
,QVH1R
52PHPRU\
FULWLFDOULVN1LQWHUYDOIDOOL1LQWHUYDO
PDMRUULVN1LQWHUYDOIDOOL1LQWHUYDO
PLQRUULVN1LQWHUYDOIDOOL1LQWHUYDO
52FSX
FULWLFDOULVN1LQWHUYDOIDOOL1LQWHUYDO
PDMRUULVN1LQWHUYDOIDOOL1LQWHUYDO
PLQRUULVN1LQWHUYDOIDOOL1LQWHUYDO
SROLF\1DPHURVBSROLF\
```

```
7\SH8VHU
,QVH1R
52PHPRU\
FULWLFDOULVLQWHUYDOIDOOLQWHUYDO
PDMRUULVLQWHUYDOIDOOLQWHUYDO
PLQRUULVLQWHUYDOIDOOLQWHUYDO
52FSX
FULWLFDOULVLQWHUYDOIDOOLQWHUYDO
PDMRUULVLQWHUYDOIDOOLQWHUYDO
PLQRUULVLQWHUYDOIDOOLQWHUYDO
3ROLF\1DPHUJRVBSROLF\

7\SH8VHU
,QVH1R
52PHPRU\
FULWLFDOULVLQWHUYDOIDOOLQWHUYDO
PDMRUULVLQWHUYDOIDOOLQWHUYDO
PLQRUULVLQWHUYDOIDOOLQWHUYDO
52FSX
FULWLFDOULVLQWHUYDOIDOOLQWHUYDO
PDMRUULVLQWHUYDOIDOOLQWHUYDO
PLQRUULVLQWHUYDOIDOOLQWHUYDO
```

+‰	AÈ
Policy Name	,¥1*+9á
Type	,¥1*+92O_
In Use	6*ü
RO memory	C5Ù,
RO cpu	C5Ùcpu

ÏGQ Q EPSá2)@Hå8)'Eå8)'Eãh(8 Hn2¥å8(8 Hnb2rCH—ãh H2)@Hã

	-
	<ã
	-
	_ 1 SRM G6(

5XLMLHVKRWHVRXUFHUHODWLRQVKLS

3RLF\ 5HVRXUFH8VHU 8VHU7\SH

JOREDO JOREDO *OREDO*URXS

UJRVBSROLF\ UJRVBJURXS 0XOWL8VHU*URXS

UJRVBSROLF\ NWLPHU 6LQJOH8VHU*URXS

+‰	A
Policy	,1*+9
Resource User	CS*5
User Type	4O_ Global Group Multi-User Group Single-User Group</<4

Q	E
-	-

-

13.13 show resource user

RU /– OX' < Öá %') D "%' â6 Y 2•D@ Ž $$B ' nòCH Õ4R„$A¯T nû$4• ò€ • R„(– Q

```
5XLMLHVKRZHVRXUFHXVHUDOO
7RWDOUHVRXUFHXVHUJURXS
0XOWL8VHU*URXSUJRVBJURXS

3ROLFUJRVBSROLF\
8VHU
5HVRXUFH2ZQHUPHPRU\
6LQJOHDWHG6L]H%
6LQJOH&RXQW
)UHH&RXQW
5HVRXUFH2ZQHUFSX
5XQWLPHV     6HF     0LQ   0LQ

6LQJOH8VHU*URXSNWLPHU

3ROLF\        UJRVBSROLF\
8VHU      NWLPHU
5HVRXUFH2ZQHUPHPRU\
6LQJOHDWHG6L]H%
6LQJOH&RXQW
)UHH&RXQW
5HVRXUFH2ZQHUFSX
5XQWLPHV          6HF     0LQ   0LQ
```

+‰	AÈ
Multi-User Group	ÎC6S*4˜
Single-User Group	)*C6S*4˜
Policy	,¥1*+9
User	C6S*5Ù
Resource Owner	C6ÝÙ
Allocated Size(B)	Ó¦XY,8VÅ
Alloc Cnt	Y,Ó!Ð
Free Cnt	Y,GÐ
Runtime(ms)	E▹
5Sec	C6S*5Ù 5 /1*ü cpu C6,X,RÚ
1Min	C6S*5Ù 1 Ú54*ü cpu C6,X,RÚ
5Min	C6S*5Ù 5 Ú54*ü cpu C6,X,RÚ

ÏÎGÐ

Ò	ÐÄ
-	-

ÐGÄð -

13.14 user

ü srm GÐBðE› **user Ð19hÐÐ¢dSÐÐ**

user *resource-user-name resource-policy-name*

no user *resource-user-name*

ÐAð

Ð	ÐÄ
resource-user-name	*C¢dSÐÐÐ* show resouce database ¡ß 2Ï¡³XC¢dS*ÐÐ
resource-policy-name	¥Á
no	ô8C¢dS*Ð[¥1*+9,XG6(Ä

Ï,ÕÐBÐ -

Ðð srm GÐBã

Ð*ô -

ÐÐ_Ð _ 1ÖÐBð rgos_policy ,X*ü,¥1*+9Ïh*ü snmpd Ä

```
5XLMLHFRQJXUHWHUPLQO
5XLMLHFRQJUHVRXFHPDQJHU
5XLMLHFRQJVUPSROFUJRVBSROLF\
5XLMLHFRQJVUPSROFH[LW
5XLMLHFRQJVUPXVHUVQSGUJRVBSROLF\
```

ÏÎGÐ

Ò	ÐÄ
resource manager	E9 srm GÐBã
policy *policy-name*	Î¥1*+9JE9 srm-policy GÐBã

ÐGÄð -

13.15 user global

ü srm GÐBðE› **user global Ð19hÏC¢dSÐÐÄ**

user global

no user global

ð

Ð	ÐÄ

global-policy-name

	Q	Ä
	resource manager	srm

-

-

%x6Q5,GY8VÖ

1. y·
2. MAC

1

1.1 carrier-delay

ÿG5BßS*Q¸ **carrier-delay** ÿA5BQÊ‡QX **no** 6E5Ó

carrier-delay [*seconds*]

no carrier-delay

ÐAß	Ð	E Ä
	seconds	ÃÝÐÐßÈ 160 /Ä

ß,Õ5BÐ EQÊ‡Õ 2 /Ä

ÜQÐ yG5BÃ

Ü*Ð AÐÛJÒÃXEQ¶#Ê DCD ¢ Down (Õ Up (ÕXÊÊp DCD Ê
¥Ê w2ÏÑ9E/¡X(ÕX6ãQ‡XDBJÒÕ‡#Ä
Vp DCD EQÊÈWKSÈwÚÐA'KSoÊC¬Ã5.ÈC¬×ÊW¿X
/Ïp,È DCD EQÊÈC¬Ã5.8,XÊÈwhAÚÐA'5B,ÎXûÈ
EÃÐ¶XC¬95Ä

Ü5B_Ð ÞX_ß8<5By¡XEQÊ 5 /Ð

```
5XLMLHFRQILJLQWHUIDFHJLJDELWHWKHUQHW
5XLMLHFRLQILJFDUULHUGHOD\
```

ÎÜQÐ

Q¸	E Ä
-	-

Ü ÄÃß

-

1.2 clear counters

#Ù8yAuD<

clear counters [*interface-id*]

ÐAß	Ð	E Ä
	interface-id	y2O_ÿÊ

ß,Õ5BÐ -

ÜQÐ (MÃ

ê y¡X4ªAuÆÆE{MÐ¸ **show interfaces ¢ÐÆü** **clear counters QÈ**
ÿ¥XAuèÐpéyÿAuDèÐ

ÏG5B_Ð 5XLMLHFOHDUFRXQWHUVJLJDELWHWKHUQHW

ÎÎGQÐ	Q¸	ÆÄ
	show interfaces	**ßA5ÐAuÇÄ**

ÏGÄê -

1.3 clear interface

y:ê@
clear interface *interface-id*

ÏÐAê

Ð	ÆÄ
interface-id	y2O_ùÆ

Ï5,Õ5BÐ -

ÏQ5ê (Mã

Ï*Ð AÐ¿¼ Switch Port,L2 Aggregrate port ,Xä0Ã¯Routed port,L3 Aggregate port ,Xä0Ã¯
¸AÐ¸bý4¼¸> **shutdown ` no shutdown QÄ**

ÏG5B_Ð 5XLMLHFOHDULQWHUIDFHJLJDELWHWKHUQHW

ÎÎGQÐ	Q¸	ÆÄ
	shutdown	GKýÁ

ÏGÄê -

1.4 descriptioin

A'5By¡Xß*ÄÐ¸X no EÑMÉÝA'5B6ä,Õ
description *string*
no description

ÏÐAê

Ð	ÆÄ
string	y¡Xä

Ï5,Õ5BÐ 5,Ûß

	yG5B
S*ü	S*ü **show interfaces Q**
G5B_Đ	5XLMLHFRQILJLQWHUIDFHJLJDELWHWKHUQHW 5XLMLHFRQILJLIGHVFULSWLRQ*%,&
GQĐ	

auto	7#GĘÄ
off	GKÁGĘÄ
on	ĐGĘÄ
receive	**M2ĐĘyå**
send	**M2ĐĘÆÕ**

ï5,Õ5BÐ 5,ÕKÁGĘÄ

ÏQ5Ð yG5Bã

ÏS*üÐ S*ü **show interfaces** ßGĘLĘÄ

ÏG5B_Ð 5%y· 1/1 ,X#GĘÖ

```
5XLMLHFRQILJLQWHUIDFHJLJDELWHWKHUQHW
5XLMLHFRQILJLIIORZZRQWURORQ
```

ÏÎGQÐ

Q¸	ÆÄ
show interfaces	¹ßA'5B»ÂuÇÄ

ÏGÄÃð -

1.7 interface aggregateport

AÇÐÐÇÆ"KÐÜÒÃÈ9yG5BÃ*ÄQ¸X no EÁMô
L8AÿÄ

interface aggregateport *port-number*

ÐAð

Ð	ÆÄ
port-number	Aggregate port ÐÈA'Ê)õ¤Ä

ï5,Õ5BÐ -

ÏQ5Ð <G5Bã

ÏS*üÐ ÃÇÐt9Ð aggregate port Ä aggregate port ,Xýý
5Ð,X2ü aggregate port ,X2ÐÄ*ü **show interfaces ê show interfaces**
aggregateport QßA5Ë

ÏG5B_Ð 5XLMLHFRQILJLQWHUIDFHDJJUHJDWHSRUW

ÏÎGQÐ

Q¸	ÆÄ
show interfaces	**ßA5ËAuÇÄ**

- -

1.8 interface fastEthernet

AÐQÈÉ%yÈ9yG5BÄ

interface fastEthernet *mod-num/port-num*

	Ð	ÄÄ
	mod-num/port-num	ÄË ÄÞX0ÈÄA'Ê)Ä¤Ä

Ä,Ã5BÐ -

ÜÇÐ <G5BÃ

Ä*Ð AÐQüÝ no

show interfaces	¡ÿA'5B¾?AuÇÄ

ÏGÄà -

1.10 interface vlan

AÇQ¸ÐÇÊ“KÐ6<.ÿsÄwitch virtual interface È SVIÀÆ9y
GÍ5BÃ*ÄÇQ¸X **no EÑMÍ8A¹** SVIÄ
interface vlan *vlan-id*
no interface vlan *vlan-id*

ÐAà

Ð	ÆÄ
vlan-id	VLAN IDÈ¥A'ÐÄ

Ï,Õ5BÐ -

ÏQÃ <G5Bã

Ï*Ð S*ü **show interfaces ê show interfaces vlan QÐA5Æ**

ÏG5B_Ð 5XLMLHFRQILJLQWHUIDFHYODQ

ÎÍGQÐ

Q¸	ÆÄ
show interfaces	¡ÿA'5B¾?AuÇÄ

ÏGÄà -

1.11 line-detect

¿ line-detect QÐõ#AÇ?y4“4ÍX(Ã
line-detect

ÐAà

Ð	ÆÄ
-	-

Ï,Õ5BÐ -

ÏQÃ yG5Bã

Ï*Ð line-detect QÐ*ü”4“4ÍX(Ã4“4ÎÍLpÿ€CÃünLp¥ÓX5BÄ

ÏG5B_Ð 5XLMLHFRQILJLQWHUIDFHJLJDELW(WKHUQHW
5XLMLHFRQILJLI*LJDELW(WKHUQHWOLQHGHWHFW

	5,ÊÄ
	yG5BÄ(=)ý Ap ` SVIÅ
	Vp 5B0,X2V(GE1 ,X2O_ 5B0,X2V(GE1 ,X2O_ O_h,X0,X2TAx2LOGG5BÄ Vp|G5B0 ,X / E’Ê*|G5B,X Ax+EG! 5Bmedium-type auto-select prefer fiber 9A’5B #{12 *TAxÄ
	5XLMLHFRQILJLQWHUIDFHJLJDELWHWKHUQHW 5XLMLHFRQILJLIPHGLXPWSHFRSSHU

	Q¸	ÆÄ
	show interfaces	**A5B uÇÄ**

	-

1.13 mtu

A’5By X mtu

Mtu *num*

	Ð	ÆÄ
	num	64 216(ÙÙ 65536 B{•

5,Õ5BÐ 92040E65536{• 4 @ =

1.14 negotiation mode

A’5By¡X7#ß*ÄQ¸X **no EÑMÝ**

negotiation mode { **on** | **off** }

no negotiation mode

Ð	Ë
on	**A5**
off	**A5B**

y¡X7#6,Ø

yG5Bä

,ß)Ú¿XA’5BÄ

M6,X_$üGKÁ· 0/1 ,X7#ß

```
5XLMLHFRQILJLQWHUIDFHJLJDELWHWKHUQHW
5XLMLHFRQILJLI*LJDELWHWKHUQHWQHJRWLDWLRQPRGHII
```

Q¸	Ë
show interfaces	**0**

-

1.15 shutdown

ÿG5Bß*ÄQ¸GKÁß*ÄQ¸X **no EÑMÛÄ**

shutdown

no shutdown

Ð	Ë
-	-

-

yG5Bã

Íyß%yÃp yßVI yßQ¸GKÁ¿XJG5B¦ßK

0*ß*ü **show interfaces Qß**

no shutdown

_ 1ØKÁ Ap 1Ö

_ 2Ô Ap 1Ö

5XLMLHFRQILJLQWHUIDFHDJJUHJDWHSRUW

5XLMLHFRQILJLIQRVKXWGRZQ

ÏĜGQÞ	Q¸	ÆÄ

1.17 speed

A'5By¡XEÿ[Ë*ÄQ¸X **no EÍMÉÚA5Bõ¸Õ**

speed [**10 | 100 | 1000 | 10G | auto**]

no speed

Ð	Ë.Ä
10	**ÿ[Kgl** 10MbpsÄ
100	**ÿ[Kgl** 100MbpsÄ
1000	**ÿ[Kgl** 1000MbpsÄ
10G	**ÿ[Kgl** 10GbpsÄ
auto	**ÿ[Kgl7ÉÕÿÄ**

Eÿ[5,ÕÉÕ,XÄ

yG5Bã

Vpy· Ap ,Xæ¸y¡XEÿ[+ Ap ,XEÿ[ÍÃ'5BAy¡XEÿ[È:K0*ÿÄ

EÕ Ap Ê*ÍÅXEÿ[A'5BÄ*ü **show interfaces Q¸5ÿ2_ÈÉ5Bó**

z2Q3ÉÈFP 2O_,XyÄÉÉA' 10M 5Ù 100MÄ

5XLMLHFRQILJLQWHUIDFHJLJDELWHWKHUQHW

5XLMLHFRQILJLIVSHHG

Q¸	Ë.Ä
show interfaces	¹ÿA'5B¾ÄuÇÄ

-

1.18 switchport

ÿG5BÊ*ÿÐ,X **switchport Q¸ÿA5B** 2 Ä*ÿ–

D,X **no switchport Q¸ÚyA5B** 3 Ä

switchport

no switchport

Ð	Ë.Ä
-	-

Ê,Õ5BÐ 5,ÿÄkyFÑÌ 2 Ä

ê AÇQ¸Ç6((=)ÚÃXyXÄ switchport Q¸X0ÚGKÁ¼JGÙÛÈE/ß
A'ÃÐ/Eý(5X#CÜpÚ¢ 2 ê 3 ê8Aý;XÝ 2
2Ä

ÜG5B_Ð 5XLMLHFRQILJLIVFWFKSRUW

ÏÎGQÞ

Q¸	£Ä
show interfaces	**ßA5ÃuÇÄ**

ÜGÄê -

1.19 switchport access

S*ÄQÞÛÃ'5B **access port** VLAN ,XäÐÃ*ÄQ¸X no EÝ
NMÁ0Ã5,ÕX VLAN Ä
switchport access vlan *vlan-id*
no switchport access vlan

ÐAê

Ð	£Ä
vlan-id	0Ø9t,X VLAN ,X IDÄ

Ü,Õ5BÐ switch port 5,ê access È,ÕX VLAN VLAN 1

ÜQê

yG5Bã

Ü*Ð Eg9Þ VLAN IDÄpEg9,XÞX VLAN IDÈ'Þ VLANÈÁ0Ã'5BA¹
VLAN ,XäÄpEg9,XÆ¡X VLAN IDÈt VLAN ,XäÐÃpA0Þ
trunkportÈ0ÚÜ*Ä

ÜG5B_Ð

```
5XLMLHFRQILJLQWHUIDFHJLJDELWHWKHUQHW
5XLMLHFRQILJLIVFWFKSRUWDFFHVVYODQ
```

ÏÎGQÞ

Q¸	£Ä
switchport mode	**ÞÛÃ**switch port ÅXÄ
switchport trunk	**Þ** trunkport ÛÞ native VLAN ÜG5BEÞ Trunk ¸XAÃE VLAN ëÄ

ÜGÄê -

1.20 switchport mode

S*ÄQÞÛÃswitch port ÅXÃÄy· access port êÙ trunk port,
êÙ' 802.1Q L{FÄS*ÄQ¸X **no EÝMÁ0ÃyÞ5Þ**

switchport mode {**access | trunk**}
no switchport mode

Ð	Ë
access	A'5BÞ switch port access portÄ
trunk	A'5BÞ switch port trunk portÄ

switch port 5,õ access

yG5Bã

Vpþ switch port ,Xã access ÀÈ5õ VLAN ,XäÄü **switchport access vlan** Qþ ,XäÄ

Vpþ switch port ,Xã trunkËÈýÃ VLAN ,XäÄýÈbº¼ VLAN +Aý¡XAÃË VLAN ëtÈ trunk port AÃË VLAN ë,XÝ VLAN ,XäÄ*ü **switchport trunk** Q9nyÄXÃË VLAN ëÄ

5XLMLHFRQILJLIVZWFKSRUWPRGHWUXQN

Q¸	Ë
switchport access	þÃ'5B statics accessportÈÚ/ÚÔ þ VLAN ,Xä0Ã
switchport trunk	þ trunkport ûþ native VLAN G5BEÞ Trunk ¡XAÃË VLAN ë

-

1.21 switchport trunk

þ trunkport ûþ native VLAN G5BEÞ Trunk ¡XAÃË VLAN ëÄ*ÄQ¸X no EÍM Áý¡X trunk 2ê5õ

switchport trunk {**allowed vlan** {**all | [add | remove | except**] *vlan-list* }**| native vlan** *vlan-id*}
no switchport trunk {**allowed vlan | native vlan**}

Ð	Ë
allowed vlan *vlan-list*	G5BEÞ Trunk ¡XAÃË VLAN ëÄ vlan-list þ VLANÈ 3ÃË VLANÞX VLAN ID ÞX VLAN ID 4È KÈÄÃËýXÖ10-20 ÄÃÄ ÄËhÖ 1-10,20-25,30,33 all ,XýAÃË VLAN ëÞX VLAN× add ×/û VLAN ët9AÃË VLAN ë× remove ×/û VLAN ëÄAÃË VLAN ëõ8× except ×/Ú8ÎX VLAN ëÞXÝ VLAN t9AÃË VLAN ë×

native vlan *vlan-id*	G5B Native VLANÄ

ï5,Õ5BÐ 5,ÕXAÆE VLAN ëA'5B allÈ,ÕX Native VLAN í VLAN 1

ÏQþÐ yG5Bã

ÏS*üÐ Native VLANÖ
0 TrunkÈþJ2bÞÔ native VLANÄç native VLANÊþþX UNTAG
y[ÈÑx2bEþ VLAN ,XÊþ¿X5,Õ VLAN IDÊ IEEE 802.1Q ,X PVIDÅ
native VLAN ,X VLAN IDÊ Trunk ëÆZb native VLAN ,XÊS*ü UNTAG ,X
ÄÅ
AÆE VLAN ëÖ
þÔ Trunk 5,ÊgA'ÕXÝ VLANÄ 1é094 ÅX#GÆÊEA'5B Trunk
¿XAÆE VLAN ë9LÊ VLAN ,X#GñÑEEþ Trunk Ä
S*ü show interfaces switchport Q¿ÅA'5BÄ

ÏG5B_Ð MI6ÞÔ VLAN 2 0ÃÃ 1/15 /ÎX_ÊÐ

```
5XLMLHFRQILJLQWHUIDFHIDVWHWKHUQHW
5XLMLHFRQILJLIVZWFKSRUWWUXQNDOORZGYODQUHPRYH
5XLMLHFRQILJLIHQG
5XLMLHVKRZQWHUIDFHIDVWHWKHUQHWVZWFKSRUW
6ZWFKSRUWLVHQDEOHG
0RGHVWUXQNSRUW
6VHVVYODQLV1DWLYHVODQLV
3URWHFWHGLVGLVDEOHG
9ODQOLVWVLV
```

ÏÎGQÞ

Q¸	ËÄ
show interfaces	/yQÄ
switchport access	ÞÃ5B statics accessportÈÚ/ÊÔ þ VLAN ,XÃÐÃ

ïGÄÃÈÐ -

1.22 show interfaces

¿ÝA'5B¾ÅuQÈÇÄ
show interfaces [*interface-id*] [**counters | description | status | switchport | trunk | transceiver** [**alarm | diagnosis**]]

ÏÐAÈÐ

Ð	ËÄ
interface-id	ÝÊ%yÃ aggregateport yÃ SVI yÃ loopback yÄÅ
counters	y¡X4ÅuQÄ



_ 2Ö Gi0/1 Access ÊÐC

```
6ZWFKSKRZQWHUIDFHVJLJDELW(WKHUQHW
,QGH[GHFKH[
*LJDELW(WKHUQHWLV2:1OLQHSURWRFROV2:1
+DUGZUHV%URDGFRP*LJDELW(WKHUQHW
,QWHUIDFHDGGUHVVLVQRLSDGGUHVV
078EWHV%:.ELW
(QFDSVXODWLRQSURWRFROV%ULGJHORRSEDFNQRWVHW
.HHSDOLYHLQWHUYDOLVVHFVHW
RUULHUGHODLVVHF
5QRDGLV7[ORDGLV
4XHXHLQJVWUDWHJ),,)2
2XWSXWTXHXHGURSV
,QSXWTXHXHGURSV
6ZFKSRUWDWWULEXWHV
LQWHUIDFHVGHVFULSWLRQ
PHGLXPWSHLVFRSSHU
ODVWFKDQJHWLPH\RXU0LQXWH6HFRQG
3ULRULWLV
DGPLQGXSOH[PRGHV8872RSHUGXSOH[LV8QNQRZQ
DGPLQVSHHGLV8872RSHUVSHHGLV8QNQRZQ
IORZHFHLYHFRQWURODGPLQVWDWXVLV2))IORZHQGFRQWURODGPLQVWDWXVLV2))IORZHFHLYH
FRQWURORSHUVWDWXVLV8QNQRZQIORZHQGFRQWURORSHUVWDWXVLV8QNQRZQ
EURDGFDVW6WRUP&RQWUROLV2))PXOWLFDVW6WRUP&RQWUROLV2))XQLFDVW6WRUP&RQWUROLV2))
    DGPLQQHJRWLDWLRQPRGHLV2))RSHUQHJRWLDWLRQLV21
3RUWWSHDFFHVV
9ODQLG$FFHVV ;X2 9/$,'
PLQXWHVLQSXWUDWHELWVVHFSDFNHWVVHF
PLQXWHVRXWSXWUDWHELWVVHFSDFNHWVVHF
SDFNHWVLQSXWEWHVQREXIIHUGURSSHG
5HFHLYHGEURDGFDVWVUXQWVJLDQWV
LQSXWHUURUV&RUDPHRYHUUXQDERUW
SDFNHWVRXWSXWEWHVQGHUUXQVGURSSHG
RXWSXWHUURUVFROOLVLRQVLQWHUIDFHUHVHWV
```

_ 3Ö Gi0/1 Hybrid ÊÆC

6ZWFKS$KRZQWHUIDFHVJLJDELW(WKHUQHW
,QGH[GHFKH[
*LJDELW(WKHUQHWLV2:1OLQHSURWRFROV2:1
+DUGZDUHLV%URDGFRP*LJDELW(WKHUQHW
,QWHUIDFHDGGUHVVLVQRLSDGGUHVV
078EWHV%:.ELW
(QFDSVXODWLRQSURWRFROV%ULGJHORRSEDFNQRWVHW
.HHSDOLYHLQWHUYDOLVVHFVHW
ÆRUULHUGHODLVVHF
5ÇRDGLV7[ORDGLV
4XHXHLQJVWUDWHJ),,)2
2XWSXWTXHXHGURSV
,QSXWTXHXHGURSV
6ZFKSRUWDWWULEXWHV
LQWHUIDFHVGHVFULSWLRQ
PHGLXPWSHLVFRSSHU
ODVWFKDQJHWLPHDV÷RXU0LQXWH6HFRQG
3ULRULWLV
DGPLQGXSOH[PRGHV8720RSHUGXSOH[V8QNQRZQ
DGPLQVSHHGV8720RSHUVSHHGV8QNQRZQ
IORZZHFHLYHFRQWURODGPLQVWDWXVLV2))IORZZHQGFRQWURODGPLQVWDWXVLV2))IORZZHFHLYH
FRQWURORSHUVWDWXVLV8QNQRZQIORZZHQGFRQWURORSHUVWDWXVLV8QNQRZQ
EURDGFDVW6WRUPÆRQWURLV2))PXOWLFDVW6WRUPÆRQWURLV2))XQLFDVW6WRUPÆRQWURLV2))
3RUWWSHKEULG
7DJJHGVODQLG„X 9/$,'
8QWDJJHGVODQLGRQHÂ„X 9/$,'
PLQXWHVLQSXWUDWHELWVVHFSDFNHWVVHF
PLQXWHVRXWSXWUDWHELWVVHFSDFNHWVVHF
SDFNHWVLQSXWEWHVQREXIIHUGURSSHG
5HFHLYHGEURDGFDVWVUXQWVJLDQWV
LQSXWHUURUV&&UDPHRYHUUXQDERUW
SDFNHWVRXWSXWEWHVXQGHUUXQVGURSSHG
RXWSXWHUURUVFROOLVLRQVLQWHUIDFHUHVHWV

_ 4Ö3 Gi0/1 yÇC

5XLMLHVKRZQWHUIDFHVJLJDELW(WKHUQHWVZFKSRUW
,QWHUIDFH6ZFKSRUW0RGH$FFHVV1DWLYH3URWHFWHG9/$OLVWV

*LJDELW(WKHUQHWHQDEOHG$FFHVVLVDEOHG$

_ 5Ö· Gigabitethernet 5/4 ,Xõ1C

5XLMLHVKRZQWHUIDFHVJLJDELW(WKHUQHWWUDQVFHLYHU
7UDQVFHLYHU7SH%$(66)3
ÆRQQHFWRU7SH/&
:DYHOHQJWKQP

```
Q
Q
P
Q
P
Q
Q
_ 6Øy        Gigabitethernet 5/4 ,XõLpA:Q
5XLMLHVKRZQWHUIDFHVJLJDELW(WKHUQHWWUDQVFHLYHUODODUP
JLJDELW(WKHUQHWWUDQVFHLYHUFXUUHQWDODUPLQIRUPDWLRQ
5QRVVRIVLJQDO
_ 7Øy        Gigabitethernet 5/4 ,XõAÆÐ,X#GQ
5XLMLHVKRZQWHUIDFHVJLJDELW(WKHUQHWWUDQVFHLYHUGLDJQRVLV
XUUHQWGLDJQRVWLFSDUDPHWHUV$$HUDJH3RZU@
7HPS&OLXV9ROWDJH9%LDVP$,SRZUG%P7,SRZUG%P
2.2.2.DODUP$Q@ODUP
```

ÏĜQÐ

Q¸	E.Ä
duplex	**E¯y¥A5Ë**
flowcontrol	**Ê¢Ç**
interface gigabitEthernet	**E**
interface aggregateport	**Ê**
interface vlan	**ïÎ¤ ¼Ô¸ Õ 6<³y ·Ä**witch virtual interfaceÈVI ÆE9yG5BÆ
shutdown	**ÿG5È¤QÇÿÄ**
speed	**A5ÿ¥Ð**
switchport priority	**A5B** 802.1q ,Xy5,Ø(Ä
switchport protected	**ÿ¤xyÄ**

ĞÄÈ

-

2 MAC

2.1 address-bind

A'5BÐ ip ` mac ,X4¥Ä

address-bind *ip-address mac-address*

no address-bind *ip-address*

ÐAð	Ð	Ä
	ip-address	IP Ä
	mac-address	mac Ä

ï5,Õ5BÐ -

ÏQ5Ð <G5Bã

Ï*Ð Vp4Ð IP Ð,X MAC 4¥À'Ð IP E IP ,XÈ

,X¥ MAC È IP 4¥,X MAC È'Á

ÏG5B_Ð M6_$ ip 3.3.3.3 ` mac 00d0.f811.1112 ,X4¥

5XLMLHFRQILJDGGUHVVELQGGI

ÏÎGQÐ

Q¸	Ä
show address-bind	**¤**

ÏGÄð -

2.2 address-bind install

]Ð™ LEQ_È*+9

address-bind install

no address-bind install

ÐAð	Ð	Ä
	-	-

ï5,Õ5BÐ -

ÏQ5Ð <G5Bã

Ï*Ð Vp|A'n_ÈAQ]Ð™+9ÑÄ

address-bind ipv6-mode strict

Ð	Ä
-	-

<G5B

4,X PAx

/Ö

IPV4+MAC 5yE@
IPV4+MAC 5yE@
IPV4+MAC 5yE@
IPV4+MAC 5yE@

IPV6 E@
ipv6 y[E@Ax
IPV6 y[E@
MAC 4,X MAC ,X IPV6 y[E@

ъ,Õ5BÐ	-
ÜQþ	<G5Bã
Ъ*Ô	Vp4þÔ IP Ô,X MAC 4₩È6ð IP Eþ IP ,XÊ ÔXð MAC Êþ IP 4₩,X MACÊÞ6ê 5ÙpAy·_Ê J4ÞÞ

2.7 mac-address-learning

G5B0Ã46ÑÔ GKÁ

mac-address-learning

ÐAê	Ð	E Ä
	-	-

ï,Õ5BÐ :46ÑÔ

ÜQê yã

Ï*Ô áÑs6ÑX0ÊKÁ MAC :46ÑÈKÁ46Ñ,X0áÑ5B]<s6Ñ

Ü5B_Ð _ 1ÖKÁ:46ÑÖ

5XLMLHFRQILJLIQRPDFDGGUHVVOHDUQLQJ

ÎGQÐ

Q¸	E Ä
-	-

ÜÄê -

2.8 mac-address-table aging-time

A’5B|ÕÊ*AQ¸X no EÑMÚA’5B6í,Õ

mac-address-table aging-time *seconds*

no mac-address-table aging-time

ÐAê	Ð	E Ä
	seconds	|Õ8Ä8EA’ÚÄ

ï,Õ5BÐ 5,Õ 300 /Ä

ÜQê <G5Bã

Ï*Ô S*ü **show mac-address-table aging-time Q5ë**

S*ü **show mac-address-table dynamic Qê**

Ü5B_Ð 5XLMLHFRQILJPDFDGGUHVVWDEOHDJLQJWLPH

ÎGQÐ

Q¸	E Ä
show mac-address-table aging-time	**|6Ê**
show mac-address-table dynamic	**|êÄ**

ĞÄâê -

2.9 mac-address-table filtering

A'5BEş*AQ¸X **no EMMĝ8Eş**

mac-address-table filtering *mac-address* **vlan** *vlan-id* [source | destination]

no mac-address-table filtering *mac-address* **vlan** *vlan-id*

ÐAê

Ð	E
mac-address	ş
vlan *vlan-id*	VLAN IDèA'ûÄ
source	MAC E>EşZA'n,X VLAN yê MAC A'n,X MAC ,XDBÄ
destination	MAC E>EşZA'n,X VLAN y,X MAC A'n,X MAC ,XDBÄ

ĕ,Õ5BÐ 5,ÛÝ'5BÏEş

8G5BÊ source ê destinationÈn,X VLAN þ,XDB¸XÊ MAC ê,X MAC A'n,X MAC ÊÑş

ÜQê <G5Bã

Ś*Ð EşÃÄ*ü **show mac-address-table filtering Qş5B**

ĞĕB_Ð 5XLMLHFRQILJPDFDGGUHVVWDEOHILOWHULQJGIYODQ

ÏĜQÞ

Q¸	E
show mac-address-table filtering	**Eş**

ĞÄâê -

2.10 mac-address-table notification

Ô MAC Eî-s6Ñ*AQ¸X **no EMMGÁ-s6Ñ**

mac-address-table notification [**interval** *value* | **history-size** *value*]

no mac-address-table notification [**interval** | **history-size**]

ÜÐAê

Ð	E
interval *value*	A'5BE Õ MAC Trap ,XÊÈh,Õ 1 /Ä
history-size *value*	MAC Eî-Æ¸××NM,XÞÈ,Õ 50Ä

ĕ,Õ5BÐ ÊÈh5,Õ 1 /èNM,XÞ5,Õ 50Ä

ÜQþ <G5Bã

Ü*Ô MAC Eî‰6ÑÑ[Ñ3ÈÈM-ÕXéó Trap EîÃ
<G5BÃEQ¸ **snmp-server enable traps mac-notification 9ÔÚÉÕ** MAC
Trap ,Xs6Ñ

ÜG5B_Đ
```
5XLMLHFRQILJPDFDGGUHVVWDEOHQRWLILFDWLRQ
5XLMLHFRQILJPDFDGGUHVVWDEOHQRWLILFDWLRQLQWHUYDO
5XLMLHFRQILJPDFDGGUHVVWDEOHQRWLILFDWLRQKLVWRU\VL]H
```

ÏGQÐ

Q¸	E Ä
snmp-server enable traps	**A5BÛ** trap ,XÑ
show mac-address-table notification	**/** MAC Eî‰6Ñ'5BEî‰Q Ä
snmp trap mac-notification	**ÔX** MAC Eî‰6Ñ

ÜGÄ -

2.11 mac-address-table static

A'5BÑ-Õ*AQ¸X **no EÚMÔ8Ñ-Õ**

mac-address-table static *mac-addr* **vlan** *vlan-id* **interface** *interface-id*

no mac-address-table static *mac-addr* **vlan** *vlan-id* **interface** *interface-id*

ÐA

ĞÄß -

2.12 show address-bind

¦ÉÍ»,XÇÄ

show address-bind

ÏÞÀß

Þ	ÆÄ
-	-

Ï,Õ5BÐ -

ÏÇß (Mã

Ï*Ô -

Ğ5B_Ð

```
5XLMLHVKRWGGUHVVELQG
,3ĞGUHVV%LQGLQJ0ĞGU

GI
GI
```

ÏÎGQÞ

Q¸	ÆÄ
address-bind	**A5BÄ**

ĞÄß -

2.13 show address-bind uplink

¦ßÇÄ

show address-bind uplink

ÏÞÀß

Þ	ÆÄ
-	-

Ï,Õ5BÐ -

ÏÇß (Mã

Ï*Ô -

Ğ5B_Ð

```
5XLMLHVKRWGGUHVVELQGXSOLQN
```

```
3RUWV6WDWH

)DLVDEOHG
)DLVDEOHG
```

ÏĨGQÐ

Q¸	ÐÆÄ
address-bind uplink	**A5B**ê

ËGÄå

-

2.14 show mac-address-learning

¹¸ÛÃ46ðÌ

show mac-address-learning

ËÐAå

Ð	ÐÆÄ
-	-

Ëĩ,Õ5BÐ

-

ËQ§

(Mã

Ës*Ð

-

ËG5B_Ð

_ 1ÛÃ46ðÌÖ

```
5XLMLHVKRZDFDGGUHVVOHDUQLQJ
```

ÏĨGQÐ

Q¸	ÐÆÄ
-	-

ËGÄå

-

2.15 show mac-address-table address

/ÝO_,X MAC Ç¿Ñ-Ëå

show mac-address-table [**address** *mac-addr*] [**interface** *interface-id*] [**vlan** *vlan-id*]

ËÐAå

Ð	ÐÆÄ
address *mac-addr*	û¸X MAC Ä
interface *interface-id*	**yË**
vlan *vlan-id*	VLAN Ë

Ëĩ,Õ5BÐ

-

2.17 show mac-address-table count

/××NMÐ,X4ÂuCÄ

show mac-address-table count [interface *interface-id* **| vlan** *vlan-id***]**

ËAÐ	Ð	EÄ
	interface *interface-id*	yË
	vlan *vlan-id*	VLAN Ë

Ëb,Õ5BÐ -

ËQÐ (Mã

ËÕ*Ð **show mac-address-table count QÐ** MAC ××NM,X2O_4Âu××NMDG£

show mac-address-table count interface QÐ MAC ××NM,Xíy4Âu××NMDG£

show mac-address-table count vlan QÐ MAC ××NM2 VLAN 4Âu××NMDGÆÄ

ËG5B_Ð _ 1Ö MAC Ø2O_,X××NMDGÆÐ

```
5XLMLHVKRW2DFDGGUHVVWDEOHFRXQW
QDPLFGGUHVVRXQW
6WDWLFGGUHVVRXQW
)LOWHUGGUHVVRXQW
7RWDO0DFGGUHVVHV
7RWDO0DFGGUHVV6SDFHV DLODEOH
```

_ 2Ö VLAN 1 ØX MAC DGÆÐ

```
5XLMLHVKRZ                    Q    Q
Q
Q
Q
Ð    Ð  Q
```

_ 3Ö interface g0/1 ØX MAC DGÆÐ

```
5XLMLHVKRZ                    Q        J
Q
Q
Q
Ð    Ð  Q
```

ÏGQÐ	Q¸	EÄ

show mac-address-table vlan	**û** VLAN ,XÝO_,XÇÄ

ËGÄà -

2.18 show mac-address-table dynamic

/|ëÇÄ

show mac-address-table dynamic [**address** *mac-addr*] [**interface** *interface-id*] [**vlan** *vlan-id*]

ËÐÀà

Ð	ÆÄ
mac-addr	û>íÝ MAC Ä
vlan-id	û>íÝ VLANÄ
interface-id	ÆÇÃ=)ÚÃ AggregatePort)

Ë5,Õ5BÐ 5,Ó<FÇ4

ËQÐ (Mã

ËS*û -

ËG5B_Ð

```
5XLMLHVKRW2DFDGGUHVVWDEOHGQDPLF
9ODQ0GUHVV7SH,QWHUIDFH

<10,&LJDELWHWKHUQHW
FD<10,&LJDELWHWKHUQHW
FGII<10,&LJDELWHWKHUQHW
FIHHH<10,&LJDELWHWKHUQHW
FIII<10,&LJDELWHWKHUQHW
EG<10,&LJDELWHWKHUQHW
EDGHF<10,&LJDELWHWKHUQHW
```

ÌÎGQÐ

Q¸	ÆÄ
-	-

ËGÄà -

2.19 show mac-address-table filtering

/E$ÇÄ

show mac-address-table filtering [**addr** *mac-addr*] [**vlan** *vlan-id*]

ËÐÀà

Ð	ÆÄ
mac-addr	û>íÝ MAC Ä

show mac-address-table filtering	**E**
show mac-address-table dynamic	**l**
show mac-address-table address	**b**
show mac-address-table vlan	**b** VLAN ,X
show mac-address-table count	**b**

-

2.21 show mac-address-table notification

/ MAC E

show mac-address-table notification [**interface**[*interface-id*] **| history**]

D	**E**
interface *interface-id*	**y** MAC E
history	/ MAC E

5, MAC E

(M

-

```
5XLMLHVKRZDFDGGUHVVWDEOHQRWLILFDWLRQLQWHUIDFH
,QWHUIDFH0&GHG7UDS0&HPRYHG7UDS

*LJDELW(WKHUQHWLVDEOHGLVDEOHG
 5 X L M L H   V K R Z  P D !#À i D & H À ,¨s8¢t€ ` `  p @ P ð € 0  p 2 _ Ð 5 P D  L P@  •  Q0H L P
```

2.22 show mac-address-table static

/M-Õ

show mac-address-table static [**addr** *mac-addr*] [**interface** *interface-id*] [**vlan** *vlan-id*]

mac-addr		MAC Ä
vlan-id		VLANÄ
interface-id		

Ï5B_Ð

```
5XLMLHVKRP2DFDGGUHVVWDEOHYODQ
9ODQ0&GUHVV7SH,QWHUIDFH

GI67$7,&LJDELWHWKHUQHW
GI67$7,&LJDELWHWKHUQHW
GI67$7,&LJDELWHWKHUQHW
```

ÏÎGQÐ

Q¸	Ë Ä
show mac-address-table static	**M-Õ**
show mac-address-table filtering	**E**
show mac-address-table dynamic	**¡Õ**
show mac-address-table address	**ôX QÄ**
show mac-address-table interface	**ôyX QÄ**
show mac-address-table count	**þX uÄ**

ÏÄÐ -

2.24 snmp trap mac-notification

ÿQX MAC Eî‰6Ñ*ÄQ¸X **no EÑMGÁ‰6Ñ**

snmp trap mac-notification {**added** | **removed**}

no snmp trap mac-notification {**added** | **removed**}

ÐAÐ

Ð	Ë Ä
added	**rtÊî Ä**
removed	**è8Êî Ä**

Ï5,Õ5BÐ 5,ÕKÁ‰6Ñ

ÏQÐ yG5Bã

Ï*Ô S*ü **show mac-address-table notification** *interface* Ø

Ï5B_Ð

```
5XLMLHFRQILJLQWHUIDFHJLJDELWHWKHUQHW
5XLMLHFRQILJLIVQPSWUDSPDFQRWLILFDWLRQDGGHG
```

ÏÎGQÐ

Q¸	Ë Ä
mac-address-table notification	**Ô** MAC Eî‰6Ñ
show mac-address-table notification	**/** MAC Eî‰6Ñ'5BEî»Q Ä

ÏÄÐ -

3 Aggregate Port

3.1 aggregateport load-balance

G5BÐ AP ,X#GE51kÐ*üQ¸X no EÝMÐ#GE5A'5B65,Ð

aggregateport load-balance {**dst-mac | src-mac | src-dst-mac | dst-ip | src-ip | src-dst-ip** }

no aggregateport load-balance

ÐAÐ

Ð	E
dst-mac	**Bg9y[** MAC E#GÐ AP ØÒ MAC ,à ,Xy[EØX0 MAC àXy[GØX0Ã
src-mac	**Bg9y[** MAC E#GÐ AP ØÒ MAC ,Xy[GØX0 MAC ,Xy[S*ØX0Ã
src-dst-ip	**8** IP IP E#GØ IP+, IP ,X#GE0E@ IP+, IP EE,XJÒG*0#GE5,X
dst-ip	**Bg9y[** IP E#GÐ AP ØÒ IP ,àXy[EØX0 IP àXy[GØX0Ã
src-ip	**Bg9y[** IP E#GÐ AP ØÒ IP ,Xy[G! àX0 IP ,Xy[S*ØX0Ã
src-dst-mac	**8** MAC MAC E#GÐ MAC+, MAC ,X#GE ,X0@ MAC+, MAC EE,XJÒ@

5,Õ5BÐ BEg9y[,X,8 MAC E#GÐ

Qð <G5B

S*Ð S*ü **show aggregateport load-balance Q5BG51k**

G5B_Ð G5BÐ,8 MAC ,X#GE5Ö

```
5XLMLHFRQILJDJJUHJDWHSRUWORDGEDODQFHGVWPDF
```

ÏGQÐ

Q¸	E
show aggregateport load-balance	**/** aggregateport A'5BÐ

GÄÐ -

3.2 port-group

Ð)ÚÃ'5B Aggregate Port ,XÐÃQ¸X no EÝMÐ8A0,8 Aggregate Port ä2Ä

port-group *port-group-number*

no port-group

ÐAÐ

Ð	ÐÄ
port-group-number	Aggregate Port ¸0Ã¯X4Ê

Aggregate Port yÐÄ

Ь¸Õ5BÐ (=)Ь¸Ð Aggregate PortÄ Ú Õ

ÏĈGQÐ	Q¸	Ɇ Ä
	aggregateport load-balance	**G5þ** AP ,X#GɆ5 1kÄ

ĞÄ **-**

4 LACP

4.1 lacp system-priority

G5B,X LACP 2ï¾{Ê*ÀQ¸X no EÍM6ê,Õ

lacp system-priority *system-priority*

no lacp system-priority

ïÐAê

Ð	Ë
system-priority	*X* LACP 2ï¾{ÈÈ 0-65535Ä

ï,Õ5BÐ 5,Ø[32768Ä

ïQ¸Þ <G5Bê

ïS*Ô LACP ,X2ï¾{+,X1u)Ú MAC À¾{4È MAC Î,XÈà

4{Õ5BÝÞ¾{,ìÈ MAC C¸X¾{CPÊ6,X|ØÒÕ.ÜE

*ÈÞï¾{ÊÈx6Þ,X8.ÜÄ

ïG5B_Ð G5B,X2ï¾{Ö

5XLMLHFRQILJODFSVVWHPSULRULW\

ïÎGQÞ

Q¸	Ë
port-group key mode active | passive	**S6ÑÃ** LACP Jû6.Ü˜ ID Eê
lacp port-priority	**G5Bê** LACP ¾{

ïGÄê -

4.2 port-group mode

S6ÑÃ LACP Jû6.Ü˜ ID ê*ÀQ¸X no EÍM¾A0Ã LACP Au

1kÄ

port-group *key* **modeactive | passive**

no port-group

ïAê

Ð	Ë
key	û6.Ü˜ ID, key Ø6.ÜD G5Ä
active	A6.êA0Ã LACP 6.Ë1kÄ
passive	A6.êA0Ã LACP

	,X LACP y[LACP Au1k.

ï5,Õ5BÐ 5,ê LACP Au1kÄ

ÏQÞÐ yG5Bä

ïS*Ð

1) ÞÊ>6.Ê4{,X0ß6.ÊÊ4{,X0ÊÝÊ
LG5BÊ0Ã¾X4“CÃG8Ã¾X4{NNcÄ

2) ÆÊU6à96ÊÎÕ AP s6ÑX0ÊÑu LACPÊ LACP àÑu
/U6à96ÊÎÕ AP s6ÑU6à96ÊÎÕÑX APÊ5B LACP
APkACP AP êÑU6à96ÊÎÕ AP ,Xs6Ñ

3) +bÊ%6ÑSÊÈ LACP EÕ AP BÐÊ EÕ AP BÙX SYSLOGØÈ
0Ã FastEthernet 0/1 EÕ AP1 BÙX SYSLOGÖ %LACP-5-UNBUNDLE_FAIL: Interface FastEthernet 0/1 failed to leave the AggregatePort 1ÅÊ5BÞU6àEÕ AP
,X,ÈG5BÊ¡ AP ,X7y[gÄ

ïG5B_Ð
```
5XLMLHFRQILJLQWHUIDFHJLJDELWHWKHUQHW
5XLMLHFRQILJLIODFSSRUWSULRULW\
```

ÏÎGQÞÐ

Q¸	Ê
port-group *key* **modeactive** | **passive**	**S6ÑÑ** LACP Jû6.Ü ID Ê

ïGÄÈÐ -

4.3 show lacp summary

/,X LACP 6.ÜÄ

show lacp summary [*key*]

ïÐAÈÐ

Ð	Ê
key	*ûÐÈÜ* idÈpÊÊAx/Ý.ÜC

ï5,Õ5BÐ -

ÏQÞÐ (MÄ

ïS*Ð -

ïG5B_Ð
```
5XLMLHVKRZ&VXPPDU\
)ODJV6HYLFHLVVHQGLQJ6ORZ&8V)HYLFHLVVHQGLQJIDVW&8V
$HYLFHLVQDFWLYHPRGH3HYLFHLVLQSDVVLYHPRGH
$JUHJDWHSRUW
```

```
/RFDOLQIRUPDWLRQ
/&SRUW2SHU3RUW3RUW
3RUW)ODJV6WDWH3ULRULW\H1XPEHU6WDWH

*L6(QGO[[[G
*L6(QGO[[[G
*L6(QGO[[[G
3DUWQHULQIRUPDWLRQ
/&SRUW2SHU3RUW3RUW
3RUW)ODJV3ULRULWHY,'H1XPEHU6WDWH

*L6(I[[[G
*L6(I[[[G
*L6(I[[[G
```

+‰	AE
Local information	/,X2ï¼1È,X0ÃX LACP ŒÄ
Port	/,X2ï¼Y0ÃX IDÄ
Flags	/,X0ÃXÔ(Ø' ù LACP (Õ 4Ønnžn£Õ LACPPDU ,X(ÕÃ'ù -0Ã¦Ä
State	/,X0Ã6.ŒÖndl ù0ÃÆ b6.(Õ Down ≠/0ÃÊý(Õ susp ≠/0Ã6.(Õ
LACP Port Priority	/,X0ÃX LACP ¼{ŒÄ
Oper Key	/,X0ÃXŒ KeyÄ
Port Number	/,X0ÃX0Æ
Port State	/,X0ÃX LACP #A(ØÄ
Partner infomation	FÆX,È0ÃX LACP ŒÄ
Dev ID	FÁX0Ã0ÃX2ï¼³ MAC ŒÄ

ÎÎGQÞ

Q¸	E

susp

5 VLAN

5.1 add

å VLAN #ïtþ Access yÈ*ü **no Q** VLAN ô8þ Access y
.

add interface { *interface-id* | **range** *interface-range* }

no add interface { *interface-id* | **range** *interface-range* }

Ð Aè

Ð	È Ä
interface-id	þ AP ·
range *interface-range*	þ AP 8È

ï ,Õ5BÐ þ%yFÑb VLAN1

ïQþ VLAN G5Bã

ï*Ð AQ¼ access port Ø
AQ¸XG5Bpþ A¼2 VLAN ,XQÈ **switchport access vlan** *vlan-idÅ*
p t9 VLAN QÈ5B*ôXsG5B,XQ¸M6G5B,XQÄ
S*¸AQÚ AP #t! VLAN È G5B¼ AP *f AP ¡Xã
Ä

ïG5B_Ð _ 1ê VLAN20 t9 GigabitEthernet 0/10 y·

```
5XLMLHFRQILJXUHWHUPLQDO
6ZWFK$FRQILJYODQ
6ZWFK$FRQILJYODQDGGLQWHUIDFH*LJDELW(WKHUQHW
5XLMLHVKRZQWHUIDFH*LJDELW(WKHUQHWVZWFKSRUW
,QWHUIDFH6ZWFKSRUW0RGH$FFHVV1DWLYH3URWHFWHG9/$OLVWV

*LJDELW(WKHUQHWQDEOHG$66LVDEOHG$
```

_ 2ê VLAN200 t9 GigabitEthernet 0/1~ GigabitEthernet 0/10 y·

```
5XLMLHFRQILJXUHWHUPLQDO
6ZWFK$FRQILJYODQ
6ZWFK$FRQILJYODQDGGLQWHUIDFHUDQJH*LJDELW(WKHUQHW
5XLMLHVKRZYODQ
6ZWFK$VKRZYODQ
9/$1DPH6WDWXV3RUWV

9/$67$7,&$L*L*L*L*L
*L*L*L*L*L*L*L*L*L
```

9/67,5L*L*L*L*L*L*L*L*L

_ 3ê VLAN20 t9 AggregatePort 10 ·

5XLMLHFRQILJXUHWHUPLQDO

6ZWFK$FRQILJYODQ

6ZWFK$FRQILJYODQDGGLQWHUIDFHDJJUHJDWHSRUW

5XLMLHVKRZQWHUIDFHDJJUHJDWHSRUWVZWFKSRUW

,QWHUIDFH6ZWFKSRUW0RGH$FFHVV1DWLYH3URWHFWHG9/$OLVWV

$JJUHJDWH3RUWQDEOHG$66LVDEOHG$

ÏĈGQÐ	Q¸	Ł Ä
	show interface *interface-id* **switchport**	¾ÐC

ĠÄê -

5.2 dot1q-vlan-current-entry mib dot1q-vlan-index max-access mode read-only

G5BAĐQÃ Dot1qVlanCurrentEntry ≈,X MIB 8V& dot1qVlanIndex ,XÐ“KÊ8Ï

ê*ÀQ¸X no EÍM6á MIB 8V& dot1qVlanIndex ,XÐ“KÊ$U6A“Kê

dot1q-vlan-current-entry mib dot1q-vlan-index max-access mode read-only

no dot1q-vlan-current-entry mib dot1q-vlan-index max-access mode

ĐAê

Đ	Ł Ä
-	-

ĕ¸Õ5BĐ -

ĊQê <G5Bã

Š*Ð ÐE?Mêg9 **end Qê** **Ctrl+C 4ë**

ĠĠ5B_Đ Â Dot1qVlanCurrentEntry ≈,X MIB 8V& dot1qVlanIndex ,XÐ“KÊ$Ïã

5XLMLHFRQILJGRWTYODQFXUUHQWHQWUPLEGRWTYODQLQGH[PD[DFFHVVPRGHUHDGRQO\

5XLMLHFRQILJ

ÏĈGQÐ	Q¸	Ł Ä
	show vlan	**/** VLAN ,XÐÃĊÄ

ĠÄê AÐQ™ S3760E-P 2ë6Ð

5.3 name

A'5B VLAN ,Xá Ä*ÄQ¸X		**no EÍMMÚA5B5Ð**
name *vlan-name*		
no name		

ÐAÐ	Ð

ÏÎGQÞ

Q¸	Ë:Ä
name	**A5B** VLAN ,XáÄ
switchport access	ý‹t9þÔ VlanÄ

ÜGÄâè -

5.5 switchport access

S*ÀÀQþÔÃ'5B access portèÚ/ÊþÔ VLAN ,XäÐÃ*ÀQ¸X **no EÝ**
NMÉÚ0ÊÃÔ VLAN Ä
switchport access vlan *vlan-id*
no switchport access vlan

ÞAâè

Þ	Ë:Ä
vlan-id	Ø VLAN ,X IDÄ

ï5,Õ5BÐ switch port 5,õ accessË:,ÕX VLAN VLAN 1

ÜQþ yG5Bã

Ï*ûÔ Eg9þÔ VLAN IDÄXpEg9,XþÔX VLAN IDÈ'ÔÔ VLANèÚ0Ã'5BA¹
VLAN ,XäÄXpEg9,XÄÊ,X VLAN IDÈ VLAN ,XäÐÃ
VpA0þÔ trunk portè,ÕÃÞ

ÜG5B_Ð

```
5XLMLHFRQILJLQWHUIDFHJLJDELWHWKHUQHW
5XLMLHFRQILJLIVZWFKSRUWDFFHVVYODQ
```

ÏÎGQÞ

Q¸	Ë:Ä
switchport mode	ûÔÄswitch port ÅxÄ
switchport trunk	ÔÞ trunk port ûÞÔ native VLAN G5BEÞ Trunk ¸XAÃË VLAN ëÄ

ÜGÄÈCÄÈÐ

trunk	**A5þ**	switch port	trunk portÄ
hybrid	**A5þ**	switch port	hybrid portÄ
uplink	**A5þ**	switch port	uplink portÄ
dot1q-tunnel	**A5þ**	switch port	802.1Q tunnel portÄ

ï5,Õ5BÐ switch port 5,õ access

ÜQþ yG5Bã

Ï*ûð Vpþô switch port ,Xã accessÁÈ¥ÿõ VLAN ,XäÄü **switchport access vlan Qþ¥Aÿþ¼** VLAN ,XäÄ

Vpþô switch port ,Xã trunkÊÿþÃ VLAN ,XäÄÿÊbð¼ VLAN +Aÿ¡XAÆE VLAN ë‡ÈÈ trunk port AÆE VLAN ë,XÝ VLAN ,XäÃ*ü **switchport trunk Q¸nyÆE** VLAN ë

ÜG5B_Ð 5XLMLHFRQILJLIVZWFKSRUWPRGHWUXQN

ÎÎGQþÐ

Q¸	Ë Ä
switchport access	**ûþÃ5B** access port È ÚW ü þô VLAN ,Xä0Ã
switchport trunk	**þô** trunk port ûþô native VLAN ÜG5BEþ Trunk ¡XAÆE VLAN ë*AQ¸X

ÜÄà¼ -

5.7 switchport trunk

þô trunk port ûþô native VLAN ÜG5BEþ Trunk ¡XAÆE VLAN ëÄ*AQ¸X **no EÍM Áÿ¡X** trunk 2ë5,Ã

switchport trunk {**allowed vlan** { **all** | [**add** | **remove** | **except**] *vlan-list* }| **native vlan** *vlan-id*}

no switchport trunk {**allowed vlan** | **native vlan** }

ÐÀà¼

Ð	Ë Ä
allowed vlan *vlan-list*	G5BEþ Trunk ¡XAÆE VLAN ëÄ vlan-list þô VLANÈ 3ÆE VLANèX VLAN ID ÔX VLAN ID 4è KÈÀÆEÿXÖ10-20 ÄÃ ÆEhÐÖ 1-10,20-25,30,33 all ,XÿAÆE VLAN ëÔX VLAN× add ×/ûÙ VLAN ët9AÆE VLAN ë× remove ×/ûÙ VLAN ëÀÆE VLAN ë08× except ×/Ú8ÎX VLAN ëÎÝ VLANt9AÆE VLAN ë×
native vlan *vlan-id*	G5B Native VLANÄ

ï5,Õ5BÐ 5,ÕXAÆE VLAN ëA'5B allÈ,ÕX Native VLAN í VLAN 1

ÏQþÐ yG5Bã

ÏS*ÐÔ **Native VLANÖ**

0 TrunkÈÞJ2bÐÔ native VLANÄç native VLANÊÞÞ¥X UNTAG y[ÈÑx2bEþ VLAN ,XÊþ,X5,Õ VLAN IDÊ IEEE 802.1Q ,X PVIDÅ native VLAN ,X VLAN IDÊ Trunk ÆÇ2b native VLAN ,XÐ*ü UNTAG ,X Ä

AÆE VLAN ë9

þÐ Trunk 5,ÊgA'ÕXÝ VLANÄ 1é094 ,X#GÆÊEA'5B Trunk ;XAÆE VLAN ë9Lê VLAN ,X#GéÑEEÞ Trunk Ä

S*ü **show interfaces switchport Q¸15Ê**

ïG5B_Ð MI6ÐÔ VLAN 2 0Ã 1/15 /ÎX_ëÐ

```
5XLMLHFRQILJLQWHUIDFHIDVWHWKHUQHW
5XLMLHFRQILJLVZLWFKSRUWWUXQNDOORZGYODQUHPRYH
5XLMLHFRQILJLIHQG
5XLMLHVKRZQWHUIDFHIDVWHWKHUQHWVZLWFKSRUW
,QWHUIDFH6ZLWFKSRUW0RGH$FFHVV1DWLYH3URWHFWHG9/$OLVWV

)LJDELW(WKHUQHWHQDEOHG7581.LVDEOHG
```

ÎÎGQÞÐ

Q¸	Ë:Ä
show interfases	**ÿ(C Ä**
switchport access	**ÏÔÃ 5B** access port È ÚW Ê Ô VLAN ,Xä0Ã

ïGÄÀè -

5.8 vlan

G5BAQÇ9 VLAN G5BÊ*ÄQ¸X no EÝMî8,ÆX VLANÄ

vlan *vlan-id*

no vlan *vlan-id*

ÐAè

Ð	Ë:Ä
vlan-id	VLAN ID Ê ê0,ÕX VLANXLAN 1 Å0BÄ

ï5,Õ5BÐ -

ÏQþÐ <G5Bã

Ï*Ð ØE?MèEg9 **end Q** **Ctrl+C 4**

ØE²G5Bèg9 **exit Q¸**

ÏG5B_Ð
5XLMLHFRQILJYODQ
5XLMLHFRQILJYODQ

ÏGQÐ

Q¸	Ä
show vlan	**/** VLAN ,XÐÃÇÄ

ÏGÄè -

6 Super-VLAN

6.1 proxy-arp

S*ÄÆQ¸Ô VLAN ,X ARP)ÉÓÑ

proxy-arp

no proxy-arp

ÐÀÐ

Ï5B_Đ

```
5XLMLHVKRWXSHUYODQ
VXSHUYODQLGVXSHUYODQDUSSUR[VXEYODQLGVXEYODQDUSSUR[VXEYODQLSUDQJH

2121
21
```

ÏÎGQÐ

Q¸	Ë
-	-

ÏGÄê -

6.3 subvlan

S*ÀQA’5BA¹ super vlan ,X subvlan 6Ô8 subvlanÄ

subvlan *vlan-id-list*

no subvlan [*vlan-id-list*]

ÐAê

Ð	Ë
Vlan-id-list	Á VLAN ,X subvlan ,X ID,ê’5Bþ vlan

ï¸Õ5BÐ -

Ïê VLAN G5Bã

Ï*Ô S*ü **no subvlan ô8A¹** supevlan ¸X subvlan

Ï5B_Đ

```
5XLMLHFRQILJYODQ
5XLMLHFRQILJYODQVXSHUYODQ
5XLMLHFRQILJYODQVXEYODQ
5XLMLHFRQILJYODQVXEYODQ
```

ÏÎGQÐ

Q¸	Ë
show supervlan	**/** supervlan ÇÄ

ÏGÄê -

6.4 subvlan-address-range

S*ÀQA’5B subvlan ,X ip 8Ã

subvlan-address-range *start-ip end-ip*

no subvlan-address-range

ÐAè

Ð	Ä
start-ip	A SubVLAN ,X IP CKŸ
end-ip	A SubVLAN ,X IP 4

Ь,Õ5BÐ

-

ÒÇÐ

VLAN G5Bã

Ь*Ð

ØE?Mèg9 **end Qè** **Ctrl+C 4**

ØE<G5Bèg9 **exit Q¸**

Ġ5B_Ð

```
5XLMLHFRQILJYODQ
5XLMLHFRQILJYODQVXEYODQDGGUHVVUDQJH
```

ÏĠQÐ

Q¸	Ä
show supervlan	**/** supervlan Ä

€ ž Ž û œ

7 Protocol VLAN

7.1 protocol-vlan ipv4

G5B IP ß%}-Ð VLAN Ø

protocol-vlan ipv4 *addr* **mask** *addr* **vlan** *id*

#Ù, X IP G5B

no protocol-vlan ipv4 *addr* **mask** *addr*

#Ý X IP G5B

no protocol-vlan ipv4

Ð A

Ð	E Ä
addr	IP È Ë x.x.x.x 6 E g9
id	VLAN ID È - {• Õ X Ù VLAN

ï5,Õ5BÐ -

ÏQþ yã

ÏS*ô -

ÏG5B_Ð 5XLMLHFRQILJLISURWRFROYODQLSY

ÏÎGQÞ

Q¸	Ë Ä
no protocol vlan ipv4	-

ÏGÄå -

7.3 protocol-vlan profile

G5By[2O_ƀ%2O_,X profile

protocol-vlan profile *num* **frame-type** *type* **ether-type** *type*

û8¤ profile G5B

no protocol-vlan profile *num*

#Ù8,ÝX profile G5B

no protocol-vlan profile

ÏÐAå

Ð	Ë Ä
num	profile 2ê
type	y[2O_ƀ%2O_

ï5,Õ5BÐ -

ÏQþ <G5Bã

ÏS*ô -

ÏG5B_Ð 5XLMLHFRQILJSURWRFROYODQSURILOHIUDPHW\SH(7+(5,,HWKHUW\SHDDUS

ÏÎGQÞ

Q¸	Ë Ä
show protocol-vlan profile	-
show protocol-vlan profile *num*	-
no protocol-vlan profile	-
no protocol-vlan profile *num*	-

ÏGÄå -

7.4 protocol-vlan profile

h*ü profile Aÿ·

protocol-vlan profile *num* **vlan** *id*

#Ù80ÃXþ profile

no protocol-vlan profile *id*

#Ù80ÃXÝ profile

no protocol-vlan profile

ÏÐAÈ

Ð	ÆÄ
num	profile 2ð
id	VLAN IDÈ- {•ÕXÛ VLAN

Ï5,Õ5BÐ -

ÏQÞ yã

ÏS*Ûð -

ÏG5B_Ð 5XLMLHFRQILJLISURWRFROYODQSURILOHYODQ

ÏÎGQÐ

Q¸	ÆÄ
show protocol-vlan profile	-
show protocol-vlan profile *num*	-
no protocol-vlan profile	-
no protocol-vlan profile *num*	-

ÏGÄÈ -

7.5 show protocol-vlan

/ Protocol VLAN ,XG5B

show vlan protocol-vlan

ÏÐAÈ

Ð	ÆÄ
-	-

Ï5,Õ5BÐ -

ÏQÞ (Mã

ÏS*Ûð

Ğ5B_Đ	5XLMLHVKRƵURWRFROYODQ

ÎĞQĮĐ		
	Q¸	Ë.Ä
	-	-

ĞÄĤĐ	
	-

8 Private VLAN

8.1 private-vlan association

G6(secondary VLAN â primary VLAN G5BQ¸

private-vlan association {*svlist* | **add** *svlist* | **remove** *svlist*}

no private-vlan association

ï**ÐAê**

Ð	Ë**Ä**
svlist	secondary VLAN list
no	#\ primary VLAN ¾X secondary VLAN G6(

ï**ь,Õ5BÐ** ĠG6(

ï**Qþ** Primary VLAN G5Bã

ï**Ь*ô** -

ï**G5B_Ð**

```
5XLMLHFRQILJYODQ
5XLMLHFRQILJYODQSULYDWHYODQDVVRFLDWLRQDGG
```

ï**ÏĠQÞ**

Q¸	Ë**Ä**
show vlan private-vlan	-

ï**GÄê** -

8.2 private-vlan mapping

ø secondary VLAN 7Ç SVI yQ¸

private-vlan mapping {*svlist* | **add** *svlist* | **remove** *svlist*}

no private-vlan mapping

ï**ÐAê**

Ð	Ë**Ä**
svlist	secondary VLAN list
no	ô8ø

ï**ь,Õ5BÐ** -

ï**Qþ** Primary VLAN ĥ,Xyã

ï**Ь*ô** -

Ï5B_Đ
5XLMLHFRQILJLQWHUIDFHYODQ
5XLMLHFRQILJLISULYDWHYODQPDSSLQJDGG

ÎGQÞ

Q¸	Ë
show vlan private-vlan	-

ÏÄð -

8.3 private-vlan type

G5B VLAN /•Ý VLAN
private-vlan {*community* | *isolated* | *primary*}
no private-vlan {*community* | *isolated* | *primary*}

ÏÐAð

Đ	Ë
community	G5B community VLAN
isolated	G5B isolated VLAN
primary	B primary VLAN
no	ô8,h,X/•Ý VLAN G5B

Ï5,Õ5BÐ /•Ý VLAN

ÏQÞÐ VLAN G5Bã

Ï*Ô -

Ï5B_Đ
5XLMLHFRQILJYODQ
5XLMLHFRQILJYODQSULYDWHYODQSULPDU\

ÎGQÞ

Q¸	Ë
show vlan private-vlan	-

ÏÄð -

8.4 switchport mode private-vlan

ÿ private VLAN ã
switchport mode private-vlan{**host**|**promiscuous**}
no switchport mode

ÏÐAð

Đ	Ë
host	/•Ý VLAN ,Xã

promiscuous	/•Ý VLAN ,X#ë
no	ô80ÃÝ VLAN G5B

ß,Õ5BÐ -

ÜQþÐ yã

Ü*ðÐ -

Ü5B_Ð 5XLMLHFRQILJLQWHUIDFHJLJDELW(WKHUQHW
5XLMLHFRQILJLVZFKSRUWPRGHSULYDWHYODQKRVW

ÏÎGQÞÐ

Q¸	Ë.Ä
show vlan private-vlan	-

ÜÄÀè -

8.5 switchport private-vlan association trunk

G5B0Ãh/• Trunk è6(àÝ VLANèG6(Ä

switchport private-vlan association trunk *p_vid s_vid*

no switchport private-vlan association trunk *p_vid s_vid*

ÐAè

Ð	Ë.Ä
p_vid	4ÊX primary VID
s_vid	ÊE secondary VID
no	ÐÝ VLAN ,XG6(

ß,Õ5BÐ -

ÜQþÐ yG5Bã

Ü*ðÐ 5XLMLHFRQILJLQWHUIDFHJLJDELW(WKHUQHW
5XLMLHFRQILJLVZFKSRUWPRGHWUXQN
5XLMLHFRQILJLVZFKSRUWSULYDWHYODQDVVRFLDWLRQWUXQN

Ü5B_Ð -

ÏÎGQÞÐ

Q¸	Ë.Ä
-	-

ÜÄÀè -

8.6 switchport private-vlan host-association

G6(private VLAN ĝG6(,X primary VLAN ȷX secondary VLAN

switchport private-vlan host-association *p_vid s_vid*

no switchport private-vlan host-association

ËDAê

Đ	ĿÄ
p_vid	4ÊX primary VID
s_vid	4ÊX secondary VID
no	/•Ý VLAN ô80Ã

ËЬ,Õ5BĐ -

ËQȩ yG5Bã

ËS*Ô -

ËG5B_Đ

```
5XLMLHFRQILJLQWHUIDFHJLJDELW(WKHUQHW
5XLMLHFRQILJLIVZWFKSRUWPRGHSULYDWHYODQKRVW
5XLMLHFRQILJLIVZWFKSRUWSULYDWHYODQKRVWDVVRFLDWLRQ
```

ÌÎGQĐ

Q¸	ĿÄ
show vlan private-vlan	-

ËGÄê -

8.7 switchport private-vlan mapping

private VLAN ,X#ÿG5BØ#ȩX secondary VLAN

switchport private-vlan mapping *p_vid* {*svlist*|**add** *svist* |**remove** *svlist*}

no switchport private-vlan mapping

ËDAê

Đ	ĿÄ
p_vid	4ÊX primary VID
svlist	ȷÆE secondary VLAN list
no	³#ȩXÝ secondaryVLAN

ËЬ,Õ5BĐ #ȩX secondary VLAN

ËQȩ /•Ý VLAN #ÿã

ËS*Ô -

Ï5B_Ð
5XLMLHFRQILJLQWHUIDFHJLJDELW(WKHUQHW
5XLMLHFRQILJLVZWFKSRUWPRGHSULYDWHYODQSURPLVFXRXV
5XLMLHFRQILJLVZWFKSRUWSULYDWHYODQPDSSLQJDGG

ÏÎGQÐ

Q¸	Ë Ä
show vlan private-vlan	-

ÏGÄð

-

8.8 switchport private-vlan promiscuous trunk

G5B0ÃË Trunk È6(à Ý VLANÈGË6(Ä
switchport private-vlan promiscuous trunk *p_vid s_list*
no switchport private-vlan promiscuous trunk *p_vid s_list*

ÐAð

Ð	Ë Ä
p_vid	4 X primary VID
s_list	secondary VID ë
no	VLAN ,XG6(

Ï,Õ5BÐ

-

ÏQÐ

yG5Bã

Ï*Ð

-

Ï5B_Ð
5XLMLHFRQILJLQWHUIDFHJLJDELW(WKHUQHW
5XLMLHFRQILJLVZWFKSRUWPRGHWUXQN
5XLMLHFRQILJLVZWFKSRUWSULYDWHYODQSURPLVFXRXVWUXQN

ÏÎGQÐ

Q¸	Ë Ä
-	-

ÏGÄð

-

8.9 show vlan private-vlan

/ private VLAN ,XG5B
show vlan private-vlan [**community** | **primary** | **isolated**]

ÐAð

Ð	Ë Ä
primary	/ primary VLAN Ç
community	/ community VLAN Ç

isolated	/ isolated VLAN Ç

Ï5,Õ5BÐ ´ private VLAN

ÏQÞÐ (Mã

Ï*Ð -

ÏG5B_Ð 5XLMLHVKRZODQSULYDWHYODQ

ÏÎGQÞÐ

Q¸	Ë Ä
-	-

ÏGÄÐ -

8.10 switchport hybrid allowed vlan

G5B hybrid 0ÃXEgÎ

switchport hybrid allowed vlan[[**add**][**tagged** | **untagged**] | **remove**] *vlist*

no switchport hybrid allowed vlan

ÐAÐ

Ð	Ë Ä
no	6á hybrid TAxEgÎ

Ï5,Õ5BÐ Ç5B

ÏQÞÐ yã

Ï*Ð -

ÏG5B_Ð 5XLMLHFRQILJLIVZWFKSRUWKEULGDOORZGYODQDGGXQWDJJHG

ÏÎGQÞÐ

Q¸	Ë Ä

ÏGÄÐ -

8.11 switchport hybrid native vlan

G5B hybrid 0ÃXTAx vlan

switchport hybrid native vlan *vid*

no switchport hybrid native vlan

ËDAê

Ð	Ë Ä
no	6á hybrid TAx VLAN

ï5,Õ5BÐ

ÞG5B

ÜQÞÐ

yã

ïS*ÐÎ

-

ÜG5B_Ð

5XLMLHFRQILJLIVZWFKSRUWKEULGQDWLYHYODQ

ÌÎGQÞÐ

Q¸	Ë Ä
-	-

ÜGÄê

-

8.12 switchport mode hybrid

G5B0Ã hybrid ·

switchport mode hybrid

no switchport mode

ÐAê

Ð	Ë Ä
no	ô8 hybrid ã

ï5,Õ5BÐ

ÞG5B

ÜQÞÐ

yã

ïS*ÐÎ

-

ÜG5B_Ð

5XLMLHFRQILJLIVZWFKSRUWPRGHKEULG

ÌÎGQÞÐ

Q¸	Ë Ä
-	-

ÜGÄê

-

9 MAC VLAN

9.1 mac-vlan enable

AÐQ*ûb0Ð GKÁ MAC VLAN s6ÑÜG5BßÕ*ÁQ¸

mac-vlan enable

ÐAß	Ð	ÆÄ
	-	-

5,ßÕXÔØGKÐ

0Ñ5Bã

NO0Ð MAC VLAN ÔÈG5B,X MAC VLAN ≈NM6ÑÑÁ

MAC VLAN s6Ñ hybrid 0ßW0Ñ

5XLMLHFRQILJXUHWHUPLQDO
(QWHUFRQILJXUDWLRQFRPPDQGVRQHSHUOLQH(QGZKLOH7/=
5XLMLHFRQILJLQWHUIDFHIDVWHWKHUQHW
5XLMLHFRQILJLIPDFYODQHQDEOH
5XLMLHFRQILJLIQRPDFYODQHQDEOH
5XLMLHFRQILJLIHQG

ÏÑGQÐ	Q¸	ÆÄ

ƀ,Õ5BÐ 5,ûX55BM-Õ MAC VLAN ≍NMÄ

ÜQƥ <G5Bã

Ƃ*Ô **mac-vlan mac-address Qƥ9G5B** MAC ĥ,X VLAN ¾¼{Äo **mac-vlan Qƥ 9ô8** MAC â VLAN ,XG6(G2Ä

ÜG5B_Ð

```
5XLMLHFRQILJXUHWHUPLQDO
(QWHUFRQILJXUDWLRQFRPPDQGVRQHSHUOLQH(QGZKH17/=
5XLMLHFRQILJPDFYODQPDFDGGUHVVYODQSULRULW\
5XLMLHFRQILJPDFYODQPDFDGGUHVVPDVN
IIIIIIIIYODQSULRULW\
5XLMLHVKRZDFYODQDOO
7KHIROORZQJ08$/$DGGUHVVH[LVW
66WDWLFQDPLF
08$06.9/$,35,2673(

IIIIIIII6
IIIIIIIIIIII6
7RWDO08$/$DGGUHVVFRXQW
```

ÎGQƥ

Q¸	Ł:Ä
show mac-vlan all	**/** MAC VLAN ≍NM

ÜGÄð -

9.3 show mac-vlan

S*ÄAQ¸1G5B,X MAC VLAN ≍NMÄ

show mac-vlan

ÜÐAð

Ð	Ł:Ä
all	**/** MAC-VLAN ≍,X¥NMÄ
dynamic	**|Õ5B**MAC-VLAN ≍NMÄ
static	**M-Õ5B**MAC-VLAN ≍NMÄ
mac-address *mac-address*	**Ý** MAC / MAC-VLAN ≍NMÄ
mask *mac-mask*	**ô** MAC 8þX MAC-VLAN ≍NMÄ
vlan *vlan-id*	**ô** VLAN ,X MAC-VLAN ≍NMÄ

ƀ,Õ5BÐ -

ÜQƥ (Mã

ÏĨGQÐ	Q¸	ÆÄ
	mac-vlan enable	**ĵb0Ø** MAC VLAN s6Ñ

ĞÄß **-**

10 SHARE VLAN

10.1 share

S*ÄQ’5B share vlanÄ

share

Đ	Ä
-	-

-

vlan G5B

0#\ share vlan *ü **no share Q**

0E?M g9 **end Q** Ctrl+C 4

0E<G5B g9 **exit Q**

5XLMLHFRQILJYODQ
5XLMLHFRQILJYODQVKDUH

Q	Ä

ØE≤G5BÈg9 **exit Q¸**

Ï5B_Ð

```
5XLMLHVKRW2DFDGGUHVVWDEOHVKDUH
9ODQ08GUHVV7SH,QWHUIDFH6WDWXV

HH<10,LJDELWRULJLQDO
HH<10,LJDELWGXSOLFDWHG
```

ÏÎGQÐ

Q¸	Ë Ä
-	-

ÏGÄÐ -

11 Voice VLAN

11.1 show voice vlan

/ Voice VLAN ,XG5BC1B6Ñ Voice VLAN s6X0,X0

11.2 show voice vlan oui

/A'ÔX OUI ÆOUI }-ÕÄ

show voice vlan oui

ÐAÕ	Ð	ÆÄ
	-	-

Ö,Õ5BÐ -

ÖQÞ (Mã

Ö*Ô EÆ8QÞÃ'ÔXAÍÇ OUI Ä

Ö5B_Ð _ 1ÐA'ÔX Voice VLAN OUI

```
5XLMLHFRQILJVKRZ ZRLFHYODQRXL
28,0DVNHVFULSWLRQ

HIIIIII6LHPHQVSKRQH
EIIIIII&VFRSKRQH
GIIIIII¥DDDSKRQH
EIIIIII3KLOLSV1(&KRQH
GHIIIIII3LQJWHOSKRQH
HIIIIII3ROFRPSKRQH
HEEIIIIIIFRPSKRQH
```

show voice vlan oui QÞCAÕ

+‰	AÊ
OUI	OUI ÈÍÍÇ,XÕ MAC Ä
Mask	OUI }-ÕOUI ,XÍSzÞ+Ö/Ä
Description	OUI ,XÆÄ

ÏGQÞ

Q¸	ÆÄ
voice vlan mac-address *mac-addr* **mask** *oui-mask* **[description** *text***]**	A'5B Voice VLAN ÃÞXAÍÇ OUI Ä

ÖÄÕ -

11.3 voice vlan

<S6Ñ Voice VLANÈ5BÞ VLAN Voice VLANÑÕ*ÄQ¸X **no EÍMGÍ** Voice VLAN s6Ñ

voice vlan *vlan-id*

no voice vlan

Ð	Ä
vlan-id	≈/ Voice VLAN ,X IDÄ

5,ÕK,ÁxÄ

<G5Bã

S*ÀŁQ,S6Ñ"|ÛX Voice VLAN s6ß Voice VLAN IDÄ

- Voice VLAN VLAN
- VLAN 1 VLAN VLAN 1 Voice VLAN
- VLAN Voice VLAN Super VLAN
- 802.1x VLAN
  VID Voice VLAN ID
- RSPAN Remote VLAN Voice VLAN 1 VLAN
  Voice VLAN

_ 1ÇS6Ñ"|ÛX Voice VLAN s6ßA'5B VLAN2 Voice VLANÄ

```
5XLMLHFRQILJYODQ
5XLMLHFRQILJYODQH[LW
5XLMLHFRQILJYRLFHYODQ
```

Q¸	Ä
show voice vlan	/ Voice VLAN ,XG5BÇ(Õ

-

11.4 voice vlan aging

<A'5B Voice VLAN 5ßÕ*ÀQ¸X **no EÝM5ßÕ**

voice vlan aging *minutes*

no voice vlan aging

Ð	Ä
minutes	≈/ Voice VLAN ,X5ßÕÄ

minutes Õ 1440 ÚsÄ

<G5Bã

Ï*Ð *Ã’Ê’5B Voice VLAN ,X5ÊÈÊÈÈÈ’ÛÉg90ÏÃÁÇ
[Ê0Ã Voice VLAN û8Ä

Ï5B_Ð _ 1Ê’5B Voice VLAN 5ÊÈ 10 Ûs
5XLMLHFRQILJYRLFHYODQDJLQJ

ÏÎGQÐ

Q¸	Ë Ä
show voice vlan	/ Voice VLAN ,XG5BÇ{Ê

ÏÄÊ -

11.5 voice vlan cos

<A’5B Voice VLAN AÁÇ,X CoS ÆÊ*ÀQ¸X **no EÁMÁG5ÊÊ**
voice vlan cos *cos-value*
no voice vlan cos

ÐAÊ

Ð	Ë Ä
cos-value	≈/ Voice VLAN AÁÇ,X CoS Ä

Ï,Õ5BÐ *cos-value* Ê 6Ä

ÏÐ <G5Bã

Ï*Ð A’ÊËÂ Voice VLAN ,XAÁÇ,X CoS â DSCP 9ÞAÁÇ,X¼{È•EÂBÇÄ

Ï5B_Ð _ 1Ï5B Voice VLAN ,XAÁÇ¼{È CoS 5
5XLMLHFRQILJYRLFHYODQFRV

ÏÎGQÐ

Q¸	Ë Ä
show voice vlan	/ Voice VLAN ,XG5BÇ{Ê

ÏÄÊ -

11.6 voice vlan dscp

<A’5B Voice VLAN AÁÇ,X DSCP ÆÊ*ÀQ¸X **no EÁMÁG5ÊÊ**
voice vlan dscp *dscp-value*
no voice vlan dscp

ÐAÐ

Ð	Ä
dscp-value	≈/ Voice VLAN AÁÍÇ,X DSCP Ä

Ð¸Õ5BÐ *dscp-value* ÐÕ 46Ä

ÐQÐ <G5Bã

Ð*ÐÔ A'ÊÐEÂ Voice VLAN ,XAÁÍÇ,X CoS â DSCP 9PAÁÍÇ,X¼{È•EÂBCÄ

Ð5B_Ð _ 1Ð5B Voice VLAN ,XAÁÍÇ¼{ÐDSCP 40Ä

```
5XLMLHFRQILJYRLFHVODQGVFS
```

ÎÐQÐ

Q¸	Ä
show voice vlan	/ Voice VLAN ,XG5BÇ{ÕÑ

ÐÄÐ -

11.7 voice vlan enable

ÿG5BÐ*ÐQ¸6ÑÃX Voice VLAN s6ÑÐ*ÐQ¸X **no EÑMGÑÃ**

Voice VLAN s6ÑÃ

voice vlan enable

no voice vlan enable

ÐAÐ

Ð	Ä
-	-

Ð¸Õ5BÐ 5,ÐÑÃX Voice VLAN s6ÑÐKÄ

ÐQÐ yG5Bã

Ð*ÐÔ EÊAÐQÐÃX Voice VLAN s6ÑVoice VLAN s6ÑÑÃ¼)ÚÑÃÃ{•Õ

Access PortÃ Trunk PortÃ Hybrid PortÃ Private VLAN Ã Private VLAN #ÐÊ Uplink Þü

Voice VLAN s6ÑÃ

Voice LAN	Voice LAN

Ð5B_Ð _ 1ÔÃ FastEthernet 0/1 ,X Voice VLAN s6ÑÃ

```
5XLMLHFRQILJLQWHUIDFHIDVW(WKHUQHW
5XLMLHFRQILJLIYRLFHYODQHQDEOH
```

ÎÐQÐ

Q¸	Ä
show voice vlan	/ Voice VLAN ,XG5BÇ{ÕÑ

ÏGÄÐ -

11.8 voice vlan mac-address

<A'5B Voice VLAN ÃÿXAÁMÇ OUI ÆÃ*ÄQ¸X **no EÁMÎ8AÐ5Þ**

Þ OUI Ä

voice vlan mac-address *mac-addr* **mask** *oui-mask* **[description** *text***]**

no voice vlan mac-address *mac-addr*

ÐAÐ

Ð	ÆÄ
mac-addr	ã *H.H.H*ØX MAC Ä
oui-mask	ã *H.H.H*ÖOUI ,XÁKSzÈÞ¼ÃÄ
text	OUI ,XÆÄ

Ï¸ÕG5BÐ 5,ØÁG5BÏ OUIÄ

ÏQÞÐ <G5Bã

ÏÕ*ÐÐ *ÐÂÏØ,X,XAÁMÇÏÄÁMÇ'Û MAC ,XÞ8V*ÐÂÏØVoice VLAN ÃÆ›

¡ÝXy[,XÐ MAC ` OUI }-ÐÞª OUIÈà¼y[ÄÁMÇÏÄ

Voice VLAN OUI

ÏG5B_Ð _ 1ÐÏ'5B OUI 0012.3400.0000 Voice VLAN ,XØÐ Company AÄ

5XLMLHFRQILJYRLFHYODQPDFDGGUHVVPDVNIIIIIGHVFULSWLRQRPSDQ\

$

ÏÎGQÞÐ

Q¸	ÆÄ
show voice vlan oui	/Ä'ÞX OUI Ã OUI }-ÐÞÄ CÄ

ÏGÄÐ -

11.9 voice vlan mode auto

ÿÏG5BÐG5B0ÃX Voice VLAN ÐÏÐÃ*ÄQ¸X **no EÁMA5BÃ**

X Voice VLAN ÐÞÄ

voice vlan mode auto

no voice vlan mode auto

ÐAÐ

Ð	ÆÄ
-	-

ï5,Õ5BÐ 0Ã Voice VLAN 0ï5,Õ

ÏQÐ yG5Bã

Ï*Ð Voice VLAN ,X0ïÐ0Õ5BÃ Voice VLAN ,X0ï
f(0K0Ã'5B3K0ïÕ Voice VLAN ,Xã
ãB0Ã?X IP +A2O_Ã2O_9A'5B0Ã Voice VLAN 0ï

> Voice VLAN Voice VLAN
> Voice VLAN
>
> native VLAN Voice
> VLAN
>
> Trunk Port/Hybrid Port VLAN Voice VLAN
> VLAN Voice VLAN Voice
> VLAN Voice VLAN
>
> Voice LAN
> Voice VLAN
>
> Voice LAN Voice VLAN

Ï5B_Ð _ 1Ð'5B0Ã FastEthernet 0/1 ,X Voice VLAN ïÃ

```
5XLMLHFRQILJLQWHUIDFHIDVW(WKHUQHW
5XLMLHFRQILJYODQYRLFHYODQPRGHDXWR
```

ÏÎGQÐ

Q¸	Ä
show voice vlan	/ Voice VLAN ,XG5BÃ6Ñ Voice VLAN s6Ñ0Ã0ï

ÏGÄð -

11.10 voice vlan security enable

<Ô Voice VLAN ,X]<ïÃ*ÄQ¸X **no EMMGÃ**

voice vlan security enable

no voice vlan security enable

ÐAð

Ð	Ä
-	-

ï5,Õ5BÐ Voice VLAN ,X]<5,Ð

ÜQþÐ <G5Bã

Ü*Ô ZÕE>ÀÁMÇÐB#ÚÉgÊÐ Voice VLAN ,X]<þÊã
À'Ù[,XÔ MAC E>Ý[Ô MAC ÃþX Voice VLAN OUI Ê
AÆÝ[ü Voice VLAN YÉgÐÝ[Ä

> Voice VLAN Voice VLAN
>
> untagged Voice VLAN tag MAC Voice VLAN tag VLAN Voice VLAN /

ÜG5B_Ð _ 1Ô Voice VLAN ,X]<Ã
5XLMLHFRQILJYRLFHYODQVHFXULWHQDEOH

ÎÜGQÞÐ

Q¸	Ë Ä
show voice vlan	/ Voice VLAN ,XG5BÇÐÕ

ÜGÄÐ -

12 MSTP

12.1 bpdu src-mac-check

ĝ X bpdu ß mac ”ÆÃQ¸X no EÝMGKÁ¸X bpdu ß mac ”s6Ñ

bpdu src-mac-check *H.H.H*

no bpdu src-mac-check

ËDAß

Đ	Ë Ä
H.H.H	≈/ÿß mac A¦X bpdu Å
no	EÝM≈/0ÿÑ¸X bpdu Å

ËЬ,Õ5BĐ 5,ÕK,ÁxÄ

ËQĝĐ yG5BÃ

ËS*ĝĐ -

ËG5B_Đ

```
5XLMLHFRQILJLQWHUIDFHJLJDELWHWKHUQHW
5XLMLHFRQILJLIESGXVUFPDFFKHFNGIHI
```

ÏĜQĝĐ

Q¸	Ë Ä
-	-

ËGÄß -

12.2 clear spanning-tree counters

#Ù8 STP ,XÀAuĢ

clear spanning-tree counters [**interface** *interface-id*]

ËDAß

Đ	Ë Ä
interface-id	ĥ,Xy·

ËЬ,Õ5BĐ -

ËQĝĐ (Mã

ËS*ĝĐ -

ËG5B_Đ

```
5XLMLHFOHDUVSDQQLQJWUHHFRXQWHUV
```

ÏĈGQÞ	Q¸	ÆÄ
	show spanning-tree counters	/ STP ¥ÐAuÇ

ËGÄß -

12.3 clear spanning-tree detected-protocols

y¥ RSTP BPDUÊ BPDU þ¾Ä

clear spanning-tree detected-protocols [**interface** *interface-id*]

ËÐAß

Ð	ÆÄ
interface-id	ĥ,Xy·

Ë5,Õ5BÐ -

ËQþÐ (Mã

Ë5*Ð -

ËG5B_Ð 5XLMLHFOHDUVSDQQLQJWUHHGHWHFWHGSURWRFROV

ÏĈGQÞ	Q¸	ÆÄ
	show spanning-tree interface	/ý· STP ,XG5BÄ

ËGÄß -

12.4 show spanning-tree

/*ßG,X<G5BÇÄ

show spanning-tree [**summary** | **forward-time** | **hello-time** | **max-age** | **inconsistentports**| **tx-hold-count** | **pathcost method** | **max_hops | counters**]

ËÐAß

Ð	ÆÄ
summary	/ MSTP ,XØ instance ,XÇ10ÃÕÄ
Inconsistentports	/x¾ÇÃ5à block ,X0Ã
forward-time	**/** BridgeForwardDelayÄ
hello-time	**/** BridgeHelloTimeÄ
max-age	**/** BridgeMaxAgeÄ
max-hops	**/** instance ,XÔÐÇÄ
tx-hold-count	**/**

Ъ,Õ5BÐ -

ÜQÞÐ (MÆÄ

Ъ*ÔÐ -

Ü5B_Ð 5XLMLHVKRWZSDQQLQJWUHHKHOORWLPH

ÏÎGQÞÐ

Q¸	ÊÄ
spanningtree pathcost method	A'5BCÃ8C,X©
spanning-tree forward-time	**A5B** BridgeForwardDelayÄ
spanning-tree hello-time	**A5B** BridgeHelloTimeÄ
spanning-tree max-age	**A5B** BridgeMaxAgeÄ
spanning-tree max-hops	**A5B** instance ,XÔÐQ
spanning-tree tx-hold-count	/ TxHoldCountÄ

ÜÄÆÞ -

12.5 show spanning-tree interface

/ STP yA'5BÆ*ÔÜ5BÄ

show spanning-tree interface *interface-id* [{**bpdufilter** | **portfast** | **bpduguard** | **link-type** }]

ÜÐAÆÞ

Ð	ÊÄ
interface-id	0Æ
bpdufilter	/ bpdufilter (Æ
portfast	**/** portfast (Æ
bpduguard	**/** bpduguard (Æ
link-type	/0ÃX linktype

Ъ,Õ5BÐ -

ÜQÞÐ (MÆÄ

Ъ*ÔÐ -

Ü5B_Ð 5XLMLHVKRWZSDQQLQJWUHHLQWHUIDFHJLJDELWHWKHUQHW

ÏÎGQÞÐ

Q¸	ÊÄ
spanning-tree bpdufilter	ÞX BPDU filter ÔÄ
spanning-tree portfast	ÞX portfast ÔÄ
spanning-tree bpduguard	ÞX BPDU guard ÔÄ

spanning-tree link-type	G5By¡XE℘2O_ǽ℘”Ä

ÏGÄâê -

12.6 show spanning-tree mst

(Mê*ïQ¡Ã MST G5BÈnstance ,XÇÄ

show spanning-tree mst { **configuration** | *instance-id* [**interface** *interface-id*] }

ÏDAâê

Ð	E.Ä
configuration	A’ÎX mst G5B
instance-id	*Instance É*
interface-id	0Ê

ï5,Õ5BÐ 5,ÕÝ InstanceÄ

ÏQ¡Ð (Mã

Ï*Ôð -

ÏG5B_Ð 5XLMLHVKRWZSDQQLQJWUHHPVWFRQILJXUDWLRQ

ÎÎGQ¡Ð

Q¸	E.Ä
spanning-tree mst configuration	E9 MST region G5B
spanning-tree mst cost	/ instance ,XCÃ8C.
spanning-tree mst max-hops	/ instance ,XÔQ¸
spanning-tree mst priority	**/** instance ,XA’Û
spanning-tree mst port-priority	/ instance ,X0Ã

ÏGÄâê -

12.7 spanning-tree

Ô MSTPèÐ MSTP ,XÊ’5B MSTP <,XÂ’5BÄ*ÀQ¸X no EÝMG KÁspanning-tree sõÑð no Q¡DEÝMMÉÐ65¸JÊKÁ spanning treeÄ

spanning-tree [**forward-time** *seconds* | **hello-time** *seconds* | **max-age** *seconds*]

no spanning-tree [**forward-time** | **hello-time** | **max-age**]

ÏDAâê

Ð	E.Ä
forward-time *seconds*	0(ÕXÊÈhÄ
hello-time *seconds*	A’ÛÊÕ BPDU y[,XÊÈhÄ
max-age *seconds*	BPDU y[#Ć*ó¸XÔSÊÃ

12.9 spanning-tree bpdufilter

pQX BPDU filter GÂÃÃAQ¸X enabled ê disabled EÝMÊGÊGÂÄÄMtpÄWdjÜÃÃpqÔMã

Ï5B_Đ 5XLMLHFRQILJLIVSDQQLQJWUHHJXDUGORRS

ÏÎGQÞÐ

Q¸	Ë Ä
-	-

ÏGÄÈ -

12.13 spanning-tree guard none

yÐGKÁ guard (MÈ*ÄQ¸X no EÝMM#yÞX guard s6Ñ

spanning-tree guard none

no spanning-tree guard none

ÐAÈ

Ð	Ë Ä
-	-

Ï,Õ5BÐ GKÁ guard s6Ñ

ÏQÞÐ yG5BÄ

Ï*Ô -

Ï5B_Đ 5XLMLHFRQILJLIVSDQQLQJWUHHJXDUGQRQH

ÏÎGQÞÐ

Q¸	Ë Ä
-	-

ÏGÄÈ -

12.14 spanning-tree guard root

yÔ root guard (MÈ*ÄQ¸X no EÝMGKÁ root guard (MÈ root guard s6ÑÏ5´

JÄÑ5BÏM2Þ[¸XÐÈ!XÄ

spanning-tree guard root

no spanning-tree guard root

ÐAÈ

Ð	Ë Ä
-	-

Ï,Õ5BÐ 5,ÕGKÁ root guard s6Ñ

ÏQÞÐ yG5BÄ

shared.

ÏQþÐ yG5BÃ

ÏS*ÐÔ -

ÏG5B_Ð 5XLMLHFRQILJLQWHUIDFHJLJDELWHWKHUQHW
5XLMLHFRQILJLVSDQQLQJWUHHOLQNWSHSRLQWWRSRLQW

ÏÎGQÞÐ

Q¸	Ë Ä
show spanning-tree interface	*/ STP 0Ñ5B

ÏGÄÀð -

12.17 spanning-tree loopguard default

<Ô loop guard (MÀ*ÀQ¸X no EÍMGKÁloop guard (MÀü loop guard s6ÑÑ6
0Ñ bpdu 5ê*ôXÑÑX)ÇÃ

spanning-tree loopguard default

no spanning-tree loopguard default

ÐAÀð

Ð	Ë Ä
-	-

Ï¸,Õ5BÐ 5,ÕKÁ loop guard s6Ñ

ÏQþÐ <G5Bã

ÏS*ÐÔ -

ÏG5B_Ð 5XLMLHFRQILJVSDQQLQJWUHHORRSJXDUGGHIDXOW

ÏÎGQÞÐ

Q¸	Ë Ä
-	-

ÏGÄÀð -

12.18 spanning-tree max-hops

ëG5BÃ*ÐQÃ'5B BPDU ÎXÔÔÇÑMax-hops Count ÀVûZ BPDU ü
ÞÔ Region Y4ËÃ'ÃX Instance Ã*ü no EÍMÑÑQ¸ãÇ
5,Ñ

spanning-tree max-hops *hop-count*

no spanning-tree max-hops

Ð	Ä
hop-count	BPDU 1 0

hop-count 20

<G5B

ü Region Y Root Bridge BPDU Hot Count Root Bridge
op Count 1 0 BPDU CY Hops 0 ,X BPDU
W Ä
¬ max-hops Instance Ä

MST Instance ,X Max-hops A' 10Ö
5XLMLHFRQILJVSDQQLQJWUHHPD[KRSV
3 9 **show spanning-tree mst**

Q	Ä
show spanning-tree	MSTP

-

12.19 spanning-tree mode

STP (no E
spanning-tree mode [**stp** | **rstp** | **mst***p*]
no spanning-tree mode

Ð	Ä
stp	Spanning tree protocol(IEEE 802.1d)
rstp	Rapid spanning tree protocol(IEEE 802.1w)
mstp	Multiple spanning tree protocol(IEEE 802.1s)

MSTP (

<G5B

-

5XLMLHFRQILJVSDQQLQJWUHHPRGHVWS

Q	Ä

show spanning-tree	**5B**

GÄ -

12.20 spanning-tree mst configure

ü *1QÃ9 MST G5B MSTP Region ü no EMÃQ
DÄame Ævision Ævlan map Ã,Õ
spanning-tree mst configuration
no spanning-tree mst configuration

Ð	EÄ
-	-

5,Õ5BÐ 5,Õ instance ` vlan ,XhG2X Vlan F Instance 0 Ä
name 0N+0Ä
revision 0Ä

<G5Bã

*Ð 0E?MEg9 end Q9 Ctrl+C 4Ä
0E<G5BEg9 exit QÄ
E9 MST G5BÃ*QE<G5BÐÖ
instance *instance-id* **vlan** *vlan-range* Vlan 4#ï MST Instance ÄG instance-id ,X8 0 64Ävlan ,X8 1409 Ävlan-range Ã vlan ,XLÃVLAN ID *EEhÐ4,X VLAN ID Ã*ý VLAN ID E_ÈVÖ instance 10 vlan 2,3,6-9 nØ VLAN 2È 3È 6È 7È 8È 9 #ï Instance 10 Ä,ÕXG5B,X VLAN ü Instance 0 Ä VLAN ¢ Instance 0,XÃ*ü **no Q o** **instance** *instance-id* [**vlan** *vlan-range*]Ø4 no Q Instance ,X8 164)
name *name* MST Ã 32 +0X+0Ãü no name Ã,Õ
revision *version* MST (D 0655535 Ãü no revision Ã,Õ
show spanning-tree mst configuration MST region Ä

5B_Ð M6_9AE)E9 MST Ã VLAN 3, 5-10 Ø MST Instance 1.

```
5XLMLHFRQILJVSDQQLQJWUHHPVWFRQILJXUDWLRQ
5XLMLHFRQILJPVWLQVWDQFHYODQ
5XLMLHFRQILJPVWQDPHUHJLRQ
5XLMLHFRQILJPVWUHYLVLRQ
5XLMLHFRQILJPVWVKRZSDQQLQJWUHHPVWFRQILJXUDWLRQ
067FRQILJXUDWLRQ
1DPHUHJLRQ@
5HYLVLRQ
,QVWDQFH9ODQV0DSSHG
```

5XLMLHFRQILJPVWH[LW

5XLMLHFRQILJ

VpØÚ VLAN 3 ¢ Instance 1 ß8ÈwE9 MST G5BßV(XE/ß

5XLMLHFRQILJPVWQRLQVWDQFHYODQ

VpØÉÞ Instance 1 ß8ØÖ

5XLMLHFRQILJPVWQRLQVWDQFH

|ÆE› MST G5BQ¸X show PÄ•ËËÁ

ÏÎGQÞ

Q¸	ÆÄ
show spanning-tree mst	¦ß MST region G5B
instance instance-id vlan vlan-range	Vlan 4#ï MST Instance
name	**G5B** MST ,Xá

ÏGÄß

-

12.21 spanning-tree mst cost

ÿß*ßQÄ'5Bß Instance ,XCÃ8CÄ*ü no EÁMÃÑQ6ÃÇ,Õ

spanning-tree [**mst** *instance-id]* **cost** *cost*

no spanning-tree [**mst** *instance-id*] **cost**

ÐAß

Ð	ÆÄ

Ï,Õ5BÐ]TJ21.5 068d()53 T 1.840370Tj

ÏÎGQÞÐ

Q¸	Ë.Ä
show spanning-tree mst	**ß¾X** MSTP Ç.Ä
spanning-tree mst port-priority	**G5B¾{**
spanning-tree mst priority	instance G5B¾{

ÏGÄßÐ -

12.22 spanning-tree mst port-priority

ÿGÞ5BßÐ*ßQ¸Ã'5BA¼ÿJ¼ß Instance ¼ßX0Ã¼{È·É¡
Region Y6¾ÇÃXÞßÐ(ßÐ*ü no ÉÑMÃÐQ¸ãÇ¸Ã

spanning-tree [**mst** *instance-id*] **port-priority** *priority*
no spanning-tree [**mst** *instance-id*] **port-priority**

ÐAßÐ

Ð	Ë.Ä
Instance-id	Instance ÐÈ 0É4
priority	0Ã{Ê*ü 0È6È24È8 É4 È0È6 È12È28 È44 È160È 176È192 È208È224È240È 16 þIDÈ 16 ,XÐÄ

Þ¸Õ5BÐ Instance-id ,X5,Õ 0
priority ,X5,Õ 128

ÏQßÐ yG5Bã

Ê*Ðß ü Region Y6¾ÇÃÉÑ¼{,X0ÃÐ(Ð¸ÊÝüËWãX
0Ã

ÏG5B_Ð ßÚ Instance 20 ,X Gigabitethernet 1/1 y¸X¼{A' 10Ö

```
5XLMLHFRQILJLQWHUIDFHJLJDELWHWKHUQHW
5XLMLHFRQILJLIVDQQLQJWUHPVWSRUWSULRULW\
```

Ã9 **show spanning-tree mst instance interface** *interface-id* ß

ÏÎGQÞÐ

Q¸	Ë.Ä
show spanning-tree mst	¼ß¸X MSTP Ç.Ä
spanning-tree mst cost	**A5BßÐC.**
spanning-tree mst priority	4ä Instance A'5BA'ÛÚ{

ÏGÄßÐ -

12.23 spanning-tree mst priority

¤GÞ5BßÐ*ßQ¸Ã- Instance A'5BA'ÛÚ{Ê*ü no ÉÑMÃÐQ¸ãÇ¸Õ
Ä

spanning-tree [**mst** *instance-id*] **priority** *priority*

no spanning-tree [**mst** *instance-id*] **priority**

Ð	EÄ
instance-id	Instance ÐÈ 0É4
priority	A’ û4{ ÐÈ Ýü 0, 4096,8192, 12288, 16384, 20480, 24576, 28672, 32768, 36864, 40960, 45056, 49152,53248, 57344 ` 61440Ä E 16 þIDÈ 4096 ,XÐÄ

ï5,Õ5BÐ *instance-id* ØÕ 0è*priority* ØÕ 32768

ÜQÞ <G5Bã

Ï*ÐÎ -

Ï5B_Ð ß4- Instance 20 A’5B,XA’ûÛ{A’ 8192Ö

5XLMLHFRQILJLIVSDQQLQJWUHHPVWSULRULW\

ÑÑ9 **show spanning-tree mst instance interface interface-id (MQÞÀ ÐÈ5Ë**

Q¸	EÄ
show spanning-tree mst	**ßX** MSTP ÇÄ
spanning-tree mst cost	**A5BÃC**
spanning-tree mst port-priority	**4ã** Instance A’5B0Ã{Ä

ïGÄÐ -

12.24 spanning-tree pathcost method

G5B0ÇÃ8C,X5,Õu1kÏ*ÀQ¸X no EÑMÚA’5B6ã,Õ

spanning-tree pathcost method {{**long [standard]}** | **short**}

no spanning-tree pathcost method

Ð	EÄ
long [standard]	G*ü 802.1t Ê’n path-cost ,XÄ standard ×/ß9,XÀu1k cost Ä
short	G*ü 802.1d Ê’n path-cost ,XÄ

ï5,Õ5BÐ 5,Õ*ü 802.1T Ê’n Path-cost ,XÄ

ÜQÞ <G5BÄ

Ï*ÐÎ -

ËG5B_Đ 5XLMLHFRQILJLIVSDQQLQJWUHHSDWKFRVWPHWKRGORQJ

ÏÎGQÞÐ

Q¸	Ë:Ä
show spanning-tree interface	/ STP yG5BÄ

ËGÄß -

12.25 spanning-tree portfast

þÔX Portfast ÔÄÄÃÃ:Q¸X disabled EÝMGKÁ¸X Portfast ÔÄ

spanning-tree portfast [**disabled**]

Ï5B_Ð 5XLMLHFRQILJVSDQQLQJWUHHSRUWIDVWESGXILOWHUGHIDXOW

ÏÎGQÞ

Q¸	Ë Ä
show spanning-tree interface	**/** STP <G5BÄ

ÏGÄð -

12.27 spanning-tree portfast bpduguard default

<,XÔ BPDU guardÆÆÆQ¸X no EÝM<,XGKÁ BPDU guardÄ

spanning-tree portfast bpduguard default

no spanning-tree portfast bpduguard default

ÐAð

Ð	Ë Ä
-	-

Ï,ÕG5BÐ 5,ÕGKÁ BPDU Guard.

ÏQþ <G5BÄ

Ï*Ô 'Ô BPDU guard È/ p ùA¹0ÃÞ BPDU ÈÈE¯9 error-disabled (SÕÆ*ü **show spanning-tree** Q¸Ä5BÄ

Ï5B_Ð 5XLMLHFRQILJVSDQQLQJWUHHSRUWIDVWESGXJXDUGGHIDXOW

ÏÎGQÞ

Q¸	Ë Ä
show spanning-tree interface	/ STP <G5B

ÏGÄð -

12.28 spanning-tree portfast default

<ÿQX Portfast ÔÆ*ÄQ¸X no EÝM<GKÿX Portfast ÔÄ

spanning-tree portfast default

no spanning-tree portfast default

ÐAð

Ð	Ë Ä
-	-

Ï,ÕG5BÐ 5,ÕGKÿX Portfast ÔÄ

ÏQþ <G5BÄ

Ь*Ð -

ĠБВ_Đ 5XLMLHFRQILJVSDQQLQJWUHHSRUWIDVWGHIDXOW

ÎĠQÞ

Q¸	ÆÄ
show spanning-tree interface	/ STP <GБBÄ

ĠÄå -

12.29 spanning-tree reset

Ú Þ spanning-tree A’5B6ß,ÕQ¦Ý no EÝMÄ

spanning-tree reset

ÐAå

Ð	ÆÄ
-	-

Ь,ÕБBÐ -

ÙÞ <GБBÄ

Ь*Ð -

ĠБВ_Đ

ÏQþÐ yG5Bã

ÏS*ÔÐ -

ÏG5B_Ð 5XLMLHFRQILJLIVSDQQLQJWUHHWFJXDUG

ÏÎGQÞÐ

Q¸	ÆÄ
-	-

ÏGÄÃÐ

12.31 spanning-tree tc-protection

<Ô tc- protection ÔØS*ÆQ¸X no EÝM<GKÁ tc- protection ÔÄ

spanning-tree tc- protection

no spanning-tree tc- protection

ÐAÃÐ

Ð	ÆÄ
-	-

Ï5,Õ5BÐ 5,Õ tc-protection ÔÄ

ÏQþÐ <G5BÃÄ

ÏS*ÔÐ -

ÏG5B_Ð 5XLMLHFRQILJVSDQQLQJWUHHWFSURWHFWLRQ

ÏÎGQÞÐ

Q¸	ÆÄ
-	-

ÏGÄÃÐ -

12.32 spanning-tree tc-protection tc-guard

<Ô tc- guard ÔØS*ÆQ¸X no EÝM<GKÁ tc- guard ÔÄu tc-guard s6ÕÑ6 tc y[,X=7Ä

spanning-tree tc-protection tc-guard

no spanning-tree tc-protection tc-guard

ÐAÃÐ

Ð	ÆÄ
-	-

ƀ,Õ5BÐ 5,ÕKÁ tc-guard ÔÄ

ÜQƀÐ <G5BÅ

ƁªÔÐ -

ÜG5B_Đ 5XLMLHFRQILJVSDQQLQJWUHHWFSURWHFWLRQWFJXDUG

ÎÜGQÐ

Q¸	ÆÄ
-	-

ÜGÄÅ -

12.33 spanning-tree tx-hold-count

STP <,X TxHoldCount A'5BÈG5BÆÐÕX BPDU ÞÄª*AQ¸X no EÝMÚA'5B6 ÅÄÕ

spanning-tree tx-hold-count *tx-hold-count*

no spanning-tree tx-hold-count

ÐAÅ

Ð	ÆÄ
tx-hold-count	TxHoldCount A'5BÄÈ 1 10Ä

ƀ,Õ5BÐ 5,Õ 3Ä

ÜQƀÐ <G5BÅ

ƁªÔÐ -

ÜG5B_Đ 5XLMLHFRQILJVSDQQLQJWUHHW[KROGFRXQW

ÎÜGQÐ

Q¸	ÆÄ
show spanning-tree	**/** MSTP <G5BÇÄ

ÜGÄÅ -

13

13.1 bridge-frame forwarding protocol bpdu

Ô BPDU #AÆÈê6Ñ*ÄÆQ¸X **no EÍMMÓÍK** BPDU #AÆÈê6Ñ

bridge-frame forwarding protocol bpdu

no bridge-frame forwarding protocol bpdu

ÐAÈ

Ð	ÆÄ
-	-

Ï5,Õ5BÐ 5,ØÛX BPDU #AÆÈê6ÑKÁXÄ

ÏQÞ <G5BÄ

ÏS*Ô -

ÏG5B_Ð _ 1ÄÐ'Ô BPDU #AÆÈê6Ñ

5XLMLHFRQILJEULGJHIUDPHIRUDUGLQJSURWRFROESGX

_ 2ÄÐ'ÔKÁ BPDU #AÆÈê6Ñ

5XLMLHFRQILJQREULGJHIUDPHIRUDUGLQJSURWRFROESGX

ÏÎGQÞ

Q¸	ÆÄ
-	-

ÏGÄÈ -

13.2 bridge-frame forwarding protocol gvrp

Ô GVRP #AÆÈê6Ñ*ÄÆQ¸X **no EÍMMÓÍK** GVRP #AÆÈê6Ñ

bridge-frame forwarding protocol gvrp

no bridge-frame forwarding protocol gvrp

ÐAÈ

Ð	ÆÄ
-	-

Ï5,Õ5BÐ 5,ØÛX GVRP #AÆÈê6ÑKÁXÄ

ÏQÞ <G5BÄ

ÏS*Ô -

Ï5B_Đ _ 1Ø'Ô GVRP #AÊê6Ñ
5XLMLHFRQILJEULGJHIUDPHIRUDUGLQJSURWRFROJYUS
_ 2Ø'ÔKÁ GVRP #AÊê6Ñ
5XLMLHFRQILJQREULGJHIUDPHIRUDUGLQJSURWRFROJYUS

ÏÎGQÞ

Q¸	Ê
-	-

ÏGÄð -

13.3 bridge-frame forwarding protocol 802.1x

Ô 802.1X #AÊê6Ñ*ÀQ¸X **no EÝMÓÁ** 802.1X #AÊê6Ñ
bridge-frame forwarding protocol 802.1x
no bridge-frame forwarding protocol 802.1x

ÐAð

Ð	Ê
-	-

Ï,Õ5BÐ 5,Ø¾X 802.1X #AÊê6ÑXÄ

ÏQÞ <G5BÁ

Ï*Ô -

Ï5B_Đ _ 1Ø'Ô 802.1X #AÊê6Ñ
5XLMLHFRQILJEULGJHIUDPHIRUDUGLQJSURWRFRO[
_ 2Ø'ÔKÁ BPDU #AÊê6Ñ
5XLMLHFRQILJQREULGJHIUDPHIRUDUGLQJSURWRFRO[

ÏÎGQÞ Q¸ÏÊ5gÞ[ÔÀ4ÐÔ6ÐÔ@ÀÐÔ#ÊÔ6ÔÔQÀÞÔXÄxVs0PÞ%eQş1þDÆSÔ"ÊSÔ@ÊÔÔPg(ÐÔPg(Ê,ÕÊGF1 bFÞ3ÞP1s="ÐÞVÐBQÐD%

-	-

Ъ,Õ5BÐ	5,ØÛX±-4#AÊõ6ÕXÄ
ÙÇÐ	<G5BÃ
Ъ*Ô	-
Ù5B_Ð	_

14 GVRP

14.1 clear gvrp statistics

#Ù8 GVRP ,X4ªAuèJGß uD

clear gvrp statistics { *interface-id* | **all**}

ÐAß	Ð	Ë Ä
	interface-id	5%4ÿ· ID

ï ,Õ5BÐ -

ÏQÞ (Mã

Ï*Ð S*ü **show gvrp statistics QÞªAu**

Ï5B_Ð 5XLMLHFOHDUJYUSVWDWLVWLFVDOO

ÏGQÞ

Q¸	Ë Ä
show gvrp statistics	**/** GVRP 4ªAuÇ

ÏÄß -

14.2 gvrp applicant state

AÐQA'5B0Ã¸XEß Ã Õ GVRP EÄ*ÄQ¸X no EÝM6ê ,Õ'5BÄ

gvrp applicant state {**normal** | **non-applicant**}

no gvrp applicant state

ÐAß	Ð	Ë Ä
	-	-

ï ,Õ5BÐ AO Ã Õ GVRP EÄ

ÏQÞ yG5Bã

Ï*Ð S*ü **show gvrp configuration QÞ5B**

Ï5B_Ð 5XLMLHFRQILJLIJYUSDSSOLFDQWVWDWHQRUPDO

ÏÎGQÞ

Q¸	Ł.Ä
show gvrp configuration	**/** GVRP G5BQ1

ËGÄà

-

14.3 gvrp dynamic-vlan-creation

AÐ{ÁQÎ vlanÈ*ÄQ¸X no EÝM6á,Ø'5BÄ

gvrp dynamic-vlan-creation enable

no gvrp dynamic-vlan-creation enable

ÐAà

Ð	Ł.Ä
-	-

Ë,Õ5BÐ /U6|Õ vlan

ËQÞ <G5Bã

Ë*Ô S*ü **show gvrp configuration QÞ5B**

ËG5B_Ð 5XLMLHFRQILJJYUSGQDPLFYODQFUHDWLRQHQDEOH

ÏÎGQÞ

Q¸	Ł.Ä
show gvrp configuration	**/** GVRP G5BQ1

ËGÄà

-

14.4 gvrp enable

AÐQÔ GVRP s6Ñ*ÄQ¸X no 6á,Ø'5BÄ

gvrp enable

no gvrp enable

ÐAà

Ð	Ł.Ä
-	-

Ë,Õ5BÐ GKÁ GVRP

ËQÞ <G5Bã

Ë*Ô S*ü **show gvrp configuration QÞ5B**

ËG5B_Ð 5XLMLHFRQILJJYUSHQDEOH

ÏÎGQÞ

Q¸	Ð£Ä
show gvrp configuration	**/** GVRP G5BQ1

ÏGÄß

-

14.5 gvrp registration mode

AÐQA'5B0Ã¥,OAßà¢ÃDA¾ÔÕX VLANÄ*ÄÐQ¸X no EÝ

NM6ß,Õ'5B

gvrp registration mode {**normal** | **disabled**}

no gvrp registration mode

ÐÄß

Ð	Ð£Ä
-	-

Ï5,Õ5BÐ AÃDA¾ÔÕX VLAN

ÏQß yG5Bã

Ï*Ð S*ü **show gvrp configuration**

```
3RUW*LJDELW(WKHUQHWDSSPRGHQRUPDOUHJPRGHQRUPDO
3RUW*LJDELW(WKHUQHWDSSPRGHQRUPDOUHJPRGHQRUPDO
3RUW*LJDELW(WKHUQHWDSSPRGHQRUPDOUHJPRGHQRUPDO
3RUW*LJDELW(WKHUQHWDSSPRGHQRUPDOUHJPRGHQRUPDO
3RUW*LJDELW(WKHUQHWDSSPRGHQRUPDOUHJPRGHQRUPDO
3RUW*LJDELW(WKHUQHWDSSPRGHQRUPDOUHJPRGHQRUPDO
3RUW*LJDELW(WKHUQHWDSSPRGHQRUPDOUHJ
PRGHQRUPDO
3RUW*LJDELW(WKHUQHWDSSPRGHQRUPDOUHJ
PRGHQRUPDO
3RUW*LJDELW(WKHUQHWDSSPRGHQRUPDOUHJ
PRGHQRUPDO
```

ÏĈGQĐ	Q¸	Ł:Ä
	-	-

ĊGÄß -

14.8 show gvrp statistics

/ðßÃX GVRP 4²Au

show gvrp statistics {*interface-id* | **all**}

ß5HÄ#ßYUS3GßÃ3Ã3Ã3ÁÃ3ÁÃAVvQ¸ß5HÄ%ßYUS3GßÃ3Ã3ÁÃ3ÁÃAUg5K€ ß5HÄßEYH,Q3Ã3Ã3ÃAVvQ¸

```
6HQW-RLQ,Q
6HQW(PSW\
6HQW/HDYH(PSW\
6HQW/HDYH,Q
6HQW/HDYHSDO
-RLQ,QGLFDWHG
/HDYH,QGLFDWHG
-RLQ3URSDJDWHG
/HDYH3URSDJDWHG
```

ÏĈGQÐ

Q¸	Ł Ä
clear gvrp statistics	è8ô8ôX GVRP 4³Au

ĊGÄê

-

14.9 show gvrp status

/+ GVRP *øX|Õ VLAN ,XýÐÕM-Õ VLAN ,X|ðÐÃ

show gvrp status

ĐAê

Đ	Ł Ä
-	-

ƀ,Ѳ5BĐ

-

ĊQê

(Mã

ĊƀHð

S*ü **show gvrp status Q(** GVRP (Õ

ĊƀB_Đ

```
5XLMLHVKRZ YUSVWDWXV
```

ÏĈGQÐ

Q¸	Ł Ä
-	-

ĊGÄê

-

15 LLDP

15.1 clear lldp statistics

#Ù8 LLDP ,X4ªAuÇ

clear lldp statistics [**interface** *interface-name*]

ÐAÈ	Ð	Ë
	interface-name	yÉ

ÏÞ,Õ5BÐ -

ÜÇÐ (Mã

Ï*Ô ô **interface** ÐÈ8ôy X LLDP 4ªAuÇ

Ï5B_Ð #Ù8y· 1 ,X LLDP 4ªAuÇÖ

```
5XLMLHFOHDUOOGSVWDWLVWLFVLQWHUIDFH*LJDELW(WKHUQHW
5XLMLHVKRØOGSVWDWLVWLFVLQWHUIDFH*LJDELW(WKHUQHW
/OGSVWDWLVWLFVLQIRUPDWLRQRISRUW*LJDELW(WKHUQHW@

7KHQXPEHURIOOGSIUDPHVWUDQVPLWWHG
7KHQXPEHURIIUDPHVGLVFDUGHG
7KHQXPEHURIHUURUIUDPHV
7KHQXPEHURIOOGSIUDPHVUHFHLYHG
7KHQXPEHURI7/9VGLVFDUGHG
7KHQXPEHURI7/9VXQUHFRJQL]HG
7KHQXPEHURIQHLJKERULQIRUPDWLRQDJHGRXW
```

ÏÎGQÞ

Q¸	Ë
-	-

ÐAê

Ð	ÆÄ
-	-

ß,Õ5BÐ 5,ØXÄ

ÙQþ <ÿÂG5Bã

ß*Ð LØ<Ô LLDP ÔÿÇ;X LLDP s6ÑÁ

Ù5B_Ð GKÁy;X LLDP s6ÑÖ

```
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJQROOGSHQDEOH
5XLMLHFRQILJLQWHUIDFHJLJDELWHWKHUQHW
5XLMLHFRQILJLIQROOGSHQDEOH
```

ÎÙGQÞ

Q¸	ÆÄ
show lldp status	**/** LLDP (ß

ÙÄê

-

15.3 lldp encapsulation snap

G5B LLDP y[,Xß'Õ*ü Ethernet II ,Xß'

lldp encapsulation snap

no lldp encapsulation snap

ÐAê

Ð	ÆÄ
-	-

ß,Õ5BÐ 5,Ø*ü Ethernet II ß'

ÙQþ yG5Bã

ß*Ð

LLDP

Ù5B_Ð G5B LLDP y[,Xß' SNAPÖ

```
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJLQWHUIDFHJLJDELWHWKHUQHW
5XLMLHFRQILJLIOOGSHQFDSVXODWLRQVQDS
```

ÎÙGQÞ

Q¸	ÆÄ
show lldp status	**/** LLDP ,X(ß

ÏGÄðø -

15.4 lldp error-detect

G5B LLDP JÀÃ#s6ßÃ#ÀÒÃX VLAN G5B"#ÃG#ÃG5B"
#ÑTU G5B"#ÆÇÃ#Ä LLDP "#JÁßA:Ç1u)ÍÄ

lldp error-detect

no lldp error-detect

ÐAðø

Ð	ÉÄ
-	-

Ï*Ô LLDP y[Time To Live TLV ,X=TTL ,Dhy[¥ÊÕÈÈh+1 ÁÈÈEA¼ TTL ,DÃ
{A'ÛÐFA'ÛX,#ÊÃ

ÏG5B_Đ G5B TTL ,D 5

```
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJOOGSKROGPXOWLSOLHU
```

ÏÎGQÞ

Q¸	Ê Ä
show lldp status	**/** LLDP ,X(Õ

ÏGÄè -

15.6 lldp management-address-tlv

G5B LLDP y[¥X1u)Ð*ü **no EÍMÑuÐ**

lldp management-address-tlv [*ip-address*]

no lldp management-address-tlv

ÐAè

Đ	Ê Ä
ip-address	LLDP y[¥X1u)Ú

Ï,ÕG5BĐ 5,Ð¥X1u)ýAÐÊ›Xê VLAN ,X IPv4 Ä

ÏQÞ yG5Bã

Ï*Ô 5,Ð¥ LLDP y[¥u)Ð¥X1u)ÚÃÐÊ›Xê VLAN ,X IPv4 È
pA¹ VLAN ÞG5B IPv4 Ê4ÁÞÐÊ›Xê VLANÞÈ IPv4 6Ä
VpÞ IPv4 È0ÃÐÊ›Xê VLAN ,X IPv6 Ä
VpÞ IPv6 È*A'ÛX MAC 01u)Ð

ÏG5B_Đ G5B LLDP y[¥X1u)Ú 192.168.1.1Ö

```
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJLQWHUIDFHJLJDELWHWKHUQHW
5XLMLHFRQILJLIOOGSPDQDJHPHQWDGGUHVVWOY
```

ÏÎGQÞ

Q¸	Ê Ä
show lldp local-information	**/** LLDP Ç

ÏGÄè -

15.7 lldp mode

G5B LLDP ,X0ÐÑ*ü **no EÍMGÍ** LLDP ,X0Ä

lldp mode {**rx** | **tx** | **txrx** }

no lldp mode

Ð	Ë Ä
rx	**ÿ Õ** LLDPDU
tx	**Ë ð** LLDPDU
txrx	**S Ë Ø e** LLDPDU

txrx

yG5Bã

GKý¸X LLDP 0 ÈÊá Ë Õ LLDP y[Ä

y· LLDP s6ÑÝX÷S6Ñ LLDP ÿ· LLDP ,X0 txÃx ê txrxÄ

G5By¡X LLDP 0 Ë ð LLDPDUÖ

```
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJLQWHUIDFHJLJDELWHWKHUQHW
5XLMLHFRQILJLIOOGSPRGHW[
```

Q¸	Ë Ä
show lldp status	**/** LLDP (Ø

-

15.8 lldp notification remote-change enable

G5B LLDP Trap s6Ñ*ü **no E MMG** LLDP Trap s6Ñ

ÏĈGQÞ	Q¸	Ł:Ä
	show lldp status	**/** LLDP ,X(ẽ

ĞGÄẽ -

15.9 lldp timer notification-interval

G5BɆÉÕ LLDP Trap ,XÊĖĖÈhẽ*ü **no EÝMẽ5ẽhÄ**

lldp timer notification-interval *seconds*

no lldp timer notification-interval

ĐAẽ

Đ

ÏQþÐ <G5Bã

ÏŠ*Ð ÆSÐ¸Ã¥0ãXNe4€K,XNe4ãÕ5B0ãKÊÆÈÃ

ÏG5B_Ð G5B LLDP 0ãKÊÆÈ 3 /Ï

```
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJOOGSWLPHUUHLQLWGHOD\
```

ÏÎGQÞÐ

Q¸	Æ£Ä
show lldp status	**/** LLDP ,X(õ

ÏGÄåÐ -

15.11 lldp timer tx-delay

G5B LLDP y[,X¥ÆÕÆÈ*ü **no EÝMMåÆÆÕÆÈÕ**

lldp timer tx-delay *seconds*

no lldp timer tx-delay

ÐAåÐ

Ð	Æ£Ä
seconds	LLDP y[,X¥ÆÕÆÈ5B8è 1-8192

Ï5,Õ5BÐ 2 /¦

ÏQþÐ <G5Bã

ÏŠ*Ð [¿¥ÆÏÏåA'ÊÕ LLDP y[ÆSÐ¿Ne4€K,XNe4

¥ÆÕ LLDP y[Æ5B LLDP y[,X¥ÆÕÆÈL$ LLDP y[,XNe4¥ÆÕ

ÏG5B_Ð G5B LLDP y[,X¥ÆÕÆÈ 3 /Ï

```
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJOOGSWLPHUW[GHOD\
```

ÏÎGQÞÐ

Q¸	Æ£Ä
show lldp status	**/** LLDP ,X(õ

ÏGÄåÐ -

15.12 lldp timer tx-interval

G5B LLDP y[,X¥ÆÕÆÈhÆ*ü **no EÝMMåÆÆÕÆÈh5Õ**

lldp timer tx-interval *seconds*

no lldp timer tx-interval

ÏÐÀð

Ð	Ë.Ä
seconds	LLDP y[,X¥ÈÕ¥ÈÈhÑ5B8¥È 5-32768

Ï5,Õ5BÐ 30 /¦

ÏQþÐ <G5Bã

Ï5*Ñ -

ÏG5B_Ð G5B LLDP y[,X¥ÈÕ¥ÈÈh 10 /Ï

```
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJOOGSWLPHUW[LQWHUYDO
```

ÏÎGQÞ

Q¸	Ë.Ä
show lldp status	***/*** LLDP ,X(Ñ

ÏGÄð -

15.13 lldp tlv-enable

G5BA¥È TLV 2O_Ä*ü **no EÝMÑX** TLV 2O_Ä

lldp tlv-enable { **basic-tlv** { **all** | **port-description** | **system-capability** | **system-description** | **system-name** } | **dot1-tlv** { **all** | **port-vlan-id** | **protocol-vlan-id** [*vlan-id*] | **vlan-name** [*vlan-id*] } | **dot3-tlv** { **all** | **link-aggregation** | **mac-physic** | **max-frame-size** | **power** } }

no lldp tlv-enable { **basic-tlv** { **all** | **port-description** | **system-capability** | **system-description** | **system-name** } **|** **dot1-tlv** { **all** | **port-vlan-id** **|** **protocol-vlan-id** | **vlan-name** } **|** **dot3-tlv** { **all** | **link-aggregation** | **mac-physic** | **max-frame-size** | **power** } }

ÏÐÀð

Ð	Ë.Ä
basic-tlv	Î1u)Ú TLV
port-description	¤/ Port Description TLV
system-capability	>≠ System Capabilities TLV
system-description	>≠ System Description TLV
system-name	>≠ System Name TLV
dot1-tlv	802.1 47ı,X TLV
port-vlan-id	>≠ Port VLAN ID TLV
protocol-vlan-id	¥ Port And Protocol VLAN ID TLV
vlan-id	ØÃ, VLAN ID
vlan-name	¥ VLAN Name TLV
vlan-id	Ø VLAN Ã,X VLAN ID
dot3-tlv	802.3 47ı,X TLV
link-aggregation	¥ Link Aggregation TLV

mac-physic	₧	MAC/PHY Configuratioin/Status TLV
max-frame-size	₧	Maximum Frame Size TLV
power	₧	Power Via MDI TLV

Ъ,Õ5BÐ 5,ÿ Location Ident ification TLV ęXŹO_,X TLV

ÜQþ yG5Bã

Ъ*ĝ G5BÎLu)Ú TLVÃ IEEE 802.1 47ת TLVÃ IEEE 802.3 47ת TLV Ž̧pû **all Ð**
A2OÃÝ TLVÄ

Ü5B_Đ G5B¥ IEEE 802.1 47ת,XÃÝ TLVÖ

```
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJLQWHUIDFHJLJDELWHWKHUQHW
5XLMLHFRQILJLIOOGSWOYHQDEOHGRWWOYDOO
```

Chassis ID type	Chassis ID 2O_ Chassis ID +‰
Chassis ID	MAC ≍/
System name	
System description	ECB
System capabilities supported	
System capabilities enabled	
Port ID type	0Ã ID 2O_
Port ID	0Ã ID
Port description	0
Management address subtype	1u)
Management address	1u)Ú
Interface numbering subtype	1u) 2O_
Interface number	1u) ID
Object identifier	1u)
Port VLAN ID	0Ã VLAN ID
Port and protocol VLAN ID	0 A, VLAN ID
PPVID Supported	0 A, VLAN
PPVID Enabled	0 A, VLAN
VLAN name f VLAN 1	VLAN 1 ,
Protocol Identity	#
Auto-negotiation supported	
Auto-negotiation enabled	
PMD auto-negotiation advertised	0
Operational MAU type	0
PoE support	POE
Port class	POE 2O_Ö PSE o+A’Û PD o+A’Û
PSE MDI power support	PSE o+
PSE MDI power enable	PSE o+
PSE pairs control ability	o+
PSE power pair	POE 0

PSE power class	0Ñ4{ÿ Class 0ëÿ4{ÿ 1 Class 1ëÿ4{ÿ 2 Class 2ëÿ4{ÿ 3 Class 3ëÿ4{ÿ 4 Class 4ëÿ4{ÿ 5
Link aggregation supported	ÕÒÑ.Ü
Link aggregation enabled	66ÕÒÑ.Ü
Aggregation port ID	JÒÑ.ÜÃX ID
Max mum frame Size	0ÃXKSz
Power-via-MDI device type	A'ÊO_Ð PSEÄ+A'Ê PDÄA'Ê
Power-via-MDI power source	+ë,X2O_
Power-via-MDI power priority	+ë,X4{
Power-via-MDI power value	0Ã+s)[
Model name	ëÄ

ÏÎGQÐ

Q¸	Ë.Ä
-	-

ÜGÄÐ -

15.15 show lldp neighbor-information

/FA'ÎX LLDP ÇÄ

show lldp neighbor-information [**brief** | **interface** *interface-name*]

ÐAÐ

Ð	Ë.Ä
interface-name	yÄ

Ü5,Õ5BÐ -

ÜÇÐ (Mã

Ü*Ð

- **brief ÐÐÐÄ**
- **interface ÐÕyË.Ä**

Ü55B_Ð /ÕÃXFA'ÎXÇÖ

5XLMLHVKRØOGSQHLJKERULQIRUPDWLRQ

+‰	AÈ
Neighbor index	F²é
Device type	FA'ÎX2O_
Update time	F£CÊ¥XÈ
Chassis ID type	Chassis ID ,X2O_
Chassis ID	*bÛÀ'Ê*ü MAC ≈/
System name	£Ä'ÎXéÄ
System description	A'ÊÐÆ@ ECÐ2Ï1Ç
System capabilities supported	2Ï#ÐXs6Ñ
System capabilities enabled	2Ï#Æ6ÑXs6Ñ
Management address subtype	1u)ÐO_
Management address	1u)Ú
Interface numbering subtype	1u)ý2O_
Interface number	1u)ý ID
Object identifier	1u)Ð5ÛÊú
Port ID type	0Ã ID 2O_
Port ID	0Ã ID
Port description	0ÃÆÄú
Port VLAN ID	0Ã VLAN ID
Port and protocol VLAN ID	0ÑA, VLAN ID
PPVID Supported	ÕÑA, VLAN
PPVID Enabled	s6ÕÑA, VLAN
VLAN name of VLAN 1	VLAN 1 ,XéÄ
Protocol Identity	#AÆÊú
Auto-negotiation supported	Õ#¼
Auto-negotiation enabled	s6Ñ#¼
PMD auto-negotiation advertised	0Ã¾¼E6Ñ
Operational MAU type	0Ã¾¼XE(Õ
PoE support	Õ POE
Link aggregation supported	ÕÒÕ.Ü
Link aggregation enabled	s6ÑÒÕ.Ü
Aggregation port ID	JÒÕ.ÜÑX ID
Maximum frame Size	0ÑXÐKSz

Power-via-MDI device type	A’2O_Ð PSEÄ+A’Ð PDÄA’Ð
Power-via-MDI power source	+6,X2O_
Power-via-MDI power priority	+6,X4{
Power-via-MDI power value	0Ã+s)[

ÏGQÞ

Q¸	ÆÄ
-	-

ÜGÄÐ -

15.16 show lldp statistics

/ LLDP ,X4ªAuÇÄ

show lldp statistics [**global** | **interface** *interface-name*]

ÜÐAÐ

Ð	ÆÄ
interface-name	yÐÄ

Ü5,Õ5BÐ -

ÜÇÐ (Mã

Ü5*Ð

- **global ÐÐ** LLDP 4ªAuÇÄ
- **interface ÐÐy¾X** LLDP 4ªAuÇÄ

ÜG5B_Ð /¸X LLDP 4ªAuÇÖ

```
5XLMLHVKRØOGSVWDWLVWLFV
OOGSVWDWLVWLFVJOREDO,QIRUPDWLRQ
1HLJKERULQIRUPDWLRQODVWFKDQJHGWLPHKRXUPLQXWHVHFRQG
7KHQXPEHURIQHLJKERULQIRUPDWLRQLQVHUWHG
7KHQXPEHURIQHLJKERULQIRUPDWLRQGHOHWHG
7KHQXPEHURIQHLJKERULQIRUPDWLRQGURSSHG
7KHQXPEHURIQHLJKERULQIRUPDWLRQDJHRXW



/OGSVWDWLVWLFVLQIRUPDWLRQRISRUW¾LJDELW(WKHUQHW@

7KHQXPEHURIOOGSIUDPHVWUDQVPLWWHG
7KHQXPEHURIIUDPHVGLVFDUGHG
```

7KHQXPEHURIHUURUIUDPHV
7KHQXPEHURIOOGSIUDPHVUHFHLYHG
7KHQXPEHURI7/9VGLVFDUGHG
7KHQXPEHURI7/9VXQUHFRJQL]HG
7KHQXPEHURIQHLJKERULQIRUPDWLRQDJHGRXW

show lldp statistics QQ¿EÄ

+‰	AÊ£
Neighbor information last change time	F¢¿ÐXÊÈ
The number of neighbor information inserted	F¢¿,Xrt Ð
The number of neighbor information deleted	F¢¿,Xû8 Ð
The number of neighbor information dropped	F¢¿,XëÐ
The number of neighbor information aged out	F¢¿,XCYÊÐ
The number of lldp frames transmitted	¥¢Õ¾X LLDP Þ
The number of frames discarded	ëX LLDP Þ
The number of error frames	JÂÃ¾X LLDP Þ
The number of lldp frames received	y,X LLDP Þ
The number of TLVs discarded	ëX LLDP TLV Þ
The number of TLVs unrecognized	ÃžX LLDP TLV Þ
The number of neighbor information aged out	F¢¿,XCYÊÐ

ÏĞGQÞ

Q¸	£Ä
-	-

ĞGÄê

-

15.17 show lldp status

/ LLDP ,X(ÕÄ

show lldp status [**interface** *interface-name*]

ĐAê

Đ	£Ä
interface-name	yéÄ

ï5,Õ5BÐ -

ÏQþÐ (Mã

ï5*Ð ÐÏ **interface Ð5ÐyX** LLDP (5Ä

ïG5B_Ð /ýÃX LLDP (5Ö

```
5XLMLHVKRØOGSVWDWXV
*OREDOVWDWXVRI//3(QDEOH
1HLJKERULQIRUPDWLRQODVWFKDQJHGWLPHKRXUPLQXWHVHFRQG
7UDQVPLWLQWHUYDOV
+ROGPXOWLSOLHU
5HLQLWGHODV
7UDQVPLWGHODV
1RWLILFDWLRQLQWHUYDOV

3RUW%LJDELW(WKHUQHW@

3RUWVWDWXVRI//3(QDEOH
3RUWVWDWH83
3RUWHQFDSXODWLRQ(WKHUQHW,,
2SHUDWLRQDOPRGH5[6G7[
1RWLILFDWLRQHQDEOH12
(UURUGHWHFWHQDEOH<(6
1XPEHURIQHLJKERUV
```

show lldp status QÐ£Ëð

+‰	Aè£
Global status of LLDP	<Ð6Ñ LLDP
Neighbor information last changed time	F¢Ð¥Ê£È
Transmit interval	LLDP y[,X¥£ÖÈh
Hold multiplier	TTL ,D
Reinit delay	0Ð£Ê£È
Transmit delay	LLDP y[¥£ÕÊ£È
Notification interval	LLDP Trap ¢,X¥£ÖÊ£Èh
Fast start counts	£¥£Õ LLDP y[,XÐ
Port status of LLDP	0Ð6Ñ LLDP
Port state	0ÃXJÒ(Ð P ê DOWN
Port encapsulation	LLDP y[,XÐ'

Operational mode	LLDP 0ã
Notification enable	0ß6Ñ LLDP Trap s6Ñ
Error detect enable	0ß6ÑÃ#s6Ñ
Number of neighbors	F•XÐ

ÏĬGQÐ

Q¸	Ł:Ä
-	-

ĠÄß

-

15.18 show lldp tlv-config

/0ß LLDP TLV G5BÇÄ

show lldp tlv-config [**interface** *interface-name*]

ÐAß

Ð	Ł:Ä
interface-name	yßÄ

Ь,Ø5BÐ

-

ÜQÐ

(Mã

Ь*Ð

ù **interface ÐßyX** LLDP TLV G5BÇÄ

Ġ5B_Ð

/y· 1 ,X TLV ÇÖ

```
5XLMLHVKRØOGSWOYFRQILJLQWHUIDFH*LJDELW(WKHUQHW
//3WOYFRQILJRISRUW*LJDELW(WKHUQHW@

1ø(67$86(')$/7

%DVLFRSWLRQDO7/9
3RUWHVFULSWLRQ7/9<(6<(6
6ÝVWHP1DPH7/9<(6<(6
6ÝVWHPHVFULSWLRQ7/9<(6<(6
6ÝVWHPØSDELOLWLHV7/9<(6<(6
0DQDJHPHQW$GGUHVV7/9<(6<(6

,(((H[WHQG7/9
3RUW9/$,7/9<(6<(6
3RUW$QG3URWRFRO9/$,7/9<(6<(6
9/$1DPH7/9<(6<(6
```

,(((H[WHQG7/9
08KVLF7/9<(6<(6
3RUUYLD0',7/9<(6<(6
/LQN$JUHJDWLRQ7/9<(6<(6
0D[LPXP)UDPH6L]H7/9<(6<(6

ÏĜQÞ	Q¸	Ł:Ä

16 QinQ

16.1 dot1q new-outer-vlan vid translate old-outer-vlan vid inner-vlan v-list

ü access trunk hybrid uplink 0 Tag ,X VID + ê Tag ,X VID vid ,X1*+9≈

dot1q new-outer-vlan *vid* **translate old-outer-vlan** *vid* **inner-vlan** *v-list*

no dot1q new-outer-vlan *vid* **translate old-outer-vlan** *vid* **inner-vlan** *v-list*

	v_list	Eg9y[vid
	vid	tag ,X vid
	no	#1*+9≈A’5B

1*+9≈0N

yã

-

Tag ,X vid 2001-3000 Tag ,X vid 1888 vid 3888

```
5XLMLHFRQILJYODQ
5XLMLHFRQILJLQWHUIDFHJLJDELW(WKHUQHW
5XLMLHFRQILJLIVZWFKSRUWPRGHWUXQN
5XLMLHFRQILJLIGRWTQHZXWHUYODQWUDQVODWHROGRXWHUYODQIQQHUYODQ

5XLMLHFRQILJLIHQG
```

	show translation-table [**interface** *intf-id*]	-

-

16.2 dot1q outer-vid vid register inner-vid v-list

ü tunnel 0 vid #1*+9≈

dot1q outer-vid *vid* **register inner-vid** *v_list*

no dot1q outer-vid *vid* **register inner-vid** *v_list*

ÐAê

Ð	Ä
v_list	YF¼vlan id ë
vid	ê¼ vlan id
no	#1*+9»A'5B

Ь,Õ5BÐ -

Qþ yã

Ь*Ð -

G5B_Ð M6_A'5BEg9y[tag ,X vid 4-22 ê tag ,X vid 3

```
UXLMLHFRQILJXUHWHUPLQDO
UXLMLHFRQILJLQWHUIDFHJLJDELW(WKHUQHW
UXLMLHFRQILJLIVZWFKSRUWPRGHGRWTWXQQHO
UXLMLHFRQILJLIGRWTRXWHUYLGUHJLVWHULQQHUYLG
UXLMLHFRQILJLIHQG
```

ÎGQÞ

Q¸	Ä
show registration-table [**interface** *intf-id*]	-

GÄê -

16.3 dot1q relay-vid vid translate local-vid v-list

ü access ètunk èybrid èplink 0Ê'5BÎ#A,Xê¼ vid Â*+9»

dot1q relay-vid *vid* **translate local-vid** *v-list*

no dot1q relay-vid *vid* **translate local-vid** *v-list*

ÐAê

Ð	Ä
v_list	Eg9y[ê¼ vid ë
vid	tag ,X vid
no	

UXLMLHFRQILJLIGRWTUHODVLGWUDQVODWHORFDOYLG
UXLMLHFRQILJLIHQG

ÏĈGQÞ	Q¸	Ë Ä
	show translation-table [**interface** *intf-id*]	-

ĭGÄð -

16.7 l2protocol-tunnel

G5B dot1q-tunnel 0ÿÃ#Ay[

l2protocol-tunnel {**stp|gvrp**}

no l2protocol-tunnel {**stp|gvrp**}

ĭÐAð

Ð	ĿÄ
stp	y stp y[
gvrp	y gvrp y[
no	#yy[A'5B

ĭ,Õ5BÐ -

ĭQþ <ã

ĭ*Ô -

ĭG5B_Ð ¥M6,X_ÔA, gvrp ` stp ,Xys6Ñ

```
UXLMLHFRQILJXUHWHUPLQDO
UXLMLHFRQILJOSURWRFROWXQQHOVWS
UXLMLHFRQILJOSURWRFROWXQQHOJYUS
UXLMLHFRQILJHQG
```

ÏĬGQÐ

Q¸	ĿÄ
show l2protocol-tunnel {**gvrp|stp**}	-

ĭGÄð -

16.8 l2protocol-tunnel *proto-type* enable

G5B0Ã6ÑAy[Eã6Ñ

l2protocol-tunnel { **stp|gvrp** } **enable**

no l2protocol-tunnel { **stp|gvrp** } **enable**

ĭÐAð

Ð	ĿÄ
stp	**Eã** stp y[
gvrp	**Eã** gvrp y[
no	**Eã[**

ĭ,Õ5BÐ -

ÏQþÐ yã

ÏS*ûÐ -

ÏG5B_Ð MM6,X_ßB6ÑAEã6Ñ

```
UXLMLHFRQILJXUHWHUPLQDO
UXLMLHFRQILJLQWHUIDFHID
UXLMLHFRQILJLIOSURWRFROWXQQHOJYUSHQDEOH
UXLMLHFRQILJLIHQG
```

ÏÎGQÐ

Q¸	Ë.Ä
show l2protocol-tunnel { **gvrp|stp** }	-

ÏGÄâê -

16.9 l2protocol-tunnel *proto-type* tunnel-dmac *mac-address*

G5B,h#A,XEã

l2protocol-tunnel { **stp|gvrp** } **tunnel-dmac** *mac-address*

no l2protocol-tunnel { **stp|gvrp** } **tunnel-dmac** *mac-address*

ÐAâê

Ð	Ë.Ä
stp	G5B stp ,XEã
gvrp	G5B gvrp ,XEã
no	Ëêã,Õ 5,Õ*ïXEêÐ 8¹ OUI 2bÊ 001aa9Ã 00d0f8Ã 14144b 1Ê,ÊâX ¥8V 01d0f8Ê 3 +8V (stp:000005,gvrp:000006)Ä 8JW OUÊ,Êê OUI 1ê8V,XÐ bit 5B1tÊ 3 +8V(stp:000005,gvrp:000006) ,X4ÐEã È_V MAC 00CCCC000001È stp y[S*ïXEã 01CCCC00005Ä

Ï,Õ5BÐ -

ÏQþÐ <ã

ÏS*ûÐ -

ÏG5B_Ð MM6,X_ßB6ÑAEã6Ñ

```
UXLMLHFRQILJXUHWHUPLQDO
UXLMLHFRQILJLIOSURWRFROWXQQHOJYUSWXQQHOGPDF$
UXLMLHFRQILJLIHQG
```

ÏĈGQÐ

ъ,Õ5BÐ -

ÜQÞ (Mã

Ъ*Ô UXLMLHVKRZGRWTWXQQHO
3RUWVRWTWXQQHO

*L (QDEOH

ÏĈGQÞ

Q¸	ÆÄ
-	-

ÜÄà -

16.12 show frame-tag tpid

/y· tpid ,XG5B

show frame-tag tpid [**interface** *intf-id*]

ÜÐAà

Ð	ÆÄ
intf-id	(Mn,Xy·

ъ,Õ5BÐ Â tpid

ÜQÞ (Mã

Ъ*Ô -

ÜG5B_Ð UXLMLHVKRZUDPHWDJWSLG
3RUWVWSLG

*L [

ÏĈGQÞ

Q¸	ÆÄ
-	-

ÜÄà -

16.13 show inner-priority-trust

/¼{G5B

show inner-priority-trust

ÏDAß

Ð	ÆÄ
-	-

Ï5,Õ5BÐ á

ÏQ5Ð (Mã

ÏS*Ô Ð -

ÏG5B_Ð

```
UXLMLHVKRŽQQHUSULRULWWUXVW
3RUWV    LQQHUSULRULWWUXVW

*L    HQDEOH
```

ÏÎGQÐ

Q¸	ÆÄ
-	-

ÏGÄß - -

16.14 show interface dot1q-tunnel

/ dot1q-tunnel G5B

show interface [*intf-id*] **dot1q-tunnel**

ÏDAß

Ð	ÆÄ
intf-id	(Mn,Xy·

Ï5,Õ5BÐ -

ÏQ5Ð (Mã

ÏS*Ô Ð -

ÏG5B_Ð

```
UXLMLHVKRŽQWHUIDFHGRWTWXQQHO
,QWHUIDFH*L
1DWLYHYODQ
ŠORŽGYODQOLVWÈ
7DJJHGYODQOLVWÈ
```

ÏÎGQÞ

Q¸	Ë Ä
-	-

ËGÄà

-

16.15 show interface intf-name remark

/¼{ØXG5B

show interface intf-name remark

ËÐAà

Ð	Ë Ä
-	-

Ëþ,Õ5BÐ

ø

ËQþ

(Mã

ËS*Ô

-

ËG5B_Ð

```
5XLMLHVKRZQWHUIDFHLQWIQDPHUHPDUN
3RUWV7SH)URPYDOXH7RYDOXH

*L&V7R&V
```

ÏÎGQÞ

Q¸	Ë Ä
-	-

ËGÄà

-

16.16 show interface mac-address-mapping x

/ MAC ê5B

show interface mac-address-mapping *x*

ËÐAà

Ð	Ë Ä
-	-

Ëþ,Õ5BÐ

á

ËQþ

(Mã

ËS*Ô

-

stp	/Eã stp y[G5B

ß,Õ5BÐ GKÁ

ÜQþ (Mã

Ü*ð

ÜG5B_Ð UXLMLHVKRØSURWRFROWXQQHOVWS
HVWLQDWLRQPDF GI
/SURWRFROWXQQHO 6WS(QDEOH
UXLMLHVKRØSURWRFROWXQQHOJYUS
HVWLQDWLRQPDF GI
/SURWRFROWXQQHO JYUSLVDEOH

ÏÎGQÞ

Q¸	Ë Ä
-	-

ÜGÄð

-

16.19 show registration-table

/ÎÞ#A,X dot1q-tunnel 0Ã vid #Ï1*+9≈

show registration-table [**interface** *intf-id*]

ÐAð

Ð	Ë Ä
intf-id	ÎÞ,Xy·

ß,Õ5BÐ 1*+9≈0N

ÜQþ (Mã

Ü*ð -

ÜG5B_Ð UXLMLHVKRØHJLVWUDWLRQWDEOH
3RUWV7ŠH2XWHU9,¦QQHU9,ŌLVW

*LŒGRXWHU

ÏÎGQÞ

Q¸	Ë Ä
-	-

ÜGÄð -

16.20 show traffic-redirect

/Ĵb#,X vid ßëï1*+9≈

show traffic-redirect [**interface** *intf-id*]

ËDAßè

Ð	ÆÄ
intf-id	*bÛX·*

Ëƃ,Õ5BÐ 1*+9≈0N

ËQþ (Mã

ËƃÛ*ĐÛ -

ËG5B_Ð

```
UXLMLHVKRWVUDIILFUHGLUHFW
3RUWV  7SH9,0DWFKILOWHU

*L0RGXWHU
*L0RGXWHU
*L0RGXWHU
*L0RGLQQHULQQHUWR
*L0RGLQQHU
*L1HVWHGYLGQHVW
```

ÏĈGQÞ

Q¸	ÆÄ
-	-

ËGÄßè -

16.21 show translation-table

/Ĵb#A,X access,trunk,hybrid 0Ã vid Âë*+9≈

show translation-table [**interface** *intf-id*]

ËDAßè

Ð	ÆÄ
intf-id	*ûl,Xy·*

Ëƃ,Õ5BÐ 1*+9≈0N

ËQþ (Mã

ËƃÛ*ĐÛ -

Ï5B_Ð

```
UXLMLHVKRWVUDQVODWLRQWDEOH
3RUWV7\SH5HOD\,2OGORFDO/RFDO2QQHU9,OLVW

*L,QQHU8,1$
*L/RFDO69,1$
*L,Q2XW
```

ÏÎGQÞ

Q¸	Ë Ä
-	-

ÏGÄÐ -

16.22 switchport dot1q-tunnel allowed vlan

A'5B dot1q-tunnel ,XAÐË vlan

switchport dot1q-tunnel allowed vlan [**add**] {**tagged**|**untagged**} *v_list*

switchport dot1q-tunnel allowed vlan remove *v_list*

no switchport dot1q-tunnel allowed vlan

ÐAÐ

Ð	Ë Ä
tagged	ú tag
untagged	á tag
v_list	vlan id ë
no	$T

16.23 switchport dot1q-tunnel native vlan

A'5B dot1q-tunnel ,XTAx vlan id

switchport dot1q-tunnel native vlan *vid*

no switchport dot1q-tunnel native vlan

ËDAê

Ð	ÉÄ
vid	A'5BTAx,X vlan id
no	A'5BTAx vlan 1

Ï,Õ5BÐ A'5BTAx vlan 1

ÜQê yã

ÜS*Ô -

ÜG5B_Ð ÑM6_A'5B dot1q-tunnel ;XTAx vid 8

```
UXLMLHFRQILJLQWHUIDFHJLJDELW(WKHUQHW
UXLMLHFRQILJLIVZWFKSRUWGRWTWXQQHOQDWLYHYODQ
UXLMLHFRQILJHQG
```

ÌÎGQÐ

Q¸	ÉÄ
show interface dot1q-tunnel	-

ÜGÄê -

16.24 switchport mode dot1q-tunnel

G5By· dot1q-tunnel ·

switchport mode dot1q-tunnel

no switchport mode

ËDAê

Ð	ÉÄ
no	ô8,h,X dot1q-tunnel G5B

Ï,Õ5BÐ M2dot1q-tunnel ·

ÜQê yã

ÜS*Ô -

ÜG5B_Ð ÑM6_A'5B0Ã dot1q-tunnel ·

```
UXLMLHFRQILJLIVƵWFKSRUWPRGHGRWTWXQQHO
UXLMLHFRQILJHQG
```

ÏĨGQÞ

Q¸	ƵÄ
show vlan	-

Ъ‚Õ5BÐ 1*+9≈0N

ЏQ Ð yã

Ъ*Ô -

Ï5B_Ð ЍM6_Ä’5BÝ Ð 1.1.1.3 Eg9y[#ï vid 9

```
UXLMLHFRQILJXUHWHUPLQDO
UXLMLHFRQILJLSDFFHVVOLVWVWDQGDUG
UXLMLHFRQILJDFOVWGSHUPLWKRVW
UXLMLHFRQILJDFOVWGH[LW
UXLMLHFRQILJLQWHUIDFHJLJDELW(WKHUQHW
UXLMLHFRQILJLIVƵWFKSRUWPRGHGRWTWXQQHO
UXLMLHFRQILJLIWUDIILFUHGLUHFWDFFHVVJURXSQHVWHGYODQLQ
UXLMLHFRQILJLIHQG
```

ÏĈGQÐ

Q¸	Ð‚Ä
show traffic-redirect	-

ЏGÄÀ

-

16.27 traffic-redirect access-group acl outer-vlan

Í access,trunk,hybrid, uplink 0Ð‚g9y[Ä’5BÎ#,XÐ¼ vid Â*+9

traffic-redirect access-group *acl* **outer-vlan** *vid* **in**

no traffic-redirect access-group *acl* **outer-vlan**

ÐAÀ

Ð	Ð‚Ä
acl	*ÐG#,X acl
vd	ÂXÐ¼ vid
no	#Î#,XÐ¼ vid Â*+9

Ъ‚Õ5BÐ 1*+9≈0N

ЏQ Ð yã

Ъ*Ô -

Ï5B_Ð ЍM6_Ä’5BÝ Ð 1.1.1.1 Eg9y[,XÐ¼ vid Â 3

```
UXLMLHFRQILJXUHWHUPLQDO
UXLMLHFRQILJLSDFFHVVOLVWVWDQGDUG
UXLMLHFRQILJDFOVWGSHUPLWKRVW
UXLMLHFRQILJDFOVWGH[LW
```

```
UXLMLHFRQILJLQWHUIDFHJLJDELW(WKHUQHW
UXLMLHFRQILJLIVƵWFKSRUWPRGHWUXQN
UXLMLHFRQILJLIWUDIILFUHGLUHFWDFFHVVJURXSRXWHUYODQLQ
UXLMLHFRQILJLIHQG
```

ÏĜGQÞ

Q¸	Ð£Ä
show traffic-redirect	-

16.29 vlan

ÐAð

Ъ,ÕЭ5BÐ

ÜÇð

Ъ*Ô

ÜG5B_Ð

1 IP /

1.1 arp

S*ARP 4<rt>X IP ` MAC no 6
M-Õ MAC

arp [**vrf** *name*] *ip-address MAC-address type*

s6	**arp anti-ip-attack**	*num*	**no**
3			

```
5XLMLHFRQILJXUHWHUIDFHYODQ
5XLMLHFRQILJXUHIDUSUDWLRXVVHQLQWHUYDO
_ 2Ö!5BÈ!6nß SVI 1 ¥ÉÕ ARP AË
5XLMLHFRQILJXUHWHUIDFHYODQ
5XLMLHFRQILJXUHQDUSUDWLRXVVHQ
```

ÏÎGÐ	Ç	£Ä
	-	-

ÜGÄß -

1.4 arp retry interval

```
S*ÅÆ5B¥ÉÕ arp AÿÇ,XNe)[Ès?dÞ IP È4ÉÕ 2 õ ARP AË
,XÊÈÈnß*ü8ÇX no 6ÆÅxÞ 1 õ ARP AÆ
arp retry interval seconds
no arp retry interval
```

ÐAß	Ð	£Ä

0.6 ref03seconds m7(no a)3600AÆ)

no arp retry times

		ARP
	number	

ÏÎGÐ		
	Ò	Ë Ä
	clear arp-cache	**è 8** ARP 4 ¢<
	show interface	**/y B 4 Au C**

ÏGÄè	-

1.7 arp trusted

S*AÐ'5BÃ ARP ><NM,XÐÄÇX no 6 TAxÄ

arp trusted *number*

no arp trusted

ÐAè		
	Ð	Ë Ä
	number	Ã5 ARP ><NM,XÐ

ï,Õ!5BÐ	¢ ,õ

Ð	<G!5Bã

S*Ð	?US!8 ÇÐ ' ARP s6 ARP ><NMJV><NME Y, Ð ¢ <NM
	4* Ë Ã Ç ARP ><NM0NK Ð Ý Ô'5B è UA'5Bk Ð

G!5B_Ð	G!5B È'5B Ð'5B 1000 ARP
	DUSWUXVWHG

ÏGÐ		
	Ò	Ë Ä
	service trustedarp	***** ARP s6Ñ

ÏGÄè	-

1.8 arp trusted aging

S*AÐ'5BÃ ARP Ô Ç no 6 TAxÄ

arp trusted aging

no arp trusted aging

ÐAè		
	Ð	Ë Ä
	-	-

ï,Õ!5BÐ	GSN ARP TAxÃÕ

Ð	<G!5Bã

Ï*Ô S*ÄÃÑ ARP ÕÕÕÐÈÕ ARP 5ÐÄÃÕÕÈEyã

ß **arp timeout Ñ5BÄ**

ÏG!5B_Ð -

ÏÎGÑ	Ñ	ÈÄ
	service trustedarp	***ÏÃ** ARP s6Ñ

ÏGÄè -

1.9 arp trusted user-vlan

S*ÄÃÑ'5BÃ ARP ><NMÊ> VLAN E@6ÄÑX no 6è8><NMÄ

arp trusted user-vlan *vid1* **translated-vlan** *vid2*

no arp trusted user-vlan *vid1*

ÐAè

Ð	È
vid1	*á<A5Ã* VID
vid2	*E@6Ã* VID

Ï,Ñ!5BÐ 5,ÕÕ> VLAN E@6

Ñ <G!5Bã

Ï*Ô ?US!8ÑÒ]ÃÃ ARP s6Ãk<ÃX VLAN ÃÃ ARP *ÐX VLAN

ã.ÐUG!5B!8Ñ

ÏG!5B_Ð G!5Bã<ÃX VLAN 3ÃÃ ARP rL*ÐX VLAN 5 Ê!5BVÑ

DUSWUXVWHGXVHUYODQUDQODWHGYODQ

ÏÎGÑ	Ñ	ÈÄ
	service trustedarp	***ÏÃ** ARP s6Ñ

ÏGÄÈ -

1.10 arp unresolve

S*ÄÃÑ!5B ARP ><NM3d><NM,XÐÄÑX no 6ÃÃÄx 8192Ä

arp unresolve *number*

no arp unresolve

ÐAÈ	Ð	È

number	ø ARP ><NM,XÐ 1-8192 >	ÄAx 8192

ĕ,Õ!5BĐ ARP 4ę<Đ 8192 Ðd><NM

ę Đ <G!5Bã

Ĕ*Đ ¥ ARP 4ç><ĴĢĐd><NMĐ8ĢĐd><NM,XÐÄ

Ğ!5B_Đ Ğ!5BÈ'5B,XÐd><NM,XÐ 500
DUSXQHVROYH

ĬĞĘĐ

Ę	ĘÄ
-	-

ĞÄè

1.11 clear arp-cache

?U¢ ARP 4ę<ĝ8|Õ ARP Đ,ĘMĘ clear arp-cache

clear arp-cache [**vrf** *vrf_name* | **trusted**] [*ip* [*mask*]] | **interface** *interface-name*]

ĐAè

Đ	ĘÄ
trusted	ĐÃ ARP ,X><NM
vrf *vrf_name*	ĝ8Ĝ VRF r_,X|Õ ARP ><NM
ip	IP ĐĞ#ÙĝĜ IP ,X ARP ><NMÈpĜ **trusted G** è8Ã ARP ><NMÐÕ ARP ><NM
mask	mask $¼ÕĞ#Ù8$%X ARP ><NMÈ6,X IP ™ NO$Ð Vpĝ trusted GK+ĝ8$%Ã ARP ><NMÈ ĝ8$%X|Õ ARP ><NMÄ
interface *interface-name*	#Ù8ĝy;X|Õ ARP ><NM

ĕ,Õ!5BĐ -

ę Đ (M*ã

Ĕ*Đ ÑĄĘ ARP 4ç><

NFPP(Network Foundation Protection Policy ,) mac (IP) ARP clear arp 1s ARP

Ğ!5B_Đ _ 1ĞĐ8Ý ARP |Đ4ę<Ö

FOHDUDUSFDFKH

_ 2Ö8|Õ ARP ><NM1.1.1.1

FOHDUDUSFDFKH

_ 3Ö8y· SVI1 ÞX|Õ ARP ><NM

FOHDUDUSFDFKHLQVHUIDFH9ODQ

ÏGÐ	Ò	Ë Ä
	arp	ü ARP ><rtM-Ø Ä

ÜGÄð -

1.12 clear ip route

?UHÞ8 IP CÃ><6Ù IP CÃ><,XÞ CÃAÞ Ø M*ß **clear ip route Ò**

clear ip route { * | *network* [*netmask*] }

ÐAð

ip-address	32 þ(M! IP è ! Ê ã</ÆK È hÊ
network-mask	32 þ(M!5¼ -Ê1” ></}-Ê” ></!Æ 8 !Ê È Ê ã</ÆK È hÊ
mask-length	$¼Ê
ip-address/mask-length	IP $¼Ê Sz
secondary	ÆÊ X IP Ä

ß,Ê!5BÐ y!Ê!5B IP

Ðþ yG!5Bã

Ê*Ð ÞÊ!5BZ IP ÞÆÕ IP DByÆG!5BZ IP ÈÀyAÈ
IP #AÄ
5¼ -ÊÞ 32 !!(M,XDÆA¹ IP ,XÞ(M5¼ Æ¼ 1Õ
,X!(Mh,X IP !(M!5¼ Æ¼ ,X!(Mh,X IP !(M!F¼
Ø A 2O5¼ h,X5¼ -Ê 55.0.0.0 Æ5¼ -Õ5¼ È ¼
ÞÀX0(M!305¼ Æ¼ È5¼ XDGÈÞX
5¼ -Ê¼Õ
RGOS ECÞG!5Bþ IP Þ IP È<F½ IP Ä IP
,XG!5B)Ø,ÆÊc!5BÆ!5BZ IP 6Ñ!5B õ IP Ä IP
â IP ž IP K2b5¼ 6¼ Â’È*ú IP È
¼A5×¼ Ê IP Ö
5¼ ÚX5½ÞUÞ C 2O5¼ Æ! 254 Ä
5Œ›E› 254 Þ C 2O5¼ 6!ÞUÚ!Þ C 2O5¼ Æ A’ÛÊUE²
yÞ5¼ ÈÊUG!5Bþ IP Ä

AÞX5¼ 1¸X9y5¼ Æ ¼ È ,XS*ÆA5¼
ç{b IP ,XCÃ5¼ 6!Þ ÆÑ!5BÞ IP Ä

Þ5¼ XÞ¼ Þ¼ h/Ê 4Þ h/5¼ X È G!5B õ IP
,XÆh/•X5¼ yCK9Þ Æ ÃÑ’ÛXÞ Ä

Ê!5B_Ð ß!5BZ· IP 10.10.10.1¼ -Õ 255.255.255.0Ä
LSDGGUHVV
ê
LSDGGUHVV
ê
LSDGGUHVV
ß!5BÆ,6‰ 10.10.10.254Ä
LSDGGUHVVDWHZ\

ÎGÞ

Ç	È Ä

1.14 ip broadcast-address

?Unp XS G!5B **ip broadcast-address** no 6 S•

G!5B

ip broadcast-address *ip-address*

no ip broadcast-address

Ð	Ä
ip-address	IP 5 XS

5,Õ IP S• 255.255.255.255

aÐ¾

/ÄŠy[Ä“Ay[,X8Vê¤Ä
ùäê¤Ê?XA'ý IP nŠy[ÈE@¥y[ÕŠy[ÄŠ
y[E',È¬A5%XA'ÊnŠy[E@6#ÚSy[ÊÙÊ IP <
1 ,XSy[ÊŠÊÈÕ¤Ä
4ÊÙXyènŠ(=)ÓE@6,Xs6ÑA¹yÊ@¥È5%Xn
ŠÄ¢ê¤ÊXnŠy[,XêgÈ,WnŠy[,X!7
E@Ä
ÿèÊÊEnA“Kê<9{E@¥nŠÄZ“Kê<ÊÙ“Kê
><n,XDBÙÈ> nŠ(=)Ó•XE@6Ä
VpÿÐ!5BZ **no ip directed-broadcast** ÈGOS ÿÙX,È5%XnŠy[Ä

Ë!5B_Ð Ê!5B_Ê'Û FastEthernet 0/1 0ÃŠ•XE@Ä

```
LQWHUIDFHIDVW(WKHUQHW
LSGLUHFWHGEURDGFDVW
```

ÏÊÐ

Ð	Ê
-	-

ËÄê

-

1.16 ip mask-reply

?UA}RGOS EC6ÑÙ ICMP }-ÕËÎhÈÕ ICMP h1(y[ÈÿG!5BÐ **ip mask-replyÄÐ** no 6ÊKÉÕ ICMP }-Õy[Ä

```
ip mask-reply
no ip mask-reply
```

ÐÄê

Ð	Ê
-	-

Ë,Ø!5BÐ 5,ØKÉÕ ICMP }-Õy[

Ê

yG!5Bã

Ë*Ê 5%A'ÊÙU-Ff6(5Ê%X$1%ÊÄ¢È%A'Û ÉÕ ICMP }-Õ
AÉÈCÿ ICMP }-ÕÉÈC,X5%A'ÊÙÕ1(#ÈÄ

Ë!5B_Ð Ê!5B_Ê'ÛX FastEthernet 0/1 yÚ ICMP ,X}-ÕÊ[

```
LQWHUIDFHIDVW(WKHUQHW
LSPDVNUHSO\
```

ÏÊÐ

Ð	Ê

ËGÄß -

1.17 ip mtu

?UA'5BIP ß)Ä MTU ßyG!5BQ **ip mtuÄß** no 6ßß,Õ!5BÄ

ip mtu *bytes*

no ip mtu

ËÐÄß

Ð	Ä
bytes	IP ß)È8V)!ßÈ 68~1500Ä

ß,Õ!5BÐ 5,ßQ mtu G!5B,X,ßÄ

ßÐ yG!5Bã

Ës*ß Vpß IP y[CYE› IP MTU ,Xßè RGOS ECß[E>ßß)5%A'Ð

ß6(y¡X IP MTU ß?UÕÃ

Vp*ýG!5BQ mtu ý¡Xß)E> A'5BÈ IP MTU ,X7ßý¡X MTU ß

7ßpA‹Z IP MTU ,Xý¡X MTU ß³Ä

ËG!5B_Ð G!5B_ß FastEthernet 0/1 y¡X IP MTU A' 512 +8V

```
LQWHUIDFHIDVW(WKHUQHW
LSPWX
```

ÏÎGÐ

Q	Ä
mtu	**A5Byß)Ä**

ËGÄß -

1.18 ip proxy-arp

?Uý‹Ú ARP s6ß **ip proxy-arp ßß** no 6ßKÁÚ ARP s 6Ñ

ip proxy-arp

no ip proxy-arp

ËÐÄß

Ð	Ä
-	-

ß,Õ!5BÐ GKÁÚ ARP

ßÐ yG!5Bã

Ï*Ð A'ÛX)Ú ARP s6ÑuÝÃ¸,XÈkV5%8% IP ,X MAC!ÄA'
ÿÔ ARP AË ARP AËÕ¸X IP ÀË¸X IP ÀbÔ%ÈA'Ê'
AË IP ,XCÃÈ'ØÕ ARP hÈ,X MAC A'ÛØ¸X5% MAC Ä
Ð¾ÚÚ ARP ,Xs6Ñ

ÏG!5B_Ð G!5BÈÊ5% FastEthernet 0/1 *ÚÚ ARP s6Ñ

1.20 ip source-route

?UAŒ RGOS ECÞ CÃ Ç,X IP y[G!5BQ **ip source-route** no 6
6 CÃÇ,X 6Ñ

ip source-route

no ip source-route

Ð	Ä
-	-

5,Ù

<G!5Bã

RGOS Õ IP CÃ'ý DBÊ IP y,X CÃ CÃ)CÃ
1E ME> ”È E M RFC 791 4 X p”#AÐB Ì
;> h,X|0¥p”#,XE MÈÐB Õ ICMP ÐK #C Ð
BÑ
RGOS EC 5, IP CÃ(M

G!5B_ G!5B_ KÁ IP CÃ(MÖ
LSVRXUFHURXWH

Ò	Ä
-	-

-

1.21 ip unnumbered

A G!5B4 G!5B4 IP #A ¥ IP DBÑ no 6 G!5BÄ

ip unnumbered *interface-type interface-number*

no ip unnumbered

ÏĈGĘÐ	Ǫ	ƐÄ
	-	-

ĠÄẽ -

1.23

mask	**/** IP $‰X ARP ><NM,Vpû trusted GK+Ã Ï ARP ><NMÈM2Ã ARP ><NMÄ
static	**/Mõ** arp ><NMÄ
complete	**/Ø)Õ** arp ><NMÄ
incomplete	**/é)Õ** arp ><NMÄ
mac-address	**/û** mac ,X ARP ><NMÄ

Ï5,Õ!5BÐ -

Ã(M*ã

Ï*ûÐ -

Ï5B_Ð _ 1Ö show arp Egî4ßÖ

```
5XLMLHVKRZUS
7RWDO1XPEHUVRIS
3URWRFROGGUHVVSHPLQDUGZUH7SH,QWHUIDFH
,QWHUQHWDDIDUSD9/$
,QWHUQHWDDEGDUSD9/$
,QWHUQHWDWEEHDUSD9/$
,QWHUQHWDWEEDUSD9/$
,QWHUQHWDWDDEDUSD9/$
,QWHUQHWDWDDEEDUSD9/$
,QWHUQHWDWGIEDUSD9/$
```

ARP 4ç<Ø1‰ÆÄÖ

+!‰	Aè
Protocol	5¼X#Aè+!‰ InternetÄ
Address	â@È,X IP Ä
Age (min)	ARP 4ç),,ïXÈÈAuXp,XÈÙ M-Ï5B,XÈ+!%á“”></Ä
Hardware	â IP Í,X.@È
Type	.@ÈO_è% ARPAÄ
Interface	â IP G6(,XyÄ

_ 2Ö **show arp** 192.168.195.68 ,XEgî4ßÖ

```
5XLMLHVKRZUS
3URWRFROGGUHVVSHPLQDUGZUH7SH,QWHUIDFH
,QWHUQHWDDIDUSD9/$
```

_ 3Ö **show arp** 192.168.195.0 255.255.255.0 ,XEgî4ßÖ

```
5XLMLHVKRZUS
3URWRFROGGUHVVSHPLQDUGZUH7SH,QWHUIDFH
```

show arp detail [*interface-type interface-number*| *ip* [*mask*] | *mac-address* | **static** | **complete** | **incomplete**]

ÏDAÐ

Ð	Ë.Ä
interface-type interface-number	/ÞÝÑÕÙÃX ARP
ip	ip ÐÕÙ ip ,X ARP ><NM
ip mask	/ ip mask ÞX5%‰ ARP ><NM
mac-address	/ÞÙ mac ,X ARP ><NM
static	/Ý-Õ arp ><NM
complete	/ÆÐd,X|Õ arp ><NM
incomplete	/Þd,X|Õ arp ><NM

Ï5,Õ!5BÐ -

Ïß (M*ã

Ï*ÐÙ *ÙÐ ARP ,XA4ÞÈÈV ARP ,X2O_ÞÕÙ-ÞÐ0Ë
Ë*l8Q

Ï!5B_Ð ß **show arp detail EgÂÞÖ**

```
5XLMLHVKRDUSGHWDLO
,3GUHVV0GUHVV7SHPLQWHUIDFH3RUW
IH6WDWLF
IH6WDWLF9O
IH6WDWLF9O*L
HIHQPLF9O*L
DQPLF*L*L
DQPLF$
DQPLF9O$
D/RFDO9O
D/RFDO*L
D/RFDO9O
D/RFDO*L
```

ARP 4Þ<Ø1‰ËXÖ

+!‰	Ë.Ä
IP Address	â@Ë,X IP Ä
MAC Address	â IP Ý,X.@Ë
Type	ARP 2O_Ø-ÞO_Ä
Age	ARP :4KSÊÞÈÄ
Interface	â IP G6(,XÝÄ

ËGÄê -

1.28 show arp timeout

/ÿ X|Õ ARP ><NM5ÐÄ

show arp timeout

ËÐAê

Ð	Ä
-	-

ËÞ,Õ!5BÐ -

Ëê -

ËS*Ð -

ËG!5B_Ð ß **show arp timeout Eg**

```
5XLMLHVKRZDUSWLPHRXW
,QWHUIDFHDUSWLPHRXWVHF

9/$
```

ÌÎGÐ

Ç	Ä
-	-

ËGÄê

1.29 show ip arp

?U/?d#AÄRP Å<ÐM*ð> AÇ

show ip arp

ËÐAê

Ð	Ä
-	-

ËÞ,Õ!5BÐ -

Ëê (M*ã

ËS*Ð -

Ï!5B_Ð ß **show ip arp Eg4ÊÄ**

```
5XLMLHVKRZSDUS
3URWRFROGGUHVVWPLQDUGZUH7SH
,QWHUIDFH
,QWHUQHWHG$3DVW(WKHUQHW
,QWHUQHWHE$3DVW(WKHUQHW
,QWHUQHWGIGF$3DVW(WKHUQHW
,QWHUQHWGIHFI$3DVW(WKHUQHW
,QWHUQHWGIG$3DVW(WKHUQHW
,QWHUQHWEGHEHH$3DVW(WKHUQHW
,QWHUQHWEGHIG$3DVW(WKHUQHW
,QWHUQHWGIIEE$3DVW(WKHUQHW
```

ARP 4¢<Ø1‰¿ÆXÖ

+!‰	Aß
Protocol	5¼X#AÆ¹+!‰ InternetÄ
Address	â@ß,X IP Ä
Age (min)	ARP 4çÅ),¡XÊßAuXp,XßÙ M-Ï!5B,XÆ¹+!%áÁ“”-”></Ä
Hardware	â IP Ín,X.@ß
Type	.@ßO_ß% ARPAÄ
Interface	â IP G6(,XyÄ

ÏÎGÐ

Q	ÆÄ
-	-

ÏGÄß

1.30 show ip interface

AÑ;X IP (ÑÐ

show ip interface [*interface-type interface-number* | **brief**]

ÏÐAß

Ð	ÆÄ
Interface-type	ûy2O_
Interface-number	ûy4ß
brief	/ý;X IP ÏG!5BQÑ primary ipÃ secondary ip ù(Ñ

ï5,Ï!5BÐ -

ÐÐ (M*ã

RGOS

RGOS

RGOS

show ip interface brief

upÈ down ` administratively down shutdown

show ip interface vlan

8QHDFKDEOH
6RXUFHTXHQK
5RXWLQHGLUHFW

/4§¢Ø!‰ŒXÖ

+!‰	Aè
IP interface state is:	5¼ÿØÑÕ(Ø:@ÐÕ"CÃA(Õ “UP” Ä
IP interface type is:	/y2O_ÈZSÈÄ
IP interface MTU is:	/yA’5B,X MTU Ä
IP address is:	/y· IP }-ÕÄ
IP address negotiate is:	/y· IP ú#9kÄ
Forward direct-boardcast is:	/È@¼ÈSÄ
ICMP mask reply is:	/ÈÕ ICMP }-Õ1(y[Ä
Send ICMP redirect is:	/ÈÕ ICMP Gnå[Ä
Send ICMP unreachabled is:	/ÈÕ ICMP Ã’y[Ä
DHCP relay is:	/ü DHCP 4Ä
Fast switch is:	/ü IP Ez6s6Ñ
Route horizontal-split is:	/ÚGÚÈ[CÃGÃA,XCÃÈ > Ä
Help address is:	/ helper IP Ä
Proxy ARP is:	/ÚÚ ARP Ä
ARP packet input number: 0 Request packet: 0 Reply packet: 0 Unknown packet: 0	/yÞX ARP y[DÈ ARP AÞ[ARP h1(y[Þ2O_y[
TTL invalid packet number:	/yÞX TTL ý[Ð
ICMP packet input number: 0 Echo request: 0 Echo reply: 0 Unreachable: 0 Source quench: 0 Routing redirect: 0	/yÞX ICMP y[DÈ[Ö Echo AÞ[Echo h1(y[Ã’y[ß0ey[CÃGnå[
Outgoing access list is	/yG!5BÐA“KÂ<Ä
Inbound access list is	/yG!5BÐA“KÂ<Ä

1.31 show ip packet statistics

AÇÐ¡ß IP y[,X4ªAuµÇÄ

show ip packet statistics [total |

2 IPv6

2.1 clear ipv6 neighbors

#Ù8|Ã4,XFÄ

clrear ipv6 neighbors

ËÐAð	Ð	Ë Ä
	-	-

ËÞ,Ã!5BÐ (Mã

Ëð EËAðÇÙ8ÉËEFÝ¿Ã4,XFðÄ-Ã!5B,Xã#Ù8Ä

ËS*Ôð -

Ë!5B_Ð 5XLMLHFOHDULSYÇÙLÄERUV

ÏËÇÐ	Ç	Ë Ä
	ipv6 neighbor	**6BÃ•**
	show ipv6 neighbors	**/FÝ**

ËÄð -

2.2 ipv6 addr[redacted]

54ÝG!5BÔ IPV6 ,X, S*ÄÇX no 6ð8G!5B,XÄ

ipv6 address *ipv6-address*/*prefix-length*

ipv6 address *ipv6-prefix*/*prefix-length* **eui-64**

ipv6 address *prefix-name sub-bits/prefix-length* [**eui-64**]

no ipv6 address

no ipv6 address *ipv6-address*/*prefix-length*

no ipv6 address *ipv6-prefix*/*prefix-length* **eui-64**

no ipv6 address *prefix-name sub-bits/prefix-length* [**eui-64**]

prefix-length	IPV6 !4ÔXKSzG IPV6 ><5¾%XFÄ4
prefix-name	*Ê4ÄÕÄ4ÔÄ*
sub-bits	*$ÔÄ4(M,Ä4ÔÄ* *ÄÕF-* RFC4291 Ê,ÄXfË</Ä
eui-64	></*äX IPV6 +G!5B,X!4Ô 64 !(M,Xy· ID Ä5Ä4˜ Ä

Ь,Õ!5BÐ -

äÐ yG!5Bã

Ь*Ðð

IPv6 VRF IPv6 VRF IPv6

þÔ IPV6 y>ðÕ(Ñ UP Êw2Ï4Ëy7þ*ðÃ

y¡X IPv6 3Ñ*Ê†Ï4ÔÄ IPv6 =Ê†Ï4Ô +Ä4Ô +

!(MÄ†Ï4Ñ*ü **ipv6 general-prefix ÇÐÑÑÊ›** DHCPv6 v0¸X PD(!4ê

))¸s6Ñ4(3ÞHCPv6 G!5B $ÄÔ +!(MÑ*ÇX *sub-bits/prefix-length*

ÐÐÄ

S*ü **no ipv6 address ÿÔÄ8È¥wÐ8ÉÐBÄ**

S * ü **no ipv6 address** *ipv6-prefix/prefix-length* **eui-64** Ã¹ ô 8 **S * üQ¸ ipv6 address**

ЬЬ,Õ!5BÐ y¡X IPv6 s6ÙÛÐ

ÐÐ yG!5Bã

Ь*Ð Ý 2 /ÐÐX IPv6 s6ÐÐG!5B **ipv6 enable** Ð ,ÐÙG!5B
Z IPv6 Ä

IPv6

5XLMLHFRQ1SY#HQUDOSUHIL[P6UHIL[

ÏĈĢĐ

Ǫ	ĖÄ
ipv6 address *prefix-name sub-bits/prefix-length*	**S*Ēſ4ĜBy·**
show ipv6 general-prefix	**ĝſ4Ô**

ĠÄĝ -

2.6 ipv6 hop-limit

S1_S<qƱĖÄ

ï‚,Õ!5BÐ 1

ï Ð yG!5Bã

ï‚*ûÐ yG!5BÐX IPV6 ÆÇ7C4Eþ!?UW|ÐU"#ÈÈÊ¹
Ø"tentative"(AÇ) ,X(ÆUE/ß> ÈpüÝ#ÐUÈwAÃ•
!7.BS*ÈpU"#ÐUÆS*ïXyÂ5G*ü EUI-64 ,XÂ5Èw><Â¹
ÐÃÐÑGÈw!8Ç47ÇKÁy(GL!6ÂyÈ> IPV6 ,X,È
ß)ÈÊOÆ!5B„XÈEa õ down/up yGÐU"#Ä™
Ø down (Õ up (ÕÑyÞXGÐU"#Ä

È!5B_Ð 5XLMLHFRQILSYQGGDGDWWHPSWV

ÏÇÐ

Ð	Ä
show ipv6 interface	Ø Ä

È Ãè -

2.8 ipv6 nd managed-config-flag

S*ÂÐ5BCÃ<@y[,X“**managed address configuration** ”Æ*ÂÐX no 6ã
ÚÈ8AÆÃ
ipv6 nd managed-config-flag
no ipv6 nd managed-config-flag

ÐÃè

Ð	Ä
-	-

ï‚,Õ!5BÐ CÃ<@y[AÆÙÝA'5B

ï Ð yG!5Bã

ï‚*ûÐ AÆXA'5BÞZCÃ<@,XÙUS*ë(Õ¦G!5B99ÆÝpÆ'
5BÐ*ë(Õ¦G!5B99kÆ*Ä

È!5B_Ð 5XLMLHFRQILSYQPDQHGFRQIODJ

ÏÇÐ

Ð	Ä
show ipv6 interface	Ø È ra-info ,XÐÄ
ipv6 nd other-config-flag	**A5B(Õ¦G!5B9ÆL8 ÆÐ,Ù Ä**

È Ãè -

2.9 ipv6 nd ns-interval

S*ÄĄ5ByÞÄ(NS) ,XGßÈhÈ*ÄĄX **no 6ÉÕ**

ipv6 nd ns-interval *milliseconds*

no ipv6 nd ns-interval

Ð	Ä
milliseconds	1000-4294967295

5,Õ!5BÐ CÃ<@y[(RA) 5,Õ 0(></þ)È A'ÛÞ FÄË*¡XGô

KÈh 1000ms(1 /)Ä

yG!5Bã

G!5B,XÚÃ<@y[(RA) >ÞÈ3>A'ÛÞS*Ã¸2UÉA'5Bk

Ä

5XLMLHFRQILSYQVLQWHUYDO

Q	Ä
show ipv6 interface	¹Q,XC

-

2.10 ipv6 nd other-config-flag

S*ÄĄ5BCÃ<@y[,X"**other stateful configuration** "ÈS*ÄĄX no 6ÉÙ

L8AÈÄ

ipv6 nd other-config-flag

no ipv6 nd other-config-flag

Ð	Ä
-	-

5,Õ!5BÐ CÃ<@y[AÛÝA'5B

yG!5Bã

A'5BÞBÈÛ'ÞXCÃ<@y[,XEÞ>5B!ÄÞÈ*ü

dhcpv6 99L8 IPv6 ÞXÞE> 7¾G!5B' managed address configuration >A'5BÈ

TAx other stateful configuration 3>A'5BÄ

5XLMLHFRQILSYQRWKHUFRQILJ

ipv6 nd ra-mtu	**A5BCđ,X** MTU +!‰Ä

ĭGÄđ -

2.13 ipv6 nd ra-interval

S*ÄĄ’5ByĐ,ÕCÃ<@(RA) y[,XKÈhŠ*ÄĄX **no 6ŠĐ**

ipv6 nd ra-interval {*seconds* | **min-max** *min_value max_value*}

no ipv6 nd ra-interval

ĐAđ

Đ	Ä
seconds	CÃ<@(RA) @y[,XĐÈhÄ!Ä
min-max	**A5BEŷ[Đh**
min_value	A’5BEŷ[ÕÈh,Xđ
max_value	A’5BEŷ[ÕÈh,Xđ

ĭ,Õ!5BĐ 200 /Ł¥Ą[,XKÈhü 200 /ĐB| 20Á

Đ yG!5Bã

Š*Đ VpAÄ’ĐĄ,ÕÃA’ĐwA’5B,XKÈhđÑCÃ<*ąXĐ!6
ÒÃXJA’đÕÃ<@y[5ą*5¼Ł¥Ą[,XKÈhÁĐB|
,RĐ
VpûGK+ **min-maxÈwrŁ¥Ą[Èhđc**

ĭG!5B_Đ

```
5XLMLHFRQILJXUDWLRQ
5XLMLHFRQILJXUDWLRQDLQWHUYDOPLQD[
```

ĬGĄ

Ą	Ä
show ipv6 interface	**Đ** ra-info ,XĄÄ
ipv6 nd ra-lifetime	**A5BAĐ**
ipv6 nd ra-hoplimit	**A5BCĄXCDX‰**
ipv6 nd ra-mtu	**A5BCđ,X** MTU +!‰Ä

ĭGÄđ -

2.14 ipv6 nd ra-lifetime

S*ÄĄ’5ByĐ,ÕCÃ<@(RA) y[,XCÃ<*đ*ÄĄX **no 6Šá**

5Đ

ipv6 nd ra-lifetime *seconds*

no ipv6 nd ra-lifetime

	seconds	

1800 /¦

yG!5Bã

5XLMLHFRQILJ

ipv6 nd ra-interval	
ipv6 nd ra-hoplimit	
ipv6 nd ra-mtu	MTU +!‰Ä

-

value	y[,X MTU +!‰Ä

5XLMLHFRQILJ

show ipv6 interface	ra-info
ipv6 nd ra-lifetime	
ipv6 nd ra-interval	

ipv6 nd ra-hoplimit	**A5BCQ**

ÏGÄê -

2.16 ipv6 nd reachable-time

S*AQ'5ByE› NDP |QXFÃ"'#F›AxÃ',XÃ
*AQX **no 6**
ipv6 nd reachable-time *milliseconds*
no ipv6 nd reachable-time

ÏDAê

Ð	E
milliseconds	F›AxÃ',XÊ!È!0-3600000

ï5,Õ!5BÐ C<@y[(RA) 5,Õ 0(></þ)È A'ÎÔ F›AxÃ',XÕ
4ÊÈ 30000ms(30 /)

ê yG!5Bã

Ï*Ô A'ÊEAG!5B,XÊÈ"#Á,XFÈ'5B,XÊÈ¹Ê-ÃX"#FÈ
ú>CÈX54ÃÃ5A'ÊXC#ÁÃÂ,ÚÊÈG!5B,XEä
G!5B,XÚÃ<@y[(RA) >Ê3>A'ÎÔ*ÜpA'5B,X 0 ></
A'þAÊÈS*5,Õ

G!5B_Ð 5XLMLHFRQILSYQUHDFKDEOHWLPH

ÎGÐ

Q	E
show ipv6 interface	****

ÏGÄê -

2.17 ipv6 nd suppress-ra

S*AQEÕÃ<@(RA) yÈAQX **no 6**EÕÃ
(RA) y[Ä
ipv6 nd suppress-ra
no ipv6 nd suppress-ra

ÏDAê

Ð	E
-	-

ï5,Õ!5BÐ ü IPv6 ,XyÕÃ<@y[

Ï Ð yG!5Bã

Ï*Ð ?UÐ CÃ<@y[Ð*ü ipv6 suppress-ra Ð

Ï5B_Ð 5XLMLHFRQILSYQVXSSUHVVUD

ÏÐ

Ð	Ä
show ipv6 interface	ra-info ,XÐ

Ï Ä -

2.18 ipv6 neighbor

S*Ð!5B Ð-Ð*Ð X **no 6 8**

ipv6 neighbor *ipv6-address interface-id hardware-address*

no ipv6 neighbor *ipv6-address interface-id*

Ð Ð

Ð	Ä
ipv6-address	F X IPV6 OFI~ RFC4291 n,X></6
interface-id	ace-87v6

2.19 ipv6 ns-linklocal-src

;> E5 **no ipv6 ns-linklocal-src**

IPv6 Ý RFC3484 E

ipv6 ns-linklocal-src

no ipv6 ns-linklocal-src

Ð	Ä
-	-

<G!5B

-

5XLMLHFRQ LSYQOLQORFDOVUF

Q	Ä
-	-

-

2.20 ipv6 redirects

ÏÎGÐ

Ð	Ð
show ipv6 interface	****

ÐGÄ

-

2.21 ipv6 route

AÐG!5B IPV6 ,XM-ÕÃÈ*ÄÐX **no 6**

ipv6 route *ipv6-prefix/prefix-length* {*ipv6-address* | *interface-id* [*ipv6-address*]} [*distance*] [**weight** *number*]

ÐA

Ð	Ð
ipv6-prefix	IPv6 !4ÐOFI~ RFC4291 ,X></6Ä
prefix-length	IPv6 !4ÐXKSzÐM6NOt#
ipv6-address	ÐE',Â5%XÐOFI~ RFC4291 ,X></6 ÐÐXEgÐÐpÐÇ ,XVpÐÐEwNOÐEgÐÄ
interface-id	ÐE',Â5%Xy[EgÐÐpG!5B,XM-ÕÃÐ EgÐ5ÐÐÇwÄx,ÂÄEgÐ· ,È²XÐÐAM-ÕÃ>0,È¢ÃÐp,Â5% 4ÐÇXVpÐÐEwNOÐEgÐÄ
distance	!ÐÄ,XL9RPÐTA"Ž¥%3Ð Ð-ÕÃuÐ· ÐE',<2RÅÐC¬ÐÃÐALÐ5BW,X<2#mÐÇÐ¥S]D>ÐÐpÐ2Ð5ÐB2D15D51 Tf-0.0022 T

number

ĠGÄǹ　-

2.22 ipv6 source-route

S*ǺĢĐA'ÊĔ@ǿĈÃǺOĘ¼Ẍ　IPv6 y[Ŝ*ǺĢẊ　**no 6ĺU6EǿĈĐẊ**
IPv6 y[Ä

ipv6 source-route

no ipv6 source-route

ÐAǹ

Ð	ȄÄ
-	-

ǚ,Ģ!5BĐ　/U!6E@ǿĈÃOĘ¼Ẍ　IPv6 y[

Ð̦　<G!5Bã

Ŝ*ĐÌ　2O_　0 CÃOĘ¼LdwŜA'ĐA4EĚ,ĐU!6E@ǿĈÃ
+OĘ¼Ẍ　IPv6 y[ĐÊ,X,ǾO_　0 CÃOĘ¼Ẍ　IPv6 y[Ä

ĠG!5B_Đ　5XLMLHFRQILJLSYVRXUFHURXWH

ÏĠGĐ

Ģ	ȄÄ
-	-

ĠGÄǹ　-

2.23 ping ipv6

AĢĐAž　IPV6 5%XEEÄ

ping ipv6-[[illegible]

!	></!ÞXAÐ,Xh1(Z
.	></ÞXAÐnÈÈüý1(
U	></A'ÛÚÃE',Â
R	></ÐÛ
F	></2ïüÚÐ
A	></y[ÐÑ½
D	></5ÐÞ Down (5ÐÑ5;X IPV6 s 6ÑU*(V"#0U)
?	></ÞÃ

ÏÐ	Ç	Ä
	-	-

ÐÄÞ -

2.24 show ipv6 address

AÇÐß IPv6 ,XÇÄ

show ipv6 address [*i.7275Cress [*

```
Ruijie#show ipv6 address
Global unicast address limit: 1024, Global unicast address count: 3
Tentative address count: 2,Duplicate address count: 1
Preferred address count: 3,Deprecated address count: 0
Gi 0/5
  FE80::1/64                                        Preferred
    Preferred lifetime: INFINITE, Valid lifetime: INFINITE
  1000::1/64                                        Duplicate
    Preferred lifetime: INFINITE, Valid lifetime: INFINITE
Gi 0/6
  FE80::1/64                                        Tentative
    Preferred lifetime: INFINITE, Valid lifetime: INFINITE
  1111:1111:1111:1111:1111:1111:1111:1111/64   Tentative
    Preferred lifetime: INFINITE, Valid lifetime: INFINITE
Gi 0/7
  FE80::1/64                                        Preferred
    Preferred lifetime: INFINITE, Valid lifetime: INFINITE
  2000:1111:1111:1111:1111:1111:1111:1111/64   Preferred
    Preferred lifetime: INFINITE, Valid lifetime: INFINITE
```

_ 2 GigabitEthernet 0/1 IPv6 Ä

```
Ruijie#show ipv6 address Gi 0/5
Global unicast address count: 3
Tentative address count: 0,Duplicate address count: 1
Preferred address count: 1,Deprecated address count: 0
FE80::1/64                                          Preferred
  Preferred lifetime: INFINITE, Valid lifetime: INFINITE
1000:1::1/64 [illegible]
  Preferred lifetime: INFINITE, Valid lifetime: INFINITE
```

ÏÇĢ

Ą	ĘÄ
-	-

ĠÄ -

2.25 show ipv6 general-prefix

/Eſ'ü4ĢX!4ĢĎ*ü **show ipv6 general-prefix**

show ipv6 general-prefix

ĎA

Ð	ĘÄ
-	-

Ď,Õ!5BĐ -

(Mã

S*ü **show ipv6 general-prefix** DHCPv6 v0Ã

4E†Ù4ÊÕÄ

Ğ!5B_Đ /E†Ù4ÔÈ¥ß

5XLMLHVKRŒSYHHQUDOSUHIL[

1UHDFKDEOHWLPHLVPLOOLVHFRQV
1DGYHUWLVHGUHDFKDEOHWLPHLVPLOOLVHFRQV

initcount	></ RA nÊG¡ÆÃCÃ<@y[þ DÄ
RA(out/in/inconsistent)	OutÖ</Ì¥CÃ<@y[,XÐÄ inÖ</,XCÃ<@y[,XÐÄ inconsistentÖ</,XCÃ<@y[CÃ<7ÐÞ @,Xy[,XÐÐÐXy[,XÐÄ
RS(input)	></,XCÃ<A¥Ï[,XÐÄ
Link-layer address	A¼y¡XÒÃ
Physical MTU	A¼y¡XÒÃ MTUÄ
!M | M	!M ></CÃ<@y[,XÄ managed-config-flag ûÐÝBÄ M: Æ6,Ä
!O | O	!O ></CÃ<@y[,XÄ other-config-flag ûÐÝBÄ OÆ6,Ä

Gb ra-info ,X!4Ö<(Prefix) ,XÐ¤%‰Ï¡

+!‰	AÈ£
total	></A¼y¡X!4ÔXÐÄ
fec0:1:1:1::/64	K¦X!4Ô
Def	Aû</A!4Ö*ü¡X5,Ô4ÔG!5BÄ
Auto | CFG	Auto û</A!4ÊbüG!5BÔn,X IPV6 5ãÞ¤ÂX!4ÔCFG û</A!4Ô!5B,XÄ
!Adv	Aû</A!4ÂÆ@Ä
vltime	></A!4ÔXÉÈ}Ä
pltime	></A!4ÔXOÉÈ}Ä
L | !L	L û</A!4ÔX on-link !5BÄ !L Æ6,Ä
A | !A	A û</A!4ÔX auto-config !5BÞ!A Æ6,Ì Ä

ÏÎGÐ

Ò	ÉÄ
-	-

ÜGÄè -

2.27 show ipv6 neighbors

/ IPV6 ,XF➢<Ä

show ipv6 neighbors [**verbose**] [*interface-id*] [*ipv6-address*]

show ipv6 neighbors static

ÐAß

Ð	Ł Ä
verbose	/F¸XA¹4ß
interface-id	**/þ¸×**
ipv6-addres	/ûF¸Xß
static	*/M-õ**

ï,Õ!5BÐ -

ð (Mã

Ï*ê -

Ï!5B_Ð _ 1Ö SVI 1 yÞXFß

5XLMLHVKRZSYÐLXERUVYODQ

State	F•X(Õstate/H(R) STATE ,XVØ INCMP(Incomplete)—AF•X?d!7E> È• AË)NS) y[ÆÕüÝ•Xh1(y[(NA)Ä REACH(Reachable) —></ÆÊÎXÈ¹ (ÕÆÇ]ÊÛNqêX|0Ä STALE — ></ F•AxÃ',XÊÈÕ(Õ'ú LÛNqêX|0,ÿ[ÆÃF•BÊÚ | NUD (Neighbor Unreachability Detection) Ä DELAY—></ý[ø STALE (ÕXF•ÕÊ S(Š Ã+DEE@L Æ(YŠ Õ È ü DELAY_FIRST_PROBE_TIME seconds(5 /)YVpüÝ FÃ'ÛXEîpDEw(Õ
Age	></F•AxÃ',XÊÈ '-'></EÃ',XÈ Í M-Õ!5B,XF•<NMúC*brLÃ'Æxpired' ></F•AxÃ',XÊÈ?¥ NUD"#Ä
Asked	></ÛdF•XÒÃÈ¥ÇXF•AË (NS),XDGÆ

DELAY E@6
ÈZÃ

_ 3ØM-Ê(Õ

5XLMLHVKRZSYQLXERUVVWDWLF
,3Y6GUHVV/LQODHUGU,QWHUIDFH6WDWH
GIDE*LDELW(WKHUQW&9(
GIDF9/$,1&9(

+!‰	AÈ
IPv6 Address	M-Ê•X IPV6
Linklayer Addr	G!5B,XÒÕ Mac
Interface	AF•Xy·

State	M-Õ•X(Õ STATE ,XVØ ACTIVE—#|,X INACTIVE—á|,XÈ!5B,XM-Õ• yÐ!5B,X á!Ø,X5%‰È ç-D¶UÅM-Õ•G!5Bá|ÈD B¼M-Õ•,X	IPV6 ê mac E@Ä

ÏĈĢĘ

Ę	ĖÄ
ipv6 neighbor	**ê•**

ĠÄê

-

2.28 show ipv6 neighbors statistics

ę¶;Ĵ IPv6 F•<,X4ÂuĻ

show ipv6 neighbors statistics

ę¶;Ý IPv6 F•<,X4ÂuĻ

show ipv6 neighbors statistics all

ĐAê

Đ	ĖÄ
-	-

ĵ,Ø!5BĐ

-

ę

(M*ã

Ĝ*Ð

-

Ġ!5B_Đ

_ 1

```
Ruijie#show ipv6 neighbors statistics
Memory: 1000 bytes
Entries: 10
  Static: 1,Dynamic: 9,Local: 0
  Incomplete:1, Reachable:5, Stale:1, Delay:1, Probe:1
```

_ 2

```
Ruijie#show ipv6 neighbors statistics all
IPv6 neighbor table count: 2
Static neighbor count: 4(2 active, 2 inactive)
Total
ÿ0Ï "bytes:8!"" ' ! -                                   'Memory:
:20          ▮                                          Entries:
::3;Dynami:::8,Local:::0          ▮
Ie0e:3;"Reachable:0,  _:.le:2;"Delay:3,"Probe:3-  ·····Incom

 Ï0000l                                                 Glob ·
1ÿÏ "bytes:8!"" ' ! -                                   'Memory:
:10          ▮                                          Entries:
::1;Dynami:::9,Local:::0          ▮
Ie0e:1;"Reachable:5,  _:.le:1;"Delay:1,"Probe:1          Incom

IIIIII                                                  VRF:
1ÿÏ "bytes:8!"" ' ! -                                   'Memory:
:10          ▮                                          Entries:
::1;Dynami:::9,Local:::0          ▮
Ie0e:1;"Reachable:5,  _:.le:1;"Delay:1,"Probe:1          Incom
```

ÏÎGÐ

Ð	ÐÄ
-	-

ÏGÄÐ -

2.29 show ipv6 packet statistics

AÐ;ß IPv6 y[,X4ªAuÐ

show ipv6 packet statistics [total | *interface-name***]**

ÏDAÐ

Ð	ÐÄ
total	**ý¾ªAuÐ`**
interface-name	*yÐÄ*

Ï5,Õ!5BÐ -

Ïð (M*ã

ÏS*Ð -

ÏG!5B_Ð _ 1Ð IPv6 y[4ªAuÐ!ðX4ªAuÐÄ

```
Ruijie#show ipv6 packet statistics
Total
  Received 1000 packets, 1000000 bytes
    Unicast:1000,Multicast:0
    Discards:0
      HdrErrors:0(HoplimitExceeded:0,Others:0)
      NoRoutes:0
      Others:0
  Sent 100 packets, 6000 bytes
    Unicast:50,Multicast:50

VLAN 1
  Received 1000 packets, 1000000 bytes
    Unicast:1000,Multicast:0
    Discards:0
      HdrErrors:0(HoplimitExceeded:0,Others:0)
      NoRoutes:0
      Others:0
  Sent 100 packets, 6000 bytes
    Unicast:50,Multicast:50
```

_ 2Ø IPv6 y[4ÆuÇÄ

```
Ruijie#show ipv6 packet statistics total
Received 1000 packets, 1000000 bytes
 Unicast:1000 Multicast:0
 Discards:0
:xceeded:0,Others:0)      HdrErrors:0(HoplimitE
                          NoRoutes:0
                          Others:0
1000 packet                    Jtes      6Ceivec
                                  :50
```

ÎÇÐ		
	Q	Ë
	-	-

ÜÄß -

2.30 show ipv6 route

/ IPv6 ,XCÃÇÄ

show ipv6 route [**static** | **local** | **connected**]

ÐAß		
	Ð	Ë
	static	/M-Õ!5B,XCÃ
	local	/CÃ
	connected	/,È¢CÃ

ß,Õ!5BÐ -

Ð (Mã

Ï*Ô EÊAÃ><,XÇÄ

Ï5B_Đ

```
5XLMLHFRQILJKRZSYURXWH
,3Y
```

ÎÇÇ	Ä
ipv6 route	**ÃÐ**

Ï Ä -

2.31 show ipv6 route summary

M6,XÇ;Ã IPv6 CÃ><,X4ÃuÇÄ

show ipv6 route summary

M6,XÇ;Ã IPv6 CÃ><,X4ÃuÇÄ

show ipv6 route summary all

Ð Ä

Ð	Ä
-	-

Ï,Õ!5BÐ -

Ô (M*ã

Ï*Ô -

Ï5B_Đ _ 1ÃCÃ><,X4ÃuÇÄ

```
Ruijie#show ipv6 route summary
IP                  :ng cable name is default, Global snooping entries
IP                  :ng cable default maximum-paths is 32
Local               2                                    ■■ ▮      ▮
Connected           0                                    ■■ ▮      ▮
Static              0                                    ■■ ▮      ▮
RIP                 0                                    ■■ ▮      ▮
OSPF                0                                    ■■ ▮      ▮
BGP                 0                                    ■■ ▮      ▮
-------------------------
Total               2                                    ■■ ▮      ▮
```

_ 2ÐŸ IPv6 CÃ><,X4ÃuÐ

```
Ruijie#show ipv6 route summary all
IPv6 routing table count: 2
Total
  Memory: 2000 bytes
  Entries: 20
    Local:2,Connected:2,Static:8,RIP:2,OSPF:2,ISIS:2,BGP:2

Global
  Memory: 1000 bytes
  Entries: 10
    Local:1,Connected:1,Static:4,RIP:1,OSPF:1,ISIS: 1,BGP:1

VRF1
  Memory: 1000 bytes
  Entries: 10
    Local:1,Connected:1,Static:4,RIP:1,OSPF:1,ISIS: 1,BGP:1
```

ÏGÐ	Ð	Ä
	-	-

ÜGÄ -

2.32 show ipv6 routers

IPv6 5 XCÃ<ÃA@y{Ã/EoFCÃ<CÃ@ **show ipv6 routers**

ÝÃ@,XÇÄ

Ï!5B_Đ / IPv6 CÃ<,XÇÏ

```
5XLMLHVKRWSYURXWHUV
5RXWHU)()))(RQ$ODVWXSGDWHVHF
+RS/LIHWLPHVHF0DQG)ODJ2WKHU)ODJ078
3UHIHUHQH 0(;80
5HDFKDEOHWLPHVHF5HWUDQVPLWWLPHVHF
3UHIL[RQLQDXWRFRQJ
9DOLGLIHWLPHVHFSUHIHUUHGLIHWLPHVHF
3UHIL[RQLQDXWRFRQJ
9DOLGLIHWLPHVHFSUHIHUUHGLIHWLPHVHF
```

ÏÎGĘ

Ę	ĘÄ
-	-

ÏGÄè | -

2.33 tunnel destination

S*ÄĘ{Fyû,X, S*ÄĘX no Ę8A¹,ÂKÄ

tunnel destination *ipv4-address*

no tunnel destination

ÐAè

Đ	ĘÄ
ipv4-address	GL{FÊX IPv4 Ä

5,Ç{FÊ,X,,ÂKüÏ!5B

yG!5Bã

6ÊÏ!5BÊ2O_Ê{F¦L{F',ÂKF¦ÊX{F'

(6to4 isatap)

Ï!5B_Đ G!5BIPv6 Ł{F',X_Ê

```
5XLMLHFRQILJXUHSHUIDFHWXEO
5XLMLHFRQILJXUHSOPRGHLSYLS
5XLMLHFRQILJXUHSOVRXUFHYODQ
5XLMLHFRQILJXUHSOGHVWLQWLRQ
```

ÏÎGĘ

Ę	ĘÄ
tunnel source	**GBL{F¦**

tunnel mode	**6BL{F**
tunnel ttl	**6BL{F TTL**

Ï GÄ **-**

2.34 tunnel mode ipv6ip

S*Ä Q!5B -Õ IPV6 L{F2O_, S*Ä Q no 6 ,Õ IPv6 L{F2O_Ä

tunnel mode ipv6ip [**6to4** | **isatap**]

no tunnel mode

Ï DA

Đ	E Ä
6to4	G!5BAŁ{F' 6to4 7 ¼{FÄ
isatap	G!5BAŁ{F' ISATAP 7 ¼{FÄ

ï ,Õ!5BĐ Î X IPv6 L{F2O_G!5BL{F'

 yG!5B

Ï *Ð L{FyÎÕK9 ,Õ xG!5BL{F È*Q tunnel mode ipv6ip ÐE MB Ú{ F'A'5BŁ{F 7 ¼{FFÑOÛ,Â Ä

Ï G!5B_Đ M6G!5B 6to4 L{F,X_ Ð

5XLMLHFRQILJXUHWXQQHO

5XLMLHFRQILJXUHWXQQHOPRGHLSYLSWR

ÏÎG Q Q E Ä

Q	E Ä
tunnel source	**6BL{F**
tunnel destination	**6BL{F**
tunnel ttl	**6BL{F TTL**

Ï GÄ **-**

2.35 tunnel source

S*Ä Q{Fy **6** , S*Ä Q no Q BA **6**

tunnel source {*ipv4-address* | *interface-type interface-number*}

no tunnel source

Ï DA

Đ	E Ä
ipv4-address	G!5BL{F **6** IPv4 È¹ IPv4 Ý ü{F Õ Xy[,X **6** Ä

interface-type *interface-number*	G!5BL{Fß,Xéýl¿pL{Fã ipv6ipÊéý· ,X ipv4 ¿ÝÙ{FÊÕXy[,Xß IPv4 ¥pL{F' ã ipv6ÊéýG!5B,X1Ô ipv6 <)¥Ù{ FÊÕXy[,Xß IPv6 Ä

ï5,Õ!5BÐ 5,ÙÝ{Fß>A'5B

ïÐ yG!5Bã

ïS*Ô L{F',Xß3BÙ,X IPv4 3Ê*þ¡X IPv4 , G!5B7¾{FÊV
6to4 ` isatap)Ç*ýÙß Ä

ïG!5B_Ð G!5BIPv6 Ł{F',X_ß

```
5XLMLHFRQILJXUHIDFHWXEQO
5XLMLHFRQILJXUHIDFHWXEQOPRGHLSYLS
5XLMLHFRQILJXUHIDFHWXEQOVRXUFHYODQ
5XLMLHFRQILJXUHIDFHWXEQOGHVWLQWLRQ
```

ïÎGÐ

Ç	Ł Ä
tunnel mode	**G!5BL{Fß**
tunnel destination	**G!5BL{FÊ**
tunnel ttl	**G!5BL{FX** TTL

ïGÄß

-

3 DHCP

3.1 address range

?Uü DHCP 4G6(,X CLASS CLASS 6!,X5

class G!5B

,X **address range** **no 6A8A5**

address range *low-ip-address high-ip-address*

no address range

low-ip-address	5XCKX
high-ip-address	*5*6Ä

5,Õ6(,X CLASS G!5B5Ax4,X5

4 CLASS G!5B

!ß CLASS CLASS KX5x

G6(,X CLASS,X5G!5B¹ CLASS TAx,X5

` CLASS X4,X5

G!5B_ G!5B4 mypool0 G6(class1 ,X5 172.16.1.1 172.16.1.8 Ä

```
5XLMLHFRQ1SGKFSSRROPSRRO
5XLMLHGKFSFRQFODVVFODVV
5XLMLHFRQGKFSSRROFODVVDGGUHVVUDQ
```

ip dhcp pool	**n** DHCP 4 DHCP 4G! 5B
class	**B** DHCP 4G6(,X CLASS4 CLASS G!5B

-

3.2 bootfile

?Un DHCP v0, DHCP 4G!5BQ **bootfileA** **no 6**

bootfile *file-name*

no bootfile

	file-name	

5,

DHCP

DHCP v0 DHCP v0 TFTP **next-server**

	router.conf 0

ip dhcp pool	n DHCP DHCP
next-server	DHCP v0 IP

-

3.3 class

?Uü DHCP CLASS DHCP **class no 6** CLASS

class *class-name*

no class *class-name*

class-name	Eg9 CLASS ,X V myclass 1Ä

5, CLASS

DHCP

!f DHCP Option82 Option82 Option82 DHCP CLASS DHCP CLASS CLASS CLASS IP CLASS CLASS CLASS CLASS E> IP CLASS

	ip-address	IP

-

(M*

DHCP ping DHCP v0#0U*0d#ARP **clear ip dhcp conflict**

5XLMLHFOHDULSGKFSFRQOLFW

7 0 Td[(DHC)7(P)]TJ/C20/C20 1 Tf 3.08 0 Td[(

3.7 clear ip dhcp relay statistics

?Uá DHCP)ÚXAuD<ÈM*ãü **clear ip dhcp relay statistics** Ø
clear ip dhcp relay statistics

ÐAãè	Ð	ÆÄ
	-	-

Ö,Õ!5BÐ -

Øõ (M*ã

Ö*Ðõ DHCP)ÚPAuAuDÝÆ,ÕX DHCP ØOy[D,Ê> ØAuÄ **clear ip dhcp relay statistics**
õ8ÆuDAõPAuÄ

Ö!5B_Ð [ÈL8â)ÐuÇ¿ÐPHVÜF!VÐ7ÐE8µÐ|V-|VÊ$TP@

,XnÆ• RFC1700 [7,XAddress Resolution Protocol Parameters 08VÄ
Ø¿> DHCP ¼¥nÐÃ*ÄÇ

Ï!5B_Ð Ø!5B_ßZ MAC 00d0.f822.33b4 ,Xþ5% DHCP v0ÃXv0ÃÄ
5XLMLHGKFSFRQILJFOLHQWLGHQWLILHU
GIEHI

ÏÎGÇ

Ç	È Ä
hardware-address	n DHCP v0ÃX.@È
host	n IP 5¼¾-ÐG!5B DHCP ¼¥Ä
ip dhcp pool	n DHCP ¼áÈ9 DHCP ¼G!5Bõ Ä

ÏGÄß -

3.9 client-name

?Un DHCP v0ÃXáÈu DHCP ¼G!5BÇ **client-name**ÄÇ no 6ß8 DHCP v 0ÃXáÄ

client-name *client-name*

no client-name

ÐAß

Ð	È Ä
client-name	n DHCP v0ÃXáÄÈX ASCII +0úÄá hÄß n river DHCP v0ÃßÑ river.i-net.com.cnÄ

Ï,Ð!5BÐ 5,ÐÍv0ÃÄ

ÇÐ DHCP ¼G!5BÄ

Ï*Ð Ø¿> DHCP ¼¥nÐÄÇ DHCP v0ÃXáÄáÄÄ
4ß

Ï!5B_Ð Ø!5B_ßÐ0ú river 0v0ÃXáÄ
5XLMLHGKFSFRQILJFOLHQWQPHULYHU

ÏÎGÇ

Ç	È Ä
host	n IP 5¼¾-ÐG!5B DHCP ¼¥ nÄ
ip dhcp pool	n DHCP ¼áÈ9 DHCP ¼G! 5BÄ

ÏGÄà -

3.10 debug ip dhcp client

?UE> DHCP Client ,XA^(M*ü **debug ip dhcp client**

debug ip dhcp client

no debug ip dhcp client

ÏDA

Ð	Ä
-	-

ï,Õ!5BÐ 5,ÕKÁ

(M*

Ï*Ð A/ dhcp client <xfE/X?Uy[Y

ÏG!5B_Ð dhcp v0XA^GÄ

5XLMLHGHEXI1SGKFSFOLHQ

ÎGÐ

Ä
-

ÏGÄà -

3.11 debug ip dhcp server

?UE> DHCP Server ,XA^(M*ü **debug ip dhcp server**

debug ip dhcp server { **event** | **event** }

no debug ip dhcp server { **event** | **packet** }

ÏDA

Ð	Ä
event	/ DHCP #CY•
packet	/ DHCP y[Y•

ï,Õ!5BÐ 5,ÕKÁ

(M*

Ï*Ð A/ dhcp server 0XfE/X?Uy[Y

ÏG!5B_Ð dhcp <y[,XA^GÄ

5XLMLHGHEXI1SGKFSVHUYHUSDFNHW

ÏĈĢĐ	Ǫ	ƐÄ
	-	

ÏGÄÈ -

3.15 hardware-address

?Un DHCP v0Ã¥.@Ê¡ DHCP ¼4G!5BQ **hardware-addressÄ¥Ð** **no 6ã**
ê8.Ê¥Ä

hardware-address *hardware-address* [*type*]

3.16 host

?Un DHCP v0ÃX IP 5¼j-Õu DHCP ¼G!5BQ **host**ÄÐ **no 6Ã**
ê8 DHCP v0Ã IP 5¼j-ÕXnÄ

host *ip-address* [*netmask*]

no host

ÏDAèÐ

Ð	ÆÄ
ip-address	*n* DHCP v0ÃX IP Ä
netmask	*n* DHCP v0ÃX5¼j-Õ

Ï5,Õ!5BÐ ùnÝ,X IP 5¼j-Õ

ÏKÐè DHCP ¼G!5BÃ

ÏS*Ûè Vp5¼j-ÕÃBnÈDHCP á<ÿÄ¹ IP ,X7%¼j-Õ 2O5¼j-Õ
255.0.0.0Ø 2O5¼j-Õ 255.255.0.0€ 2O5¼j-Õ 255.255.255.0Ä
Ø> DHCP ¼mmÊ*ÄKÅ

ÏG!5B_Ð G!5B_ØÕÃ IP A' 192.168.12.91ÈÕ 255.255.255.240Ä
5XLMLHGKFSFRQLKRVW

ÏÎGKÐè

KÅ	ÆÄ
client-identifier	**n** DHCP v0ÃXÕ%mÔXAE¯ D></Å
hardware-address	**n** DHCP v0ÃX.@Ê
ip dhcp pool	**n** DHCP ¼ëÈ9 DHCP ¼G! 5BÃ

ÏGÄèÐ -

3.17 ip address dhcp

?USkp5%U PPPÃ HDLCÃ FR Õ,TXy6ÑE› DHCP 9k IP ¿ÊyG!5BKÅ **ip address dhcp**ÄÐ **no 6Ã**G!5BÄ

ip address dhcp

no ip address dhcp

ÏDAèÐ

Ð	ÆÄ
-	-

Ï5,Õ!5BÐ 5,ÿ6ÑE› DHCP 9k IP Ä

-

3.19 ip dhcp database write-delay

DHCP

FLASH

no

FLASH

ip dhcp database write-delay *time*

no ip dhcp database write-delay

time	DHCP FLASH

FLASH

<

EE FLASH DHCP FLASH

3600S m FLASH

-	-

-

3.20 ip dhcp database write-to-flash

DHCP FLASH

ip dhcp database write-to-flash

-	-

<

EE DHCP FLASH

FLASH

-

ÎĈĢĐ		
	Ç	ÆÄ
	-	-

ĬĢÄâê -

3.21 ip dhcp excluded-address

?Unø IP È½k DHCP á<Ú!4- DHCP v0Ê¾G!5BÇ **ip dhcp excluded-address**ÄÇĐ **no 6ÃÍ-n**Ä

ip dhcp excluded-address *low-ip-address* [*high-ip-address*]

no ip dhcp excluded-address *low-ip-address* [*high-ip-address*]

ĐAâê		
	Ð	ÆÄ
	low-ip-address	*fy* IP Ê½fy IP 8ÈXCKŸ IP Ä
	high-ip-address	*fy8È8* IP Ä

ĭ,Õ!5BÐ 5,Õ DHCP á<Ú!HÐ,X IP Ä

ÐÇ <G!5BÄá

Ĭ*ÐÛ VpùÚ!5Bfy IP ÈDHCP á<ÂÚ! DHCP ¼,XÝ IP ÄÇM n±-Ô IP È½S!Eø>Ú!4- DHCP v0Ã'.Bnfy IP ÈÃ DHCP á<Ú!ÊX0U"#ÊÄ

Ĭ!5B_Đ G!5B_ÈDHCP á<ÂÚ! 192.168.12.100~150 8È£,X IP Ä

5XLMLHFRQ1SGKFSH[FOXGHGDGGUHVV

ÎĈĢĐ		
	Ç	ÆÄ
	ip dhcp pool	**n** DHCP ¼áÆ9 DHCP ¼G! 5BÄá
	networkÐDHCP Å	**n** DHCP ¼,X5¼Ê¾4j-Ô

ĬĢÄâê -

3.22 ip dhcp ping packets

?UG!5BDHCP á<"#0UÊ ping A¡X ÐÊ¾G!5BÇ **ip dhcp ping packets**Ä¹ ÇĐ **no 6ÃÍÃBÄ**

ip dhcp ping packets[*number*]

no ip dhcp ping packets

ĐAâê		
	Ð	ÆÄ

number	0 10È 0 ></GKÁ ping

5,Õ ping 2Ä

<G!5B

DHCP á<¢ DHCP 4AG! IP ping 09"#A V4
*p4*A,0p4*4-
DHCP v0Ã Ping 05,BÊ
10

G!5B_Đ G!5B_ ping 0BDA’ 3
5XLMLHFRQ1SGKFSSLSDFNHWV

clear ip dhcp conflict	DHCP UA),Ä
ip dhcp ping timeout	DHCP á< ping 01Yh1(,XCY ping h1 A!,XÅ),0UÄ
show ip dhcp conflict	/ DHCP á< !,X† 0UÄ

-

3.23 ip dhcp ping timeout

ÏÎGĘ

Ǫ	ĘÄ
clear ip dhcp conflict	**ǿ8** DHCP ǿĘUA)Ä **n** DHCP á<Ú!Ê0U,X
ip dhcp ping packets	ping ǫ¬ _ǫ

ip dhcp relay check server-id

no ip dhcp relay check server-id

Ï DAÐ	Ð	Ë Ä
	-	-

Ï ,Õ!5BÐ GKÁ

Ï Ð <G!5Bã

Ï *Ð EË G!5B!8Ò DHCP Relay Ë @¥ DHCP AÿÊ Ê option server-id Ë ÝÒ UE@¥X DHCP á<Ø pù 6!5BA !5B,X DHCP á<E@¥ DHCP AÿÄ

N0 Ð Ð

service dhcp	**Ô** DHCP 4»
ip dhcp relay information option dot1x access-group *acl-name*	G!5Boption dot1x acl

ÏGÄÐ -

3.27 ip dhcp relay information option dot1x access-group

?UG!5BDHCP Relay option dot1x G6(,X ACL

HDFHVV(DFK2WKHU2I8XWKUL]H	
ÏĜ	Ą	Ä

缺省级别： 3级

视图： 全局配置视图

缺省情况： 未配置option dot1x sub-option

命令格式： [no] ip dhcp relay information option dot1x sub-option

参数说明： 无

配套说明：

前置命令	说明
service dhcp	开启 DHCP 功能
ip dhcp relay information option dot1x	开启 DHCP option dot1x sub-option

使用指南： -

3.30 ip dhcp relay suppression

命令功能： 配置 DHCP Relay 抑制功能，使能后，不转发 DHCP relay 报文

命令格式：

ip dhcp relay suppression

no ip dhcp relay suppression

缺省级别： 3级

视图： 全局配置视图

缺省情况： 未配置

配套说明：

前置命令	说明
-	-

使用指南： 无

命令功能： 配置 DHCP relay 报文

缺省级别： 1级

视图： DHCP relay 视图

缺省情况： 未配置

命令格式：

配套说明：

前置命令	说明
service dhcp	开启 DHCP 功能

使用指南： -

3.31 ip dhcp use class

?UG!5B*ü CLASS E> Ó!ÄG!5B **ip dhcp use class** **no 6Ã**

CLASS E> Ó!Ä

ip dhcp use class

no ip dhcp use class

Đ	Ä
-	-

5,Õü CLASS E> Ó!Ä

<G!5BÄ

-

G!5B_ G!5B*ü CLASS E> Ó!Ä

5XLMLHFRQILSGKFSXVHFODVV

Q	Ä
-	-

-

3.32 ip helper-address

?U#ïÐ DHCP á<*A **no**

DHCP á<ÃG!5BG!5B

ip helper-address { cycle-mode | [vrf *vrf-name* **] A.B.C.D }**

no ip helper-address { cycle-mode | [vrf *vrf-name* **] A.B.C.D }**

Đ	Ä
vrf-name	2,X VPN 0N VPN 0N

ùG!5Bá<Ä

<G!5Bã yG!5BÄ

<G!5B 20 þ DHCP á<Ä

G!5B DHCP á<,X DHCP Relay G*ü DHCP á<pyG!5BZ

DHCP á<DHCP Relay ,G*üG!5B,Xá<G*üá<Ä

G!5B vrf Đ,X<,XG!5By;XG!5B/<,XG!5BVp vrf –

DHCP xab vrf y;XG!5BVp vrf á<y2b vrf
<G!5B dhcp relay ,X cycle-mode G!5B cycle-mode ,X </ dhcp relay
X dhcp client E@ XÝ dhcp server cycle-mode ,X
> </ dhcp relay ¼,X dhcp client E@ ,X1 dhcp server
cycle-mode G!5B G!5B *<y x*

G!5B_ G!5B_ G!5B <Ö
G!5B á< 192.168.1.1×
1 G!5B vrf r_ dep1 ,X á< 192.168.2.1×
5XLMLHFRQIXUHWHUPLQDO
5XLMLHFRQIXUHWHUPLQDO
5XLMLHFRQIXUHWHUPLQDO
5XLMLHFRQIXUHWHUPLQDO
G!5B<á< 192.168.1.1×
2 G!5B vrf r_ dep1 ,X á< 192.168.2.1×
5XLMLHFRQIXUHWHUPLQDO
5XLMLHFRQIXUHWHUPLQDO
5XLMLHFRQIXUHWHUPLQDO

service dhcp	DHCP 4

-

3.33 lease

?Un DHCP á<G!4v0 DHCP 4G!5B **lease** **no 6**
lease { *days* [*hours*] [*minutes*] | **infinite** }
no lease

days	*n*
hours	*DÄ*
minutes	
infinite	

5, DHCP 4G!5B

DHCP v0 DHCP á<

ÏG!5B_Ð ÐG!5B_ÐÑ DHCP /áÄ’ 1 ÐÄ

5XLMLHGKFSFRQQDHDVH

ÐG!5B_ÐÑ DHCP /áÄ’ 1 ÐÚÄ

5XLMLHGKFSFRQQDHDVH

ÏÎGÐÇ

Ç	ÐÆÄ
ip dhcp pool	**n** DHCP '4áÐÈ9 DHCP '4G!5BÐÄ

ÏGÄÐè -

3.34 netbios-name-server

?UG!5B ,EÐDHCP v 0Ã NETBIOS ,X WINS á+ áu < È¨ü DHCP '4G!5BÇ

netbios-name-serverÄÐÇ **no 6ÐÑ8** WINS á<Ä

netbios-name-server *ip-address* [*ip-address2…ip-address8*]

no netbios-name-server

ÐÄÐè

Ð	ÐÆÄ
ip-address	*n* WINS á<,X IP Ä¾U7ÐG!5BÐÐ
ip-address2…ip-address8	ÐÑB 8 Þ WINS á<Ä

Ï5,ÕG!5BÐ 5,ÕÝ WINS á<Ä

ÐÇ DHCP '4G!5BÃ

ÏS*ÐÐ nÞ WINS á<ÊÙM6,XPÐDHCP v0ÐÑX WINS á<ÊÀƒ BÈÊÐè WINS á<Ä

ÐG!5B_Ð ÐG!5B_ÐÏ DHCP v0ÐÑZ WINS á< 192.168.12.3Ä

5XLMLHGKFSFRQQDHDVH

ÏÎGÐÇ

Ç	ÐÆÄ
ip address dhcp	**y*ü** DHCP v0Ð¾ IP ÇÄ
ip dhcp pool	**n** DHCP '4áÐÈ9 DHCP '4G!5BÐÄ

ÏGÄÐè -

3.35 netbios-node-type

?UnÆC DHCP v0Ã NetBIOS ,X8V¾O_È¨ü DHCP '4G!5BÇ **netbios-node-typeÄ**

AÇX **no 6Ã8** NetBIOS 8V&O_G!5B

netbios-node-type *type*

no netbios-node-type

Ð	Ä
type	*n* NetBIOS 8V&O_ÐÃ D+nÈÈ 0~FFÈEDÐÐÕ 1È< b-node× 2È< p-node× 4È< m-node× 8È< h-nodeÄ +0úÖ b-nodeÈ•_8V& p-nodeÊ_8V& m-nodeÈÈ8V& h-nodeÊ8VÄ&

5,ÕÐ!5BÐ 5,ÕÝ NetBIOS 8V&O_Ä

ÐÇ DHCP 4G!5BÄ

È*Ð ÈC DHCP v0Ã NetBIOS 8V&O_ÝÖ 1Å Broadcast È_8VÈEÈ> NetBIOS á?d× 2ÅPeer-to-peeÍÈ_8VÈEÈ,ÿÄË WINS á<È> NetBIOS á?d× 3ÅMixedÈ #Ê8VÈEÈÈÄÊ?dÊEâ WINS á<EÿÈ> á?d× 4Å HybridÊ Ü8VÈ¡ÿÄË WINS á<È> NetBIOS á?dÝpùÝh1(ÈEÈÊ¯ > NetBIOS á?dÄ

5,ÕÐC02Ï¾X8V&O_S•_6ÊÜXpùÝG!5B WINS á<È•_ 8V&pG!5BZ WINS á<Ê8VÄ¡Ú NetBIOS ,X8V&O_A' HybridÄ

ÜG!5B_Ð GG!5B_ÕÐC DHCP v0ÃX NetBIOS 8VÄ'Ê8VÄ& 5XLMLHGKFSFRQLQWELRVRQGHWSHKQGH

Q	Ä
ip dhcp pool	**n** DHCP 4áÈ9 DHCP 4G!5BÄ&
netbios-name-server	**6BÐC** DHCP v0Ã NETBIOS ,X WINS áá u<

ÜÄÐ -

3.36 network DHCP

?Un DHCP 4,X5 DHCP 4G!5B **network no 6**

network *net-number net-mask*

no network

net-number	DHCP 4,X IP 5
net-mask	DHCP 4,X IP 5

5, 5 DHCP 4G!5B

DHCP á<o 4v0 X0NK 8M2Ý

fyG!5B XF 4v0 DHCP 4,X Nc

E ~ @?P V =

Ï5,Õ!5BÐ	-
ÏÐ	DHCP ¼G!5BÃ
Ï*Ô	n[á<ËnUM6,XPÈDHCP v0ÃX|á<EÄAÞÈ !EÞÃ<Ä
Ï!5B_Ð	Ï!5B_È DHCP v0ÃÞá< 192.168.12.4Ä 5XLMLHGKFSFRQLÐ[WVHUYHU

ÏÎÐ

Ò	Ë
bootfile	**n** DHCP v0Ã,ÞÃ
ip dhcp pool	**n** DHCP ¼áÈ9 DHCP ¼G!5BÃ
ip help-address	**yn** Helper Ä
option	**6B** RGOS ECÊ DHCP á<,XEÍMÄ

ÏÄÃÈ -

3.38 option

?UG!5ÈDHCP á<,XEÍMËü DHCP ¼G!5BÒ **optionÄÞ** **no 6Ã8** option ,XnÄ

option *Ã¼ 0ÞÈÃaÀÞÐ*

></GKÁ IP È@¥ ></*ü IP È@Ø!5BÈk DHCP v0Ãü IP È@Ä

5XLMLHGKFSFRQ RSWLRQH[

_ 2Ø!5B_ÊÍM-Õ 33 E> ÆÈEÍM4- DHCP v0ÃÍM-ÕÃÇÈ DHCP

v0ÃÍM-ÕÃÖ

1

3.40 relay-information hex

?Uë,X CLASS E9 Option82 G!ÇG!5Bè CLASS G!5BÐX **relay-information hex** ÐÐ **no 6Ã86Ç**

relay-information hex *aabb.ccdd.eeff…* [*]

no relay-information hex *aabb.ccdd.eeff…* [*]

ÐAÐ	Ð	ÐÄ
	aabb.ccdd.eeff… [*]	16 E,X Option82 G!ÇÈ *><ăG!ÐÛG!!M6F¼ ÓÃ</EEG!Ð >ÐÛ<G!Ä

Ð,Õ!5BÐ -

Ð < CLASS G!5BÃ -

CLASS ÐDrNÐ0Ð50Ð0

class-remark	CLASS

-

< CLASS

-

CLASS

ip dhcp class	CLASS

-

3.42 service dhcp

DHCP **service dhcp** **no**

DHCP

service dhcp

no service dhcp

-	-

DHCP

<

IP DHCP

3.43 show dhcp lease

?U/ DHCP v9k,X/4zp EXEC Q **show dhcp lease**

show dhcp lease

	-	-

Ѣ*Ð Vpù IP Ð X4 IP Ð¹ IP ,X4™

/4ß,X@?%KEÜÄ

+!‰	Aß
ip address	ß!4- DHCP v0ÃX IP Ä
Detection Method	0U”#ß
dhcp excluded ipaddress	fy8ß

Q	EÄ
clear ip dhcp conflict	#Ù8 DHCP 0UA)

-

3.46 show ip dhcp server statistics

?U/ DHCP á<,XÀ?AuDBÈü EXEC Q **show ip dhcp server statisticsÄ**

show ip dhcp server statistics

Đ	EÄ
-	-

-

(M*ã

AÃ) DHCP á<!,XØM4?AuDBÄ

ß **show ip dhcp server statistics ßgÎ6Ä**

```
5XLMLHVKRZSGKFSVHUYHUVWDWLVWLFV
/HDVHFRXQW
6GUHVVSROV
XWRPDWLFELQLQ
0DQDOELQLQ
([SLUHGELQLQ
0DOIRUPHGPHVVDHV
0HVVDH5HFHLYHG
2275(48(67
+&'62(5
+&5(48(67
+&(&1(
+&5(/(6(
+&1)250
0HVVDH6HQW
```

```
22275(3/<
+&2))(5
+&&
+&1$
```

/4 !%

+!‰	A
Lease count	4/4zÐ
Address pools	4Ð
Automatic bindings	7 4,XD,Â
Manual bindings	4,XD,Â
Expired bindings	E 4,XD,Â

```
5HVHW
1DN
HFOLHQW
5HOHDVH
,QIR
'HG

LUHFWLRQXQW
5[FOLHQW
5[FOLHQWXQ
5[FOLHQWEUR
7[FOLHQW
7[FOLHQWXQ
7[FOLHQWEUR
5[VHUYHU
7[VHUYHU
```

/4§§2!‰¥ÉXÄ

+!‰	A£
Cycle mode	cycle mode !E¤ ¢ >< ></*ü
Rx client/ uni/ bro	¢ client y,Xy[D/)Ð/ SÐ
Tx client/ uni/ bro	¥ÕÕ client ,Xy[D/)Ð/ SÐÄ
Rx server	¢ server y,Xy[DÄ
Tx server	¥ÕÕ server ,Xy[DÄ

ÏÎGÇ

Ç	£Ä
clear ip dhcp relay statistics	**ô8** DHCP)Á4AuDBÄ

ÏGÄ

-

4.2 ip helper-address

G!5BUDP Sy[4Ez@¥X,ÂXá‹Ä ü no EÝM*9ô8 UDP Sy[4Ez@¥X,ÂXá<Ä

ip helper-address *address*

no ip helper-address [*address*]

ÏDAè

Ð	Ez Ä
address	6B UDP Sy[4Ez@¥X,ÂXá<ÐÐ yÕ 20 µ<Ä

ï5,Õ!5BÐ ùÓ!5B UDP Sy[4Ez@¥X,ÂXá<

ïÐ yG!5BÄ

Ï*Ð ÃÐG!5BÔ 20 µÂXá<Ïp4Ez@¥X,ÂXá<ÿG!5B,X, µ

Z UDP-Helper s6Ãyy,XÛ UDP 0ÃSy[ÐÐEÃyG!5B

,X,ÂXá<Ä

S*ü **no ip helper-address** Ez@y[ÛÂÄ

Ï!5B_Ð MI6,X_G!5B UDP Sy[4Ez@¥X,ÂXá<Ö

5XLMLHFRQILSKHOSHUDGGUHVV

ÏÎGÐ

Ð	Ez Ä
ip forward-protocol	6BLÔ4Ez@ UDP 0Ã

Ï!Äè -

4.3 udp-helper enable

udp-helper enable Ð| UDP Sy[,X4Ez@¥6Ñ **no udp-helper enable** ÐÉ

UDP Sy[,X4Ez@¥6Ñ

5,ÐDP Sy[,X4Ez@GK(Õ

udp-helper enable

no udp-helper enable

ÏDAè

Ð	Ez Ä
-	-

ï5,Õ!5BÐ 5,Õ UDP Sy[,X4Ez@GK(Õ

ïÐ <G!5Bã

Ï*Ô Ô UDP-Helper ,X4Ez@¥6ÑAxÍ 69,53,37,137,138,49 ,X UDP Sy[E> 4Ez@Ä

Ï!5B_Ð MI6,X_$ UDP 4Ez@¥6Ñ

5XLMLHFRQILJXGSKHOSHUHQEOH

ÎÏGÐ	Ò	Ë
	ip forward-protocol	**udp** **BLÔ4Ez@** UDP 0Ã

ÏÄÐ -

5 DHCPv6

5.1 clear ipv6 dhcp binding

?U#Ù8 DHCPv6 4¥µÇÆËÏ*ü **clear ipv6 dhcp binding** Ø

clear ipv6 dhcp binding [*ipv6-address*]

ÐAê	Ð	Ë
	ipv6-address	IPv6 ê4Ô

Ï5,Õ!5BÐ -

Ø (Mã

Ï*ô *ipv6-address* DHCPv6 4¥µÇ *ipv6-address*

Ù8 DHCPv6 4¥µÇ,X_Ï

ÎÇ	Ò	Ë
	-	-

ÏÄê -

5.2 clear ipv6 dhcp client

?Uÿ DHCPv6 v0ÆÏ*ü **clear ipv6 dhcp client** Ø

clear ipv6 dhcp client *interface-type interface-number*

ÐAê	Ð	Ë
	interface-type *interface-number*	*y2*2ó

Ï5,Õ!5BÐ -

Ø (Mã

Ï*ô **clear ipv6 dhcp client** DHCPv6 v0Æ0Ò<0ÃË!

5BµÇÄ

Ï¤G!5B_Ð

```
5XLMLHFOHDULSYGKFSFOLHQWYODQ
```

ÏÎGÐ

-	-

ÏGÄÐ -

5.3 clear ipv6 dhcp conflict

DHCPv6 v0Ã#7Ð, IPv6 0UÈK Decline y[È DHCPv6 Server Ëy[,X #ï0UKÐ#ï0UKÐXÉG!ÑU#ÙÐ DHCPv6 Server ,X† 0UÇÈË*ü **clear ipv6 dhcp conflict Ð**

clear ipv6 dhcp conflict {*ipv6-address* | *}

ÐAÐ

ipv6-address	IPv6 ÐÂ
*	,X IPv6 ÐÂ

5,Õ!5BÐ -

Ð (Mã

Ô*Ð Qpû* ÐÈ</#Ù8,X IPv6 0UÐÂQpûÐ *ipv6-address*Ð# *ÐûØUÇ*

Ï¤G!5B_Ð

```
5XLMLHFOHDULSYGKFSFRQOLFW
```

ÏÎGÐ

show ipv6 dhcp conflict	**/0UÇÄ**

ÏGÄÐ -

5.4 clear ipv6 dhcp relay statistics

#Ù8!A'Ô DHCPv6 Relay s6ÐOy[Ð#AuÈ*Q

clear ipv6 dhcp relay statistics

ÐAÐ

-	-

ï5,Õ!5BÐ -

ïÐ (Mã

ïS*Ôð EÊA§ÇÙ8A'Û DHCPv6 Relay ,ÌGØOy[¾ÄuÄ

ïG!5B_Ð #Ù8 DHCPv6 Relay Agent 4²AuÇCQÄÙ8Q> ÈÊ4²Au/ÆÖ
¢ 0 ÆÖu1kÆÖ
5XLMLHFOHDULSYGKFSUHODVWDWLVWLFV

ïÎGÐ

Q	Ê.Ä
show ipv6 dhcp relay statistics	**/4²Au**

ïGÄÆ -

5.5 clear ipv6 dhcp server statistics

?U#Ù8 DHCPv6 á<4²AuÇÈÊ*ü **clear ipv6 dhcp server statistics** Ø
clear ipv6 dhcp server statistics

ÐAÆ

Ð	Ê.Ä
-	-

ï5,Õ!5BÐ **-**

ïÐ (Mã

ïS*Ôð #Ù8 DHCPv6 á<4²AuÇ

ïG!5B_Ð #Ù8 DHCPv6 á<4²AuÇ,X_Ö
5XLMLHFOHDULSYGKFSVHUYHUVWDWLVWLFV

ïÎGÐ

Q	Ê.Ä
-	-

ïGÄÆ -

5.6 dns-server

?UG!5BDHCPv6 Server ,X DNS Server ë<Çu(@HFO'2CrSll A3á<4²ÃÖ¼ÊÊÙX -4248 r1CF233/TT0>1D001D041D94TjTT

Ï PâíTr T Ð

no dns-server *ipv6-address*

ÐAÐ

Ð	ÆÄ
ipv6-address	DNS Server ,X

ipv6 dhcp pool	DHCPv6

no ipv6 dhcp client pd

	prefix-name	IPv6
	rapid-commit	

!4

yG!5B

Vp DHCPv6 DHCPv6
ipv6 dhcp client pd DHCPv6 Server client
!4 IPv6
rapid-commit GK+A two-message GK+
solicit rapid-commit

```
```

clear ipv6 dhcp client	DHCPv6	
show ipv6 dhcp interface	/ DHCPv6	

Ï!5B_Ð î DHCPv6 Server G!5BÇ4,XÕ$ Ö

```
5HOHDVH
5HOHDVH
5HOHDVH
```

ÏÇÐ

Ç	Ë
ipv6 dhcp server	DHCPv6 Server s6Ñ
show ipv6 dhcp pool	/ DHCPv6 4Ç

ÏÄÐ -

5.11 ipv6 dhcp relay destination

?U*ü DHCPv6 relay !5B#ÇE@¥X,ÂÀË*ü **ipv6 dhcp relay destination**

S*ÀÐ no 6 8E 6 8E

ipv6 dhcp relay destination *ipv6-address* [*interface-type interface-number*]

no ipv6 dhcp relay destination *ipv6-address* [*interface-type interface-number*]

ÐÀÐ

Ð	Ë
ipv6-address	

```
3001::2
```

	ipv6 dhcp pool	DHCPv6
	show ipv6 dhcp interface	DHCPv6

-

5.13 prefix-delegation

?UG!5BDHCPv6 Server ,XM- **prefix-delegation** **no**

prefix-delegation *ipv6-prefix/prefix-length client-DUID* [*lifetime*]

no prefix-delegation *ipv6-prefix/prefix-length client-DUID* [*lifetime*]

ipv6-prefix/prefix-length	IPv6
client-DUID	DUID
lifetime	

DHCPv6 G!5B

1u) **prefix-delegation** IAPD |G!5B

client-DUID IAPD

DHCPv6 Server request

server

	ipv6 dhcp pool	DHCPv6
	ipv6 local pool	
	prefix-delegation pool	DHCPv6
	show ipv6 dhcp pool	/ DHCPv6

-

5.14 prefix-delegation pool

5.17 show ipv6 dhcp conflict

?U/ DHCPv6 ,XtUQÈËü **show ipv6 dhcp conflict Q**

show ipv6 dhcp conflict

ËÐAê

Ð	Ë
-	-

ËÕ!5BÐ -

ê Ø (Mã

ËÔ / DHCPv6 Server ,XtUQÄ

Ë!5B_Ð ß DHCPv6 tUQ,X_Ô

```
5XLMLHVKRZSYGKFSFRQOLFW
GHFOLQG
GHFOLQG
GHFOLQG
GHFOLQG
GHFOLQG
GHFOLQG
```

ÌÈQ

Q	Ë
clear ipv6 dhcp conflict	**ê8tUQÄ**

ËÄê -

5.18 show ipv6 dhcp interface

?U/ DHCPv6 yQÈËü **show ipv6 dhcp interface Q**

show ipv6 dhcp interface [*interface-type interface-number*]

ËÐAê

Ð	Ë
interface-type *interface-number*	*y2Q2ó*

ËÕ!5BÐ -

ê Ø (Mã <ã yã

ËÔ Vpù Ð *interface-type interface-number* DHCPv6 yQ pbØ

interface-type interface-number yQÄ

5XLMLHVKRWSYGKFSLQWHUIDFH	
9/$LVLQHUYHUPRGH	

```
6ROLFLWUHFHLYHG
5HTXHVWUHFHLYHG
5HQHZUHFHLYHG
5HELQGUHFHLYHG
5HOHDVHUHFHLYHG
HFOLHQWUHFHLYHG
5HODLRUHSOLHGUHFHLYHG
,QIRUPDWLRQUHTXHVWUHFHLYHG
8QVXSSRUWHGPHVVDJHWSHUHFHLYHG
(UURUPHVVDJHUHFHLYHG

&YSDFNHWVHQW
&YHUWLVHVHQW
5HSOLHVHQW
5HODUHSOLHVHQW
6HQGUHSO\HUURU
6HQGSDFNHWHUURU

,QLWDWLVWLFV
,QIRUPHQUDWHG
,$DVVLJQHG
,$SROOHG

&RQXUDWLRQWDWLVWLFV
&YVHUYHULQWHUIDFH
&YSRRO
&YLDSGELQLQ
```

ÏÎGĘ	Ę	ĘÄ
	ipv6 dhcp pool	**6Bþ** DHCPv6 ‴Ä

ĞÄê -

6 DNS

6.1 clear host

?U#Ù8|Ðê<ÊM*ê> AÇÐ

clear host [*host-name*]

ËÐAêð

Ð	ÊÄ
host-name	êÐ¿ÐÇÄ" ><#Ù8<F¦ÐÇç †

ËÞ,Õ!5BÐ -

ËÐ (M*ê

ËS*Ð 4¢<,XÐ),Þ8Ö

ÊÊ› ip host ê ipv6 host M-Õ!5B×

ÊÊ› DNS |Ø4,Ä> AÇÐ8!ÊÊ› DNS |Ø4,XÐ),Ä

ËG!5B_Ð G!5BÈ8áP 4¢<|Ø4,XÐ) Ä

FOHDUKRVW

ÏÎGÐ

Ç	ÊÄ
show hosts	**/** DNS ,ÙG!5BÇÄ

ËGÄêð -

6.2 ip domain-lookup

| DNS E> ¤dÄ*AÇX no EÍMMGKÁ DNS ¤ds6Ñ

ip domain-lookup

no ip domain-lookup

ËÐAêð

Ð	ÊÄ
-	-

ËÞ,Õ!5BÐ 5,Ø¤ DNS ¤ds6Ñ

ËÐ <G!5Bê

Ï*Ô AÇ DNS ¤ds6|XÔÈ> AÈ DNS E> ¤dÄ

Ô!5B_Đ M6,X_Ô DNS ¤ds6|XÔ
5XLMLHFRQ1SGRPDLQRRNXS

ÎÔÈ

Ç	Ê
show hosts	/ DNS ,Ô!5BÇ

Ô¤Ä -

6.3 ip host

AÈ!5Bă IP ,X¤*AÇX no EÍMÎ8ë<Ä
ip host *host-name ip-address*
no ip host *host-name ip-address*

Đ¤

Đ	Ê
host-name	*A¤*
ip-address	*A¤* IP

Ï,Õ!5BĐ -

È Ç <G!5Bã

Ï*Ô |Vp?UÎ8ë<Ê **no ip host** *host-name ip-address* È

Ô!5B_Đ 5XLMLHFRQ1SKRVWVZWFK

ÎÔÈ

Ç	Ê
show hosts	*/* DNS ,Ô!5BÇÄ

Ô¤Ä -

6.4 ip name-server

AÈ!5Bă<,X IP/IPv6¤!5Bă<!6Ñ> |Ð¤*AÇX
no EÍMÎ8G!5B,Xă<
ip name-server {*ip-address* | *ipv6-address*}
no ip name-server [*ip-address* | *ipv6-address*]

Đ¤

Đ	Ê

ip-address	éý×	IP
ipv6-address	éý×	IPV6

Ï5,Õ!5BÐ 5,ÛÕ!5Béá<

Ïð <G!5Bã

Ï*Ûð #ï DNS Server ,X IP/IPv6 Æ> E5ÐÊÑÎÛ DNS Server ÐÛ
þ Server 9 Server ÆÕ DNS AÐ7.Bñ!6Ä
2ïÛ 6 á<Ä8 DNS Server ÐþÛZ ip-address ê ipv6-address ÐÐ
ô8Û,Xá<Ð8,Ý DNS á<Ä

Ï!5B_Ð 5XLMLHFRQILSQPHVHUYHU
5XLMLHFRQILSQPHVHUYHU
ÐIIHHIP

ÏÛÐ

Q	ÆÄ
show hosts	**/** DNS ,Ï!5BÛÄ

Ï!ÄÐ -

-

6.6 show hosts

/ DNS ,XG!5B
show hosts [*hostname*]

7 FTP Server

7.1 debug ftpserver

Ô FTP á<,XAA¡ÐEgÊ*ÀÇX no 6ÊKÁA¡ÐEgÃ

ËÐ	<G!5Bã
Ŝ*Ð	' FTP á<*ÊÈ› FTP v0Åý È> [ÊÇ0Ä

ftp-server topdir FTP FTP

```
5XLMLHFRQQHFWSVHUYHUSDVVZRUGSDVV
ê
5XLMLHFRQQHFWSVHUYHUSDVVZRUGSDVV
_ 2ÐÐ¥)G!5BÞõÕ 8001Ö
5XLMLHFRQQHFWSVHUYHUSDVVZRUG
_ 3ÐÐ¥)#¥õÕ!5BÖ
5XLMLHFRQQHFWSVHUYHUSDVVZRUG
```

Ï©Ç	
-	-

Ï©Ä | -

7.4 ftp-server timeout

G!5BFTP ˆÀ¿X0NK£Ä session idle timeout Ê*ÀQX no 6ÍNK£ÊAxÃ0 éÅ

ftp-server timeout *time*

no ftp-server timeout

Ð	
time	0Þ3600 Å

Ï,Õ!5BÐ TAxÊ$ 30 éÄ

Ï | <G!5BÄ

Ï*Ð G!5BFTP ˆÀ¿X0NK£Äp!ÀÐ,XÊ¥ÏÝ]ÐÄ0NK£Æ FTP á<
GÃxEÿ4ÈÊ*¡XEÿÄ

FTP FTP FTP
FTP 0

Ï!5B_Ð _ 1ÐÐ¥)G!5B0NK£Ê 5 éÖ
5XLMLHFRQQHFWSVHUYHUWLPHRXW
_ 2ÐÐ¥)6ÍNK£ÊAxÃ0 éÖ
5XLMLHFRQQHFWSVHUYHUWLPHRXW

Ï©Ç	
-	-

默认视图 -

7.5 ftp-server topdir

L$ FTP v0ÃÑ> [ÆÏm0,X,JÂ8Æ*ÄÇX no 6ÐDi/U!6v0Ã“KÂ FTP á u<Þ[ÆÄ

ftp-server topdir *directory*

no ftp-server topdir

缺省级别

Ð	ÆÄ
directory	FTP v0ÃÑ> 0,XNJÂ

视图 TAxNJÂ'5B

缺省用户 <G!5Bã

缺省 FTP á<NJÂ8Z0Ã)Ã“KÂX[Ã8ÆVO!7.BÛNJÂ6Ã} FTP v0Ã“KÂ FTP á<ÞX[ÆÄ 8*tÚG!5BAÇTP v0Ã“KÂ<Þ[ÆÄ

G!5B_Đ _ 1(B¥)| FTP á<1$0ÃÑ“KÂ syslog $JÖ

```
5XLMLHFRQIWSVHUYHUWRSGLUVVORJ
5XLMLHFRQIWSVHUYHUHQDEOH
```

_ 2(B¥)#\JÂXG!5BÖ

```
5XLMLHFRQIWSVHUYHUWRSGLU
```

ÎÎGÇ

Ç	ÆÄ
-	-

默认级别

7.6 ftp-server username

G!5BFTP á<,X,O)*ã*ÄÇX no 6#*G!5BÄ

ftp-server username *username*

no ftp-server username

缺省级别

Ð	ÆÄ
username	,O)*å

视图 TAx*å

缺省用户 <G!5Bã

	G!5Bv0ÃOL FTP á<ÊÛu,X*ÃÛÃO)ÊÛÊ!7.B,X*ãÕÑ ,O)Ä *ÛSz 64 þ0ÈÈÛÊNÃ8Å+!ÃD+?pÛÄ FTP á<ÛÕ!5BÛÄ
	FTP

	_ 1ÛV)G!5B*á userÖ 5XLMLHFRQIWSVHUYHUXVHUQPHXVHU _ 2ÛV)#*6!5BÖ 5XLMLHFRQIWSVHUYHUXVHUQPH

	Ã
	-

	-

7.7 show ftp-server

	/ FTP á<,X,È(ÕÄ **show ftp-server**

	Ã
	-

	-

	(M*ã
	/ FTP á<,X,È(ÕÛ á<ú Û[Ë?ÄÈG IP Port Å ÛÝBE?Ä>ÛG IP Port Å ![ÊgO_ á<,O)*ÛÕ!5BÅ á<N,JÂ Â0NKÛÄ'5B

Ï!5B_Ð ß¥)¡ß FTP á<,X,Ì(õÖ

```
5XLMLHVKRZWSVHUYHU
IWSVHUYHULQRUPDWLRQ

HQEOH<
WRSGLU
WLPHRXWPLQ
XVHUQPHFRQ3
SDVVZRUGFRQ3
WSH¼1$<
FRQQURFRQFW<
IWSVHUYHULS SRUW
IWSFOLHQWLS SRUW
SRUWGDWDFRQFW<
IWSVHUYHULS SRUW
IWSFOLHQWLS SRUW
SDVVLYHGDWDFRQFW1
```

ÏÎGÐ

Q	EÄ
-	-

ÏGÄß -

8 FTP CLIENT

8.1 copy ftp

ªV¥(B,X CLI)WBE› **copy ftp** Ð-[ÊgÄ ØS*ü FTP Client á<[Ê
EQ'ÐMEg9Q **copy ftp:url flash:url** E>ÈÐQ **copy flash:url ftp:url** í
Ñ0ÐÄ

copy ftp://*username*:*password*@*dest-address* [/*remote-directory*]/*remote-file*

flash:[*local-directory*/]*local-file* [**vrf** *vrfname*]

copy flash:[*local-directory*/]*local-file* **ftp:**//*username*:*password*@*dest-address* [/*remote-directory*]/*remote-file* [**vrf** *vrfname*]

ÐAÐ

Ð	EÄ
username	,O) FTP Server ,XBÐSzL$ 40 +8VÐ Ã @Ã / 0N1+0Ð9
password	,O) FTP Server ,XBÐSzL$ 32 +8VÐ @Ã Ã / 0N1+0Ð9
dest-address	A“KÂX FTP Server ,X IP
remote-directory	ÐX FTP Server Þ[ÊÃÐSzL$ 255 +8VÐN [+0Ùp0NÈ</ FTP á<!0CÃ
remote-file	Ð[ÐzL$ 255 +8VÐN[+0ú
local-directory	Ð[ÊÐÂ[ÊÐA[ÊÃÊÊÐ[Ð0Ñ /ÐÐ 255 +8VÐN[+0ú
local-file	ÐÐ 255 +8VÐN[+0ú
vrfname	Ù VRF á

Ð,Õ!5BÐ -

Ð (M*ã

Ð*Ð S*ü **copy ftp**:*url* **flash**:*url* ÐÐ
S*ü **copy flash**:*url* **ftp**: *url* ÐÐ

Ð!5B_Ð tá user Õ pass Þ 192.168.23.69 ,X FTP Server ,X root ,Ð[Ê
remote-file ,X[Ê'Ô home ,Ð,X[Ê local-file

```
5XLMLHFRSI\WSXVHUSDVV#URRWUHPRWHILOHIODVKKRPHORFDOILOH
```

A'Ô home ,Ð,X local-file [Ê FTP Server ,X root ,ÐÊ remote-file

```
5XLMLHFRSI\ODVKKRPHORFDOILOHIWSXVHUSDVV#URRWUHPRWHILOH
```

ÏÐÐ

Ð	EÄ

copy tftp	tftp #AE> [g

vrfname	VRF IP

IP

9

9.1 ping

AşĐ#A54%XEEĘĘ}*AĂ54%XEEĘĘÂÎĘĘÖ

ping [**ip**] [*ip-address* [**length** *length*] [**ntimes** *times*] [**timeout** *seconds*] [**data** *data*] [**source**



Q	Ä
-	-

-

9.2 ping ipv6

ping [**ipv6**] [*ip-address* [**length** *length*] [**ntimes** *times*] [**timeout** *seconds*] [**data** *data*] [**source** *source*]]

Đ	Ä
ip-address	IPv6
length	**z**
times	
seconds	
data	**B**
source	IPv6 V::1

5, 2 / 5 100Byte ,XDB IP

(M*

Ping ipv6 ping ipv6 ping ipv6 s6 M* ping ipv6 ,X=)s6 ping ipv6 s6 *(M* 2 / 5 100Byte ,XDB IP 1(1(1(,XDBY• A XDBYG!È) ping ipv6 s6 M*) ping ping ipv6 s6 AuC DNS G!5BF

_ 1 ping ipv6 ,Xr_Ö

```
5XLMLHSLQSY
6HQLWH,&3(FKRHVWRWLPHRXWLVVHFRQV
SUHVVWVUOWREUHDN!

6XFFHVVUDWHLVSHUFHQWURQWULSPLQYPD[ PV
```

_ 2 ping ,Xr_Ö

```
5XLMLHSLQSYOHQVKQVLPHVWLPHRXWDWDIIIIVRXUFH
```

IP 61.154.22.36 ,

traceroute

5XLMLHWUDFHURXWH
SUHVVWOWREUHDN!
7UDFLQJKHURXWHWR
PVHFPVHFPVHF
PVHFPVHFPVHF
PVHFPVHFPVHF

PVHFPVHFPVHF
PVHFPVHFPVHF
PVHFPVHFPVHF
PVHFPVHFPVHF
PVHFPVHFPVHF

```
H
H


H
```

ÏÎGÐ

Ò	ÐÄ
-	-

ÏGÄê

-

9.4 traceroute ipv6

;> **traceroute ipv6 ÑòÙ¹ÁÐBÙ¾ÐÉ¿Ú½**

traceroute [**ipv6**] [*ip-address* [**probe** *number*] [**timeout** *seconds*] [**ttl** *minimum maximum*]]

ÐAê

Ð	ÐÄ
Ip-address	*ò* IPv6 ¶Á
number	*ò¿ÐÐG*
seconds	*òCÐ*
minimum maximum	*òÐ* TTL

Ï,Õ!5BÐ

-

Ïê

(M*ã

Ï*ô

Traceroute ipv6 Ò*ò5¼¾ÐÉ¿Ò¼Lp¹¿ÐBÄ¿XLp¹¿ÐBÄ

Ø*S*á6ÑÑ6BáÈBAÐ× DNS G!5BFÐ¼

Ï5B_Ð

ñ*ü traceroute ipv6 ,XÐÐ¼Eý+EÐÐ¼Eý,ü5Ö¾ÐîX™

Ø‰

_ 15Ö¾ÐEîX traceroute ipv6 _ÐÐ

```
5XLMLHWUDFHURXWHLSY
SUHVV&WUOO&WREUHDN!
7UDFLQJKHURXWHWR
PVHFPVHFPVHF
PVHFPVHFPVHF
PVHFPVHFPVHF
PVHFPVHFPVHF
```

M6,X4ÐÑÀÐ?UA“KÂ IP 3004::1 ,XÐ¼DBÈÑÐE¿Ø5%

GÄ É ÐZ'A5Ö8C,XÊÈÍÐ5¼ÐÐM2¹(XÄ

_ 2Ö¾Ö5Ö¾ÐîX traceroute ipv6 _ÐÐ

```
5XLMLHWUDFHURXWHLSY
SUHVV&WUOO&WREUHDN!
7UDFLQJKHURXWHWR
```

■
■
■

■

■ IP 3004::1 ,XÈ■■DBÈÑÑE■5%

G■ É ■■ 4 Ì■pÄ

ÏĈG■		
	Q	E■Ä
	-	-

Ï■GÄ■ -

10 TCP

10.1 ip tcp mss

A’5BÛŸ TCP E²,X MSS ,XÞ**ip tcp mss** no 6ã!8NM G!5BÄ

ip tcp mss *max-segment-size*

no ip tcp mss

ËDAê

Ð	ÆÄ
max-segment-size	MSS ,XÞ)!+8VÈ

Ëõ,Õ!5BÐ

Ëð <ã

Ës*û **ip tcp mss** TCP E²,X MSS ,XÐ,XE²#,X MSS

MSS G!5BAÇ UG!5BÄ

ËG!5B_Ð 5XLMLHFRQ1SWFSPVV

ÌGÇ

Ç	ÆÄ
-	-

ËGÄê -

10.2 ip tcp not-send-rst

?U/U!6Í TCP 0 ’,Xy[¥Õ reset y[**ip tcp not-send-rst**

X no 6ã!8NMG!5BÄ

ip tcp not-send-rst

no ip tcp not-send-rst

ËDAê

Ð	ÆÄ
-	-

Ëõ,Õ!5BÐ Í TCP 0 ’,Xy[¥Õ reset y[

Ëð <ã

Ï*Đ ÔÈ‰ TCP õú TCP yÊRÁy[2,X TCP E¿Fw]Ô reset
y[*ú0Ã TCP E¿ÁÊÍÇ£X0Á,X TCP y[Á’Ê> ÆE›
!8Ñ!6ÔÁ’,Xy[ÆÕ reset y[Ä

ÏG!5B_Đ 5XLMLHFRQILSWFSQWVHQUVW

ÏÎGÑ

Ñ	Æ Ä
-	-

ÏGÄè -

10.3 ip tcp path-mtu-discovery

?U*ü TCP ,XCÃÊg)(PMTU) ¥s6ÃÊ*ü **ip tcp path-mtu-discovery** S Ä
*Á Ñ no 6Ã!8NMG!5BÄ

ip tcp path-mtu-discovery [**age-timer** *minutes* **| age-timer infinite**]

no ip tcp path-mtu-discovery

ÐAè

Đ	Æ Ä
age-timer *minutes*	TCP ¥ PMTU Æ > v#,XÊÈhÄÃÊ 10-30Ã,Õ 10Ä
age-timer infinite	TCP ¥ PTMU Èy#Ä

Ï,Õ!5BÐ GKÁ PMTU ¥s6Ñ

Ñ <ã

Ï*Đ TCP ,XCÃÊg)¥s6Ñ RFC1191 r)„XÈÞ6Ñ5%XÿÑ[Ü
S*ü TCP 9MGÆgûDBÆs6ÃÆg0KÄ
EÞ6ÑX*ÆGKÃ4Æ,X TCP E¿ÃÊ0,X TCP E¿*Ñ
Í IPv4 ` IPv6 ,X TCP Ã
Ý RFC1191 ,XÆÃCP ¥ PMTU Èh0ÃÊ*ÞX MSS 9v#„X PMTUÄ-
ÊÈhS*Đ **age-timer 9**Ñ PMTU !¨ TCP E¿0Ã0,X MSS ã
Æ’ÊÃ!5BÊÈhÊ¥X PMTUÆ PMTU E’ MSS ,XÈÙü
0!6EÞÊÈÞ#E›0!6Ñ!6EÞÊÈ*ü **age-timer infinite ÐÄ**

ÏG!5B_Đ 5XLMLHFRQILSWFSSDWKPWXGLVFRYHU\

ÏÎGÑ

Ñ	Æ Ä
show tcp pmtu	/ TCP E¿,X PMTU

ÏGÄè -

State	TCP E¿¹!,X(ß 11 /ß(Ñ CLOSEÐ¿¹Ø LISTENØß SYNSENTÐYN y[ß‰ SYNRCVDÐYN y[¿ß‰ ESTABLISHEDÐ¿¹ØÝ FINWAIT1ÜÃß FIN y[FINWAIT2ÜÃX FIN y[ABxBAx CLOSEWAITÜÃX FIN y[LASTACKÜÃX FIN y[ÜÃX FIN y[CLOSINGÜÃX FIN y[ÜÃA¹ FIN y[,X ACK y[9! ÜÃX FIN y[TIMEWAITÜÃX FIN y[>•BAxÜÃBAxZ,X FIN y[

ÏÎGÐ		
	Q	Ä
	-	-

ÐGÄß -

10.7 show tcp pmtu

¦ß TCP ,X PMTU ,XÄ

show tcp pmtu

ÐAß

Foreign Address	E0 M6,XD+0 !V“2002::2.23” 192.168.195.212.23” ,X “23”0
PMTU	PMTU ,X

Q	Ä
Ip tcp path-mtu-discovery	TCP ,X PMTU 6Ñ

-

10.8 show tcp port

/2 TCP 0

show tcp port

TCB	! TCP {+¥,,X!5B
Foreign Address	E²ý0,ÃX
Port	E²ý0,ÃX0ÊÃ
State	TCP E²ý!,X(ÕÕ 11 /ÊÃ(ÑÕ CLOSED: E²ý0Ê LISTEN(ÊÕ SYNSENTÕSYN y[ÃÊ‰ SYNRCVDÕSYN y[ýÊÃ!‰ ESTABLISHEDÊ²ýØÊÝ FINWAIT1ÜÃÊ FIN y[FINWAIT2ÜÃK FIN y[4Ê•BAx CLOSEWAITÜÊ,ÃX FIN y[LASTACKÜÊ,ÃX FIN y[ÊÃ²K FIN y[CLOSINGÜÃK FIN y[ÊÃA¹ FIN y[,X ACK y[9! Ê,ÃX FIN y[TIMEWAITÜÊ,ÃX FIN y[>•BAxÊÃ4ÊBAxý,X FIN y[

ÏĈĢĘ	Ą	ĘÄ
	-	-

ĊĠÄÊ -

-

1. SNMP
2. RMON
3. NTP
4. SNTP
5. SPAN
6. RSPAN

1 SNMP

1.1

ÏGÄ5BÐ MI6,X/_ SNMP ,XÐÂuÇÖ

```
5XLMLHVRRZQS
RVVLV)
6103SDFNHWLQXW
6103MUVLRQUURUV
8QQRRPXQQPH
,OOHJDORSHUDWRUFRPPXQQPHVXSSOLHG
RGLQHUURUV
1XPEHURIUHTXHVWGURSULDEOHV
1XPEHURIOWUHGURSULDEOHV
HWHTXHVW38V
HQ[38V
6HWHTXHVW38V
6103SDFNHWRXW8XW
7RREJHUURUV0D[LPXPSDFNHWL]H
1RVXFQPHUURUV
GGOXHUURUV
HQUDOHUURUV
5HSRQH38V
7UDS38V
6103JOREDOWDSGLVDEOHG
6103ORJJLQGLVDEOHG
6103DJHQQEOHG
```

ÏÎGÐ

Ç	ÉÄ
snmp-server *chassis-id*	SNMP 2ÏÎ3ÉË

ÏGÄÐ -

1.3 snmp trap link-status

ÄÕyG5BÉÕy¡X LinkTrapsÈ6Õpy Link Õ
SNMP Ù LinkTrap,ÐÄÇX **no** ÍM SNMP Ù LinkTrapÄ

snmp trap link-status

no snmp trap link-status

ÐÐ

–D	ÉÄ
-	-

Ï,ÕGÕ5BÐ 5,ÐÐ6Õpy Link Õ SNMP Ù LinkTrapÄ

Ð yG5BÄ

ÏÊÎ Íyþÿÿ Ap yÃ SVI yÆQ5BÆÕy;X LinkTrapÈ6Ñ
Vpy¥ Link Õ SNMP Ÿ LinkTrap,Æ

ÏG5BÐ _ 1Ø6G5BÓ5By¥ÆÕ Link trapÖ
5XLMLHFRQILJLIQWHUIDFHJLJDELWUHQW
5XLMLHFRQILJLIVQSWDSOLQVDXW
_ 2Ø6G5BÓ5By¥ÆÕ Link trapÖ
5XLMLHFRQILJLIQWHUIDFHJLJDELWUHQW
5XLMLHFRQILJLIVQSWDSOLQVDXW

ÏÎGÐ

Ç	ÆÄ
snmp trap link-status	ÈÕy· link trap ,Xs6Ñ
no snmp trap link-status	GÆÕy· link trap ,Xs6Ñ

ÏGÄè -

1.4 snmp-server chassis-id

Ø SNMP ,X2ÏÈÆ5BÇ **snmp-server chassis-idÄÇ** **no 6Æ**
Ï

snmp-server chassis-id *text*

no snmp-server chassis-id

Ïè

–D	ÆÄ
text	2ÏÈÆ[Ê+ê0Ä

Ï,Õ5BÐ cÆ,Õ 60FF60

Ï Ç5Bã

ÏÊÎ

1.5 snmp-server community

SNMP **snmp-server community** **no**
SNMP

ÏG5BÐ ÑM6,X/[ÆÕ SNMP ÊKŒÖ

```
5XLMLHFRQJVQSVHUHMHUQEOHVDSVVQS
5XLMLHFRQJVQSVHUHMRRVWXEOLFVQS
```

ÏÎGÇ

Ç	ÆÄ
snmp-server host	û SNMP

ÏGÄê -

1.8 snmp-server group

ØA5B SNMP ¤ÆÆÆG5BÇ **snmp-server groupÄÇ** **no 6ê¤Ä**

snmp-server group *groupname* { **v1** | **v2c** | **v3** { **auth** | **noauth** | **priv** } } [**read** *readview*] [**write** *writeview*] [**access** { **ipv6** *ipv6-aclname* | *aclnum* | *aclname* }]

no snmp-server group *groupname* { **v1** | **v2c** | **v3** {**auth** | **noauth** | **priv**} }

ê¤ê

–D	ÆÄ
v1	**v2c** |**v3**	û SNMP Ä
auth	A¼˜Xfg,XÆLÔPÀÐBáÔ¼ v3 Ø
noauth	A¼fg,XÆáÔPÀÐB3áÔ¼ v3 Ø
priv	**A¼gÔAg¼** v3 Ø
readview	**6ÔÔ**
writeview	6ÔÔ
aclnum	**ÆÔÆ6Ñ** MIB ,X ipv4 NMS 8Æ
aclname	**ÆÔÆ6Ñ** MIB ,X ipv4 NMS 8Æ
ipv6-aclname	ipv6 AÆ6Ô,XÆÃÑ MIB ,X ipv6 NMS 8Æ

ï,Õ5BÐ 5,ÔÝ5B¤˜

Ç ¢5Bã

ïÔ -

ÏG5BÐ ÑM6,X/A5BÔÖ

```
5XLMLHFRQJVQSVHUHMUJURXSMLEXVHUSULYHDGPLE
```

ÏÎGÇ

Ç	ÆÄ
show snmp group	**/** SNMP ÔÇ¼

1.9 snmp-server host

snmp-server host { *host-addr* | **ipv6** *ipv6-addr* } [**vrf** *vrfname*] [**traps**] [**version** { **1** | **2c** | **3** { **auth** | **noauth** | **priv** }] *community-string* [**udp-port** *port-num*] [*notification-type*]

no snmp-server host { *host-addr* | **ipv6** *ipv6-addr* } [**vrf** *vrfname*] [**traps**] [**version** { **1** | **2c** | **3** { **auth** | **noauth** | **priv** }] *community-string* [**udp-port** *port-num*]

–D	E
host-addr	SNMP
ipv6-addr	SNMP ipv6 Å
vrfname	A5B vrf E@
version	E snmp È V1 2C 3
auth | **noauth** | **priv**	**A5B** V3
community-string	3 Å
port-num	snmp 0
notification-type	E snmp

5, V LK2O LK2O

SNMP

G5B

A5B **snmp-server enable traps** - NMS E SNMP LK E LK2O 0 vrf E@ , vrf G5B G5B M6,XG5B G V 4, E K, XE 5B K E oG5B O

M6,X/ SNMP SNMP E K

5XLMLHFRQJVQSVHUHUVXEOLFVQS

Q	E
snmp-server enable traps	

-

1.10 snmp-server location

A5B SNMP ,X2 5B **snmp-server location** **no** -s 5B 1643 1 1 0 2 5 3 4 1

–D	Ë
text	Ë

Ë
SNMP

Ë	Ë
snmp-server contact	SNMP

1.11 snmp-server net-id

1.12 snmp-server packetsize

snmp-server packetsize *byte-count*

no snmp-server packetsize

byte-count	484 +8V 17876 +8V

1472 +8V

-

SNMP 1492

5XLMLHFRQQJVHUYHUSDFNHWVL]H

snmp-server queue-length	SNMP

-

1.13 snmp-server queue-length

snmp-server queue-length *length*

length	1 1000

10

4

5XLMLHFRQQJVHUYHUXHXHOHQJWK

snmp-server packetsize	SNMP

-

1.14 snmp-server system-shutdown

snmp-server system-shutdown **no**

SNMP

snmp-server system-shutdown

no snmp-server system-shutdown

-	-

SNMP

reload/reboot NMS

SNMP

-	-

8 5 9 5 . 2

RUIJIE-TRAP-FORMAT-MIB.mib

SNMP v1	Trap

1.17 snmp-server trap-timeout

snmp-server trap-timeout *seconds*

no snmp-server trap-timeout

–	
seconds	– 1000

30

-

-

1.18 snmp-server udp-port

snmp-server udp-port *port-num*

no snmp-server udp-port

–	
port-num	SNMP

161

SNMP

-

-

-	-

-

1.19 snmp-server user

snmp-server user *username groupname* {**v1** | **v2c** | **v3** [**encrypted**] [**auth** {**md5** | **sha**} *auth-password*] [**priv des56** *priv-password*]} [**access** {**ipv6** *ipv6-aclname* | *aclnum* | *aclname*}]

no snmp-server user *username groupname* {**v1** | **v2c** | **v3** }

username	
groupname	
v1 | **v2c** | **v3**	SNMP v3
encrypted	16 MD5

2 RMON

2.1 rmon alarm

rmon alarm *number variable interval* {**absolute** | **delta** } **rising-threshold** *value* [*event-number*] **falling-threshold** *value* [*event-number*] [**owner** *ownername*]

no rmon alarm *number*

number	1-65535
variable	1~255 entry.integer.instance OID 1.3.6.1.2.1.2.1.10.1
interval	12147483647
absolute	
delta	
rising-threshold *value event-number*	*value* -2147483648~+2147483647 *event-number* 0-65535
falling-threshold *value event-number*	*value* -2147483648~+2147483647 *event-number* 0-65535
owner *ownername*	*ownername* 1~64

-

variable absolute/delta owner interval rising-threadhold/falling-threadhold event

MIB ifInNUcastPkts.6

5XLMLHFRQJUPRQODUPGHOHWHULQWHUVRO IDOOLQJWKUHVKROGRZQHUVDQ

rmon event *number* [**log**] [**trap** *community*]	

[**description** *description-string*] [**owner** *owner-string*]	

缺省级别 -

2.2 rmon collection history

视图 接口视图

缺省级别 2：system

格式 **rmon collection history** *index* [**owner** *ownername*] [**buckets** *bucket-number*] [**interval** *seconds*]

no rmon collection history *index*

参数

参数	描述
index	指定RMON历史统计组的索引，取值范围为1~65535
owner *ownername*	指定拥有者的名称，*ownername*表示拥有者的名称，为1~64个字符的字符串，区分大小写
buckets *bucket-number*	指定为此历史统计组申请的采样间隔内部存储空间，*bucket-number*表示申请的采样间隔内部存储空间，取值范围为1~65535
interval *seconds*	指定采样间隔，*seconds*表示采样间隔，取值范围为1~3600，单位为秒

缺省级别 -

描述

视图

缺省级别

格式

参数

缺省级别 -

2.3 rmon collection stats

	–D	Ä
	index	4 ,X2 -65535
	owner *ownername*	*ownername* 1~64

-

yG5B

-

1 ,X4 Ä

[*event-number*] [**owner** *ownername*]	

-

2.6 show rmon event

show rmon event

–	–
-	-

-

-

-

```
5XLMLHVHRZPRQHYHQW
UPRQHYHQWEOH
LQHU[
GHVFULSWLRQIQFDVHWW
WH
FRPPXQLWPRQ
ODVWLPH6HQWRV
```

–D	ÆÄ
-	-

-

(Mã

-

Æ¾Au¸ÇÖ

```
5XLMLHVRZPRQDLWVWFV
HWUVDLWVWFDEOH
LQH[
LQUIDFH DVWUHQW
RU ]RQVDQ
VDXV
GURSHQW
RFHW
SNW
EURDGFDVWNW
PXOWLNW
FUFDLQURUV
XQHU6L]H3NW
RU6L]H3NW
IUDJPHQW
MDEEHUV
FROOLVLRQ
SDFNHW2FHW
SDFNHW7R2FHW
SDFNHW7R2FHW
SDFNHW7R2FHW
SDFNHW7R2FHW
SDFNHW7R2FHW
```

Q	ÆÄ
rmon collection stats *index* [**owner** *ownername*]	¡ÊAu¼M

-

3 NTP

3.1 debug ntp

/ NTP AA¢ÇÄ

debug ntp

no debug ntp

Ï-DAèð

–D	ÉÄ
-	-

ï5,Õ5BÐ 5,ÕÁ

ïÇ (Mß

ïõ ?ÐE> NTP s6ÑAÆÉA¢Ç¿gÐ'¼XAA¢ÇÈ>LpA¥L8Ä

ïG5BÐ Ê NTP AA¢Ç

5XLMLHFRQJGHEXJ

ïÎGÇ

Ç	ÉÄ
-	-

ïGÄè

3.2 no ntp

GÁ ntp ¤áÈ5ê,×Ê8 ntp ,XÉ5BÇÄ

no ntp

ïè

–D	ÉÄ
-	-

ï5,Õ5BÐ 5,õ NTP áGÁ

ïÇ G5Bã

ïõ 5,õ NTP s6ÑÁ¿GÉ5BZ NTP áê NTP]A¢ NTP s6Ñ

Ê

ïG5BÐ G5BÑGÁ NTP á

5XLMLHFRQJJ

ÏĊĢ	Ç	Ł Ä
	ntp server	**ûĵĵ** NTP á<

ĠÄå **-**

3.3 ntp access-group

G5B NTP á,XA **no 6** 5

ntp access-group { **peer** | **serve** | **serve-only** | **query-only** } *access-list-number* | *access-list-name*

no ntp access-group {**peer** | **serve** | **serve-only** | **query-only**} *access-list-number* | *access-list-name*

Ï-DA	–D	Ł Ä
	peer	**ÁÍ** NTP á
	serve	**AÍ** NTP á
	serve-only	**AÍ** NTP á
	query-only	**AÍ** NTP á

Á NTP

ip access-list	Î IP A[

ĠÄ -

3.4 ntp authenticate

G5B NTP

ï5,Õ5BÐ	ù§ý

ïÐ	€5Bã

ÏÐ	G5B«AA«ðyÈGÝù	md5 E¾tðyÝÐX	key-id ÛðÈÃ	**ntp**
trusted-key Ú¹	key-id ñ,Xðyä5Bðyä
ðyÞ$	1024 ðÐyÄ

ïG5BÐ	ð5BÐ	ID	6 ,XAAðyÖ
5MBQQQHRRRRS

ÏGÐ

Ç	Ë
ntp authenticate	**ðý**
ntp trusted-key	**6ð**

ïGÄð	-

3.6 ntp disable

GñÝyy	NTP y[,Xs6Ñ
ntp disable

Ï-DAð

–D	Ë
-	-

ï5,Õ5BÐ	5,ÿÐÑk«	NTP y[

ïÐ	yG5Bã

ÏÐ	5,ÿÐ¾X	NTP y[FÑ4¬0Ã¾ðsA«ÈEA5BEþ6Ñ
ñyÞX	NTP y[Ä

IP

ïG5BÐ	G5BÈñy	NTP y[Ö
5XLMLHFRQJ

ÏG7b»JÀ$ÐÀ ÃðXÐQXDÐ4-ÿcVVðÆ21y['ÀÑÇ@ ¾e4@ÐVVE–Ý

3.7 ntp master

A5BÊs0 NTP Ês– 5 4 no 6ã

NTP ÊsA5BÄ

ntp master *[stratum]*

no ntp master

–D	ÊÄ
stratum	1 15 8 1 Ax 8Ä

5, 5B NTP Ês s6Ñ

5B

4 b5 L p1s5à

5B 4 s DDÈ, Ês E 0Ä

ō Ŏ

5B Ês– 5 4 A5BJÊsD 12Ä

Q	ÊÄ
-	-

-

3.8 ntp server

NTP v0 NTP á

ntp server *ip-addr* [**version**

version	*ßß* NTP ,XÄ-3 ÊÄAGü NTPv3 (<
if-name	*ßßÇ* NTP y[,Xßyÿ¾Ä
keyid	*ßßáäß*
prefer	**ßßhä2¼³** Prefer á<

ï5,Õ5BÐ 5,ÛÝG5B NTP áÄ

ïÇ GG5BÃä

ÏßÊ ,Ä¾2¼ßÕÃáÉ0ÇÃ¾0äáÆ$ 20 Ç¾

ÛE>ã,>XtÈÇÐ¿LÔA5Bt¤yÿÇÃh,X3yá

uÇyÿÇÃä,>XtÈÇÐã,>XtÈÇÛúÇÊX<

t¤yÿÇy

¡ÇÃBÈÃ½ prefer ÊsE>ß

G5B NTP ÆÇÛ[,Xßy¡XÊÄAßÇ5B,XyÑÛOG5BZ IP ,XJÑÄ NTP á

uÈ¡îXyÄ

ÏG5BÐ GG5BÈ5B5¼ßXAÛ NTP serverÄ

,3YG5BÇÖXLMLHFRQJÇVHUYHU

,3YG5BÇÖXLMLHFRQJÇVHUYHU

ÎÏGÇÐ

Ç	ÆÄ
no ntp	**ßß** NTP ás6Ñ

ÏGÄÇß -

3.9 ntp synchronize

È> NTP rßÊÄ

ntp synchronize

no ntp synchronize

Ï-DAÇß

–D	ÆÄ
-	-

ï5,Õ5BÐ -

ïÇ GG5Bã

ÏßÊ NTP ÇÆÈ>XñßE¼ÁX 8 ÿ[ÈhÛs,XßÆÁÈßÇ,XÈ

LhßÇpLÔ6ÇßÊÄÇÐ

ÏG5BÐ GG5BÈ> NTP rßÊÖ

Ç

ÏÎGĘ

Ę	Ę
ntp server	**ûñô** NTP á< JE∋

ĞÄå

-

3.10 ntp trusted-key

ñô ID ń,Xȝ̈yG5Bå̈yÄ

ntp trusted-key *key-id*

no ntp trusted-key *key-id*

Ï-DAå

–D	Ę
key-id	*ø* IDÄ

ȝ,Ø5BÐ

TÁ**ø**yÄ

Ï¸ÃµÕ5BÐ TA¡ß5Bnè@Êss6Ñ

Ïê¶ ¢5Bã

Ï¸Êõ Sªs6Ñ} NTP v0ÃÆÊs¹¹k9,XÊsÈÀX.@ÊsÄÀX.@
ÊsGSÄÀÂÄÀXÊõÄ¼CD|Ä
5,ÊõÆ5B NTP È@ÊsÄ5BÊ NTP v0ÃÆÊs¹¹ÄÀÊ
ÄÀX.@ÊsÄ

Ï¸5BÐ ÆÄ¥G5B NTP nè@Ês
5XLMLHFRQJXUHSGDWHFDOHQDU

ÏÎGÇ	Ç	ÊÄ
	-	-

Ï¸ÄÄê -

3.12 show ntp status

/ NTP ÇÄ

show ntp status

Ï-DAê	–D	ÊÄ
	-	-

Ï¸Õ5BÐ -

Ïê¶ (Ma

Ï¸Êõ Vp2Ï¼³X NTP áÊX NTP ÇÈÊáÄÐÏ
ÇÄ

4 SNTP

4.1 sntp enable

sntp enable

no sntp enable

–D	Ä
-	-

Disable

Sü **show sntp**

SNTP ,Ò–DÄ

	Ä
show sntp	/ SNTP ,XG5BÕ
clock update-calendar	
clock set	

-

4.2 sntp interval

sntp interval *seconds*

no sntp interval

–D	Ä	
seconds		60 /¦-65535 /Ä

1800s

Sü **show sntp**

SNTP ,Ò–DÄ

sntp enable

5XLMLHFRQJVQWS

Q	Ä
sntp enable	SNTP
show sntp	SNTP ,X,G–D
clock update-calendar	

-

4.3 sntp server

SNTP Server SNTP NTP Server internet NTP Server

sntp server *ip-address*

no sntp server

–D	Ä
ip-address	NTP/SNTP IP

NTP/SNTP

show sntp SNTP ,G–D

5XLMLHFRQJVQWS

Q	Ä
show sntp	SNTP ,XG5B
sntp enable	SNTP

-

4.4 show sntp

SNTP ,X,G–DÄ

show sntp

–D	Ä

-	-

缺省级别 -

视图 Sử **show sntp** ử SNTP ,Ò–D

缺省用户角色 5XLMLHVRRZHU
6173VDGPLQEOH
6173VHUYLFH
6173VHFLQUDO
7LPH]RQH

相关命令

Ọ	Ä
sntp enable	**Ô** SNTP
show sntp	**ß** SNTP ,X,Ò–D

缺省配置 -

5 SPAN

5.1 monitor session

õ SPAN Â±Ù,Â×0ÃÅ0ÃÅ SÅ[Q no EÝM08Â±
ôÀ8Å0ÃX0Ã

monitor session *session_number* {**source** [**interface** *interface-id* | **vlan** *vlan-id-list*] [**both** | **rx** | **tx**] | **destination interface** *interface-id* { **encapsulation | switch** } | **mac** {**source** *mac-addr*| **destination** *mac-addr* } [**both** | **rx** | **tx**] | **filter vlan** *vlan-id-list*} [**acl** *name*]

no monitor session *session_number* [**source**(sse)-4(n)]TJ /TT2 16Tf -0.0019 Tc 0.0005 Tc 09012 Tc 1.4 28 0 Td [(vllion))-(d)2(-

acl

session 1 SPAN session 1

gigabitEthernet 1/1 gigabitEthernet 1/8

show monitor	SPAN

RX TX VSPAN

5.2 show monitor

SPAN

show monitor [**session** *sn*umbeor

6 RSPAN

6.1 monitor session

no RSPAN

monitor session *session_num* {**remote-destination** | **remote-source**}

monitor session *session-num* **destination remote vlan** *vlan-id* **interface** *interface-name* [**switch**]

monitor session *session-num* **source interface** *interface-name* [**rx** | **tx** | **both**]

–D	
session-num	
vlan-id	**remote span vlan id**
Interface-name	

-

end Ctrl+C

exit

show monitor	

-

6.2 remote-span

RSPAN VLAN

[**no**] **remote-span**

-IP

IP CÃÆQÒGYÀ8VÖ

1. #AÇG
2. ECMP/WCMP 1*+9
3. RIP
4. RIPng
5. OSPFv2
6. OSPFv3
7. IS-IS
8. 1*+9CÃ
9. VRF

1

1.1 accept-lifetime

Ð¾ÑyJаÑyбÑÂÑy,Xyе¾X*ð¾Ë*Ç **accept-lifetimeÄÇ no 6**

accept-lifetime *start-time* {**infinite** | *end-time* | **duration** *seconds*}

no accept-lifetime

Ð	ÆÄ
start-time	**ô*¢ÊÊÓÓ** *hh:mm:ss month date year* *hh:mm:ss date month year* *hh*—Ê *mm*—Ú *ss*—/¦ *month*—Ü *date*—¹ *year*—H 5,ÊÓXÓÉÈ Jun 1È993
infinite	**AÊÊÓ**
end-time	*ÓÓÊÊ* *start-time*
duration *seconds*	*bÓ* *start-time* 2147483646

Ð¸,Õ5BÐ ÑyJаÑyÆÝ

Ç ÑyJаÑyG5Bã

Ð*Ê SÐ*ÄÇÑyyе¾X*¢Á

ÐG5B_Ð ÐG5BÈ5BÑy 1 ,Xy*¢<¢ 2000 H 9 Ü 9 ŁÊ• 2011 H 10 Ü 12 ŁÊÄ

```
5XLMLHFRQJNHFKDLQLSNHV
5XLMLHFRQJNHFKDLQH\
5XLMLHFRQJNHFKDLQHDFFHSWOLIHWLPH6HS'HF
```

ÏÎGÇ

Ç	ÆÄ
-	-

ÐGÄÊ -

1.2 ip default-network

ØG5B5,5Õ%4ÆËë*ëG5BQ

permit	**íbGK¥ÆÊÃ**
ip-prefix	*G¥ÆÊÃz¢* 0 32Ä
minimum-prefix-length	*ú¢Ê8è¤XCKÏKSz* **ge**
maximum-prefix-length	*ú¢Ê8è¤X4ÊKSz* **le**

Ï5,Õ5BÐ ùÿ¼Ê<

Ïº <G5Bã

Ï*Ð **ip prefix-list ÇúG5B** IP ¼ÊÄ ¼Ê<*ü permit ÊÙ deny GK+9¼ÊG¦XÿÆ ¼¥„X|0Ä ¼Ê<>*9nbúÇX2'.BGÊ8èÄ ge ÊÙ le GK+*9nÇúG¦X ¼ÇX8èÊÿ4Fg9 ip-prefix È&I#,XGÊG5BXÿpÇÝ ge ÊÙ le GK+È ip-prefix ¤Z'.B,X¼ÊÈXÿpÊ¼g9 geÊ8è minimum-prefix-length 32Ÿ pÊ¼g9 leÊ8è ip-prefix ,X}-ÕSz maximum-prefix-lengthXÿp5ÈÆg9Ê! 8è minimum-prefix-length maximum-prefix-lengthÊÄ ip-prefix }-Õ minimum-prefix-length ` maximum-prefix-length , X G 2 Ï Öip-prefix } - ÕK S z < minimum-prefix-length < maximum-prefix-length <= 32Ä

Ê5B_Ð Í OSPF #AÇ¥ý RIP ÊgÎXCÃÁÇ¥ÝÂX IP E> E¦È¦B6(,X IP ¼Ê ><n(#X¢Ä IP ü201.1.1.0/24 8è,XCÃÇ>ÿÄ

```
5XLMLHFRQJXUHWHUPLQO
5XLMLHFRQJLSSUHIL[OLVWSUHSHUPLW
5XLMLHFRQJURXWHURVSI
5XLMLHFRQJURXWHUGLVWULEXWHOLVWSUHIL[SUHRXWULS
5XLMLHFRQJURXWHUHQ
```

ÏÊG Ç

Ç	ÊÄ
-	-

Ê GÄè -

1.4 ip prefix-list description

Ç¤Ê<#Ï[+ÊÄÊ*ü **ip prefix-list description ÄÇ** **no 6ê8Ô 4ÇÊÄ**

ip prefix-list *prefix-list-name* **description** *descripton-text*

Ä è

Ð	ÊÄ

prefix-list-name	¼ê<á
descripton-text	¼ê<£Ä

Ь,Õ5BÐ ù¥Ï¼ê<[+£Ä

ÿÐ <G5Bã

Ь*Ð -

Ï5B_Ð IP ¼ê<#ï[+£Ä Deny routes from Net-AÄ

```
5XLMLHFRQJXUHWHUPLQO
5XLMLHFRQJLSSUHIL[OLVWSUHGHVFULSWLRQRXWHVIRP1HW$
```

ÎÍÐ

Ç	£Ä
-	-

ÏÄÐ -

1.5 ip prefix-list sequence-number

Ø¼ê<*fcs6ÃÑ*ü **ip prefix-list sequence-number**ÄÐ **no** 6¤Ô ¤fcs6Ñ

ip prefix-list sequence-number

Ð	£Ä
-	-

Ь,Õ5BÐ ù¥¼ê<fcs6Ñ

ÿÐ <G5Bã

Ь*Ð -

Ï5B_Ð ¼ê<*fcs6Ñ

```
5XLMLHFRQJXUHWHUPLQO
5XLMLHFRQJLSSUHIL[OLVWVHTXHQHXQPEHU
```

ÎÍÐ

Ç	£Ä
-	-

ÏÄÐ -

1.6 ip route

Ø0G5BM-ÕÃÀÈË*ëG5BQ ip routeÄÇX no 6ß8Œ5B,XM-ÕÃÄ

ip route [**vrf** *vrf_name*] *network net-mask* { *ip-address* | *interface* [*ip-address*] } [*distance*] [**tag** *tag*] [**permanent**] [**weight** *number*] [**disable** | **enable**]

ïðè

Ð	ÉÄ
vrf_name	Æ VRF
network	*ÊÆ6*
net-mask	*ÊÆÕ*
ip-address	*M-Æ*
Interface	*M-Æ*
distance	*M-ÆÚ*
tag	*M-Æ?Ê•*

¢ -

1.7 ip routing

Ø*ü IP CÃs6ÑÐ AÇÇX no 6ÑKÁ IP CÃs6Ñ

ip routing

no ip routing

¢ÑÐ

Ð	ÆÄ
-	-

Ï5,Õ5BÐ *ü IP CÃ

ÇÐ <G5Bã

Ï*Ð 'A'Ø9yA'ÐÑ¼ VOIP 5%GA'ÐÑØ IP CÃÆ¥ÐÑÑKÁ IP CÃs6Ñ

Ï5B_Ð GKÁ IP CÃs6Ñ

```
5XLMLHFRQILJXUHLSURXWLQJ
```

ÏÎGÇ

Ç	ÆÄ
-	-

ÏÄÑ -

1.8 ip static route-limit

ØG5BM-ÕÃ,X5DÑÈ*üG5BÇ **ip static route-limit**ÄÇ no 6Ã'5B¬

AxCÃ5DÄ

ip static route-limit *number*

no ip static route-limit

¢ÑÐ

Ð	ÆÄ	
number	Ñ	1-10000È,Õ 1024Ä

Ï5,Õ5BÐ Ð5,Õ

ÇÐ <G5Bã

Ï*Ð G5BM-ÕÃDÆ$X,ÂXÇM-ÕÃ,X5DÈE›

ª*Ø3È5B,XM-ÕÃDÆYEA'5B,XÑÈE›

G5BXM2TAxM-ÕÑÄ

ip static route-limit G5BM-ÕÃDÆ$

show running-config Ã

Ï5B_Ð A’5BM-ÕÃD5×

1.11 ipv6 prefix-list sequence-number

Ø IPv6 ¼êº<*fcs6ÑËÊ*ü **ipv6 prefix-list sequence-number** ÔÐÇ **no 6ã** **¾ÖÐfcs6Ñ**

ipv6 prefix-list sequence-number

Ïêϸ

Ð	ÆÄ
-	-

Ï£,Ø5BÐ ù*¼êº<fcs6Ñ

Ê¾Ø

<G5Bã

Ï*Ð

-

ÏG5B_Ð ß$ IPv6 ¼êº<*fcs6Ñ

```
5XLMLHFRQJXUHWHUPLQDO
5XLMLHFRQJLSYSUHIL[OLVWVHTXHQHXQPEHU
```

ÎÖÇ

Ç	ÆÄ
-	-

ÏGÄÊ -

1.12 ipv6 route

ØG5B ipv6 M-ÕÃÆÊ*üG5BÇ ipv6 routeÄÇX no 6ã8ÆÊ5B,XM-ÕÃÄ

ipv6 route *pv6-prefix / prefix-length* { *ipv6-address* | *interface* [*ipv6-address*] } [*distance*] [**weight** *number*]

Ïêϸ

Ð	ÆÄ
ipv6-prefix	IPv6 ¼ÑOFI~ RFC4291 ,X></6ã
prefix-length	IPv6 ¼ÇXKSÑ6ÑOtt#
Ipv6-address	M-ÕÃ,XÖÇ
interface	M-ÕÃ,XÖÇ
distance	M-ÕÃ,X1u)Ó•-

number

¢ <G5Bã

Ï*Ð M-ÕÃ,X5,Õu)ÓÅ• 1ÈÈA'5B1u)ÓÅ[ÕÃ:,XCÃ2M-ÕÃŽ
|ÕÃ:Ê*M-ÕÃËÈA'5BM-ÕÃ,X1u)ÓÅ„4"CÃXÊXM-Õ
CÃÕÃB|CÃX OSPF CÃ#A,X1u)ÓÅ• 110ÊM-ÕÃ,X1u)ÓÅA'5B
125È¦C¥ OSPF ,X4"CÃpÊB#GŽ'ÊM-ÕÃ,X4"CÃ

Ï5B_Ð rtÕ 2001::/64 ,Ê%4;XM-ÕÃÊÇ 2002::2Èu)ÓÅ• 115Ä
LSYURXWH

ipv6 route	G5B ipv6 M-ÕÃ
show ipv6 route	/ IPv6 CÃ><Ä

ËGÄê -

1.14 ipv6 unicast-routing

Ø*ü IPv6 CÃs6ÑêÃ AÇÇX no 6êKÁ IPv6 CÃs6Ñ

ipv6 unicast-routing

no ipv6 unicast-routing

ê

Ð	Ë
-	-

Ëõ,Õ5BÐ *ü IPv6 CÃ

Ëê <G5Bã

Ë*Ð 'A'Ø9yA'ÊØ VOIP 5%GA'ÊØ IPv6 CÃË6ÑêKÁ

IPv6 CÃs6Ñ

Ë5B_Ð GKÁ IPv6 CÃs6Ñ

5XLMLHQLSYXQFDVWURXWLQ

ÌGÐ

Ç	Ë
ipv6 route	G5B ipv6 M-ÕÃ
show ipv6 route	/ IPv6 CÃ><Ä

ËGÄê -

1.15 key

ØðyJÒÊyË9ðyJðyG5BÊ*Ç **key** **no 6ê8Ø**

ÿÄ

key *key-id*

no key *key-id*

ê

Ð	Ë
key-id	ðyJÒxAðy,X IDÊØ-2147483647

Ëõ,Õ5BÐ ðyJðy

Êê ðyJÒ5Bã

Ï*Ð	S*ÄQ3yÄ			
Ï5B_Ð	5BÈ5B3yJÒ	ripkeysæE93yJÒ5Bè5B3y	1æE93y	1 G5BÆ

0	**ô¾ß**
7	**ô¾ß**
text	*ô¾xA¤ú*

Ï¿Õ5BÐ ¾yJô¾ýAxA•

ÏÇ ¾yJô¾yG5Bã

Ï*Ðî S*ÄÇô¾yÄ

ÏG5B_Ð ¢G5BÈ5B¾yJÒ ripkeysÈ¯9¾yJÒ5BÈ5B¾y 1È¯9¾y 1 G5BÈn¾y
abcÄ

```
5XLMLHFRQJNHFKDLQLSNHV
5XLMLHFRQJNHFKDLQH\
5XLMLHFRQJNHFKDLQHNHVWULQDEF
```

ÎÏGÇ

Ç	Ë¢Ä
-	-

ÏÄÈ -

1.18 match interface

²ÐGÔÕÇyÈ AË*ÐÃÒ5BÇ **match interface**ÄÇ **no** 6È8Œ **5B¾**

match interface *interface-type interface-number* [*…interface-type interface-number*]

no match interface [*interface-type interface-number* [*…interface-type interface-number*]]

È

Ð	Ë¢Ä
interface-type	*y2O*
interface-number	*y4Ë*

Ï¿Õ5BÐ -

ÇÐ CÃÒ5Bã

Ï*Ðî **match interface Ç6ÐÄ**
CÃÐÃÆ7ÐÃÆ7Xs6ÑÐ OSPF CÃ¾XCÃG¡
Ñî RIP CÃÑÐ RIP CÃ¾XCÃGÑî OSPF CÃÄ
ÐÃGÑÆÐCÃÐoute maps ÅXh*ÐÃKÈXCÃ¸ì¯> ý
ÐX{ÐÃÒ5BÃ 1 ÐX **match** Ç 1 ÐX **set** Ç
ÜÝ **match** ÈÝpÜÝ **set** ÐÄ
CÃÒXG5BÝl#Ë*ÐÃGÝ*+9CÃ¸XG5BÝuV)h*ÐÃÈG5Bs
)ÔXÆÖXÇ5ÆSà*ÐÃGÑXCÃ#Aḥ*ÐÃÐ

Ï

ĬG5B_Đ G5B OSPF CÃ#AGý RIP CÃÈZQÇ fastethernet 0/0 ,X RIP CÃÄ

```
5XLMLHFRQJURXWHURVSI
5XLMLHFRQJURXWHUUHGLVWULEXWHULSVXEQWVURXWHPDSUHGULS
5XLMLHFRQJURXWHUQWR2UNDUHD
5XLMLHFRQJURXWHUH[LW
5XLMLHFRQJURXWHPDSUHGULSSHUPLW
5XLMLHFRQJURXWHPDSPDWFKLQWHUIFHIDVWHWKHUQW
```

ÏĞĢĐ

Ç	ÉÄ
match ip address	**GAÎ**
match ip next-hop	**GAÎÇ**

Ï*Ð **match ip address** ¸Q6Ã¸Ã¸Ã¸Ã

CÃ¸Ã¸ÃE7¸Ã¸ÃE7¸Xs6ÃÃ OSPF CÃ¸XCÃG¡

éî RIP CÃ¸ÃÃ RIP CÃ¸XCÃG¸éî OSPF CÃ¸Ã¸Ã¸X,Ì

fG¸Ã IP CÃ#AĶÈ> Ä

ÚÃG¸ÃEÚÃ¸Ã¸ute maps Åxh*¸ÃÃ¸KÈXCÃ¸Ìé> ý

Ê{¸ÃÃ¸5B¸Ã 1 ¸X **match** Ç 1 ¸X **set** ¸Ã¸p

ùÝ match ¸ÇÝ¸pùÝ **set** ¸Ä

CÃ¸XG5BÚl#Ã*ÚÃG¸*+9CÃ¸XG5BÃuV)h*ÚÃ¸G5Bs

)ÚXÈÚ¸XÇ¸ÃÃSà*ÚÃG¸ÃKCÃ#Aĥ*ÚÃÈ

J6Ã*¡X¸Ã

Ï5B_Ð G5B OSPF CÃ#AĢÚ RIP CÃÈ¸ÚÚ"KÂ< 10 ,X RIP CÃÈ OSPF CÃÈ

AÈCÃ¸X2O_ÈÈCÃ type-1Ã£ 40Ä

```
5XLMLHFRQJURXWHURVSI
5XLMLHFRQJURXWHUUHGLVWULEXWHULSVXEQWVURXWHPDSURHGULS
5XLMLHFRQJURXWHUQWR2UNDUHD
5XLMLHFRQJURXWH[LW
5XLMLHFRQJDFFHVVOLVWSHUPLW
5XLMLHFRQJURXWHPDSURHGULSSHUPLW
5XLMLHFRQJURXWHPDSPDWFKLSDGGUHVV
5XLMLHFRQJURXWHPDSVHWPHWULF
5XLMLHFRQJURXWHPDSVHWPHWULFWSHWSH
```

ÏÏG¸Ç

Ç	Ã
access-list	**nA**
match interface	**GCÃ¸Ç**
match ip next-hop	**GA¸ÇÇ**
match ip route-source	**GA¸ÇCÃ**
match metric	**GC¸ÃG£**
match route-type	**GC¸Ã2O_**
match tag	**GC¸Ã**
set metric	**A5BG¸ÃG£**
set metric-type	**A5BG¸Ã2O_**
set tag	**A5BG¸Ã**

ÏGÄ -

1.20 match ip next-hop

Ç¸G¸Ç IP 0Ú"KÂ<¢ê<?X,Ê%4CÃÈCÃÒ5BÇ **match ip next-hop**Ä¸Ç **no** 6Ã8Ã5BÄ

match ip next-hop { *access-list-number* [*access-list-number...* | *access-list-name...*] |

access-list-name [*access-list-number...* | *access-list-name*] | **prefix-list** *prefix-list-name* [*prefix-list-name...*] }

no match ip next-hop [*access-list-number* [*access-list-number...* | *access-list-name...*] | *access-list-name* [*access-list-number...* | *access-list-name*] | **prefix-list** *prefix-list-name* [*prefix-list-name...*]]

ÏêÐÅ

Ð	ÉÄ
access-list-number	*AÐÊ<Ë* ÊÌ"KÊ<ËÈ99 È300-1999 =)A"KÊ<ËÈ00-199 È2000-2699
access-list-name	*AÐÊ<á*
prefix-list *prefix-list-name*	*ØÁKÊ<á*

Ï¿ÕÑ5BÐ -

ÏÇ CÁÀÒ5BÄ¾

Ï*ÐÔ **match ip next-hop** ÇÖ6ÕÊÞÄÊÙÙÊ

CÁÇÐÕÁE7ÒÇÞÕÁE7ÒXs6ÑÌ ÙÑÌ OSPF CÁE7ÒÇÚ

ÞÕÁE7ÒXs6ÑÌÙÑÌ OSPF CÁ³XCÁGÞÎî RIP CÁÈÃ

Ú RIP CÁ³XCÁGÞÎî OSPF CÁÑÃ,X,ÌGÞK IP CÁ#A,

KÈ> Ä

ÒÁGÞÆÉÒÁÕute maps ÅXh*ÞÃ¤KÈXCÁ,ÌÉ> Ý

ÞX{ÞÃÒ5BÞÆ 1 ÞX **match** ÇÖ 1 ÞX **set** ÇÖÞ

ÙÝ match ÇÖÝÞÙÝ **set** ÞÖÄ

Ï¿5B_Ð G5B OSPF CÁ#AÇÚ RIP CÁÆÄ RIP CÁ,XÔÇÖÙ"KÊ< 10 ê 20È OSPF

AÒÉÇÚÌ

```
5XLMLHFRQJURXWHURVSI
5XLMLHFRQJURXWHUUHGLVWULEXWHULSVXEÇÖWVURXWHPDSUHGULS
5XLMLHFRQJURXWHUÇÖWZURUHD
5XLMLHFRQJURXWH[LW
5XLMLHFRQJDFFHVVOLVWSHUPLWKRVW
5XLMLHFRQJDFFHVVOLVWSHUPLWKRVW
5XLMLHFRQJURXWHPDSUHGULSSHUPLW
5XLMLHFRQJURXWHPDSPDWFKLSÇÖ[WKRS
```

Ï¿ÇÖ

Ç	ÉÄ
access-list	**nAÊ**
match ip address	**GAÞÊ**
match interface	**GCÁÒÇ**
match ip route-source	**GAÞÊCÃ**
match metric	**GCÁÇÉ**
match route-type	**GCÁÒO_**

match tag	GC‚ÃÛ„
set metric	A5BGÐ¿ÃGŁ
set metric-type	A5BGÐ¿Ã2O_
set tag	A5BGÐ¿ÃÛ„

ÏGÄÐ -

1.21 match ip route-source

ÐGÐ¿ÃÐ IP 0Ð“KÐ<ÐÐ<?X‚Ð%4CÃÈCÃÒ5BQ **match ip route-sourceÄÐ no 6Ð8ÐÐ5BÄ**

match ip route-source { *access-list-number* [*access-list-number...* | *access-list-name...*] | *access-list-name* [*access-list-number...* | *access-list-name*] | **prefix-list** *prefix-list-name* [*prefix-list-name...*] }

no match ip route-source [*access-list-number* [*access-list-number...* | *access-list-name...*] | *access-list-name* [*access-list-number...* | *access-list-name*] | **prefix-list** *prefix-list-name* [*prefix-list-name...*]]

Ðð

Ð	Ł Ä
access-list-number	*AÐ<Ë*
access-list-name	*AÐ<á*
prefix-list *prefix-list-name*	*ÐÐ<á*

Ï‚Õ5BÐ -

Ð CÃÒ5Bã

Ï*Ð **match ip route-source Ð6ÐÐ**

CÃÐÐÃE7ÐÐÃE7Ð‚XsÐÐ OSPF CÃ³XCÃG¡

Ð RIP CÃÐÐ RIP CÃ³XCÃGÐî OSPF CÃÐÐÃ‚X‚Ì

fGÐ IP CÃ#AÐÈ> Ä

ÐÃGÐÐCÃÐ route maps ÅXh*ÐÐÃ³KÐXCÃ‚Ìé> 5

ÐX{ÐÐÃÒ5BÃ 1 ÐX **match Ð** 1 ÐX **set Ð**

Ð **match ÐÐ** Ð **set ÐÄ**

Ï5B_Ð G5B OSPF CÃ#AÐ RIP CÃÐÄ RIP CÃ‚XCÃÐ IP 0Ð“KÐ< 5È OSPF AÐE GÐ

```
5XLMLHFRQJURXWHURVSI
5XLMLHFRQJURXWHUUHGLVWULEXWHULSVXEQWV5XLMLHFRQJURXWHURXWHPDSUHGULS
5XLMLHFRQJURXWHUQWR2UNDUHD
5XLMLHFRQJURXWHU[LW
5XLMLHFRQJDFFHVVOLVWSHUPLWKRVW
5XLMLHFRQJURXWHPDSUHGULSSHUPLW
5XLMLHFRQJURXWHPDSPDWFKLSURXWHVRXUFH
```

ÏĈGĘ

Ę	ĖÄ
access-list	**nAß**
match ip address	**GA**
match interface	**GC**
match ip next-hop	**GA**
match metric	**GC**
match route-type	**GC2O_**
match tag	**GC**
set metric	**A5BG**
set metric-type	**A5BG2O_**
set tag	**A5BG**

ĖGÄß -

1.22 match ipv6 address

nØGÁ"Kß<¢êÔ<AQŒ,Ù IPv6 5%4ŒÃÆÈË*ŒÃÒ5BĘ **match ipv6 address**ÄĘ **no 6ß8Á5BÄ**

match ipv6 address { *access-list-name* | **prefix-list** *prefix-list-name* }

no match ipv6 address

ßß

Ð	ĖÄ
access-list-name	*A<á*
prefix-list *prefix-list-name*	*Ø IPv6 ¼Ô<á*

Ь,Õ5BÐ -

ę CÃÒ5Bã

Ь*Ù Ù route map ,X sequence ßÑÙ IPV6 ACL×

Route map ,X sequence 5,ŒË 10×

IPv6 PBR sßÑ prefix-list ÔS*È,ÆÐãÄ

CÃŒÙÃE7ÙÙÃE7ÙXs6ÑÙ OSPF CÃ¡XCÃG¡

áî RIP CÃÈÙ RIP CÃ¡XCÃGáî OSPF CÃŒÃ,X,Ì

fGßK IP CÃ#AĶÈ> Ä

ŒÃGßÆEŒÃÙoute maps ÅXh*ßÃĶÈXCÃ,ìÁ> Ý

ÊX{ÙÃÒ5BÃ 1 ÞX **match** Ę 1 ÞX **set** Ę

ü Ý match ę**Ý**pü Ý **set** ß Ä

CÃ,XG5BÁl#Ê*ŒÃGÞ*+9CÃ,XG5BÁuV)h*ŒÃÈG5Bs

)ÔXÆÔ)XĘ,ÃÆSà*ŒÃGßXCÃ#Aḥ*ŒÃÈ

J6Ñ*¡XĘ,ÃÄ

¶ G5B OSPF CÃ#AÇ¼Ù RIP CÃÐÈ¿ÓÚ“KÊ< v6acl ,X RIP CÃÈ OSPF CÃ³
ÊÉ£ 30Ä

```
5XLMLHFRQJLSYURXWHURVSI
5XLMLHFRQJURXWHUUHGLVWULEXWHULSVXEQWVURXWHPDSUHGULS
5XLMLHFRQJURXWHUH[LW
5XLMLHFRQJLSYDFFHVVOLVWYDFO
5XLMLHFRQJLSYDFOSHUPLWLSYDQ
5XLMLHFRQJLSYDFOH[LW
5XLMLHFRQJURXWHPDSUHGULSSHUPLW
5XLMLHFRQJURXWHPDSPDWFKLSYDGGUHVVYDFO
5XLMLHFRQJURXWHPDSVHWPHWULF
```

ÏÎGÐ

Ò	Ë Ä
ipv6 access-list	**n** IPv6 A“KÊ<?
match interface	**GC ÃÔÇ**
match ipvGC ÃÔÇpÔ	

Ïâê

Đ	Ë.Ä
access-list-name	*Aß<á*
prefix-list *prefix-list-name*	></Ø,X IPv6 ¼Ê<á

Ь,Õ5BĐ -

Ïê CÃÒ5Bã

Ь*Ð CÃ¡ÐÃE7Ø¢ÐÃE7[¡Xs6ÑÑ OSPF CÃ¡XCÃG¡ é¤î RIP CÃ¤Ñ RIP CÃ¡XCÃGêî OSPF CÃ¢ÃX,Ì fGÊK IP CÃ#AĶÈ> Ä

ÐÃGÊE€ÐÃute maps ÅXh*ÊÃĶÈXCÃ,Ìé> ý ÊX{ÊÃÒ5BÊ 1 ÞX **match Ò** 1 ÞX **set ÏêÞ** **üÝ match ÈÒÝpüÝ** **set ÊÄ**

CÃ¡XG5Bú#Ê*ÐÃGÞ*+9CÃ,XG5BÚuV)h*ÐÃÈG5Bs

)ÒXÈÐ¡XÐ¢ÊSà*ÐÃGÊXCÃ#Aḥ*ÐÃÐ

J6Ñ*¡XÐ¢Ã

Ï5B_Đ G5B OSPF CÃ#AÐÞ RIP CÃÈÈ¢ÞÚ“KÊ< v6acl ,X RIP CÃÈ OSPF CÃ³ ÊÉ 50Ä

```
5XLMLHFRQJLSYURXWHURVSI
5XLMLHFRQJURXWHUUHGLVWULEXWHULSVXEQWVURXWHPDSURHGULS
5XLMLHFRQJURXWHUH[LW
5XLMLHFRQJLSYDFFHVVOLVWYDFO
5XLMLHFRQJLSYDFOSHUPLWLSYDQ
5XLMLHFRQJLSYDFOH[LW
5XLMLHFRQJURXWHPDSURHGULSSHUPLW
5XLMLHFRQJURXWHPDSPDWFKLSYURXWHVRXUFHYDFO
5XLMLHFRQJURXWHPDSVHWPHWULF
```

ÏÎG¢Ð

Ð	Ë.Ä
ipv6 access-list	**n** IPv6 A“KÊ<?

1.25 match metric

ØGCÃ¸XGÆÈ*ÄÑÒ5BÇ **no 6ß8Æ5BÄ**

1.26 match origin

ØGÁ"Kê<AQ£96¶,XCÃÆËË*CÃÒ5BQ **match originÄÐ** **no 6ê8 ÁÉ5BÄ**

match origin { **egp** | **igp** | **incomplete** }

no match origin [**egp** | **igp** | **incomplete**]

Ä¬ê

Ð	ÆÄ
egp	**96ÆE0Ã** EGP
igp	**96¶X** IGP
Incomplete	**96¶ê2O_**

Ï5,Õ5BÐ -

Ð CÃÒ5Bã

Ï*Ê **ÆÑÔ96¶,XCÃÆËË!96¶2O_Ä**
AÇA'5BG¦XCÃ96¶,X5Ê

Ï5B_Ð -

ÎGÐ

Ç	ÆÄ
match metric	**GCÃG£**
match origin	**GCÃ¶¥**
set metric	**A5BGÐÃG£**
set origin	**A5BGÐÃ2O_**

ÏÄÊ -

1.27 match route-type

ØGCÃ,XCÃ2O_ÈË*CÃÒ5BQ **match route-typeÄÐ** **no 6ê8ÁÉ5BÄ**

match route-type { **local | internal | external** [**type-1 | type-2**] **| level-1 | level-2** }

no match route-type [**local | internal | external** [**type-1 | type-2**] **| level-1 | level-2**]

Ä¬ê

Ð	ÆÄ
local	***ÐCÃ**
Internal	OSPF ,XYFÇÃ
external	ÊÇÃ(BGP ê OSPF ,XÊÇÃ)
type-1	**type-2**	OSPF ,X2O_ 1 ê2O_ 2 ÊÇÃ
level-1	**level-2**	ISIS 1 ê 2 CÃ

Ï5,Õ5BÐ

ÏÒ CÃÒ5Bã

Ï*Ð CÃ Ã E7 Ã E7 Xs6 OSPF CÃ³XCÃG¡
é RIP CÃ RIP CÃ³XCÃGé OSPF CÃ X,Ì
fG K IP CÃ#AÈ> Ä
CÃG EE CÃ route maps Xh* ÃK XCÃ,Ì> ý
X{ ÃÒ5B 1 X **match** Ò 1 X **set** p
ü **match** ÒÝp ü **set** Ä

Ï5B_Ð G5B RIP CÃ#AG OSPF CÃRIP OSPF CÃ³XYF CÃÄ

```
5XLMLHFRQJURXWHUULS
5XLMLHFRQJURXWHUUHGLVWULEXWHRVSIURXWHPDSUHGULS
5XLMLHFRQJURXWHUQWR
5XLMLHFRQJURXWHU[LW
5XLMLHFRQJURXWHPDSUHGULSSHUPLW
5XLMLHFRQJURXWHPDSPDWFKURXWHWSHLQWHUQO
```

ÏÒÐ

Ò	Ä
access-list	**n**
match ip address	**G**
match interface	**GC**
match ip next-hop	**GA**
match ip route-source	**GA C**
match metric	**GC G**
match tag	**GC**
set metric	**A5BG G**
set metric-type	**A5BG 2O_**
set tag	**A5BG**

ÏÄ**è** -

1.28 match tag

Ø GC X Ë*C Ò5BÒ **match tag** Ä **no** 6 8 5BÄ

match tag *tag* [*…tag*]

no match tag [*tag* [*…tag*]]

è **è**

Ð	Ä
tag	

¶ CÃÀG5Bã

Ï*Ð **match tag ¶6Ê** tagÄ

CÃ¡ÐÃE7GÐÃE7ÐÑ OSPF CÃ³XCÃGÐ

Eî RIP CÃÐÑ RIP

ÏÐ <G5Bã

Ï*Ô G5B1ËÃ5D,X,ÂXÇ1ËÃ,X5DÈÊ› **maximum-paths G5B1ËÃÐ**
***ÚÞÈÈÈÈÈXÓÃÊG5BX1ËÃÊ› **show running**
config Ã5BX1ËÃ
AÇXG5BÍ ipv4 ` ipv6 ªÈÀÈG5BÆÇ'Ô ipv4 ,ÂX,XÐËÃ
X5,ÐAG5BÈ'Ô ipv6 ,ÂX,XÐËÃ5,Ð3AG5BÄ

ÏG5B_Ð A'5B1ËÃÔ 10 5ÈãÎAxÄ

```
5XLMLHFRQJPD[LPXPSDWKV
5XLMLHFRQJÐPD[LPXPSDWKV
```

ÏÎGÇ

Ç	ÊÄ
-	-

ÏGÄÈ -

1.30 route-map

ÐnCÃÐÊ9CÃÒG5BÈÊ*ïG5BÇ **route-mapÄÇ** **no 6È8Ð**
CÐnÄ

route-map *route-map-name* [**permit** | **deny**] [*sequence-number*]

no route-map *route-map-name* [{ **permit** | **deny** } *sequence-number*]

ÄÈ

Ð	ÊÄ
route-map-name	*4ÈÐÔÄÇ* CÃÊ7G5BÇÊÄ¹ áëCÃÒXÐÃÈÇCÃÒ*+9ÐÃÒ 1*+9ÍÐË
permit	**VpnZ** permit GK+ÈÊÜ match n,XGÇÄ set Ç GKÓÃÊ> {x1*+9CÃÈ set ÇBÈÈ> { ÄÊÕÃÒXÐÄ VpnZ permit GK+ÈÊÜ match n,XGÈÐ 1ÐCÃÒ*+9E> Ð,ÆÐeZ set Ç
deny	**VpnZ** deny GK+ÈÊÜ match n,XGÇÄ)ÐÈCÃÒ*+9ÄÊ> CÃGÐ*+9CÃÈÈÕ CÃÒÄ VpnZ deny GK+ÈÊÜ match n,XGÈÐ ÐÃÒ*+9E> Ð,ÆÐeZ set Ç
sequence-number	*ÆÐhÆÄÊ9kSÈÐ ÆÄ*

Ï,ÕG5BÐ 5,ÐXG5BCÃÒ

¢ <G5Bã

Ï*Ð ,Â RGOS ECÊXCÃÒ*ÐÃGÁ*+9CÃÄ

CÃGÁCÃÐÃE7ÐÃE7ÐXs6ÑÑ OSPF CÃ

+³XCÃGÐî RIP CÃÐÑ RIP CÃ³XCÃGÐî OSPF CÃ

ÐÃ,X,ÎGÐ IP CÃ#AÇÈ> Ä

ÐÃGÐEEÐÃÐute maps ¸Xh*ÐÃ*KÈXCÃ,Îé> ý

ÊX{ÐÃÐ5BÐ 1 ÞX **match** Ò 1 ÞX **set** Ðp

üÝ match ÐÝpüÝ **set** ÐÄ

'G5BCÃÊÃÐÈXS*üÔ¾Ð

1Xp1ÎÐÃÒ*+9ÈÐ *sequence-number*Ð 10×

2Xp³ÐÃÒ*+9ÈÐ *sequence-number*Ð9ÆE9Æ

Ð9E> GÐ

3Xp,ÐÃÒ*+9ÐÑÔ²ÎÐÃÄ

Ï5B_Ð G5B OSPF CÃ#AÇÐ RIP CÃÐÐÇÐ 4 ,X RIP CÃÈ OSPF CÃÈÃ

pe-1E2CD5>-7<040E>]TJ/TT2.77Tf-0.0028 Tc 1 Tf7F10F945AF315AF06DD1 1 Tf0.807 0 Td<1 Tf0 Tc 7/TT0 1 Tf4 Ï5

hh—Ê

mm—Ú

ss—/¦

month—Ü

date—¹

year—H

5,[illegible]È Jun 1È

	è 1..20000Ê,Õ 2000Ä
max-suppress-time	ØÕe,ØÃ 8Ê 1..255(Ú)Ê,Õ 4* half-life

Ï,Õ5BÐ -

Ïº CÃÀ5Bã

Ï*Ð SªÄ¸Ç5BG¦XCÃ,XCÃ95ÐÄ

Ï5B_Ð

```
5XLMLHFRQJURXWHPDSWDJ
5XLMLHFRQJURXWHPDSPDWFKDVSDWK
5XLMLHFRQJURXWHPDSVHWGDPSHQQ
5XLMLHFRQJURXWHPDSH[LW
```

ÎGÇ

Ç	ÊÄ
match metric	**GCÃG£**
match origin	**GCÃ¤¥**
set metric	**A5BGØÃG£**
set local-preference	**A5BGØÃ£**

ÏÄè -

1.33 set ip default next-hop

ØÍG! match ÞXDBÛTAxÔÇ IPÆÊ*CÃÀ5BÇ **set ip default next-hopÄ**

AÞ **no 6è8ÉÊ5BÄ**

set ip default next-hop *ip-address* [*weight*] [*…ip-address* [*weight*]]

no set ip default next-hop [*ip-address* [*weight*] [*…ip-address* [*weight*]]]

è

Ð	ÊÄ
ip-address	Ç IP
weight	Ø¡

Ï,Õ5BÐ -

Ïº CÃÀ5Bã

Ï*Ð 5 set ÞÊ¤ ØWCMP BÊÇ5E¤ è2 WCMP BÊÇ5E¤ Ê¤

> ÈÍ¸Ð*Ê g9,X weight DÍ#GÊ> WCMP BÊÇ5Ä

set ip default next-hop Ø6ÊÞ IP ÊÐYE› 32 Þ

Vpü ip address è weight DÊ5BÊYE› 4 ÞX nexthop Ä

next-hop weight set WCMP

WCMP weight nexthop

weight 1

set ip next-hop ` **set ip default next-hop** ÇÜÖ G5BZ **set ip next-hop** Ç2ÏE@

¥Ç5*Ü*9CÃ5BZ **set ip default next-hop** X2ÏÊ¥Ç5*CÃ@

S*5ÇÜn*üA5BÔnTAxCÃs6ÑpECÊÇX¥ÇRE¥@

CÃ¥Ç5BXÔÇ(nexthop) Ä

h*Ü*+9CÃÊÒÜ1*+9CÃS*¡XCÃÊÊÎCÃÊÃÈ61*+94È

ß*+9FÑZ 1 ÞXGÎ0ÊÔn*Ü*+9CÃÊ¥yy,X

Ê> "ÊÜÃÊÜ1*+9,XDBÊ¡XCÃEÊ> ÊÜÃÊÜ

1*+9,XDBÊÜ1*+9n,XÇE> ÊÜ

ÇÃÜ*+9ß set Ä

G5B_Đ Ây· 1 Þ,X¢ 1.1.1.1 ÊXy[ÈpECÊÊÊÊÊÛ 6.6.6.6 ×

5à,X¢ 2.2.2.2 ÊXy[ÈpECÊÊÊÊÊÛ 7.7.7.7 Ä

5XLMLHFRQJDFFHVVOLVWSHUPLW

5XLMLHFRQJDFFHVVOLVWSHUPLW

5XLMLHFRQJLQWHUIDFHDVÇ

5XLMLHFRQJILSSROLFÙRXWHPDSHTXDODFFHVV

5XLMLHFRQJURXWHPDSHTXDODFFHVVSHUPLW

5XLMLHFRQJURXWHPDSPDWFKLSDGGUHVV

5XLMLHFRQJURXWHPDSVHWLSGHIDXOWÇ[WKRS

5XLMLHFRQJURXWHPDSHTXDODFFHVVSHUPLW

5XLMLHFRQJURXWHPDSPDWFKLSDGGUHVV

5XLMLHFRQJURXWHPDSVHWLSGHIDXOWÇ[WKRS

ÎÎGÇ

Ç	Ê Ä
route-map	**nCÃ**
match ip address	**GÀÂ**
set ip next-hop	**A5BÐÇ** IP ÈpCÃ><ÙÃB,XCÃ
set ip precedence	**A5BÐÙ** IP ì

ÈGÄ

-

1.34 set ip dscp

ÐÍG! match ÞXy[A'5B DSCP ÆË*CÃÒ5BÇ **set ip dscp** ÆÇ **no 6** 8

Æ5BÄ

set ip dscp *dscp_value*

no set ip dscp

Æ

Đ	Ê Ä
dscp_value	*AB* IP y[IP DSCP

¶ -

Ð CÃÒ5Bã

Ò*Ð -

Ò5B_Ð -

ÏÒÐ

Ò	ÆÄ
route-map	**nCÃ**
match ip address	**GÀÂ**
set ip default next-hop	**A5BBÐÙÔÇ** IP ÙpCÃ><ÚãB,XCÃ
set ip precedence	**A5BBÙ** IP ì

ÒÄã

1.35 set ip next-hop

IP

Ë¶Ñ

Ñ

ÐÃÒ*+9ß **set ÐÄ**

Ï5B_Ð ü serial 1/0 Þ1*+9CÃÄpy¦y ü 10.0.0.0/8 8ÈY,XD'B ÕÈ

192.168.100.1 5%4° 172.16.0.0/16 8È,XDBÙX#GÈÕ 172.16.100.1Ä

5XLMLHFRQJLQWHUIDFHVHULDO

5XLMLHFRQJLSILSSROLFURXWHPDSORDGEDODQH

5XLMLHFRQJDFFHVVOLVWSHUPLW

5XLMLHFRQJDFFHVVOLVWSHUPLW

5XLMLHFRQJURXWHPDSORDGEDODQHSHUPLW

5XLMLHFRQJURXWHPDSPDWFKLSDGGUHVV

5XLMLHFRQJURXWHPDSVHWLSQ[WKRS

5XLMLHFRQJURXWHPDSORDGEDODQHSHUPLW

5XLMLHFRQJURXWHPDSPDWFKLSDGGUHVV

5XLMLHFRQJURXWHPDSVHWLSQ[WKRS

ÏÎGÑ

Ñ	Ë
route-map	**nCÐ**
match ip address	**GA**
set ip default next-hop	**A5BÐ** IP ÈpCÃ><ú,X CÃ
set ip precedence	**A5BÐÙ** IP ì

Ï**G**Ä**Ð** -

1.36 set ip next-hop verify-availability

Ð**û**.BAx**Ô**Ç IP ,XÃ'È**Ë***CÃÒ5BÑ **set ip next-hop verify-availability**Ä**Ñ**

X no 6ß8É5BÑ1*9CÃ5BÄ

set ip next-hop verify-availability *ip-address* **track** *track-obj-number*

no set ip next-hop verify-availability *ip-address* **track** *track-obj-number*

Ð

Ð	Ë
ip-address	*Ô* IP
track-obj-number	*É*

Ï5,Ñ5BÐ -

Ï**Ñ** CÃÒ5Bã

Ï5*Ô**Ð** -

Ï**G**5B_Ð **û**.BAx**Ô**Ç 192.168.1.2 ,XÃ'È**C**ß54Ë 1Ä

```
¶
¶
```

ÏÎGÐ

Ò	ÐÄ
route-map	**nCÃ**
match ip address	**GÄ**
set ip default next-hop	**A5BBÐ** IP ÈpCÃ><ÙãB,XCÃ
set ip precedence	**A5BBÐÙ** IP ì

ÈGÄ

-

1.37 set ip precedence

ÐÍG! match ÐXy[A'5B IP ,Xì{ÆÈ*CÃÒ5BÒ **set ip precedence**ÄÐ

no 6 G5BX,4ò8 5BÄ

set ip precedence { *number* | **critical** | **flash** | **flash-override** | **immediate** | **internet** | **network** | **priority** | **routine** }

no set ip precedence

Ä

Ð	ÐÄ
number	Ð>< IP ,Xì{Æ 0-7Ä 7Critical 6Flash 5Flash-override 4Immediate 3Internet 2Network 1Priority 0Routine
critical | **flash** | **flash-override** | **immediate** | **internet** | **network** | **priority** | **routine**	IP ,Xì{Ä

È,Ò5BÐ

-

Ð

CÃÒ5Bã

È*Ð

4Æ'5B IP y[,Xì{9S1*+9CÃEÍÃ IP y[E> à{,XÈÃÒ
CÃÒ5BÈ5Bþ **set ip precedence** Ð5BÐ
1*9CÃ**Xy[** IP yFÑ'5Bû,Xì{Ä

È5B_Ð

ý· FastEthernet 0/0 E9,XÐ 192.168.217.68 ,Xy[A'5B precedence 4Ä

```
5XLMLHFRQJFFHVVOLVWSHUPLW
5XLMLHFRQJURXWHPDSQPH
5XLMLHFRQJURXWHPDSPDWFKLSDGGUHVV
```

```
¶
¶
¶
```

ÏĈĢĐ

Ǫ	ĖÄ
match interface	**GĊÃÔǪ**
match ip address	**GÄÂ**
match ip next-hop	**GÄÂÔÇ**
match ip route-source	**GÄÂĊÃ**
match metric	**GĊÃGŁ**
match route-type	**GĊÃ2O_**
match tag	**GĊÃÔ„**
set metric-type	**A5BGØÃ2O_**
set tag	**A5BGØÃÔ„**
set ip tos	**A5B** IP y[,X tos

ĭĠÄȁ -

1.38 set ip tos

ØÍĠ! match ?Xy[A'5By[IP ,X TOSÈĖ*ĊÃÒ5BQ **set ip tosÄĐ no 6**
ÔĠ5BX tos ô8Ķ5BÄ

set ip tos { *number* | **max-reliability | max-throughput | min-delay | min-monetary-cost | normal** }

no set ip tos

ÏȁÔ

Đ	ĖÄ
number	Ø>< IP ,X TOSÔĖ 0-15Ä
max-reliability |	IP ,X¾{Ô+,XĥG2Ö
max-throughput |	max-reliabilityØ
min-delay |	max-throughput4Ø
min-monetary-cost |	min-delayÖ 8
normal	min-monetary-costØ
	NormalÖ 0

ĭ,Õ5BĐ -

Ę Ċ ÃÒ5Bã

ĭ*Ô 4ĖĖA'5B IP y[,X TOS Ĭ*ØØ*+9CÃĖĆÃX IP y[E> ăBGĻXĖÕ
Ø1*+9CÃG¦Xy[IP yFÑA'5BÔ,X TOS Ä

ĠĭB_Đ ý· fastEthernet 0/0 E9,XÔ 192.168.217.68 ,Xy[A'5B tos 4Ä

```
5XLMLHFRQJDFFHVVOLVWSHUPLW
```

```
¶
¶
¶
¶
¶
```

ÏĈĢĐ

Ǫ	Ɛ Ä
match interface	**GĊÃÔǪ**
match ip address	**GA¶Â**
match ip next-hop	**GA¶ÂÔÇ**
match ip route-source	**GA¶ÂCÃ**
match metric	**GĊÃGɛ**
match route-type	**GĊÃ2O_**
match tag	**GĊÃÛ„**
set metric-type	**A5BGØ¶Ã2O_**
set tag	**A5BGØ¶ÃÛ„**
set ip precedence	**A5B** IP y[,X¼{+‰

ĬĠÄȁ -

1.39 set ipv6 default next-hop

ØÍĠ! match ĵX IPv6 y[ûTAx,XÔÇ IPv6ÆĒ*ĊÃÔ5BǪ **set ipv6 default next-hopÄĵǪ** no 6ß8ÆĒ5BĵǪ1*+9CÃG5BÄ

set ipv6 default next-hop *global-ipv6-address* [*weight*] [*global-ipv6-address* t-9(8144709C441C8TT0 1 Tf ( )Tjip)-6(

ÏG5B_Đ ÿ· fastEthernet 0/0 E9,X,ÂX 2001:0db8:2001:1760::/64 ,Xy[A'5BTÂx,XÔÇ 2002:0db8:2003:1::95Ä

```
ÆXMLHÆQ1ISØFFWVDVDFÆEU
ÆXMLHÆQ1ISØFGÆLWSØQE
ÆXMLHÆQÆDSØBIB
ÆXMLHÆQÆDSPDÆKSØGGWVDFÆEU
ÆXMLHÆQÆDSVÆSCHDÆV
GE
ÆXMLHÆQ1ÆFÆVÆV
ÆXMLHÆQ1ILSSÆFÆDSØBIB
```

ÏÎGÇ

Ç	ÆÄ
match ipv6 address	**n1*9CÃGÎ**
ipv6 policy route-map	**ÿh*Î*9CÂ**
set ipv6 next-hop	**A5B1*9CÃÔÇ**

ÏGÄÈ -

1.40 set ipv6 next-hop

ØÍG! match ÎX IPv6 y[ûÔÇ IPv6 ÈËÖ*ÇÃÒ5BÇ **set ipv6 next-hopÄ**

AÈ no 6È8ÉÆ5BÈÑ1*+9CÃG5BÄ

set ipv6 [**global**] **next-hop** *global-ipv6-address* [*weight*] [*global-ipv6-address* [*weight*] ...]

no set ipv6 [**global**] **next-hop** *global-ipv6-address* [*weight*] [*global-ipv6-address* [*weight*] ...]

ÈÈ

Đ	ÆÄ
global	*Çb<Ä*
global-ipv6-address	y[EÈÔÇ IPv6 ÔÇÃ<NOFyCÂ<Ä
weight	*ÈÈÉ* 8

Ï,Õ5BĐ -

ÈÑ CÂÒ5BÄ

Ï*ÔÐ 5 set ÇÆ¤ ÐWCMP BÈÇ5E¤ ÈÑ2 WCMP BÈÇ5E¤ ÇÆ¤ > ÈÄÉ*Eg9,X weight DÍ#GÆ> WCMP BÈÇ5Ä

set ipv6 next-hop ÈÑ6ÃÎ IP ÊÐYE› 32 ÇÄ

VpÛÇ5B,XÔÇXGÊ5B 4 ÞXÔÇ

weight set WCMP

WCMP weight nexthop

weight 1

y[Ì*+9CÃGÃ><EÆ{X{E> Ö

set ipv6 next-hop > BECÃGM2TAxCÃÅ> **set ipv6 default next-hop** > TAxCÃ

ËG5B_Đ Íy · fastEthernet 0/0 E¯9,X,ÂX 2001:0db8:2001:1760::/64 ,X y [A'5B ÎÇ
2002:0db8:2003:1::95Ä

```
XMLHQ1SDFFVDVDFEU
XMLHQ1SDFOLVSDQE
XMLHQDSDBIB
XMLHQDSPDPKSDGGVDVDFEU
XMLHQDSVSGE
XMLHQ1QFFDVQV
XMLHQ1ILSSFDSDBIB
```

ÏÎGÇĐ

Ç	ÉÄ
match ipv6 address	**n1*9CÃGÎ**
ipv6 policy route-map	**ÿh*Î1*9CÃ**
set ipv6 default next-hop	**A5B1*9CÃTAxÎÇ** IPv6

ËGÄÊ -

1.41 set ipv6 precedence

ÐÍG! match ÎXy[A'5B IPv6 ,X{ÈË*CÃÒ5BÇ **set ipv6 precedence**ÄÇ
X **no** ÊG5BX{Î8ÉB5BÄ

set ipv6 precedence { *number* | **critical** | **flash** | **flash-override** | **immediate** | **internet** | **network** | **priority** | **routine** }

no set ipv6 precedence

ÏÊ

Đ	ÉÄ
number	Î> </ IP ,X{ÊÈ 0-7Ä 7Ò critical 6Ò flash 5Ò flash-override 4Ò immediate 3Ò internet 2Ò network 1Ò priority 0Ò routine
critical | **flash** | **flash-override** | **immediate** | **internet** | **network** | **priority** | **routine**	IP ,X{

Ë,Õ5BĐ -

Ï¤Ð	CÃÀG5Bã
Ï*Ð	-
Ï5B_Ð	A’5B route-map Â IPV6 y[¼{ 3Ä

ĞÄâê -

1.44 set metric

ØÍĞ! match ÞXCÃA'5BGâËË*ĞCÃÒ5BQ **set metric**ÄÞQ **no** 6â8Æ Ê5BÄ

set metric [+ *metric-value* | **-** *metric-value* | *metric-value*]

no set metric

âê

Đ	ËÄ
+	*rt*âÃ metric ÞÅ
-	âÃ metric â
metric-value	*A*ÃÞ£

ĕ,Ò5BĐ -

Þ CÃÒ5Bã

Ĕ*Đ CÃGÆ£ĘCÃ,XEâ2ÔBrL,X5%4%âËÊ> A'5BÄÆ> set metricÃ

Þ Þmetric ,XÞhÞÃ#A,XÞÃb RIP #AĢÞW#AĢÃ

Êmetric rÞX4§8È 1-16Ä

CÃĢÞÃE7ĢÞÃE7ĢXs6ÑÃ OSPF CÃ³XCÃG¡

âî RIP CÃÈÊ RIP CÃ³XCÃGÞî OSPF CÃÆÃ,X,Ì

fGÞK IP CÃ#AĶÈ> Ä

CÃGÞÆECÃÂoute maps ÅXh*ÞÃĶÈXCÃ,ĺ> ĕ

ÞX{ÞÃÒ5BÃ 1 ÞX **match** Ą 1 ÞX **set** Ąp

ŭÝ **match** ĘÝpŭÝ **set** ÞÄ

ĞĕB_Đ G5B OSPF CÃ#AĢĶ RIP CÃÈĞĶÃ,XâÆ'5B 40Ä

```
5XLMLHFRQJURXWHURVSI
5XLMLHFRQJURXWHUUHGLVWULEXWHULSVXEQWVURXWHPDSURHGULS
5XLMLHFRQJURXWHUQWR2UNDUHD
5XLMLHFRQJURXWHUH[LW
5XLMLHFRQJURXWHPDSURHGULSSHUPLW
5XLMLHFRQJURXWHPDSVHWPHWULF
```

ÎĞĄ

Ą	ËÄ
match interface	**G**CÃÒĞ
match ip address	**G**AÞÃ
match ip next-hop	**G**AÞÃÒÇ
match ip route-source	**G**AÞÃCÃ
match metric	**G**CÃG£

match route-type	**GC‚Ã2O_**
match tag	**GC‚ÃÛ„**
set metric-type	**A5BGØ‚Ã2O_**
set tag	**A5BGØ‚ÃÛ„**

ÜGÄè -

1.45 set metric-type

ÐÍG! match ÞXCÃA'5BÇ2O_ÆË*ÜÃÒ5BÇ **set metric-typeÄÞÇ** **no 6**
è8Í5BÄ

set metric-type *type*

no set metric-type

ÄÞÇ	Ð	ÉÄ

match route-type	**GCÃ2O_**
match tag	**GCÃÛ„**
set metric	**A5BGÓÃG£**
set tag	**A5BGÓÃÛ„**

Ï¨ÄÃè -

1.46 set next-hop

Ò¹ÍG! match ¦XCÃ¸ÇÛÒÇ IP ÆÈ*ÇÃÒ5BQ **set next-hopÄÃ¦**

no 6è8Ê5BÄ¦ÇÃ*9G5BÄ

set next-hop *ip-address*

no set next-hop

Ä¦è

Ð	ÆÄ
ip-address	ÒÇ IP

Ï¨Õ5BÐ -

Ä¦ CÃ¸Ò5Bã

Ï*Ô CÃ¸ÇÛÃÆ/ÒGÔÃÆ/¦Xs6ÑÑ OSPF CÃ¦XCÃG¡

èî RIP CÃÈÑ RIP CÃ¦XCÃGÉî OSPF CÃÆÃ¸X,Ì

fGÔK IP CÃ#AĶÈ> Ä

ÇÃGÔÆÈÈÇÃÔoute maps Åxh*ÔzÃ¸KÈXCÃ¸ìÉ> ý

ÊX{ÔÃÒ5BÃ 1 ÔX **match Ò** 1 ÔX **set Ò¦p**

ùÝ match ÈÒÝpùÝ **set ÔÄ**

Ï¨5B_Ð ÓÍA“KÊ>< 1 ,XÃ¸XÔÇ’5B 192.168.1.2Ä

```
5XLMLHFRQJURXWHPDSUHGULSSHUPLW
5XLMLHFRQJURXWHPDSPDWFKLSDGGUHVV
5XLMLHFRQJURXWHPDSVHWÐ[WKRS
```

ÎÏGÐ

Ò	ÆÄ
match interface	**GCÃÔÇ**
match ip address	**GA¸Ê**
match ip next-hop	**GA¸ÊÔÇ**
match ip route-source	**GA¸ÊCÃ**
match metric	**GCÃG£**
match route-type	**GCÃ2O_**
match tag	**GCÃÛ„**
set metric-type	**A5BGÓÃ2O_**
set tag	**A5BGÓÃÛ„**

ÜGÄê -

1.47 set origin

Ø0Ú! match ?XCÃÇÎCÃ9¢2ÆË*CÃÒ5BQ **set originÄÇ no 6**
ê8Ê5BÄ

set origin { **egp** | **igp**

Ï	CÃÀG5Bã
Ï*Ð	AÇÐA'5BG¦XCÃ,X
Ï5B_Ð	-
ÏGÇ	

¶ 172.16.0.0/16 8È,XDB¦Ù#GÐ vrf_B EÚÃ¥@,XDB

#G¤CÃ><EÚÃ¥@

1 1

```
¶
¶
¶
```

ÎĠĢ	Ą	£Ä
	-	-

ĞÄâê -

1.52 show ip route

Ø¦ß IP CÃ><ĻĊÈ*ü **show ip route** Ą

show ip route [[**vrf** *vrf-name*] [*network* [*mask*] | **count** | *protocol* [*process-id*] | **weight**]]

âêâê

Ð	£Ä
vrf *vrf-name*	²Á¹ VRF ,XCÃĻ
network	²Á¸Ê%4,ºXCÃĻ
mask	*²Á¸ÃÃ*
count	/'CÃ5DÄ ECMP/WCMP CÃÊCÃAu1kÅ
protocol	**ÆÊ¾KĊonnected** , **staticĶMnÃĻÆ** ***ÊÆKÐgp** , **isis**, **ospf**, **rip**
process-id	**CÃĘ/È**
weight	**ĶM2TAxGĻXCÃ**

Ĕ,Õ5BÐ -

Ą (M*ÃG5BãG5BÆÃ#AĻG5BÆÃÒ5BãÄ

Ĕ*Ð AÊĶMÈI#/ĎCÃĻÄ

ĞĕB_Ð _ 1Ĕ**show ip rout** e Ą/4ß

```
5XLMLHVKRZSURXWH
&RGHV&FRQQHFWHG6VWDWLF55,3%%*3
2263),ß363)LQWHUDUHD
1263)166ßH[WHUQOWSH1263)166ßH[WHUQOWSH
(263)H[WHUQOWSH(263)H[WHUQOWSH
L,6,6VX,6,6VXPPDU\,6,6OHYHO/,6,6OHYHO
LD,6,6LQWHUDUHDFDQLGDWHGHIDXOW
*DWHZRIODVWUHVRUWLVÑVHW
6LVGLUHFWOFRÑFWHG9/$
6>Ø LD
2(>Ø LD9/$
5>Ø LD9/$
```

0
Q
V
0

+‰	AÈ
O	AÈCÃ,X0CÃ#AÄ¹ÐÐ) C(ÐCÃ× SØ-ÕÃ× RØIP CÃ× BØGP CÃ× OÖSPF CÃ× iØS-IS CÃÄ
E2	CÃ2O_Ä¹ÐÐ) E1ÖSPF ÐCÃ2O_Í E2ÖSPF ÐCÃ2O_Î N1ÖSPF NSSA ÐCÃ2O_ 1× N2ÖSPF NSSA ÐCÃ2O_ 2× IAÖSPF CÃYFCÃ× suØS-IS 'CÃ× L1ØS-IS 1 4{CÃ× L2ØS-IS 2 4{CÃ× iaØS-IS CÃYFCÃÄ
20.0.0.0/8	,Ð%4;X5%4}-ØSz
[1/0]	1u)ÓÐS£
Via 20.0.0.1	ØÇ IP
00:00:06	#AÇCÃ,#ÐÈ
VLAN 1	ØÇ¥@

_ 2Ø**show ip route** *network Ø6*

5XLMLHVKRZSURXWH
5RXWLQHQWU\IRU
'LVDEHPHPHWULF
5RXWLQHVFULSWRU%ORFNV
DJRYLD9/$JHUDWHGE263)H[WHUQ

ÐgÎC¥ØÖ

+‰	AÈ
Routing Descriptor Blocks	/CÃÇ,XØÇ IP CÃ9ÐÐÃ 4£ÐÐCÃ#AÇO_ÐGP ¶1

_ 3Ø**show ip route count** Ø/4Ð

5XLMLHVKRZSURXWHFRXQW
URXWHLQ
WKHQPRIDFWLYHURXWH

_ 4Ë**show ip route weight** Ø/4ß

```
5XLMLHVKRZSURXWHØLJKW
>GLVWDQHPHWULFØLJKW@
6>Ø@LD
6>Ø@LD
```

ÏĈGÐ	Ç	Ł:Ä
	-	-

ĞÄß | -

1.53 show ip route summary

Ø6,XÇ¾

```
Ruijie#show ip route summary all
IP routing table count: 2
Total
  Memory: 2000 bytes
  Entries: 20
    Connected:4,Static:8,RIP:2,OSPF:2,ISIS:2,BGP:2

Global
  Memory: 1000 bytes
  Entries: 10
    Connected:2,Static:4,RIP:1,OSPF:1,ISIS: 1,BGP:1

VRF1
  Memory: 1000 bytes
  Entries: 10
    Connected:2,Static:4,RIP:1,OSPF:1,ISIS: 1,BGP:1
```

Total ØVE×Ã><,X4ªAuÇÄ

ÏÇÐ	Ò	ÆÄ
	-	-

ÜÄÀê -

1.54 show ipv6 prefix-list

Ø¦ß IPv6 ¼ê<Ç5Ùê<><NMÇÈ*ü **show ipv6 prefix-list Ø**

show ipv6 prefix-list [*prefix-name*]

Øê

Ð	ÆÄ
prefix-name	IPv6 ¼ê<á

Ь,Õ5BÐ -

Ø (M*ãG5BãG5BãÃ#AG5BãÃÒ5Bã

Ь*Ð Vpù¼ê<áØê<,XG5BÇ¼ê<,XG5BÇÄ

ÜG5B_Ð

```
5XLMLHVKRZSYSUHIL[OLVW
LSYSUHIL[OLVWSHQULHV
SHUPLW
SHUPLW
```

ÏÇÐ	Ò	ÆÄ
	-	-

ÜÄÀê -

1.55 show ipv6 route

Ø¼ß IPv6 CÃ><Ç£È*ü **show ipv6 route Ë¾**

show ipv6 route [[*network / prefix-length*] | **summary** | *protocol* | **weight**]

Ëæ¾

Ð	£Ä
network / prefix-length	²Á¼Ê%4¸XCÃÇ
summary	/'! ipv6 CÃ5D,XØO4ªuÇ
protocol	**ÆÊ¾ÄÇonnected** , **staticÑMnªÁÇÃ** ***BÆÄKÐgp** , **isis**, **ospf**, **rip**
weight	**²M2TªxG¸XCÃ**

Ï£,Õ5BÐ -

Ë¾ (M*ãG5BãG5BÃ#AÇ5BÃÇÕ5Bã

Ï*Ê Aã¾MÈl#/ÊCÃÇ

Ï5B_Ð 5XLMLHFRQJVKRZSYURXWH
,3YURXWLQWDEOH'HIDXOW– **¶**
¶

E2	CÃ2O_Ä¹+ßÕ) E1ÖSPF ÈŒÃ2O_Í E2ÖSPF ÈŒÃ2O_Î N1ÖSPF NSSA ÈŒÃ2O_ 1× N2ÖSPF NSSA ÈŒÃ2O_ 2× IAÖSPF CÃ³YFŒÃ× suŒS-IS ŒÃ× L1ŒS-IS 1 4{CÃ× L2ŒS-IS 2 4{CÃ× iaŒS-IS CÃ³YFŒÃÄ
20::/64	,ß%4;X5%4}-ŒSz
[1/0]	1u)ÓßÈ£
via 10::4	ÔÇ IPv6
VLAN 1	ÔÈ¥@

ÏÎGÐ

Ç	È.Ä
ipv6 route	G5B ipv6 M-ÕÃ

ÏGÄß

-

1.56 show key chain

Ø/ȝyJÒXG5BÇÀÈ*(M*ÐÇ **show key chainÄ**

show key chain [*key-chain-name*]

ÏßÐ

Ð	È.Ä
key-chain-name	***ÃÑÑÐB***

ÏЬÕ5BÐ

5,ØȝyJÒ5BÇÄ

ÏÐ

(M*ßGŠBßGŠBßÃ#AÇŠBßyJÒŠBßÄ

ÏŠ*Ð

VpùßȝyJÀßȝyJÒXG5BÇßȝyJÒXG5BÇÄ

ÏG5B_Ð

```
5XLMLHVKNHFKDLQ
NHFKDLQLSNHV
NHWH[WDEF
DFFHSWOLIHWLPH6HS'HF
VHQOLIHWLPH6HS'HF
```

+‰	AÈ
key chain	ȝyJß
key	ȝy ID

text	ȝyAxA•
accept-lifetime	yåóó
send-lifetime	¥ëõóó

ÏĈĢĘ

Ę	ĘÄ
-	-

ĞÄâê -

1.57 show route-map

Ø/CÃĄXG5BĘĖÈË*(M*ĘĘ **show route-mapÄ**

show route-map [*route-map-name*]

ëâê

Ð	ĘÄ
route-map-name	*ĘĘĘĘ*

Ь,Ğ5BÐ -

ĘĘ (M*ãĞ5Bã

2 ECMP/WCMP

2.1 ip ref ecmp load-balance

A’5B ECMP/WCMP 1*+9Ä

ip ref ecmp load-balance [**crc32_lower** | **crc32 upper**] [**dip**] [**port**] [**udf** *number*]

no ip ref ecmp load-balance [**crc32_lower** | **crc32 upper**] [**dip**] [**port**] [**udf**]

] [(ip ref ec0.199 346.96.24S.)T9 - Tf ( )6 re 1.69 -7.9d [9d _9d 36 uppe A’5Bhash u

3 RIP

3.1 address-family

address-family

no

address-family ipv4 vrf *vrf-name*

no address-family ipv4 vrf *vrf-name*

vrf *vrf-name*	VRF

auto-summary

no auto-summary

	-	-

5,

CÃE7G5BÃ

RIP CÃ7%CÃ0SCÃ2O5%4E+ÃO5%4CÃÄ

ip rip bfd [**disable**]

bfd all-interfaces

]

ip default-network **default-information originate**

RIP

RIP

5XLMLHFRQJURXWHUGHIDXOWLQRUPDWLRQULJLQWHDOV

ip rip default-information	
redistribute	RIP

-

3.5 default-metric

RIP **default-metric** **no**

default-metric *metric-value*

3.6 distance

ØA'5B RIP CÃ‚,X1u)ÓÆÈË*CÃ‚Æ7Ç55BQ **distance**ÄÀQ **no 66**ÕÕ5BÄ

distance *distance* [*ip-address wildcard*]

no distance [*distance ip-address wildcard*]

ïåè

Ð	Ë Ä
distance	A'5B RIP CÃ‚1u)ÓÆÈ-255 KÈXHD
ip-address	ØÕ IP ¼Ô
wildcard	*n* IP ËWÝMÈ ></2'.BGÈ ></ãËWÄ

ï5,Õ5BÐ 5,Õ 120Ä

ïQ CÃ‚Æ7Ç55BäÄ

ïÉ*Ð S*ÄÀQ'5B RIP CÃ‚,X1u)ÓÆÄ

Ã‚*8ÇQ8¼Ô,X1u)ÓÆÈ RIP CÃ‚8Ëo¼ÔXÈË*ìh

,X1u)ÓÆÈCÃ‚h*ü RIP A'5B,X1u)ÓÆÄ n

	RIP Fastethernet 0/0 172.16

```
5XLMLHFRQJURXWHUULS
5XLMLHFRQJURXWHUQWWR
5XLMLHFRQJURXWHGLVWULEXWHOLVWLQVWHWKHUQW
5XLMLHFRQJURXWHUDXWRVXPPDU\
5XLMLHFRQJDFFHVVOLVWSHUPLW
```

access-list	**nA**
prefix-list	**n**

-

3.8 distribute-list out

distribute-list outA no 6

distribute-list { [*access-list-number* | *name*] | **prefix** *prefix-list-name* } **out** [*interface* **|** [**bgp | connected | isis** [*area-tag*] **| ospf** *process-id* **| rip | static**]]

no distribute-list { [*access-list-number* | *name*] | **prefix** *prefix-list-name* } **out** [*interface* **|** [**bgp | connected | isis** [*area-tag*] **| ospf** *process-id* **| rip | static**]]

access-list-number | *name*	*A*
prefix *prefix-list-name*	S*
interface	*y*
bgp	bgp
connected	
isis [*area-tag*]	isis *area-tag* isis r_
ospf *process-id*	ospf *process-id* *p* ospf r_
rip	rip
static	

-

3.10 ip rip authentication key-chain

RIP

no ip rip authentication mode

	Đ	Ë
	text	RIP
	md5	RIP MD5

5,Õ5BÐ 5,

yG5B

'G5B RIP RIP CA,XA'5B,X RIP

RIP DB5BA

VpG*ü MD5 5BG6(yBA

RIPv1 RIP DBxA RIPv2

fastEthernet 0/1 y;X RIP MD5

5XLMLHFRQJLJ
5XLMLHFRQJLJ)DVW(WKHUQWLSULSDXWKHQWLFDWLRQRGHPG

	Ñ	Ë
	ip rip authentication key-chain	***ü** RIP RIP AS*ü,X3yX RIPv2 Õ RIP DBxA
	ip rip authentication text-password	***ü** RIP A'5B RIP RIPv2 Õ RIP DBxA
	key chain	**G5B**

	yG5BÄ
	AÐxAÄ VpÜ*ü RIP ÐAxA6ÐS*Ð5BÐAxA0ÐEG6(3y9ª ÐAxA0ÐÜ(Ph5Ü RIPv1 õ RIP DBÙxAž¼ RIPv2 Õ
G5B_Ð	fastEthernet 0/1 y¡X*ü RIP ÐAxAÈ'5BÐAxA0ú helloÄ 5XLMLHFRQJLQWHUIDFHIDVW(WKHUQHW 5XLMLHFRQJLJI)DVW(WKHUQHWLSULSDXWKHQWLFDWLRQ[WSDVVZRUGKHOOR

ÏGÐ	Ð	Ä
	ip rip authentication mode	**n** RIP AxA¡XÄ
	ip rip authentication key-chain	***ü** RIP AxAÈÛ RIP AxAS*ü3yž¼ RIPv2 Õ RIP DBÙxAÄ

GÄÈ	-

3.13 ip rip bfd

3.14 ip rip default-information

ip rip default-informationÄ

no 6

ip rip default-information { **only** | **originate** } [**metric** *metric-value*]

no ip rip default-information

only	**E**
originate	**E**
metric *metric-value*	**5** 15

metric 1Ä

ip rip default-information RIP **default-information originate**

ip rip default-informationRIP

ethernet0/1

Ï*ô Vp/U6y RIP DBÙy;Xy **no 6G5BQ'ü**
G5BZQyÃ*AQ **default 6éy** RIP DBÙ

ïG5B_Ð fastEthernet 0/1 y/U6y RIP ,XDBÙ

```
5XLMLHFRQJLJ
5XLMLHFRQJLJ)DVW(WKHUQHW
5XLMLHFRQJLJ)DVW(WKHUQHWLSULSUHFHLYHHQEOH
```

ÏGQ

Q	Ä
ip rip send enable	**AGyÃÕ** RIP DBÙ
passive-interface	**G5B** RIP >y·

ïGÄê -

3.16 ip rip receive version

n RIP X RIP DBÙG5BQ **ip rip receive versionÄQ**
X **no 6G5BÄ**

ip rip receive version [**1**] [**2**]

no ip rip receive version

ÄêÐ

Ð	Ä
1	¥ RIPv1 ,XDBÙ
2	¥ RIPv2 ,XDBÙ

ï,ÕG5BÐ 5,Õ **version QG5BÄ**

ÑQ yG5BÄ

Ï*ô AQXG5B4ü **vesion QG5BÄy** RIP y[,X>Ã
AGyÃ RIPv1 ` RIPv2 ,XDBÙQG5BÃý> version ,X
G5BÄ

ïG5B_Ð S fastEthernet 0/1 yÃ RIPv1 ` RIPv2 ,XDBÙ

```
5XLMLHFRQJLJ
5XLMLHFRQJLJ)DVW(WKHUQHW
5XLMLHFRQJLJ)DVW(WKHUQHWLSULSUHFHLYHYHUVLRQ
```

ÏGQ

Q	Ä
version	**nýX** RIP DBÙX5,ÕÄ

ïGÄê -

3.17 ip rip send enable

ip rip send enable

no ip rip send enable

-	-

3.18 ip rip send supernet-routes

ip rip send supernet-routes

no ip rip send supernet-routes

-	-

,X **no 6**

AJ RIPv2 y[

S fastEthernet 0/1 y/U RIP ,XCY5%CÃÄ

5XLMLHFRQJLQVHUIDFHIDVW(WKHUQHW

5XLMLHFRQJLJI)DVW(WKHUQHWQLSULSVHQVXSHUQWURXWHV

ip rip send enable	**A** RIP DBÙ
version	**G5BA** RIP (

-

3.19 ip rip send version

n RIP RIP DB **ip rip receive version** "ÈAËQqN1`î

3.20 ip rip split-horizon

Ø*ü RIP ÙGÉs6ÆÑË*ÿ¿G5BQ

	ip-address	
	ip-network-mask	IP

RIP

yG

ip rip summary-address RIP

RIPv2 FastEthernet 0/1

yG5BA

RIP)s6N RIP È Triggered RIP RIP #A5%W WAN È Wide Area Network=

)h*bLC

'*z RIP)s6N RIP #Aán XÊ RIP

5%y CÃA

1yCA[Ä

2RIP CA¥A

3y(

4CA'[Ä

+b#Z RIP nOG*BAxG[5%X

retransmit-timer ` **retransmit-count**

-	-

version

RIP y[,X>Æ

RIPv1 ` RIPv2 ,XDB

version ,X

S fastEthernet 0/1 y

RIPv2 y[Ä

5XLMLHFRQJLJVHUIDFHIDVW(WKHUQHW

5XLMLHFRQJLJ)DVW(WKHUQHWLSULSYEURDGFDVW

ïGÄêð -

3.25 network

Ø0n RIP CÃE7Ø0Eî¡X5%4ë<ÆË*ÐCÃE7G5BQ **network**ÄÆQ **no 6ã8Æ**
nX5%4Ä

network *network-number* [*wildcard*]

no network *network-number* [*wildcard*]

ïèê

Ð	ÆÄ
network-number	È54%X54%54%2O54%Æ IP 2bA7'%4° ,XýFÃÑÕ RIP DBÃ
wildcard	*n* IP EW(MÈ ></2'.BGÈ ><ÆWÄ

ï5,Õ5BÐ -

ïÇ CÃE7G5BÃ

ïS*ÐÐ *Ã5B *network-number* ` *wildcard ÐÈ:ÆÀ RIP E¤ Ä
Vp5B *wildcard ÐÈ* RGOS ÚAxÝO8ÈÀÐ:ÆÀÝO8È,Xy·
â RIP E¤ Ä
ý¼ü RIP n,X5%4ë<ÈýÃÕ RIP CÃÀÇÈy RIP CÃ
ÀÄ

ïG5B_Ð AGÆ 192.168.12.0/24 ` 172.16.0.0/24 8È,Xyâ RIP E¤ Ö

```
5XLMLHFRQJURXWHUUOS
5XLMLHFRQJURXWHUQWR2UN
5XLMLHFRQJURXWHUQWR2UN
```

ÎGÇÐ

Ç	ÆÄ
-	-

ïGÄêð -

3.26 offset-list

Ø0rtyÆÕX RIP CÃ,X metric Ã*ÐCÃE7G5BQ **offset-list**ÈÆQ **no 6ã**
ô8ôX offset ë<

offset-list { *access-list-number* | *name* } { **in** | **out** } *offset* [*interface-type interface-number*]

no offset-list { *access-list-number* | *name* } { **in** | **out** } *offset* [*interface-type interface-number*]

ïèê

Ð	ÆÄ

access-list-number | name	
in	**h*ü** acl
out	**h*ü** acl
offset	metric
interface-type	acl
interface-number	

offset

CÃE

offset-list offset-list RIP

offset-list metric

_ 1 acl 7 RIP metric rt 7

```
5XLMLHFRQJURXWHURIIVHWOLVWRXW
```

_ 2 fastethernet0/1 acl 8 RIP metric rt 7

```
5XLMLHFRQJURXWHURIIVHWOLVWLQVWHWKHUQW
```

-	-

-

3.27 output-delay

RIP **output-delay** **no**

output-delay *delay*

no output-delay

delay	*A* 8-50>

5,

CÃE

7 MP 512 +8V 25 5CÃ 25

ÿ8FÿÄ

ÜG5B_Ð Ú RIP ,XÿÇÈÆÊÑ'5B 30 ¿

```
5XLMLHFRQJURXWHUULS
5XLMLHFRQJURXWHURXWSXWGHOD\
```

ÏÎGÐ		
Ò		
-	-	

ÜÄÀÐ •¾#PâÍP- passive p*ęr}"_ÐÞb}(-ÐX‰¥,ÇÃGE7ß

3.28 passive-interface

Ò#ÿÐÆÑ,Xs6ÑË*ÿG5BÒ **passive-interface** **no**

6ÐÆÑXs6Ñ

passive-interface { **default** | *interface-type interface-num* }

no passive-interface { **default** | *interface-type interface-num* }

ÐÐ		
Ð		
default	**ÐÐ5BÝ·**	passive

3.29 redistribute

redistribute

redistribute { **bgp** | **connected** | **isis** [*area-tag*] | **ospf** *process-id* | **static** } [{ **level-1 | level-1-2 | level-2** }] [**match** { **internal | external** [**1 | 2**] **| nssa-external** [**1 | 2**] }] [**metric** *metric-value*] [**route-map** *route-map-name*]

no redistribute { **bgp** | **connected** | **isis** [*area-tag*] | **ospf** *process-id* | **static** } [{ **level-1 | level-1-2 | level-2** }] [**match** { **internal | external** [**1 | 2**] **| nssa-external** [**1 | 2**] }] [**metric** *metric-value*] [**route-map** *route-map-name*]

bgp	bgp
connected	
isis *area-tag*	isis *area-tag* isis
ospf *process-id*	ospf *process-id* ospf 1-65535
static	

level-1 | **level-1-2** |

2 p no
V 5B redistribute isis 112 level-2 redistribute isis 112 level-2 no level-2
level-2 D 5, 5B redistribute isis 112 level-2
redistribute isis 112

RIP RIP
default-information originate

5B_ GM- RIP
5XLMLHFRQJURXWHUHGLVWULEXWHVWDWLF

default-metric *metric*	**A5BG 5 G**
default-information originate	RIP E 5,

-

3.30 router rip

RIP

3.31 show ip rip

Ø/ RIP RIPRIP

```
>@LD)DVW(WKHUQW

_ 3Ö  RIP CÃDBgÆO_CÃ,X4?AuC,Ø
5XLMLHVKRZSULSGDWDEDVHFRXQW
SO9DOLG,QDOLG
GDWDEDVH
DXWRVXPPDU\

FRQFWHG
ULS
```

ÏĜĘ	Ą	Ł Ä
	show ip rip	**/E¤XCÃĘ/ŢĄCÄ**

ĞĠÄĝ -

3.33 show ip rip external

Ø/ RIP GĝXĒŒÃCÈĖ*ü **show ip rip external Ą**

show ip rip external [**bgp** | **connected** | **isis** [*process-id*] | **ospf** *process-id* | **static**] [**vrf** *vrf-name*]

Ąĝĝ

Đ	Ł Ä	
bgp	**/GĝĶ**	BGP CÃÄ
connected	**/GĝĶĘĒCÃ**	
isis *process-id*	**/GĝĶ**	ISIS CÃĄ*process-id* ISIS Ę/Ţ

```
>FRQILFWHGHIHXOW
QRS LI
>FRQILFWHGHIHXOW
QRS LI
```


show ip rip	**/E¤XCÃE/ÞÇÄ**

-

3.34 show ip rip interface

show ip rip interface [**vrf** *vrf-name*] [*interface-type interface-number*]

vrf *vrf-name*	VRF ,X RIP y·
interface-type interface-number	**Xy2O_4Ë**

-

(MÃG5BÃE/ÇÄ

A RIP yÇÄ RIP yÇÄ

/ RIP ,XyÇÄ

```
5XLMLHVKRZSULSLQWHUIDFH
)DVW(WKHUQHWLVXSOLQSURWRFROLVXS
5RXWLQJ3URWRFRO5,3
5HFHLYH5,3YSDFNHWVRQ\
6HQG5,3YSDFNHWVRQ\
3DVVLYHLQWHUIDFH'LVDEOHG
6SOLW+RUL]RQWK3RLVRQG5HYHUVH(QDEOHG
7ULJJHUHG5,3(QDEOHG
5HWUDQVPLWWLPHU5HWUDQVPLWFRXQW
9%URDGFDVW'LVDEOHG
0XOWLFDVWUHJLVWH5HJLVWHG
,QWHUIDFH6XPPDU5LS
1RW&RQJXUHG
$XWKHQWLFDWLRQ0RGH7H[W
$XWKHQWLFDWLRQ6HFKDLQ
$XWKHQWLFDWLRQ7H[WSDVVZRUGXLMLH
'HIDXOWLQRUPDWLRQ0HWULF
,3LQWHUIDFHDGGUHVV
```

ĝ[WXSGDWHGXHLQHFRQV
ĝ[WXSGDWHGXHLQHFRQV
ĝLJKERUĝ[WXSGDWHGXHLQHFRQV
ĝLJKERUĝ[WXSGDWHGXHLQHFRQV
ĝ[WXSGDWHGXHLQHFRQV

Vp*ü RIP â BFD 6(|Ê/ BFD Ç:

5XLMLHVKRZSULSLQWHXSGDWHÀ^

RIP

2Mbps

G5B_Đ G5B RIP

3.38 version

version

version { 1 | 2 }

no version

1	**n** RIP (Ë 1Ä
2	**n** RIP (Ë 2Ä

RIPv1 ` RIPv2 ,XCÃ RIPv1 ,XCÃ

CÃ

*

RIP E> ,X(**ip rip receive versionÃ ip rip send version**

RIP y[E> GnÄ

Ú RIP ,X(Ë'5B 2Ä

```
5XLMLHFRQJURXWHUULS
5XLMLHFRQJURXWHUYHUVLRQ
```

ip rip receive version	**n** RIP DB
ip rip send version	**n** RIP DB

4 RIPNG

4.1 default-metric

ØnGÞWCÃ#AÊ RIPng 5,ÕXCÃËŠ*CÃE/G5BQ **default-metric**ÄQ
X no 6ãÕ5BÄ
default-metric *metric*
no default-metric

ä

Ð	Ä
metric	ÞGÊ 1 16Ÿp metric ß1b 16ÈGOS ÚxACÃÃ’Ä

ï5,Õ5BÐ 5,Õ 1

ïQ CÃE/G5Bã

ïŠ*Ù AQÕCÃ#AG5BQ **redistribute GŠ*ÄÞÃE/ÈGÚ**
RIP CÃE/ÞCÃ#A,XCÃu1k,XÞCÃCÈÆÈÊ
LÕnGÞÚÃü RIP CÃ³XCÃpGÞÃ#AE/ÞBnCÈ
RIPng Š*ü **default-metric nXzGÃpÃBnzGÈÞ** **default-metric n**
XzGÃ5BAQ **default-metric 5Õ** 1Ä

ïG5B_Ð GÚ OSPF 100 E/XCÃ RIP CÃE/ÞA’5B 3Ä

```
5XLMLHFRQJURXWHUGHIDXOWPHWULF
5XLMLHFRQJURXWHUUHGLVWULEXWHRVSI
```

ïÎGQ

Q	Ä
redistribute	**ÓÞÃÃÞÃ**

ïGÄè -

4.2 distance

ØA’5B RIPng CÃ,X1u)ÓÆÈŠ*CÃE/G5BQ **distance**ÄQ **no 6ãÕ5BÄ**
distance *distance*
no distance

ä

Ð	Ä
distance	A’5B RIPng CÃ1u)ÓÆÈE5B<1-254> KÈXHD

ï5,Õ5BÐ 5,Õ 120

ïÐ CÃE7G5Bã

ïS*Ô RIPng CÃA'5B1u)ÚÆÈBÇ

ïG5B_Ð G5B RIPng CÃ1u)ÚÆ• 160

```
5XLMLHFRQJLSYURXWHUULS
5XLMLHFRQJURXWHUGLVWDQH
```

ïÎGÐ

Ç	ÉÄ
-	-

ïGÄè -

4.3 distribute-list

ØS*ü prefix-list ><É7 ÊÃE> Eè§S*ÚÃE7G5BÇ **distribute-list**ÄÐ **no** è¡XEè

distribute-list prefix-list *prefix-list-name* { **in** | **out** } [*interface-type interface-name*]

no distribute-list prefix-list *prefix-list-name* { **in** | **out** } [*interface-type interface-name*]

ïè

Ð	ÉÄ
prefix-list *prefix-list-name*	**prefix-list** Xè*ÚÊÇÃ
in | **out**	bÛAé<#ýÉÐÃS*É$
interface-type interface-name	Aé<#ÛÝ·

ï5,Õ5BÐ TAxüÝé<Ä

ïÐ CÃE7G5Bä

ïS*Ô Æ¥ÿ5ÈÕÛCÃÊEG5BCÃé<ÊXCÃÐ[E> E›
ÈpüÛyÊXy¡XCÃÐ[E> Eè

ïG5B²Ð ÿ· eth0 ÉXÈÇÃE> Eè¼ **prefix-list** *allowpre* ÆÕ<Ê

```
5XLMLHFRQJLSYURXWHUULS
5XLMLHFRQJURXWHUGLVWULEXWHOLVWSUHIL[OLVWDOORZSUHLÐWK
```

ïÎGÐ

Ç	ÉÄ
redistribute	**G5BCÃé**

ïGÄè -

4.4 ipv6 rip default-information

Ø{*ôTAx IPv6 ,XCÃ RIPngÆË*ÿG5BQ **default-informationÄÐ** no 6ã L8TAxCÃÄ

ipv6 rip default-information { **only** | **originate** } [**metric** *metric-value*]

no ipv6 rip default-information

ä¾è

Ð	ÆÄ
only	**Eî** ipv6 TAxCÃÆÈJWCÃ
originate	**Eî** ipv6 TAxCÃÆÈEJWCÃ
metric *metric-value*	**TAxCÃzGÆÐ** 15ÄAx 1Ä

ë,Õ5BÐ TAxüÝAxCÃG5B

ÐQ yG5Bã

Ê*Ð yG5BÆÐÝTÆÊÐ IPv6 5,ÕÃÆCÃDéüA'ÎXCÃ

E¥®` RIPng ,XCÃDBgÄ

FS66Ã)CÐG5BÆÐRIPng ÚÝFÆîX5,ÕÃÆ

G5B_Ð ÿ· ethernet0/0 ÐTAxCÃ RIPng CÃE/ÐÆyÐZÃTAxCÃÄ

5XLMLHFRQJLQWHUIDFHHWKHUQW

5XLMLHFRQJILSYULSGHIDXOWLQRUPDWLRQQ\

ÎGÐ

Q	ÆÄ
show ipv6 rip	**/** RIPng CÃ#AÆ/ÐXÐâ?uDB
show ipv6 rip database	**/** RIPng CÃ

GÄÐ -

4.5 ipv6 rip enable

ØSyt9 RIPng E¤ ÆË*ÿG5BQ **ipv6 rip enableÄÐ** **no 6ÐnyÞ**

E¤ RIPngÄ

ipv6 rip enable

no ipv6 rip enable

ä¾è

Ð	ÆÄ
-	-

ë,Õ5BÐ -

ÐQ yG5BÆ

Ï*Ô AÇÔA'5Bâ RIPng #AÉ¤ ,XyÔ5BAÇÔ¤ RIPng #AÔ5BA¹
ÇÔÉ¤ RIPng CÃ#AÄ

Ô5B_Đ ý ethenet 0/0 t9 RIPng E¤ Ä
5XLMLHFRQJLJ9HUIDFHHWKHUQW
5XLMLHFRQJLILSYULSHQEOH

ÎÔÇ

Ç	ÉÄ
-	-

ÔÄè -

4.6 ipv6 rip metric-offset

Ø A'5ByÞXÇÈË*üG5BÇ **ipv6 rip metric-offset** *value*ÄÇ **no** 6è
ÇA5BÄ
ipv6 rip metric-offset *value*
no ipv6 rip metric-offset

è

Đ	ÉÄ
value	*yzG*16

ï,Õ5BĐ TAx 1

Ç yG5Bã

Ï*Ô CÃt9CÃ><ÈÃ,X metric Øt A'5B,XÇÈÉA'5By¡XÇÉ¡
CÃ,XS*Ä

Ô5B_Đ ý ethernet 0/1 ÞXyÇA'5B 5Ä
5XLMLHFRQJLJ9HUIDFHHWKHUQW
5XLMLHFRQJLILSYULSHWULFRIIVHW

ÎÔÇ

Ç	ÉÄ
-	-

ÔÄè -

4.7 ipv6 router rip

Ø Î RIPng CÃE7ÔE9CÃE7Ô5BÈË*üG5BÇ **ipv6 router ripÄÇ** **no**
6è8 RIPng CÃE7Ä

ipv6 router rip

no ipv6 router rip

Ð	ÐÄ
-	-

Ъ,Õ5BÐ ъÝ RIPng CÃÐ7Ъ¤

<G5Bã

Ъ*ÐTrpbêÜÝ-4(g)]TJ 1 A-4(gj/90 TdIPn)-4(g)]TJ Tf5.807 0 Td(88 40 Tc 3.027 0 Td[<43C3>-7<2B0545A72FDF0CFC45A43E20>]TJ/T

-	-

ÏGÄêø -

4.9 redistribute

ÐÚÚWCÃ¸XCÃGÝ RIPng YÆÊ*ÇÃÆÐG5BQ **redistribute** ÄØÐ **no** 6èÐXGÐ5BÄ

redistribute { **bgp | connected | isis** [*area-tag*] **| ospf** *process-id* **| static** } [**metric** *metric-value* | **route-map** *route-map-name*]

no redistribute { **bgp | connected | isis** [*area-tag*] **| ospf** *process-id* **| static** } [**metric** *metric-value* | **route-map** *route-map-name*]

Äêø

Ð	ÆÄ
bgp	¢ BGP GÝ
connected	**ÆÇÃGÝ**
isis [*area-tag*]	¢ ISIS GÐ*area-tag* ></ ISIS ÆÐ
ospf *process-id*	¢ OSPF GÐ*process-id* ></ OSPF ÆÐ 1-65535
static	**M-ÕÃGÝ**
metric *metric-value*	A'5B>GÝ RIPng ¸XCÃ,XÐ£
route-map *route-map-name*	A'5BGÝÃE$

Ï5,Õ5BÐ TAxGÝWCÃ#A,XCÃ×

Vpù×Ã'5B **default-metricÈ metric** TAx 1×

TAxÁ'5B **route-map×**

TAxGÐÇÃÆÐXÝO_CÃ

Ï Ð CÃÆÐG5Bã

Ï5*Ð S*ÁÐÇÃ¸CGÝ RIPng Ä

CÃGÐÃ#A,XÐÆÐÇÃ#A,XÐÆÐÇÃ#A,XÐÈÃ#A,

G*¡XÐÆu1kÐXRIP ÐÆu1kÎÐCÇÈSPF ÎÐWÀu1kÎ

9,XÐÆÐÃÄ

G5BGÝ_#AÆÎÔÚK'Ð¿GÝÃ¸C RIPngÄ

Ï5B_Ð M-ÕÃGÐ*ÇÃÒ *mymap E> EÐGÆAB* 8Ä

```
5XLMLHFRQJLSYURXWHUULS
5XLMLHFRQJURXWHUUHGLVWULEXWHVWDWLFURXWHPDSPPDSPHWULF
```

ÎÏGÐ

Ç	ÆÄ
default-metric	**nGÝWCÃÆ** RIPng 5,ÕXÐ£
distribute-list	RIPng CÃÐ¸XÝ$

-

4.10 show ipv6 rip

show ipv6 rip

-	-

-

*

-

```
5XLMLHVKRZSYULS
5RXWLQJ3URWRFROV5,3Q
6HQLQXSGDWHVHYHUVHFRQVZWKQ[WGXHLQHFRQV
7LPHRXWDIWHUVHFRQVJDUEDJHFROOHFWDIWHUVHFRQV
2XWJRLQXSGDWHILOWHUOLVWIRUDOOLQWHUIDFHLV
GLVWULEXWHOLVWSUHIL[DDRXW
,QRPLQXSGDWHILOWHUOLVWIRUDOOLQWHUIDFHLVQWVHW
'HIDXOWUHGLVWULEXWLRQHWULFV
'HIDXOWGLVWDQHV
5HGLVWULEXWLRQ
5HGLVWULEXWLQSURWRFROFRQFWHGURXWHPDSUP
5HGLVWULEXWLQSURWRFROVWDWLF
5HGLVWULEXWLQSURWRFRORSSI
'HIDXOWYHUVLRQRQURVHQYHUVLRQHFHLYHUVLRQ
,QWHUFH6HQ5HFY
9/$1
/RRSEDFN
5RXWLQJRUPDWLRQRXUFHV
1RQH
```

show ipv6 rip	**/** RIPng CÃ#AE7[XÐaAuDB

-

4.11 show ipv6 rip database

Ø/ RIPng CÃ><,XØM,ÊÈËŠ*ü **show ipv6 rip database** Ø

show ipv6 rip database

ÏÈ	Ð	ÆÄ
	-	-

Ï,Õ5BÐ -

Ø *ÊMã

Ï*Ø S*ÀĄ RIPng CÃ><,XØMÇÄ

Ï5B_Ð

```
5XLMLHVKRZSYULSGDWDEDVH
&RGHV55,3Q&&RQFWHG66WDWLF2263)%%*3
VXEFRGHVQUPDOVVWDWLFGGHIDXOWUUHGLVWULEXWH
LLQVHUIDFHDVDJJUHJDWHGVXSSUHVVHG
6UGEPHWULFWDJ
/RRSEDFN
6UGEPHWULFWDJ
/RRSEDFN
&UGEPHWULFWDJ
9/$
6UGEPHWULFWDJ
1XOO
&LGEPHWULFWDJ
/RRSEDFN
6UGEPHWULFWDJ
1XOO
```

ÎÇ	Q	ÆÄ
	-	-

ÏÄ -

4.12 split-horizon

Ø*ü RIPng ÏÉs6ÑË*CÃE7Ç5BQ **split-horizon**ÄØ **no 6**ÉÁ RIP Ï

Ésó*µÉ¿ØÏÉÈËŠ*CÃE7Ç5BQ **split-horizon poisoned-reverse**È

A **no 6**ÉØÏÉÄ

split-horizon [**poisoned-reverse**]

no split-horizon [**poisoned-reverse**]

	poisoned-reverse	

4.13 timers

timers *update invalid flush*

no timers

update		

RIP

RIPng **show ipv6 rip**

2Mbps

RIP 30 180 240

invalid 5XLMLHFRQJLSYURXWHUULS

5XLMLHFRQJURXWHUWLPHUV

show ipv6 rip	**/** RIPng
show ipv6 rip database	**/** RIPng

-

5 OSPFv2

5.1 area

G5BÛ,XËS*AQX **no 6è8ÛX** OSPF Ä

area *area-id*

no area *area-id*

ÐAè	Ð	Ä
	area-id	OSPFè IP Ä

Ï,Õ5BÐ 5,ÛX5B OSPF Ä

è CÃE7G5Bä

Ïš*Ð *üÃS*üQX no 6 è Ù8 û OSPF ³XG5B J 8 A ¹³ Ù8 **area**

authentication **area default-cost** **area filter-list** **area nssa** **1ÞXG5BÇ**

Ù8 OSPF ³XG5BÖ

Ø#Ù8F³XG5Bè.JÒÃXG5BÄÊO#Ù8<.JÒÃG5BÈÑ8FÄ

3 Tc 0 Þ302C850 Td 090E0Þ32Q è X721322026 5Fj/TT0 1 Tf (Tj/C2_0 1 Tf -16.22 -1.733 Td 090E0Þ22026 5Fj/T2F44C3841B9090E0Þ85AF080A10

message-digest	**G*ü** MD5Ämessage digest 5 ÅxAÄ

Ï5,Õ5BÐ 5,ÛÝÇ*ÄxA•

ÏÞ CÃE7Ç5BÄ

Ï*Û RGOS ECÞÄxA²O_Ö
ÅO_ÄÄxAÈ*ÝÄÇü OSPF AxAÈSPF DBÙÝXAxA²O_Ù
ÅO_ÞÄxAÈ5BAÞÝÇ*ü message-digest EÝMM×
ÅO_Ê MD5 AxAÈ5BAÞÇ*ü message-digest EÝMÄ
ÞÛ OSPF ¦ÝXCÃA'ÊOG*ÞÄxA²O_Ø×p*ÄxAÈÑOÉÝF•
,XyG5BAxAÿG5BQ **ip ospf authentication-key Ê5BÞÄxAyG5BQ**
¸ **ip ospf message-digest-key Ê5B** MD5 AxAÇÄ

Ï5B_Ð OSPF CÃE7Ø³ 0Ä|FÊ*ü MD5 AxAÈxA• backboneÄ

```
5XLMLHFRQJLQWHUIDFHIDVW(WKHUQHW
5XLMLHFRQJLI)DVW(WKHUQHWLSDGGUHVV
5XLMLHFRQJLI)DVW(WKHUQHWLSRVSIPHVVDJHGLJHVWNHPGEDFNERQ
5XLMLHFRQJURXWHURVSI
5XLMLHFRQJURXWHUQWR2UNDUHD
5XLMLHFRQJURXWHUDUHDXWKHQWLFDWLRQHVVDJHGLJHVW
```

ÎÏGÞ

Þ	ÐÄ
ip ospf authentication-key	**n** OSPF ÞÄxAÇÄ
ip ospf message-digest-key	**n** OSPF MD5 AxAÇÄ
area virtual-link	**nÞÐÃ**

Ï5ÄÊÞ -

5.3 area default-cost

ÐnE7- STUB ÊÙ NSSA 5,ÕÃ,X8CÄOSPF ,XGÊË*ÛCÃE7Ç5BQ
area default-costÄÞÞ **no** 6ÊÊ,Õ5BÄ
area *area-id* **default-cost** *cost*
no area *area-id* **default-cost**

ÐÄÊÞ

Ð	ÐÄ
area-id	STUB ê NSSA ,XÊÄ
cost	¾ STUB ÊÙ NSSA ,X5,Õ.CÃ,X8C.ÈÈÒ 1-16777214Ä

Ï5,Õ5BÐ 5,Õ 1

ÏÞ CÃE7Ç5BÄ

ÏĈĢĐ

Ǫ	ƐÄ
-	-

ĠÄȣ -

5.5 area nssa

ȼȷĐ OSPF Ⱥ'5B NSSAȣȣ*ĊÃE7Ġ5BǪ **area nssa**ÄĐǪ **no 6ȣ8** NSSA ê NSSA ¾XG5BÄ

area *area-id* **nssa** [**no-redistribution**] [**default-information-originate** [**metric** *value*] [**metric-type** *type*]] [**no-summary**] [**translator** [**stability-interval** *seconds* | **always**]]

no area *area-id* **nssa** [**no-redistribution**] [**default-information-originate** [**metric** *value*] [**metric-type** *type*]] [**no-summary**] [**translator** [**stability-interval** | **always**]]

ĐAȣ

Đ	ƐÄ
area-id	NSSA ¾XȣȣË
no-redistribution	**'ACÃĐ** NSSA ABRVȣp4ĐǪÃ +ȣ9BEKȣȣ}WE9 NSSA IȣȣEÍMÄ
default-information-originate	**{ȣȣ2O_** 7 ,X LSA E9 NSSA IȣȣEÍMĐ¼ NSSA ABR ȣÙ ASBR Ȣ
metric *value*	**A5B{ȣȣ5Õ** LSA ,XĐȣȣmetric 8ȣȣ 0-16777214ȣȣ ,Õ 1Ä
metric-type *type*	**A5B{ȣȣ5Õ** LSA ,XCÃ2O_Ä type ª 1 ê 2Ä 1 ></ N-1× 2 ></ N-2ȣȣ,Õ 2

- **area default-cost**

advertise ` not-advertise

A'ßÑÑ,XCÃÆÈ ABR {*ôXYF¾ÕÃÄ

þô OSPF ³A'5B!_ßÑQ **area stub ` area default-cost**Ñÿ!_}XCÃÛ

ÈÑÑOG5B area stub Ò¸ **area default-cost** ¸Ò¸Ô Stub ³X ABR Ø5BÄrea default-cost ¸¸ZF¾ÕÃ,XßÑCÃGÅÄ

Ï5B_Ð ¶Ú 1 A'5B!_ßÑbA³XCÃA'ÊÑÑOG5BÄ

```
5XLMLHFRQILJURXWHURVSI
5XLMLHFRQILJURXWHUQWR2UNDUHD
5XLMLHFRQILJURXWHUQWR2UNDUHD
5XLMLHFRQILJURXWHUDUHDVWXE
```

ÏÏGÐ¸

Ò¸	Ë¡Ä
area default-cost	**n Eî4-** STUB ¯5,Ø5.CÃ,X8Ï. Ø OSPF ,XGÅÄ

Ï GÄÅÐ -

5.8 area virtual-link

Ø¹n OSPF <.³JÒÃÆ*ÏÃE7Ï5BÒ¸ **area virtual-link**ÄÃÒ¸ **no 6ß8<ÐÃ nÄ**

area *area-id* **virtual-link** *router-id* [**authentication** [**message-digest** | **null**]] [**dead-interval** { *seconds* | **minimal hello-multiplier**

	0-65535 LSA ,X,#KÈ LSA ,X,#KÈ'ÔKÈ LSA
authentication-key [**0**|**7**] *key*	n OSPF AxA•XyÄ•KÈXAxA•XyÑÔÆ service password-encryption A•yt•XÄ 0 yf 7 yf
message-digest-key *key-id* **md5** [**0**|**7**] key	n OSPF MD5 AxA•XyÔyÄ•KÈX MD5 AxA•Xš JyÔyÑÔÆservice password-encryption A yt•XÄ 0 yf 7 yf
authentication	**A5BAxA2O_È*AxA•Ä**
message-digest	**A5BAxA2O_** MD5 AxA•Ä
null	**A5BAxA•Ä**

,Õ5BÐ **dead-interval** 0 /
hello-interval 0 /
retransmit-interval 5 /
transmit-delay 1 /
5,AxA•
5, Fast Hello s6Ñ
J-Ð'5Ý,Õ

CÃE7G5BÄ

*GG5BÄ

Ê5BÄ

ËG5B_Đ _ 1Ë 1 0E#ê• 2.2.2.2 Ô¥.3ÒÃ

5XLMLHFRQJEXLM ÉUð

Ð CÃE7G5BÄ

Ë*Ð -

G5B_Ð S*ü rfc 2328 ,XÐ.BnÔCÃÄ

```
5XLMLHFRQJURXWHURVSI
5XLMLHFRQJURXWHUQFRPPDWLEOHUIF
```

ÏGÐ

Ç	ÉÄ

GÄè -

5.13 default-information originate

Ð{*õ5,ÕCÃ¾ OSPF CÃÈË*ÍCÃE7G5BÇ **default-information originate**Ä

AÐ **no** 6ÉÕÃ

default-information originate [**always**] [**metric** *metric*] [**metric-type** *type*] [**route-map** *map-name*]

no default-information originate [**always**] [**metric**] [**metric-type**] [**route-map** *map-name*]

ÐAè

Ð	ÉÄ
always	AGk OSPF 5ê5,ÕÃÈ,õ5,Õ¾Ä
metric *metric*	5,Õ¾ÑXGÈÐ16777214 Ä 5,Õ¾,X2O_ÐOSPF ÉÍCÃÇO_ÐO_ 1ÈÃA'Û
metric-type *type*	ÐXGÐO_ 2ÈÃA'ÛXGÉÑ 2O_ 1

OSPF ¡¢£¤¥¦§¨©ª«¬®¯°±²³´µ¶·¸¹º»¼½¾¿ÀÁÂÃÄÅÆÇÈÉÊËÌÍÎÏÐÑÒÓÔÕÖ×ØÙÚÛÜÝÞßàáâãäåæçèéêëìíîïðñòóôõö÷øùúûüýþÿ

show ip route

STUB

G6(,X route-map ,X set metric

0-16777214

5XLMLHFRQJURXWHURVSI

5XLMLHFRQJURXWHUQWRUDHD

5XLMLHFRQJURXWHGHIDXOWLQRUPDLRULJLQDWHDOVPHWULFPHWULFWSH

Q	E
show ip ospf database	**/** OSPF JÒÕ

5XLMLHFRQJURXWHUGHIDXOWPHWULF
5XLMLHFRQJURXWHUUHGLVWULEXWHULSVXEQWV

SPF Au1k,XCÃ><NMÊü ABR ê

Ï*Ô **distribute-list out â redistribute route-map ÇÓÈ OSPF ,XCÃE> E›**
redistribute ÇÏ*Ä ACL E **prefix-list E**
ACL E **prefix-list E> E**

ÏG5B_Ð ÍGXM-ÕÃE> E$

```
5XLMLHFRQJURXWHURVSI
5XLMLHFRQJURXWHUHGLVWULEXWHVWDWLFVXEQWV
5XLMLHFRQJURXWHUGLVWULEXWHOLVWRXWVWDWLF
5XLMLHFRQJURXWHUGLVWULEXWHOLVWSUHIL[MMMRXWVWDWLF
FHVVOLVWILOWHUH[LVWVSOHDVHGHFRQJILUVW
```

ÏÎGÇ

Ç	Ë
distribute-list in	**G5B** LSA E
redistribute	**GVCÃ**

ÏGÄ -

5.19 enable mib-binding

enable mib-binding ÇÚ MIB 4 OSPFv2 E **no**
n
enable mib-binding
no enable mib-binding

ÐA

Ð	Ë
-	-

Ï,Õ5BÐ 5, MIB 4 OSPFv2 E

Ç CÃE 5B

Ï*Ô +b OSPFv2 MIB ü OSPFv2 E SNMP OSPFv2 E
E , SPFv2 MIB 4 OSPFv2 E
Vp* E› SNMP OSPFv2 E MIB 4 E

ÏG5B_Ð E SNMP E 100 ,X OSPFv2 E

```
5XLMLHFRQJURXWHURVSI
5XLMLHFRQJURXWHUHQEOHPLEELQLQ
```

ÏÎGÇ

Ç	Ë
show ip ospf	OSPF <G5B,X,ÏG
enable traps	**G5B** OSPF TRAP s6Ñ

ÏGÄ -

5.20 enable traps

OSPFv2 E7ÏÃÕ 16 /¡ TRAP Ç,ÉÐ 4 /¿O_È*vÃÑ5B|ù TRAP Ç,XÆÃÕ*Á¿X **no 6ÃÑ** TRAP Ç,XÆÃÕ

enable traps [**error** [**IfAuthFailure | IfConfigError | IfRxBadPacket | VirtIfAuthFailure | VirtIfConfigError | VirtIfRxBadPacket**] | **lsa** [**LsdbApproachOverflow | LsdbOverflow | MaxAgeLsa | OriginateLsa**] | **retransmit** [**IfTxRetransmit | VirtIfTxRetransmit**] | **state-change** [**IfStateChange | NbrRestartHelperStatusChange | NbrStateChange | NssaTranslatorStatusChange | RestartStatusChange | VirtIfStateChange | VirtNbrRestartHelperStatusChange | VirtNbrStateChange**]]

no enable traps [**error** [**IfAuthFailure | IfConfigError | IfRxBadPacket | VirtIfAuthFailure | VirtIfConfigError | VirtIfRxBadPacket**] | **lsa** [**LsdbApproachOverflow | LsdbOverflow | MaxAgeLsa | OriginateLsa**] | **retransmit** [**IfTxRetransmit | VirtIfTxRetransmit**] | **state-change** [**IfStateChange | NbrRestartHelperStatusChange | NbrStateChange | NssaTranslatorStatusChange | RestartStatusChange | VirtIfStateChange | VirtNbrRestartHelperStatusChange | VirtNbrStateChange**]]

ÐAÐ

Ð	Ë
	G5BÝ error Ý¢,X traps ÔÀÐEÃ5BV(Mn,X error Ý ¬,Å€

error

VirtNbrRestartHelperStatusChange GR

A”ÐpA’Ø6Ñ GR Help 6ÑÈ Grace-LSA é GR HelperÈY}Fà™
G disable EÍM#6ÐL7¸XAÊ>

area authentication	***ü** OSPF ?AxA•nAxAÄ
ip ospf authentication-key	**G5B** OSPF ,XßAxAðyÄ
ip ospf message-digest-key	**G5B** OSPF ,X MD5 AxAðyÄ

ÏGÄê -

5.23 ip ospf authentication-key

ØG5B OSPF ,XßAxAðyÈË*üG5BQ **ip ospf authentication-key**ÄßQ **no 6ê**
L8ßAxAðyÄ

ip ospf authentication-key [**0**|**7**] *key*

no ip ospf authentication-key

ÏÐAê

Đ	ËÄ
0	*bßß*
7	*bßß*
key	*yÐ* 8 þ0ú

ï5,Õ5BÐ 5,ÕÓ5BAxAðyÄ

ïQ yG5BÄ

ïS*Ô **ip ospf authentication-key** Q5BXßÝ OSPF yðyÄ
E?,XA'êÕÑÝ OSPF FG2Ë3ëÑ> CÃÇ,Xx6Ä
ð,Xyð5BÄ¥ê)5%‰CÃA'ÊOG5BQX3yÄ
ÞÔ OSPF ?AxAÈCÃE/G5BQ **area authentication E>G5BÄ**
ÿ¥ÃÑÀAxA• S*üßXG5BQ **ip ospf authentication E>G5B**, '?AxA•
ùAxAF5BÊ;XAxA2O_Ä

ï5B_Đ A'5B fastEthernet 0/1 0ÃX OSPF AxAðy ospfauthÄ

```
5XLMLHFRQILJXUHUIDFHIDVWHWKHUQW
5XLMLHFRQILJ)DVW(WKHUQWLSDGGUHVV
5XLMLHFRQILJ)DVW(WKHUQWLSRVSIDXWKHQWLFDWLRQHRVSIDXWK
```

ÎGQ

Q	ËÄ
area authentication	***ü** OSPF ?AxA•nAxAÄ
ip ospf authentication	***ü¥KAxAðAxAã**

ÏGÄê -

5.24 ip ospf bfd

G5BE¤ OSPF ,Xûy|6ÒGKÁ*ü BFD E> JÒÃ?ÈË*üG5BQ **ip ospf bfd**

[**disable**]Ä*üÄ¡Q× no 6ß8yÞ **ip ospf bfd G5BÄ**

ip ospf bfd [**disable**]

no ip ospf bfd [**disable**]

ÏÐAß

Ð	ÆÄ
disable	**GÉ¤** OSPF ,XûyS*ü BFD E> JÒÑ#

Ï,Õ5BÐ 5,ûX5BÈ OSPF E7G5BßX BFD G5BßÄ

ÏÞ yG5BÄ

Ï*Ûð yG5B,X¼{PÞE7G5BßX **bfd all-interfaces** Þ

|ÆrL)ÿWÈ› **ip ospf bfd ÞÛXyS*ü** BFD E> JÒÑßÄ*ü OSPF E7G5BßKÞ **bfd all-interfaces G5Bâ** OSPF E¤ ,XýÆ› BFD E> JÒÑ#Ï

*ü **ip ospf bfd disable EÉßyX** BFD "#s6Ñ

ÏG5B_Ð -

ÏGÞ

Þ	ÆÄ
router ospf	**Î** OSPF CÃE7ÐE9 OSPF CÃG5BÄ
bfd all-interfaces	**G5BE¤** OSPF ,XýS*ü BFD E> JÒÃ #Ä

ÏGÄß -

5.25 ip ospf cost

ÐA'5B OSPF yÆÞBÌX8CÄOSPF y· costÄË*üG5BÞ **ip ospf costÄ¹**

ß no 6ßßÞ

ip ospf cost *cost*

no ip ospf cost

ÐAß

Ð	ÆÄ
cost	OSPF y¡X8CÈÐ65535 Ä

Ï,Õ5BÐ OSPF y· cost 1b7ßÆ× yÄ

ÏÞ yG5BÄ

Ï*Ûð 5,ßOSPF y· cost 1b7ßÆ× yÄ

S*ü **auto-cost ÞÐ5ÄÕ** 100MbpsÄ

S*ü **bandwidth Þ5ByÄ**

/Ì_4“CÃX OSPF y· cost 5,Õ

64K > 4“CÃost 1562×

E1 4“CÊost 48×

10M þ5%Ècost 10×

100M þ5%È cost 1Ä

EÊ› **ip ospf cost Ç5B** OSPF y· costÞ5,Ç5BÄ

Ç5B_Ð A’5B fastEthernet *0*/1 y· cost 100Ä

```
5XLMLHFRQJLQWHUIDFHIDVW(WKHUQHW
5XLMLHFRQJLI)DVW(WKHUQHWLSRVSIFRVW
```

ÎÇÐ	Ç	ÊÄ

5.27 ip ospf dead-interval

ØA'5B OSPF ŵyF•Ou,XÊÆËë*ÿG5BQ ip ospf dead-intervalØ*ü OSPF
,X Fast Hello s6ÑË*ÿG5BQ ip ospf dead-interval minimal hello-multiplierÄQX no 6
ää,Õ5BÄ

ip ospf dead-interval { *seconds* **| minimal hello-multiplier** *multiplier* }

no ip ospf dead-interval

ÐAß \r

```
5XLMLHFRQJLI)DVW(WKHUQHWLSRVSIGHDGLQWHUYDOPLQPDOKHOORPXOWLSOLHU
```

ip ospf hello-interval	OSPF 接口 Hello 报文发送间隔
show ip ospf interface	显示 OSPF 的信息

-

5.28 ip ospf disable all

禁止在指定的 ospf 进程

ip ospf disable all

no ip ospf disable all

缺省	
-	-

-

缺省

-

命令模式

network area 命令指定的接口地址范围内的接口所属网络类型为

network 命令指定的接口所属网络类型为 OSPF 广播网络

```
5XLMLHFRQJLI)DVW(WKHUQHWLSRVSIGHDGLQWHUIDFHIDVW(WKHUQHW
5XLMLHFRQJLI)DVW(WKHUQHWLSRVSIGDGGUHVV
5XLMLHFRQJLI)DVW(WKHUQHWLSRVSIGLVDEOHDOO
```

缺省	
-	-

-

5.29 ip ospf hello-interval

配置接口发送 OSPF 报文的 Hello 报文发送间隔。使用 **ip ospf hello-interval** 命令可以修改接口发送 Hello 报文的间隔。使用 **no ip ospf hello-interval** 命令恢复缺省配置。

ip ospf hello-interval *seconds*

no ip ospf hello-interval

缺省	
seconds	指定接口发送 OSPF 报文的 hello 报文发送间隔	1-65535

Ï5,Õ5BÐ 5% 10 /ĸ
PPPÃDLC Õ¸X y· 10 /ĸ
1&&$· 10 /ĸ
M21&&$Ã.25 y· 30 /Ä

Ï yG5BÃ

Ï*Ô hello y[ÊÈÈhÙ hello y[ÄÊÈ^ÐSPF "#%ÞXÊÈÓÐ
rt5%4#GÃ%ÞXÓÃA'¸X hello y[ÊÈÈhNOÕÃpEÞ•
OuÊÈNOÃ• hello y[ÊÈÈhÑF•OuÊÈÃ

Ï5B_Ð Ú fastEthernet 0/1 y¡X OSPF ¥ÕÕ Hello y[ÊÈÈhA' 15 /Ä

```
5XLMLHFRQILJXUHIDFHIDVW(WKHUQHW
5XLMLHFRQILJI)DVW(WKHUQHWLSDGGUHVV
5XLMLHFRQILJI)DVW(WKHUQHWLSRVSIKHOORLQWHUYDO
```

ÏÕÐ

Ð	£Ä
ip ospf dead-interval	**A5B** OSPF ÞÐuÊÃ

Ï-

5.30 ip ospf message-digest-key

G5BÊ¿XAxA²O_Ä
RGOS ECÕ¾E> MD5 AxAª³yÊÃFI~ê8,XsÁÑÔÃ
A'ÛX OSPF MD5 AxAª³yÊCÃA'ÛxJWCÃA'Êu¹(X³yÊÊÝa
²X³y¼ÑÕ OSPF y[ÈBAxFÆG5BZX³yÝÇÃA'Ô5BZX³yÈ
Ê8¡X³yÄ

ËG5B_Đ fastEthernet 0/1 0ÃÊX OSPF AxAª³yÈyË 5È³y hello5Ä

```
5XLMLHFRQILJXUHIDFHIDVW(WKHUQHW
5XLMLHFRQILJI)DVW(WKHUQHWLSDGGUHVV
5XLMLHFRQILJI)DVW(WKHUQHWLSRVSIDXWKHQWLFDWLRQHVVDJHGLJHVW
5XLMLHFRQILJI)DVW(WKHUQHWLSRVSIPHVVDJHGLJHVWNHPGKHOOR
5XLMLHFRQILJI)DVW(WKHUQHWLSRVSIPHVVDJHGLJHVWNHPGKHOOR
```

1¸ÝXF¹ÑZX³yèFÇÃA'ÊÑÔ8¡X³yÄ

```
5XLMLHFRQILJXUHIDFHIDVW(WKHUQHW
5XLMLHFRQILJI)DVW(WKHUQHWLSRVSIPHVVDJHGLJHVWNHPGKHOOR
```

ÏÎGÐ

Ð	Ê
area authentication	***ü** OSPF ÃxA³nAxAÃ
ip ospf authentication	***ü**KAxA³AxAÃ

ËGÄÈ -

5.31 ip ospf mtu-ignore

Ð¼Ñ9A¼D BgÊ¿Ä[Ê mtu ,XÐÊ*ÄÇÐX **no 6È5Ð5BÄ**

ip ospf mtu-ignore

no ip ospf mtu-ignore

ËÐAÈ

Ð	Ê
-	-

Ë5,Ð5BÐ 5,È mtu E> ÐÄ

Ê¿ yG5BÈ

Ë*Ô OSPF DBgÊ¿Ä[ÊF•Xy¡X MTU 7Ê¿X MTU µÈ Vp,XDB gÊ¿Ä[ÛXy¡X MTU ûyy¡X MTU,FwF¼yG2ÈÑÔ,Ÿ 8ÊÊ¿GKÁ MTU ,XÐ¹9Ê

ËG5B_Đ Ú fastEthernet 0/1 ,X MTU Ð¹s6ÑKÄ

```
5XLMLHFRQILJXUHIDFHIDVW(WKHUQHW
5XLMLHFRQILJI)DVW(WKHUQHWLSRVSIPWXLJQUH
```

ÏÎGÐ

Ð	Ê

-	-

ÏGÄÀê -

5.32 ip ospf network

A'ny¡X OSPF 5%42O_Ä ĘX **no 6ĕ5Õ5BÄ**

ip ospf network { **broadcast** | **non-broadcast** | **point-to-multipoint** [**non-broadcast**] | **point-to-point** }

no ip ospf network

ÐAê

Đ	ĘÄ
broadcast	ý**A**h**S**2**O**_Ä
non-broadcast	ý**A**h NBMA 2O_Ä
point-to-multipoint	ý**A**h P2MP 2O_Ä
[**non-broadcast**]	Vpyk Ŝ6ñÈÛ non-broadcast ÐÄ
point-to-point	ý**A**h P2P 2O_Ä

ï,Õ5BÐ S2O_ĕ%Õ™

P2P 2O_Ð PPĘLIP Ãà&8ÃÄ.25 à&ÿÕ™

NBMA 2O_ÐÄà&ÿL8Ã.25 ÕÄà&ÿL8Å

5,Ũý· P2MP 2O_Ä

ïĕ yG5BÄ

ïŠ*Ð S2O_Ðý̈KŚ6ñÄ

P2P 2O_Ðý· 1 Í 1 f6(Ä

NBMA 2O_Ð<5%(Šý6(,XCÃA'ÛO6ĵÊ?Ä

P2MP 2O_ÐÄ

ïG5B_Đ _ 1Ðý A'n P2P 2O_ÈÖ 1 Í 1 f6(,XÄ

```
5XLMLHFRQJLQWHUIDFH6HULDO
5XLMLHFRQJ6HULDOLSDGGUHVV
5XLMLHFRQJ6HULDOHQDSVXODWLRQJDPHUHOD\
5XLMLHFRQJ6HULDOLSRVSIHQWR2UNSRLQWWRSRLQW
```

_ 2Ðý A'n NBMA 2O_ÈÏ5%(Šý Ä

```
5XLMLHFRQJLQWHUIDFH6HULDO
5XLMLHFRQJ6HULDOLSDGGUHVV
5XLMLHFRQJ6HULDOHQDSVXODWLRQJDPHUHOD\
5XLMLHFRQJ6HULDOLSRVSIHQWR2UNSRQURDGFDVW
5XLMLHFRQJ6HULDOH[LW
5XLMLHFRQJURXWHURSI
5XLMLHFRQJURXWHUHLJKERUSULRULWSROOLQWHUYDO
```

ÏÎGĘ

Ę	Ë.Ä
dialer map ip	**n** IP ø¢ÕXØ
frame-relay map	**n** IP â» DLCI ,XØ
neighbor	ûFÈÖ NBMA 2O_` P2MP 2O_Ä
X25 map	**n** IP â X.25 5%4¦XØ
ip ospf priority	**ûy·** DR/RDR ¼{Ä

ĠÄâ -

5.33 ip ospf priority

ØG5By¡X OSPFÆË*µG5BĘ **ip ospf priority**ÄĄ **no**

seconds	LSU 1-65535

area virtual-link retransmit-interval

area virtual-link	**n** OSPF

5.35 ip ospf transmit-delay

ip ospf transmit-delay *seconds*

no ip ospf transmit-delay

seconds	*n* OSPF LSU 1-65535

Ï5B_Ð Ú fastEthernet 0/1 ,XEgÊ’ 10Ä

```
5XLMLHFRQJLQWHUIDFHIDVW(WKHUQHW
5XLMLHFRQJLI)DVW(WKHUQHWLSVSIWUDQVPLWGHOD\
```

ÏGÐ

Ç	Ë
area virtual-link	**n** OSPF <.3ÒÃ

ÏGÄð -

5.36 log-adj-changes

AÇ'5BÁ)Fy(ÕXÈÇX no ` default EÝMÕKÁs6ÑÑ

log-adj-changes [**detail**]

no log-adj-changes [**detail**]

ÐAð

Ð	Ë
detail	**AÇ**

ï,Õ5BÐ 5,Ø s6ð detail ÐÈ)Fy(Õ' Full ôÒ Full (ÕXÇÄ

ð CÃE7G5Bä

Ò*Ð -

Ï5B_Ð 'Ê(ÕXÄ

```
5XLMLHFRQJURXWHURSI
5XLMLHFRQJURXWHUORJDGMFKDQHVGHWDLO
```

ÏGÇ

Ç	Ë
show ip ospf	ß ospf <G5B,X,ÒÇÄ

ÏGÄð -

5.37 max-concurrent-dd

AG5B*ÜA'5B'(ç3ß-2_Ø CKüÇFð,)Ä

x-iconcurrent-d

ï5,Õ5BÐ 5,Õ 5Ä

ïÐ CÃE7G5BÄ

ïß*Ô 'CÃA'ÊÄ6DBÈÑÊ5BAÊÐ OSPF r_AÐE
ÊxfÈKêÅXFÔ,Â

ïG5B_Ð ÚxfÈKêÅXFÔ,Â'5B 4ÆG5B,XpGExf,XEÆÈ'Ô
AÐEKâ 4 ÞxfÈÔÐ 4 ÞFCK,XxfÈA'Ð
8 ÞFE> xfÄ
5XLMLHFRQJURXWHURVSI
5XLMLHFRQJURXWHUPD[FRQXUUHQWGG

ïÎGÐ

Ð	Ä
router ospf max-concurrent-dd	A'5BÝ OSPF CÃE7ÊxfXFÔ D,Â

ïGÄÐ -

5.38 max-metric

ÔG5BE¤ OSPF #A,XCÃA'ÊÔÈWCÃA'Ô SPF Au1kÚA'Ô
Eg8V&ÆÈCÃE7G5BÐß*Ð **max-metricÄ*ÆÐ** **no 6ÊÔGÄ**

max-metric router-lsa [**external-lsa** [*max-metric-value*]] [**include-stub**] [**on-startup** [*seconds*]] [**summary-lsa** [*max-metric-value*]]

no max-metric router-lsa [**external-lsa** [*max-metric-value*]] [**include-stub**] [**on-startup** [*seconds*]] [**summary-lsa** [*max-metric-value*]]

ïÐÐ

Ð	Ä
router-lsa	*GB* Router LSA ,XM2 stub links ,XÈÔxFFFF Å
external-lsa	**G5BCÃß*ÔGÄ¼** LSAÐl Type-5 ` Type-7Å ,XÈÄ
max-metric-value	LSA ,XÔÄ,Õ 16711680ÐÔ-16777215 Ä
include-stub	*GÃÊî* Router LSA ,X stub links ÔÄ
on-startup	**G5BCÃÊÔGÄ**
seconds	**EÔGXÔÈhÄ,Õ** 600sÐÔ-86400 Ä
summary-lsa	**G5BCÃß*ÔGÄ** LSAÐl Type-3 ` Type-4Å ,XÈÄ

ï5,Õ5BÐ 5,ÊÐ7È-X LSAsÄ

ïÐ CÃE7G5BÄ

max-metric router-lsa Router LSA ,XM2 stub links ,XC
FFFF
stub links **include-stub**
stub links
0 ABR **summary-lsa** LSA
0 ASBR **external-lsa** LSA
max-metric router-lsa
BGP BGP
on-startup
OSPF r) RFC 1247 (LSA links SPF
LSAs ,XC

100 /

```
5XLMLHFRQJURXWHURSI
5XLMLHFRQJURXWHUPD[PHWULFURXWHUOVDRQWDUWXS
```

show ip ospf	ospf ,X,

-

5.39 neighbor

OSPF **neighbor** **no**

neighbor *ip-address* [**poll-interval** *seconds*] [**priority** *priority*] [**cost** *cost*]

no neighbor *ip-address* [**poll-interval**] [**priority**] | [**cost**]

ip-address	IP
poll-interval *seconds*	2147483647 NBMA 2O
priority *priority*	255 NBMA 2O
cost *cost*	65535 P2MP 2O

5,
120 /
M2S 0

	NBMA 2O_y P2MP 2O_M2S IP IP ü NBMA 5%4 Hello y[È OSPF Hello y[Hello y[,È/ OSPF 1 0 , Hello y[È’ 0 , DR/BDR ,X0 1 DR/BDR {* DR/BDR Hello y[0 ü P2MP M2S 5%4 OS* P2MP 2O_,X5%4 cost
	ü NBMA 5%4 172.16.24.2È 1È 150 /

ÏG5B_Đ n 3 þÐ 0È 1È 172.16.16.0Á IP :ü 192.168.12.0/24 8Ê,Xyn³ 1Ê IP :ü 172.16.16.0/20 8Ê,Xyn³ 172.16.16.0Ê-yn³ 0Ä

```
5XLMLHFRQJURXWHURVSI
5XLMLHFRQJURXWHUQWR2UNDUHD
5XLMLHFRQJURXWHUQWR2UNDUHD
5XLMLHFRQJURXWHUQWR2UNDUHD
```

ÏÎGĘĐ

no overflow database external

ÏDAêè

Ð	ÆÄ
max-dbsize	external lsa ,XÛ,Â AS YÉÃA'ÛLÆÂ 8è-2147483647 Ä
wait-time	ÆÉÛ overflow (ÃÈE{ÕÛY,XÊÈ 0-2147483647Ä

Ï,Õ5BÐ 5,ÆÕ$ external-LSA ,XÛ,Â
VpL$ external-LSA ÛÈ external-LSA ,XD,ÂYEG5B,XÆ6ÃÕ

ÏÞ CÃE7G5BÆ

Ï*Û 'A'ÛX external-LSA D,ÂYEG5B,X *max-dbsize* ÆE¯9$ÛÃ{Æ *tEQ*
external-LSAÈÉÙ8*ÞX external-LSAÄ4E› *wait-time* Æ6ÊÞ¡
tEQ external-LSAÄ
S*A$6ÑOÆ• OSPF F¤BE¡XÉÃ<G5B,ÈX *max-dbsize* È ÆÑ
ÆÞ
H5%,XJÒ(ÕBgÆ'ÊÆ' Full (Õ
JÁ,ÃXCÃÞÆ,ÃX‰
Ne4,X AS-External-LSA GÞ

ÏG5B_Ð G5B external lsa Û,Â 10ÈYE¡ overflow (ÆÊ overflow (Õ¢XÆÈÈh
3 /Ä
5XLMLHFRQJURXWHURVSI
5XLMLHFRQJURXWHURYHUIORZGDWDEDVHH[WHUQO

ÎGÞ

Ò	ÆÄ
-	-

ÏGÄè -

5.43 overflow memory-lack

AÞXÆÉÊ OSPF E9 OVERFLOW (Õ*AÞX no EÑMGKÁ$6Ñ
overflow memory-lack
no overflow memory-lack

ÏDAè

Ð	ÆÄ
-	-

Ï,Õ5BÐ Y,É‰ OSPF AÆ9 OVERFLOW (Õ

ÏÞ CÃE7G5Bã

OSPF E9 OVERFLOW (

OSPF E9 OVERFLOW (

OSPF

G5BGý **isis C** level ÐÊAxA level-2 ,XCÃ G5BG

ú level Ð G5B,X level Ð,XCÃ G5B G5B level 1, level 2 level-1-2 ÐÄ

G5BGý **ospf C** match ÐÊAxAG O_,X ospf CÃ× 5X1Ô

G5B match Ð match ÐÈ G XO_,XCÃE no Q

match ÐTAxA

G5BG G5B route-map E route-map ,X match GýKsE G

bGý OSPF ISIS C XCÃ G5B,X match level ,X E route-map ,X

G6(,X route-map ,X set metric <0-16777214> CYÎ C

redistribute no 6 G5B,X

1 **no** G5B×

2 **no**

_V G5BZ **redistribute isis 112 level-2** **no redistribute isis 112 level-2** G5B

level-2 Ð level-2 D no

5B **redistribute isis 112 level-2** **no redistribute isis 112** G5B_Ð Ú ospf 2 ` isis isis-001 Gý OSPF1Ö

```
5XLMLHFRQJURXWHURVSI
5XLMLHFRQJURXWHUUHGLVWULEXWHRVSIVXEQWV
5XLMLHFRQJURXWHUUHGLVWULEXWHRVSIPDWFKH[WHUQOLQWHUQO
5XLMLHFRQJURXWHUUHGLVWULEXWHWLVLVLV
5XLMLHFRQJURXWHUUHGLVWULEXWHWLVLVLVLVOHYHO
```

show run /4 VÖ

```
URXWHURVSI
UHGLVWULEXWHRVSIPDWFKH[WHUQOLQWHUQOVXEQWV
UHGLVWULEXWHWLVLVLVLVOHYHO
```

ÏGQ

Q	Ä
summary-address	**G5B** OSPF CÃ ,X6.CÃÄ
default-metric	**A5B** OSPF GÃ ,X5,

GÄ -

5.46 router ospf

Ï OSPF CÃE OSPF CÃG5B G5BQ router ospf X no 6 8 X OSPF CÃE

router ospf

router ospf *process-id* [**vrf** *vrf-name*]

no router ospf *process-id*

Ð

Ð	Ä
process-id	OSPF E 5BE < /G5BE 1Ä

	vrf-name	û OSPF E7Ø,X VRF

Ï5,Õ5BÐ	5,ñ	OSPF CÃE7Ã
ë	<G5Bã	
Ï*Ð	RGOS10.1	

ËG5B_Ð

```
5XLMLHVKRZLSRVSI
5RXWLQJ3URFHVVRVSIZLWK,'
'RPDLQWSH[YDOXH[
3URFHVVXSWLPHLVPLQXWHV
3URFHVVERXQGWR95)GHIDXOW
0HPRU\RYHUIORZLVHQDEOHG
5RXWHULVQRWLQRYHUIORZVWDWHQRZ
&RQIRUPVWR5)&DQG5)&&RPSDWLELOLW\IODJLVHQDEOHG
6XSSRUWVRQO\VLQJOH726726URXWHV
(QDEOHWZRZPDLQWDLQ
6XSSRUWVRSDTXH/6$
6XSSRUWV*UDFHIXO5HVWDUW
7KLVURXWHULVDQ$%5LQWHFWLQH[WHUQDOURXWLQJLQIRUPDWLRQ
2ULJLQDWLQJURXWHU/6$VZLWKPD[LPXPPHWULF
&RQGLWLRQRQVWDUWXSIRUVHFRQGV6WDWHLQDFWLYH
$GYHUWLVHVWXEOLQNVZLWKPD[LPXPPHWULFLQURXWHU/6$V
$GYHUWLVHVXPPDU\/6$VZLWKPHWULF
$GYHUWLVHH[WHUQDO/6$VZLWKPHWULF
8QHWUHDVRQWLPHUH[SLUHG2ULJLQDWHGIRUVHFRQGV
8QHWWLPH7LPHHODSVHG
63)VFKHGXOHGHOD\VHFV+ROGWLPHEHWZHHQWZR63)VVHFV
,QLWLDO/6$WKURWWOHGHOD\PVHFV
0LQLPXPKROGWLPHIRU/6$WKURWWOHPVHFV
0D[LPXPZDLWWLPHIRU/6$WKURWWOHPVHFV
/VD7UDQVPLW3DFLQJWLPHUPVHFV/68SG
0LQLPXP/6$DUULYDOPVHFV
3DFLQJIODJURXSVHFV
1XPEHURILQFRPPLQJFXUUHQW'H[FKDQJHQHLJKERUV
1XPEHURIRXWJRLQJFXUUHQW'H[FKDQJHQHLJKERUV
1XPEHURIH[WHUQDO/6$&KHFNVXP[(
1XPEHURIRSDTXH$/6$&KHFNVXP[
1XPEHURIQRQHIDXOWH[WHUQDO/6$
([WHUQDO/6$GDWDEDVHLVXQOLPLWHG
1XPEHURI/6$RULJLQDWHG
1XPEHURI/6$UHFHLYHG
/RJ1HLJKERU$GMHQF\&KDQJHV(QDEOHG
*UDFHIXOUHVWDUWGLVDEOHG
*UDFHIXOUHVWDUWKHOSHUVXSSRUWHQDEOHG
1XPEHURIDUHDVDWWDFKHGWRWKLVURXWHU
%)'HQDEOHG
$UHD%$&.%21(
1XPEHURILQWHUIDFHVLQWKLVDUHDLV
1XPEHURIIXOOTf0 0ÈÕÆ
```

```
6KRZDVSRXWHGDWDEDVH
63)OLVWKPODVWH[HFXWHGDJR
63)OLVWKPH[HFXWHGWLPHV
1XPEHURI/6$&KHFNVXP[EI
6KRZ166$
1XPEHURILQWHUIDFHVLQWKLVDUHDV
1XPEHURIIXOODGMDFHQWQELJKERUVLQWKLVDUHDV
1XPEHURIIXOODGMDFHQWYLUWXDOQELJKERUVWKURXJKWKLVDUHDV
6KRZDVSRXWHGDWDEDVH
63)OLVWKPODVWH[HFXWHGDJR
63)OLVWKPH[HFXWHGWLPHV
1XPEHURI/6$&KHFNVXP[
166$UDQGODWU6WDWHLVGLVDEOHGEWDELOLW\QWHUYDOH[SLUHGLQ
```

+‰	AÈ
Router ID	CÃA'ÛßÄ
Process uptime	OSPF E7ßXÊÊouter-id 0.0.0.0 Ê7ßo ,XÅ
Bound to VRF	OSPF E7Ø,X VRFÄ
Conforms to RFC2328	â RFC2328 ÔÆÄ
RFC1583Compatibility flag	Au1kÊÇÃÊ³¡X RFC1583 Ø¬ RFC2328 ,X? ÊØ,X ASBR CÃEWÊÊÞÄ
Support Tos	Õ TOS0Ä
Supports opaque LSA	Õ opaque-LSAÄ
Graceful-restart	RFC3623 Graceful Restart Ê,ÄX GR Restart 6ÑÄ
Graceful-restart helper	RFC3623 Graceful Restart Ê,ÄX GR Help 6ÑÄ
Router Type	OSPF CÃA'ØO_Ý normal ÃBR ÃSBR Ä
SPF Delay	‰Å×ü SPF E¹kÙÊ³XÊÊ
SPF-holdtime	ø SPF Au1kKÈ4ßXÊÊ
LsaGroupPacing	LSA ,XÈAu1kÊÊ,XÊÊÈhÄ
Incomming current DD exchange neighbors	7ïf,XFÐDGÈ incomming Ôj Ê9 exstart (ÑXFÄ
Outgoing current DD exchange neighbors	7ïf,XFÐDGÈ outgoing Ø(ÑÔ exstart Gx f,XFÄ
Number of external LSA	DBg,|,XÊ¼ LSA ,XDGÆÄ
External LSA Checksum Sum	DBg,|,XÊ¼ LSA ,X"P`XÄ
Number of opaque LSA	DBg,|,X opaque-LSA ,XDGÆÄ
Opaque LSA Checksum Sum	DBg,|,X opaque-LSA ,X"P`XÄ
Number of non-default external LSA	M25,ÕÃ,X external-LSA ,XDGÆÄ
External LSA database limit	external-LSA DGÆÄ
Exit database overflow state	

Ø S P / F g < B A 9 Y b •

```
&RGHVL,QWUDDUHDURXWH,,QWHUDUHDURXWH
L>@LD)DVW(WKHUQHW%56%5HDVHOHFW
```

+‰	AÈ
Codes	CÃ2O_-ÕÄ ></ÝFÇÃÈ ></ÞÈÃÄ
I	></AÇÃÝFÇÃÄ
1.1.1.1	/E← CÃA'ÎX OSPF ÎÖÅ
[2]	/E'AÆ← CÃA'ÎX8CÆost Å
via 10.0.0.1	/E'E← CÃA'ÎXÔÕ%GÄ
FastEthernet 0/1	/E'E← CÃA'ÎXyÄ
ABR, ASBR	/E← CÃA'ÎX2O_ÝÆ ABR ` ASBR ÆÆ ABR ` ASBRÄ
Area 0.0.0.1	/:4ACÃ,XÄ
select	'ÞCÃE' ASBR È select ></'E¾ÔÃÄ

ÏÎGÇÐ

Ç	ÆÄ
-	-

ÏGÄÈ -

5.51 show ip ospf database

Ò/ OSPF JÒÃÕBgÇÆÈ*(M*ÇÐ **show ip ospf databaseÄÇÐ**

Net Link States	></	5%4JÒ(ÕÄ
Summary Net Link States	></	5%4JÒ(ÕÄ
NSSA-external Link States	></	2O,X7 JÒ(ÕÄ
AS External Link States	></	h2O,X7 JÒ(ÕÄ
Link ID	JÒÕ
ADV Router	EJÒ(ÕXCÃA’
Age	/AJÒ(ÕX,
Seq#	/AJÒ(ÕXcÊ”#5ÇXG
Cksum	/AJÒ(ÕXÞÄ
Link-Count	/CÃA’JÒ(Õ,XJÒÃXDG£
Route	/8 LSA XCÃ
Tag	/AJÒ(ÕXÄ

_ 2Ösh**ow ip ospf database asbr-summary**

```
5XLMLHVKRZSRVSIGDWDEDVHDVEUVXPPH
263)5RXWHU0DP
6%56XPPH/LQ6WDWH(
/6DJH
2SWLRQ_____(_
/67
/LQ6WDWH,'(6RXQDP5RXWHU0HVV
6HpA
/66HT1XPEH
&KHFNVXP[EHF
/HQWK
1HWR2UN0HN
7260HWULF
```

+‰	A
OSPF Router with ID	/Ch,XCÃA’ OSPF Í h,XE/
AS Summary Link States	></X AS ,JÒÄ
LS age	/AJÒ(ÕX,
Options	EMÄ
LS Type	/AJÒ(ÕX2O_Ä
Link State ID	/AJÒ(ÕXJÒÕ
Advertising Router	/AJÒ(ÕXEÃA’

TOS	TOS
Metric	

_ 3. **show ip ospf database external**

```
5XLMLHVKRZSRVSIGDWDEDVHH[WHUQO
263)5RXWHUZWK,'3URFHVV,'
6([WHUQO/LQ6WDWHV
/6DJH
2SWLRQ[_____(_
/67SH6H[WHUQO/6$
/LQ6WDWH,'([WHUQO1HWZRUN1XPEHU
6YHUWLVLQ5RXWHU
/66HT1XPEHUD
&KHFNVXP[
/HQWK
1HWZRUN0DVN
0HWULF7SH/DUHUWKDQQLQVWDWHSDWK
726
0HWULF
)RUZDUG6GUHVV
([WHUQO5RXWH7DJ
```

OSPF Router with ID	OSPF
Type-5 AS External Link States	
LS age	
Options	
LS Type	
Link State ID	
Advertising Router	
LS Seq Number	
Checksum	
Length	
Network Mask	

show ip ospf database network

```
5XLMLHVKRZSRVSIGDWDEDVHQHWZRUN
263)5RXWHUZLWK,'3URFHVV,'
1HWZRUN/LQN6WDWHVHHD
/6DJH
2SWLRQ[_____(_
/67SHQHWZRUN/6$
/LQN6WDWH,'DGGUHVVRI'HVLJQDWHG5RXWHU
$GYHUWLVLQJ5RXWHU
/66HT1XPEHU
&KHFNVXP[
/HQJWK
1HWZRUN0DVN
WWDFKHG5RXWHU
WWDFKHG5RXWHU
```

```
/HQWK
1XPEHURI/LQNV
/LQNFRQQHFWHGWR6WXE1HWZRUN
/LQN,'1HWZRUNVXEQHWXQPEHU
/LQN'DWD1HWZRUN0DVN
1XPEHURI726PHWULFV
7260HWULF
```

+‰	AÈ
OSPF Router with ID	/Bh,XCÃA'ÛÕá OSPF Í h,XE/È
Router Link States	></BÃA'ÛÒÕÈÄ
LS age	/AÒÕÈX,È
Options	EÍM
Flag	router ,Xû
LS Type	/AÒÕÈX2O_Ä
Link State ID	/AÒÕÈXJÒÕÈ
Advertising Router	/AÒÕÈXECÃA'Û
LS Seq Number	/AÒÕÈXcÈ
Checksum	/AÒÕÈXÞÄ
Length	/AÒÕÈXKSÈ8V)Ä
Number of Links	/AÃA'Û6(,XJÒÕÄ
Link connected to	/JÒÃAÊýÈ%42O_Ä
(Link ID)	JÒÕÈ
(Link Data)	JÒÕBÄ
Number of TOS metrics	TOS Ø TOS0Ä
TOS 0 Metrics	TOSÒÈ

_ 6ê **show ip ospf database summary** Ø/4ß

```
5XLMLHVKRZSRVSIGDWDEDVHVXPPDU\
263)5RXWHUZWK,'3URFHVV,'
6XPPDU\LQN6WDWHVSHD
/6DJH
2SWLRQ[_____(_
/67SHVXPPDU\6$
/LQN6WDWH,'VXPPDU1HWZRUN1XPEHU
SYHUWLVLQJ5RXWHU
/66HT1XPEHU
&KHFNVXP[H
/HQWK
1HWZRUN0DVN
7260HWULF
```

+‰	AÈ

OSPF Router with ID

OSPF Í

interface-type	*ûÿ¿2OÄ*
interface-number	*ûÿ¿4Æ*

Ï¿Õ5BÐ -

Ïð (M*ã

Ï*Ðð 8ßÿ¿E¤ OSPFÈ£oyC³ OSPF ,ÌG,XA’5BÇÄ

Ï5B_Ð 5XLMLHVKRWZSRVSILQWHUIDFHIDVW(WKHUQHW
)DVW(WKHUQHWLVXSLQSURWRFROLVXS
,QWHUQHWGGUHVV,ILQH[SHD078
0DFKLQHWRUNFRQJ
3URFHVV,'5RXWHU,'1HWZRUN7\SH%52$&67&RVW
7UDQVPLW'HODLVVHF6WDWH'53ULRULW\)'HQEOHG
'HVLJQWHG5RXWHU,',QWHUIDFHGGUHVV
%DFNXS'HVLJQWHG5RXWHU,',QWHUIDFHGGUHVV
7LPHULQWHUYDOVFRQJXUHG+HOOR'HDG:DLW5HWUDQVPLW
+HOORGXHLQ
1HLJKERU&RXQWLVGMDFHQWQHLJKERUFRXQWLV
&USW6HTXHQH1XPEHULV
+HOORUHFHLYHGVHQW"UHFHLYHGVHQW
/65HTUHFHLYHGVHQW/68SGUHFHLYHGVHQW
/6NUHFHLYHGVHQW"LVFDUGHG

+‰	Aê
FastEthernet 0/1 State	A5%4ÿ;X(Õ UP Aè0È Down Aê ÝpÄ
Internet Address	y· IP Ä
Area	y2 OSPF ÆÄ
MTU	Íh,X MTU
Matching network config	Íh OSPF E7ÐX network area G5B
Process ID	Íh,XE7Ð
Router ID	OSPF CÆA’ÛšÄ
Network Type	OSPF 5%42O_Ä
Cost	OSPF y8CÄ
Transmit Delay is	OSPF yêgÆ
State	DR/BDR (ÕÛšÄ
Priority	Aÿ;X¾{
Designated Router(ID)	Aÿ;X DR ,XCÆA’ÛšÄ
DR's Interface address	Aÿ;X DR ,Xy·
Backup designated router(ID)	Aÿ;X BDR ,XCÆA’ÛšÄ
BDR's Interface address	Aÿ;X BDR ,Xy·

Time intervals configured	yń,X HelloÈeadÈVait ÈetransmitÊÈ
Hello due in	HELLO
Neighbor count	FÐ
Adjacent neighbor count	Full ,XFÐG£
Crypt Sequence Number	yń,X md5 AxA;XcË
Hello received send	HELLO y[4ÆuÄ
DD received send	DD y[4ÆuÄ
LS-Req received send	LS y[4ÆuÄ
LS-Upd received send	LS y[4ÆuÄ
LS-Ack received send	LS ny[4ÆuÄ
Discard	OSPF y[4ÆuÄ
BFD enabled	OSPF â BFD 6(|

Q	EÄ
-	-

-

5.53 show ip ospf neighbor

/ OSPF ,XF<ÈË*(M* **show ip ospf neighborÄ**

show ip ospf [*process-id*] **neighbor** [**detail**] [*interface-type interface-number*] [*neighbor-id*]]

Ð	EÄ
process-id	OSPF E
detail	**/FA**
interface-type *interface-number*	*/*
neighbor-id	*/*

-

(M*

A OSPF E Ä

```
5XLMLHVKRZ SRVSIQLJKERU
263)SURFHVV1HLJKERUVLV)XOO
1HLJKERU,'3UL6WDWH%)'6WDWH'HDG7LPHGGUHVV,QWHUIDFH
)XOO%'58S)DVW(WKHUQW
```

```
5XLMLHVKRZ SRVSIQLJKERUGHWDLO
1HLJKERULQWHUIDFHDGGUHVV
```

```
,QWKHDUHDYLDLQWHUIFH)DVW(WKHUQW
1HLJKERUSULRULW\LV6WDWHV)XOOVWDWHFKDQHV
'5LV%'5LV
2SWLRQLV[_2__($__(_
'HDGWLPHUGXHLQ
1HLJKERULVXSIRU
```

Link State Request List	F• LS A[47Au
Link State Retransmission List	FG[47Au
Crypt Sequence Number	3 MD5 AxA•Õ
Thread Inactivity Timer	Fn(Õ
Thread Database Description Retransmission	8y· DD y[n(Õ
Thread Link State Request Retransmission	8y· LS A[n(Õ
Thread Link State Update Retransmission	8y· LS [n(Õ
Thread Poll Timer	M-Õ5B,XFPoll Timer |(Õ
Graceful-restart helper	LS

ÏÎGÐÇ

Ç	ÐÄ
-	-

ÏGÄÐè -

5.55 show ip ospf spf

/ OSPF ¾XCÃÄAu1k ÐÞ

show ip ospf [*process-id*] **spf**

ÏÐAÐè

Ð	ÐÄ
process-id	OSPF EÏÐ£

Ï5,Õ5BÐ -

ÏÐÇ (M*ð

Ï5*ÐÞ AÇÐ¦ß OSFP Ð¥ 30 ÚsYCÃÄAu1k,X ÐÞ7ÚÊÈÃÄAu1k,X ÐÞÄ

ÏG5B_Ð

```
5XLMLHVKRZSRVSIVSI

263)SURFHVV
HDBLGPLBFRXQWV7RWDOBFRXQWV
```

+‰	Aè£
Area_id	OSPF ³ ID
30min_counts	Ð¥ 30 ÚsÊÈÐSPF CÃÄAu1k,X ÐÞ
Total_counts	7ÚÊÈÐSPF CÃÄAu1k,X ÐÞ

ÏÎGÐÇ

Ç	ÐÄ
show ip ospf	/ OSPF ÇVÐÞ

ÏGÄÐè -

5.56 show ip ospf summary-address

ÐÞ/ OSPF ÚÉÚÃ,X5.CÃÄË*(M*ðÇ **show ip ospf summary-addressÄ**

show ip ospf [*process-id*] **summary-address**

ÏÐAÐè

Ð	ÐÄ

process-id OSPF

```
7UDQVLWDUHDYLDLQWHUIDFH)DVW(WKHUQHW
/RFDODGGUHVV
5HPRWHDGGUHVV
7UDQVPLW'HODLVVHF6WDWH3RLQW7R3RLQW
7LPHULQWHUYDOVFRQJXUHG+HOOR'HG:DLW5HWUDQVPLW
+HOORGXHLQ
6MDFHEVWDWH)XOO
```

+‰	AÈ
Virtual Link VLINK0 to router	/<.ÌÒÃXF
Virtual Link state	A<.ÌÒÃX(
Transit area	/<.ÌÒÃXE#
via interface	/<.ÌÒÃXG6(y
Local address	0
Remote Address	0

E‡- OSPF CÃA’ûp¾XCÃÊ4Á0NKÈ‡ CÃA’Êþ

5.60 timers pacing lsa-group

AQ'5B LSA 5,Õy#PD

Ä

CÃE7G5BÄ

Ê*Ô

)W LSA DGÈ'ÔÞ0KÊ5BEÖX **transmit-time ` transmit-count Ã**

54Ä LS-UPD y[DGÄ

CPU B0KÊÈ%4B0KÊ **transmit-time rt transmit-count ÔVX/Ä**

G5B_Đ

G5Byß 50ms ¥ÕÔ LS-UPD y[ÈÄ¥Õ 20 ÿ[Ä

```
5XLMLHFRQJURXWHURVSI
5XLMLHFRQJURXWHUWLPHUVSFLQDVDWUDQPLW
```

ÏGĐ

Ç	ÉÄ
show ip ospf	**/** OSPF E7[XÇÉÃA'ÔÞÄ

GÄè

-

5.62 timers spf

ØG5B OSPF ÿ%,XÇÈ> SPF Au1k,XÊÈ SPF Au1k,XÊÈhÈ

Ã*ÇCÃE7G5BÇ **timers spfÄÇ** no 6ÈÃ,Õ5BÄ

timers spf *spf-delay spf-holdtime*

no timers spf

ĐAè

Đ	ÉÄ
spf-delay	*n* SPF Au1k,X1YÈÊ 0-2147483647(/}Ä OSPF CÃE7G%ÈO1ûÇXÊÈ> SPF E¤1kÄ
spf-holdtime	*n ø õ* SPF E ¤1 k K È¸X ÊK ÈK È h È¼/¦) ! È B ×È 0-2147483647(/}ÄYÊÈ6¤1kKÈhÊÈÈ6Ñ E> SPF E¤1kÄ

Ê,Õ5BĐ

ü RGOS 10.4 (Ê **timers throttle spf Ç45Õ** **timers spf** 5 10Ä

RGOS 10.4 (Ê **timers throttle spf Ç5%** **timers spf È**SPF

Au1kÊ **timers throttle spf Ç5Õ5BÈ** **timers throttle spf ÇÄ**

Ä

CÃE7G5BÄ

Ê*Ô

spf-delay ` spf-holdtime ÄÈSPF E%ÊXÊÈC¤ÄAÈ%4/ÊÈ

C¤Ê*ÇCÃA'ÔX CPU ÊÄ

timers spf G5Bâ timers throttle spf G5BÔÄ

G5B_Đ

Ú OSPF ,XÊÄ' 3 ` 9 /Ä

```
5XLMLHFRQJURXWHURVSI
5XLMLHFRQJURXWHUWLPHUVVSI
```

	show ip ospf	ß ospf ,X,ÈG5BQ
	timers throttle spf	**G5B** SPF Au1kÛEÊSÉÊÈ6Ñ **timers spf** **timers throttle spf** **timers spf G5B**

-

5.63 timers throttle lsa all

timers throttle lsa all *delay-time hold-time max-wait-time*

no timers throttle lsa all

delay-time	LSA 1-600000
hold-time	2 LSA 1-600000
max-wait-time	LSA LSA 1-600000

5,

delay-time

hold-time 5000

max-wait-time 5000

delay-time CPU #

hold-time delay-time max-wait-time hold-time

G5B_ G5B 10ms hold-time 1s 5s

5.64 timers throttle spf

ÐG5B OSPF ÿ%,XÈ> SPF Au1k,XÊÃ SPF Au1k,XÊÈhÃ
ÊÈhÆÊ*CÃE7G5BQ **timers throttle spf**ÄÐ no 6ÃÃ,Õ5BÄ

timers throttle spf *spf-delay spf-holdtime spf-max-waittime*

no timers throttle spf

ÐAÊÐ

Ð	ÆÄ
spf-delay	*n* SPF Au1k,X1YÊÐÈÈ 1-600000ÄOSPF CÃE7G%ÐÈ SPF Au1k7Ðü spf-delay ÊÈÈ LhÆ Ä
spf-holdtime	*nø* SPF E¹kKÈXÊÈhÐÈÈ 1-600000Ä
spf-max-waittime	*nø* SPF E¹kKÈXÊÈhÐÈÈ 1-600000Ä

Ð,Õ5BÐ spf-delayÖ000 Ð×
spf-holdtimeÖ 5000 Ð×
spf-max-waittimeÖ0000 ÐÄ

ÐÐ CÃE7G5BÆÄ

Ð*Ê SPF Au1k`õ
spf-delay ></Ê% SPF Êu1kÈÆÐÊ¾XÊÃÊÐ
Ð SPF Au1k,XÊÈÈh *spf-holdtimeÈ* 8È4Ã SPF Au1k,XÊÈÈh7Ðê
KÈÈh,XÊÈÈhE' *spf-max-waittime ÊrtÄpø* SPF Au1k,XÊÈÈhÆ
4ÊYEÐ"XÊw SPF Au1kÊÈÈhÓ¿ *spf-holdtime Êu1kÄ*
spf-delay ` spf-holdtime

timers spf	**G5B** SPF Au1kÊÊÃ 10.4 ¦X RGOS (ÕX SPF Au1kÊ¯ÇA,S*ü **timers throttle spf ª timers spf G5BÄ**

ÏGÄÃè -

5.65 two-way-maintain

*ü OSPF åÃ6ÑS*AÇX no 6ªU*ü OSPF åÃ6ÑN

two-way-maintain

no two-way-maintain

ÏDAè

Đ	ÊÄ
-	-

ï,Õ5BĐ 5,Õü OSPF åÃ6ÑN

ïÇ CÃÆ7G5BÄ

ïS*Đ ÊWj¸X5%4ÄÑÇÊXy[È*ÊWP¸X CPU Ÿ,CÄÈ6Ý¿,XÊ³

ÈÇp Hello y[,XÇÓŸÒuKÈhÆÊ,XF¥yCYÊÇåÃ6ÑN

Vp5%4¸ÇÊXy[È8Z Hello y[È7Ç¸X DDÃ LSUÃ LSRÃ LSAck y[36ÑN

*ü4ÑF¸Xê2ÈS¦b Hello y[,XÊ6ÇÈ¸XÄ

ÏG5B_Đ /U*ü OSPF åÃ6ÑN

```
5XLMLHFRQJURXWHURVSI
5XLMLHFRQJURXWHUQWRZDPDLQDLQ
```

ÎÏGÇ

Ç	ÊÄ
-	-

ÏGÄè -

6 OSPFv3

6.1 area default-cost

ü stub ³X ABR Ä’5BA Ð n stub ¥Y5,ÕÃ,XË*ÄÇX **no EÍMÓ**

area *area-id* **default-cost** *cost*

no area *area-id* **default-cost**

ÐAÈ

Ð	Ë
area-id	stub ³XË JÃÐDÕÐ IPv4 ¼Ð
cost	stub ¥Y5,ÕÃ,XË 8È 1-16777214Ä

rÐÈ5 7D4Ð 38Ñ¼583.4 -5.16 -15.6 re119.94 583<01CF 0 0re4 5219.46 Tj/C2_045AF2FDFc 0.28 11FF514E364 419.4 0.48 ref10 Tc 0 -

ipv6-prefix/prefix-length	¶.Ä
advertise	Æ¶.Ä
not-advertise	Æ¶.8È 5,Æ

Ï,Õ5BÐ þK£.8È

Ëþ CÃE7Ç5Bã

Ï*Ê AÇ ABR ÊÞÊ,X5CÃ¶.ÊCÃÈÎÊÃÇ
,XÜ> ¥¶+ ÈFÇÃA'ÇXFÑ',XCÃÇÈW¸XA'Ê¼
6ÑÊ¶.CÃÊÃEA'5B advertise ` not-advertise EÍM9ÈÑÊ¶.8È
CK#È¸X0*È,ÊÈ› cost EÍM9A'5BÈ¶.CÃ,XÇÈÄ
ÃÇÃ¶.È¸Hþ OSPF C㸸XCÃÍ1TÈMµ5%4ÊÈ
Ð5%4EÊÑ
'G5BÊÈM,ÃÊ2Ï¸XÊÃBÊSG½íBn>¦X area range
,XÄ

ÏG5B_Ð í 1 ,XCÃE> ¶.Ö

```
5XLMLHFRQQJLSYURXWHURVSI
5XLMLHFRQQJURXWHUDUHDUDQH'%
```

ÏÎGÐ

Ç	È
summary-prefix	**A5BÈÇÃ.8È**

ÏGÄÈ -

6.3 area stub

S*ÄÇÐ stub È5Ù'5B stub ¸X2È*ÄÇX **no EÍM6ÊBÈ5Ù**
Ê8 stub ¸XG5BÄ

area *area-id* **stub** [**no-summary**]

no area *area-id* **stub** [**no-summary**]

ÐÄÈ

Ð	È
area-id	stub ¸XË JÈÊÐD5Ð IPv4 ¼Ô
no-summary	**AEÍM¿¼** stub ¸X ABR>È/A¹ ABR Ê></5,ÕÃ +,X2O_ 3 ,X LSA @ stub ¥Ê2D_ 3 ,XJª LSAÄ

Ï,Õ5BÐ þ stub ³

Ëþ CÃE7Ç5Bã

S*Ð

Vp̂ØHþ%4,XÿFÛÄ’Au stub È stub Y,XCÃA’ÐÑ NO,> **area stub Ü̧pA’Au** stub ÈÉ4á AS ÈC,Ã(type 5 LSAs) È 5ã Lh*ÈC,ÃùÒ(ÕBg4È stub YF,Ä,4 àXCÃÈLE> OSPFv3 #A,Ô4*iX24CÄ ü stub ,X ABR Ð,Õ><5,ÕÃ,X2O_ 3 ,X LSA @ stub YÈstub YF,XA’Ä’ A , AS ÈÄ SX ABR stub VpLÔG5B totally stubÄ stubÄÔ ABR Þ **area stub ÊÝ** **no-summary** stub E’

hello-interval 5,Õ 10 /þý

dead-interval 5,Õ hello-interval ,Xþý

retransmit-interval 5,Õ 5 /þý

transmit-delay 5,Õ 1 /@

CÃE7G5Bå

ï*ô ü OSPFv3 B:4Hþ

dead-interval À instance F

5XLMLHFRQJLSY0P 0@

```
5XLMLHFRQJLSYURXWHURVSI
5XLMLHFRQJURXWHUDXWRFRVWUHIHUHQHHDQZGWK
```

ÏÎGÐ

Ò	ÐÄ
ipv6 ospf cost	**A5ByXË**
show ipv6 ospf	**/** OSPFv3 CÃÆÐ

ËGÄð -

6.6 bfd all-interfaces

G5BE¤ OSPFv3 ,X ý S*ü BFD E> JÒÃ# ÆÏ OSPFv3 CÃG5Bð **bfd all-interfaces**Ä*ÁÐ no 66,Õ5BÄ

bfd all-interfaces

no bfd all-interfaces

ÐAð

Ð	ÐÄ
-	-

Ï,Õ5BÐ GKÁ BFD "#

Ðð CÃÆÐG5Bã

Ï*Ð OSPFv3 #AÆÐ› Hello y[|Ð È OSPFv3 | BFD "#s6Ð FULL G2Ï ,XFÐÝ BFD ÀÆÐ› BFD "#FÐ BFD FÈ OSPFv3 ÐÆ> 5%4° /Ä

|3ÆEyG5Bð **ipv6 ospf bfd** [**disable**]|5ÒGKÁy;X BFD "#s6Ð G5B,X¼{PÞÆÐG5Bð **bfd all-interfaces** Ð

ËG5B_Ð -

ÏÎGÐ

Ò	ÐÄ
ipv6 router ospf	**|** OSPFv3 ÐÐ OSPFv3 CÃÆÐG5Bõ Ä
ipv6 ospf bfd	**G5B** OSPFv3 yS*ü BFD E> JÒÃ#Ä

ËGÄð -

6.7 clear ipv6 ospf process

S*ÁÆÐÙ8JG¡ OSPFv3 r_Ä

clear ipv6 ospf [*process-id*] **process**

ÏÐAð

Ð	Ë Ä
process-id	*ú* OSPFv3 E7 ß È 1-65535

Ï,Õ5BÐ -

Ïð (Mã

Ï*ô 7 ß Õ*ð

S*ü *process-id Ð ú ð* OSPFv3 rVÄ'ùŵ *process-id ß Ž* OSPFv3 r_Ä

Ï5B_Ð GÝ OSPFv3 r_

5XLMLHFOHDULSYRVSISURFHVV

ÎÏGÐ

Ò	Ë Ä
-	-

ÏÄð -

6.8 default-information originate

+ CÃA'Â

redistribute OSPFv3 CÃXCÃA'ÂSBR {*õ,ÕÃ

+ **default-information originate** **A5BÄ**

VpE always Dâu—CÃ><µõ,ÕÃÈ OSPFv3 E7BÑEõE¾Õ

CÃÄCÃA'âA5,ÕÃÐ.BAx{r*õ,ÕÃÐü **show ipv6 ospf database** OSPFv3 JÒ{ÕBgÐOSPFv3 ,XFEE> **show ipv6 route** 5Õ,ÄÄ

E¾,ÕÃ,XCÃ**default-information originate** **default-metric A5BÄ**

OSPFv3 1 EÇCÃ,XCÃ2 2 EÇCÃ,XCÃ

1 2O_ 2 {PE **show ipv6 route** 2O_ 1 Fw5CÃÄ

stub XCÃA'**A5**,ÕÃ,XÄ

G5B_Đ G5BG{*õ,ÕÃÖ

```
5XLMLHFRQJLSYURXWHURSI
5XLMLHFRQJURXWHUGHIDXOWLQRUPDWLRQULJLQWHDO2V
```

Q	E
redistribute	**A5BC,XG**
show ipv6 ospf	**/** OSPFv3 CÃE7
show ipv6 ospf database	**/** OSPFv3 JÒ{ÕBg

G -

6.9 default-metric

S*A5BG,X5,ÕE*A **no EM65**

default-metric *memet4ts-valt4tue*

faault-m

6.11 ipv6 ospf area

S*ÅĄ'5Byâ OSPFv3

ÏDAêê

Ð	ÆÄ
disable	**GÉ¤** OSPF ,XûÙyS*ü BFD E> JÒÑ#Ä
instance *instance-id*	*ýÝMn* OSPFv3 r'E> G5B 8ÈÆ 0-255Ä

Ï5,Õ5BÐ 5,ÛÝG5BÈ OSPFv3 E7ÛG5BßK BFD G5BßÅ

ÏÐ yG5BßÅ

ÏS*ûÐ yG5B,Xä{PÞE7ÛG5BßK **bfd all-interfaces Ø**

|ßrL)ÿWÈE› **ipv6 ospf bfd ØÉXyS*ü** BFD E> JÒÑ#ÈßS*ü

OSPFv3 E7ÛG5BßKQ **bfd all-interfaces G5Bâ** OSPFv3 E¤ ,XýÆE› BFD E> JÒ

CÑ#ÈS*ü **ipv6 ospf bfd disable EÉßyX** BFD "#s6Ñ

ÏG5B_Ð -

ÏÎGØ

Q	ÆÄ
ipv6 router ospf *process-id*	| OSPFv3 E7ÛE9 OSPFv3 CÃE7ÛG5Bõ Ää
bfd all-interfaces	**G5BE¤** OSPFv3 ,XýS*ü BFD E> JÒÃ "#Ä

ÏGÄêê -

6.13 ipv6 ospf cost

S*ÀÇQ'5By¡XÈS*ÀÇX **no EÑM6ÈÐ**

ipv6 ospf cost *cost* [**instance** *instance-id*]

no ipv6 ospf cost [**instance** *instance-id*]

ÏDAêê

Ð	ÆÄ
cost	*yÆ* 8ÈÆ 1-65535Ä
instance *instance-id*	*ýÝMn* OSPFv3 r'E> G5BÈÆ 0-255Ä

Ï5,Õ5BÐ 5,ØXy8C5ÆBandwidth ÆÆAx 100MbpsÅ

ÏÐ yG5BßÅ

ÏS*ûÐ 5,Ø% OSPFv3 y8C. 100Mbps/BandwidthÈ Bandwidth y¡XÈEyG!

5BÇ bandwidth E> A'5BÄ

/ÌL_4"CÃK OSPFv3 5,Ø8CÖ

64K > 4"CÃost 1562×

E1 4“CÃost 48×

10M Þ5%Èost 10×

100M Þ5%È cost 1Ä

EÈ› **ipv6 ospf cost Q5BX** OSPFv3 8CÞ5,Õ5BÄ

Ï5B_Ð G5By¡XË 1Ö

5XLMLHFRQJLQWIDVWHWKHUQW

5XLMLHFRQJLILSYRVSIFRVW

ÎGÐ

Q	EÄ
show ipv6 ospf interface	**/** OSPFv3 yÇÄ
ipv6 ospf area	**A5Byâ** OSPFv3 CÃE7ß

ÏÄÐ -

6.14 ipv6 ospf dead-interval

S*ÀQ’5ByÞxF¡XÊÀÊÈüÝ•X hello Eì y0Dé

show ipv6 ospf interface	**/** OSPFv3 yÇÄ
ipv6 ospf area	*Aþâ* OSPFv3 CÃE7ß

ÏGÄêð -

6.15 ipv6 ospf hello-interval

S*ÄÇ'5ByÆÕ Hello y[,XÊÈÈhÈ*Ç× **no ÉÑM65Õ**

ipv6 ospf hello-interval *seconds* [**instance** *instance-id*]

no ipv6 ospf hello-interval [**instance** *instance-id*]

ÏDAêð

Ð	ÆÄ
seconds	ÆÕ Hello y[ÊÈÈhÄ 8è 1-65535(/)Ä
instance *instance-id*	ý(Mn OSPFv3 r'E> G5B 8è 0-255Ä

ï,Õ5BÐ S5%4ä&5%4° 10 /þ&5%4â NBMA 5%45,Õ 30 /þÄ

ïÇ yG5Bäá

ïS*ð FKÆÕ Hello y[,XÊÈÈhÑO,ðÝ,XFyG2Ä

ïG5B_Ð A'5ByÆÕ hello y[,XÊÈÈh 20sÖ

```
5XLMLHFRQJLGQIDVWHWKHUÇW
5XLMLHFRQJILSYRVSIKHOORLQWHUYDO
```

ÏÎGÇ

Ç	ÆÄ
ipv6 ospf dead-interval	**A5ByÆxFýÊ**
show ipv6 ospf interface	**/** OSPFv3 yÇÄ
ipv6 ospf area	*Aþâ* OSPFv3 CÃE7ß

ïGÄêð -

6.16 ipv6 ospf mtu-ignore

S*ÄÇDBgÆÄ[ÑÍ MTU ,XÐÄÇ× **no 6ÑÕ5BÄ**

ipv6 ospf mtu-ignore [**instance** *instance-id*]

no ipv6 ospf mtu-ignore [**instance** *instance-id*]

ÏDAêð

Ð	ÆÄ
instance *instance-id*	ý(Mn OSPFv3 r'E> G5B 8è 0-255Ä

ï5,Õ5BÐ 5,Õ MTU E> ÐÄ

ÄÐ yG5BÄ

Ï*Ð OSPFv3 ÐBgEÄ[ÊFy;X MTU 7Å‰X MTU µÊp,XD
BgEÄ[ÛXFy;X MTU ï7Å‰y;X MTUÈwFyG2ÊÑÐÊ
ÆÊEGKÁ MTU ,XÐ9ÄÅ

Ï5B_Ð ÞXG5B_Ð ethernet 1/0 ,X MTU Ð>s6ÑKÄ
5XLMLHFRQJLQWHUIDFHHWKHUQHW
5XLMLHFRQJILSYRVSIPWXLJRUH

ÎGÞ

Þ	ÆÄ
ipv6 router ospf	**|** OSPFv3 CÃE7Å
ipv6 mtu	**A5By** IPv6 MTU Ä

ÏGÄÐ -

6.17 ipv6 ospf neighbor

S*ÄÞ5B OSPFv3 ,XFÈ*ÄÞX **no EÍM6ÃÐ**

ipv6 ospf neighbor *ipv6-address* { [**cost** *cost*] | [**poll-interval** *seconds* | **priority** *value*] } [**instance** *instance-id*]

no ipv6 ospf neighbor *ipv6-address* { [**cost** *cost*] | [**poll-interval** *seconds* | **priority** *value*] } [**instance** *instance-id*]

ÐÄÐ

Ð	ÆÄ
cost *cost*	A’5B&&5%4ÞÞU,XC*È,ÕÈ*ÿÐ! 5B,X costÐÈ 1-65535Ä &&5%42O_(point-to-multipoint) ÕÆÍM
poll-interval *seconds*	FÆBAÐÈÆEhÞÐÈ 1-2147483647Ä2S5%42O _(NBMA) ÕÆÍMÄ
priority *value*	A’5BM2S5%4F•XÐÈ 0-255Ä2S5%42O_(NBMA) ÕÆÍMÄ
instance *instance-id*	*ýMn* OSPFv3 r'E> G5BÐÈ 0-255Ä

ï5,Õ5BÐ 5,ÕíF×
FÆBAÐÈÆEhÕ,Õ 120 /×
M2S5%4F•XÕ,Õ 0Ä

ÄÐ yG5BÄ

Ï*Ð |ÑrL5%42O_È’5BF•hÐÄ

ÏÔ5B_Ð ÞXG5B_Æ5B OSPFv3 ,XFÈ IPv6 2001:DB8:4::1È 1ÈBA¶ÈÞ 150 /Ä

```
5XLMLHFRQJLJXUHIDFHIDVW(WKHUQHW
5XLMLHFRQJLJILSYRVSIHQLJKERU'%SURULWSROOLQWHUYDO
```

ÏÔGÞ

Ò	ÆÄ
Ipv6 ospf priority	**A5By¸XÄ**
Ipv6 ospf network	**A5By¸X5%42O_**

ÏGÄÞ -

6.18 ipv6 ospf network

S*ÄÒ5By¸X5%42O_È*ÄÒX **no EÑM6ÕÞ**

ipv6 ospf network { **broadcast** | **non-broadcast** | **point-to-point** | **point-to-multipoint** [**non-broadcast**] } [**instance** *instance-id*]

no ipvinstance-id

ÏĈĢĐ	Ǫ	ĖÄ
	ipv6 ospf priority	**A5By¸Ẋ4Ą**
	show ipv6 ospf interface	*/* OSPFv3 yǪÄ
	ipv6 ospf area	*Aβâ* OSPFv3 CÃĖƤß

ĠÄâð -

6.19 ipv6 ospf priority

S*ÆĄ'5By¸Ẋ4{È*ĄǪ **no EḾM6ãĐ**

ipv6 ospf priority *number-value* [**instance** *instance-id*]

no ipv6 ospf priority [**instance** *instance-id*]

ĐAð	Ð	ĖÄ		
	number-value	*yĦĐ*		0-255Ä
	instance *instance-id*	*ýM*	OSPFv3 r'E> GƖBÈĸ	0-255Ä

ƀ,Ğ5BĐ 1

ðĐ yG5Bã

ÏDAê

Ð	Ë
seconds	Æ Õ LSA ,XGß È hÄ 8è 1-65535(/)Ä
instance *instance-id*	ý(*Mn* OSPFv3 r'E> G5B 8è 0-255Ä

Ï,Õ5BÐ 5 /¦

ê yG5Bã

Ï*ê ÆC Ã Ç Ë Õ Ø 4 Æ LSA Ê Ø kF•BAx Ã rLE) W È
EÊ Q'5BA Ø YF•BAx,XÊ È È h Ø pû ,XÊ È È BAx Ê ô LSA Ç Ä

Ï5B_Ð M6_ A'5BGô LSA ,XÊ È È h 10sÖ
5XLMLHFRQJLQWHUIDFHHWKHUQW
5XLMLHFRQJLILSYRVSIUHWUDQPLWLQWHUYDO

ÎÏGÐ

Q	Ë
show ipv6 ospf interface	**/** OSPFv3 yÇ Ä
ipv6 ospf area	*Aþ* OSPFv3 C Ã E Ï ß

ÏÄê -

6.21 ipv6 ospf transmit-delay

S*AQ'5Bÿ Õ LSA Ê È Ê È *AQ **no E M6 Ð**
ipv6 ospf transmit-delay *seconds* ß3þ Ð

5XLMLHFRQJLILSYRVSIWUDQPLWGHOD\

Q	Ä
show ipv6 ospf interface	**/** OSPFv3 yÄ

-

6.22 ipv6 router ospf

S*AQ OSPFv3 CÃE*AQ **no EMMGK** OSPFv3 CÃE

ipv6 router ospf [*process-id*]

no ipv6 router ospf *process-id*

Ð	Ä		
process-id	OSPFv3 E5BE<	1Ä	process-id

ÏÐ	<G5BÄ
Š*Ð	'CÃA'ÞÍ6DBÈÑÊ5BAÐ OSPFv3 CÃE/ß AÈfÆKÿÅXFÐ,Â
Ĝ5B_Ð	VßÐ OSPFv3 CÃE/ßÈfÆKÿÅXFÐ,Â'5B 4ÈĜ5B ,XpĜÈf,XE/Â'ÐÊKâ 4 þÈfÈÐÿ 4 þ FÆK,XxfĜA'Ð 8 þÈ> xfÖ 5XLMLHFRQILJLSYURXWHURVSIPD[FRQFXUUHQWGG
ÏĜÐ	

Q	EÄ
max-concurrent-dd	A'5BOSPFv3 CÃE/ßÈf,XFÐ ,Â

Ï*Ð hello y[Ä

OSPFv3 E¤ ,Xy*

Ï5B_Ð VLAN1 yâ OSPFv3 E¤ Ö

```
5XLMLHFRQJURXWHURVSI
5XLMLHFRQJURXWHUSDVVLYHLQWHUIDFHGHIDXOW
5XLMLHFRQJURXWHUSSDVVLYHLQWHUIDFHYODQ
```

ÏGÐ

Ç	EÄ
ipv6 ospf area	**A5Byâ** OSPFv3 CÃE7Ã
show ipv6 ospf	**/** OSPFv3 CÃE7Ç
show ipv6 ospf neighbor	**/** OSPFv3 FÇ

ÏGÄ -

6.27 redistribute

S*ÄÇÃGÐCÃ#A,XCÃÇ% OSPFv3 CÃE7Ã*ÄÇ

no E MÃs6

redistribute { **bgp** | **connected** | **isis** [*area-tag*] | **ospf** *process-id* | **rip** | **static** } [{ **level-1** | **level-1-2** | **level-2** } **| match** { **internal | external** [**1 | 2**] **} | metric** *metric-value* **| metric-type** { **1** | **2** } | **route-map** *route-map-name* | **tag** *tag-value*]

no redistribute { **bgp** | **connected** | **isis** [*area-tag*] | **ospf** *process-id* | **rip** | **static**} [{ **level-1** | **level-1-2** | **level-2** } **| match** { **internal | external** [**1 | 2**] **} | metric | metric-type** { **1** | **2** } | **route-map** *route-map-name* | **tag** *tag-value*]

ÐAÐ

Ð	EÄ
bgp	¢ bgp G
connected	
isis [*area-tag*]	¢ isis G E› *area-tag* isis r_
ospf *process-id*	¢ ospf G E› *process-id* ospf r_ 1-65535
rip	¢ rip G
static	
level-1 | **level-1-2** | **level-2**	IS-IS CÃ* level ,XCÃE> G¡
match	OSPFv3 CÃ* MnCÃE> G internal CÃ external [1|2] 1 2 CÃ
metric *metric-value*	OSPFv3 external 2 LSA ,X metric E› metric-value metric 16777214
metric-type {*1*|*2*}	E-1 ê E-2

route-map *route-map-name*	*G* map-tag ,X 32 +0
tag *tag-value*	OSPFv3 YC,X tag 4294967295

metric-type 5,Õ 2×

ISIS level-2 CÃ×

OSPFv3 OSPFv3 CÃ×

route-mapÄ

CÃ

'A' #A level-2 ,XYÄ

> #A ISIS #A level-1Ã level-2 ê level-1-2 /G ISIS CÃh

level ,XCÃ level-2 2O_,X ISIS CÃÄ

OSPFv3 #A OSPFv3 CÃ 2O_,XCÃ

OSPFv3 CÃ

ISIS level-2 OSPFv3 ,X route-map ,X

route-map tag

metric-type

route-map

set

G6(,X route-map ,X set metric <0-16777214>

redistribute

no

1 no

2 no

redistribute isis 112 level-2 **no redistribute isis 112 level-2**

level-2 level-2 D no

redistribute isis 112 level-2 **no2_04 F11 0.0038 0.0d 996015 Tc 0..00**

show ipv6 ospf	**/**	OSPFv3 CÃE7ÇÄ
show ipv6 ospf database	**/**	OSPFv3 JÒÃÕBgÇÄ

ÜGÄß -

6.28 router-id

S*ÆÇ'5BA'ÎXÂß Router ID) SÈÆÇX **no**

process- id	ospf

-

(M

-

/ OSPFv3

```
5XLMLHVKRWSYRVSI
5RXWLQJ3URFHVV263)YHUVLRQ
3URFHVVXSWLPHLVPLQXWHV
63)VFKHGXOHGHODVHFV+ROGWLPHEHWHHQ63)VFKFV
0LQPXP/6$UHDVHFV0LQPXP/6$UULYDOVHFV
1XPEHURILQWHUIDFHVLQ"H[FKDQJHORJKERUV
1XPEHURIRXWJRLQJFXUUHQW"H[FKDQJHORJKERUV
1XPEHURIH[WHUQO/6$&KHFNVXP6XP[
1XPEHURI6$6FRSHG8QRXW$
1XPEHURI/6$RULJLQDWHG
1XPEHURI/6$HFHLYHG
/RJ1HLJKERUSXEOLF&KDQJHV(QEOHG
1XPEHURIDUHDVLQWKLVURXWHULV
$UHD%$&.%21(
1XPEHURILQWHUIDFHVLQWKLVDUHDLV
63)DOJRULWKPH[HFXWHGWLPHV
1XPEHURI/6$&KHFNVXP6XP["
1XPEHURI8QRXW$
```

Vp OSPFv3 â BFD 6(|ÈBFD is enabled” Ä

```
5XLMLHVKRWSYRVSI
5RXWLQJ3URFHVV263)YHUVLRQ
3URFHVVXSWLPHLVPLQXWHV
63)VFKHGXOHGHODVHFV+ROGWLPHEHWHHQ63)VFKFV
0LQPXP/6$UHDVHFV0LQPXP/6$UULYDOVHFV
1XPEHURILQWHUIDFHVLQ"H[FKDQJHORJKERUV
1XPEHURIRXWJRLQJFXUUHQW"H[FKDQJHORJKERUV
1XPEHURIH[WHUQO/6$&KHFNVXP6XP[
1XPEHURI6$6FRSHG8QRXW$
1XPEHURI/6$RULJLQDWHG
1XPEHURI/6$HFHLYHG
/RJ1HLJKERUSXEOLF&KDQJHV(QEOHG
1XPEHURIDUHDVLQWKLVURXWHULV
%)'LVHQDEOHG
```

```
SHD%&.%21(
1XPEHURILQWHUIDFHVLQKLVDUHDV
63)DOJRULWKPH[HFXWHGWLPHV
1XPEHURI/6$KHFNVXP6XP[")
1XPEHURI8QRXW
```

Q	E
ipv6 router ospf	| OSPFv3 C
default-information originate	**A5B5**
default-metric	**A5BG** **A5**
router-id	**A5B** OSPFv3 C
timers spf	**G5B** OSPFv3 SPF Au1k,X SPF Au1k,X Lh

-

6.30 show ipv6 ospf database

/ OSPFv3 E

show ipv6 ospf [*process- id*] **database** [*lsa-type* [**adv-router** *router-id*]]

D	E

```
[[F
/LQ/6HUIDFH/RRSEDFN
```

```
,QWHUIDFH,'
,3Y3UHIL[HV
IHGIIIH/LQN/RFDO6GUHVV
263)Y3URFHVV6HD,QWDEH,'
5RXWHU,'1HWZRUN7SH%52'&67&RVW
7UDQVPLW'HODLVVHF6WDWH%'53ULRULW\
'HVLJQDWHG5RXWHU,'
,QWHUIDFH6GUHVVIHFHIIIHF
%DFNXS'HVLJQDWHG5RXWHU,'
,QWHUIDFH6GUHVVIHGIIIH
7LPHULQWHUYDOFRQJXUHG+HOOR'HDG:DLW5HWUDQVPLW
+HOORGXHLQ
1HLJKERU&RXQWLVG6MDFHQVHLJKERUFRXQWLV
+HOORUHFHLYHGVHQ"UHFHLYHGVHQ
/65HTUHFHLYHGVHQ/68SGUHFHLYHGVHQ
/6$NUHFHLYHGVHQ'LVFDUGHG
```

VpAÿ;XF*â BFD 6(|È BFD enabled Ä

```
5XLMLHVKRZSYRVSILQWHUIDFH
)DVW(WKHUQHWLVXSOLQHSURWRFROLVXS
,QWHUIDFH,'
,3Y3UHIL[HV
IHGIIIH/LQN/RFDO6GUHVV
263)Y3URFHVV6HD,QWDEH,'
5RXWHU,'1HWZRUN7SH%52'&67&RVW
7UDQVPLW'HODLVVHF6WDWH%'53ULRULWÈ)'HQEOHG
'HVLJQDWHG5RXWHU,'
,QWHUIDFH6GUHVVIHFHIIIHF
%DFNXS'HVLJQDWHG5RXWHU,'
,QWHUIDFH6GUHVVIHGIIIH
7LPHULQWHUYDOFRQJXUHG+HOOR'HDG:DLW5HWUDQVPLW
+HOORGXHLQ
1HLJKERU&RXQWLVG6MDFHQVHLJKERUFRXQWLV
+HOORUHFHLYHGVHQ"UHFHLYHGVHQ
/65HTUHFHLYHGVHQ/68SGUHFHLYHGVHQ
/6$NUHFHLYHGVHQ'LVFDUGHG
```

ÏÎGĘĐ

Ą	ĘÄ
ipv6 router ospf	| OSPFv3 CÃE7Ã
ipv6 ospf area	| OSPFv3 CÃE7Ã

ĞGÄð -

6.32 show ipv6 ospf neighbor

/ OSPFv3 E/ßC

show ipv6 ospf [*process- id*] **neighbor** [*interface-type interface-number* [**detail**] | *neighbor-id* | **detail**]

	Ð	E
	process-id	OSPFv3 E/
	detail	**/F**
	interface-type *interface-number*	*by2_*
	neighbor-id	*bF•* Router ID

-

(M

-

_ 1

OSPFv3 F;

```
5XLMLHVKRWSYRVSIQLJKERU
263)Y3URFHVV1HLJKERUVLV)XOO
1HLJKERU,'3UL6WDWH'HDG7LPH,QWHUIDFH,QWDQH,'
)XOO'5)DVW(WKHUQW
```

_ 2

OSPFv3 F

```
5XLMLHVKRWSYRVSIQLJKERUGHWDLO
1HLJKERULQWHUIDFHDGGUHVVIHFHIIIHF
,QWKHUHDYLDLQWHUIDFH)DVW(WKHUQW
1HLJKERUSULRULW\LV6WDWHLV)XOOVWDWHFKDQHV
'5LV%'5LV
2SWLRQLV[_5___(_9
'HDGWLPHUGXHLQ
'DWDEDVH6XPPDU\LVW
/LQN6WDWH5HTXHVW/LVW
/LQN6WDWH5HWUDQVPLVVLRQLVW
```

Vp* E› BFD "# F; XE BFD session state up Ä

```
5XLMLHVKRWSYRVSIQLJKERUGHWDLO
1HLJKERULQWHUIDFHDGGUHVVIHFHIIIHF
,QWKHUHDYLDLQWHUIDFH)DVW(WKHUQW
1HLJKERUSULRULW\LV6WDWHLV)XOOVWDWHFKDQHV
'5LV%'5LV
2SWLRQLV[_5___(_9
'HDGWLPHUGXHLQ
```

```
'DWDEDVH6XPPDU\LVW
/LQN6WDWH5HTXHVW/LVW                                    9
/LQN6WDWH5HWUDQVPLVVLRQLVW
%)'VHVVLRQWDWHXS
```

6.34 show ipv6 ospf summary-prefix

/ OSPFv3 è¢Ã6.Ä

show ipv6 ospf [*process-id*] **summary-prefix**

ÏDAê

Ð	Ë
process- id	OSPFv3 E

Ï,Õ5BÐ -

Ê

(Mã

Ï*Ð

-

Ï5B_Ð ¡ß OSPFv3 è¢Ã6.

```
5XLMLHVKRZSYRVSIVXPPDUSUHIL[
263)Y3URFHVV6XPPDUSUHIL[
GE0HWULF7SH7DJ0DWFKFRXQWDGYHUWLVH
```

ÎGÐ

Ð	Ë
ipv6 router ospf	OSPFv3 CÃE
summary-prefix	**5B** OSPFv3 CÃè¢Ã,X6.CÃ

ÏGÄê -

6.35 show ipv6 ospf topology

/ OSPFv3 Þ%Ä

show ipv6 ospf [*process- id*] **topology** [**area** *area-id*]

ÏDAê

ÐBbg%&(5%bl”(5/S	&rV%&&rdan&'$

ĬGÄß -

6.37 summary-prefix

ÜG5B OSPFv3 CÃÆÇÃ,X6.CÃÆÈ*CÃÆ7G5BQ **summary-prefixÄÃÇ** **no 66ãÕ5BÄ**

summary-prefix *ipv6-prefix/prefix-length* [**not-advertise** | **tag** *number*]

no summary-prefix *ipv6-prefix/prefix-length* [**not-advertise | tag** *number*]

ÐAß

Ð	ÆÄ
ipv6-prefix/prefix-length	*6.Ã*
not-advertise	*åÆÐ.Ã* 8Ð></Eî
tag *number*	**A5BGÞ** OSPFv3 YCÃ,X tag 8È 0-4294967295

spf-delay 0000
spf-holdtime 5000
spf-max-waittime 0000

spf-delay spf-holdtime spf-max-waittime SPF

timers spf timers throttle spf

timers throttle spf timers spf

timers throttle spf timers throttle spf

OSPFv3 5 000 0000

5ms 5s 31s 3s 9s 179s 179+90

5CLMLCFBAILJLSYUBCWCURFSI
5CLMLCFBAILJUBCWCUWLPCUVVSI

clear ipv6 ospf	**S*** OSPFv3
show ipv6 ospf	**/** OSPFv3
timers spf	**G5B** SPF Au1k

7 IS-IS

7.1 adjacency-check

S*ÅĘ5Bü Hello y["#FÞÕX#AÞ*ÅĘX **no 6ßÅÄ**

adjacency-check

no adjacency-check

ÏÐAß

Ð	Ł Ä
-	-

Ï,Õ5BÐ *Å*#

ß IS-IS CÃŁ7Ć5Bã

Ï*Ð TÅxß‰ Hello y["#FÞÕX#AÞ*ÅĘX no 6ß#Ł/¡#Ä

Ï5B_Ð 5XLMLHFRQJURXWHULVLV

5XLMLHFRQJURXWHUDGMDFHQF\FKHFN

ÎĆĘÐ

Ę	Ł Ä
-	-

ÏÄß -

7.2 area-password

S*ÅĘ'5B Level-1 area ,XÞÅxAšÕ*ÅĘX **no 6ßÅ5BXšÕ**

area-password [**0** | **7**] *password-string* [**send-only**]

no area-password [**send-only**]

ÏÐAß

Ð	Ł Ä
0	ûŠyß
7	*ûßŠ*
password-string	*AÞÅxAšÕÅ* ûSÕ 126 þ0Å
send-only	**û** Level-1 area ,XÞÅxAšÕ*ûÏ*ŁÇXy[ÊXy[ß> PÅ•

Ï,Õ5BÐ Þ'5BAxAšÕ

IS-IS

IS-IS

Level-1 area LSP SNP SNP

Area IS-IS password

authentication mode **authentication mode**

send-only

IS-IS *redgiant*

Ï5B_Ð ûÙ IS-IS Ÿ,XAxAS*ü kc ,XšÕÊ

```
5XLMLHFRQJURXWHULVLV
5XLMLHFRQJURXWHUDXWKHQWLFDWLRQQHFKDLQFOHYHO
```

ÏÎGÐ

Ç	ÉÄ
authentication mode	**û** IS-IS AxAã
authentication send-only	**û** IS-IS AxAÞ¾*üÉÕXy[Ê,Xy [ê> AxA•
key-chain	**G5BšÕ**

ÏGÄè -

7.4 authentication mode

S*ÄÇÐ IS-IS AxA¸XÄ*ÄÇX **no 6ûÞX** IS-IS AxAã

authentication mode { **md5** | **text** } [**level-1** | **level-2**]

no authentication mode { **md5** | **text** } [**level-1** | **level-2**]

ÐÄè

Ð	ÉÄ
md5	**ûS*ü** MD5 Axã
text	**ûS*Þ AxAã**
level-1	*ûAxAã* Level-1 ÞÓ
level-2	**ûAxAã** Level-2 ÞÓ

Ï5BÐ ûAxAã

Ïè IS-IS CÃE7G5Bã

Ï*û Ø S*ü **authentication key-chain Ç5B,XšÕ*ÞOS*ü** **authentication mode Ç AxAã**

8ÞûÙ Level ,XAxAã*ü Level-1 ` Level-2Ä

G5B **authentication mode Ç S*ü** **area-password ê domain-password Ç5B Ç AxAÐo5B,XÇ**

8G5BZ **authentication mode ÇG5B** **area-password ê domain-password ÇÔ Ø authentication mode Ç8Ä**

Ï5B_Ð ûÙ IS-IS Ÿ,XAxAS*ü MD5 Axã

```
5XLMLHFRQJURXWHULVLV
5XLMLHFRQJURXWHUDXWKHQWLFDWLRQRGHPGOHYHO
```

ÏÎGÐ

Ç	ÉÄ
area-password	**A5B** Area ÞAxAšÕ

authentication key-chain	û IS-IS AxAS*ïXõÒ
authentication send-only	û IS-IS AxA½*üE×Xy[Ê,Xy [ê> AxA•
domain-password	**A5B** Domain ÊAxAõÕ

ÜGÄê -

7.5 authentication send-only

S*ÄÊ IS-IS AxA½*üE×Xy[Ê,Xy[ê> AxAÄ*ÄÊX **no 6ª**
E/ê6éXyÊE>AxAÄ
authentication send-only [**level-1** | **level-2**]
no authentication send-only [**level-1** | **level-2**]

ÜAê

Ð	ÆÄ
level-1	*û* Level-1 A'5B **send-only**
level-2	û Level-2 A'5B **send-only**

ü,Õ5BÐ ê Xy[E> AxA•

ê IS-IS CÃE7G5Bã

Õ*û G5BAê IS-IS ÍXy[A'5BAxAõXy[ê> AxAÄÄ*üø
ê¼4;XÄ'ûF IS-IS AxAÊxAõxAê> ê
üê'5BÞ **authentication send-only êXyE>AxAÈSê**
XAxAõFE/8¼(ü05Ä5¼XAxAõFêS*ü **no isis authentication**
send-only ê **send-only êE>AxAÄ**
Aê*üêAxAã MD5 AxAõE› **authentication mode ê5BS*½Ax**
Aê
8ü Levelê,XAxAê*ü Level-1 ` Level-2Ä

GÜ5B_Ð û IS-IS Y,XAxA• send-only Ä

```
5XLMLHFRQJURXWHULVLV
5XLMLHFRQJURXWHUDXWKHQWLFDWLRQHQRQOHYHO
```

ÎÎGÐ

Q	ÆÄ
authentication key-chain	û IS-IS AxAõÒ
authentication mode	û IS-IS AxA,Xã
key-chain	**G5Bõ**

ÜGÄê -

7.6 clear clns neighbors

AÇÐ#Ù8Ý IS-IS ,XF•G2Þ<Ä

clear clns neighbors

ÐAå

Ð	Ë
-	-

Þ,Õ5BÐ -

Ð

(Mã

Þ*Ð S*8ÐÇ„ IS-IS ,XF•G2Þ<Ä

Ü5B_Ð -

ÎÇÐ

Ç	Ë
clear isis *	**Ù8Ý** IS-IS ,XDB4Ø

ÜÄå -

7.7 clear isis *

AÇÐ#Ù8Ý IS-IS ,XDB4ØÄ

clear isis *

ÐAå

Ð	Ë
-	-

Þ,Õ5BÐ -

Ð

(Mã

Þ*Ð ÇÐLÔ0Ç„ LSP ,XÐWÞ Z area-password ` domain-password â CÃ<E¬É¹X LSP Ø*ÇÐ#Ù8Eö LSPÄ

Ü5B_Ð -

ÎÇÐ

Ç	Ë
clear clns neighbors	**Ù8Ý** IS-IS ,XF•

ÜÄå -

7.8 clear isis counter

AÇÐ#Ù8 IS-IS ,XÐ4Au¿Ä

clear isis [*tag*] **counter**

ÏÐAß

Ð	Ë Ä
tag	IS-IS r_

Ï5,Õ5BÐ -

Ïß (Mã

Ï5*ÐÔ -

ÏG5B_Ð -

ÏÎGÐ

Ç	Ë Ä
clear isis *	Ù8Ý IS-IS ,XDB4Ø

ÏGÄß -

7.9 debug isis

S*8ÇÔ IS-IS ĥ,X DEBUG ¿ÔÄAÇ **no 6819GÌX** DEBUG ¿ÔÄ

debug isis { **all** | **auth | events** | **gr** | **ifsm** | **lsp** | **nfsm** | **nsm** | **pdu** | **spf** | **warn** }

no debug isis { **all** | **auth | events** | **gr** | **ifsm** | **lsp** | **nfsm** | **nsm** | **pdu** | **spf** | **warn** }

ÏÐAß

Ð	Ë Ä
all	Ø IS-IS ,X DEBUG Ô
auth	Ô IS-IS ,X authentication AxA•DEBUG Ô
events	Ô IS-IS ,X_ËG,X DEBUG Ô
gr	Ô IS-IS ,X GR ,ÙG,X DEBUG Ô
ifsm	Ô IS-IS ,Xy(ÕG,X DEBUG Ô
lsp	Ô IS-IS ,X LSP ,ÙG,X DEBUG Ô
nfsm	Ô IS-IS ,XF(ÕG,X DEBUG Ô
nsm	Ô IS-IS ,X NSM ,ÙG,X DEBUG Ô
pdu	Ô IS-IS ,Xy[,ÙG,X DEBUG Ô
spf	Ô IS-IS ,X SPF Au1k,ÙG,X DEBUG Ô
warn	Ô IS-IS ,XA:,ÙG,X DEBUG Ô

Ï5,Õ5BÐ Ý DEBUG ¿ÔGKÁ

Ïß (Mã

Ï*Ê -

ÏG5B_Đ _ 1ÏÕ IS-IS ,X GR ,ÌG,X DEBUG Ô
5XLMLHGHEXJLVLVJU
_ 2ÏÕ IS-IS ,X SPF ,ÌG,X DEBUG Ô
5XLMLHGHEXJLVLVVSI

ÏÎGÐ

Ç	Ë
show debugging	**/AÐÝ** DEBUG Ô'(Ê

ÏGÄê -

7.10 default-information originate

S*ÀÇÕTAxCÃÇJEE› LSPSÄÀÐX **no 6ê** LSP ô8TAxCÃÇÄ

default-information originate [**route-map** *map-name*]

no default-information originate [**route-map** *map-name*]

ÐAê

Ð	Ë
route-map *map-name*	G6(route-mapÄ

Ï,Õ5BÐ ÇTAxCÃ

Ðê IS-IS CÃE7G5Bã

Ï*Ê Level-2 domain ÇTAxCÃÈ*ÀÐXTAxCÃE9 Level-2 domainÄ

ÏG5B_Đ
5XLMLHFRQJURXWHULVLV
5XLMLHFRQJURXWHUGHIDXOWLQRUPDWLRQULJLQWH

ÏÎGÐ

Ç	Ë
-	-

ÏGÄê -

7.11 distance

S*ÀÇ'5B IS-IS CÃ,X1u)ÚÆÈ*ÀÐX **no 6ê1uÚ5Õ**

distance *my-cost*

no distance

my-cost	Ã<1-255>	Ь,Õ	115Ä

Ь,Õ5BÐ Ð5,Õ

Ð IS-IS CÃE7G5Bã

Ь*Ð CÃ1u)kÈ£ãCÃ¢CÃ

Ï5B_Ð 5XLMLHFRQJURXWHULVV
5XLMLHFRQJURXWHUGLVWDQH

ÎGÐ

Ç	£Ä
isis metric	**A5By¥X** metric

ÏGÄð -

ÏÎGÐ

Ò	ËÄ
area-password	**A5B** Level-1 area ÞAxAšÕ
authentication mode	**ô** IS-IS AxAã

ËGÄã -

7.13 graceful-restart helper disable

AÐGKÁ IS-IS GR Helper 6ÑÄ*ÀÐX **no 6ãS6Ñ6ÑÄ**

graceful-restart helper disable

no graceful-restart helper disable

ËDAã

Ð	ËÄ
-	-

Ë,Õ5BÐ S6Ñ IS-IS GR Help 6Ñ

Ëã IS-IS CÃE7G5Bã

Ës*ô 'LÔGKÁ IS-IS GR Help 6ÑÊ5BAÐÊ IS-IS Ñ9GÀ'ÀXLG¼Ä

ËG5B_Ð G5Bs6Ñ IS-IS GR Help 6Ñ

```
5XLMLHFRQJURXWHULVLV
5XLMLHFRQJURXWHUJUDFHIXOUHVWDUWKHOSHUGLVDEOH
```

ÏÎGÐ

Ò	ËÄ
-	-

ËGÄã -

7.14 hello padding

S*ôÐÑÍ IS-IS Hello y[E> ÄÐX **no 6ã5Bã** IS-IS Hello y[Ä

hello padding [**multi-point | point-to-point**]

no hello padding [**multi-point | point-to-point**]

ËDAã

Ð	ËÄ
multi-point	ôÍ LAN 2O_ Hello y[E> ?
point-to-point	ôÍ P2P 2O_ Hello y[E> ?

Ë,Õ5BÐ 5,Õ LAN 2O_ž P2P 2O_ Hello y[FÑ

Ëã IS-IS CÃE7G5Bã

Hello

7.16 ignore-lsp-errors

AşĐA'5B IS-IS Ñ9 LSP ,XĐ"PJÁÃX **no** 6Á'5BÑ9 LSP ,XĐ"PJí AÃ

ignore-lsp-errors

no ignore-lsp-errors

ĐAĐ

Đ	ĐÄ
-	-

Đ,Õ5BĐ Ñ9 LSP ,XĐ"PJÁÃ

Đ IS-IS CÃĐ7Õ5Bã

Đ*Đ ' IS-IS LSP y[ĐÍX LSP EÞ ĐÀu1kĐÉu1kĐ,XĐà LSP y[,XĐEÞ EWĐÍX LSP EÞ Đ"PĐ,ÕĐpÿ[,XĐÀu 1kĐ,XĐĐĐ LSP ĐĐpĐĐEQ ignore-lsp-errors A'5BÑ9 "PJÁĐSS"PÎ LSP ,XĐPJÁĐĐy[ÝyĐĐ

Õ5B_Đ

```
5XLMLHFRQJURXWHULVLV
5XLMLHFRQJURXWHULJRUHOVSHUURUV
```

ÎÕĐQ

Q	ĐÄ
-	-

ÕÄĐ -

7.17 ip router isis

S*ĐQĐA'5BAÿÕ IPv4 IS-IS CÃÄ IS-IS G5BÑOÁ5Q5BÿĐÞ ü Tag ĐX IS-IS r_ĐpĐü Tag ĐX IS-IS r_Đ3ü|JĐ Tag ĐX IS-IS r_Đÿ· ĐÜ IS-IS CÃĐ*ĐQX **no 6**ĐÁÿ· ÞX IPv4 IS-IS CÃÄ

ip router isis [*tag*]

no ip router isis [*tag*]

ĐAĐ

Đ	ĐÄ
tag	IS-IS r_ĐÄ

Đ,Õ5BĐ yÞü IPv4 IS-IS CÃ

Đ yG5Bã

Đ*Đ A'5BE5ĐÝâ IS-IS IPv4 CÃ#ĐQX no **6ĐĐ8yÞü** IS-IS CÃĐ7Ã

VpëG5BG5B no ip routingÈw IS-IS ýG KÁ IPv4 CÃs6Ü
ýP **no ip router isis** [*tag*]ÈG5B IS-IS G5BÃ

ËG5B_Đ
```
5XLMLHFRQJLJ9HUIDFH*LJDELW(WKHUQHW
5XLMLHFRQJLILSURXWHULVLV
```

ÏÎGĐ

Ç	ÉÄ
router isis	Î IS-IS r_

ËGÄà -

7.18 isis authentication key-chain

S*ÀÇ5B IS-IS yAxAS*ïXšÕÃÇX **no 6ÃyAxAS*XšÕ**
isis authentication key-chain *name-of-chain* [**level-1 | level-2**]
no isis authentication key-chain *name-of-chain* [**level-1 | level-2**]

ĐÀà

Đ	ÉÄ
name-of-chain	šÕÃSz 255
level-1	*b* Level-1 ,XAxAšÕÒ
level-2 b Level-2 ,XAxAšÕÒ	

ë,Õ5BĐ b IS-IS yAxAšÕÒ

Ç yG5Bã

ËS*Đ VpüŠ*ü **key chain Ç5B,XÃyAxAÃ** IS-IS šÕÒxAÈCK0*È
LÔÃ5B **isis authentication mode Ç**
AšÕÒ*üÇAxAã MD5 tÀxAÃÈ› **isis authentication mode Ç5B**
S*XAxAÁ
S*ÇAxAÃÕÒXšÕ key-string áÑ 254 +0Ã5BÄ
Ã*Đ key-chainÈ5BÃÇX key-chain šÇ,X key-chainÄ
Vpü Level-1 ` Level-2Ä
AÇXšÕÒ*ü Hello y[Ä IS-IS ÉÇ2bAšÕÒXšÕ
šÕÃÃÕ[Ê*üÃXšy[Ã,Xy[
,XšÕÒÃÃÄy[Ä
IS-IS E7Ã5B,XAxAÇÍX LSPÃ SNP y[È IS-IS yCK0*È **authentication**
key-chain Ç

ËG5B_Đ bÿ· GigabitEthernet 0/1 ,XAxAšÕÒ*å kc ,XšÕÒ
```
5XLMLHFRQJLJ9HUIDFH*LJDELW(WKHUQHW
5XLMLHFRQJLILVLVDXWKHQWLFDWLRQHFKDLQF
```

ÏÎGĐ

Ç	ÉÄ

isis authentication mode	ô IS-IS yAxAã
isis authentication send-only	ô IS-IS yAxAÅ¥ùÆÕXy[ÿ ,Xy[ê> AxAÄ
key-chain	**G5Bšõ**

ÜGÄß

7.20 isis authentication send-only

S*ÄÃÇ IS-IS yAxAÄ¾*üÆÇÕy[Ê,Xy[ÊE> AxAÄ*ÄÃÇX **no 6ã**
9ÆÄÀ6ãÇÇXyÇE>AxAÄ
isis authentication send-only [**level-1** | **level-2**]
no isis authentication send-only [**level-1** | **level-2**]

ÐÄÃÀ

Ð	ÆÄ
level-1	*ÇüX* Level-1 Ä'5B **send-only**
level-2	**ÇüX** Level-2 Ä'5B **send-only**

Ö,Õ5BÐ ÇÆÆÇÕXy[E> AxA•

ÖÇ yG5Bã

Ö*üÐ G5BAÀÇ-IS ÚÆÇÕX Hello y[A'5BAxAšÇÕX Hello y[ÊE> AxA•
'ÆÄ*üÇÐ¾4;XÁ'šF IS-IS yAxAÀÊxAšÕxA•
ÊE> ÊÄÇÀÀ'5BÞ **isis authentication send-only ÐÇÜ**
X Hello y[E> AxAÀÊSÊ,X IS-IS yAxAšFE⁄ß%4{*üÜ5ÄÇ5%4;XAxA×
5FÀS*ü **no isis authentication send-only Ð** **send-only ÐE>AxAÄ**
AÇ*üÇAxAã MD5 AxAÃÊE› **isis authentication mode Ç5B** IS-IS
yS*üXAxAÃÄ
8üÜ Level ÊXAxAÃ*üy¡X Level-1 ` Level-2Ä

ÖG5B_Ð ÇÜy· GigabitEthernet 0/1 ,X Level-1 ,XAxAS*ü send-only Ä
5XLMLHFRQILJLVWHUIDFH*LJDELW(WKHUQHW
5XLMLHFRQILJLILVLVDXWKHQWLFDWLRQHQRQHOHYHO

ÎÎGÇÐ

Ç	ÆÄ
isis authentication key-chain	**Ü** IS-IS yAxAS*üXšÕÒ
isis authentication mode	**Ü** IS-IS y¡XAxAã
key-chain	**G5BšÕ**

ÖGÄÃÀ -

7.21 isis circuit-type

S*ÄÃÇ'5B IS-IS y¡X circuit-typeÄ*ÄÃÇX **no 6ãG5B** circuit-type TAxÄ
isis circuit-type { **level-1 | level-1-2 | level-2-only** }
no isis circuit-type

ÐÄÃÀ

Ð	ÆÄ
level-1	**6ä** Level-1 F•

level-2-only	**6ä** Level-2 F•
level-1-2	**6ä** Level-1-2 F•

Ъ,Õ5BĐ circuit-type Level-1-2

ä Ð yG5Bã

Ъ*Ð VpA'5BZ Level-1 ê Level-2-only ,X circuit-typeÈ IS-IS ¥Ð Level ,X PDUÄ
Vp is-type >G5B Level-1 ê Level-2-onlyÈ IS-IS r_ Level ,X_uBAA¹
y¥Õ is-type â circuit-type ,G X Level PDUÄ

G5B_Đ 5XLMLHFRQJLQWHUIDFH*LJDELW(WKHUQHW
5XLMLHFRQJILVVFLUFXLWWSHOHYHORQ\

ÏGÐ

Ç	Ä
is-type	**A5B** IS-IS r_,X Level

GÄà -

7.22 isis csnp-interval

AÐA'5B IS-IS y;X CSNP y[,XSKÈhÐÄ*ÄÇX **no 6G5B** CSNP y[,XSKÈhTAxÄ

isis csnp-interval *interval* [**level-1 | level-2**]

no isis csnp-interval [*interval*] [**level-1 | level-2**]

ÐAà

Ð	Ä

ÏĈĢĐ

Ǫ	ƐÄ
-	-

ĬĠÄȁ -

7.23 isis hello-interval

S*ÄĄǪ'5B IS-IS yƐÕ Hello y[,XKÈhÊÊ*ÄĄǪX **no 6ȁ5B** Hello KÈhÊÈ¬ AxÄ

isis hello-interval { *interval* | **minimal** } [**level-1 | level-2**]

no isis hello-interval { *interval* | **minimal** } [**level-1 | level-2**]

ĐAȁ

Đ	ƐÄ
interval	Ɛ*Õ* Hello y[,XKÈhÊÈ 1-65535È,Õ 10
minimal	Holdtime ȏ 1
level-1	**h*ü** Level-1 hello y[
level-2	**h*ü** Level-2 hello y[

ĭ,Õ5BĐ Level-1 ` Level-2 S*Đ5,Ȑ

}

ĬGÄê -

7.24 isis hello-multiplier

S*ÄĄ5B IS-IS y¡X Hello holdtime ,X,DŠ*ÄĄX **no 6ê** Hello holdtime ,D5B TÄxÄ

isis hello-multiplier *multiplier-number* [**level-1 | level-2**]

no isis hello-multiplier [*multiplier-number*] [**level-1 | level-2**]

ĬĐAê

Đ	ĘÄ
multiplier-number	*Đê* 2-100Ę,Õ 3

ĭ,Õ5BĐ Đ5,Õ

ĭĐ IS-IS CÃĘ/Ğ5Bã

ĬS*Đ Hello y[,X holdtime + hello-interval ,Ą¡DÄ

- 0 Td[(Tda)5(dds hllo)7(dding)]TJ/TT0 W 53/TT0 1 Tf5.99 g/TT0 116.966.7288Tc -9.48 -1.727 Td( )Tj/C2_0 1 Tf99642C0m<01CF144709

ĞŠB_Đ 5XLMLHFRQJURXWHULVLV

5XLMLHFRQJURXWHULVLVKHOORPXOWLSOLHU

ĬĞĐ

Q—•ws Þµ°C < ‡'°Đa °P	ĘÄ
isis hello-interval	**A5B** Hello ĘÕÈhÊÈ

ĬGÄê -

Hello

7.25 isis hello padding

S*ĐĘKĐ0

,X Hello y[,XÙÆÕX Hello y[È> Ä

ËG5B_Đ

```
5XLMLHFRQLJLQWHUIDFH*LJDELW(WKHUQHW
5XLMLHFRQLJLIPLVLVKHOORSDGGLQ
```

ÎÍGĘ

Ą	Ę
isis hello-interval	**A5B** Hello ÆÕÈhÊÈ
hello padding	**A5B** Hello y[,XÆ

ËGÄÆ -

7.26 isis lsp-interval

S*ÆĄ'5B IS-IS yÆÕ LSP PDU ,XKÈhÊÆĄX **no** 6ÆÈhÊÈ'5BTAxÄ

isis lsp-interval *interval*

no isis lsp-interval

ĐAÆ

Đ	Ę
interval	ÆÕ LSP PDU ,XKÈhÊÆÈ 1-4294967295È ,Õ 33

Ë,Õ5BĐ Đ5,Õ

Æ yG5Bã

ËS*Đ -

ËG5B_Đ

```
5XLMLHFRQLJLQWHUIDFH*LJDELW(WKHUQHW
5XLMLHFRQLJLILVLVOSLQWHUYDO
```

ÎÍGĘ

Ą	Ę
isis retransmit-interval	P2P 5%4ÈSP GÆÈhÊÈ

ËGÄÆ -

7.27 isis mesh-group

AĘÚ IS-IS yt9Û,X<E4ÆS*ÆĄX **no**

mesh-group-id	ú19Đ mesh-group-id ,X<E‡Ä 8È 1-4294967295

ß,Õ5BÐ yþ9Ï<E‡˜

Ïð yG5Bã

ß*Ð Mesh-groups Ê$ NBMA 5%4E#ðXÃ-,X LSP =7#|Ï‰ IS-IS CÃ<ý
yêXJý=7 LSPÈAèpÊÃ<G5BÐÈw LSP ‰X
ÐÈÊ8ðX LSPÈ>CG¿X CPU Ä
IS-IS <E‡ÄÁÊÃ<yÚèpÊ LSP >4˜XÐyÈwA¹ LSP ÊE›
4JÐ=7ÎpCÃ<4Z LSP FwÉBy=7 LSPÄ
VpLÊü IS-IS yG5B **mesh-group**Ê5**4**Ê**X** LSP Ê,XHÐS*ü **isis**
csnp-interval Ç5BM2 0 ,X CSNP y[ÈÊÈhèÊÕ CNSP y[Ê LSPÄ

ïG5B_Ð 5XLMLHFRQJLQWHUIDFH*LJDELW(WKHUQHW
5XLMLHFRQJILLVLPHVKJURXS

ÏÎGÇ

Ç	Ê
isis network point-to-point	**G!5B Ú** IS-IS ,X Broadcast y·2O_A'5B Point-to-Point 2O_

ïÎÄè)!Ð -

7.28 isis metric

S*ÐÇ'5B IS-IS y¡X Metric È*ÐÇX **no 6é** IS-IS y¡X Metric A'TxÄ

isis metric *metric* [**level-1| level-2**]

no isis metric [*metric*] [G!5B Ú

5XLMLHFRQJLILVLVPHWULF

ÏĈĢĐ		
	Ǫ	ĖÄ
	metric-style	**A5B** Metric 2O_
	isis wide-metric	**A5B** IS-IS y¡X wide Metric

ĬĠÄß **-**

7.29 isis network point-to-point

AǪ Broadcast 2O_,XyA'5B Point-to-Point 2O_S¨ÄAĘX **no 6ßá** Broadcast 2O_Ä

isis network point-to-point

no isis network [**point-to-point**]

ĐAß		
	Đ	ĖÄ
	point-to-point	**ß2O_**

ĭ,Õ5BĐ Broadcast 2O_Ä

ĕǪ yG5Bã

Ĭ*Đ S*ÄAǪ IS-IS ,X Broadcast y2O_A'5B Point-to-Point 2O_ĘǪ Broadcast 5%4° y2O_Ø

ĬG5B_Đ

5XLMLHFRQJLQWHUIDFH*LJDELW(WKHUQHW
5XLMLHFRQJLILVVHWR2UNSRLQWRSRLQW

ÏĈĢĐ		
	Ǫ	ĖÄ
	isis mesh-group	**G5BÚ** IS-IS yt9ĝ,X<Eã˜

ĬĠÄß **-**

7.30 isis password

S*8Ǫ'5By¡X Hello y[ĘAxAsÕ*ÄAĘX **no 6ßA5BX¸Õ**

isis password [**00TE31 Tw 1 1 Tf08025 Tc 1|2 Tc 0 Tw [Tj/TT2 1 Tf0f5025 Tc 17sis password**

Ï5B_Đ

```
5XLMLHFRQJLJ WHUIDFH*LJDELW(WKHUQHW
5XLMLHFRQJILVLVSULRULW OHYHO
```

ÏÎGĐ

Ç	È
-	-

ÏÄÀè

-

7.32 isis retransmit-interval

S*ÀÇ'5ByGô LSP ,XKÈhÊÃ*ÀÇX **no 6é** LSP GßÈhÊÃ'TÀxÄ

isis retransmit-interval *interval-time*

no isis retransmit-interval

ÏÀè

Đ	È
interval-time	LSP GßÈhÊÈ 0-65535È,Õ 5

ï,Õ5BĐ

Đ5,Õ

ê

yG5Bã

Ï*ô

S*ÀÇ'5B LSP GôXKÈhÊÇô P2P 5%Ê LSP yÈ retransmit-interval

ÊÈüÝ PSNP h1(È¥ÊÕ¹ LSP y[Ä

Vp retransmit-interval A' 0È¥ LSP y[Ä

Ï5B_Đ

```
5XLMLHFRQJLJ WHUIDFHVHULDO
5XLMLHFRQJILVLVUHWUDQPLWWHUYDO
```

ÏÎGĐ

Ç	È
isis lsp-interval	**y** LSP ¥XKÈhÊÈ

ÏÄÀè

-

7.33 isis wide-metric

S*ÐÇ'5By;X wide Metric È*ÐX **no 6ý** wide Metric A'TÀxÄ

isis wide-metric *metric* [**level-1 | level-2**]

no isis wide-metric [*metric*] [**level-1 | level-2**]

ÏÀè

Đ	È
metric	Metric È 1-16777214È,Õ 10
level-1	**h*** Level-1 circuit

	level-2	**h*ü** Level-2 circuit

Ï5,Õ5BÐ Level-1 ` Level-2 S*Ð5,Õ

Ïð yG5Bã

Ï*Ûð Metric ü IP Ã'Ç,X TLV Ù/ü SPF Au1k>h*ÛÇX Metric ></8y;XEÇÃ5ë
CÙPF Au1kJCÃCKSÄ
Metric ¢¼ metric-style ùJ wide Ã

ÏG5B_Ð 5XLMLHFRQJLQWHUIDFH*LJDELW(WKHUQHW
5XLMLHFRQJILLVLVZGHPHWULF

ÏGÇÐ	Ç	ÉÄ
	metric-style	**A5B** Metric 2O_
	isis metric	**A5B** IS-IS y;X Metric

ÏGÄÃð -

7.34 is-type

S*ÄÇÛ IS-IS E¤ ,X LevelÄ*ÄÇX **LevelgTxpÃ**

ÏGÄê -

7.35 log-adjacency-changes

AşS6ê debug ,XÑ IS ,XF(ÐÄ*AQX **no 6ê**

6Ñ

log-adjacency-changes

no log-adjacency-changes

ÐAê

Ð	Ë Ä
-	-

Ï,Õ5BÐ Aš6ÑÐ

ê IS-IS CÃE7G5Bã

Ï*Ð 3Ã*ü **debug ÐA),** IS ,XF(ÐÈ56ÈX2Ï‹C Ä

ÏG5B_Ð -

ÏGÐ

Ð	Ë Ä
-	-

ÏGÄê -

7.36 lsp-gen-interval

S*ÐQ'5B LSP KÈhÊÈXÐ*AQX **no 6ê**

lsp-gen-interval [**level-1 | level-2**] *value*

no lsp-gen-interval

ÐAê

Ð	Ë Ä		
value	LSP KÈhÊÈXÐ	1-120È,Õ	5
level-1	**h*ü** Level-1 IS-IS		
level-2	**h*ü** Level-2 IS-IS		

Ï,Õ5BÐ Level-1Level-2v2l-KÈÑ@

Ï ó]a´D €

ÏG5B_Đ
```
5XLMLHFRQJURXWHULVLV
5XLMLHFRQJURXWHUOVSJHQQWHUYDO
```

ÏÎGĐ

Ç	Ł Ä
lsp-refresh-interval	LSP GĶÈhÊÈ

ÏGÄê -

7.37 lsp-refresh-interval

S*ĐÇ'5B LSP ,XĶÈhËS*ÁÇX **no 6ê1AxÄ**

lsp-refresh-interval *interval*

no lsp-refresh-interval

ÏÐAê

Đ	Ł Ä
interval	LSP ,XĶÈhÈÈ 1-65535Ł,Õ 900

Ï,Õ5BĐ Đ5,Õ

Ê IS-IS CÃE/G5Bã

ÏS*Đ '7Đ•X LSP 0n(ÕÁ refresh interval EĶS,XÊÊ LSP Ú refresh Eþ LSPÈÉ LSP (4{JÃ

lsp-refresh-interval ÑOõ max lifetimeÄ

ÏG5B_Đ
```
5XLMLHFRQJURXWHULVLV
5XLMLHFRQJURXWHUOVSUHIUHVKLQWHUYDO
```

ÏÎGĐ

Ç	Ł Ä
-	-

ÏGÄê -

7.38 max-area-addresses

S*ĐÇ'5BAGŁ5B area address ,XÔS*ĐÇX **no 6ê15BAGŁ5B** area address ,XÔTAxÄ

max-area-addresses *value*

no max-area-addresses

ÏÐAê

Đ	Ł Ä
value	*AŒ* area address ,XÔÈÈ 3-6Ł,Õ 3

ï¿Õ5BÐ	Ð5,Õ
ïÐ	IS-IS CÃE7G5Bã
ïS*Ð	Í Level-1 ,X IS CÃ<Ë¼ max-area-addresses ,èÑÏ°G2Ä
ïG5B_Ð	5XLMLHFRQJURXWHULVLV 5XLMLHFRQJURXWHUPD[DUHDGGUHVVHV

ïÎGÐ	Ç	Ë.Ä
	net	**A5B** IS-IS ,X NET(Network Entry Title)

ïGÄè	-

7.39 max-lsp-lifetime

S*ÐÇ'5B LSP *ÐÈXÐ*ÐÇX **no 6à5B** LSP *ÐÈÐAxÄ

max-lsp-lifetime *value*

no max-lsp-lifetime

ÐAè	Ð	Ë.Ä	
	value	LSP *ÐÈXÐÐÈ	1-65535È,Õ 1200

ï¿Õ5BÐ	Ð5,Õ
ïÐ	IS-IS CÃE7G5Bã
ïS*Ð	max-lsp-lifetime Ñ¥Oî lsp-refresh-intervalÄ
ïG5B_Ð	5XLMLHFRQJURXWHULVLV

Ğ5B_Đ	5XLMLHFRQJURXWHULVLV 5XLMLHFRQJURXWHUŲW

ÎĞĮĐ	Ų	Ł Ä
	router isis	**Î** IS-IS r_

ĞÄß	-

7.42 redistribute

A’5BÚĈÃGĸJ ISIS Ä*ÆĮX **no 6ß8GĺĮ0Ä**

redistribute { **bgp** | **ospf** *process-id* [**match** { **internal** [**external** [**1 | 2**]] [**nssa-external** [**1 | 2**]] | **external** [**1 | 2**] [**internal**] [**nssa-external** [**1 | 2**]] **| nssa-external** [**1 | 2**] [**internal**] [**external** [**1 | 2**

IS-IS

IS-IS

IS-IS

route-map **distribute-list** Level-1 Level-2 **route-map** **distribute-list** 2 **no redistribute** **no redistribute** isis *tag1* **no redistribute isis** *tag1* **level-1 into level-2 route-map** **route-map** *Í* isis *tag1*

ÏÎGĘÐ

Ę	Ë.Ä
ip router isis	**G5Byâ** IS-IS IPv4 CÃ#A,
net	**G5B** NET

ĞGÄâ -

7.46 show clns is-neighbors

/,ý IS FèCÃ<FyG2Ï.Ä

show clns [*tag*] **is-neighbors** [*interface-type interface-number* | **detail**

7.47 show clns neighbors

/ý IS FèCÃ<Ç1ãÕ¼FyG2Ï¿Ä

show clns [*tag*] **neighbors** [*interface-type interface-number* | **detail**]

ÐAè	
Ð	Ä
tag	*ô* IS-IS r_
interface-type *interface-number*	*ôÌyÆ*
detail	**/A¤ÇÍb¿Ý·**

Ï¿Õ5BÐ -

Ï¿Ð (Mã

Ï*Ô -

Ï5B_Ð 5XLMLHVKRZ ZOVQHLJKERUVGHWDLO
6HDQOO
6VWHP,G6136WDWH+ROGWLPH7SH3URWRFRO
,QWHUIDFH
UGIDG8S/,6,6
9/$
8S/,6,6
9/$
6MDFHQ'
8SWLPH
6HDGGUHVVHV

ÏÎGÐ		
Ç	Ä	
show clns is-neighbors	**S*ÐÇ**	IS FÈ ¤CÃ<FyG 2Ï¿

Ï5Aè -

7.48 show isis counter

/ IS-IS ,XÆ¿Au¿

show isis [*tag*] **counter** Ï – D

–	£ E Ä
tag	IS-IS r_

ĭ5,Õ5BĐ -

Ëđ (Mã

Ĭ*Ê -

Ï5B_Đ

```
5XLMLHVKRZVLVFRXQWHU
$HDQOO
,6,6/HYHOLVV6VWHP&RXQWHU(QWU\
LVLV6V6WDW&RUU/63V
LVLV6V6WDWSXWK7SH)DLOV
LVLV6V6WDWSXWK)DLOV
LVLV6V6WDW/63'EDH2ORDGV
LVLV6V6WDW0DQGU'URS)URP$HDV
LVLV6V6WDWSWPSW7R([0D[6HT1XPV
LVLV6V6WDW6HT1XP6NLSV
LVLV6V6WDW2Ø33XUJHV
LVLV6V6WDW,')LHOG/HQLVPDWFKHV
LVLV6V6WDW0D[$HDG6GU0LVPDWFKHV
LVLV6V6WDW3DUW&KDQHV
LVLV6V6WDW63)5XQ
,6,6/HYHOLVV6VWHP&RXQWHU(QWU\
LVLV6V6WDW&RUU/63V
LVLV6V6WDWSXWK7SH)DLOV
LVLV6V6WDWSXWK)DLOV
LVLV6V6WDW/63'EDH2ORDGV
LVLV6V6WDW0DQGU'URS)URP$HDV
LVLV6V6WDWSWPSW7R([0D[6HT1XPV
LVLV6V6WDW6HT1XP6NLSV
LVLV6V6WDW2Ø33XUJHV
LVLV6V6WDW,')LHOG/HQLVPDWFKHV
LVLV6V6WDW0D[$HDG6GU0LVPDWFKHV
LVLV6V6WDW3DUW&KDQHV
LVLV6V6WDW63)5XQ
```

ÎĞĮĐ

Ą	ĘÄ
-	-

ĞÄâê -

7.49 show isis database

/ LSP DBgĮ

show isis [*tag*] **database** [*FLAGS* | *LEVEL* | *LSPID*]

ĐAđ

Đ	Ä
tag	ĵ IS-IS r_
FLAGS	¥ detail | verbose detailÖ4 verboseÖ detail
LEVEL	¥ l1 | l2 | level-1 | level-2 l1 ` level-1 Level-1 ,X LSP DBg l2 ` level-2 Level-2 ,X LSP DBg
LSPID	ĵ LSP ,X ID LSP ,X

Ь,Õ5BĐ -

đ (M

Ь*Đ -

Ġ5B_Đ

```
5XLMLHVKRZVLVGDWDEDVHGHWDLO
$HDQOO
,6,6/HYHO/LQ6WDWH'DWDEDVH
/63,'/636HT1XP/63&KHFNVXP/63+ROGWLPH732/
5XLMLH[[&"
$HDG6GUHVV
1/3,'[&&
+RVWQPH5XLMLH
,3G6GUHVV
0HWULF,6U
0HWULF,3
U[[$
$HDG6GUHVV
1/3,'[&&
+RVWQPHU
,3G6GUHVV
0HWULF,6U
0HWULF,3
U[[$
0HWULF,6U
0HWULF,65XLMLH

,6,6/HYHO/LQ6WDWH'DWDEDVH
/63,'/636HT1XP/63&KHFNVXP/63+ROGWLPH732/
5XLMLH[[&'
```

```
$HHDG$GUHVV
1/3,'[&&
+RVW1DPH5XLMLH
,3$GUHVV
0HWULF,6U
0HWULF,3
U[[$
$HHDG$GUHVV
1/3,'[&&
+RVW1DPH
,3$GUHVV
0HWULF,6U
0HWULF,3
U[[$
0HWULF,6U
0HWULF,65XLMLH
```

ÏĈĠĘ

Ę	ĘÄ
-	-

ĔĠÄê

-

7.50 show isis graceful-restart

/ IS-IS GR ,ĔG,X(ĝÄ

show isis [*tag*] **graceful-restart**

ĔÐAê

Ð	ĘÄ
tag	IS-IS r_éÄ

ĕ,Õ5BÐ

-

ĕĘ

(Mã

ĕ*Ð

-

Ĕ5B_Ð

```
5XLMLHFRQJVKRZVLVJUDFHIXOUHVWDUW
*UDFHIXOUHVWDUWHQDEOHGJUDFHIXOSHULRGV/HYHOWLPHU,QWHUIDFHWLPHUV
*UDFHIXOUHVWDUW+HOSHUHQDEOHG
```

ÏĈĠĘ

Ę	ĘÄ
graceful-restart helper disable	**6Ñ** IS-IS GR Help 6ñ

ĔĠÄê

-

7.51 show isis hostname

/CÃ<ă System ID ,XĥG2Ï

show isis [*tag*] **hostname**

ĎAđ

Đ	Ł Ä
tag	*ĥ* IS-IS r_

ĭ,Õ5BĐ -

đ (Mã

Ĭ*Ĥ -

Ğ5B_Đ

```
5XLMLHVKRWVLVKRVWQPH
6VWHP,"QPLF+RVWQPH
5XLMLH
U
```

ÏĜĘ

Ę	Ł Ä
-	-

ĞÄđ -

7.52 show isis interface

/ IS-IS y¡XA4ĮĊ

show isis [*tag*] **interface** [*interface-type interface-number*]

ĎAđ

Đ	Ł Ä
tag	*ĥ* IS-IS ,Xr_á
interface-type *interface-number*	*ĥ yá*

ĭ,Õ5BĐ -

đ (Mã

Ĭ*Ĥ -

Ğ5B_Đ

```
5XLMLHVKRWVLVLQWHUIDFH
$HDQOO
9/$LVXSOLQSURWRFROVXS
```

```
5RXWLQJ3URWRFRO,6,6XQOO
1HWZRUN7\SH%URDGFDVW
&LUFXLW7\SHOHYHO
/RFDOFLUFXLW,'[
([WHQGHG/RFDOFLUFXLW,'[
/RFDO613$GIDE
,3LQWHUIDFHDGGUHVV

/HYHO0HWULF3ULRULW\&LUFXLW,'U
1XPEHURIDFWLYHOHYHODGMDFHQF\LHV
/HYHO0HWULF3ULRULW\&LUFXLW,'U
1XPEHURIDFWLYHOHYHODGMDFHQF\LHV
1H[W,6,6/$/HYHO+HOORLQWHUYDO
1H[W,6,6/$/HYHO+HOORLQWHUYDO
```

7.54 show isis neighbors

/ IS-IS ,XFµ

show isis [*tag*] **neighbors** [**detail**]

ÐAÈ

Ð	Ä
tag	*ô* IS-IS r_
detail	**/A¹µÉbÝy·**

level-2	**ĐÛ** Level-2 ,X%

ĐĐ,Õ5BĐ -

Đ -

Đ*Đ -

ĐG5B_Đ
```
5XLMLHVKRZVLVWRSRORJ\
SHDQOO
,6,6SDWKVWROHYHOURXWHUV
6VWHP,G0HWULF1H[W+RS613QVHUIDFH
UUGIDG9/$
5XLMLH
,6,6SDWKVWROHYHOURXWHUV
6VWHP,G0HWULF1H[W+RS613QVHUIDFH
UUGIDG9/$
5XLMLH
```

ĐĐGĐ

Q	EÄ
-	-

ĐGÄè -

7.56 spf-interval

A'5B SPF Au1k,XÊÈhË*ĐQX **no 6ÊÈAxÄ**

spf-interval [**level-1 | level-2**] *interval*

no spf-interval

ĐAè

Đ	EÄ		
interval	SPF Au1k,XÊÈhÈ	1-120Ê,Õ	10

ĐĐ,Õ5BĐ ĐĐ5,Õ

Đ

Đ*Đ 8 SPF ,XKÈhÊÊ*ü Level-1 ` Level-2Ä

rû SPF Au1k,XÊÈhÊS! SPF ,XNe4Au1kÈN5ë CPU C8ÄÊÃęXhÊ

4ę

ĐG5B_Đ
```
5XLMLHFRQJURXWHULVLV
5XLMLHFRQJURXWHUVSILQHUYDOOHYHO
```

ÏĈĢĐ

Ç	Ł Ä
-	-

ĠÄâĕ -

7.57 summary-address

G5B IPv4 6.ÖÃÆ*ßQX **no 6ĝ886.ÖÃ**

summary-address *ip-address net-mask* [**level-1 | level-2 | level-1-2**]

no summary-address *ip-address net-mask*

ĐAâĕ

Đ	Ł Ä
ip-address	6.Æ IP Ä
net-mask	**6.C Æ5 4 -Đ**
level-1	ü Level-1 *ó
level-2	ü Level-2 *ß Õ Level-2 *Æ
level-1-2	ĝ Level-1 ` Level-2 *ó

ĕ,Õ5BĐ 6.ÖÃ

ĕĐ IS-IS CÃE7Ġ5Bã

Ĕ*Ð A’5BƵ.ÖÃĕ,6.ÖÃYĐ’Ł’5%‰ÃĻĝ.ÖÃĖà
¼4ŁÃÄ

ĠĕB_Đ

```
5XLMLHFRQJURXWHULVLV
5XLMLHFRQJURXWHUVXPPDUDGGUHVVOHYHO
```

ÏĈĢĐ

Ç	Ł Ä
-	-

ĠÄâĕ -

8

8.1 ip local policy route-map

ÐÉÆÕXy[h*Ì*+9CÃÀÈË*Ò **ip local policy route-map** ÄÐ **no** 6ÈÉ*9 CÃh*Ä

ip local policy route-map *route-map*

no ip local policy route-map

ÐAÈÐ

Ð	ÆÄ
route-map	Ã

Ì,Õ5BÐ 5,Õ*Ì*+9CÃÄ

Ò <G5BÃ

Ì*Ð SÝ 192.168.217.10 ÐÆÕXy[ÔÇ- 6.6.6.6Ä

1ÈG! IP y[,X ACL

5XLMLHFRQJDFFHVVOLVWSHUPLWKRVW

2ÈCÃÒ

5XLMLHFRQJURXWHPDSODESHUPLW

5XLMLHFRQJURXWHPDSPDWFKLSDGGUHVV

5XLMLHFRQJURXWHPDSVHWLSQ[WKRS

5XLMLHFRQJURXWHPDSH[LW

3È'Ô*Ì*+9CÃ

5XLMLHFRQJLSORFDOSROLFURXWHPDSODE

ÏÐÒ

Ò	ÆÄ
access-list	**nA**
route-map	**nC**
set vrf	**n1*9CÃ** IP y[,X VRF r_
set ip next-hop	**n1*9C**
set ip default next-hop	**n1*9CÃAxÔÇ**
set ip tos	**A5By[** IP ,X TOS
set ip dscp	**A5B** IP y[,X DSCP

set ip precedence	**A5By[** IP ,Xï{
match ip address	**A5BEþ**

ÏGÄèø -

8.2 ip policy

A'5B1*+9CÃ,X **set ip** [**default**] **nexthop** X[ÔÇ*ü-Ñ55ÇG5B
ß*ü **ip policy E>G5BÄ** Aþ **no 6ñ1*9CÃEÆ**
ip policy { **load-balance | redundance** }
no ip policy

ÐAèø

Ð	EÄ
load-balance	**B5Ñ**
redundance	**k-Ñ**

ï5,Õ*ü-Ñ 5,Õ*ü-Ñ

þ <G5Bä

Ó*Ð G5B **set ip next-hop ß5BÔÇ5Bï-Ñ*9CÃþ**
dXÔÇ*A5BB5ÇE*9CÃXÔÇ*ü/CMP Ñ'5B 8
ÔÇCMP Ñ'5B 32 ÔÇ

MAC

ÏG5B_Ð CÃÀ'5Bþ nexthop,ïG5BÄ'5Bï-Ñ*ü FastEthernet 0/0 þX1*
+9CÃÝÔ nexthop CK0*Ä
1È5BþCMP Ô þ

3ÿÐh*Ì*+9CÃ
5XLMLHFRQJLQVHUIDFH)DVW(WKHUQHW
5XLMLHFRQJLILSSROLFURXWHPDSODE
5XLMLHFRQJLH[LW
5XLMLHFRQJLSSROLFUHGXQDQH

ÏÎGÐ

Ç	ÉÄ
-	-

ÏGÄè -

8.3 ip policy route-map

ÒÐh*Ì*+9CÃÈË*G5BÇ **ip policy route-mapÈ*ÀÐ** **no 6ÉÝÞ**

h*Ì*+9CÃ

ip policy route-map *route-map*

no ip policy route-map

ÐAè

Ð	ÉÄ
route-map	è

Ì,ÕG5BÐ 5,ÕKÁ*+9CÃÄ

Ðè yG5Bè

Ì*Ð 1*+9CÃÑ'Ô,Xyh*è¼yy,XDBÈ> 1*+9CÃÊAýÉÇX

DBè> 1*+9CÃÄ

h*Ì*+9CÃÑ'Ò1*+9CÃS*¡XCÃÈÊÎCÃÐÃÈÌ1*+94È

ÿ*+9FÑZ 1 ÿXGf0Ðh*Ì*+9CÃè¼yy,X

¼> "ÈÜÃÐ1*+9,XDBÈÉ¡XCÃÉÈ@> ÝÈÜÃÐ

1*+9,XDBÝ¼1*+9n,XÐE> ÝÈ¼

A'ÐÈÑG5BÐÃÐÈG5BCÃÈ5B,XCÃÐ

G5B,XCÃÈÐ

ÌG5B_Ð 'ÉÐ%y· FastEthernet 0/0 yDBy¼ÝpDByÈ 10.0.0.1È'5BÐÇ

196.168.4.6¼ÝpÈ 20.0.0.1 Á'5BÐÇ 196.168.5.6È> BEÉÝÈ

1È5BG! IP y[,X ACL

5XLMLHFRQJDFFHVVOLVWSHUPLWKRVW
5XLMLHFRQJDFFHVVOLVWSHUPLWKRVW
2ÈCÃÒ
5XLMLHFRQJURXWHPDSODESHUPLW
5XLMLHFRQJURXWHPDSPDWFKLSDGGUHVV
5XLMLHFRQJURXWHPDSVHWLSÐ[WKRS

```
ë
ë
ë
ë
ë
```

3ÿÐ*ë*+9CÃ

```
5XLMLHFRQJLQVHUIDFH)DVW(WKHUQHW
5XLMLHFRQJILSSROLFURXWHPDSODE
5XLMLHFRQJLIH[LW
```

ÏĜĘĐ

Ę	Ę Ä
access-list	**nAê**
route-map	**nCÕ**
set vrf	**n1*9CÃ** IP y[,X VRF r_

WCMP ÐÝ5B 8 ÐÈCMP ÐÝ5B 32 ÐÇ

8

ÏÐAèè

Ð	ÆÄ
route-map-name	CÃ¸ÒXÆÆE› **route-map Ò5BÒXÄ**

Ï5,Ò5BÐ yÐ*Ï1*+9CÃs6Ñ

ÏÐ yG5Bã

Ï*ÐÎ ÿÏ*ü IPv6 1*+9CÃÆÿy,X IPv6 y[E> 1*+9CÃÆÿÆ¿ÒX IPv6 y[Ê> 1*+9CÃÄ

h*Ï1*+9CÃÆÑÒ²Ï1*+9CÃS*¡XCÃÆÐÎCÃÐÃÆ51*+94È

Ð*+9FÑZ 1 ÐXGÍ²ÐÐh*Ï1*+9CÃÆÿy,X

Ï> "èÜÃÐ1*+9,XDBÏÐ¡ÎXCÃÆE@> ÿÐÜÃÐ

1*+9,XDBÏÐ1*+9n,XÐE> ÿÐ

A'ÐÐÒ5BÐ IPv6 ,XCÃÐÐ5BCÃÐ5B,XCÃÒ

ÆG5B,XCÃÐ

>• IPv6 1*+9CÃé¡XCÃÒXÑO IPv6 ÒXÐ1*+9CÃÆÁ

Ï5B_Ð 'Ð5%y· FastEthernet 0/0 y IPv6 ,XDBy[ÐpDByÐ 10::/64 5%‰D

set ipv6 default next-hop	**A5B5Õ¥ÆKÔÇ**
set ipv6 next-hop	**A5BE¥ÆKÔÇ**
show ipv6 policy	**/ÀÛ*¼1*9CÃ‰**
show route-map	**/¸KCÆ5B¥‰**

ÜÄß -

8.7 show ip policy

/'Ú5BZ*+9CÃ¸XyžÀ¼ÿh*¡¸KCÃ¸ÒXßÄ

show ip policy

ÐAß

Ð	ÆÄ
-	-

/ ' !

ÏÐ (MÆÄ

ÏS*Ð ÆÐ¼ïªÝh*Ï IPv6 ,ÏG,X1*+9CÃÆÆ*ÄÇ

ÏG5B_Ð /ÆÐ¼ïªÏX1*+9CÃÄ

```
5XLMLHVKRZSYSROLF\
%DQDÐH0RGHUHGXQDÐH
,QWHUIDFH5RXWHPDS
9/$50BIRUB9ODÐ
9/$50BIRUB9ODÐ
```

+‰	Aè
Banlance Mode	**Ä Ù*9CÆ**
Interface	**h*Ï*9CÃyÆÄ**

Route

9 VRF

9.1 ip vrf

VRF

ip vrf *vrf-name*

no ip vrf *vrf-name*

Ï5B_Ð yt9)#A, VRF

5XLMLHFRQJLILSYUIIRUDUGLQUHGYUI

ÏÎGÐ

Ð	ÐÄ
-	-

ÏGÄð -

9.3 show ip vrf

/)#A, VRF Ð

show ip vrf [**brief** | **detail** | **interfaces**] [*vrf-name*]

ÐAð

Ð	ÐÄ
brief	1T+9/ VRF ðyÐ
detail	A9š VRF ðyÐ
interfaces	*A9š* VRF ðyÐ
vrf-name	VRF ,XáÄ

ï,Õ5BÐ '!ùÐÊT+9/2Ï1Ý VRF Ð

ðÐ (M*ã

ï*ÐÐ S*ÄÐ VRF ÐÖ

GK+ brief 1T)/

GK+ detail A9š

GK+ interfaces / VRF ,XyÐ

Ï5B_Ð -

ÏÎGÐ

-IP

IP 4

1. IPv4 4
2. IPv6 4
3. IGMP
4. MLD
5. PIM-DM
6. PIM-SM
7. PIM-SMv6
8. MSDP
9. IGMP Snooping
10. MLD Snooping

1 IPv4

1.1 clear ip mroute

AÐQ¸*9#Ù8 IP 4€ÇÃ¸Ä

clear ip mroute { * | *group-address* [*source-address*] }

Ï-DAðð

–D	Ä
*	#Ù84€ÇÃ><¸ÝXEÐÄ
group-address	Ã
source-address	ÃÄ

Ï5,Õ!5BÐ -

ÏQðð (Mã

ÏS*Ñð -

ÏG!5B_Ð 4€ÇÃ><#Ù84˜ 230.0.0.1 ,X47Ã¸><NMÖ

5XLMLHFOHDULSPURXWH

ÏÎGQÐ

Q¸	Ä
show ip mroute	4Ð

ÏGÄðð -

1.2 clear ip mroute statistics

#Ù8 IP 4€ÇÃ47Au¸Ä

clear ip mroute statistics { ***** | *group-address* [*source-address*] }

Ï-DAðð

–D	Ä
*	Ù84Ð
group-address	Ã
source-address	ÃÄ

Ï5,Õ!5BÐ -

ÏQðð (Mã

ÏS*Ñð -

Ï¨G!5B_Ð 4CÃ><#Ù84˜ 230.0.0.1 ,X4CÃ4?Au¿Ö

5XLMLHFOHDULSPURXWHVWDWLVWLFV

ÏÎGQÞÐ

Q¸	Ë¨Ä
show ip mroute	**4Õ**
clear ip mroute	**Ù84Õ**

ÏGÄß¨ -

1.3 debug ip mrf event

ÏÔÀÔÈÌ IPv4 4CÃEXØÉ/Ë*ÀQ¸X no 6ÉKÁÀÔÄ

debug ip mrf event

no debug ip mrf event

Ï-DAß¨

–D	Ë¨Ä
-	-

Ï¸,Õ!5BÐ AÀÔGKÁ

ÏQÞÐ (Mã

ÏS*Ô¨ -

Ï¨G!5B_Ð -

ÏÎGQÞÐ

Q¸	Ë¨Ä
-	-

ÏGÄß¨ -

1.4 debug ip mrf forwarding

ÏÔÀÔÈÌ IPv4 4ÿ[CÃEXØÉ/Ë*ÀQ¸X no 6ÉKÁÀÔÄ

debug ip mrf forwarding

no debug ip mrf forwarding

Ï-DAß¨

–D	Ë¨Ä
-	-

Ï¸,Õ!5BÐ AÀÔGKÁ

ÜQþÐ (Mã

Ü5*Ð -

ÜG!5B_Ð -

ÜÎGQÞÐ

Q¸	Ë Ä
-	-

ÜGÄÀÐ -

1.5 debug ip mrf mfc

ÐÀÂÊÈ IPv4 ÁÇÃÆÈ¢<NM,XÞÆ/Ü5*ÀÐQ¸X no 6ÈGKÁÀÂÄ

debug ip mrf mfc

no debug ip mrf mfc

Ì-DÀÐ

–D	Ë Ä
-	-

Ü5,Õ!5BÐ ÀÀÂGKÁ

ÜQþÐ (Mã

Ü5*Ð -

ÜG!5B_Ð -

ÜÎGQÞÐ

Q¸	Ë Ä
-	-

ÜGÄÀÐ -

1.6 debug msf api

ÐÀÂÊÈ IPv4 ÀÆÈ¢X api y>À*XÞÆ/Ü5*ÀÐQ¸X **no 6ÈGK**

Ø Ä

debug msf api

no debug msf api

Ì-DÀÐ

–D	Ë Ä
-	-

ï5,Õ!5BÐ AA©GKÁ

ÏQÇÐ (Mã

ï5*Ô -

ÏG!5B_Ð -

ÏÏGQÇÐ

Q¸	ÉÄ
-	-

ÏGÄÀÐ -

1.7 debug msf event

ÔA©ÈGb IPv4 ¾ÉÇÐXÔ/Ï5*AQ¸X **no 6ÔÄ**

debug msf event

no debug msf event -

ÏDAÀÐ

–D	ÉÄ
-	-

ÏGÁ¼ -

ï5,Õ!5BÐ AA©GKÁ

ÏQÇÐ (Mã

-

ï5BA%ÐÐ - ÏÇQÐ

ЬЗ,Õ!5BÐ	AA©GKÁ
ÜQþÐ	(Mã
Ь*Ð	-
Ü!5B_Ð	-
ÎGQÞÐ	[redacted] Ë Ä
	- -
ÜÄÐ	-

1.9 debug msf mfc

ÐA©ÈÈ IPv4 -

Ï–DAèð

–D	ÆÄ
-	-

Ï5,Õ!5BÐ AA©GKÁ

ÏQÇÐ (Mã

ÏS*Ðð -

ÏG!5B_Ð -

ÏÎGQÇÐ

Q¸	ÆÄ
-	-

ÏGÄèð -

1.13 debug nsm mcast mrt

ÐA©Ê¼GÈb4CÃ,XÇÄ*AÆQ¸X no 6ÆKÁA©Ä

debug nsm mcast mrt

no debug nsm mcast mrt

Ï–DAèð

–D	ÆÄ
-	-

Ï5,Õ!5BÐ AA©GKÁ

ÏQÇÐ (Mã

ÏS*Ðð -

ÏG!5B_Ð -

ÏÎGQÇÐ

Q¸	ÆÄ
-	-

ÏGÄèð -

1.14 debug nsm mcast register

ÐA©Ê¼GÈb¼M¸XÇÄ*AÆQ¸X no 6ÆKÁA©Ä

debug nsm mcast register

no debug nsm mcast register

Ï-DAèð

–D	ÆÄ
-	-

Ï¿,Õ!5BÐ AªÂGGKÁ

ÜQþÐ (Mã

Ï*ÐÔ -

Ü!5B_Ð -

ÌÎGQÞÐ

Q¸	ÆÄ
-	-

ÜÄèð -

1.15 debug nsm mcast stats

ÊÔªÂGÈÆ-by><NM4²Au¿,XÞÉ¾ÄÆQ¸X no 6ÆKÁªÂGÄ

debug nsm mcast stats

no debug nsm mcast stats

Ï-DAèð

–D	ÆÄ
-	-

Ï¿,Õ!5BÐ AªÂGGKÁ

ÜQþÐ (Mã

Ï*ÐÔ -

Ü!5B_Ð -

ÌÎGQÞÐ

Q¸	ÆÄ
-	-

ÜÄèð -

1.16 debug nsm mcast vif

ÊÔªÂGÈÆ-byE> E/Ï*ÄÆQ¸X no 6ÆKÁªÂGÄ

debug nsm mcast vif

no debug nsm mcast vif

Ï-DAèê

–D	Ë.Ä
-	-

ï5,Õ!5BÐ AA©GKÁ

ÜQÞÐ (Mã

ïS*ûÐ -

ÜG!5B_Ð -

ÏÎGQÞÐ

Q¸	Ë.Ä
-	-

ÜGÄèê -

1.17 ip mroute

G!5B4ŤM-ÕÃÄS*ÄaQ¸X **no ê8G5ÞÃ**

ip mroute *source-address mask* [*protocol*] { *rpf-addrress* | *interface-type interface-number* } [*distance*]

no ip mroute *source-address mask* [*protocol*]

Ï-DAèê

–D	Ë.Ä
source-address	Ø
mask	4ê,X}-Õ
protocol	!!7ïS*¡X)€Ã#A,
rpf-address	RPF FÄê,XÎÞÇX
interface-type *interface-number*	RPF yÄê,XÿÅ
distance	Øõ 0-255È¿Õ 0Ä

ï5,Õ!5BÐ 4ŤM-ÕÃ

ÜQÞÐ <ã

ïS*ûÐ M-ŒCÃ*ü RPF Ä

VpÞÙM-ŒCÃ,Xÿ5ÃM2ÎÇ IP ÈwAÿŤOé&O_Ä

ÜG!5B_Ð

5XLMLHFRQILJLSPURXWH

ÏĈGQÞ	Q¸	ÆÄ
	-	-

ĞGÄð -

1„18 ip multicast-routing

AĐQ¸*9|4€ÇÃÆ*ÆQ¸X **no GÁÃ**

ip multicast-routing

no ip multicast-routing

Ï-DAð	–D	ÆÄ

Ï*Ð G!5B!8QÇ8yÅ43Ì,X IGMPÃ PIM-SM y[E> EÇDB#Åy·
#9#Ã
!8QG6(,X ACL ÐX ACLÈÃ ACLÐ),X ACL ¢!,ÂXÈ!
ÐÄ

ÏG!5B_Ð A5B svi1 ý4¯XE Ä
5XLMLHFRQILJLSDFFHVVOLVWVWDQGDUGPXOERXQ

1.21 ip multicast rpf longest-match

ÏØSG!sE½ RPF CÃÄ*ÄQ¸X **no Í66µÕ5Ä**

ip multicast rpf longest-match

no ip multicast rpf longest-match

Ï-DAÄð	
–D	ÉÄ
-	-

Ï5,Õ!5BÐ E¼{Ð,¬XCÃ0 RPF CÃÄ

Vp¼{,ÄM-ÕÃÃMBGP CÃÿCÃ,XNNcE> E¼

ÜÇð <ã

Ü*Ðð E½ RPF CÃ,X!9PxÖ

1È 4M-ÕÃ><ÃMBGP CÃ><ÿCÃ><ÐÕÃu RPF ¨XÔÃÄ

2È É5CÃEÄð RPF CÃÄ

VpG!5BØSG!sE½ÃQÇ5CÃEØSG!,XFw5CÃ¼pE-

5CÃ,X}-Ð½{Ð,¬XFw5CÃ¼pWÀX¼{3,Ä•

M-ÕÃÃMBGP CÃÿCÃ,XNNcE> E¼

Vpü!5BØSG!E½ÃÉ5CÃEÑ{Ð,¬XFw5CÃ¼pWÀX

¼{,ÄM-ÕÃÃMBGP CÃÿCÃ,XNNcE> E¼

Ü!5B_Ð -

ÏÜGQÐ	
Q¸	ÉÄ
-	-

ÜÄÄð -

1.22 ip multicast static

AÉQ*9G!5B4#ÄQ¸X no 6ÃG!5BÄ

ip multicast static

ÜQþ <ã

Ü*Ô íô4#Ê!5BÞQ¸ÈAÈ!5Bþ»AÈ@X0Ê#G!5B¥Æ
êÈ4#ÊÑEo@È5B,X0ÈÊÔ»AÇX0ÊÈ@Ä
AÐ¿¼4#0ÊXE»0ÊÈE¿4#A#Ay[,XÔÊb4#A,
ÝÖ PIM-DM ê PIM-SMÊXo(MôC*4ÐB#PE|,XÈÈCÃ#A,X> ÊÑ•
EÄ

Ü!5B_Ð G!5B4# (192.168.43.4 È 225.1.1.5)#XÐE GigabitEthernet 2/6 ` FastEthernet 3/2 EÊÐ
UXLMLHFRQILJLSPXOWLFDVWVWDWLF*
UXLMLHFRQILJLSPXOWLFDVWVWDWLF)

ÎÜGQÐ

Q¸	ÈÄ
-	-

ÜGÄÈ -

1.23 ip multicast ttl-threshold

AÐQ¸*9G!5By¡X TTLÄime-To-Live ÅÊ*AÐQ¸X **no Ê6ÈÐ**

ip multicast ttl-threshold *ttl-value*

no ip multicast ttl-threshold

.6603 Tm( )TjET0.D00262g/B6.9.807 0 Td( )TjETq12/B6.9.67.8246.96/B6.9.807 0 Td( )Tjmh328.92 56

1.24 msf ipmc-overflow override

G!5B4:ê<NMÄ$ÊÄ*ÄQ¸X **no Ê6ÊÕ**

msf ipmc-overflow override

no msf ipmc-overflow override

Ï-DAê

–D	ÆÄ
-	-

Ï5,Õ!5BÐ !8s6ÑKÁ

ÏQê <ã

ÏS*Ô -

ÏG!5B_Ð -

ÏÎGQÊ

Q¸	ÆÄ
-	-

ÏGÄê -

1.25 show ip mrf mfc

/ IPv4 4ÆÃÆE¥<Ä

show ip mrf mfc [*soure-address group-address*]

Ï-DAê

–D	ÆÄ
source-address	Ê
group-address	Ê

Ï5,Õ!5BÐ -

ÏQê (Mã

ÏS*Ô 3 ÞDFÊ,ÝÈ4TÎOÊÄ

ÊÃÆX mfc ><NMÄ

ÊÃÆ,X mfc ><NMÄ

ÏG!5B_Ð /Ê 20.0.1.30 ,X IPv4 ,XÝÆE¥<NM

```
5XLMLHVKRZSPUIPIF
0XOWLFDVW5RXWLQJDQG)RUZDUGLQJ&FKH7DEOH
```

```
5XLMLHVKRZSPURXWH
,30XOWLFDVW5RXWLQJ7DEOH
)ODJV,,PPHGLDWH6WDW77LPHG6WDW))RUDUGHULQVWDOOHG
7LPHUV8SWLPH6WDW([SLU\
,QWHUIDFH6WDWH,QWHUIDFH77/
XSWLPHVWDWH[SLUHV
2ZHU3,060)ODJV7)
,QFRPLQJLQWHUIDFH)DVW(WKHUQHW
2XWJRLQJLQWHUIDFHOLVW
)DVW(WKHUQHW
```

_ 2ÖX/_/(Mn,XCÃ><NMµ

```
5XLMLHVKRZSPURXWH
,30XOWLFDVW5RXWLQJ7DEOH
)ODJV,,PPHGLDWH6WDW77LPHG6WDW))RUDUGHULQVWDOOHG
7LPHUV8SWLPH6WDW([SLU\
,QWHUIDFH6WDWH,QWHUIDFH77/
XSWLPHVWDWH[SLUHV
2ZHU3,060)ODJV7)
,QFRPLQJLQWHUIDFH)DVW(WKHUQHW
2XWJRLQJLQWHUIDFHOLVW
)DVW(WKHUQHW
```

_ 3ÖX/_/CÃ><AuDµ

```
5XLMLHVKRZSPURXWHFRXQW
,30XOWLFDVW6WDWLVWLFV
7RWDOURXWHVXVLQJEWHVPHRU\
5RXWHOPLW5RXWHWKUHVKOG
7RWDO12&(:521*9,):+2/(3.7UHFYIURPIZG
7RWDO12&(:521*9,):+2/(3.7VHQWWRFOLHQWV
,PPHGLDWH7LPHGVWDWXSGDWHVVHQWWRFOLHQWV
5HJ&UHFY5HJ1&UHFY5HJSNWVHQW
1H[WVWDWVSOO
)RUDUGLQJ&RXQWV3NWFRXQWW:HFRXQW2WKHU&RXQWV:URQJ,SNWV
)ZPVJFRXQWV:521*9,):+2/(3.7UHFY
&OLHQWPVJFRXQWV:521*9,):+2/(3.7,PP6WDW7LPHG6WDWVHQW
5HJSNWFRXQWV5HJ&UHFY5HJ1&UHFY5HJSNWVHQW
)RUDUGLQJ2WKHU
```

_ 4ÖX/_/CÃ><NM,X,ºµ

```
5XLMLHVKRZSPURXWHVXPPDU\
,30XOWL¥URXGLQJ0RW&\
```

7LPHUV8SWLPH6WDW([SLU\
,QWHUIDFH6WDWH,QWHUIDFH77/
3,060)ODJV7

+!‰	Aê
Flags	I-0Ÿ34Au T-nÊAu F-4B5BE¥@<
Timers:Uptime/Stat Expiry	A¹><NMÊ6È
Interface State	y(Õ
Owner	A¹><NM,X25ÃC#A,
Incoming interface	NXôXy[Eg9yÈprL,XEg9yã 0[Ó»
Outgoing interface list	EgÎë<[0<,Xy>E@ •
Forwarding CountsÖkt count/Byte count,	E@uDÖ><NME@y[D/ +8VD

ÏÎGQÐ

Q¸	Ë.Ä
-	-

ËGÄâê -

1.28 show ip mvif

/4õ¥;XÎ.Ä

show ip mvif *interface-type interface-number*

Ï–DAâê

–D	Ë.Ä
interface-type *interface-number*	*ôÿ·*

ËÞ,Õ!5BÐ -

ËQÐê (Mã

ËÞ*Ðê -

ËG!5B_Ð / svi1 ,X4¥;XÎ.

```
5XLMLHVKRZSPYLIYODQ
,QWHUIDFH9LI2ZQHU77//RFDO5HPRWH8SWLPH
,G[0RGXOHHGUHVVHGUHVV
9/$3,00
```

ÏÎGQÐ

Q¸	Ë.Ä
-	-

ËGÄâê -

1.29 show ip rpf

/(Mnê,X RPF Î.Ä

show ip rpf *source-address*

Ï–DAâê

–D	Ë.Ä
source-address	*ôÐÄ*

ËÞ,Õ!5BÐ -

ËQÐê (Mã

Ï*Ð -

ÏG!5B_Ð /E’ 192.168.1.54 ,X RPF Ç

```
5XLMLHVKRZSUSI
53)LQIRUPDWLRQIRU
53)LQWHUIDFH9/$
53)QHLJKERU
53)URXWH
53)WSHXQLFDVWFRQQHFWHG
53)UHFXUVLRQFRXQW
RLQJGLVWDQFHSUHIHUUHGORRNXSVDFURVVWDEOHV
LVWDQFH
0HWULF53)LQIRUPDWLRQIRU
53)LQWHUIDFH9/$
53)QHLJKERU
53)URXWH
53)WSHXQLFDVWFRQQHFWHG
53)UHFXUVLRQFRXQW
RLQJGLVWDQFHSUHIHUUHGORRNXSVDFURVVWDEOHV
LVWDQFH
0HWULF
```

ÏÎGQÐ

Q¸	Ë.Ä
-	-

ÏGÄÐ -

1.30 show msf msc

/ IPv4 ²Ë¥®<Ä

show msf msc [*soure-address*] [*group-address*] [*vlan-id*]

Ï-DAÐ

–D	Ë.Ä
soure-address	Ð
group-address	Ð
vlan-id	*Ð VLAN IDÈÎ 4096 Ê ><ÐÃÄ

Ï¸Õ!5BÐ /¸Ý IPv4 ²Ë¥®<NM

ÏQÐ (Mã

2 IPv6

2.1 clear ipv6 mroute

ô8 IPv6 4ŒÆ@<NMÄ

clear ipv6 mroute { ***** | *v6group-address* [*v6source –address*] }

Ï–DA®

–D	Œ Ä
*	#Ù8 IPv6 4ŒÃ><¸ŸXEÆ@Ä
v6group-address	IPv6 4ŒÃ¸X

Ï*Ð -

Ï!5B_Ð ô8<F#CÃ><NM,X4Auµ
5XLMLHFOHDULSYPURXWHVWDWLVWLFV

ÏGQÞ

Q¸	E
show ipv6 mroute	/4CÃEÐ
clear ipv6 mroute	#Ù84CÃEÐ

ÏÄð -

2.3 debug ipv6 mrf6 event

ÐÊÈ IPv6 4CÃEXÐ»*Q¸X no 6KÁÊÄ
debug ipv6 mrf6 event
no debug ipv6 mrf6 event

Ï-Dð

–D	E
-	-

Ï,Ï!5BÐ ÁÊGKÁ

ÏÞð (Mã

Ï*Ð -

Ï!5B_Ð -

ÏGQÞ

Q¸					E
8	628.7	0.48	0.48	refBT0.194n12	efBT4(v

ï5,Õ!5BÐ AA©GKÁ

ÏQ¸Ð (Mã

ïS*Ð -

ïG!5B_Ð -

ÏÎGQ¸Ð

Q¸	ÆÄ
-	-

ïGÄÀÐ -

2.5 debug ipv6 mrf6 mfc

ÐA©ÊÈ IPv6 ¾ÇÃE¥<NM,XÞE/ÐS*¼Q¸X no 6ïGKÁA©Ä

debug ipv6 mrf6 mfc

no debug ipv6 mrf6 mfc

Ï-DAÀÐ

–D	ÆÄ
-	-

ï5,Õ!5BÐ AA©GKÁ

ÏQ¸Ð (Mã

ïS*Ð -

ïG!5B_Ð -

ÏÎGQ¸Ð

Q¸	ÆÄ
-	-

ïGÄÀÐ -

2.6 debug msf6 api

ÐA©ÊÈ IPv6 ¾ÆE¥ÐX api y>A*¼XÞE/ÐS*¼Q¸X **no 6ïGK**

ÊÄ

debug msf6 api

no debug msf6 api

Ï-DAÀÐ

–D	ÆÄ

Ï-DAèè

–D	ÆÄ
-	-

Ï5,Õ!5BÐ AA©GKÁ

ÏQÇÐ (Mã

ÏS*ÐÐ -

ÏG!5B_Ð -

ÏÎGQÇÐ

Q¸	ÆÄ
-	-

ÏGÄèè -

2.9 debug msf6 msc

ÐA©ÈÈ IPv6 ßÆ€<NM,XÇE½ßS*AQ¸X **no 66ÐÄ**

debug msf6 msc

no debug msf6 msc

Ï-DAèè

–D	ÆÄ
-	-

Ï5,Õ!5BÐ AA©GKÁ

ÏQÇÐ (Mã

ÏS*ÐÐ -

ÏG!5B_Ð -

ÏÎGQÇÐ

Q¸	ÆÄ
-	-

ÏGÄèè -

2.10 debug msf6 ssp

ÐA©ÈÈ IPv6 ¹ÆÐ@ÐÐÉßS*AQ¸X **no 66ÐÄ**

debug msf6 ssp

no debug msf6 ssp

Ï–DA¤ð

–D	Ë Ä
-	-

GÄ

debug nsm mcast6 fib-msg

no debug nsm mcast6 fib-msg

Ï-DAèè

–D	ÆÄ
-	-

Ï¸Õ!5BÐ AA©GKÁ

ÜQêÐ (Mã

Ü*ÐÐ -

Ü!5B_Ð -

ÏÎGQÐ

Q¸	ÆÄ
-	-

ÜÄèè -

2.13 debug nsm mcast6 register

ÐA©È IPv6 4Cbyy¸XÐ/Ü*¸Q¸X no 6ÜKÁ×

A©Ä

debug nsm mcast6 register

no debug nsm mcast6 register

Ï-DAèè

–D	ÆÄ
-	-

Ï¸Õ!5BÐ AA©GKÁ

ÜQêÐ (Mã

Ü*ÐÐ -

Ü!5B_Ð -

ÏÎGQÐ

Q¸	ÆÄ
-	-

ÜÄèè -

2.14 debug nsm mcast6 stats

ÛÂÊÈ IPv6 4ÊÈby><)#Au¢,XÛÉ½Ë*ÂQ¸X no 6ÈKÁ×
AÊÄ

debug nsm mcast6 stats

no debug nsm mcast6 stats

Ï-DAÈ	–D	ÆÄ
	-	-

Ï,Õ!5BÐ AÂÊGKÁ

ÏQÈ (Mã

Ï*Ê -

Ï!5B_Ð -

ÏÊGQÈ	Q¸	ÆÄ
	-	-

no 6ÈKÁÂÊÄ

ÏGÄê -

2.16 ipv6 mroute

G!5BIPv6 4¥M-ÕÃÄS*ÄQ¸X **no 6ê8G5Þ** IPv6 4¥M-ÕÃÄ

ipv6 mroute *ipv6-prefix/prefix-length* [*protocol*] { *v6rpf-addrress* | *interface-type interface-number* } [*distance*]

no ipv6 mroute *ipv6-prefix/prefix-length* [*protocol*]

Ï-DAê

–D	EÄ
ipv6-prefix/	4ê,X IPv6
prefix-length	4ê,X IPv6 ,X}-Õ
protocol	!!7G*¡X)€Ã#A,
v6rpf-address	RPF FÄê,XÔÇX IPv6
interface-type *interface-number*	RPF yÄê,XÿÅ
distance	Äê 0-255È,Õ 0Ä

ï,Õ!5BÐ ´ IPv6 4¥M-ÕÃ

ÜÇê <ã

Ï*ÐÜ IPv6 4¥M-ÕÃõ™ RPF Ä

Vp‰Ù IPv6 M-ÕCÃ,Xÿ5M2ÔÇ IP ÈwAÿ¥NOÉO_Ä

Ï!5B_Ð G!5BÔ IPv6 M-ÕCÃ233 Ö4 EÈ› 33330333 EÄ

5XLMLHFRQILJLSYPURXWHÖ

ÏÎGQÐ

Q¸	EÄ
-	-

ÏGÄê -

2.17 ipv6 multicast boundary

A5B(Mn IPv6 48ê X IPv6 4E← Ä*ÄQ¸X **no 6ê8G5Þ** IPv6 4E← Ä

ipv6 multicast boundary *acc¯6ê-list-name*[**in** | **out**]

no ipv6 multicast boundary *access-list-name* [**in** | **out**]

Ï-DAê

–D	EÄ
access-list-name	éü ACL 9Lê48È
in	Ä
out	Ä

ï5,Õ!5BÐ ÞG!5B IPv6 4Ë←

ÏQÞÐ yã

Ï*ÐÔ !8Q¢¸X ACL ßX ACLÐÞÃ ACLÔ¸X ACLÐ¿!¸ÂXÈ
6!ßÄ
AÇQÞÃ¹ IPv6 48ÐG¸X MLD ÃIM-SMv6 #Ay[E> EÞDB#Â4˜
E← y#9#Ä

ÏG!5B_Ð A5B svi1 Ý IPv6 4Ã4¸XE← Ä

```
5XLMLHFRQILJLSYDFFHVVOLVWPXOERXQ
5XLMLHFRQILJVWGQDFOSHUPLWLSY
5XLMLHFRQILJVWGQDFOH[LW
5XLMLHFRQILJLQWHUIDFHYODQ
5XLMLHFRQILJLILSYPXOWLFDVWERXQGDUPXOERXQ
```

ÏÎGQÞÐ

Q¸	Ë¸Ä
-	-

ïGÄÐÐ -

2.18 ipv6 multicast route-limit

L6ÑÑ IPv6 4ÏCÃ><,X5,ÐGÐ*Ä¸Q¸X **no 6ÐÑÞGË$**
5Þ
ipv6 multicast route-limit *limit* [*threshold*]
no ipv6 multicast route-limit *limit* [*threshold*]

Ï-DAÐÐ

–D	Ë¸Ä
limit	*6ÐÑ* IPv6 4ÏCÃ¸XDGÐÐ 1~2147483647Ã¸Õ 1024Ä
threshold	' IPv6 4˜CÃ¸D,Ë'ÔA¹KÇ*Ð:/#\CÐ¸Õ 2147483647Ä

ï5,Õ!5BÐ –D5,Õ

ÏQÞÐ <ã

Ï*ÐÔ ¿ÔÐ,XLÐÈYE›Ð<NM,XCÃNMN¹O+ECÊÐÐÑÄ

ïG!5B_Ð L6ÑÑ IPv6 4ÏCÃ><,X5,ÐG£ 100Ð:/ 90Ä

```
5XLMLHFRQILJLSYPXOWLFDVWURXWHOLPLW
```

ÏÎGQÞ

Q¸	Ë.Ä
-	-

ÜGÄß

-

2.19 ipv6 multicast-routing

| IPv6 4ŒÃs6Ñ*ÄQ¸X **no 6ßK** IPv6 4ŒÃs6Ñ

ipv6 multicast-routing

no ipv6 multicast-routing

Ï–DAß

–D	Ë.Ä
-	-

ß¸Õ!5BÐ IPv6 4ŒÃs6ÑKÁ

ÜQß

-

ÜS*Ô NWO| IPv6 4ŒÃs6ÑÑ|Ø IPv6 4#AÄ

IPv6 4ŒÃs6Ñ MLD snooping s6ñy¸XÄ

ÜG!5B_Ð

-

ÏÎGQÞ

Q¸	Ë.Ä
-	-

ÜGÄß

-

2.20 ipv6 multicast rpf longest-match

ÞSG!sEÝ½ RPF CÃS*ÄQ¸X **no Ñ6ßÕ5Ë**

ipv6 multicast rpf longest-match

no ipv6 multicast rpf longest-match

Ï–DAß

–D	Ë.Ä
-	-

ß¸Õ!5BÐ E½{Ô¸XCÃ0 RPF CÃÄ

Vpì4{¸ß IPv6 4M-ÕÃÃPv6 MBGP CÃÃPv6)ŒÃ¸XNNcE> E½

ÜQß

<ã

ÜS*Ô EÝ½ RPF CÃ¸X!9PxÖ

¢ IPv6 4ŧM-ÕÃ><Ã IPv6 MBGP CÃ><Ã IPv6)€Ã><ÐÕÃü RPF ¦¸XÔ
CÃÄ
Ð£5CÃEÐ¢Ô RPF CÃÄ
VpG!5BÐSG!sÐ¢ÃQÐ£5CÃEÐSG!,XFw5CÃŸpE5
CÃ¸X}-Ð5Ð¼{Ô¸XFw5CÃŸpW¸Xì{3,Ð£ IPv6 4ŧM-Õ
CÃÑPv6 MBGP CÃÑPv6)€Ã¸XNNcE> E¥½
VpüG!5BÐSG!E¢ÃÐ£5CÃEÐ{Ô¸XFw5CÃŸpW¸Xì
4{¸Ð£ IPv6 4ŧM-ÕÃÑPv6 MBGP CÃÑPv6)€Ã¸XNNcE> E¥½

Ü¨G!5B_Ð -

ÏÎGQÐ

Q¸	Ð£Ä
-	-

Ü¨GÄÐ¢ -

2.21 ipv6 multicast static

AÐQ¸*9G!5B4ŧ##ÐÄÐQ¸X no 6ÐÃG!5BÄ

ipv6 multicast static *source-address group-address interface-type interface-number*

no ipv6 multicast static *source-address group-address interface-type interface-number*

Ï-DA¢Ð

–D	Ð£Ä
source -address	**4Ð¢Ä**
group-address	**44Ä**
interface-type	

ÏGÄð -

2.22 show ipv6 mroute

AÐQ¸*0¸ß IPv6 4ÐE¥@<ÇÄ

show ipv6 mroute [*group-or-source-address* [*group-or-source-address*]] [**dense** | **sparse**] [**summary** | **count**]

Ï-DAð

–D	ÐÄ
group-or-source-address	*ð*
group-or-source-address	*ðð*
dense	/ PIM-DMv6 4ã><NMÄ
sparse	/ PIM-SMv6 4ã><NMÄ
summary	*/* IPv6 4ÐÃ><NM,X,ØÇÄ

)RUDUGLQJRXQWV3NWFRXQWWHFRXQW2WKHURXQWV:URDUGEpbP @Pp PnjxRUPpsRPPUR pPPpWV5 08DÀ

2.24 show ipv6 mvif

/ IPv6 4ÿ¡XŒÄ

53)WSHXQLFDVWFRQQHFWHG

53)UHFXUVUDAPRX6WHG

3 IGMP

3.1 clear ip igmp group

#Ù8 IGMP 4ç¸X|ÇÕÃ¸Ä

clear ip igmp group [*group-address* [*interface-type interface-number*]]

Ï-DAèð

–D	Ë.Ä
group-address	*7*
interface-type *interface-number*	*yéÄ*

Ï5,Õ!5BÐ -

ÏQþÐ (Mã

Ï5*ÔÐ IGMP 4çÞ<Ãè<,XY¤,È5%Ú9¾4ÄÃpAÔt9þ
4ÈÄ43Ï5+ÉÞþ<Ä
S*éD,X **clear ip igmp group** ÞÇ IGMP 4ç#Ù8|ÇÕÃ¸Ä

Ï5B_Ð #Ù8<F½¾|ÇÕÃ¸Ö

```
5XLMLHFOHDULSLJPSJURXS
```

ÏÎGQÞÐ

Q¸	Ë.Ä
show ip igmp groups	/¼ÇÃ¸
show ip igmp interface	/ÿÞ0¸Ã¾4ÇÃ¸

ÏGÄèð -

3.2 clear ip igmp interface

#Ù8yÞXÝ IGMP 4ÃuÇ¼4ÇÃ¸

clear ip igmp interface *interface-type interface-number*

Ï-DAèð

–D	Ë.Ä
interface-type *interface-number*	yéÄ

Ï5,Õ!5BÐ -

ÏQþÐ (Mã

Ï*Ð AQ¸9#Ù8yý IGMP :4,X4Ù¸yÞXÔy[4ªAuÙËoy[4ªAuÙÙ
ÿ,X report y[ÐÙÈeave y[ÐÙÈyÞX4ãA),XAuDÙÄ

ÏG!5B_Ð #Ù8y· E0/1 ÞX IGMP Ù
5XLMLHFOHDULSLJPSLQWHUIDFHHWK

ÏÎGQÞ

Q¸	ËÄ
-	-

ÏGÄÐ -

3.3 ip igmp access-group

ÿÙÐÄÙË,X4ÐÏ*Ù8Q¸X **no 6ÐÏs6Ñ**
ip igmp access-group *access-list*
no ip igmp access-group

Ï-DAÐ

–D	ËÄ
access-list	ëü ACL n48È

Ï5,Õ!5BÐ AÙ9Ï4˜

ÏQÞ yã

Ï*Ð EÊÿÙ!5B!8QÞÈ5‰,X6Ñ9,X4ÐÏü ACL LÞ48ÐÏpy
>• ACL deny ,X report y[ÐÏy[Ä
tü IGMPv3 ÐÏBQÞÕ ACLÿÄ,X IGMP report ÙÐS1,S2,S3…Sn,G ÐÏÄ
Q¸(0,G) ÙS*ì¸h,X ACL E> G!ÐÏ!7S*ÄAQÞÈÏOÉ= ACL 6!5B
6(0, G) È!Ñ,XÐS1,S2,S3…Sn,G Ð> EÞÄ

ÏG!5B_Ð _ 1ÐÿÙ· Eth0/1 ÐÑ9˜ 225.2.2.2.
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJDFFHVVOLVWSHUPLW
5XLMLHFRQILJLQWHUIDFHHWKHUQHW
5XLMLHFRQILJLILSLJPSDFFHVVJURXS

_ 2ÿØ Eth0/1 G!5B4{ë<G6()= ACLÿÙÐÑ 1.1.1.1È˜ 233.3.3.3
,X igmp #Aÿ[Ä
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJLSDFFHVVOLVWH[WHQGHGH[WBDFO
5XLMLHFRQILJH[WQDFOSHUPLWLSKRVWKRVW
5XLMLHFRQILJLQWHUIDFHHWKHUQHW
5XLMLHFRQILJLILSLJPSDFFHVVJURXSH[WBDFO

ÏÎGQÞ	Q¸	Ë£Ä
	-	-

ËGÄà¤ -

3.4 ip igmp immediate-leave group-list

ÿ!Ë¢Ê£ÚÊÑ*ÄQ¸X **no 6ÊÉs6Ñ**

ip igmp immediate-leave group-list *access-list*

no ip igmp immediate-leave

Ï–DAà¤	–D	Ë£Ä
	access-list	é¨ ACL n48È

Ï¸Ê!5BÐ GKÉÊ6Ñ

ËQÞ¤ yã

ËS*Ð AÊQÞ¸Ë¤Ê¤ IGMPv2 ê v3è¤Ê¤ÿ¸ÞÊX¤Ä¼

VpÊ!5BAÊQÞÿy/ÿ¸Þ¤Mn47Ä¥[ÈYhÉÊYÊã

,A)Ê8!8yÉÊYÊÈb(Mn47Ä¥[Èhâ IGMP 9ÊÐ,X,/Ê£Ä¼ 2sÄ

VpÊ!5BÄÊQÞÊÊ8È,X4ÈÿyÿÞ¤Ê(Mn47Ä¥[Èà¸

4ãA)Ê8!8yX!8¤Ð

ËÊ!5B_Ð Ê!5BÞÞÊ6Ñ

Ï-DAèð	–D	Ë Ä
	group-address	4˜

Ï5,Õ!5BÐ yþ9ïþÔÄ

ÏQþð yã

Ï5*ôð G!5B!8Qýèé âèQÃ4¸˜X join y[Ä
!8Q¸*ïrP#AÆ

Ï!5B_Ð ý Eth0/1 t94˜ 233.3.3.3Ä
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJLQWHUIDFHHWKHUQHW

ï‚,Õ!5BÐ –D5,Õ

ÜQÞ <ßãã

Ï*ô IGMP 4ãA),XDGÆÄ
IGMP 4ãA),XDGÆÄ
Vp4ãA),CYÎÇè,XLÆBê,X report y[ÐÑ9Ä
except _ê<ÆÇ)ûÔ8Æ,X,X report y[Ì36ãX4ãA),á
ÆuDÄ
y<ßÔÜG!5BÜp<G!5B,XÞDLÆyÆG!5BÆÄ

G!5B_Ð L$ IGMP 4ãA), 400ÿÞ E0/1 ,X4ãA), 300ÐÇ‡ acl1 ,X4Ì8Æ
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJLSLJPSOLPLWH[FHSWDFO
5XLMLHFRQILJLQWHUIDFHHWK
5XLMLHFRQILJLILSLJPSOLPLWH[FHSWDFO

ÏÎGQÞ

Q¸	Æ‚Ä
-	-

ÜGÄÆÐ -

3.9 ip igmp mroute-proxy

ÿ¡P mroute-proxy s6ÆÑ*ü **no 6ÆÑ6ÆÑ**
ip igmp mroute-proxy *interface-type interface-number*
no ip igmp mroute-proxy

Ï-DAÆÐ

–D	Æ‚Ä
interface-type *interface-number*	yÆÐ(Å

ï‚,Õ!5BÐ þ18s6ÆÑ

ÜQÞ yG!5Bã

Ï*ô S*ü **ip igmp proxy-service ÆÐ¶B** proxy-service yÄ
S*ü **ip igmp mroute-proxy ÆÐ¶B** mroute-proxy yÄ
+ proxy-service yå mroute-proxy yE¥@ IGMP Ä¥Ÿ[Ä mroute-proxy yå proxy-service yE¥@ IGMP report y[Ä

G!5B_Ð ü E0/1 Þ proxy-service s6ÆÑ E0/2 Þ mroute-proxy s6ÆÑ
5XLMLHFRQILJLQWHUIDFHHWK

```
5XLMLHFRQILJLILSLJPSSUR[VHUYLFH
5XLMLHFRQILJLILQWHUIDFHHWK
5XLMLHFRQILJLILSLJPSPURXWHSUR[HWK
```

ÏĈGQÞ	Q¸	ÆÄ
	ip igmp proxy-service	ÿÞ proxy-service s6Ñ

ĬGÄß -

3.10 ip igmp proxy-service

ÿÞ proxy-service s6Ñ*ü **no 6ß6Ñ**
ip igmp proxy-service
no ip igmp proxy-service

Ï-DAß	–D	ÆÄ
	-	-

Ĭ,Õ!5BÐ -

ĬQß yG!5Bä

Ĭ*Ð S*ü **ip igmp proxy-service** S*ü proxy-service yÄ
S*ü **ip igmp mroute-proxy** S*ü mroute-proxy yÄ
+ proxy-service yå mroute-proxy yE¥© ÁÝ[Ä mroute-proxy yå proxy-service yE¥© y[Ä
AÐG!5B 32þ proxy-service yÄ ' proxy-service yy ÁÝ[Ä
4ãÁ¸0ĥ1(Ä
ÿ6AÐpí proxy-service y¸ Z **switchport** mroute-proxy yÐ!5B,X
mp mroute-proxy 8Ä

0/1 Þ proxy-service s6Ñ E0/2 Þ mroute-proxy s6Ñ

```
5XLMLHFRQILJLQWHUIDFHHWK
5XLMLHFRQILJLILSLJPSSUR[VHUYLFH
5XLMLHFRQILJLILQWHUIDFHHWK
5XLMLHFRQILJLILSLJPSPURXWHSUR[HWK
```

ÏĈGQÞ	Q¸	ÆÄ
	ip igmp mroute-proxy	ÿÞ mroute-proxy s6Ñ

ĬGÄß -

3.11 ip igmp query-interval

G!5BBEâA¶KÈhÄ8Q¸X **no 66ßÕ**

ip igmp query-interval *seconds*

no ip igmp query-interval

Ï-DAß	–D	Ë-Ä					
	seconds	BEâA¶KÈhÄ	sßÈ	118000	È¸Õ	125	

È¸Õ!5BÐ –D5,Õ

ÜQß yG!5Bã

Ü*Ð -

Ü!5B_Ð ÿ·

ÏGÄê -

3.13 ip igmp query-timeout

G!5BJWA¶¦Ù#ÊÊ8Q¸X **no 6ê¶Ð**

ip igmp query-timeout *seconds*

no ip igmp query-timeout

Ï-DAê

–D	Ë.Ä
seconds	JWA¶¦Ù#Ê¦È sêÈ 60 300È¸Õ 255

Ï5,Õ!5BÐ –D5,Õ

ÏQê yG!5Bã

Ï*Ð yÀ¶[ÈYJ²À¶X¶[ÏpCYÊx,È5%¾7Ê
À¶¦Ù

2

ÏG!5B_Ð ÿ· Ethernet 0/1 Ï!5BJWA¶¦Ù#ÊÈ 200sÄ

```
5XLMLHFRQILJLQWHUIDFHHWKHUQHW
5XLMLHFRQILJLILSLJPSTXHUWLPHRXW
```

ÏÏGQÐ

Q¸	Ë.Ä
-	-

ÏGÄê -

3.14 ip igmp robustness-variable

A5BA¶¦Ù2ÏDÄ8Q¸X **no 6ê¶Ð**

ip igmp robustness-variable *number*

no ip igmp robustness-variable

Ï-DAê

–D	Ë.Ä
number	92ÏDêÈ 2-7È¸Õ 2

Ï5,Õ!5BÐ –D5,Õ

ÏQê yG!5Bã

Ï*Ð -

ÏG!5B_Ð A5B9ÂÏD 3

```
5XLMLHFRQILJLQWHUIDFHHWKHUQHW
5XLMLHFRQILJLILSLJPSUREXVWQHVVYDULDEOH
```

ÏÎGQÐ

Q¸	Ë Ä
-	-

ÏGÄð -

3.15 ip igmp ssm-map enable

| ssm-map s6Ñ8Q¸X **no 6ðÉs6Ñ**

ip igmp ssm-map enable

no ip igmp ssm-map enable

Ï-DAð

–D	Ë Ä
-	-

Ï¸Õ!5BÐ GKÁs6Ñ

ÏQð <G!5Bã

Ï*Ð S*ü **ip igmp ssm-map enable** Ò ssm-map s6Ñ

S*ü **ip igmp ssm-map static** ÐÑ-õÄ

yE¤ IGMPv3Ä X IGMPv1 ê IGMPv2 ,X report y[ËM-ØXÏÄ

ÏG!5B_Ð *ü ssm-map s6ÑCL11 ,X4Ø 192.168.2.2Ä

```
5XLMLHFRQILJLSLJPSVVPPDSHQDEOH
5XLMLHFRQILJLSLJPSVVPPDSVWDWLF
```

ÏÎGQÐ

Q¸	Ë Ä
ip igmp ssm-map static	**G5ÐÑ-õ**

ÏGÄð -

3.16 ip igmp ssm-map static

G!5BM-õ<NMÄÏ8Q¸X **no 6ð88ÑÄ**

ip igmp ssm-map static *access-list source-address*

no ip igmp ssm-map static *access-list source-address*

Ï–DAèð

–D	Ë.Ä
access-list	+ ACL A5B,X48È
source-address	ß

Ï5,Õ!5BÐ M-ßØ<NM

ÏQÇð <G!5Bã

Ï5*Øß S*ü **ip igmp ssm-map enable** È¢ ssm-map s6Ñ

S*ü **ip igmp ssm-map static** ÇÈ-ßÄ

yE¤ IGMPv3ÆX IGMPv1 ê IGMPv2 ,X report y[ËM-ßX

Ï!5B_Ð *ü IGMP ssm-map s6Ñ ACL11 ,X4ßØ 192.168.2.2Ä

5XLMLHFRQILJLSLJPSVVPPDSHQDEOH

5XLMLHFRQILJLSLJPSVVPPDSVWDWLF

ÎÏGQÇÐ

Q¸	Ë.Ä
ip igmp ssm-map enable	| IGMP ssm-map s6Ñ

ÏGÄèð -

3.17 ip igmp static-group

yM-ßÕ94ÆÜ8Q¸X **no 6èG5Ë**

ip igmp static-group *group-address*

no ip igmp static-group *group-address*

Ï–DAèð

–D	Ë.Ä
group-address	4˜

Ï5,Õ!5BÐ yÞM-ßÕ)4Ä

ÏQÇð yã

Ï5*Øß AÐQSyáÔE> IGMP y[xfGÕ94ÆÝ¸È5%ßA4È

A4¸˜X4ãA¸FßyÄ

ÏĈGQÞ	Q¸	ÐĿÄ
	ip igmp join-group	**yt9ϕ˜**

ĬGÄȀ -

3.18 ip igmp version

A5ByÐ▫ ,X IGMP (Ä¼8Q¸X **no 6ȀȀÞ**

ip igmp version { **1** | **2** | **3** }

no ip igmp version

Ï-DAȀ	–D	ÐĿÄ
	1	IGMPv1
	2	IGMPv2
	3	IGMPv3

Ĭ5,Õ!5BÐ IGMPv2

ĬQȀ yG!5BȀ

Ĭ5*Ð G!5B!8QȀGMP 7ÞĬ¿Ä

ĬG!5B_Ð y· E0/1 E▫ IGMPv3Ö

```
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJLQWHUIDFHHWKHUQHW
5XLMLHFRQILJLILSLJPSYHUVLRQ
```

ÏĈGQÞ	Q¸	ÐĿÄ
	-	-

ĬGÄȀ -

3.19 show ip igmp groups

/ÀÏÞ¸È²X4¢ IGMP :4,X4ĮÄ

show ip igmp groups [*interface-type interface-number*] [*group-address*] [**detail**]

Ï-DAȀ	–D	ÐĿÄ
	group-address	*7*
	interface-type *interface-number*	*yȀÄ*
	detail	**Ä¢**

ï5,Õ!5BÐ -

ÏQþÐ (Mã

ï5*ôÐ Vpþ–DÆÃÕ2O_ùÈ²X¼4ÇÄ
Vpá7(Mn4˜XÇÄ

Ï!5B_Ð _ 1ÇÕX4ÇÇ

```
5XLMLHVKRWZSLJPSJURXSV
,*03RQQHFWHG*URXS0HPEHUVKLS
*URXSGGUHVV,QWHUIDFH8SWLPH([SLUHV/DVW5HSRUWHU
HWK
HWK
HWK
HWK
HWK
HWK
```

_ 2ÇÕMn4˜XA4ÇÇ

```
5XLMLHVKRWZSLJPSJURXSVGHWDLO
,QWHUIDFHHWK
*URXS
8SWLPH
*URXSPRGH,QFOXGH
/DVWUHSRUWHU
7,0XQW
7,0XQW
*URXSVRXUFHOLVW55HPRWH06600DSSLQJ
6RXUFHGGUHVV8SWLPHY([S)ZG)ODJV
<HV5
<HV5
```

ÎÏGQÞÐ

Q¸	Ë.Ä
-	-

ïGÄÃÐ -

3.20 show ip igmp interface

¹Q¼X IGMP G!5BÇÇ

show ip igmp interface [*interface-type interface-number*] [**detail**]

ï–DAÃÐ

–D	Ë.Ä
interface-type	*yáÄ*

interface-number	
detail	**Aş**

Ъ¸Õ!5BÐ -

ÜQþ (Mã

Ъ*Ð VpáDßÝÇÄ

Ü!5B_Ð ¦ý¸X IGMP G!5BÇÖ

5XLMLHVKRWSLJPSLQWHUIDFH

[redacted]

,*0ãXXHUCLQQVHUBPHãVVHFRQGV

,*0ÕTXHUHLHSQ@Q_QÀ6Ñ

Ğ!5B_Đ /4˜ 233.3.3.3 ,X ssm-map ₾

```
5XLMLHVKRŻSLJPSVVPPDSSLQJ
*URXSDGGUHVV
DWDEDVH6WDWLF
6RXUFHOLVW
```

ÏĞGQĘĐ

Q¸	Ł£Ä
-	-

ĞÄđ -

4 MLD

4.1 clear ipv6 mld group

#Ù8 MLD 4ç¸X|ÐÕÃA¸Ä

clear ipv6 mld group [*group-address*] [*interface-type interface-number*]

Ï-DAèê

–D	Ë.Ä
group-address	7
interface-type *interface-number*	6ÿ·

ï5,Õ!5BÐ -

ÏQ¸Þ (Mã

ïS*ÐÎ MLD 4çÞ<Èè<,XY¤J,È5%xÍ2¾4-ÝpAÔ3t9
µÈ43Ï5+ÉÞ<Ä
S*éD,X **clear ipv6 mld group** ÕÞ MLD 4ç#Ù8|ÐÕÃA¸Ä

ïG!5B_Ð _ 1Ð8<F|ÐÕÃA¸

```
5XLMLHFOHDULSYPOGJURXS
```

_ 2Ð86Ô4ãA¸

```
5XLMLHFOHDULSYPOGJURXSIIH
```

_ 3Ð8ÇÙMny¡X4ãA¸

```
5XLMLHFOHDULSYPOGJURXSIIHLQWHUIDID
```

ÏÎGQÞ

Q¸	Ë.Ä
show ipv6 mld groups	/Ý4ãA¸
show ipv6 mld interface	/ÙÐ0¸Ã¾X4ãA¸

ïGÄè -

4.2 clear ipv6 mld interface

#Ù8yÞXÝ MLD 4ªAuÇ¿4ãA¸

clear ipv6 mld interface *interface-type interface-number*

Ï-DAèê

–D	Ë.Ä

interface-type *interface-number*	*yéÄ*

ï5,Õ!5BÐ -

ÏQ¸Ð (Mã

Ï*ÐÔ AŒQ¸0#Ù8y½ MLD :4,X4Œ¸ÿÞXÔy[4²AuÐŒÆoy[4²AuÐ¸Ù
y,X report y[ÐÐ¸Èone y[ÐÐ¸ÿÞX4ãA¸AuDÐ¸Ä

Ï!5B_Ð #Ù8y· E0/1 ÞX MLD Ð¸
5XLMLHFOHDULSYPOGLQWHUIDFHHWKHUQHW

ÏÎGQÐ

Q¸	Æ Ä
-	-

ÏÄÀê -

4.3 ipv6 mld access-group

ÿÆÆ4ŒÆ,X4ÐQ¸#Ï **no ê s6Ñ**
ipv6 mld access-group *access-list*
no ipv6 mld access-group

Ï–DAê

–D	Æ Ä
access-list	*éü* ACL n48²È

ï5,Õ!5BÐ AŒ9)4˜

ÏQÐ yã

Ï*ÐÔ EÆÿÏ!5B!8QÐÈ5‰,X6Ñ),X4Ê ACL L¸48²Ê py
>• ACL deny ,X report y[Ê y
tü MLDv2 !ÊQÐ ACL ê Æ!BE$ MLDv2 y[,X ¸A¸Ð¸X MLD
report Ð¸Ê1,S2,S3…Sn,G Ê QÍ0,G) Ð¸S*ì,X ACL E> G!Ê!7
S*ÆQÐ¥OÍ ACL ê 5BÔ(0, G) È!Ñ,XÊ1,S2,S3…Sn,G Ê> E›
Ð

Ï!5B_Ð ÿ· Eth0/1 Þ5B4Æ$
5XLMLHFRQILJLSYDFFHVVOLVWDFO
5XLMLHFRQILJLSYDFOSHUPLWLSYII
5XLMLHFRQILJLSYDFOSHUPLWLSYII
5XLMLHFRQILJLQWHUIDFHHWKHUQHW
5XLMLHFRQILJLILSYPOGDFFHVVJURXSDFO

ÏÎGQÞ

Q¸	Ë.Ä
-	-

ÏGÄâê -

4.4 ipv6 mld immediate-leave group-list

ytËÉ£ÚÊÑ*ÄQ¸X **no 6ÉÚÊs6Ñ**

ipv6 mld immediate-leave group-list *access-list*

no ipv6 mld immediate-leave group-list

Ï–DAâê

–D	Ë.Ä
access-list	éü ACL n48Ëè

ï¸,Õ!5BÐ GKÉÚÊ6Ñ

ÏQÞê yã

Ï5*Ðê !8s6ÑËÏbyÆ²ÞÔX‰

VpÏG!5BAÇQÞy MLD /ÿ[ÆMn4ÄÝ[ÈYhÄYÉ

4ãÄ¸ï8!8yÄYÉÈb(Mn4ÄÝ[È â MLD 9ÄÏD,X,/Ñ¸‰ 2sÄ

VpG!5BÄÇQÞï8È,X4Èÿ/ÿ[ÆÛÉ(Mn4ÄÝ[Èã

yï8,h4ÏX!8ÆÐ

ÏG!5B_Ð G!5BÉÚÊ6Ñ

```
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJLSYDFFHVVOLVWDFO
5XLMLHFRQILJLSYDFOSHUPLWLSYII
5XLMLHFRQILJLQWHUIDFHHWKHUQHW
5XLMLHFRQILJLILSYPOGLPPHGLDWHOHDYHJURXSOLVWDFO
```

ÏÎGQÞ

Q¸	Ë.Ä
-	-

ÏGÄâê -

4.5 ipv6 mld join-group

yt9ÿÄ*Ï8Q¸X **no 6Ë5Ë**

Ipv6 mld join-group *group-address*

no ipv6 mld join-group *group-address*

Ï-DAèð

–D	ÆÄ
group-address	4˜ áG5B¹ 0xFF*1Õ0xFF*2 Ø0xFF3* ÇXÄ

Ï5,Õ!5BÐ yþ9)þØÄ

ÏQþð yã

Ï5*Ûð G!5B!8Qþéý áèØÕÄ4,˜X join y[Ä
!8Q¸ürP#AÄ

ÏG!5B_Ð ýJ Eth0/1 t94˜ ff55::100Ö

```
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJLQWHUIDFHHWKHUQHW
5XLMLHFRQILJLILSYPOGMRLQJURXSII
```

ÏÎGQÞ

Q¸	ÆÄ
-	-

ÏGÄèð -

4.6 ipv6 mld last-member-query-count

ýJA5B(Mn4ÂÝ[,XÆÕÐÄ*ü **no Ç5ÕÐ**

ipv6 mld last-member-query-count *number*

no ipv6 mld last-member-query-count

Ï-DAèð

–D	ÆÄ
number	(Mn4ÂÝ[,XÆÕÐÄÈ 2-7È¸Õ 2

Ï5,Õ!5BÐ –D5,Õ

ÏQþð yG!5Bã

Ï5*Ûð ý· done yÈ4Á(Mn4ÂÝ[ÆLYÞÇYÄx,È5%áÆ
,ÍÄ¼˜ãÈ MLD 4˜ãA¸) Î8A¼ý·ÇYÆÈb last-member-query-interval â
last-member-query-count ,X,/ÃtÞ 1/2 ,X query-max-response-timeÄ

ÏG!5B_Ð A5B(Mn4ÂÝ[,XÆÕÐ 3.

```
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJLQWHUIDFHHWKHUQHW
5XLMLHFRQILJLILSYPOGODVWPHPEHUTXHUFRXQW
```

ÏÎGQÞ

Q¸	ÆÄ

ipv6 mld last-member-query-interval	**no ipv6 mld last-member-query-interval**

ÏGÄÐ -

4.7 ipv6 mld last-member-query-interval

ÿÄA5B(Mn4ÆÅ¶[,XÆÈÕÈhÄ*ÄÆQ¸X **no ipv6 mld last-member-query-interval**

ipv6 mld last-member-query-interval *interval*

no ipv6 mld last-member-query-interval

Ï-DAÐ

–D	ÆÄ
interval	(Mn4ÆÅ¶[,XÆÈÕÈhÄ 0.1sÐÈ 1-255È¸Õ 10Ä 1sÅ

Ï5,Õ!5BÐ –D5,Õ

ÏQÐ yG!5Bã

ÏS*ÐÐ ÿ· done yÐÈ4ÆÅ(ÕMn4ÆÅ¶[ÆÈ1YÞÄÄÅx,È5%ÆÆ

,ÄÅ4˜ãÆÈ MLD 4˜ãA¸) Ä8Aÿ·ÄÈYÞÐÆÈÆb last-member-query-interval â last-member-query-count ,X,/ÃÆÞ 1/2 ,X query-max-response-timeÄ

ÏG!5B_Ð A5B(Mn4ÆÅ¶[ÆÈÕÈh 2 /¦

```
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJLQWHUIFHID
5XLMLHFRQILJLILSYPOGODVWPHPEHUTXHU LQWHUYDO
```

ÏÎGQÐ

Q¸	ÆÄ
ipv6 mld last-member-query-count	**no ipv6 mld last-member-query-count**

ÏGÄÐ -

4.8 ipv6 mld limit

A5B MLD 4˜ãÄ¸,XÛÐGÄÐ*ü **no ipv6 mld limit**

ipv6 mld limit *number* [**except** *access-list*]

no ipv6 mld limit *number* [**except** *access-list*]

Ï-DAÐ

–D	ÆÄ
number	MLD 4˜ãÄ¸,XÛÐGÄÐÈ'ÄÛÐÿÄ5,Õ 1024È5,Õ 65536Ä
except *access-list*	Æccess-list ,X4˜ãÄuDÈÞL8ÐGÆÐÄ

Ï5,Õ!5BÐ –D5,Õ

ÜQþ <ßõã

Ü5*ûÜ <õõÜ MLD 4ãA„,XDGÆÄ

yõÜÜy¡X MLD 4ãA„,XDGÆÄ

Vp4ãA„CYÿÊ,XLÆBû„X report y[ÚÑ9Ä

VpG!5BZ except

5XLMLHFRQILJLILSYPOGPURXWHSUR[HWK

ÏĈGQÞ

Q¸	Ë.Ä
ipv6 mld proxy-service	ÿÞ proxy-service s6Ñ

ĞGÄß -

4.10 ipv6 mld proxy-service

ÿÞ proxy-service s6Ñ*ü **no 6ß6Ñ**
ipv6 mld proxy-service
no ipv6 mld proxy-service

Ï-DAß

–D	Ë.Ä
-	-

ß¸Õ!5BÐ -

ÖQß yG!5Bä

Ö*Ð S*ü **ipv6 mld proxy-service ß** proxy-service yÄ
S*ü **ipv6 mld mroute-proxy ß** mroute-proxy yÄ
+ proxy-service yå mroute-proxy yE@ MLD Ay[Ä mroute-proxy yå proxy-service yE@ MLD report y[Ä
AÊ!5B 32 þ proxy-service yÄ ' proxy-service yy MLD Ay[Ä MLD 4ãA¸0ĥ1(Ä
ÿ6AÊpÍ proxy-service y> Z **switchport** mroute-proxy yÐ!5B,X
ipv6 mld mroute-proxy 8Ä

Ğ!5B_Ð ü E0/1 Þ proxy-service s6Ñ E0/2 Þ mroute-proxy s6Ñ

```
5XLMLHFRQILJLQWHUIDFHHWK
5XLMLHFRQILJLILSYPOGSUR[VHUYLFH
5XLMLHFRQILJLILQWHUIDFHHWK
5XLMLHFRQILJLILSYPOGPURXWHSUR[HWK
```

ÏĈGQÞ

Q¸	Ë.Ä
ipv6 mld mroute-proxy	ÿÞ mroute-proxy s6Ñ

ĞGÄß -

4.11 ipv6 mld querier-timeout

G!5BJWA¶¸]#ËÄ8Q¸X **no 6ß**

ipv6 mld querier-timeout *seconds*

no ipv6 mld querier-timeout

Ï–DAêð

–D	Ë.Ä
seconds	JWÁ¶¦Ù#ÊÈ sêÈ 60 300È¸Õ 255

Ï¸Õ!5BÐ –D5,Õ

ÏQ¸ð yG!5Bã

Ï*ôð yÎÁ¶¦[ÈYJ³ÁÛXÁ¶¦[ÏpCYÊx,È5%¸¸ÐÁ
Á¶¦Ù
ÍÁ¸Ù5,ÕÊãÁ¶ÈhX 2 ÄÁ

ÏG!5B_Ð G!5BJÁ¶¦ÙuÊKÈh 200sÄ
5XLMLHFRQILJLILSYPOGTXHULHUWLPHRXW

ÏÎGQÐ

Q¸	Ë.Ä
-	-

ÏGQêð -

4.12 ipv6 mld query-interval

G!5BBEãÁ¶ÈhÄ8Q¸X **no 6ëëÕ**

ipv6 mld query-interval *seconds*

no ipv6 mld query-interval

Ï–Dixêð

–D	Ë.Ä
seconds	ÄÁ sêÈ 118000 È¸Õ 125

Ï¸Õ!5BÐ –D5,Õ

ÏQ¸ð yG!5Bã

Ï*ôð -

ÏG!5B_Ð ÿ· Ethernet 0 G!5BBEãÁ¶ÈhÄ 120sÄ
5XLMLHFRQILJLILSYPOGTXHULQWHUYDO

ÏÎGQÐ

Q¸	Ë.Ä
-	-

ÏGÄÐ -

4.13 ipv6 mld query-max-response-time

G!5BÐÎÊÈ8Q¸X **no 6ÈÈÐ**

ipv6 mld query-max-response-time *seconds*

no ipv6 mld query-max-response-time

Ï–DAÐ

–D	È–Ä					
seconds	ÎÊÐ	sÐÈ	125	È¸Õ	10	

È¸Õ!5BÐ –D5¸Õ

ÏQÐ yG!5Bã

È*Ð yÐ[ÈYhÄYÊx,È5%á3È84ÎÄ

ÏG!5B_Ð ÿ· Ethernet 0 G!5BÎKÈh 20sÄ

5XLMLHFRQILJLILSYPOGTXHUPD[UHVSRQVHWLPH

ÎÏGQÐ

ÏĈGQÞ	Q¸	Ł:Ä
	-	-

ĬGÄß | -

4.15 ipv6 mld ssm-map enable

| ssm-map s6ÑßQ¸X **no 6ßÁs6Ñ**

ipv6 mld ssm-map enable

no ipv6 mld ssm-map enable

Ï–DAß	–D	Ł:Ä
	-	-

ï5,Ø!5BÐ | GKÁßs6Ñ

ÜQß | <G!5Bã

Ï*ð | S*ü **ipv6 mld ssm-map enable** Þ ssm-map s6Ñ

S*ü **ipv6 mld ssm-map static** ÞÑ-ñÄ

yE¤ MLDv2ÄX MLDv1 ,X report y[ËtM-ØX6y#TÕDAßÐe-45.3 4 8 1 5 9 4 (5) 5 0 V C 2 . g C 2 T 0 2 4 1 5 2 9 1 0 7 3 9 c T (A < 1 9 7 9 0

ÜQþ <G!5Bã

Ü*Ô S*ü **ipv6 mld ssm-map enable** Ò ssm-map s6Ñ

S*ü **ipv6 mld ssm-map static** ¸ÇÄ-ÕÄ

yE¤ MLDv2¸X MLDv1 ,X report y[ÊïM-ØX6Ä

ÜG!5B_Đ

4.18 ipv6 mld version

A5ByÐ¤ ,X MLD (Ä8Q¸X **no 6**

ipv6 mld version {**1** | **2** }

no ipv6 mld version

Ï-DAð

–D	Ð
1	MLDv1
2	MLDv2

Ï,Õ!5BÐ MLDv2

Ïðþ yG!5Bã

Ï*Ð G!5B!8QþMLD

Ï!5B_Ð y· E0/1 E¤ MLDv1Ö

```
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJLQWHUIDFHHWKHUQHW
5XLMLHFRQILJLILSYPOGYHUVLRQ
```

ÏÕQÞ

Q¸	Ð
-	-

Ïäð -

4.19 show ipv6 mld groups

/ÀÏÞÐ MLD :4,X4ÏÄ

show ipv6 mld groups [*group-address* | *interface-type interface-number*] [

Ï S*ü ™a´ Ð

Ġ!5B_Đ

5 PIM-DM

5.1 clear ip pim dense-mode track

please try again!Ëë ÃG!5BAQÄ
G!5BAQ¸XÊp}¸PIM-DM Configure failed! VIF limit exceeded in NSM!!! È</!4˜
yG!5B,XDG4E'AÕ!5B,X4ÿLÐXp¸LÔAyÔ PIM-DM h*È
AÊ8ÔÐ¸X PIM-DM ê PIM-SM ê DVMRP yÄ
ÂÃÐÔXÿG!5BàX v4 4ÇÃ#AÄ
Vpy2O_L{F2O_ÐÝ¼ 4Over4 G!5BL{FÃ 4Over4 GRE L{FÃ 4Over6 G!5BL{FÃ 4Over6
GRE L{FÕ IPv4 4šs6ÃWÐXL{FyÐÝ¼s6ÃAÄ
CÈÊ> 4ÿ[,XyÈÊÕ
4L{FÕÐL{FÈDB,X Qos/ACLÄ

ËG!5B_Ð
```
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJLQWHUIDFHIDVWHWKHUQHW
5XLMLHFRQILJLILSSLPGHQVHPRGH
```

ÏÎGQÐ

Q¸	ÉÄ
-	-

ËGÄÈ -

5.3 ip pim neighbor-filter

ÐÏÔXFÉÈŞÊ*ü **ip pim neighbor-filter** ÐÈ
ÐÊÉ PIM-DM ÈÍF¬ÔÏyÄeering Ô2ÈÈ6ÀFÆÐ¸X
FyG2ÄQ¸X no 6ÃU*ÉÉE$6Ñ
ip pim neighbor-filter *access-list*
no ip pim neighbor-filter *access-list*

Ï¬DAÈ

–D	ÉÄ
access-list	access-listÕ+ acl 8È 1-998ÕÁ acl

Ëˌ,Õ!5BÐ yÐÈÉE$6Ñ

ËQÈ yG!5Bã

ËS*Ô ÝÚ ACL EŞÐXF¬6ÑÙy¡X PIM FÈ• ACL EŞXFÚ
!y¡X PIM FÄ
AçXFyÐeeringÔ2ÐX PIM F¬ÈX#Ay[xfÝp!6ÐÈ PIM AÔXF•
yG2ÈÃ6È•G2ÈÑ97ÝAÔX PIM #Ay[Ä

ËG!5B_Ð
```
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJLQWHUIDFHIDVWHWKHUQHW
5XLMLHFRQILJLILSSLPQHLJKERUILOWHU
```

ÏÎGQÐ

Q¸	ÉÄ

-	-

ÏGÄà -

5.4 ip pim override-interval

ØGG¸G!5B hello #Ć,X override-interval ÀËË*ü **ip pim override-interval** ØØ no 6ã
ËÃ hello #Ć,X override-interval 6ãtAxÄ

ip pim override-interval *interval-milliseconds*

no ip pim override-interval

Ï–DAà

–D	ÆÄ
interval-milliseconds	È1-65535> Þ!¿

Ïb,Õ!5BÐ 2500 !¿

ÏQ¸à yG!5Bã

ÏÕ*Ð G!5By¡X override-interval GG!5By¡X>qÐÆÃ

ÏG!5B_Ð ØM6,X_G!5By¡X override-interval 3000 !¿Ä

```
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJLQWHUIDFHIDVWHWKHUQHW
5XLMLHFRQILJLILSSLPRYHUULGHLQWHUYDO
```

ÏÎGQÞ

Q¸	ÆÄ
-	-

ÏGÄà -

5.5 ip pim propagation-delay

ØGG¸G!5B hello #Ć,X propagation-delay ÀËË*ü **ip pim propagation-delay** ØØ no
6ãË hello #Ć,X propagation-delay 6ãtAxÄ

ip pim propagation-delay *interval-milliseconds*

no ip pim propagation-delay

Ï–DAà

–D	ÆÄ
interval-milliseconds	È1-32767> Þ!¿

Ïb,Õ!5BÐ 500 !¿

ÏQ¸à yG!5Bã

no ip pim state-refresh disable

Ï-DAèð

–D	ÆÄ
-	-

Þ¸Õ!5BÐ 5,ÿØÞ¼ÕCÄ

ÜQþÐ <G!5Bã

Ö*ÔÐ GK(ÕÕÕ[X Hello y[ÐÝMÈ

ü Hello y[Ð[,X SR Cap +!‰

GK(Õ6ÕÕÈ,X PIM-DM 4ÆÞ¸ÈÐ,Xú>C4•

CÃ><95ÐÐF-ÐGK(Õ6Ñ

ÜG!5B_Ð -

ÏÎGQÞÐ

Q¸	ÆÄ
-	-

ÜGÄèð -

5.8 ip pim state-refresh origination-interval

ÞÐG¸5B PIM-DM ,X(ÕC,X¢CKÊÈÈÀÆ*ü **ip pim state-refresh origination-interval**

no 6ÕX¢CKÊÈÈhG¸’

5BTAxÄ

ip pim state-refresh origination-interval *interval-seconds*

no ip pim state-refresh origination-interval

Ï-DAèð

–D	ÆÄ
interval-seconds	1-100> È/¦

Þ¸Õ!5BÐ 60 /¦

ÜQþÐ yG!5Bã

Ö*ÔÐ -

ÜG!5B_Ð 5XLMLHFRQILJXUHWHUPLQDO

5XLMLHFRQILJLQWHUIDFHIDVWHWKHUQHW

5XLMLHFRQILJLILSSLPVWDWHUHIUHVKRULJLQDWLRQLQWHUYDO

ÏÎGQÞÐ

Q¸	ÆÄ

-	-

ÏGÄê -

5.9 show ip pim dense-mode interface

Ø/ PIM-DM y¡XµÈËÏ*ü **show ip pim dense-mode interface** Ö¸

show ip pim dense-mode interface [*interface-type interface-number*] [**detail**]

Ï-DAê

–D	Ë:Ä
interface-type *interface-number*	*yØ)yË*
detail	*y¥¥¢*

ï5,Õ!5BÐ -

ÏQÇê (Mãâãäã

ïS*Ôê -

Ï!5B_Ð

```
5XLMLHVKRZSSLPGHQVHPRGHLQWHUIDFH
6GUHVV,QWHUIDFH9,)9HU1EU
,QGH[0RGH&XQW
)DVW(WKHUQHWY'
9/$Y'
```

+!‰	Aê
Address	PIM-DM y¡X IP
Interface	PIM-DM y¡Xyá
VIF Index	VIF ÂÖê Å
Ver/Mode	PIM (/ ã
Nbr Count	PIM-DM y¡XFÐ

ÏÎGQÇÐ

Q¸	Ë:Ä
show ip pim dense-mode neighbor	*/* PIM-DM y¡XFÇµ

ÏGÄê -

5.10 show ip pim dense-mode mroute

Ø/ PIM-DM CÃ><µÈËÏ*ü show ip pim dense-mode mroute QÄ

show ip pim dense-mode mroute [*group-or-source-address*

Ï-DAèð

–D	Ë Ä
group-or-source-address	*ø*
group-or-source-address	*øøõ*
summary	**õ¤**

Ъ,Ø!5BÐ -

ÜÇþ (Mèõõõ

Ъ*ðÐ -

Ï¨G!5B_Ð

```
5XLMLHVKRWSSLPGHQVHPRGHQHLJKERU
1HLJKERUG6GUHVV,QWHUIDFH8SWLPH([SLUHV9HU
)DVW(WKHUQHWY
9/$Y
```

+!‰	AÈ£
Neighbor-Address	F•
Interface	£¡•È²¿Xy·
Uptime/Expires	><NM,#ÊÈÈÕÈ
Ver	PIM (

ÏÎGQÐ

Q¸	£Ä
-	-

Ï¨GÄÈð

-

5.12 show ip pim dense-mode nexthop

Ø/ PIM-DM ÔQ¸ÈÈ*ü **show ip pim dense-mode nexthop Ø¸**

show ip pim dense-mode nexthop

Ï-DAÈð

	£Ä
-	-

Ï¨Õ!5BÐ

-

Ï¨Ø¸Ð

(Mãã

Ï¨Ð*Ø

-

Ï¨G!5B_Ð

ÏÎGQÞÐ

Q¸	Ë£Ä
-	-

ÏGÄÃð

-

5.13 show ip pim dense-mode track

Ò/ PIM-DM #Ay[4ªAu¸ÇÈËS*ü **show ip pim dense-mode track** ÔÇ

show ip pim dense-mode track

Ï–DAðÐ

–D	Ë£Ä
-	-

Ï5,Õ!5BÐ

-

ÜÇÞÐ

(MãÃãÃã

Ï*ÐÐ

¼ªAu,XÐÐÈÇÕX PIM y[Ò2Ä¼ÊÈ5B4ªAu,XÐÐÈ

ÐÈA*ü **clear ip pim dense-mode track** Ê¸ÐÐÐ PIM y[,XAu

D<Ä

Ï!5B_Ð

```
5XLMLHVKRWSSLPGHQVHPRGHWUDFN
3,0SDFNHWFRXQWHUV
(ODSVHGWLPHVLQFHFRXQWHUVFOHDUHG
        5HFHLYHGVHQW
9DOLG3,00SDFNHWV
+HOOR
-RLQ3UXQH
*UDIW
*UDIW$FN
6RXWH5HIUHVK
3,0605HJLVWHU
3,0605HJLVWHU6WRS
3,060600
3,060&39
8QNQRZ07SH
(UURUV
0DOIRUPHGSDFNHWV
%DGFKHFNVXPV
8QNQRZ3,0YHUVLRQ
6HQGHUURUV
```

6 PIM-SM

6.1 clear ip mroute

#Ù84€Ã><NM

clear ip mroute { * | *group-address* [*source-address*] }

Ï-DAè

–D	E Ä
*	Æ
group-address	7
source-address	6

Ï5,Õ!5BÐ -

ÏQè (Mã

ÏS*ô S*l8Q¿€Ã><Ä

ÏG!5B_Ð _ 1Ö84€Ã><NM

```
5XLMLHFOHDULSPURXWH
```

_ 2Ö8Ô4˜ 224.2.2.2 ,X4€Ã><NM

```
5XLMLHFOHDULSPURXWH
```

_ 3Ö8Ô4˜ 224.2.2.2ã 2.2.2.2 ,X4€Ã><NM

```
5XLMLHFOHDULSPURXWH
```

ÏÎGQÐ

Q¸	E Ä
-	-

ÏGÄè -

6.2 clear ip mroute statistics

#Ù84€Ã,X47Au¿

clear ip mroute statistics {* | *group-address* [*source-address*] }

Ï-DAè

–D	E Ä
*	Æ
group-address	7

6.4 clear ip pim sparse-mode track

GĄ5B4ŦAu,XĞĞ#Ù8 PIM y[,XAuD<Ä

clear ip pim sparse-mode track

Ï-DAĞĞ

–D	Ł.Ä
-	-

Ï5,Ğ!5BĐ -

ÏQĢĞ (Mã

ÏƁ*Ğ -

ÏG!5B_Đ 5XLMLHFOHDULSSLPVSDUVHPRGHWUDFN

ÏĨGQĢĐ

Q¸	Ł.Ä
show ip pim sparse-mode track	/ PIM y[4ŦAuĮ

ÏGÄĞ -

6.5 ip multicast-routing

|4€ÃĂ8Q¸X no 6ƁKÁs6Ğ-ŽŽPY]ĞĹ

6.6 ip pim accept-bsr list

L¶X BSR 8ÃBQ¸X no 6ãL¶Ä

ip pim accept-bsr list *access-list*

no ip pim accept-bsr

Ï–DAèð	–D	Ë¢Ä
	list *access-list*	é¨ IP ¶Ù ACL L¶ BSR 8È 8È 1-99Ã300-1999 Ã word

Ï5,Õ!5BÐ L$

ÏQ¸Ð

Ï*Ôð G!5B!8QÈIM-SM CÃ<¾ÝÏÙ BSR ¼X BSM y[Ä

ÏG!5B_Ð 5XLMLHFRQILJLSSLPDFFHSWEVUOLVW

ÏÎGQ¸Ð

Q¸	Ë¢Ä
-	-

ÏGÄèð -

6.7 ip pim accept-crp-with-null-group

AŒ BSR y prefix-count 0 ,X C-RP-ADV y[ÃBQ¸X no 6ãGKÁs6Ñ

ip pim accept-crp-with-null-group

no ip pim accept-crp-with-null-group

Ï–DAèð	–D	Ë¢Ä
	-	-

Ï5,Õ!5BÐ BSR ý prefix-count 0 ,X C-RP-ADV y[

ÏQ¸Ð <ã

Ï*Ôð ü C-BSR G!5B!8QÈ¹ C-BSR ä BSR ÈõÑ prefix-count 0 ,X C-RP-ADV y[È
JÀxA¹ C-RP 6ñX4Ä

ÏG!5B_Ð 5XLMLHFRQILJLSSLPDFFHSWFUSZWKQXOOJURXS

ÏÎGQ¸Ð

Q¸	Ë¢Ä
-	-

ÏGÄêø -

6.8 ip pim accept-crp list

LêX C-RP 8êéá,X48êBQ¸X no 6ê¾LêÄ

ip pim accept-crp list *access-list*

no ip pim accept-crp

Ï–DAêø

–D	ÆÄ
list *access-list*	éü IP }– ACL Lê C-RP 8êéá,X48è 8êÈ00-199 Ã 2000-2699ÑWORD

ï5,Õ!5BÐ C-BSR yéÉ¼XÆÝ RP Eî

ÏQêÞ <ã

ïS*êÐ ü C-BSR ê!5B!8QÈ¯ C-BSR ä BSR6êÑX C-RP 8êéá,X44˜

8è> Lê

ï!5B_Ð 5XLMLHFRQILJLSSLPDFFHSWFUSOLVW

ÏÎGQÞÐ

Q¸	ÆÄ
-	-

ÏGÄêø -

6.9 ip pim accept-register list

Lê¼X(S,G) 8êBQ¸X no 6ê¾LêÄ

ip pim accept-register list *access-list*

no ip pim accept-register

Ï–DAêø

–D	ÆÄ
list *access-list*	éü IP }– ACL Lê(S,G) 8è 8êÈ00-199 Ã 2000-2699ÑWORD

ï5,Õ!5BÐ LêRP yéS,G) ,X¼

ÏQêÞ <ã

ïS*êÐ M-Õ RP ê C-RP ê!5B!8QÈêMn84˜X¼

Ï¨G!5B_Ð

```
5XLMLHFRQILJLSSLPDFFHSWUHJLVWHUOLVW
5XLMLHFRQILJDFFHVVOLVWSHUPLWLS
```

ÏÎGQÞ

Q¸	Ë£Ä
-	-

Ï¨GÄÀê

-

6.10 ip pim bsr-border

G!5BBSR E÷ ÄßQ¸X no 6ß8E÷ Ä

ip pim bsr-border

no ip pim bsr-border

Ï-DAÀê

–D	Ë£Ä
-	-

Ï¸Õ¨G!5BÐ ´ BSR E÷

Ï¨Qþê yã

Ï¨*Ûð Ë£$ BSM y[,XÞ¨G!5B BSR E÷ È£Ëþ· BSM ãÏ¨Gè

BSM 3ãëþE¥@

Ï¨G!5B_Ð ü gi 0/3 ¨G!5B BSR E÷

```
5XLMLHFRQILJLQWHUIDFHJL
5XLMLHFRQILJLILSSLPEVUERUGHU
```

ÏÎGQÞ

Q¸	Ë£Ä
-	-

Ï¨GÄÀê

-

6.11 ip pim bsr-candidate

G!5BC-BSRÄßQ¸X no 6ãÏ¨G!5BÄ

ip pim bsr-candidate *interface-type interface-number* [*hash-mask-length* [*priority-value*]]

no ip pim bsr-candidate [*interface-type interface-number*]

Ï-DAÀê

–D	Ë£Ä
interface-type *interface-number*	*ûÿ·*
hash-mask-length	ã0-32> È RP E¥G!5B HASH }-ÕSSÈ¸Õ

	10
priority-value	Æ0-255> 4ÈÉÝ BSR G!5B¼{–DÈ¿Õ 64

Ï¿Õ!5BÐ ´ C-BSR

ÜQÞ <ã

Ï*Ð PIM-SMÑÈÐ¿Þ7ÇÃ< BSRÄBSR BÐÈ¿¾ RP ÞÄ C-BSR
EÈ·ý¸È{Ý*ÐÆx¿X BSRÄ¹ BSR Þ¿!È C-BSR Ax7Æ¼ BSRÜ¼Ãß
PIM-SM ¼• 224.0.0.13 ÈÇÜý¸ÈÄý¹[Ü BSR ¿X¼{Ä
S*l8QÞÃ}AßÜ!4- BSR ¿Xý¸ÈÞÇ4¿Ý PIM FÈ !ÞÑÐ
¿X BSR Þ¿àX7ÇÆ¼!EWÜÈpÞ¥¼X7ý¸ÈÜ¼¿È·Ý¸È¿X
0 BSR ÆÈÉÇÆÄ
! C-BSR AÆÇ¼ BSRÆÈ¼Þ C-BSR yÆX7ÇÆÈ•Þ
C-BSR ÞÐ¿XÆÞÈ¿X IP Å

Ï¿G!5B_Ð 5XLMLHFRQILJLSSLPEVUFDQGLGDWHJL

ÏÏGQÞ Q¸

5XLMLHFRQILJLILSSLPGUSULRULW\

ÏĈGQÞ	Q¸	ÆÄ
	-	-

ĞGÄß -

6.13 ip pim ignore-rp-set-priority

Ê¼ýn,X RP ß9 RP ,X¾{Ø8Q¸X no 6ää,Ğ!5BÄ

ip pim ignore-rp-set-priority]TJ/TT0 1 Tf0 Tc 0 Tw 13.167 Tm( )Tj29orit Tc -7.007 20 T67I Td()Tj/TC2_0 1 Tf0 Tc 0

Ï*Ð -

ÏG!5B_Đ 5XLMLHFRQILJLSSLPMSWLPHU

ÏÎGQÞ

Q¸	Ë Ä
-	-

ÏGÄà -

6.15 ip pim mib dense-mode

S Mib 4¥ PIM-DMÏ8Q¸X no 6ëõ,Õ!5BÄ

ip pim mib dense-mode

no ip pim mib dense-mode

Ï-DAà

–D	Ë Ä
-	-

ï,Õ!5BĐ Mib 4¥ PIM-SM

ÏQÞà <ã

Ï*Ð -

ÏG!5B_Đ 5XLMLHFRQILJLSSLPPLEGHQVHPRGH

ÏÎGQÞ

Q¸	Ë Ä
-	-

ÏGÄà -

6.16 ip pim neighbor-filter

*ËE$6Ñ8Q¸X no 6ãËEÄ

ip pim neighbor-filter *access_list*

no ip pim neighbor-filter *access_list*

Ï-DAà

–D	Ë Ä
access_list	Ï IP Ê acl L£8È 8È 1-99Ã0ú

ï,Õ!5BĐ ÞÄ¹s6Ñ

ÏQ¸Þ yã

Ï*Ô PIM 54%X]<ÈÏ•XÈÔ>E¸¼KÂ
><¼È PIM-SM ÁF¹Ï¸eering Â2Ê1ÃF¬È¸ÝÍG2Ä

ÏG!5B_Đ
```
5XLMLHFRQILJLQWHUIDFHJL
5XLMLHFRQILJLILSSLPQHLJKERUILOWHU
5XLMLHFRQILJLIH[LW
5XLMLHFRQILJDFFHVVOLVWGHQ\
```

ÏÎGQÞ

Q¸	Ë¬Ä
-	-

ÏGÄÈ -

6.17 ip pim neighbor-tracking

/U!6y¡Xt9e6ÑÈ¸F¢CÞ¸Q¸X no 66Ñ,Õ!5BÄ
ip pim neighbor-tracking
no ip pim neighbor-tracking

Ï-DAÈ

–D	Ë¬Ä
-	-

Ï5,Õ!5BĐ |y¡Xt9e6Ñ

ÏQ¸Þ yã

Ï*Ô y¡Xt9e6Ñ>¼ÈÃ<ÇÞ¥Õ join y[Ê¿pF¬ÞÃ<
¥ÇX join y[ÈwÈÃ<,X join y[Î>eGÊ¿py¡Xt9e6Ñ>/U
!6Èw!8ÊÃ<¥ÇÕ join y[Þ5¸Xt9e6ÑF¬/U!6ÞÃ
EÊy,X join y[È5àBÛF¬Þ5ÈF¢CÞÄ

ÏG!5B_Đ /U!6y¡Xt9e6Ñ
```
5XLMLHFRQILJLQWHUIDFHJL
5XLMLHFRQILJLILSSLPQHLJKERUWUDFNLQJ
```

ÏÎGQÞ

Q¸	Ë¬Ä
ip pim propagation-delay	**G5Þ** propagation-delay

ÏGÄÈ -

6.18 ip pim override-interval

ise al

A5By¡X Override-Interval‚ØQ¸X no 66ä,Õ!5BÄ

ip pim override-interval *milliseconds*

no ip pim override-interval

Ï-DAÈ	–D	Ł Ä

¥#ÊÈÈhâÑYE¥ÊÈXÐ!5BãÆgÐfG WarningÄ

5à 3*¥ÊÈÈ ¥#ÊâÑYE› 65535ÆgÐfG WarningÄ

ÏG!5B_Ð G!5B¥#ÊÈ 6s

5XLMLHFRQILJLSSLPSUREHLQWHUYDO

ÏÎGQÐ

Q¸	ÆÄ
ip pim register-suppression	-

ÏGÄð -

6.20 ip pim propagation-delay

G!5By¡XÊ³ propagation-delayØQ¸X no 6ææ,Õ!5BÄ

ip pim propagation-delay *milliseconds*

no ip pim propagation-delay

Ï-DAð

–D	ÆÄ		
milliseconds	Ø	1-32767È,Õ	500

ï,Õ!5BÐ –D5,Õ

ÏQð yã

!8N ØÆ6ÆMÈ,æÆSÆÆ2Ô~BÅ1]9RuÆEÔLÊ5,Ø¸Ø+x¥V¬yã

Ï5*uÐT!ÅROALÐ0

Ï-DAèð

–D	Ë Ä
seconds	hello y[Ë Õó)!/ßÈ 1-65535È,Õ 30

Ï5,Õ!5BÐ –D5,Õ

ÜQþð yã

Ï*Ûð !£ Hello #CË ÕÈh>þÊ Hello #CËÕÈÈcþÐ Hello #CËÕÈ
>þÈ Hello #CË ÕÈh,X 3.5 ¥ãp Hello #CË ÕÈh * 3.5 > 65535 Jè Hello #CË ÕÈ
Lh>þÈ 18725Ä

Ü!5B_Ð

```
5XLMLHFRQILJLQWHUIDFHJL
5XLMLHFRQILJLILSSLPTXHULQWHUYDO
```

ÎÜQÞ

-	-

ÏGÄê -

6.23 ip pim register-decapsulate-forward

AŒ RP ¥[E> ÕÏÆ¥@X4ÞDBy[Ä8Q¸X no 6ëë,Õ!5BÄ

ip pim register-decapsulate-forward

no ip pim register-decapsulate-forward

Ï-DAê

	E Ä
-	-

ï,Õ!5BÐ RP ¥[E> ÕÈ¥@X4ÞDBy[Ä

ÏQê <ã

ÏŠ*Ð M-Õ RP ê C-RP

5BÄ8QÚ!8 DR ` RP ,XBÈ'YE‹$X¶¡6ÑÆÕ

ËG!5B_Đ 5XLMLHFRQILJLSSLPUHJLVWHUUDWHOLPLW

ÏĜGQĐ

Ïð <ã

Ï*ð

no ip pim rp-address *rp-address* [*access_list*]

Ï–DAèð

–D	EÄ
rp-address	RP ,X ip
access_list	éü ACL Lè!8 RP á¸X48Ê¸ÊÄ Õ+ acl 8È <1-99>Ã1300-1999> × 3Qá aclÄ

Ï¿Õ!5BÐ M-Õ RP

ÜÇð <ã

Ï*Ð 2ÜÍ)Ç!5B4¥M-Õ RPÈ¥3ÕM-Õ RP ` BSR ê> Ä*Ù8QÇÐ6´ ê

VpEÊ› BSR ` RP M-Õ!5BÐê*ÇÕ!5BÄ

S*ÄÀ¥KÂ<M-Õ!5B RP Õ!5BÇX44ÄÄ*ü ACLÐÈX44ÄÄ*ü ACLÄ

ÇÐ RP M-ÐÕ¥Õ!5BS*Ä

VpÝM-Õ RP áb¿ÐÊ¸XM-Õ RP ÝÊÉ¿*Ä

ý¼ ACL n¸XAÊÐÇÝX4¯4ÄCL 5¸ÐÀx AÇX4¯4˜

224/4Ä

G!5BÐè-ÇX RP ÐÇb48ÈXM-Õ RP 4ÄÄ8ÈM-Ç4ÊÐ

ÇM-Õ RP 4¸XJÈ<48ÈJÈ<Ý IP Ê¸ÐÈÇÊ2 RPÊÇÐÊ

3 IP Ð¸XFwÇj>ÊÄ

Ð8Ç RP M-ÐX4Ð8ÊÐÇÈ8ÊÇ2 RP Ä

Ç!5B_Ð 5XLMLHFRQILJLSSLPUSDGGUHVV
5XLMLHFRQILJDFFHVVOLVWSHUPLW

ÏÇQÐ

seconds	å BSR ¥ÆÕ C-RP #Œ,X<å ª 8 × È <1-16383> È interval interval-seconds 5 , ÕÊ È interval-seconds 60sÄ
access_list	é*ü* ACL Lß!8 C-RP á¸X48Ê¸ßb¼ÄÕ+ acl 8È 1-99 8Qá acl× group-list access_listÄ

ï¿Õ!5BÐ þ!5B C-RP

ÏQþÐ <ã

Ï*ÐÐ ü PIM-SM #AÈ¸Ã4ÐDBÎXEå RPT ¶&. RP å¸ÊRP EÆ›
ÆÝ RP E¶ÝXÄ BSR E¶ÝX C-RP nå BSR)• C-RP #ŒÈ+ BSR å
þ PIM ¥ÄÄ
8LÔÛyÇMn48ÈXEÝ rpÈwAQþ acl EÝMÄÔÝX48ÈXAu1k
Ï¼ permit ,X aceÊ deny ,X ace E> 4ÐÐu1k,XÄ

ïG!5B_Ð 5XLMLHFRQILJLSSLPUSFDQGLGDWHJLSULRULWLJURXSOLVWLQWHUYDO
5XLMLHFRQILJDFFHVVOLVWSHUPLW

ÎÏGQÞÐ

Q¸	Æ:Ä
-	-

ïGÄÈÐ -

6.30 ip pim rp-register-kat

A5B RP þX KAT KÈhÄ8Q¸X no 6ÊÊ¸Õ!5BÄ

ip pim rp-register-kat *seconds*

no ip pim rp-register-kat

Ï-DAÈÐ

–D	Æ:Ä
seconds	KAT nÊ¸XÊÆÊ)!/þÈ 1-65535È¸Õ 210Ä

ï¿Õ!5BÐ –D5¸Õ

ÏQþÐ <ã

Ï*ÐÐ -

ïG!5B_Ð 5XLMLHFRQILJLSSLPUSUHJLVWHUNDW

ÎÏGQÞÐ

Q¸	Æ:Ä

-	-

ÏGÄê

-

6.31 ip pim sparse-mode

ÿÞ PIM-SMÄ8Q¸X no 66ä,Õ!5BÄ

ip pim sparse-mode

no ip pim sparse-mode

Ï-DAê

–D	Ë-Ä
-	-

Ï5,Õ!5BÐ

þ PIM-SM

ÏQêÞ

yã

Ï5*Ûð

þ PIM-SM !ÈÈG!5BÞ¼CÃE¥6ÕS|Z PIM-SMÞ6ÑÑ@

¥ÐBy[Ä

þ PIM-SM ,XêGMP ÞÞ¼ÈÔ|G!5BÄ

G!5BA¹Q¸X êÈV pî)„Failed to enable PIM-SM on < y·á >, resource temporarily

Ï-DAèè

–D	Ë.Ä
group-list *access-list*	é*ü* ACL Lè§ÁŒ SPT ô0¸X4ªÃÄ access-listÕ+ acl 8è¢ 1-99Ã300-1999 × 3Õá aclÄ

Ï5¸Õ!5BÐ á SPT ô0

ÜQêè <ã

Ï*ôð VpáD **group-list** *access-list*Ë SPT ô0Ä

Ü!5B_Ð

```
5XLMLHFRQILJLSSLPVSWWKUHVKROGJURXSOLVW
5XLMLHFRQILJDFFHVVOLVWSHUPLW
```

ÏÕGQÞ

Q¸	Ë.Ä
-	-

Ü-Äèè -

6.33 ip pim ssm

| SSMÈ5B SSM 4ªÃQ¸X no 66ª¸Õ!5BÄ

ip pim ssm { **default** | **range** *access_list* }

no ip pim ssm

Ï-DAèè

–D	Ë.Ä
default	SSM 5,Œ3ÈÃ232.0.0.0/8
range *access_list*	é*ü* ACL Lè§ SSM 4ªÃÄ Õ+ acl 8è¢ 1-99ª¸Õá acl

Ï5¸Õ!5BÐ GKÁ SSMÄ

ÜQêè <ã

Ï*ôð VpLÔü PIM-SM 5¼%)„ SSM h*ÈOG!5B!8QÄ

Ü!5B_Ð _ 1Ö SSMÈ5B SSM 4ªè¢ 232/8Ä

```
5XLMLHFRQILJLSSLPVVPGHIDXOW
```

_ 2Ö SSMÈ5B SSM 4ªè¢ 226/8Ä

```
5XLMLHFRQILJLSSLPVVPUDQJH
5XLMLHFRQILJDFFHVVOLVWSHUPLW
```

ÏÎGQÐ

Q¸	Ë.Ä
-	-

ÏGÄÀð -

6.34 ip pim triggered-hello-delay

G!5By¡X Triggered-Hello-DelayÏ8Q¸X no 6ää,Õ!5BÄ

ip pim triggered-hello-delay *seconds*

no ip pim triggered-hello-delay

Ï–DAÀð

–D	Ë.Ä
seconds	Triggered-Hello-Delay ,XÄ)!/ÞÈ 1-5È,Õ 5

Ï5,Õ!5BÐ –D5,Õ

ÏQÞÐ yã

ÏS*ÐÐ y|ÊÞ#Ë,ÈÈBÊ*ü Triggered-Hello-Delay 9{*ÐcÊÈ

Eþc ÊÈÈÈÈÕ hello y[Ä

ÏG!5B_Ð G!5By¡X Triggered-Hello-Delay 3sÄ

```
5XLMLHFRQILJLQWHUIDFHJL
5XLMLHFRQILJLILSSLPWULJJHUHGKHOORGHOD\
```

ÏÎGQÐ

Q¸	Ë.Ä
-	-

ÏGÄÀð -

6.35 show debugging

/A¤ÊÔÛX‰

show debugging

Ï–DAÀð

–D	Ë.Ä
-	-

Ï5,Õ!5BÐ -

ÏQÞÐ (Mãã

Ï*Ð -

ÏG!5B_Ð
```
5XLMLHVKRWGHEXJJLQJ
LSSDFNHWGHEXJ
LSSDFNHWGHEXJGHEXJJLQJLVRQDFO
```

ÏÎGQÞ

Q¸	Ë Ä
-	-

ÏGÄð -

6.36 show ip pim sparse-mode bsr-router

¦ß BSR ÇÄ

show ip pim sparse-mode bsr-router

Ï–DAð

–D	Ë Ä
-	-

Ï,Õ!5BÐ -

ÏQÞ (Mðãã

Ï*Ð -

ÏG!5B_Ð
```
5XLMLHVKRW6SSLPVSDUVHPRGHEVUURXWHU
3,0YRWRVVWUDSLQIRUPDWLRQ
7KLVVVWHPLVWKHRWVWUDS5RXWHU%6
%6DGGUHVV
8SWLPHGKP%63ULRULW\DVKPDVNOHQJWK
1H[WERRWVWUDSPHVVDJHLQ
5ROHQQGLGDWH%63ULRULW\DVKPDVNOHQJWK
6WDWH(OHFWHG%6
QGLGDWH53*LGELW(WKHUQHW
SYHUWLVHPHQWLQWHUYDOVHFRQGV
1H[WQGB53BDGYHUWLVHPHQWLQ
```

ÏÎGQÞ

Q¸	Ë Ä
-	-

ÏGÄð -

6.37 show ip pim sparse-mode interface

¦ß PIM SM yŒÄ

detail

ъ‚Õ!5BÐ -

ÜQþÐ (Mãâãã

Ъ*ÐÐ -

Ü!5B_Ð 5XLMLHVKRWSSLPVSDUVHPRGHUSKDVK
53
,QIRVRXUFHYLDERRWVWUDS

ÏÜGQÞÐ

Q¸	ÆÄ
-	-

ÜÄâÐ -

6.43 show ip pim sparse-mode rp mapping

¦ÑX RP Ъá‚X4Ä

show ip pim sparse-mode rp mapping

Ï-DAâÐ

–D	ÆÄ
-	-

ъ‚Õ!5BÐ -

ÜQþÐ (Mãâãã

Ъ*ÐÐ -

Ü!5B_Ð
```
5XLMLHVKRWSSLPVSDUVHPRGHUSPDSSLQJ
3,0*URXSWR530DSSLQJV
*URXSV
53
,QIRVRXUFHYLDERRWVWUDSSULRULW\
8SWLPHH[SLUHV
53
,QIRVRXUFHYLDERRWVWUDSSULRULW\
8SWLPHH[SLUHV
*URXSV6WDWLF
53
8SWLPH
```

ÏÜGQÞÐ

Q¸	ÆÄ

-	-

ÏGÄêð -

6.44 show ip pim sparse-mode track

¹¼ÆAu,XÐÈÀÑ¸X PIM y[,XÐÄ

show ip pim sparse-mode track

Ï–DAêð

–D	ÆÄ
-	-

Ï5,Õ!5BÐ -

ÒQêð (MÃÃÃã

Ï5*Ðð 2Ä¼ÆÊÔA5B4ÆAu,XÐÈÀÑ¸X clear ip pim sparse-mode track Ê¡

A5B4ÆAu,XÐÈÀÑ¸Ù8 PIM y[,XAuD<Ä

Ï!5B_Ð

```
5XLMLHVKRWSSLPVSDUVHPRGHWUDFN
3,0SDFNHWFRXQWHUVWUDFN
(ODSVHGWLPHVLQFHFRXQWHUVFOHDUHG
UHFHLYHGVHQW
9DOLG3,060SDFNHWV
+HOOR
-RLQ3UXQH
5HJLVWHU
5HJLVWHU6WRS
ÑVHUW
ÑÑ0
ÑÑ3Ñ
3,00*UDIW
3,00*UDIWÑN
3,006WDWH5HIUHVK
8QNQRZQ3,07ÑH
(UURUV
0DOIRUPHGSDFNHWV
ÑGFKHFNVXPV
6HQGHUURUV
3DFNHWVUHFHLYHGÑWKXQNQRZQ3,0YHUVLRQ
```

ÏÏGQÐ

Q¸	ÆÄ
-	-

ÏGÄÈ -

7 PIM-SMv6

7.1 clear ipv6 mroute

#Ù84€ÃA><NM

clear ipv6 mroute { ***** | *ipv6_group_address* [*ipv6_source_address*] }

Ï-DAê

–D	Ë.Ä
*	ë
ipv6_group_address	7
ipv6_source_address	6

ï5,Õ!5BÐ -

ÏQê -

ï5*ô -

ÏG!5B_Ð _ 1ÐÖ8¸Ý4€ÃA><NM

```
5XLMLHFOHDULSYPURXWH
```

_ 2ÐÖ8(Mn4¸Ý4€ÃA><NM

```
5XLMLHFOHDULSYPURXWHII
```

_ 3ÐÖ8(Mn,X4ë,X4€ÃA><NM

```
5XLMLHFOHDULSYPURXWHII
```

ÏÎGQÐ

Q¸	Ë.Ä
-	-

ÏGÄê -

7.2 clear ipv6 mroute statistics

ô84€ÃA><NM,X47uÇ

clear ipv6 mroute statistics { * | *ipv6_group_address* [*ipv6_source_address*] }

Ï-DAê

–D	Ë.Ä
*	ë
ipv6_group_address	7

ipv6_source_address	*6*

ï5,Õ!5BÐ -

ÏQÇÐ (Mã

ÏS*Ô Ð -

ÏG!5B_Ð _ 1Ï8¸Ý¼4€CÃ><NM,X4?Au

```
5XLMLHFOHDULSYPURXWHVWDWLVWLFV
```

_ 2Ï8(Mn4¸Ý¼4€CÃ><NM,X4?Au

```
5XLMLHFOHDULSYPURXWHVWDWLVWLFVII
```

_ 3Ï8(Mn,X4ßí¼4€CÃ><NM,X4?Au

```
5XLMLHFOHDULSYPURXWHVWDWLVWLFVII
```

ÏÎGQÐ

Q¸	Ë.Ä
-	-

ÏGÄÈ - -

7.3 clear ipv6 pim sparse-mode bsr rp-set *

#Ù8|Õ RP ÇÄ

clear ipv6 pim sparse-mode bsr rp-set *

ÏDAÈ

–D	ËÄ
-	-

ï5,Õ!5BÐ -

ÏQÇÐ (Mã

ÏS*Ô !8Q§Ñ8:,X C-RP ,XÇÈÑ8M-Õ RPÄ

ÏG!5B_Ð

```
5XLMLHFOHDULSYSLPVSDUVHPRGHEVUUSVHW
```

ÏÎGQÐ

Q¸	Ë.Ä
-	-

ÏGÄÈ - -

7.4 clear ipv6 pim sparse-mode track

GąA5B4ªAu,XÐÈ#Ù8 PIMv6 y[,XAuD<Ä

clear ipv6 pim sparse-mode track

Ï-DAèð

–D	ÆÄ
-	-

Ï5,Õ!5BÐ -

ÏQęð (Mã

ÏS*Ôð -

ÏG!5B_Ð 5XLMLHFOHDULSYSLPVSDUVHPRGHWUDFN

ÏÎGQÐ

Q¸	ÆÄ
show ipv6 pim sparse-mode track	*/* PIM y[4ªAuÇ

ÏGÄèð -

7.5 ipv6 multicast-routing

| IPv6 4€CÃŸ8Q¸X no 6ÈGKÁ IPv6 4€CÃÄ

ipv6 multicast-routing

no ipv6 multicast-routing

Ï-DAèð

–D	ÆÄ
-	-

Ï5,Õ!5BÐ GKÁ IPv6 4€CÃ

ÏQęð <ã

ÏS*Ôð N¥O| IPv6 4€CÃÈSb IPv6 4¸XJ€G!5B!6ÑÃ

ÏG!5B_Ð 5XLMLHFRQILJLSYPXOWLFDVWURXWLQJ

ÏÎGQÐ

Q¸	ÆÄ
-	-

ÏGÄèð -

7.6 ipv6 pim accept-bsr list

L$ BSR ,X8ÆBQ¸X no 6ÆL$Ä

ipv6 pim accept-bsr list *ipv6_access-list*

no ipv6 pim accept-bsr

Ï-DAÆð

–D	ÆÄ
list *ipv6_access-list*	éü IPv6 ACL Lñ BSR ,X8È Õá acl

Ï5,Õ!5BÐ yý BSM y[

ÜQÞð <ã

Ü5*Ðð -

Ü!5B_Ð 5XLMLHFRQILJLSYSLPDFFHSWEVUOLVWEVUOLVW

ÏÎGQÞÐ

Q¸	ÆÄ
-	-

ÜGÄÆð -

7.7 ipv6 pim accept-crp-with-null-group

AÿÆ prefix-count 0 ,X C-RP-ADV y[ÆBQ¸X

Ï¨G!5B_Ð /U!6ß fe80::2d0:f8ff:fe22:33ad ,X¥Y¡

```
5XLMLHFRQILJLSYSLPDFFHSWUHJLVWHUOLVWUHJLVWHUDFFHVVOLVW
5XLMLHFRQILJLSYDFFHVVOLVWUHJLVWHUDFFHVVOLVW
5XLMLHFRQILJLSYDFOGHQLSYIHGIIIIHDGDQ\
```

ÏÎGQÐ

Q¸	Ë£Ä
-	-

Ï¨GÄÀß -

7.10 ipv6 pim bsr-border

G!5BBSR E«Ä¾Q¸X no 6ß8 BSR E«Ä

ipv6 pim bsr-border

no ipv6 pim bsr-border

Ï–DAß

–D	Ë£Ä
-	-

Ï¸Õ¨G!5BÐ ´ BSR E«

Ï¨Qß -

Ï¨*Ð Ë£ BSM y[,XÐG!5B BSR E« ÈËÞ· BSM ßÏ¨Ç

BSM 3ßÞEÄ@

Ï¨G!5B_Ð ü gi 0/3 G!5B BSR E«

```
5XLMLHFRQILJLQWHUIDFHJL
5XLMLHFRQILJLILSYSLPEVUERUGHU
```

ÏÎGQÐ

Q¸	Ë£Ä
-	-

Ï¨GÄÀß -

7.11 ipv6 pim bsr-candidate

G!5BC-BSRÄ¾Q¸X no 6ßG!5BÄ

ipv6 pim bsr-candidate *interface-type interface-number* [*hash-mask-length* [*priority-value*]]

no ipv6 pim bsr-candidate [*interface-type interface-number*]

Ï–DAß

–D	Ë£Ä

interface-type *terface-number*	*yéÄ* !8y¡X C-BSR ,X
hash-mask-length	hash }-ÕSz 8È 0-128Ê,Õ 126
priority-value	*ÿ* 8È 0-255Ê,Õ 64

Ê,Õ!5BÐ ´ C-BSR

ÒQÞÐ <ã

Ê*ÐÐ þÔ PIM-SMv6 ÆÐX7ÇÃ< BSRÄ BSR BÐÊ3¥ RP ÇÞÄ
EÝBSR EÊ7ÿ¡E{*ÐX,X BSRÄ¹ BSR Ç!È-BSR Ax7Å¼ BSRÈW
ÀÔ PIM-SMv6 ÆÇÝ¡ÊÝ[Ù BSR ,X¼{Ä
S*Ì8QÃ}AÚÔ!4¡X BSR ÆÇÞ¼4¡X PIM ÆÐÊ,X
BSR à7Þ¼,X!EWÈpÿ¥X,X IPV6 å16ÙWPÈW±
,EÐ BSR ÈÆÇÞÄ
!AÐÞ¼ BSRÈWÐÝ BSR yÞÇÈ!AÙWÐ
È¸XÐÔXÈ¸X IPV6 Å

Ê!5B_Ð 5XLMLHFRQILJLSYSLPEVUFDQGLGDWHJL

ÌÊGQÞÐ

Q¸	Ê:Ä
-	-

ÊGÄÐ -

7.12 ipv6 pim dr-priority

G!5BDR¼{Ä8Q¸X no 6ÊÔ,Õ

ipv6 pim dr-priority *priority-value*

no ipv6 pim dr-priority

Ì-DAÐ

–D	Ê:Ä
priority-value	*ÿ* 8È 0-4294967294Ê,Õ 1Ä

Ê,Õ!5BÐ –D5,Õ

ÒQÞÐ yã

Ê*ÐÐ EÞ DR Ð6ÞÐ*Ö
ÔXAÔX Hello y[FÑ5B¼{–DÈwÊ:½ DR ÊEW¼{ÈÔXì
4{PÈÊõ DR8ÞÐX¼{ÈwÈÔX IP PÈÊÕ DRÄ

Hello #Cy[ùÝ5B¾{–DEwvE

ï5,Õ!5BÐ –D5,Õ

ÏQÇÐ <ã

ÏS*ÛÐ -

ÏG!5B_Ð 5XLMLHFRQILJLSYSLPMSWLPHU

ÏÎGQÇÐ

Q¸	Ë.Ä
-	-

ÏGÄÀÐ -

7.15 ipv6 pim neighbor-filter

L¢5Ë8ÃÐQ¸X no 6ãÀLÄ

ipv6 pim neighbor-filter

no ipv6 pim neighbor-filter

Ï-DAÀÐ

–D	Ë.Ä
ipv6_access-list	éü IPv6 ACL L¢5F8È

ï5,Õ!5BÐ ¿ÄÀ

ÏQÇÐ yã

ÏS*ÛÐ S*Ù8QÍ-È> EÇÃ PIM 5¼%X]<ÈÐ¸X8ÃÐF»È›

ÇÀKÄ<¼ÍÈ PIM-SMV6 ÐÑN0ÇÐeeringt

ËG!5B_Ð G!5By¡X Override-Interval 3000 !¿

5XLMLHFRQILJQWHUIDFHJL

5XLMLHFRQILJLILSYSLPRYHUULGHLQWHUYDO

ÏÎGQÞ

Q¸	Ë Ä
ipv6 pim propagation-delay	G!5By¡XÊ³ propagation-delay

ËGÄê

-

7.18 ipv6 pim probe-interval

G!5BÌ¥#ÊÈÕQ¸X no 6ëë,Õ

ipv6 pim probe-interval *seconds*

no ipv6 pim probe-interval

Ï–DAê

–D	Ë Ä
seconds	Ì¥#ÊÈ)!/þÈ« 1-65535Ë¸Õ 5

Ëõ,ÕG!5BÐ

–D5,Õ

ËQþ

<ã

ËS*Ð

Ì¥#ÊÈÌ¥KÊÈYÊÈÊE DR å RP Ë£ÕNÌ¥¡G NULL-Register ,XÊÈ

KÈhÄ

Ì¥#ÊÈÈhëÕYEÌ¥KÊ¡XÐ!5Bá8Ä4Vp|ÐÞ

>€ Ì¥#ÊÈÕYE• Ì¥

Ï–DAêè

–D	Ë.Ä
milliseconds	Hello EÝXM,X Propagation_Delay ,XÄ)!!/êè« 1-32767È¸Õ 500

Ï¿,Õ!5BÐ -

ÏQêÐ yã

Ï*êÐ êêqëËÌ¡ J/P-override-intervalÄÀÐ" J/P-override-interval
NÝOã Join-Prune y[,X holdtimeÑÑàÝ,X#ÄÈÊ5¼1u)ÚÙÈ±
AÄ

Ï!5B_Ð G!5By¡X propagation-delay 600 !¿¸

```
5XLMLHFRQILJLQWHUIDFHJL
5XLMLHFRQILJLILSYSLPSURSDJDWLRQGHOD\
```

ÏÎGQÐ

Q¸	Ë.Ä
ipv6 pim override-interval	G!5By¡XÐÈh override-interval
ipv6 pim neighbor-tracking	G!5By¡XF¢¢Cþ6Ñ

ÏGÄêè -

7.20 ipv6 pim query-interval

G!5BHello y[Ë¢ÊÕÑQ¸X no 6ëë¸Õ
ipv6 pim query-interval *seconds*
no ipv6 pim query-interval

Ï–DAêè

–D	Ë.Ä
seconds	Hello y[Ë¢ÊÕó)!/êè« 1-65535È¸Õ 30

Ï¿,Õ!5BÐ -

ÏQêÐ yã

Ï*êÐ !£ Hello #ÏCË¢ÊÕÈh>Ê« Hello #ÏCÊÕÈÑÑcÐ Hello #ÏCÊÕÈ
>Ê« Hello #ÏCË¢ÊÕÈh,X 3.5¥xp Hello #ÏCË¢ÊÕÈh * 3.5 > 65535 Jè« Hello #ÏCË¢ÊÕÈ
Lh>Ê« 18725Ä

Ï!5B_Ð

```
5XLMLHFRQILJLQWHUIDFHJL
5XLMLHFRQILJLILSYSLPTXHULQWHUYDO
```

ÏĈGQÞ	Q¸	£Ä
	-	-

ĞGÄß -

7.21 ipv6 pim register-checksum-wholepkt

Au1kHþ[¸XÞ?ßQ¸X no 6ßG!5BÄ

ï5,Õ!5BÐ L$

ÏQ¸Ð <ã

ï*Ô AÐQÍ¸ÐÈ G¸Õ¥Ï¸Ð¿Õ¿> G!5BÐÈ¸Ð¿Ï¸³X¥Ï¸Ð¿Õ¿¯

> G!5BÏ¸8Q¸Ú!¥ DR ` RP ,XBÐ¥YE¸Ł¸X¥Ï¸6Ñ¿ÐÕ

Ï!5B_Ð 5XLMLHFRQILJLSYSLPUHJLVWHUUDWHOLPLW

ÏÎGQ¸Ð

Q¸	Ð¿Ä
-	-

ÏÄÐ¥ -

7.23 ipv6 pim register-rp-reachability

¿Ð¥Ï!¥ RP Ð¿Ä¸Q¸X no 6Ð¿ï5,Õ!5BÄ

ipv6 pim register-rp-reachability

no ipv6 pim register-rp-reachability

Ï-DAÐ¥

–D	Ð¿Ä
-	-

ï5,Õ!5BÐ ¿Ð¥Ï¿Ð¿ RP Ð¿Ä’

ÏQ¸Ð <ã

ï*Ô G!5BAQ¸Ð¿Ð¥Ï!¥ RP Ð¿ÄÐ¿Ä¿Ð¿Ä¿Ð¿Õ

Ï!5B_Ð 5XLMLHFRQILJLSYSLPUHJLVWHUUSUHDFKDELOLW\

ÏÎGQ¸Ð

Q¸	Ð¿Ä
-	-

ÏÄÐ¥ -

7.24 ipv6 pim register-source

ÎÏ¥¸X¥Ï IPv6 Ï¸8Q¸X no 6Ð¥G!5BÄ

ipv6 pim register-source { *ipv6_local_address* | *interface-type interface-number* }

no ipv6 pim register-source

Ï-DAÐ¥

–D	Ð¿Ä

ipv6_local_address	*bÎF* IPV6 0¥ł¸X®
interface-type *interface-number*	*bÎFX* ipv6 0¥ł¸X®

Ï5¸Õ!5BÐ ¥ł¸X® IPV6 S*ä®Eº¸X DR y·

ÏQ¸Ð <ã

Ï5*Ð G!5B,X¹ÖÆ¸XÄ RP ¥ł¸Ê/¥ł¸X® IPv6 0¸ÂXÆÕ

Register-Stop y[Ä

!8G!5BÐ"¸ÏG6(¸Xy¦Æ PIM-SMv6Ä

ÏG!5B_Ð 5XLMLHFRQILJLSYSLPUHJLVWHUVRXUFH

5XLMLHFRQILJLSYSLPUHJLVWHUVRXUFHJL

ÎÏGQÐ

Q¸	Æ Ä
-	-

ÏGÄÐ -

7.25 ipv6 pim register-suppression

G!5B¥ÊÆÐQ¸X no 6ÐPyl@

-

7.26 ipv6 pim rp-address

G!5BM-ÕRPÄ¾ÃQ¸X no 6ãÄG!5BÄ

ipv6 pim rp-address *ipv6_rp-address* [*ipv6_access_list*]

no ipv6 pim rp-address *ipv6_rp-address* [*ipv6_access-list*]

Ï–DAêð

–D	ÆÄ
ipv6_rp-address	RP ¸X IPv6
ipv6_access_list	é*ü IPv6 ACL Lê§M-Õ RP á¸X48È *ipv6_access-list*ÐÑ acl

Ï5¸Õ!5BÐ M-Õ RP

ÏÐÇð <ã

ÏÕ*Ûð Õ!5B4¼M-Õ RPÑM-Õ RP ` C-RP ßÄ

¼NMÖ

1ÛpEÆ› BSR ` RP M-Õ!5BßÆ*¡Õ!5BÄ

1Ø*{è<M-Õ!5B RP Õ!5BÞX4ÆÆ*ü ACLÅÞX4ÆÆ

*ü ACLÐð RP M-ÕÑ¾G!5BS*ÜÄ

1ÛpÝM-Õ RP ábÞÆPv6 P¸XM-Õ RP ÚÝG*ÜÄ

1ÛÅ ACL n¸XAÆßÞX4ÆÆ,ÑÝX4ÆÄ

1hÆ!5BÑ-ÕX RP ßÝÎb48ÈXM-Õ RP 4ãÆ!ß8ÈM-

Õ4ÞM-Õ RP 4¸XJÈ<48ÆJÈ<Ý IPV6 EæÞ8ÈÞ RPÈ

ÞÈ IPV6 Ð¸XFwÞj>EÄ

1AÆ8ÞM-Õ RP ÑX4Ð8EÞM-Õ RP ÆÆEÞ

0 RP Ä

Ï!5B_Ð G!5BM-ÕRP ábÆ8È ff66::6666/64

```
5XLMLHFRQILJLSYSLPUSDGGUHVVDFO
5XLMLHFRQILJLSYDFFHVVOLVWDFO
5XLMLHFRQILJLSYDFOSHUPLWLSYDQ
```

ÏÎGQÞ

Q¸	ÆÄ
-	-

ÏÄêð -

7.27 ipv6 pim rp-candidate

G!5BC-RPÄ¾ÃQ¸X no 6ãÄG!5BÄ

ipv6 pim rp-candidate *interface-type interface-number* [**priority**

no ipv6 pim rp-candidate [*interface-type interface-number*]

Ï-DAèð

–D	Ë.Ä
interface-type *interface-number*	*yéÄ* !8y· C-RP
priority *priority-value*	*ûÙ* C-RP ,X¾{ 8Ëè 0-255è¸Õ 192
interval *seconds*	*Æ* BSR ¥ÉÕ C-RP #'C¸X<á)!/ßÈè 1-16383è¸Õ 60
group-list *ipv6_access-list*	*éü* IPv6 L§ C-RP á¸X48è Qá acl

ß¸Õ!5BÐ ´ C-RP

ÙQÞð <ã

ß*ôð ü PIM-SMV6 #AÈÉCÃÎXEå RPT ¶6.& RP 8Vä BSR E{*é
,X C-RP nå BSR)• C-RP #'Cè+ BSR åÞ PIM ¥Ä
8ŁÔûyÞMn48ÞXEÝ RPÈwAQÞ acl EÝMÄÔÞK48ÞXAu1k
Þ¼ permit ,X aceê deny ,X ace E> 4ÐÙu1kÄ
VpéD **group-list** ipv6_access-listêb¥Ä

Ù!5B_Ð G!5BC-RPèb48è ff66::6666/64

```
5XLMLHFRQILJLSYSLPUSFDQGLGDWHJLSULRULWLJURXSOLVWDFOLQWHUYDO
5XLMLHFRQILJLSYDFFHVVOLVWDFO
5XLMLHFRQILJLSYDFOSHUPLWLSYDQlI
```

ÏÙGQÞ

Q¸	Ë.Ä
-	-

ÙGÄèð -

7.28 ipv6 pim rp-register-kat

G!5BRP ¼ÎX(S,G) ,X,#ÊèBQ¸X no 6èµ¸Õ

ipv6 pim rp-register-kat *seconds*

no ipv6 pim rp-register-kat

Ï-DAèð

–D	Ë.Ä
seconds	KAT nÊ¸XÊÈÄ)!/ßÈè 1-65535è¸ÊÊÈ* 3 + ¼#ÊÈÄ

ß¸Õ!5BÐ –D5¸Õ

ÜQþ <ã

Ü*Ô KAT nÊhÔ8 DR AÞXtÝÊÈ* 3 + Ù#ÊÈ RP ÑÑÔ DR a õ
ÆÞ¦!(S,G) (ÕYÊÈâ#-Ý,X#Ä

ÜG!5B_Đ 5XLMLHFRQILJLSYSLPUSUHJLVWHUNDW

ÏÖGQÞ

Q¸	Æ.Ä
-	-

Ï5,Õ!5BÐ yþ PIM-SMv6

ÏQ¸Ð yã

ÏS*Ô µ PIM-SMv6 !ÀËG!5BÄ¢C¬ÃE¥ÖÕS|Z PIM-SMv6ÈÁ
6ÑÑÐBy[Ä
µ PIM-SMv6 ,XÊ MLD ÞÞ¦ÈÔ|G!5BÄ
G!5BA¹Q¸XÊZpî„ Failed to enable PIM-SMv6 on <yá >, resource temporarily unavailable, please try againÀË ÃG!5BA¹Q¸Ä
G!5BA¹Q¸XÊZpî„PIM-SMv6 Configure failed! VI F limit exceeded in NSM!!! È</'
!4ÿG!5B,XDGÆE'AÕ!5B,X4ÿÞÞXpL¸ÔÄ¼ÿÔ PIM-SMv6
h*ÀË8ÔÞ,X PIM-SMv6 ê PIM-DMv6 yÄ
Vpy2O_L{F2O_ÞÝ¼ 6Over4 G!5BL{FÃ 6Over4 GRE L{FÃ 6Over6 G!5BL{FÃ 6Over6 GRE L{FÕ IPv6 4šs6ÃWÆXL{FyÞÃš6ÃÄ¸Ã
CÈÊ> 4ÿ[,XyÆÃÕ
4ÿL{FÑÃÞL{FÆDB,X Qos/ACLÄ

ÏG!5B_Ð
```
5XLMLHFRQILJLQWHUIDFHJL
5XLMLHFRQILJLILSYSLPVSDUVHPRGH
```

ÏÎGQÞ

Q¸	ÆÄ
-	-

ÏGÄÈÞ -

7.31 ipv6 pim spt-threshold

| SPT ÔÏÐQ¸X no 6ÆGKÁs6ÃÑ

ipv6 pim spt-threshold [**group-list** *ipv6_access-list*]

no ipv6 pim spt-threshold [**group-list** *ipv6_access-list*]

Ï-DAÈÞ

–D	ÆÄ
group-list *ipv6_access-list*	éü IPv6 ACL LÆÆACŒ SPT ÔÏ¸X48ÐÆ ipv6_access-listÕá aclÄ

Ï5,Õ!5BÐ µá SPT ÔÏ

ÏQ¸Þ <ã

ÏS*Ô VpéD **group-list** ipv6_access-listÈÁ4ÆE> SPT ÔÏÄ

ÏG!5B_Ð | SPT ÔÏÈÔÏÆ fe80::2d0:f8ff:fe22:33adÁ 4˜ ff66::6666/64

```
5XLMLHFRQILJLSYSLPVSWWKUHVKROGDFO
```

```
5XLMLHFRQILJLSYDFFHVVOLVWDFO
5XLMLHFRQILJLSYDFOSHUPLWLSYIHGIIIIHDGII
```

ÏĈGQÐ

Q¸	Ł.Ä
-	-

ĬGÄâê -

7.32 ipv6 pim ssm

| SSMÆ5B SSM 48âêQ¸X no 6ĞGKÁ SSMÄ

ipv6 pim ssm { **default** | **range** *ipv6_access-list* }

no ipv6 pim ssm

Ï-DAâê

–D	Ł.Ä
default	SSM 5,Ø8È FF3x::/32
range *ipv6_access-list*	é*ü* IPv6 ACL Lê SSM 48âêá aclÄ

ĭ,Ø!5BÐ GKÁ SSM

ĬQĵÐ <ã

ĬŠ*Ð Vpº ü PIM-SMv6 5¼ñ*ü SSMÈ¥OG!5B!8QĵÄ

ĬG!5B_Ð | SSMÆ5B SSM 48âêÐ fe80::2d0:f8ff:fe22:33adÃ˜ ff32::3333/64

```
5XLMLHFRQILJXUHWHUPLQDO
        RQILJLSYSLPVVPUD0PÀÐ
```

ï5,Õ!5BÐ C-RP ¼{PÞM-Õ RPÄ

ÏQþÐ <ã

ïS*Ûð G!5BAÐQþÐ-Õ!5B,X RP ¼{PÞ BSR E¸Ý¥ RPÄ

ÏG!5B_Ð 5XLMLHFRQILJLSYSLPVWDWLFUSSUHIHUUHG

ÏÎGQÞÐ

Q¸	£ÄÄ
-	-

ÏGÄÐð -

7.34 ipv6 pim triggered-hello-delay

G!5By¡X Triggered-Hello-Delay ¸XÊÐBQ¸X no 6ðð5¸Ð

ipv6 pim triggered-hello-delay *seconds*

ñbÞ[pMÐy602 r6ÞÐE llo-lE0 1 ñ0 c 0 w 14.213 0 ñ5 ÞF25.22 -1.-7.007 -1.722ïS*ñ¢119.94 645.8 mh4640 645240161464ñ

Ï-DAèð

–D	Ë.Ä
-	-

Ï5,Õ!5BÐ -

ÜQþÐ (Mèãâãã

ÏÕ*ÐÐ -

ÜG!5B_Ð

```
5XLMLHVKRWGHEXJJLQJ
3,060HEXJJLQJVWDWXV
3,0SDFNHWGHEXJJLQJLVRQ
```

ÏÎGQÞÐ

Q¸	Ë.Ä
-	-

ÜGÄèð -

7.36 show ipv6 pim sparse-mode bsr-router

¦ß BSR ÇÄ

show ipv6 pim sparse-mode bsr-router

Ï-DAèð

–D	Ë.Ä
-	-

Ï5,Õ!5BÐ -

ÜQþÐ (Mèãâãã

ÏÕ*ÐÐ -

ÜG!5B_Ð

```
5XLMLHVKRWSYSLPVSDUVHPRGHEVUURXWHU
3,0YRWRVVWUDSLQIRUPDWLRQ
7KLVVVWHPLVWKHRWRVWUDS5RXWHU%5
%5DGGUHVV
8SWLPH%53ULRULW\DVKPDVNOHQJWK
1H[WERRWVWUDSPHVVDJHLQ
5ROH%QGLDWH%53ULRULW\DVKPDVNOHQJWK
6WDWH(OHFWHG%5
%QGLDWH53*LDELW(WKHUQHW
%YHUWLVHPHQWLQWHUYDOVHFRQGV
1H[W%QGB53BDGYHUWLVHPHQWLQ
```

ÏÎGQÞ

Q¸	Ë.Ä
-	-

ËGÄß

-

7.37 show ipv6 pim sparse-mode interface

¦ß PIM-SMv6 yÇ.Ä

show ipv6 pim sparse-mode interface [*interface-type interface-number*] [**detail**]

Ï-DAß

–D	Ë.Ä
interface-type *interface-number*	*yá.Ä*
detail	**Ñ¢**

Ëƀ,Ø!5BÐ

-

ËQÞ

(Mãõõã

ËƱ*Ô

-

ËG!5B_Ð

```
5XLMLHVKRZSYSLPVSDUVHPRGHLQWHUIDFHGHWDLO
*LJDELW(WKHUQHWYLI
GGUHVVIHGIIIIHDG5IHGIIIIHE
+HOORSHULRGVHFRQGV1H[W+HOORLQVHFRQGV
7ULJJHUHG+HOORSHULRGVHFRQGV
6HFRQGDUDGGUHVVHV



1HLJKERUV
IHGIIIIHE
```

ÏÎGQÞ

Q¸	Ë.Ä
-	-

ËGÄß

-

7.38 show ipv6 pim sparse-mode local-members

¦ß PIM-SMv6 yÞX MLD Ç.Ä

show ipv6 pim sparse-mode local-members [*interface-type interface-number*]

7.40 show ipv6 pim sparse-mode neighbor

¦Ï5ÇÄ

show ipv6 pim sparse-mode neighbor [**detail**]

Ï-DAèê

–D	ÆÄ
detail	**Æ**

ï5,Õ!5BÐ -

ÜQÞÐ (Mèêêê

Ü*ÐÔ -

Ü!5B_Ð

5XLMLHVKRZSYSLPVSDUVHPRGHQHLJKERUGHWDLO
1EUIHGIIIIHE*LJDELW(WKHUQHW
([SLUHVLQVHFRQGV
6HFRQGDU\DGGUHVVHV

ÎÜGQÞÐ

Q¸	ÆÄ
-	-

ÜÄèÐ -

7.41 show ipv6 pim sparse-mode nexthop

¦ÔQX,ÜGÐQXyÆmetric 1Ä

show ipv6 pim sparse-mode nexthop

Ï-DAèê

–D	ÆÄ
-	-

ï5,Õ!5BÐ -

ÜQÞÐ (Mèêêê

Ü*ÐÔ -

Ü!5B_Ð -

ÎÜGQÞÐ

Q¸	ÆÄ
-	-

Ï G!5B_Ð

```
5XLMLHVKRZSYSLPVSDUVHPRGHUSKDVKII
53
,QIRVRXUFHYLDERRWVWUDS
3,0Y+DVK9DOXH
53YLDERRWVWUDSSULRULWKDVKYDOXH
```

ÏÎGQÐ

Q¸	Ë Ä
-	-

Ï GÄÐ

-

7.44 show ipv6 pim sparse-mode track

¹4Au,XÐÈÈÕX PIM y[,XÐÄ

show ipv6 pim sparse-mode track

Ï-DAÐ

–D	Ë Ä
-	-

Ï5,Õ!5BÐ

-

ÏQÐ

(MÃÃÃ

Ï S*Ð

2Ï¼ÊÔ5B4²Au,XÐÈÈA*ü **clear ipv6 pim sparse-mode track Ê**

G¸¸8 PIM y[,XAuD<Ä

Ï G!5B_Ð

```
5XLMLHVKRZSYSLPVSDUVHPRGHWUDFN
3,0YSDFNHWFRXQWHUVWUDFN
(ODSVHGWLPHVLQFHFRXQWHUVFOHDUHG
5HFHLYHGVHQW
9DOLG3,060YSDFNHWV
+HOOR
-RLQ3UXQH
5HJLVWHU
5HJLVWHU6WRS
VVHUW
0
&3
3,00Y*UDIW
3,00Y*UDIWSN
3,00Y6WDWH5HIUHVK
8QNQRZQ3,0Y7SH
(UURUV
```

0DOIRUPHGSDFNHWV
ØGFKHFNVXPV
6HQGHUURUV
3DFNHWVUHFHLYHGZWKXQNQRQ03,0YYHUVLRQ

ÏĈGQĐ

Q¸	Ł Ä
clear ipv6 pim sparse-mode track	-

ĠÄð

-

8 MSDP

8.1 clear ip msdp peer

G5Bâ MSDP Í1¦X TCP E¥yÈ#Ù8!8 MSDP Í1¦X4ªAuµCÄ

ÏQ¸Ð <ã

Ï5*ÐÎ ¢ MSDP Í1¥9,X SA #CÃõÑE› Peer-RPF 5à¥ÏpÚ MSDP Í1'A'
5BTA-x MSDP Í1È MSDP Í1¥9,X SA #CÔ6ÑE› Peer-RPF Ä
VpéD **prefix-list** *prefix-list-name*ÊÝ SA #CÄ
VpúD **prefix-list** *prefix-list-name*ÊÝ SA #CÄ
VpúD **prefix-list** *prefix-list-name*ÊÝ RP ¥CK,X
SA #CÄ

ÏG!5B_Ð A5B MSDP Í1' 172.16.33.1 TA-xÍ1'

```
5XLMLHFRQILJLSPVGSSHHU
5XLMLHFRQILJLSPVGSSHHU
5XLMLHFRQILJLSPVGSGHIDXOWSHHU
```

ÏÎGQ¸Ð

Q¸	E.Ä
ip msdp peer connect-source	ï¿Ð MSDP Í1'

ÏGÄÃè

-

8.5 ip msdp description

MSDP Í1#ïE¸ÊÃ*ÄQ¸X no 6ã8E¸ÊÄ

ip msdp description *peer-address text*

no ip msdp description *peer-address*

Ï-DAÃè

–D	E.Ä
peer-address	MSDP Í1' IP Ä
text	(pÃF5–Ïd¸Q¹S(…nõ–32ÈV#3(…nõÉ E2P¾47ÃÊSƒèÏ'SƒèÏPdeB–6õ¸Q¹G!5@

ÏGÄê -

8.6 ip msdp filter-sa-request

E$ MSDP Í1¥,X SA AËCÄ*ÄQ¸X no 6ÃÆE$Ä

ip msdp filter-sa-request *peer-address* [**list** *access-list*]

no ip msdp filter-sa-request *peer-address*

Ï–DAê

–D	ÆÄ
peer-address	MSDP Í1',X IP
list *access-list*	é*ü* ACL 9L¢48È

ï5,Õ!5BÐ y¢97¾ MSDP Í1',XÝ SA AËCJ4h1(Ä

ÏQ$ê <G!5Bã

ïS*Ðê LÔ{¾ SA AËCAG¥J4h1(Ã*ÄQ¸Ä

VpéD **list** *access-list*Ã SA AËCFÑÑ9Ä

VpúD **list** *access-list*È ACL ãÃX SA AËCFÑÑ9Ä

VpúD **list** *access-list*Ê ACL ¸ÿ« ACL AQX SA AËCÈ²XÓÑ9Ä

ïG!5B_Ð E$' 172.16.223.1 ¥,X SA A¿[ÊBÈ 224.0.1.0/24

5XLMLHFRQILJLSPVGSILOWHUVDUHTXHVWOLVW

5XLMLHFRQILJDFFHVVOLVWSHUPLW

ÏÎGQÐ

Q¸	ÆÄ
ip msdp peer connect-source	ïê MSDP Í1'

ïGÄê -

8.7 ip msdp mesh-group

Ô MSDP Í1t9<EÆ?ÄS*ÄQ¸X **no 6ê5Ë**

ip msdp mesh-group *mesh-name peer-address*

no ip msdp mesh-group *mesh-name peer-address*

Ï–DAê

–D	ÆÄ
mesh-name	<EÆ?Ãê
peer-address	MSDP Í1',X IP

ï5,Õ!5BÐ á¨EÆ?ÄÌMSDP Í1p9Ï<EÆ?˜

ÏQ$ê <G!5Bã

Ï*Ð t9ÊEE‡,˜XÝ MSDP Í‰ÎÐÝ MSDP Í‰G2Ä

¢E‡4,˜X SA #CÊE› Peer-RPF Ä

ÊE‡4,˜y,X SA #CÊEXÊE‡4,˜XJ‡4,˜Ä

Ï!5B_Ð Ú MSDP Í' 192.168.1.3 t9<EÊ‡4˜ msdp-mesh

5XLMLHFRQILJLSPVGSPHVKJURXSPVGSPHVK

ÎÏGQÐ

ip msdp password peer *peer-address* [*encryption-type*] *string*

no ip msdp password peer *peer-address*

Ï–DAèð

–D	Ë Ä
peer-address	MSDP Í Ľ';X IP
encryption-type	šÕ4{ÞÆ 0 ` 7ø Ä Ê 7 Ôß Õ 0Ä
string	S ú TCP MD5 AxA¸•Xš Õ 8Ø*t 2O_ 0 Ê 80 þ0ú S*t 2O_ 7 Ê 160 þ0ú

Ï5,Õ!5BÐ Þ> MD5 tš

ÏQþð <G!5Bã

Ï5*ðð LÔí MSDP Í Ľ';XDÑ> PÆÆÊ MSDP Í Ľ';X TCP E ÿE> MD5 tš MSDP Í Ľ'NOE> Í Ľ,XG!5BÆÆÕO,è ÿ6ãÑÄ VpG!5B6ÆÆÆe!,XÀÆS*¸ÞÕÆÈYÆ VpAÔ!5BZ MD5 tÆ MSDP Í Ľ'G!5BÈgÎVÄ:#CÖ 7 8 7+0GLJHVW127+H[SHFWHGÆXWRXQG VpAÆÔ MSDP Í Ľ'G!5B,X MD5 šÕÆEgÎVÄ:#CÖ 7 8 7+0GLJHVWIDLOHGIRU!

0 TCP 0

0 MSDP MSDP

0

7 TCP

TCP 7 7

7 show run 7

MSDP 3.3.3.3 7 123456 show run

show run ip msdp password peer 3.3.3.3 7 110174 110174

show run ip msdp password peer 3.3.3.3 7 072d50 072d50

show run ip msdp password peer 3.3.3.3 7 15595e 15595e

Ï!5B_Ð â MSDP Í Ľ' 10.32.43.144 ,X TCP E ÿG!5B MD5 šÕ test

5XLMLHFRQILJLSPVGSSDVVRUGSHHUWHVW

ÏÌGQÞ

Q¸	Ë Ä
-	-

ÏGÄê -

8.10 ip msdp peer connect-source

#ïþÔ MSDP Í‰Ë*ÄQ¸X **no 6ê8** MSDP Í‰Ä

ip msdp peer *peer-address* **connect-source** *interface-type interface-number*

no ip msdp peer *peer-address*

Ï–DAê

–D	ÊÄ
peer-address	MSDP Í‰¦X IP Ä MSDP Í‰S*ü IP ÄÀÔÊŸ TCP Eÿ¿Ä
interface-type *interface-number*	yÃ¸S*ü loopback yÄ AÊ*ü8y¡X IP â MSDP Í‰ÔŸ TCP Eÿ¿Äp !8yüÓ!5B IP ÿ(Õ shutdownÈv MSDP Í‰' ,XG2ÕÄ

Ï5,Õ!5BÐ ´ MSDP Í‰'

ÏQê <G!5Bã

ÏS*Ð AÊü MSDP Í‰KÊŸ TCP Eÿ¿Ä

S*ü **ip msdp peer** *peer-address* **connect-source** *interface-type interface-number*Ø

ž MSDP Í‰¦XEÿ¿Ä MSDP Í‰ÞNOE> Í‰,XG!5BÄ

ÏG!5B_Ð â 192.168.5.1 ÔŸ MSDP Í‰G2ÿ loopback 0

```
5XLMLHFRQILJLSPVGSSHHUFRQQHFWVRXUFHORRSEDFN
```

ÏÎGQÞÐ

Q¸	ÊÄ
show ip msdp peer	**/** MSDP Í‰¦XÇ

ÏGÄê -

8.11 ip msdp redistribute

L$ MSDP ¥X (S,G)Ç‰Ë*ÄQ¸X no 6ê‰LÄ

ip msdp redistribute [**list** *access-list*] [**route-map** *route-map*]

no ip msdp redistribute

Ï–DAê

–D	ÊÄ
list *access-list*	éü ACL n(S,G) ÐÈ
route-map *route-map*	éÇÃÇ(S,G) ÐÈ

Ï5,Õ!5BÐ ü RP ÞX46ÇÇ(S,G) FÑ MSDP ¥

ÜQþ <G!5Bã

Ü5*Ô **ip msdp redistribute** ßQÜ**ý5B**Ø,G) Q¢È
¥A,X(S,G) Q¢!6Ñ MSDPÄ
aÅpúD **list** *access-list*Ø ACL ,X(S,G)Q¢!Ñ
bÅpúD **route-map** *route-map*Ø route map ,X(S,G)Q¢!ÞÑ
cÅpêÈþD Ø!5Ê X(S,G) Q¢!ÞÑ
dÅpÿÈ–DØ(S,G) Q¢Ä
GÉÇ6(route-map ,XS*ØÖ
aÅp route-map æÈ¸Ý4ØQ¢
bÅpùÝ BGPÈ¸Ý4ØQ¢
cÅÔÃÈu1kû,X AS-PATHÅÈ7%XÈÈÔÃ9¢ÃÚ
,X AS-PATHÞ7%XÈÐ AS ,X AS-PATHÍÄÅ AS-PATH h*ü route-map
,X AS-PATH G!ÈG!4ßÈE¸ßÄ
_Ö RP¦È BGPÈ AS Ë 100ÈÉ6(,X route-map á re-route-mapØÑ¡
Ý,X4ØQÈ route-map A5BÝJ AS ,X AS-PATH G!Ø route-map ` as-path
ACL ,XG!5B(!Ø‰

```
URXWHPDSUHURXWHPDSSHUPLW
PDWFKDVSDWK
LSDVSDWKDFFHVVOLVWSHUPLWB
```

Ü G!5B_Ð ÆÇE MSDP ¥Øü 200.200.200.0/24 8ÈÆÃü 225.1.1.0/24 8È,X(S,G)Q¢

```
5RXWHUFRQILJLSPVGSUHGLVWULEXWHOLVW
5RXWHUFRQILJLSDFFHVVOLVWH[WHQGHG
5RXWHUFRQILJH[WQDFOSHUPLWLS
```

ÏÎGQÐ

Q¸	Ë¢Ä
ip msdp sa-filter in	**G5B** SA #Ç,X90E¸$
ip msdp sa-filter out	**G5B** SA #Ç,XÛ0E¸$

Ü GÄÀè -

8.12 ip msdp sa-filter in

G!5BSA #Ç,X90E¸$Ä*Ä¢Q¸X no 6ê890E¸$Ä

ip msdp sa-filter in *peer-address* [**list** *access-list*] [**route–map** *route-map*] [**rp-list** *rp-access-list*] [**rp-route-map** *rp-route-map*]

no ip msdp sa-filter in *peer-address*

Ï–DAè

–D	Ë¢Ä
peer-address	MSDP Í¦,X IP Ä
list *access-list*	û(S,G) ,X}– IP A¥Â<ÆQ{¾4ØQ¢(S,G) AÆÈÄ

route-map *route-map*	ûÝ(S,G) ,XCÃ,X AS-path ß¦!8CÃØÝ ,X AS-Path G!,X4ßÇ(S,G) !6ÑÊÄ
rp-list *rp-access-list*	ûÝ RP ,XÊÝKÂ<ÆÐ{¾ RP Ñ,X4ß ÇÇ(S,G) AÆÊÄ
rp-route-map *rp-route-map*	ûÝ RP ,XCÃ,X AS-Path ß¦!8CÃØÝ ,X AS-Path G!,X4ßÇ(S,G) !6ÑÊÄ

Ъ,Õ!5BÐ yÝ MSDP Ílý,X SA #Ċ

ÜÇþ <G!5Bã

Ъ*ûÐ VpG!5BÇÈÇÊÝÂ<ÆÜÃÆÝg9,X SA #ĊÍ<FÆÇÄ
VpS*ü **list** ê **route-map** ÇÊÝ SA #Ċ,X!ÇÝß(S,G) ÆÇ‡
EÇGK+Ñ,XÈÇÝß(S,G) ÃyÄ
VpS*ü **rp-list** ê **rp-route-map** ÇÊÝA #Ċ,XÇX RP Æ6ÇÝ‡
EÇGK+Ñ,XÈwEÞ SA #ĊÃyÄ
VpS*ü **list** Ñ**route-map** Ã **rp-list**Ã **rp-route-map** ÇÊÝ SA #Ċ
,XÇÝß(S,G) ÈVOÇÝ,XGK+Ñ,XÈÆÝyÄ
90E$G6(route-map ,XS*ÆÝ
aÝp route-map ÆÇÝX4ßÇ
bÝpú¡Ý BGPÈÇÝX4ßÇ
cÆÔÃÆu1kû¸X AS-PATHÆÆ7%XÈÈÔÃ9ĊÃú
,X AS-PATHÞ7%XÈÞ AS ,X AS-PATÍÆÅ AS-PATH h*ü route-map
,X AS-PATH G!ÈG!4ÇÈÆ$ÇÄ

ÜG!5B_Ð G!5BE$7Í¼ 10.234.1.43 ,XÝ SA #Ċ

```
5XLMLHFRQILJLSPVGSSHHU
5XLMLHFRQILJLSPVGSVDILOWHULQ
```

ÏÎGQÞ

Q¸	Æ Ä

list *access-list*	ûö6*,X}÷ IP AKÂ<ÆÐ{ø4ßÇ¿È GÅÆÆEÄ
route-map *route-map*	ûö(S,G) ,XCÃÆÆÄ S ,XCÃ,X AS-path ß!8CÃØ ,X AS-Path G!,X4ßÇ(S,G) !6ÑEÄ

peer-address	MSDP Íl',X IP

ÏGÄê -

8.16 ip msdp timer

G!5BTCP GĘ₹KÈhŠ*ÄQ¸X no 6ää5,Õ

ip msdp timer *interval*

no ip msdp timer

Ï–DAê

–D	ĘÄ		
interval	TCP GĘ₹KÈhÞ/ßÈ	1-60È¸Õ	30

Þ¸Õ!5BÐ –D5,Õ

ÜQê <G!5Bã

Š*Ð ü TCP GĘ₹KÈhÊÈØÈĘ÷0ÃX MSDP Í17Ç₹KÕ TCP Eÿ@h*CÈ
ÆÉó MSDP ÍG2ÏX/Ê TCP GĘ₹KÈhAÄ

ÏG!5B_Ð A5B TCP GĘ₹ÊXKÈh 20sÄ

```
5XLMLHFRQILJLSPVGSWLPHU
```

ÎÕGQÞ

Q¸	ĘÄ
-	-

ÏGÄê -

8.17 ip msdp ttl-threshold

L$ SA #CÞX4ÐBÞX TTL Š*ÄQ¸X no 6ãLÄ

ip msdp ttl-threshold *peer-address ttl-value*

no ip msdp ttl-threshold *peer-address*

Ï–DAê

–D	ĘÄ		
peer-address	MSDP Í';X	IP	
ttl-value	TTL ØÈ	0-255È¸Õ	0

Þ¸Õ!5BÐ L$

ÜQê <G!5Bã

È w4ÐDBy[ú SA #Ć9/Jè9/4ÐDBâX SA #ĆŒÆÕ MSDP Íl
Ä
AÇQ¸Æ¡ SA #Ć4ÐDB,XÆÕ¡ SA #Ć,X4ßC(S,G) ,XÆÕ

G!5BÍl' 192.168.10.1 ,X TTL KÜ 8
5XLMLHFRQILJLSPVGSWWOWKUHVKROG

Q¸	ÆÄ
-	-

-

v ip msdp count

/ SA #Ć{*ôX¼4¨XDGÆ7¾ MSDP Íl'X SA #Ć4ç5,ÊGÆÄ

show ip msdp count [*as-number*]

–D	ÆÄ

	_Ö 200.200.200.200 : 2 ></¢ MSDP Íl' 200.200.200.200 :4 2 5 SA 5,Â
<asn>: <# sources>/<# groups>	RP ,X7ÿÿÈ RP ¢K,X6D4ÐÄ _Ö00 : 1/2 ></7ÿÿ³ 100 Y,X RPÈ 1 µ6` 2 µ4Ä
Total entries	¢ MSDP Íl',XÝ SA 5,ÐGÆ _Ötotal entries: 2 ></¢ MSDP Íl',XÝ SA 5 ,ÐG£ 2 µÄ

ÏÖGQÐ

Q¸	Æ
-	-

ÖGÄè -

8.19 show ip msdp mesh-group

/<EÆ¾¯XQ¢

show ip msdp mesh-group

Ï–DAè

–D	Æ
-	-

Ö5,Õ!5BÐ -

ÖQÐ (Mèèè

Ö*Ð -

ÖG!5B_Ð

```
5XLMLHVKRZSPVGSPHVKJURXS

063SHHUVLQHDFK0HVKJURXSÈHVKJURXSQDPH!SHHUV!

PVGSPHVK
```

6$HVSRQVHVRXW
DWD3DFNHWVLQRXW

+!‰	AÊ£
MSDP Peer	MSDP Í1¦X IP Ä
AS	MSDP Í12,X7ø¼Ÿp7ø¼ÐÏ unknownÄ
State:	MSDP Í1(Õ
Connection source:	TCP E§*¡X8,XyÈBy¡X IP Ùp!8y¼u Ý IP È wí8y¡X IP /Ünknown Ä
MD5 signature protection on MSDP TCP connection: enabled	Vp4- MSDP Í1¦X TCP E§G!5BZ MD5 tÈ8+!‰ È8+!‰
Peer is member of mesh-group MSDP	Vp MSDP Í1t9≥EE¼È wÚ8+!‰ /!8+!‰
Uptime(Downtime):	MSDP Í1E¤ ÊÈ 0ÊÈ
Messages sent/received:	¢ MSDP Í1¥£Õ SA #Œ,XDG£
SA Filtering:	SA Eg9/ EgÈp
SAs learned from this peer:	¢ MSDP Í1'4,X SA DG£
SAs limit:	MSDP Í1¦X SA #Œ4ç1ÞG£
Data Packets in/out	Eg9/ EgÂÐB,X SA y[Þ

ÏŒGQÞ

Q¸	£Ä
-	-

ŒGÄÈ -

8.21 show ip msdp rpf-peer

,S

53)SHHU
53)UXOH3HHULVRQOD DFWLYHSHHU
53)URXWHPDVN1RWXVHG
53)WSH1RWXVHG

+!‰	AÈ
RPF peer information for	û RP ,X RPF-Peer Ç
RPF peer	û RP ,X RPF-Peer
RPF rule	S*Æu1kû RP ,X RPF-Peer
RPF route/mask	û RP ,X5%‰Ð.Bn RPF-PeerÄ Æu1kû RP ,X RPF-PeerVÊpS*ü XÐS*ÇÃ +ÇÈw+!Æ Not-used È</ÞS*ü RP ,X5% !‰Ñ !VÐÄÞS*ü XÐC,X MSDP ÍÈBÊ Ý*ü RP ,XCÃÆÈ RPF route/mask +!‰ Not-usedÄ
RPF type	Au1kû RP ,X RPF-Peer Ê*ü X RP CÃ,XCÃ#AÄ Æu1kû RP ,X RPF-PeerVÊpS*ü XÐS*ÇÃ +ÇÈw+!Æ Not-used È</ÞS*ü RP CÃ ,XCÃ#AÄ !VÐÄÞS*ü XÐC,X MSDP ÍÈBÊ Ý*ü RP ,XCÃÆÈRPF type +!‰ Not-usedÄ

ÏÎGQÞ

Q¸	ÊÄ
-	-

ËGÄÆ -

8.22 show ip msdp sa-cache

/:4,X(S,G) Ç

show ip msdp sa-cache [*group-address* **|** *source-address*] [*group-address* **|** *source-address*] [*as-number*]

Ï–DAÆ

–D	ÊÄ
group-address	4˜
source-address	ß
as-number	SA #Ć{*ôX72¼ÄË

Ë5,Õ!5BÐ -

ËQÞ (MÆÆÆ

ËS*Ð VpùÐÈwTÆx/,ÝX(S,G) ÇÄ

Vpû Bwé E4Zp!8)ÈwAx
E 8 S 8 S ,XÝS,G) ¥p!84ÈwAxEþ
4 4˜ G 4 4˜ G ,XÝS,G) ¥pE 84ÈwÃ
/ C×
Vpû wÚ 8 S 4˜ GŸpÛ
,X Ý 4 ÈwÐC Ä

Ï!5B_Ð

```
5XLMLHVKRZSPVGSVDFDFKH
0636RXUFH6WLYH2FKHHQWULHV
530%36HHU

/HDUQHGIURPSHHU53)SHHU
6¥UHFHLYHG(QFDSXODWHGDWDUHFHLYHG
530%36HHU

/HDUQHGIURPSHHU53)SHHU
6¥UHFHLYHG(QFDSXODWHGDWDUHFHLYHG
```

ï5,Õ!5BÐ -

ÏQþÐ (Mãâãã

ïš*Ô ' PIM-SM ,X RP5ßâ(S,G) ¼ RP5ßâ!5BZ MSDP íÌÈÊ
EÊQ¸ÏÔ€K,X(S,G) µÄ
Q¿,X(S,G) µ4ÊÊÉ¿ÉÉ¸h,XQ¸ **ip msdp redistribute**)È¤(S,G) µ
C¤Ñ€K4- MSDP íÌÈÊÔ¿ÉÊÔÊ¸h,XQ¸ **ip msdp sa-filter out**)Ä

ïG!5B_Ð
```
5XLMLHVKRZSPVGSVDRULJLQDWHG
0636RXUFHßWLYH2ULJLQDWHGHQWULHV
53
53
53
53
53
```

+!‰	Aß

(192.168.23.78, 225.0.0.1)),(

8S1RGHVFULSWLRQ
RQSHHU$

Q¸	Ë Ä
Peer Address	MSDP Í1' IP Ä
AS	MSDP Í12,X7ø¼Ä
State	MSDP Í1'(Ê
Uptime/Downtime	MSDP Í1';XÛ0ßÊ
Reset-Count	MSDP Í1ÛÊ¾ÊÝ,X Ð
Sa-count	Ë Þ MSDP Í1y,X SA y[,XÞ
Peer-description	Ë Þ MSDP Í1';XËÄÈ¼ÝÞ Ë Þ MSDP Í1ÛÊÄ Ç È wÛo description Ä

ÏÛGQÞ

ѣ,Õ!5BÐ -

ÙQþ (Mã

9.4 ip igmp profile

p profileÈ9 profile Ä*AQ¸X **no 6è88** profileÄ

ip igmp profile *profile-number*

no ip igmp profile *profile-number*

Ï-DAè	–D	EÄ

ÜQ
<ã

Ü5*
ü IVGL VLAN

seconds	¦ÕÃ¸X5ðÈ/ÞÈ<	1-3600Ь¸Õ	300

Ь¸Õ!5BÐ

9.8 ip igmp snooping filter

L¹ßÃÑ,X4Ë*ÀQ¸X **no 6ÈLÄ**

ip igmp snooping filter *profile-number*

no ip igmp snooping filter *profile-number*

Ï-DAè

–D	Ë
profile-number	profile ,X4ßÈ 1-1024

Ï5,Õ!5BÐ AÇÆÄ˜

ÏQ¸ yã

Ï*Ð NVOÎ profileÈÑÌ **ip igmp snooping filter** profileÄ G!5B!8Q¸à0Ã Report

G!5B‰ IP ‰6ÑX!9PxÖ

1È‰ IP ‰6‰A5BTAx‰ IPÄ

2ÉÁMn VLAN/4Ô‰ IPÄ

Ï!5B_Ð *‰ IP ÈAx‰ IP 192.168.4.243È‰an1 4˜ 224.0.0.1 ,X‰ IP 192.168.4.241

5XLMLHFRQILJLSLJPSVQRRSLQJVRXUFHFKHFNGHIDXOWVHUYHU

5XLMLHFRQILJLSLJPSVQRRSLQJOLPLWLSPFYODQDGGUHVVVHUYHU

ÏÎGQÐ

Q¸	£Ä
ip igmp snooping source-check default-server	***‰ IP ‰6‰Õ5,‰ IPÄ

ÏÄÀ‰ -

9.10 ip igmp snooping max-groups

L¥6ÞÕXt9,X4¸XDGÄÆQ¸X no 6‰8LÄ

ip igmp snooping max-groups *number*

no ip igmp snooping max-groups

Ï-DAèð	–D	Ë-Ä
	vlan *vid*	ûÙ vlan

Ï5,Õ!5BÐ *ÙBs6Ñ

ÜQþÐ <ã

Ï5*ÐÙ CÃEý4?ÃÂ¼FÃÙÇÈ¿X0ÃÃÐÐ¼CÃEýs6Ñ
x67þ¼ IGMP Query/Dvmrp/PIM Hellp y[þÕÐÇÃEýÄ

Ï¨G!5B_Ð 4ŕNXßß6Ñ(ŕü profile 1)â IGMP Snooping filter(ŕü profile 2)G!Ü*Ä

```
5XLMLHFRQILJLSLJPSVQRRSLQJSUHYLHZ
5XLMLHFRQILJLILQW(WKHUQHW
5XLMLHFRQILJLILSLJPSVQRRSLQJILOWHU
```

ÏÎGQÐ

Q¸	ÆÄ
ip igmp profile	Õ profile
ip igmp snooping preview interval	**G5ßß**

Ï¨GÄß

-

9.13 ip igmp snooping preview interval

G!5B4ŕNXßßÆÆ*ÄÆQ¸X **no** 66ßÆÕ

ip igmp snooping preview interval *seconds*

no ip igmp snooping preview interval

Ï–DAß

–D	ÆÄ
seconds	NXßÈ/ßÈ 1-300Ê,Õ 60

Ï5,Õ!5BÐ –D5,Õ

ÏQß <G!5Bã

Ï¨Ô Ô -

Ï¨G!5B_Ð *ŕNXßß6ÑNXßÈ 100 /Ä

```
5XLMLHFRQILJLSLJPSVQRRSLQJSUHYLHZ
5XLMLHFRQILJLSLJPSVQRRSLQJSUHYLHZQWHUYDO
```

ÏÎGQÐ

Q¸	ÆÄ
ip igmp snooping preview	ŕNXßß6Ñ

Ï¨GÄß

-

9.14 ip igmp snooping querier

*ü IGMP Snooping Ä¶s6ÑÆQ¸X no 6ÊKÁs6Ñ

ip igmp snooping [**vlan** *vid*] **querier**

no ip igmp snooping [**vlan** *vid*] **querier**

Ï–DAß

–D	ÆÄ
vlan *vid*	Ô vlan

Ï,Õ!5BÐ	GKÁs6Ñ
ÜQ¸Ð	<ã
Š*ÛÐ	<¦A¶s6Ñü VLAN ¶A¶s6ÑVLAN þXA¶s6ÑÑ Vpü GKÁ¶s6Ñ VLAN þXA¶s6ÑFGKÄ
ÜG!5B_Ð	_ 1Ö*A¶s6Ñ

```
5XLMLHFRQILJLSLJPSVQRRSLQJTXHULHU
```

_ 2ÜÞ VLAN *A¶s6Ñ

```
5XLMLHFRQILJLSLJPSVQRRSLQJYODQTXHULHU
```

ÏÎGQ¸Ð

Q¸	£Ä

ÜGÄè -

9.15 ip igmp snooping querier address

G!5BIGMP Snooping A¶,XÞ IP ÄQ¸X no 6ã8!8Ä

ip igmp snooping [**vlan** *vid*] **querier address** *a.b.c.d*

no ip igmp snooping [**vlan** *vid*] **querier address**

Ï–DAè

–D	£Ä
vlan *vid*	Û vlan
a.b.c.d	Þ IP

Ï,Õ!5BÐ	-
ÜQ¸Ð	<G!5Bã
Š*ÛÐ	¦A¶s6ÑOA¶ÛÞÐ IP ÅA¶s6ÑÄ Vp VLAN ÛA¶,XÞ IP Š*ÛG VLAN þXG!5BÄ
ÜG!5B_Ð	_ 1Û IGMP Snooping A¶,XÞ IP

```
5XLMLHFRQILJLSLJPSVQRRSLQJTXHULHUDGGUHVV
```

_ 2ÜÞ VLAN Û IGMP Snooping A¶,XÞ IP Ö

```
5XLMLHFRQILJLSLJPSVQRRSLQJYODQTXHULHUDGGUHVV
```

ÏÎG0y1LÀ%L1%2%Ã)ÈÆ‚...(A¥)ÆHnö8rA!V) ÂX(yS)<XS#À...28%V8%V<XyA)2%V8%Hnö8rA!V3Ec–ÊÀ

ÏGÄê -

9.16 ip igmp snooping querier max-response-time

G!5BIGMP Snooping Á¶,XÛÊÃÉQ¸X no 6ää,Ã

ip igmp snooping [**vlan** *vid*] **querier max-response-time** *seconds*

no ip igmp snooping [**vlan** *vid*] **querier max-response-time**

Ï-DAê

–D	ÉÄ		
vlan *vid*	û vlan		
seconds	ûÃ	1-25È,Õ	10pt2m3 767r

Ï*Ð Vp VLAN ÞXG!5BÄ VLAN ÞXG!5BÄ

ÏG!5B_Ð _ 1Ö!5BÄ¶CYÊÈ

```
5XLMLHFRQILJLSLJPSVQRRSLQJTXHULHUTXHULQWHUYDO
```

_ 2Ö Þ VLAN G!5BÄ¶CYÊÈ

```
5XLMLHFRQILJLSLJPSVQRRSLQJYODQTXHULHUTXHULQWHUYDO
```

ÏÎGQÞ

Q¸	Ë Ä
-	-

ÏGÄÈ -

9.18 ip igmp snooping querier timer expiry

G!5BIGMP Snooping Ä¶,XCYÊÈQ¸X no 6ÈÕ,Ö

ip igmp snooping [**vlan** *vid*] **querier timer expiry** *seconds*

no ip igmp snooping [**vlan** *vid*] **querier timer expiry**

Ï-DAÈ

–D	Ë Ä		
vlan *vid*	Ù vlan		
seconds	CYÊÈ/Ë	60-300Ë,Õ	125

Ï,Õ!5BÐ –D5,Õ

ÏQÞÐ <ã

Ï*Ð *Ä¶s6ÑÑÑÝBÜp:B5Ù¶CYÊÈ'ÙÝÄ¶

ÎÄÝ[Ëx!Ä¶ÊKÔBEÄ

Vp,Ì VLAN ÆG!5BÄ¶CYÊÈ*ü VLAN ÞXG!5BÄ

ÏG!5B_Ð _ 1Ö!5BÄ¶CYÊÈ

```
5XLMLHFRQILJLSLJPSVQRRSLQJTXHULHUWLPHUH[SLU\
```

_ 2Ö Þ VLAN A5BÄ¶CYÊÈ

```
5XLMLHFRQILJLSLJPSVQRRSLQJYODQTXHULHUWLPHUH[SLU\
```

ÏÎGQÞ

Q¸	Ë Ä
-	-

ÏGÄÈ -

9.19 ip igmp snooping querier version

G!5BIGMP Snooping Ä¶E¤ ,X IGMP (ÄQ¸X **no** 6ää,Õ

ip igmp snooping [**vlan** *vid*] **querier version** { **1** | **2** }

no ip igmp snooping [**vlan** *vid*] **querier version**

Ï–DAè

–D	Ë*Ä
vlan *vid*	û vlan
1	IGMPv1
2	IGMPv2

ï5,Õ!5BÐ IGMPv2

ÏQ¸Ð <ã

ÏS*Ûð Ä¶Õ IGMPv1 ê IGMPv2Ä

Vp VLAN ÆG!5BÄ¶E¤ ,X IGMP (È*ü VLAN ÞXG!5BÄ

ÏG!5B_Ð _ 1Ø5BÄ¶E¤ ,X IGMP (

5XLMLHFRQILJLSLJPSVQRRSLQJTXHULHUYHUVLRQ

_ 2Ûð VLAN A5BÄ¶E¤ ,X IGMP (

5XLMLHFRQILJLSLJPSVQRRSLQJYODQTXHULHUYHUVLRQ

ÎÎGQÐ

Q¸	Ë*Ä
-	-

ÏGÄè -

9.20 ip igmp snooping query-max-response-time

G!5BÄ¶[ûÊÈ|õÕÊÈQ¸X **no** 6ää,Õ

ip igmp snooping query-max-response-time *seconds*

no ip igmp snooping query-max-response-time

Ï–DAè

–D	Ë*Ä
seconds	Ä¶[ûÊÈ/ÞÈ 1-65535È,Õ 10

ï5,Õ!5BÐ –D5,Õ

ÏQ¸Ð <ã

ÏS*Ûð ü IGMP BEîÄ¶[æÈ˜Ä’ÎG5B Ý¶Q¸X5ØnÊÈnÊÈÈ

query-max-response-timeŸpnÊCYÊxA0ðµ4ý[,X*èA'
ÊÑ0Ã IGMP Snooping ,Xä8Ä
ü IGMP (Mn4ÃY[èÃG5BA{Mn4¸X¦ÕX5ÕÊèÊÊ
KÈ query-max-response-timeŸpnÊCYÊxA0ðµ4ý[,X*È
ÃÊÑ0Ã IGMP Snooping ,Xä8Ä
Íb IGMPv3 ,X(Mn4ÈÃY[èÊ,XÐÑ

Ï¨G!5B_Ð G!5BÃY[ÕÊÈ 100sÖ

5XLMLHFRQILJLSLJPSVQRRSLQJTXHUHPD[UHVSRQVHWLPH

ÏÎGQÐ

Q¸	ÊÄ
-	-

Ï¨GÄè -

9.21 ip igmp snooping source-check default-server

*è IP ¹56ÕÃ5BTÃxè IPÄQ¸X no 6èGKÁs6Ñ

ip igmp snooping source-check default-server *source-address*

no ip igmp sooping souce-check

Ï¨DAè

–D	ÊÄ
source-address	TÃxè IP

Ï¨Õ¸Ø!5BÐ GKÁs6Ñ

Ï¨Qè <ã

Ï¨S*Ðè è IP ¹56ÑÑL¼¾#,XèÐÈs6Ñ2è¸X4¾#FÑÄ
è IP ¹56Ñ IP 4¹s6ÑÜÄ
G!5Bè IP ¹56Ñ!X!9PxÖ
1Êè IP ¹56ÕÃ5BTÃxè IPÄ
2ÊÁ(Mn VLAN/4Ôè IPÄ

Ï¨G!5B_Ð *è IP ÊÃxè IP 192.168.4.243Ïlan1 4˜ 224.0.0.1 ,Xè IP 192.168.4.241

5XLMLHFRQILJLSLJPSVQRRSLQJVRXUFHFKHFNGHIDXOWVHUVHU
5XLMLHFRQILJLSLJPSVQRRSLQJOLPLWLSPFYODQDGGUHVVVHUVHU

ÏÎGQÐ

Q¸	ÊÄ
ip igmp snooping limit-ipmc	(Mn VLAN/4Ôè IPÄ

Ï¨GÄè -

9.22 ip igmp snooping source-check port

*ÍÕ56ÃÑQ¸X **no 6ÉÁs6Ñ**

ip igmp snooping source-check port

no ip igmp snooping source-check port

ßÑl IGMPv1/v2 ,X Report y[Ê IGMPv3 ,X Report y[Á

Ï!5B_Ð *ü Report y[,Xes6Ñ

5XLMLHFRQILJLSLJPSVQRRSLQJVXSSUHVVLRQHQDEOH

ÎGQÐ		
	Q¸	Ë
	-	-

ÏÄß -

9.24 ip igmp snooping svgl profile

ûË» ü SVGL ßX48ÃQ¸X **no 6ß5ß**

ip igmp snooping svgl profile *profile-number*

no ip igmp snooping svgl profile

Ï-DAß		
	–D	Ë
	profile-number	profile 6ÞÑf Aßð GgÏ‡H~ß8l~ß8l– FIFÏvß8fÇ–ß8Qyûd–HG–Ñldc7ÇÐpÐ»80 1 Tf5.80735

ï‡,Õ!5BÐ L8E• VLAN ê²ª VLAN FÑÑ VLANÄ

ÏQÇÐ <ã

Ï*ÔÐ ' IGMP Snooping ,XE¤ ã SVGL ê IVGL-SVGL ÊÑ!5B!8QÄ

ÏG!5B_Ð ûE• VLAN VLAN3È VLAN VLAN 2Ñ Ã Ã 7Ö

```
5XLMLHFRQILJLSLJPSVQRRSLQJVYJOYODQ
5XLMLHFRQILJLSLJPSVQRRSLQJVYJOVXEYODQ
```

ÏÎGQÇÐ

Q¸	Ê.Ä
ip igmp snooping	Ì‡ IGMP Snooping JA5BE¤ ã
ip igmp snooping svgl vlan	**G5Ê** SVGL ÐXE• VLAN

ÏGÄÃÐ -

9.26 ip igmp snooping svgl vlan

ûE¤ ü SVGL ÐXE• VLANÊ Shared VLANÅQ¸X **no 6ê5Ñ**

ip igmp snooping svgl vlan *vid*

no ip igmp snooping svgl vlan

Ï–DAÐ

–D	Ê.Ä
vid	VLAN 4Ê,Õ 1

ï‡,Õ!5BÐ –D5,Õ

ÏQÇÐ <ã

Ï*ÔÐ ' IGMP Snooping ,XE¤ ã SVGL ê IVGL-SVGL ÊÑ!5B!8QÄ

ÏG!5B_Ð ûE• VLAN VLAN3È VLAN VLAN 2Ñ Ã Ã 7Ö

```
5XLMLHFRQILJLSLJPSVQRRSLQJVYJOYODQ
5XLMLHFRQILJLSLJPSVQRRSLQJVYJOVXEYODQ
```

ÏÎGQÇÐ

Q¸	Ê.Ä
ip igmp snooping	Ì‡ IGMP Snooping JA5BE¤ ã
ip igmp snooping svgl subvlan	**G5Ê** SVGL Ð$ VLAN

ÏGÄÃÐ -

9.27 ip igmp snooping tunnel

*ü QinQ Eâ IGMP y[,Xs6ÑQ¸X **no 6ÉÁs6Ñ**

ip igmp snooping tunnel

no ip igmp snooping tunnel

Ï-DAèð

–D	Ë-Ä
-	-

Ï5,Õ!5BÐ GKÁ8s6Ñ

ÏQ¸ð <â

ÏS*Ôð ÁØ IGMP Snooping JG!5BZ dot1q-tunnel 0ÃÈ dot1q-tunnel 0Ã¸X IGMP y[È-GMP Snooping ÃK¸ÁÃÔ

ÔQinQ Eâ IGMP y[ÁÄ><NMÔÏÝ IGMP y[¡X VLAN ÈÃü IGMP y[¡X VLAN E¥@ IGMP y[Ä

!VÄØÔ IGMP Snooping¸ÈÌX0Ã A dot1q-tunnel 0ÃÃ A ,X5,Õ VLAN VLAN 1èÃÃ A AŒ VLAN 1 ` VLAN 10 ,Xy[ÈÈÃÃ A ¥Õ VLAN 10 ,X IGMP report y[È IGMP Snooping ÕÝ VLAN 10 ,X4Ä><NMÈÉU IGMP report y[E¥@ VLAN 10 ,XCÃE¿ÄÃ ÃÄ><NMÔÏÝ dot1q-tunnel 0Ã¸X5,Õ VLAN Ä IGMP y[#tÔ dot1q-tunnel 0Ã 5,Õ VLAN ,X VLAN Tag ÈúÜü dot1q-tunnel 0Ã¸X5,Õ VLAN YE¥@

!VÄØÔ IGMP SnoopingÈÀ¸ÌX0Ã A dot1q-tunnel 0ÃÃ A ,X5,Õ VLAN VLAN 1èÃÃ A AŒ VLAN 1 ` VLAN 10 ,Xy[ÈÈÃÃ A ¥Õ VLAN 10 ,X IGMP report y[È IGMP Snooping ÕÝ VLAN 1 ,X4Ä><NMÈÉ IGMP report y[#tÔ VLAN 1 ,X VLAN Tag ÈúÜE¥@ VLAN 1 ,XCÃE¿ÄÃ 5,ÃÃÄ

Ï-5B_Ð *ü QinQ Eâ IGMP y[,Xs6ÑÑ

5XLMLHFRQILJLSLJPSVQRRSLQJWXQQHO

ÏÎGQÞð

Q¸	Ë-Ä
-	-

Ï-Äèð -

9.28 ip igmp snooping vlan

vid	VLAN 4ÊÈ	1-4094

ÏЂ,Õ!5BÐ Vp<| IGMP SnoopingÄVGL Æ VLAN | IGMP SnoopingÄVGL Æ
Vp<þ IGMP SnoopingÄVGL ÍÆ VLAN þ IGMP SnoopingÄVGL Æ

ÏQþÐ <ã

ÏЂ*ÐÎ ¤| IGMP SnoopingÄVGL ÆKÈ*ü **no ip igmp snooping vlan** *vid* ÆÕ
ÐÎ VLAN êXJª VLAN Þ IGMP SnoopingÄVGL Æ
PIM Snooping ÑOqC*b IGMP SnoopingÈ*ü **no ip igmp snooping vlan GK** VLAN ÞX IGMP
Snooping sÑÃ¹ VLAN Þ PIM SnoopingGKÆÈGKÁ PIM SnoopingÄ

ÏG!5B_Ð <| IGMP SnoopingÄVGL Æ vlan 2 GKÁ IGMP SnoopingÄVGL Æ
5XLMLHFRQILJLSLJPSVQRRSLQJLYJO
5XLMLHFRQILJQRLSLJPSVQRRSLQJYODQ

ÏÎGQÞÐ

Q¸	ÆÄ
ip igmp snooping	**|** IGMP Snooping JA5BJE¤ Æ

ÏGÄÆÐ -

9.29 ip igmp snooping vlan mrouter interface

G!5BM-ÕÃEºýÄÐQ¸X **no 6È5Æ**
ip igmp snooping vlan *vid* **mrouter interface** *interface-type interface-number*
no ip igmp snooping vlan *vid* **mrouter interface** *interface-type interface-number*

ÏÎDAÆÐ

–D	ÆÄ
vid	VLAN 4ÊÈ 1-4094
interface-type *interface-number*	*yÆÄ*

ÏЂ,Õ!5BÐ M-ÕÃEºý·

ÏQþÐ <ã

ÏЂ*ÐÎ *|Ú4CÃEºys6Ã,ÕÃk|ÕÃEºÄ
G!5B**ip igmp snooping vlan mrouter interface** ÆkM-ýÄ
M-ÕÃEºýÆÕ
VpÚÕG!5BM-ÕÃEºýÈ6ÞX4#FÃEA0ÃEÆ@
*¤0Ã6ÆÃEºýE9¸X4#!ÚXÈÚ#EÆ0Ã
¤M2CÃEºýE9¸X4#>M2ÚXÈÆÄ

ÏG!5B_Ð G!5BM-ÕÃEºýÖ

5XLMLHFRQILJLSLJPSVQRRSLQJYODQPURXWHULQWHUIDFHIDVW(WKHUQHW

ÏÎGQÐ

Q¸	Ë.Ä
ip igmp snooping mrouter learn pim-dvmrp	***lÕÕs6Ñ**
ip igmp snooping source-check port	*ß0Õ56Ñ

ËGÄß -

9.30 ip igmp snooping vlan static interface

G!5BM-ÕÄQ¸X **no 6ß88Ä**

ip igmp snooping vlan *vid* **static** *group-address* **interface** *interface-type interface-number*

no ip igmp snooping vlan *vid* **static** *group-address* **interface** *interface-type interface-number*

Ï-DAß

–D	Ë.Ä
vid	VLAN 4ßè 1-4094
group-address	4˜
interface-type *interface-number*	*yáÄ*

Ëb,Õ!5BÐ M-Õ

ËQÕ <ã

ËS*Ô IGMP Snooping E¥€<NMÿVLAN 4ÕÃÃE²ÿÄ

VLAN 4ÕÔÕ€<NMÄ

Ô€<NMÕÃE²ÃÕÃE²M-ÕÃE²Ã-ÕÃE²

ãÕ

Ô€<NMÕÃ|ÕM-Õ-ÕÕ*ü

clear ip igmp snooping gda-table ÕÑ8M-Õ

ËG!5B_Ð G!5BEthernet 0/1 vlan 1 4˜ 224.0.0.2 ,XM-ÕÐ

5XLMLHFRQILJLSLJPSVQRRSLQJYODQVWDWLFLQWHUIDFH(WKHUQHW

ÏÎGQÐ

Q¸	Ë.Ä
clear ip igmp snooping gda-table	#Ù8|Ð€<NM

ËGÄß -

9.31 permit

AÔBÞX4Ä

permit

Ï-DAð	–D	Ł Ä
	-	-

Ъ,Õ!5BÐ profile 5,þ **deny**

ÜQþ profile ã

Ï¨G!5B_Ð G!5Bprofile 1ÆÈ4Œ 224.2.2.2224.2.2.244

```
5XLMLHFRQILJLSLJPSSURILOH
5XLMLHFRQILJSURILOHUDQJH
5XLMLHFRQILJSURILOHSHUPLW
```

ÏÎGQÐ

Q¸	Œ¨Ä
ip igmp profile	Õ profile
permit	AûBÞX4˜
deny	/U!6ûBÞX4˜

Ï¨GÄÃð -

9.33 show ip igmp profile

¦ß profile ,XG!5BÇ

show ip igmp profile [*profile-number*]

Ï–DAÃð

–D	Œ¨Ä
profile-number	profile ,X4ÆÈ 1-1024

Ï¨Ò,Õ!5BÐ -

Ï¨QÐ (Mã

statistics	¦ß	IGMP Snooping ,X4ªAuµÇÄ
vlan *vid*	ô	VLAN

Ъ¸Õ!5BÐ -

ÜQþ (Mã

Ъ*ô VpéDÞ× IGMP Snooping ,XØMµÇÄ

Ü!5B_Ð -

ÎÜGQÞ

Q¸	Ë.Ä
-	-

ÜÄà¤ -

10 MLD Snooping

10.1 clear ipv6 mld snooping gda-table

#Ù8|ÐÕ@<NM

clear ipv6 mld snooping gda-table

Ï-DAè	–D	Ð£Ä
	-	-

Ï5,Õ!5BÐ -

ÏQþ (Mã

Ï5*ü MLD Snooping E@<NMÿVLAN 4ãÃÃ-ÃE?ÿÃ
VLAN 4ãÃÃ@<NMÄ
þ@<NMÿÃ-ÃE?ÿÃÑÃ-ÃE?ÿM-ÕÃ-ÃE?ÿÅM-ÕÃ-ÃE?ÿ
ãÃÃ
þ@<NMÿÃÃ|ÃM-ÃÃM-ÃÃÃ*ü
clear ipv6 mld snooping gda-table ÃÑ8M-ÃÃ

Ï5B_Ð 5XLMLHFOHDULSYPOGVQRRSLQJJGDWDEOH

ÏÏGQÞ

Q¸	Ð£Ä
ipv6 mld snooping vlan static interface	**G5BM-ÃÃ**

Ï5Äè -

10.2 debug mld-snp

S*ü **debug ÃÃ** MLD Snooping ,Ï5,XA^GÃÃ*ü **undebug ÃÃÄ**

debug mld-snp [**event** | **packet** | **msf** | **warning**]le18(6)þ(msf)4(n)6(p)]TJ /TT0 1 Tf 0.0022 Tc 0 Tw ([ )Tj /TT2 1 Tf 0

ï5¸Õ!5BÐ -

ÏQ¸Ð (Mã

ïS*ûÐ -

ÏG!5B_Ð 5XLMLHGHEXJPOGVQS

ÏÎGQ¸Ð

Q¸	Ë.Ä
-	-

ÏGÄÀð -

10.3 deny

/U!6ûÔ8¸è¥X4˜

deny

Ï-DAÀð

–D	Ë.Ä
-	-

ï5¸Õ!5BÐ profile 5¸Ð **deny**

ÏQ¸Ð profile ã

ïS*ûÐ profile ÔÚ¼¸˜XE¸$è5JWs6ÑÑG!5B!9PxÖ

1ïS*ü **ipv6 mld profile** Ð profileèÆ9 profile ã

2ïS*ü **range** ÇÔûÈ¸è

3ïS*ü **permit** ÆÐ¸èÑÑ*ü **deny** ÇÐ¸èÄ

ÏG!5B_Ð G!5Bprofile 1Æ!64˜ FF77::1FF77::100Ä

```
5XLMLHFRQILJLSYPOGSURILOH
5XLMLHFRQILJSURILOHUDQJH))))
5XLMLHFRQILJSURILOHGHQ\
```

ÏÎGQ¸Ð

Q¸	Ë.Ä
ipv6 mld profile	Ð profile
range	n48¸è
permit	AûÐ¸è¥X4˜

ÏGÄÀð -

10.4 ipv6 mld profile

õõ profileÈ9 profile ê*ÄQ¸X **no 6è88** profileÄ

ipv6 mld profile *profile-number*

no ipv6 mld profile *profile-number*

Ï-DAè	–D	Ł Ä
	profile-number	profile ,X4ê‹ 1-1024

Ï,Õ!5BÐ -

ÏQõ <ã

Ï*Ð profile ¸Ú¼¯XE$ÈJWs6ê!5B!9PxÖ

1È*ü **ipv6 mld profile õ** profÈ9profile

ÜQþ <ã

Ü*Ô ü IVGL Ø VLAN KÈX4#,ì(À,ÜX8ÕÕÕÔ VLAN ,XCÃE¿

AÿX4#x6ÿ)Ô VLAN ,X4#ÕÕÑ,à VLAN Y,XåEÄ@

ü SVGLØ VLAN ,XEÀÕÕÈ¼ VLAN +AÉ#ÄÔÔþÔ shared

VLANÄ,Õ VLAN1Ø shared VLAN ,X4#ÉEÄ@A4ñ,XåEo

åÕÕbØ VLANÄÔ*ü profile ØÈ- SVGLÈ8È,X4#Ñ¼

VLAN EÀ@8ÈX4#ÚÄ

ü IVGL-SVGL ØVGL ÉVGL /Ø,ÄÔ*ü Profile ØÈ- SVGLÈ

!88È,X4#EÜ SVGL È88ÈX4#EÜ IVGL Ä

Ü!5B_Ð _ 1Ö MLD Snooping IVGL Ä

```
5XLMLHFRQILJLSYPOGVQRRSLQJLYJO
```

_ 2Ö MLD Snooping SVGL Èshared VLAN VLAN1ÈSVGL 48È profile 1Ä

```
5XLMLHFRQILJLSYPOGVQRRSLQJVYJO
5XLMLHFRQILJLSYPOGVQRRSLQJVYJOSURILOH
```

_ 3Ö MLD Snooping IVGL-SVGL Èshared VLAN VLAN1È SVGL 48È profile 1Ä

```
5XLMLHFRQILJLSYPOGVQRRSLQJLYJOVYJO
5XLMLHFRQILJLSYPOGVQRRSLQJVYJOSURILOH
```

ÏÜGQÞ

Q¸	Ë.Ä
ipv6 mld snooping svgl vlan	ûÔ Shared VLANÄ
ipv6 mld snooping svgl profile	ûÔ SVGL G6(,X profileÄ

Ü GÄØ -

ÊÈ›ÃÕÈÃE¿yNe4,X#ïÐ8Ä

ÏG!5B_Ð G!5B|ÕÃ5ÕÈ 100sÄ

5XLMLHFRQILJLSYPOGVQRRSLQJGQPUDJLQJWLPH

ÎÏGQÐ

Q¸	ÉÄ
-	-

ÏGÄÐ -

10.7 ipv6 mld snooping fast-leave enable

*0Ãé(ÊÕ6Ã*ÄQ¸X **no 6ÉÄs6Ñ**

ipv6 mld snooping fast-leave enable

no ipv6 mld snooping fast-leave enable

Ï-DAÐ

–D	ÉÄ
-	-

Ð¸Ï!5BÐ GKÁs6Ñ

ÏQÐ <ã

Ï*Ð *0Ãé(ÊÕ6Ã done y¸ÐÁh,XE¥@<NM,XäÐ8A¹

0ÃÈ6h,X(Mn4ÄÝ[Ê6áÅ0ÃÄ@

0Ãé(ÊÕ6Ã*Ðx6ÐÃ%ÝÄXÃV4ÈÐÄ

ÏG!5B_Ð

ï5¸Õ!5BÐ

ÏQ¸Ð

ïS*Ð

ïG!5B_Ð

ÏÎGQ¸Ð

ïGÄÐ

10.9 ipv6 mld snooping max-groups

ipv6 mld snooping max-groups *number*

no ipv6 mld snooping max-groups

ï-DAÐ

ï5¸Õ!5BÐ

ÏQ¸Ð

ïS*Ð

10.10 ipv6 mld snooping query-max-response-time

G!5BA¥[ÕÊÈ|õÊÊQ¸X **no** 6ê5,Õ

ipv6 mld snooping query-max-response-time *seconds*

no ipv6 mld snooping query-max-response-time

Ï–DAè

–D	Ë£Ä		
seconds	A¥[ÕÊÈ/ÊÈ	1-65535Ê¸Õ	10

ï5,Õ!5BÐ –D5,Õ

ÜQ¸è <ã

Ü*Ô G!5BA¥[ÕÊÈ 100sÖ

5XLMLHFRQILJLSYPOGVQRRSLQJTXHUPD[UHVSRQVHWLPH

ÎGQ¸Ð

Q¸	Ë£Ä
-	-

ÜGÄè -

10.11 ipv6 mld snooping source-check port

*ê0Õ6ÑQ¸X **no 6êÉs6Ñ**

ipv6 mld snooping source-check port

no ipv6 mld snooping source-check port

Ï–DAè

–D	Ë£Ä
-	-

ï5,Õ!5BÐ GKÉs6Ñ

ÜQ¸è <ã

Ü*Ô ê0Õ6Ñ0L¤4#ê¾NCÃEÿE¯ê0s6¸Ê¾K4#FÑÑO97ÊÃ

+Eÿ[illegible]p¤ VLAN Yá[illegible]EÿÈwd[illegible] VLAN Yá[illegible]ó
Ä

no ipv6 mld snooping svgl profile

Ï-DAå

–D	Ë Ä
profile-number	profile ,X4 Ê È 1-1024

Ï5,Õ!5BÐ þ SVGL ,X4 È

ÏQÞ <ã

Ï*Ô Vp MLD Snooping ,XE¤ ã SVGL ê IVGL-SVGL È OG!5B!8QÄ
þ profile nLÔE¤ ü SVGL X4 È 8QÞ profileÄ

ÏG!5B_Ð G!5BE¤ ü SVGL X4 È profile 2Ö
5XLMLHFRQILJLSYPOGVQRRSLQJVYJOSURILOH

ÏÎGQÞ

Q¸	Ë Ä
ipv6 mld snooping	Ì MLD Snooping JA5BJE¤ ã

ÏGÄå -

10.14 ipv6 mld snooping svgl vlan

ôE¤ ü SVGL XE• VLANÏ Shared VLANÅQ¸X **no 6**

ipv6 mld snooping svgl vlan *vid*

no ipv6 mld snooping svgl vlan

Ï-DAå

–D	Ë Ä
vid	VLAN 4 Ê,Õ 1

Ï5,Õ!5BÐ –D5,Õ

ÏQÞ <ã

Ï*Ô ' MLD Snooping ,XE¤ ã SVGL ê IVGL-SVGL Ê!5B!8QÄ

ÏG!5B_Ð ôE• VLAN VLAN3
5XLMLHFRQILJLSYPOGVQRRSLQJVYJOYODQ

ÏÎGQÞ

Q¸	Ë Ä
ipv6 mld snooping	Ì IGMP Snooping JA5BE¤ ã

ÏGÄå -

10.15 ipv6 mld snooping vlan

ü VLAN Þ MLD Snooping JE¤ IVGL ÄŒQ¸X **no 6ã** VLAN ÐKÁ MLD SnoopingÄ

ipv6 mld snooping vlan *vid*

no ipv6 mld snooping vlan *vid*

Ï-DAèð

–D	ÆÄ
vid	VLAN 4ßÈ 1-4094

Ï5,Õ!5BÐ -

ÏQþÐ <ã

ÏS*ôÐ ë| MLD SnoopingÄVGL ÅXÈ‰ü **no ipv6 mld snooping vlan** *vid* ÆÕ

ßÐ VLAN êXJª VLAN Þ MLD SnoopingÄVGL Å

ÏG!5B_Ð <| MLD SnoopingÄVGL Å vlan 2 ÐKÁ MLD SnoopingÄVGL Å

```
5XLMLHFRQILJLSYPOGVQRRSLQJLYJO
5XLMLHFRQILJLSYPOGVQRRSLQJYODQ
```

ÏÎGQÞÐ

Q¸	ÆÄ
ipv6 mld snooping	**|** MLD Snooping JA5BJE¤ Å

ÏGÄèð -

10.16 ipv6 mld snooping vlan mrouter interface

G!5BM-ÕÃÆ²ÿÄŒQ¸X **no 6èÈ5B**

ipv6 mld snooping vlan *vid* **mrouter interface** *interface-type interface-number*

no ipv6 mld snooping vlan *vid* **mrouter interface** *interface-type interface-number*

Ï-DAèð

–D	ÆÄ
vid	VLAN 4ßÈ 1-4094
interface-type *interface-number*	*yáÄ*

Ï5,Õ!5BÐ M-ÕÃÆ²·

ÏQþÐ <ã

ÏS*ôÐ G!5B**ipv6 mld snooping vlan mrouter learn** Æk|ÞÄ

G!5B**ipv6 mld snooping vlan mrouter interface** ÆkM-ÞÄ

VpÐÆG!5BM-ÕÃÆ²ÿÈ6ÞX¥#FÑÆA0ÃÆÆ@

ipv6 mld snooping vlan *vid* **static** *group-address* **interface** *interface-type interface-number*
no ipv6 mld snooping vlan *vid* **static** *group-address* **interface** *interface-type interface-number*

Ï-DAê

–D	Ë Ä
vid	VLAN 4ÊÈ< 1-4094
group-address	4˜
interface-type *interface-number*	*yéÄ*

Ъ,Õ!5BÐ M-Ð@<NM

ÜQþ <ã

Ъ*ô MLD Snooping E@<NMÿ2ØLAN 4ãÃ
VLAN 4ÊÔÞ@<NMÞ@<NMÃ
S*ü **clear ipv6 mld snooping gda-table** ÇÑ8M-ÐÄ

Ü!5B_Ð G!5BM-Ð@<NMÖ
5XLMLHFRQILJLSYPOGVQRRSLQJYODQVWDWLF))LQWHUIDFHIDVW(WKHUQHW

ÏÎGQÞ

Q¸	Ë Ä
clear ipv6 mld snooping gda-table	ô8|Ð@<NM

ÜGÄê -

10.19 permit

AõBÞX4Ä
permit

Ï-DAê

–D	Ë Ä
-	-

Ъ,Õ!5BÐ profile 5,Þ **deny**

ÜQþ profile ã

Ъ*ô profile

5XLMLHFRQILJSURILOHUDQJH))))
5XLMLHFRQILJSURILOHSHUPLW

ÏĈGQÞ

Q¸	Ë.Ä
ipv6 mld profile	p profile
range	n48Ê
deny	/U!6û8þX4˜

ĞĠÄê -

10.20 range

nþ3Ê*ÆQ¸X **no 6ê8ûX3Ê**

range *low-ip-address* [*high-ip-address*]

no range *low-ip-address* [*high-ip-address*]

–D	Ë.Ä
low-ip-address	û8þXCKŸ
high-ip-address	û8þX4ş

10.21 show ipv6 mld profile

¦ß profile ,XG!5BQ

show ipv6 mld profile [*profile-number*]

Ï-DAð

Ï¨G!5B_Ð

_ 1ÐÐ MLD Snooping ,XØMG!5B

```
5XLMLHVKRWSYPOGVQRRSLQJ
0/VQRRSLQJPRGH,9*/
69*/YODQLG
69*/SURILOHQXPEHU
6RXUFHFKHFNSRUWLVDEOHG
4XHU\PD[UHVSRQHWLPH6HFRQGV
```

_ 2ÐÐ MLD Snooping ,X4ÃuÇ

```
5XLMLHVKRWSYPOGVQRRSLQJVWDWLVWLFV
*5283,QWHUIDFH/DVWUHSRUW/DVWOHDYH/DVW
WLPHWLPHUHSRUWHU

))9/*LGKPV
5HSRUWSNWV/HDYHSNWV
```

_ 3ÐÐ MLD Snooping ,XCÃE÷·

```
5XLMLHVKRWSYPOGVQRRSLQJPURXWHU
9ODQ,QWHUIDFH6WDWH0/SURILOHQXPEHU

*LJDELW(WKHUQHWVWDWLF
*LJDELW(WKHUQHWGQDPLF
```

_ 4ÐÐ MLD Snooping ,XE¥@<

```
5XLMLHVKRWSYPOGVQRRSLQJJGDWDEOH
6EU0PURXWHU
GQDPLF
6VWDWLF
9/$6GUHVV0HPEHUSRUWV

))*LJDELW(WKHUQHW6
```

_ 5ÐÐ MLD Snooping filtering ,XG!5B

```
5XLMLHVKRWSYPOGVQRRSLQJLQWHUIDFH*LJDELW(WKHUQHW
,QWHUIDFH)LOWHU3URILOHQXPEHUPD[JURXSV

*LJDELW(WKHUQHW
```

ÏÎGQÞ

Q¸	E Ä
-	-

ÏGÄÐ -

execÄÆÇ no 6ß Exec AÞú6Ñ

aaa accounting exec {**default** | *list-name*} **start-stop** *method1* [*method2*...]

no aaa accounting exec {**default** | *list-name*}

ÐAß

–D	Ë Ä
default	Sß¹–Dß6n,Xß<0 Exec AÞúXTAxß
list-name	nÇ Exec AÞúXß<Ñ-0Á
method	Ñ**none Ã group**
none	ß AÞ
group	**Sß4ß AÞ** RADIUS ` TACACS+á<4˜

Ö,Õ5BÐ GKÁÞú6Ñ

Ç <G5Bß

ÖÇ RGOS ßÆÆ)AxAß Exec AÞú6ßptÇ)ß AxAßAxA›

ptXÇ noneß Exec AÞÁ

ßAÞú6ßÐ) NAS ,X CLI + M6ÆÕÞßÐstart ß4]<á<ß

	äÄÀÞÈÄÑÕ 5%4Ä“KÂ
method	Ñ 4 þ
none	é AÞú
group	Sé<4É AÞÞÕ RADIUS ` TACACS+á<4˜

Ö¸ÕÖBÐ GKÁÞé6Ñ

Þ <GÖBÅ

default	**S** 802.1X
list-name	802.1X
method	

ï5,Õ5BÐ -

ïÇ <G5Bß

ïSß VpA'ûÙ AAA Enable AxAáìMOSü AAA E> Enable AxAµMOSü **aaa authentication enable** Ç5BAxXß Enable AxAÄ
M6,XßýÈÑM6,XE> DÑxAÄ
Enable AxAß<G5BÈnable AxAs6ÑµÄ

ïG5B_Ð M6,X/_n AAA Enable DÑxAß<ÄAxAß<Sü RADIUS]<á<E> DÑ
AxAÈpûÊ$ùÝ RADIUS]<á<,Xh1(ÈßBgE> DÑxAÄ
5XLMLHFRQDDDDXWKHQWLFDWLRQQEOHGHIDXOWURXSUDGLXVORFDO

ïGÇ

Ç	Ë
aaa new-model	**S** AAA]<á
enable	**ê{ÿ**
username	**n**

ïGÄß -

1.8 aaa authentication login

ÙSü AAA E> Login,Ö)ÅxAÈ> <G5BÇ **aaa authentication login G5B** Login AxA•
,Xß<ÄÇX **no** 6ß8AxA,Xß<Ä
aaa authentication login {**default** | *list-name*} *method1* [*method2*...]
no aaa authentication login {**default** | *list-name*}

ÐAß

–D	Ë
default	S¹–DM6n,Xß<0 Login AxA•XTAxß
list-name	**n** Login AxA,Xß<Ã+0Ä
method	M local Ã none Ã group€K+ß<Ù 4 ß
local	**S gÐÑxA•**
none	**ÐÑxA•**
group	**S 4ÐÑxAÃ** RADIUS ` TACACS+á<4˜

ï5,Õ5BÐ -

ïÇ <G5Bß

ïSß VpA'ûÙ AAA ,O)AxA]<áìMOSü AAA E> Login AxAµMOSü **aaa authentication login** Ç5BAxXßÃ Login AxAÄ

aaa authorization commands	n AAA Ç<

ÏGÄê -

1.10 aaa authorization config-commands

Ø Sü AAA Í5BêG5BêXÇ> È <G5BÇ aaa authorization config-commandsÄÇ no 6ÉÍ AAA Í5BêKÇX s6Ñ
aaa authorization config-commands
no aaa authorization config-commands

ÏÐAê

–D	ÉÄ
-	-

Ï,Õ5BÐ TAxÉ5BêXE> Ä

Ç Ø <G5Bê

ÏÐ VpÍM2G5Bê(MêXÇ> ÉÄÇX no 6É5B\ s6Ñ5BÇÉÄ

ÏG5B_Ð MI6,X/_Õ5BêXs6Ñ
5XLMLHFRQILDDDDXWKRUL]DWLRQRQFRPPDQV

ÏÎGÇ

Ç	ÉÄ
aaa new-model	S6Ñ AAA]<á
aaa authorization commands	n AAA Ç

ÏGÄê -

1.11 aaa authorization console

Ø Sü AAA ÉE{Ä),Xê> ,XÇ> È <G5BÇ aaa authorization consoleÄÇ no 6É AAA ÉE{Ä),Xê> ÇXs6Ñ
aaa authorization console
no aaa authorization console

ÏÐAê

–D	ÉÄ
-	-

Ï,Õ5BÐ TAxÉê> ,XÇ> Ä

	<G5BA
	RGOS

aaa new-model	**S6Ñ** AAA]<á
authorization exec	**ïoâC Ãï**
username	

1.14 aaa domain

E9¢G5BB5B³X2ÄÇX **no 6ÄÇ**

aaa domain {**default** | *domain-name*}

no aaa domain {**default** | *domain-name*}

–D	Ë
default	S¹DÈ> 5,ÕXG5B
domain-name	*b*

ï5,Õ5BÐ ùG5BÏÄ

ÇÐ <G5BÄ

ÏÐ bÎÃX AAA áG5BÄ default 5,Õ5BÈVpùÇ%4A'Ô

ùXÃ<Ä *domain-name b*

ÄÐ 32 Ä

ïG5B_Ð M6,X/_A'5BG5BÖ

5XLMLHFRQQDDGRPDLQXLMLHFRP

5XLMLHFRQQDDGRPDLQ

ÎGÇÐ

Ç	Ë
aaa new-model	**Ô** AAA]<á
aaa domain enable	**Õ** AAA áÔ
show aaa domain	**/G5B**

ïGÄÃ -

1.15 aaa domain enable

bÃX AAA áÔÈAx K XÎbÃX AAA

áG5BÄÇX **no 6GÁÔÄ**

aaa domain enable

no aaa domain enable

–D	Ë
-	-

ï5,Õ5BÐ bÃX AAA áÔGKÄ

ÇÐ <G5BÄ

ÏÐõ E> ÎãX AAA áG5BÈÔÊÇG5BÔÄ

ÏG5B_Đ ÕãX AAA áÔÖ

5XLMLHFRQQDDGRPDLQQDEOH

ÎÏGÇÐ

Ç	ÉÄ
aaa new-model	**Ô** AAA]<á
show aaa domain	**/ÏG5B**

ÏGÄãð -

1.16 aaa group server

É9 AAA á<4ÏG5BÄÇX **no 6ãá<4Ä**

aaa group server {**radius** | **tacacs+**} *name*

no aaa group server {**radius** | **tacacs+**} *name*

ÐAãð

–D	ÉÄ
name	á<4,ˆXãÕK+radius è acacs+ È-RADIUS ` TACACS+TAx,Xá<4ÄÄ

Ï,ÕG5BĐ -

Ïçð <G5BÄ

ÏÐõ AÇQ5B AAA á<4È ,Õ RADIUS ` TACACS+á<4Ä

ÏG5B_Đ M6/_Ä

5XLMLHFRQQDDDUXSVHUYHUUDGLXVVV

5XLMLHFRQQDVUDGLXVHQ

5XLMLHVKRWDDDUXS

ÚRXS1DPHVV

ÚRXS7SHUDGLXV

5HIHUUHG

6HUYHU/LVW

ÎÏGÇÐ

Ç	ÉÄ
show aaa group	**/** aaa á<4ˆ

ÏGÄãð -

1.17 aaa local authentication attempts

G5B login ,O)ÆÇ)BÙÐ

aaa local authentication attempts *max-attempts*

ÏÐÆÃ

–D	ÆÄ
max-attempts Ó	1~2147483647Ä

Ï5,Õ5BÐ 5,Õ3 õ

Ïº

<G5BÃ

ÏÊÔ AÇ5B Login ,O)ÆÇ)BÙÐ

ÏG5B_Ð MI6,X/_Ö

```
5XLMLHFRQ;XUHWHUPLQO
5XLMLHFRQDDDORFDODXWKHQWLFDWLRQWWHPSWV
```

ÏÎGÇ

Ç	ÆÄ
show running-config	**/AÊ5B**
show aaa lockout	**/!** login ,XÕG5B–D

ÏGÄÃ -

1.18 aaa local authentication lockout-time

G5B login ,O)ÆÇCYEG5B,O)BÙÐÈÃ,XÊÈSz

aaa local authentication lockout-time *lockout-time*

ÏÐÆÃ

–D	ÆÄ
lockout-time	1~2147483647

Ï5,Õ5BÐ 5,Õ15 Ê

Ïº

<G5BÃ

ÏÊÔ G5B login ,O)ÆÇCYEG5B,O)BÙÐÈÃ,XÊÈSz

ÏG5B_Ð MI6,X/_Ö

```
5XLMLHFRQ;XUHWHUPLQO
5XLMLHFRQDDDOFDÃÊWFRQFÃÇÄ00
```

ÎÎGĘ

Ę	ĘÄ
show running-config	**/AĜ5B**
show aaa lockout	**/!** login ,XŐG5B–D

ĞGÄß -

1.19 aaa new-model

ÞSŭ RGOS ,X AAA]<áś6ÆĘ> <G5BĘ **aaa new-model S6Ñ** AAAÄĘX **no 6**
ßK AAA]<áÄ
aaa new-model
no aaa new-model

ÐAß –D ĘÄaa ne(w)-20(-)2(m)12(ode)5(l)]TJ62_0 1 Tf0 Tc 0 Tw 7.4 0 Td<055336D1>Tj/TT0 1 T

	num	IEEE802.1x ŭ

Ъ,Õ5BÐ 5,GÄ

Ð ¢G5BÄ

5XLMLHFRQILJDFFRXQWLQJRPPDQGV

ÏĈĢĐ

Ç	ÉÄ
aaa new-model	**S6Ñ** AAA]<á
aaa accounting commands	**n** AAA ÇĢB6<

ĞÄâê -

1.22 accounting exec

ÐÚ Exec AĢBá<hÛ40ÃCÃ 4“CĞ5BĢÐ **accounting execÄĢÐ no 6**
âCÃ Exec AĢBá6Ñ
accounting exec {**default** | *list-name*}
no accounting exec

ÐÄâê

–D	ÉÄ
default	Sâ¹DÈtú Exec AĢBúXTAxÖ
list-name	hĢÐX Exec AĢBúX6<Ä

Ï5,Ğ5BÐ GKÁĢBá6Ñ

ÏĐĢÐ 4“CĞ5BâÄ

ÏĐ TAx,X Exec AĢB6<ÐĞ5BĢÐÐ¾hâÚÖÃCÃÚM2TAx Exec AĢB6
><ĐAx,X6<ÜpAÒĢp,X6<ÈĢÐ:ÁÇÈ4“CÃ
,X Exec AĢBÐÐÇZ¹ Exec AĢB6<Á

ĞĞ5B_Ð ÐM6,X/_G5BĢÐ exec-1 ,X Exec AĢBâ<ÈtúRADIUS 0]<á<ÈÐpá<ú¡Ý
hĞÚú none Ö5BâtúÐ

Ï5BÐ Network AÞßé<ÄÇÇX **no 6ÐÇ**

accounting network {**default |** *list-name*}

no accounting network

ÏÐAÐ	–D	Ë Ä
	default	SÐ¹–DÊSÕ,Õ5BÐ<
	list-name	*ûÐÄ*

Õ,Õ5BÐ ûÐ<ÊpÉKAÊ%4A'Ê¢AÐ default Ð<Ä

ÇÐ Ï5BÄ

ÏÐ ÐSÇX Network AÞÐ<Ä

Ï5B_Ð MÐ6,X/_ÐA'5BÐ Network AÞÐ<Ö

```
5XLMLHFRQILJDFFRXQWLQJQHWZRUNGHIDXOWQR
5XLMLHFRQILJDFFRXQWLQJQHWZRUNGHIDXOWQR
```

```
5XLMLHFRQDDGRPDLQXLMLHFRP
5XLMLHFRQDDGRPDLQXWKHQLFDWLRQRW[GHIDXOW
```

ÎÍGĐ

default	SÐ¹–DÊSõ,Õ5BÐ<
list-name	*bÐÄ*

Ï5,Õ5BÐ ÙÛÐ<ÊpÐKAÊ%4A'Ê¼AÙ default Ð<Ä

ÏÇ ÇG5BÄ

ÏÐÛ ÛÐ<Ä

ÏG5B_Ð ÑM6,X/_ÐA'5BÛÐ<Ö

```
5XLMLHFRQILJDDDGRPDLQXLMLHFRP
5XLMLHFRQILJDDDGRPDLQXWKRUL]DWLRQWR2UNGHIDXOW
```

ÏÎGÇ

Ç	ÊÄ
aaa new-model	**Ô** AAA]<á
aaa domain enable	**ÕÛ** AAA áÔ
show aaa domain	**/ÏG5B**

ÏGÄÐ -

1.28 clear aaa local user lockout

Ð8>õ,Xÿ<

clear aaa local user lockout {**all** | **user-name** *word* }

ÏÐÄÐ

–D	ÊÄ
word	ÿ ID

Ï5,Õ5BÐ -

ÏÇ (MÄ

ÏÐÛ Ð8>õ,Xÿ<ÕF-Ð83ÕÐ8

ÏG5B_Ð ÑM6,X/_Ö

```
5XLMLHFOHDUDDDORFDOXVHUORFNRXWDOO
```

ÏÎGÇ

Ç	ÊÄ
show running-config	**/AÛ5B**
show aaa lockout	**/!** login ,XÐG5B–D

ÏGÄÐ -

1.29 debug aaa

Ô AAA áAAÇÄÇX **no 6ÉÁAÇÄ**

debug aaa event

no debug aaa event

ÐAÈ –D

ÏĈĢҨ

Ҩ	₤Ä
aaa group server	**G5B** aaa á<4˜

no server *ip-addr* [**auth-port** *port1*] [**acct-port** *port2*]

ÏÐÀâê

–D	ÊÄ
ip-addr	á< ip
port1	á<AxA0Ã¼ RADIUS á<4Ð
port2	á<AÞ0Ã¼ RADIUS á<4Ð

Ï¿ÕõBÐ á<G5B

Ïî á<4ÇG5BÄá

ÏßÎñ TÛá<Ïá<ê0ÊTAxÄ

ÏG5B_Ð

```
5XLMLHFRQQDDDUXSVHUYHUUDGLXVVV
5XLMLHFRQQJVUDGLXVVHUYHUDFFWSRUWDXWKSRUW
5XLMLHFRQQJVUDGLXVHQ
5XLMLHVKRØDDDUXRXS
7ŠH5HIHUHQH1DPH

UDGLXVUDGLXV
WDFDFVWDFDFV
UDGLXVVV
```

ÎÌGÐ

Ç	ÊÄ
aaa group server	**G5B** aaa á<4˜
show aaa group	**/** aaa á<4˜

ÏGÄâê -

1.33 show aaa domain

/Ñ5BÐCÄ

show aaa domain [**default** | *domain-name*]

ÏÐÀâê

–D	ÊÄ
default	SÄ¹DÊVTAx,XÐC
domain-name	/ÛÐC

Ï¿ÕõBÐ -

Ïî (MÄ

ÏßÎñ VpÛÐÉXÐCÄ

ÏG5B_Ð ÑM6,X/_/ûÉá domain.com ,XÇÄ

```
5XLMLHVKRWDDGRPDLQRPDLQRP

        RPDLQRPDLQRP
6WDWHSWLYH
8VHUQPHIRUPDW:LWKRXWGRPDLQ
#FHVVOLPLW1ROLPLW
;#FHVVVWDWLVWLF

6HOHFWHGPHWKRGOLVW
DXWKHQWLFDWLRQRW[GHIDXOW
```

ÏÎGÇÐ

Ç	ÉÄ
aaa new-model	**Ô** AAA]<á
aaa domain enable	**ÕÖ×** AAA áÔ

ÏGÄÈÐ -

1.34 show aaa group

/ AAA G5B,XÉá<4Ä

show aaa group

ÐAÈÐ

–D	ÉÄ
-	-

Ï,Õ5BÐ -

ÈÐ (MÈÄ

ÏÉÖ AÇÐ AAA ÉÉ5B,Xá<4Ä

ÏG5B_Ð

```
5XLMLHVKRWDDDUXRXS
7ŠH5HIHUHQH1DPH

UDGLXVUDGLXV
WDFDFVWDFDFV
UDGLXVGRW[BUXRXS
UDGLXVORLLÇUXRXS
UDGLXVHQEOHBUXRXS
```

ÏÎGÇÐ

Ç	ÉÄ
aaa group server	**G5B** AAA á<4˜

ĞÄâê -

1.35 show aaa method-list

/ AAA ¸ÝXê<Ä

show aaa method-list

ÐAâê

–D	Ł Ä
-	-

Ъ,ÕЭ5BÐ -

ÿÇ (Mã

ЪÐ AÇ AAA ¸ÝXê<Ä

ĞЭ5B_Ð ÑM6,X/_/ AAA ê<Ä

```
5XLMLHVKRZDDDPHWKRGOLVW
$XWKHQWLFDWLRQPHWKRGOLVW
DDDDXWKHQWLFDWLRQRIQHIDXOWURXSUDGLXV
DDDDXWKHQWLFDWLRQSSSGHIDXOWURXSUDGLXV
DDDDXWKHQWLFDWLRQRW[GHIDXOWURXSUDGLXV
DDDDXWKHQWLFDWLRQRW[VDQRFDOURXSDÐOURXSUDLÇÐ
DDDDXWKHQWLFDWLRQÐEOHGHIDXOWURXSUDGLXV
$FFRXQWLQJPHWKRGOLVW
DDDDFFRXQWLQÐWRUNGHIDXOWVWDUWVWRSURXSUDGLXV
$XWKRUL]DWLRQPHWKRGOLVW
DDDDXWKRUL]DWLÐWRUNGHIDXOWURXSUDGLXV
```

ÎĞÇÐ

Ç	Ł Ä
aaa authentication	**nÐ xAê**

-	

Ï,Õ5BÐ -

Ïç (MÄ

ÏÊÍ /!Õ,X<ÈÉ>È8ÕÄ

ÏG5B_Ð ÑM6,X/_Ö
5XLMLHVKRØDDXVHUORFNRXW

ÎÏGÇ

Ç	Ë
show running-config	**/AÛG5B**
show aaa lockout	**/!** login ,XÕG5B–D

ÏGÄÈ -

1.37 state

A’5BÄÇ X **no 6ÄAxG5Ë**
state {**block** | **active**}
no state

ÐAÈ

–D	Ë
block	G5B,XÝ
active	**Æ**

Ï,Õ5BÐ 5,Ñ

Ïç ÈG5BÄ

ÏÊÍ ÛG5B,XÄ

ÏG5B_Ð ÑM6,X/_ÆA’5BÄ
5XLMLHFRQDDGRPDLQXLMLHFRP
5XLMLHFRQDDGRPDLQWDWHEORFN

ÎÏGÇ

Ç	Ë
aaa new-model	**Ô** AAA]<á
aaa domain enable	**ÕÆ** AAA áÛ
show aaa domain	**/G5B**

ÏGÄê -

1.38 username-format

ÐA¤ê¤5BÐG5B NAS á<xfÐÈÇQX **no 6á¤AxG5Ð**

username-format {**without-domain** | **with-domain**}

no username-format

ÏÐAê

–D	ÉÄ
without-domain	9/Ð
with-domain	Ð

Ï,Õ5BÐ 5,ÐÐÇÄ

Ïê Ð¤5BÁ

ÏÐ ÐG5B¤5B NAS ÏÁ<xfÐÄ

ÏG5B_Ð ÐÍ6,X/_ÐA'5B9/ÇÖ

5XLMLHFRQILJDGRPDLQXLMLHFRP

5XLMLHFRQILJDGRPDLQVHUQPHGRPDLQWKRXWGRPDLQ

ÏÎGÐ

Q	ÉÄ
aaa new-model	**Ô** AAA]<á
aaa domain enable	**ÕÐ** AAA áÔ
show aaa domain	**/ÐG5B**

ÏGÄê -

2 RADIUS

2.1 debug radius

Ô RADIUS AAGÄ **no 6 RADIUS AAGÄ**

debug radius [**event | detail**]

no debug radius [**event | detail**]

	–D	Ä
	-	-

-

(M EXEC

-

-

radius y[¢ fastEthernet 0/0 y9ª ip 90 radius y[,X

radius-server host	**n** RADIUS á<
ip address	ip

-

2.3 radius attribute

radius attribute {*id* | **down-rate-limit** | **dscp** | **mac-limit** | **up-rate-limit**} **vendor-type** *type*

no radius attribute { *id* | **down-rate-limit** | **dscp** | **mac-limit** | **up-rate-limit**} **vendor-type**

id	s6Ñ id <1-255>
type	type

17	version to server	17
18	flux-max-high32	18
19	flux-max-low32	19
20	proxy-avoid	20
21	dailup-avoid	21
22	ip privilege	22
23	login privilege	42

	max up-rate 2O_n	211	

-	-

	id
	<G5BÄ
	SÄ id ,X2 G5B+2O_A
	M6,X/_Ö 5XLMLHFRQUDGLXVYHQRUVSHFLILFH[WHQ

Q	EÄ
radius attribute	**G5B**
radius set qos cos	**G5B** qos cos

-

2.6 radius-server attribute 31

RADIUS Calling-Station-ID 2 MAC <G5BQ **radius-server attribute 31** **no 6 5B**

radius-server attribute 31 mac format {ietf | normal | unformatted}

no radius-server attribute 31 mac format

–D	EÄ
ietf	ETF RFC3580 MAC 00-D0-F8-33-22-AC
normal	MAC 00d0.f833.22ac
unformatted	00d0f83322ac

U0 _ V b Ä ñ6(s ÔA

-	-

ÏGÄê -

2.7 radius-server dead-criteria

ÞÐG5BA'ø RADIUS]<á<Ê',XÊ <G5BÇ **radius-server dead-criteria**Ä

A **no 6** **A**xÄ

radius-server dead-criteria {**time** *seconds* [**tries** *number*] | **tries** *number*}

no radius-server dead-criteria {**time** *seconds* [**tries** *number*] | **tries** *number*}

ÏA

–D	Ë Ä
time *seconds*	G5BÊ DÄ'û,XÊ ù¾ RADIUS]<á u<,X7.Bhy[xA¹ RADIUS]<á<Ê',XÊS 5Ê'5B,X,X8 1-120 /Ä
tries *number*	G5BAË4ÉYÊ5 DÄ'ð RADIUS]<á< ÆÕXAÿ[E4ÉYÊ E'An,X ÕÈxA¹ RADIUS] <á<Ê',XE4ÉYÊ5Ê'5B,X,X8 1-100Ä

Ï,Õ5BÐ **time** *seconds* 60 /Ä

tries *number* 10 Ä

Ïð **<G5BÄ**

ÏÊÐ VpÊ RADIUS]<á<ÊÈÊÈ4ÉYÊ5ÊÚxA¹ RADIUS]< á<Ê'ÄÊÕÈÊË4ÉYÊ5Ê–DE> AHÄ

ÏG5B_Ð M6,X/_ÊS 120 /È4ÉYÊ 20 õ

5XLMLHFRQQHFWUHWU\WLPHVGHIDXOWV

ÏÎGÇÐ

Ç	Ë Ä
radius-server host	**n** RADIUS]<á<,X
radius-server deadtime	**nA** RADIUS]<á< ÆÕÿ[,XÊSz
radius-server timeout	**n** RADIUS y[CYÊ

ÏGÄê -

2.8 radius-server deadtime

no radius-server deadtime

ignore-auth-port		RADIUS]<á<,XAxA0,Ã”ÈAxÊ
ignore-acct-port		RADIUS]<á<,XAß0,Ã”ÈAxÊ

Ï5,Õ5BÐ ùM,X RADIUS Ä

<G5Bá

Z ù RADIUS r)„ AAA]<áÈOn RADIUS]<á<Ãù **radius-server host**

RADIUS]<á<Ä

M6,X/_nÔ IPv4)W3X RADIUS]<á<Ö

5XLMLHFRQUDGLXVVHUYHUKRVW

M6,X/_nÔ IPv4)W3X RADIUS]<á<Õ#6Èh<ó 60

UDP Gmy-rÈrÜÇý ÐÏ1s=ÚKRÈrR¼Ø<Ä

ÏG!5B _ Ð M6,X/_nÔ0

Ïê© <G5BÄ

Ïêõ EÇÄ'Û RADIUS]<á<E> 7.BE¡XÏÄA'Û RADIUS]<á<6Ñ>
EÇ¥ÏOÄ'Û RADIUS]<á<h,¥XEÇÄ

ÏG5B_Ð ¥M6,X/_n RADIUS]<á<,XE¸• aaaÖ
5XLMLHFRQUDGLXVVHUYHUNHDDD

ÏÎGÇ

Ç	ÉÄ
radius-server host	**n** RADIUS]<á<,X
radius-server retransmit	**n** RADIUS y[G¥Ð
radius-server timeout	**n** RADIUS y[CYÊÉ

ÏGÄê© -

2.11 radius-server retransmit

?UG5BA'ÛÄx RADIUS]<á<'u Ýh¹G¡¥y[,X õDÈÄË¸> <G5BÇ
radius-server retransmitÄÇ **no 6ÄTAxG¥ÐÄ**
radius-server retransmit *retries*
no radius-server retransmit

ÐÄê©

–D	ÉÄ
retries	RADIUS ÄG¥ÐÄ

5,Õ5BÐ TAxG¥Ð 3Ä

Ïê© <G5BÄ

Ïêõ AAA ê©> AxA¸XÄAxA¸X]<á<'uÝÄ'ê<á<
'uÝ,Xê<á<Ä'Ûê©Ð RADIUS y[KÈÝ1(ÈGKÉYÊ
KÈhÄ

ÏG5B_Ð ¥M6,X/_ûG¥Ð 4Ö
5XLMLHFRQUDGLXVVHUYHUUHWUDQVPLW

ÏÎGÇ

Ç	ÉÄ
radius-server host	**n** RADIUS]<á<,X
radius-server key	**n** RADIUS ,XE¸•
radius-server timeout	**n** RADIUS y[CYÊÉ

ÏGÄê© -

2.12 radius-server timeout

radius-server timeout *seconds*

no radius-server timeout

	–	
	seconds	1-1000

5

radius-server host	**n** RADIUS
radius-server retransmit	**n** RADIUS
radius-server key	**n** RADIUS

-

2.13 show radius parameter

/ RADIUS

show radius parameter

–	
-	-

-

(

radius

6HUYHU5HWULHV
6HUYHUHDG&ULWHUD
7LPH6HFRQGV
7ULHV

ÎÍGÇÐ

Ç	Ë Ä
radius-server host	**n** RADIUS]<á<,X
radius-server retransmit	**n** RADIUS y[G¥Ð
radius-server key	**n** RADIUS ,XE¸•
radius-server timeout	**n** RADIUS CYÊÈ
radius-server dead-criteria	**n** RADIUS]<á<Á',XøŠJ
radius-server deadtime	**nA0ÕõÊõ** RADIUS]<á<ËÕ y[,XÊÈ

ÏGÄê -

```
$FFRXQWUHTXHVWWLPHRXWV

6HUYHU,3
$FFRXQWLQRUW
$XWKHQRUW
7HVW8VHUQPH1RWRXQG!
7HVW,GOH7LPH0LQXWHV
7HVW3RUWV$XWKHQQ$FFRXQWLQ
6HUYHU6WDWH$FWLYH
$XUHVGXUDWLRQSUHYLRXVGXUDWLRQ
HDGWRWDOWLPHVFRXQW
6WDWLVWLFV
$XWKHQHTXHVWWLPHRXWV
$XWKRUUHTXHVWWLPHRXWV
$FFRXQWUHTXHVWWLPHRXWV
```

ÏĜĘ	Ę	Ę.Ä

```
PD[GRQDWH
SRUWSULRULW\
XVHULS
YODQG
ODVWVXSSOLFDQYHUV
LRQ
WLS
XVHUQPH
SDVVZRUG
ILOHGLUHFWRU\
ILOHFRXQW
ILOHQPH
ILOHQPH
ILOHQPH
ILOHQPH
ILOHQPH
PD[XSUDWH
FXUUHQVVXSSOLFDQY
HUVLRQ
IOX[PD[KLJK
IOX[PD[ORZ
SUR[DYRLG
GLDOXSDYRLG
LSSULYLOHJH
ORQLQULYLOHJH
LSYPXOWLFDVWDGGUH
VV
LSYPXOWLFDVWDGGUH
VV
```

ÏÎGÇ

Ç	ÉÄ
radius-server host	**n** RADIUS]<á<,X
radius-server retransmit	**n** RADIUS y[G¥Ð
radius-server key	**n** RADIUS ,XE¸•
radius-server timeout	**n** RADIUS CYÊÈ

ÏGÄÈ -

3 TACACS+

3.1 aaa group server tacacs+

TACACS+

ÏèÐ -

ÏGÕB_Ð -

ÎÌGÐ

Ç	ÉÄ
-	-

ÏGÄê -

3.3 ip tacacs source-interface

8ÇÕB TACACS+y[,Xê¶Ä

ip tacacs source-interface *interface*

no ip tacacs source-interface

ÐAê

–D	ÉÄ
interface	TACACS+y[,Xê¶y·

Õ,ÃÕBÐ TACACS+y[,Xê¶+5%4Ä'5BÄ

ê Ç <GÕBÄ

ÏèÐ ä TACACS+á<ÞÈGÇX nas Ç,X0GÊÉAÇA'5B TACACS+y[,Xê¶ÄÇy¡X1Ç ip 0 TACACS+y[,Xê¶ÄÇ'ÏÄ

ÏGÕB_Ð MI6,X/_ÇZ TACACS+y[¢ fastEthernet 0/0 y9ª ip 90 TACACS+y[,Xê¶Ö

5XLMLHFRQILJWDFDFVVRXUFHLQWHUIDFHIDVW(WKHUQW

ÎÌGÐ

Ç	ÉÄ

Ï-DAêð

–D	Ë.Ä
vrf-name	vrf á«

Ï,ÕG5BÐ -

Ïê TACACS+á<4ĞG5Bäá

ÏÊÔ ûÙ,X TACACS+á<4ûÙ vrf á«Ä

ĞG5B_Ð ®M6/_ TACACS+á<4ûÙ VRF á« vpn1Ö

```
5XLMLHFRQILJXUHVHUYHUWDFDFVWDF
5XLMLHFRQILJWDFDFVVHUYHU
5XLMLHFRQILJWDFDFVLSYUIIRUWDUGLQSQ
```

ÏĞÇÐ

Ç	Ë.Ä
aaa group server tacacs+	**G5B** TACACS+á<4˜
server	**G5B** TACACS+á<4¸˜X server ë<

ĞGÄêð -

3.5 server(TACACS+)

8ÇG5B TACACS+á<4¸˜Xá<Ä

server {*ip-address* | *ipv6-address*}

no server {*ip-address* | *ipv6-address*}

ÐAêð

–D	Ë.Ä
ip-address	TACACS+á<4¸˜Xá< IP
ipv6-address	TACACS+á<4¸˜Xá< IPV6

Ï,ÕG5BÐ -

Ïê TACACS+á<4ĞG5Bäá

ÏÊÔ G5B8ÇÑOEËÇ **aaa group server tacacs+**Ë TACACS+4ĞG5Bäá TACACS+á<4ĞG5B,Xá<ÑOäG5BäËÉ› **tacacs-server host ÇG5B 8áÄ**

á<4¸˜XG5B,X TACACS+á<ðê<ú¡ýðê<ËÃÕÄ

ĞG5B_Ð ®M6,X/_G5Bðê tac1 ,X TACACS+á<4êÄ4ĞG5Bðê 1.1.1.1 ,X TACACS+ á<Ö

```
5XLMLHFRQILJXUHVHUYHUWDFDFVWDF
5XLMLHFRQILJWDFDFVVHUYHU
```

ÏÎGĘ

Ç	Ł Ä
aaa group server tacacs+	**G5B** TACACS+á<4˜
ip vrf forwarding	**G5B** TACACS+á<4ÇX VRF á

ĞGÄê -

3.6 show tacacs

/Ø TACACS+á<,XxfE¤ Ø‰

show tacacs

ĐAê

–D	Ł Ä
-	-

ĕ,Õ5BĐ -

ê Ç (Mã

ĞÊ SÆÇØ TACACS+á<,XxfE¤ Ø‰

ĞG5B_Đ

```
5XLMLHVKRWDFDFV
7DFDFV6HUYHU
6RFNHW2SHQ
6RFNHWRVHV
7RWDO3DFNHWV6HQW
7RWDO3DFNHWV5HFY
5HIHUHHRXQW
```

ÏÎGĘ

Ç	Ł Ä
tacacs-server host	**n** TACACS+]<á<,X

ĞGÄê -

3.7 tacacs-server host

8Ç5B TACACS+á< IP Ä

tacacs-server host {*ip-address* | *ipv6-address*} [**port** *integer*] [**timout** *integer*] [**key** *string*]

no tacacs-server host {*ip-address* | *ipv6-address*}

Ï–DAèð

–D	ÆÄ
Ip-address	TACACS+]<á<,X IP Ä
ipv6-address	TACACS+]<á<,X IPV6 Ä
port *integer*	TACACS+EÂ§ÞX TCP 0Ã
timeout *integer*	TACACS+,XCYÊÆÃ
key *string*	TACACS+ client á<E•Xß¾Ä

ß,Ø5BÐ ùÙ,X TACACS+Ä

ðÇ <G5BÃá

ßÐ Sù TACACS+r)„ AAA]<áÈ¥On TACACS+]<á<þÃù **tacacs-server host** ÇÊ TACACS+]<á<Ä

Ø5B_Ð ¥6,X/_nÞ TACACS+]<á<Ö

5XLMLHFRQWDFDFVVHUYHUKRVW

5XLMLHFRQWDFDFVVHUYHUKRVW

ÏØÇÐ

Ç	ÆÄ
aaa authentication	**n** AAA ,XDÑxAè<
tacacs-server key	**ñ** TACACS+]<á<,XE¸•
tacacs-server timeout	**ñ** TACACS+á<hy[CYÊÆ

ØÄèð -

3.8 tacacs-server key

5Bkey EMM,Xá<G5BÐ keyÄ

ËG5B_Ð MI6,X/_n TACACS+]<á<,XE¸• aaaÖ

5XLMLHFRQWDFDFVVHUYHUNHDDD

ÏÎGÐ

Ç	ÉÄ
tacacs-server host	**n** TACACS+]<á<,X
tacacs-server timeout	**n** TACACS+y[CYÊÈ

ËGÄê -

3.9 tacacs-server timeout

8Ç5Bâ TACACS+á<EÄÐÊYá<,X<CYÊÈ

tacacs-server timeout *seconds*

no tacacs-server timeout

ÐAê

–D	ÉÄ	
seconds	CYÊÐÃ'5B,X8è	1-1000 /Ä

Ë,Õ5BÐ 5 /¦

Ê <G5Bá

ËÐ SÄÐy[,XCYÊÈ> A+ÀÂÔÐá<ûàXCYÊÈŠ

tacacs-server host Ç **timeout ÁÑÈ5Ê5B** **timeout ÁÑ**

áG5Ð **timeoutÄ**

ËG5B_Ð MI6,X/_ÚYÊè 10 /Ö

5XLMLHFRQWDFDFVVHUYHUWLPHRXW

ÏÎGÐ

Ç	ÉÄ
tacacs-server host	**n** TACACS+]<á<,X
tacacs-server key	**n** TACACS+,XE¸•

ËGÄê -

4 802.1X

4.1 dot1x auth-address-table

no **dot1x auth-address-table address** *mac-addr* **interface** *interface*

dot1x auth-address-table address *mac-addr* **interface** *interface*

–D	
mac-addr	
interface	

Ï5,Õ¥5BÐ Vp AAA ¦ÐD)AxA5,ÕXÉü AAA áÄ

Ïð yG5Bå

ÏÉð Vpü AAA]<áÆÐ dot1x

Ïêð Êü **show dot1x** ¡Ç 802.1x A'5BÄ

Ïê 852.1x A'5B GŒ@

ÏGÄê -

4.7 dot1x auto-req packet-num

A’5BA’ÎÄxAÄÿ¿X ÐÈo 6ÊÄxÄ

dot1x auto-req packet-num *num*

no dot1x auto-req packet-num

ÐÄê

–D	Ë.Ä
num	**AÎÄxAÄÿ¿X ÐÄ**

Ï,Õ5BÐ num = 0; GÕÍÄÕ

ÿÐ <G5BÄ

Ï5Ð A’5BA’ÎÄxAÄÿ¿X ÐÊÄú **show dot1x auto-req** ÇÄs6ÑXA’5BÄ

Ï5B_Ð MI6A’5BA’ÕÇ¢K 802.1x AxA¬X_Ð

```
5XLMLHFRQDXWUHWUPLQO
5XLMLHFRQG5RW[DXWRUHTSDFNHWXQP
5XLMLHFRQHQ
5XLMLHVKRZ5RW[DXWRUHT
[XWR5HT(QEOHG
8VHUHWFW(QEOHG
3DFNHW1XP
5HT,QWHUYDO6HFRQ
```

ÎÏGÐ

Q	Ë.Ä
show dot1x auto-req	**ÞAxA¬XA5Þ**

ÏGÄê -

4.8 dot1x auto-req req-interval

A’5BA’ÎÄxAÄÿ¿XÊÊÈhèoTc 0 -1.793 TD<01CF210.199<2C5801520E4E3EDB1>7<9A54178E54A354200610

ÏÒ <GÕBÄ

ÏôÖ A’5BA’ÎÄxAÄÿ[,XÊÈÈhÊÄü **show dot1x auto-req** Ïs6ÑXA’5BÄ

ÏGÕB_Ð MA6A’5BA’ÊK 802.1x AxAÊÈÈh 60s ,X_ÊÖ

```
5XLMLHFRQIXUHWHUPLQDO
5XLMLHFRQIGRW[DXWRUHTUHTLQWHUYDO
5XLMLHFRQIHQG
5XLMLHVKRZGRW[DXWRUHT
[XWR5HT(QEOHG
8VHUHWHFW(QEOHG
3DFNHW1XP
5HT,QWHUYDO6HFRQ
```

ÎGÇÑ	Ç	ÉÄ
	show dot1x auto-req	**ÏAxAÄXA5ÏÄ**

ÏGÄÈ -

4.9 dot1x auto-req user-detect

A’5BA’ÛÑp,ÄxAÉÉ›XÈ¦ÑxAÄÿ[ñ **6ÊAxÄ**

dot1x auto-req user-detect

no dot1x auto-req user-detect

ÐAÈ

–D	ÉÄ
-	-

Ï,ÕÖ5BÐ Ô

ÏÒ <GÕBÄ

ÏôÖ A’5BA’ÛÑp,ÄxAÉÉ›XÈ¦ÑxAÄÿ[ÑÊü **show dot1x auto-req**

Ïs6ÑXA5ÏÄ

ÏGÕB_Ð MA6A’5BA’ÛÑ“ÈÍ0ÊÑ[ÕxAÄÿ[Ö

```
5XLMLHFRQIXUHWHUPLQDO
5XLMLHFRQIGRW[DXWRUHTXVHUGHWHFW
5XLMLHFRQIHQG
5XLMLHVKRZGRW[DXWRUHT
[XWR5HT(QEOHG
8VHUHWHFW(QEOHG
3DFNHW1XP
5HT,QWHUYDO6HFRQ
```

ÏĈĢĘ	Ǫ	[redacted]
	show dot1x auto-req	**ƀAxAɣXA5ƀÄ**

ĠÄȁ **-**

4.10 dot1x client-probe enable

ƱÔÃ“vs#6Ñ

dot1x client-probe enable

no dot1x client-probe enable

ĐAȁ	–D	ĿÄ
	-	-

Ï,Õs“““““Ĥ[illegible]ÔÃV01ɜMȁMȁ[illegible]r99999ĐÑMAaȁĤ01ɜ4@

ÏGÄê -

4.11 dot1x critical

Ý RADIUS AxAá<<ÍÊX 802.1x AxAÊ<ÌúÝG5BJWÈ
,ÊxAÈÊ“KÂ%4ËÆÀ¼“KÂ%4ÆÊÃ
Ê<CÃxAÄaccessible Authentication Bypass ÈT/Ä IABsÅ6Ñ
Sú **no ÉÊÇ4ÇÕ**
dot1x critical
no dot1x critical

ÐAê	
–D	Ë Ä
-	-

Ï5,Õ5BÐ 5,ÕKÁ

Ïê 0Ç5Bã

ÏÊÐ 0Ê IAB s6ÑÍp<G5B,X 802.1x AxAÊ<,Ù RADIUS AxAÊÆ©
ë<,X RADIUS á<<FÆÊÈ› IAB é= 5%4Ã“KÊÆÕ
EAPOL-SUCCESS y[Ä
Vp 802.1x AxAÊ<ÈB RADIUS AxAÊ,ÙAxAÊ© IAB sÆÑÐ
aaa authentication dot1x default group radius noneÈ RADIUS AxAÊ,ú none AxA•
Å
ÍbÈ› IAB ÊXÈb'BAxÐ¡ÑÊÆ6G5BAuä6ÑÍ
a¢KAuÄÆ
<Ô AAA ÃxAs6Ñ02.1x ÄxAÊSúG5B,XÊ<Äb IAB s6Ñ
• 802.1x <G5BÊ<,X RADIUS á<<F,ÿÊÃxAäÊÐEg9ú
ê AAA ÃxAs6Ñ0Ã

Ï5B_Ð
```
5XLMLHFRQXUHWHUPLQO
(QDEOHFRQXUDWLRQRPPDQGVRQSHUOLQH(QWHUWK27/=
5XLMLHFRQILQHUIDFHID
5XLMLHFRQILGRW[
```

ÎGÇ	
Ç	Ë Ä
-	-

ÏGÄê -

4.12

RADIUS

VLAN

VLAN

```
5XLMLHFRQ[XUHWHUPLQO
5XLMLHFRQGRW[HDSROWDJ
5XLMLHFRQHWKQ
5XLMLH
```

ÏÎGÇ	
Ç	Ë
show dot1x	ß 802.1x ,XA'5BÇÄ

ÜGÄß -

4.17 dot1x guest-vlan

G5BÁŒ **guest vlan** CÇßÄÇX **no** EÝMÑßKÁÊÄ
dot1x dynamic-vlan *vid*
no dot1x guest-vlan

ÐAß

–D	Ë
vid	**ÐX8È**1 - 4094>

Ü,Õ5BÐ 5,ØÊGKÁ

ÇÐ 0Ñ5B

ÜÐ 1Ê Sú guest vlan sÇÑG5B **dot1x dynamic-vlan enable** guest vlan Á
1 G5B guest vlan sÇÂ0,X2ßG5B0Ñþ vlanÄ
1 ú **show running-config** 802.1x A'5BÄ

ÜG5B_Ð MÍ6A'5B 802.1x ,X guest vlan CÇ_Ð
```
5XLMLHFRQ[XUHWHUPLQO
5XLMLHFRQGRW[XHVWYODQ
5XLMLHFRQHWKQ
5XLMLH
```

ÏÎGÇ	
Ç	Ë
show running-config	ß 802.1x ,XA'5BÇÄ

ÜGÄß -

4.18 dot1x mac-auth-bypass

A'5B MAC ÇÃxAÄ
dot1x mac-auth-bypass

no dot1x mac-auth-bypass

Ð Aß –D

ÏÎGÐ		
	Ç	Ë Ä
	show dot1x port-control interface	ß X 802.1x Ç Ä

ËGÄß -

4.20 dot1x mac-auth-bypass violation

A’5B 802.1x MAC ÇÃxA¸XE±Ä

dot1x mac-auth-bypass violation

no dot1x mac-auth-bypass violation

ËÐAß		
	–D	Ë Ä
	-	-

Ë¸,Õ5BÐ 5,Ð±ý

ËÐ yG5Bß

ËÐ ßSú **show run** Ç 802.1x A’5BÄ

ËG5B_Ð ¾M6A’5B 802.1x MAC ÇÃxAË±,X_ß

```
5XLMLHFRQIXUHWHUPLQDO
5XLMLHFRQIQWHUIDFHID
5XLMLHFRQIIGRW[PDFDXWKEVSDVVYLRODWLRQ
5XLMLHFRQIIHQ
5XLMLHØLWH
```

ÏÎGÐ		
	Ç	Ë Ä
	show dot1x port-control interface	ß X 802.1x Ç Ä

ËGÄß -

4.21 dot1x mac-move permit

G5B 802.1x ßxAËËßËÜV0ßßËÜV0ßÑ

A0ßÃ“KßÂ%4Ä

Sú **no ÉÑÇ6Ð**

dot1x mac-move permit

no dot1x mac-move permit

show dot1x	ß 802.1x ,XA'5BÇÄ

ÏGÄß -

4.23 dot1x port-control auto

ÿGÕ5BßÈ'5BAÿútAxAËßÄÇX **no** EÝMÚA'5B6å,Ã

dot1x port-control auto

no dot1x port-control

ÐAß	–D	Ë Ä
	-	-

Ï,Õ5BÐ y5,ê 802.1x AxA• Ä

ß yGÕ5Bã

Ï ÆÜ Ã¨ **show dot1x** ß 802.1x A'5BÄ

ÏÕ5B_Ð MÍ6A'5B0Ã 802.1x –åAxA•X_Ï

```
5XLMLHFRQIXUHWHUPLQDO
5XLMLHFRQIQWHUIDFH
5XLMLHFRQIIGRW[SRUWFRQWURODXWR
5XLMLHFRQIIHQG
5XLMLH
```

ÎGÇ

Ç	Ë Ä
show dot1x	ß 802.1x ,XA'5BÇÄ

ÏGÄß -

4.24 dot1x port-control-mode

802.1x ÍX{TAxÃ MAC E> {,XÆEAxA•XÑ5%4Èà

```
bÿÇÃXÑ5%4Èà0ÃX{à<ÇÃxA•
EÈÈ0ÃxA0ÃÑ0ÃÑ5%4Ê0Ãü
,X{à0ÃÇÃxAÈÈÈ0ÃxA0ÃÑ,XSÑ5%4Ä
ÿÇX{ÃxA0ÃpÿÇÃW,XÇÃÝ
ÆÈGÃxAÇ5BAxAÃÇÇÖ
```

dot1x port-control-mode {**mac-based** | {**port-based** [**single-host**]} }

no dot1x port-control-mode

Ï-DAèê	–D	Ë Ä
	mac-based	**îb** mac ,X 802.1X A“KÂ
	port-based	**îb0Ã** 802.1X A“KÂ
	single-host	**îb0ÃÀ** 802.1x A“KÂ

ï,Õ5BÐ 5,õ mac-based A“KÂ

ëÇ yG5Bâ

ÏÊÎ Ê ü **show dot1x port-control ÎÃ** 802.1x A’5BÄ
single-host îb0Ã¢ü X 802.1x A“KÂÈ **show dot1x port-control ÎÃ**
port-basedÈ **show running-config î dot1x port-control-mode port-based single-host**Ä
single-host +bÎÃG5B0Ãdefault-user-limit È single-host ê
G5B single-host êÃ5B default-user-limitÈÐGÉ single-host ù¼3Ê0Ã¾
AÎÊ%Ä

Ï5B_Ð _ 1Ê6A’5B0Ã 802.1x –âxA¸X_Ê

```
5XLMLHFRQILJXUH
5XLMLHFRQILJIGRW[SRUWFRQWURODXWR
5XLMLHFRQILJIGRW[SRUWFRQWUROPRGHSRUWEDVHG
5XLMLHFRQILJIHQG
5XLMLH
```

_ 2Ê6A’5B0Ã¢ü 802.1x AxA¸X_Ê

```
5XLMLHFRQILJXUH
5XLMLHFRQILJIGRW[SRUWFRQWURODXWR
5XLMLHFRQILJIGRW[SRUWFRQWUROPRGHSRUWEDVHGVLQJOHKRVW
5XLMLHFRQILJIHQG
5XLMLH
```

ÎÏGÐ	Ç	Ë Ä
	show dot1x port-control	**ÎÃ** 802.1x ,XA’5BÇÄ
	Show running-config	**Î6A5BÄ**

ÏGÄè -

4.25 dot1x private-supplicant-only

ïG5Bâ’5BÎÃ0Ão EÍMÚA’5B6á,Ã
dot1x private-supplicant-only
no dot1x private-supplicant-only

Ð Aè	–D	Ë Ä

-	-

Ï5,Õ5BÐ 5,6Ş$

Ïê <G5BÃ

ÏÐ Ã¤ **show dot1x private-supplicant-only** Ç 802.1x A’5BÄ

ÏG5B_Ð MM6A’5BSÃ0Ã_Ð

```
5XLMLHFRQ[
5XLMLHFRQGRW[SULYDWHVXSSOLFDQWRQ\
5XLMLHFRQHQ
5XLMLH
```

ÏÎGÇ

Ç	Ë
show dot1x private-supplicant-only	**A5BÄ**

ÏGÄ -

4.26 dot1x probe-timer

G5Bv0Ã#Ê.

dot1x probe-timer{**interval** | **alive**}*interval*

no dot1x probe-timer

ÐÄ

–D	Ë

```
+HOOR,QWHUYDO6HFRQV
+HOORSLYH6HFRQV
```

ÎÍGÇ

Ç	ÉÄ
Show dot1x probe-timer	**/v0ÃVr#G5Ë**

ÏGÄè -

4.27 dot1x re-authentication

SÄÇ'5BÚ'GAËbGAxAÄÇ **no** EÍMÚA'5B6á,Ã

dot1x re-authentication

no dot1x re-authentication

ÐAè

–D	ÉÄ
-	-

Ï,Õ5BÐ 5,ÐGAËbGAxAÄ

Ç <G5BÄ

ÏÐ A'5BÄÇxAGAËÙxAÉÈÈÊÈÍOGAxÃÏÚ **show dot1x Q**

ß 802.1x A'5BÄ

Ï5B_Ð MÍ6ÔAxAs6Ñ

```
5XLMLHFRQ;UHWHUPLQO
5XLMLHFRQGRW[UHDXWKHQWLFDWLRQ
5XLMLHFRQJHQ
5XLMLHVKRZGRW[
;6WDWXV(QEOHG
;XWKHQWLFDWLRQRGH($0'
;XWKG8VHU1XPEHU
5HDXWKHQ(QEOHG(QEOHG
5HDXWKHQHULRGVHF
4XLHW7LPU3HULRGVHF
7[7LPU3HULRGVHF
6XSSOLFDQW7LPHRXWVHF
6HUYHU7LPHRXWVHF
5HDXWKHQD[WLPHV
0D[LPXP5HTXHVWWLPHV
)LOWHU1RQ6XSSLVDEOHG
2LHQW2OLQ3UREHLVDEOHG
(DSRO7DQEOHLVDEOHG
```

```
¥XWKRUL]DWLRQ RRGH URXS6HUYHU
```

ÏÎGÇ

Ç	ÉÄ
show dot1x	ß 802.1x ,XA'5BÇÄ

ÜGÄß -

4.28 dot1x reauth-max

SÄÇ'5BGAÉÕ¸AxA•ÐÄÄÇX **no** ÉMMÚA'5B6ß,Õ
dot1x reauth-max *count*
no dot1x reauth-max

ÜÐAß

–D	ÉÄ
count	**Õ¸AxA•ÐÄ**

Ü,Õ5BÐ 5,Õ 3

Çß <G5Bß

ÜÕ A'5BÄÇxAGAÉÕ¸AxAB¸X ßß **show dot1x** Çß 802.1x A'5BÄ

Ü5B_Ð MI6A'5BG¸AxAÕs6Õ

```
5XLMLHFRQXUHWHUPLQO
5XLMLHFRQGRW[UHDXWKPD[
5XLMLHFRQHQ
5XLMLHVKRZGRW[
;6WDWXV(QEOHG
¥XWKHQWLFDWLRQRGH(¥0'
¥XWKHG8VHU1XPEHU
5HDXWKHQWEOHG(QEOHG
5HDXWKHQHULRGVHF
4XLHW7LPU3HULRGVHF
7[7LPU3HULRGVHF
6XSSOLFDQW7LPHRXWVHF
6HUYHU7LPHRXWVHF
5HDXWKHQD[WLPHV
0D[LPXP5HTXHVWWLPHV
)LOHU1RG6XSSLVDEOHG
¥LHQW2OLH3UREHLVDEOHG
(DSRO7DQEOHLVDEOHG
¥XWKRUL]DWLRQRGH URXS6HUYHU
```

ÏÎGÇÐ	Ç	ÉÄ
	show dot1x	ß 802.1x ,XA'5BÇÄ

ËGÄß -

4.29 dot1x stationarity enable

802.1x ÎÒ0Ã×{ßÄxÇßÕÉ¾CÉÉMß½

A}ÉÑÚ 802.1X 0ÕÉ9ÉEG5BÇ',Â×Ä

dot1x stationarity enable

no dot1x stationarity enable

ËÐAß	–D	ÉÄ
	-	-

Ë5,Õ5BÐ 5,ÇÕÉ¾CÉÄ

ËÇ <G5BÄ

ËÐ LÔÉÄxAÉG5BÄÇÇÔÉGÄxAÄ

ËG5B_Ð MI6A'5B0Ã 802.1x –ÄxA•X_Ð

```
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJGRW[VWDWLRQULWHQEOH
5XLMLHFRQILJHQ
5XLMLH
```

ÏÎGÇÐ	Ç	ÉÄ
	-	-

ËGÄß -

4.30 dot1x timeout quiet-period

SÄÇ'5BA'ÔxABÄVAxÄÇÃÉGÄxA•X1YÉÇDÃú

AÇX **no** EÍMMÔA'5B6ã,Õ

dot1x timeout quiet-period *seconds*

no dot1x timeout quiet-period

ËÐAß	–D	ÉÄ
	seconds	**AÔxAxfßÉGÄxAX1ÐÈ** 0 65535Ä s

Ï5,Õ5BÐ 5,Õ 10 /Ä

Ïç <G5BÃ

ÏÊÔ GAËÙxABÅÖÉ€KGçAxAÈÙO1YÖÃü **show dot1x** Ïç

ÏG5B_Ð ÍM6A'5BGçAxA¹YÊÈ 1000sÖ

```
5XLMLHFRQ;XUHWHUPLQO
5XLMLHFRQGRW[WLPHRXWTXLHWSHULRG
5XLMLHFRQHIQ
5XLMLHVKRZGRW[
;6WDWXV(QEOHG
;WKHQWLFDWLRQRGH($0'
;WKHG8VHU1XPEHU
5HDXWKHQEOHGLVBEOHG
5HDXWKHQHULRGVHF
4XLHW7LPU3HULRGVHF
7[7LPU3HULRGVHF
6XSSOLFDQW7LPHRXWVHF
6HUYHU7LPHRXWVHF
5HDXWKHQD[WLPHV
0D[LPXP5HTXHVWWLPHV
)LOWHU1RW6XSSLVBEOHG
KLHQW2OLQ3UREHLVBEOHG
(DSO7DQEOHLVBEOHG
;WKRUL]DWLRQRGHURXS6HUYHU
```

ÏÎGÇÐ

Ç	Ë Ä
show dot1x	ß 802.1x ,XA'5BÇÄ

ÏGÄß -

4.31 dot1x timeout re-authperiod

Ø"GAËÙÊçAxA¸XÔÊßÅÇ'5BGAËÙXGçAxAÊÈÈhÈAxA<ßü

AÇX **no** EÍMMÁA'5B6ß,Õ

dot1x timeout re-authperiod *seconds*

no dot1x timeout re-authperiod

ÐAß

–D	Ë Ä
seconds	**AxAçÃ8È** 0 65535ÿÄ sÄ

Ï5,Õ5BÐ 3600 /¦

ÄÐ <G5BÃ

ÏÊÐ ÃÚ **show dot1x** [Ç 802.1x A'5BÄ

ÏG5B_Ð ÍM6A'5BGÆxA<ó 1000sÖ

```
5XLMLHFRQWUHWHUPLQO
5XLMLHFRQGRW[WLPHRXWUHDXWKSHULRG
5XLMLHFRQJHQ
5XLMLHVKRZGRW[
;6WDWXV(QEOHG
XWKHQWLFDWLRQRGH(STD
XWKHG8VHU1XPEHU
5HDXWKHQWEOHGLVDEOHG
5HDXWKHQHULRGVHF
4XLHW7LPU3HULRGVHF
7[7LPU3HULRGVHF
6XSSOLFDQW7LPHRXWVHF
6HUYHU7LPHRXWVHF
5HDXWKHQD[WLPHV
0D[LPXP5HTXHVWWLPHV
)LOWHU1RSXSSLVDEOHG
QLHQW2OLF3UREHLVDEOHG
(DSO7DQEOHLVDEOHG
XWKRUL]DWLRQRGHURXS6HUYHU
```

ÎÏGÇ

Ç	ÆÄ
show dot1x	Ç 802.1x ,XA'5BÇ

ÏGÄè -

4.32 dot1x timeout server-timeout

AÇ'5BA'ÊxAá<KÈxAxf,XCYÉÃÇX **no** EÍMÁA'5B6ã,Õ

dot1x timeout server-timeout *seconds*

no dot1x timeout server-timeout

ÐAè

–D	ÆÄ
seconds	**AÊxAáÈxAxfXCÉ8È** 0 65535Ä

ã,Õ5BÐ 5,Õ 5 /Ä

ÄÐ <G5BÃ

ÏÔ5Ð ÆÃü **show dot1x** [Ç 802.1x A’5BÄ

ÏG5B_Ð MM6A’5Bá<xfCYÊÈÈ 10sÖ

```
5XLMLHFRQWXUHWHUPLQDO
5XLMLHFRQWGRW[WLPHRXWVHUYHUWLPHRXW
5XLMLHFRQWHQG
5XLMLHVKRZGRW[
;6WDWXV(QEOHG
6WKHQWLFDWLRQRGH($0'
6WKHG8VHU1XPEHU
5HDXWKHQWEOHGLVDEOHG
5HDXWKHQWHULRGVHF
4XLHW7LPHU3HULRGVHF
7[7LPHU3HULRGVHF
6XSSOLFDQW7LPHRXWVHF
6HUYHU7LPHRXWVHF
5HDXWKHQD[WLPHV
0D[LPXP5HTXHVWWLPHV
)LOWHU1RG6XSSLVDEOHG
2LHW2OLQ3UREHLVDEOHG
(DSRO7DJEOHLVDEOHG
6WKRUL]DWLRQRGHURXS6HUYHU
```

ÏÎGÐ

Ç	ÆÄ
show dot1x	¦ß 802.1x ,XA’5BÇ

ÏGÄÈ -

4.33 dot1x timeout supp-timeout

AÇ’5BA’ÎGAÈÈÈxAxf,XCYÊÈÃÇX **no** EMÍÁA’5B6È,Õ

dot1x timeout supp-timeout *seconds*

no dot1x timeout supp-timeout

ÏÐAÈ

–D	ÆÄ
seconds	**AÎGAÈÈxAxfXCÊ8È** 0 65535Ä

Ï,Õ5BÐ 5,Õ 3 /Ä

Ï 5BÃ

ÏÔ5Ð ÆÃü **show dot1x** [Ç 802.1x A’5BÄ

ÏG5B_Ð MM6A’5Bv0ÃfCYÊÈÈ 10sÖ

```
5XLMLHFRQILXUHWHUPLQDO
5XLMLHFRQILGRW[WLPHRXWVXSSWLPHRXW
5XLMLHFRQILJHQ
5XLMLHVKRZGRW[
;6WDWXV(QEOHG
6XWKHQWLFDWLRQRGH($0'
6XWKHG8VHU1XPEHU
5HDXWKHQWEOHGLVDEOHG
5HDXWKHQHULRGVHF
4XLHW7LPU3HULRGVHF
7[7LPU3HULRGVHF
6XSSOLFDQW7LPHRXWVHF
6HUYHU7LPHRXWVHF
5HDXWKHQD[LPHV
0D[LPXP5HTXHVWWLPHV
)LOWHU1RS6XSSLVDEOHG
2LHQW2OLQ3UREHLVDEOHG
(DSO7DQEOHLVDEOHG
6XWKRUL]DWLRQRGHURXS6HUYHU
```

ÏĞĢ	Ç	Ł Ä
	show dot1x	ß 802.1x ,XA’5BÇÄ

ÜĠÄß -

4.34 dot1x timeout tx-period

A’5BÿZ[GÇXÔßÄÇ’5BĠÇXÊÈÈÈĠĠĝßÄÇX **no** EÝ
NMÉÄA’5B6ã,Õ

ª\@

```
5XLMLHFRQWURO
5XLMLHVKRWGRW[
;6WDWXV(QDEOHG
6XWKHQWLFDWLRQRGH(SRO'
6XWKG8VHU1XPEHU
5HDXWKHQWDEOHGLVDEOHG
5HDXWKHQWHULRGVHF
4XLHW7LPHU3HULRGVHF
7[7LPHU3HULRGVHF
6XSSOLFDQW7LPHRXWVHF
6HUYHU7LPHRXWVHF
5HDXWKHQD[WLPHV
0D[LPXP5HTXHVWWLPHV
)LOWHU1RQ6XSSLVDEOHG
&OLHQW2OLQH3UREHLVDEOHG
(DSOO7DJ(QDEOHLVDEOHG
6XWKRUL]DWLRQRGH'URS6HUYHU
```

ÏÎGÇ

Ç	ÉÄ
show dot1x	ß 802.1x ,XA'5BÇÄ

ÜGÄß -

4.35 aaa authorization ip-auth-mode {disabled | dhcp-server | radius-server | supplicant }

A'5B ip \,Xß disableÈdhcp-server Èradius-server ` supplicant ã

aaa authorization ip-auth-mode {**disabled** | **dhcp-server** | **radius-server** | **supplicant** }

no aaa authorization ip-auth-mode

ÜÐAß

–D	ÉÄ
disabled	ip \ disable ã
dhcp-server	ip \ dhcp-server ã
radius-server	ip \ radius-server ã
supplicant	ip \ supplicant ã

Ü,Õ5BÐ 5,Õ disable ã

Çß <G5BÄ

ÜßÐ ÉÜ **show running-config** ÇÇ A'5BÄ

ÜG5B_Ð ÑM6A'5B ip ã radius-server

```
5XLMLHFRQILXUHWHUPLQDO
5XLMLHFRQILDDDDEHQRGHO
5XLMLHFRQILDDDDXWKRUL]DWLRQSDXWKPRGHUDGLXVVHUYHU
5XLMLHFRQILHQ
5XLMLHVKRZXQRQJ
```

```
5HDXWKHQ D[WLPHV
0D[LPXP5HTXHVWWLPHV
)LOWHU1RQ 6XSSLVDEOHG
&OLHQW2OLQH3UREHLVDEOHG
(DSRO7DQ EOHLVDEOHG
$XWKRUL]DWLRQ RGH*URXS6HUYHU
0RYH3HUPLW Q EOHG
```

ÏĜĐ

Q	ĘÄ
dot1x auth-mode	**A5B** 802.1x ,XAxAÄ
dot1x max-req	**A5B ÕĞ[X ÐÄ**
dot1x port-control auto	**A5B ÁxAÄ**
dot1x reauth-max	**A5B AÖÕĜ AxA Ð**
dot1x re-authentication	**A5B ĜAÈĜ AxAÄ**
dot1x timeout quiet-period	**A5B xAÈĜ AxA 1Ä**
dot1x timeout re-authperiod	**A5B AÈĜ AxAÄ**
dot1x timeout server-timeout	**A5B xAÈ xAxfXCÄ**
dot1x timeout supp-timeout	**A5B ĜAÈ xAxfXCÄ**
dot1x timeout tx-period	**A5B ĜÄÈĜÄ**

ĞÄĐ   -

4.37 show dot1x auth-address-table

AĐ   802.1X AÆxA,X><Ä

show dot1x auth-address-table[*addressmac-addr*][*interface interface*]

ĐAĐ

–D	ĘÄ
mac-addr	**ÃxAX(}Ú**
interface	**yË**

Ĕ,Õ5BĐ   -

ĔpÜĕ"i"i"i"i"i"i"i"i"mF43VA" ĔpÜĜs=ÄÌpÜi"i"i"i"i"i"i"i"i•ĞRG_Ė04D@AHiRe@@

ÏĈĢĘ

Ę	ĘÄ
dot1x auth-mode	**A5B** 802.1x ,XAxAÄ
dot1x max-req	**A5B**ĘĈĢ[X ĐÄ
dot1x port-control auto	**A5B**ÉAxAÄ
dot1x reauth-max	**A5B**AĖĈĘAxA•Đ
dot1x re-authentication	**A5B**ĈAĖĈĢAxAÄ

dot1x timeout re-authperiod	**A5BAÊ)GAxAÊÄ**

C4>Tj /TT0 1 Tf ( )T07.8 0.602 g 11

Ïê(Mã

ÏÊê -

ÏG5B_Ð MI6/_ê

```
5XLMLHVKRZGRW[SULYDWHVXSSOLFDQWRQ\
SULYDWHVXSSOLFDQWRQGLVDEOHG
5XLMLH
```

ÏÎGÇ

Ç	ÉÄ
dot1x auth-mode	**A5B** 802.1x ,XAxAÄ
dot1x max-req	**A5B** [X ÐÄ
dot1x port-control auto	**A5B** AxAÄ
dot1x reauth-max	**A5B** AxA•Ð
dot1x re-authentication	**A5B** AxAÄ
dot1x timeout quiet-period	**A5B** AxA X1Ê
dot1x timeout re-authperiod	**A5B** AxAÊÄ
dot1x timeout server-timeout	**A5B** AxA xAxfXCÊ
dot1x timeout supp-timeout	**A5B** AxA xAxfXCÊ
dot1x timeout tx-period	**A5B** AxA

ÏÄÄê -

4.42 show dot1x probe-timer

/v0Ã“v#ÊG5B

show dot1x probe-timer

ÏÐAê

–D	ÉÄ
-	-

Ï,Õ5BÐ -

Ïê(Mã

ÏÊê /v0Ã“v#ÊG5B

ÏG5B_Ð MI6/_ê

```
5XLMLHVKRZGRW[SUREHWLPHU
+HOOR,QWHUYDO6HFRQV
+HOORSLYH6HFRQV
```

ÏĈĢĮ

Ç	Ł Ä
dot1x auth-mode	**A5B** 802.1x ,XAxAÄ
dot1x max-req	**A5B**Ê Ô ê p [X Ð Ä
dot1x port-control auto	**A5B** ÿ é AxAÄ
dot1x reauth-max	**A5B** Ä Ë Ô Ą AxA • Ð
dot1x re-authentication	**A5B** Ø Ć A Ë ò Ĉ Ą AxAÄ
dot1x timeout quiet-period	**A5B**ÊxA**Ê**Ê Ĉ Ą AxA Ɣ 1 Ê
dot1x timeout re-authperiod	**A5B** Ä Ë Ø Ĉ Ą AxA Ê Ä
dot1x timeout server-timeout	**A5B**ÊxA á Ê xA x fƔ C Ê
dot1x timeout supp-timeout	**A5B**Ê Ô A Ë Ê xA x fƔ C Ê
dot1x timeout tx-period	**A5B** Ĉ ß Ê Ê Ĉ Ą

ĊÄÊ -

4.43 show dot1x re-authentication

/GĄxAĊ5B

show dot1x re-authentication

ĊAÊ

–D	Ł Ä
-	-

Ƃ,Õ5BĐ

Ê (Mã

ĊƑ GĄxAĊ5B‰

ĊG5B_Đ ℳ6/_Ƒ

```
5XLMLHVKRWGRW[UHDXWKHQWLFDWLRQ
UHDXWKHQWEOHGGLVDEOHG
```

ÏĈĢĮ

Ç	Ł Ä
dot1x auth-mode	**A5B** 802.1x ,XAxAÄ
dot1x max-req	**A5B**Ê Ô ê p [X Ð Ä
dot1x port-control auto	**A5B** ÿ é AxAÄ
dot1x reauth-max	**A5B** Ä Ë Ô Ą AxA • Ð
dot1x re-authentication	**A5B** Ø Ć A Ë ò Ĉ Ą AxAÄ
dot1x timeout quiet-period	**A5B**ÊxA**Ê**Ê Ĉ Ą AxA Ɣ 1 Ê
dot1x timeout re-authperiod	**A5B** Ä Ë Ø Ĉ Ą AxA Ê Ä
dot1x timeout server-timeout	**A5B**ÊxA á Ê xA x fƔ C Ê
dot1x timeout supp-timeout	**A5B**Ê Ô A Ë Ê xA x fƔ C Ê
dot1x timeout tx-period	**A5B** Ĉ ß Ê Ê Ĉ Ą

ÏGÄð -

4.44 show dot1x reauth-max

/GÅxAêð

show dot1x reauth-max

Ï5,Õ5BÐ -

Ïê Ç (Mã

ÏÊÎ /VÜG5B

ÏG5B_Ð ÑM6/_Ê

```
5XLMLHVKRÆGRW[VXPPDU\
,8VHU0ÆQVHUIDFH9/$ÆXWK6WDWH
%DFNHQ6WDWH3RUW6WDWXV8VHU7ÆH7LPH



WVXVHUDHDD)DÆXWKHQVLFDWHG
,GOHÆXWKHGVWDWLFGDVKPV
```

ÏÎGÇ

Ç	Ë Ä
dot1x auth-mode	**A5B** 802.1x ,XAxAÆ
dot1x max-req	**A5BÆÎGÇ[X Ð** Ä
dot1x port-control auto	**A5Bé** AxAÄ
dot1x reauth-max	**A5BÆAËÎÇAxA•Ð**
dot1x re-authentication	**A5BÜGAËÈÈGÇAxAÄ**
dot1x timeout quiet-period	**A5BÆxAÆÆËGÇAxAÇX1Ê**
dot1x timeout re-authperiod	**A5BÆAËÈÜGÇAxAÊÄ**
dot1x timeout server-timeout	**A5BÆxAáÈxAxfÇXCÊ**
dot1x timeout supp-timeout	**A5BÆÎGÆËÈxAxfÇXCÊ**
dot1x timeout tx-period	**A5BÆÇÊÈGÆ**

ÏGÄÆ -

4.46 show dot1x timeout

AÇ 802.1X CYÊÐÇ

show dot1x timeout quiet-period
show dot1x timeout re-authperiod
show dot1x timeout server-timeout
show dot1x timeout supp-timeout
show dot1x timeout tx-period

ÐAÆ

Ïð (Mã

ÏÊð /CYÊDG5B

ÏG5B_Ð MÍ6/_ð

```
5XLMLHVKRØGRW[WLPHRXWTXLHWSHULRG
TXLHWSHULRGVHF
5XLMLH
```

ÏGÐ

Ç	ÉÄ
dot1x auth-mode	**A5B** 802.1x ,XAxAÄ
dot1x max-req	**A5B**ÐÔ[X ÐÄ
dot1x port-control auto	**A5B**ÝÄxAÄ
dot1x reauth-max	**A5B**BAÊÔ¸AxA•Ð
dot1x re-authentication	**A5B**ØGAÊÈÔG¸AxAÄ
dot1x timeout quiet-period	**A5B**ÐxAÐÐÊGÐ¸AxA¸X1Ê
dot1x timeout re-authperiod	**A5B**BAÊÈÔGÐ¸AxAÊÄ
dot1x timeout server-timeout	**A5B**ÐxAáÐÈxAxf¸XCÊ
dot1x timeout supp-timeout	**A5B**ÐÔAÊÈÐxAxf¸XCÊ
dot1x timeout tx-period	**A5B**ÐÐÊÈGÐÄ

ÏGÄÐ -

4.47 show dot1x user id

AÇÐ 802.1X AxAÐG5B><Ç

show dot1x user id <*id*>

ÏÐAÐ

–D	ÉÄ
id	ü show summary Ì„Xü id

Ï5,Õ5BÐ -

Ïð (MÐÄ

ÏÊð /(MnÞXÇ

ÏG5B_Ð MÍ6/_ð

```
5XLMLHVKRØGRW[XVHULG
8VHUQPHFDLNRY
LG
```

```
7SHVWDWLF
0DFDGGUHVVLV
9ODQGLV
FFHVVIURPSRUWL
8VHULSDGGUHVVLV
0D[XVHUQPEHURQWKLVSRUWLV
26RQWKLVSRUWLV
8SEDQZGWKLVNESV
RDQZGWKLVNESV
XWKRUL]DWLRQODQVGHS
XWKRUL]DWLRQHHVLRQLPHLVVHFQV
XWKRUL]DWLRQSDGGUHVVLV
6WDUWDFFRXQWLQ
3HUPLWSUR[XVHU
3HUPLWGLDOXVHU
,3SULYLOLHLV
```

ÎGĢ

Ą	Ł.Ä
dot1x auth-mode	**A5B** 802.1x ,XAxAÄ
dot1x max-req	**A5B**[X Ð Ä
dot1x port-control auto	**A5B**AxAÄ
dot1x reauth-max	**A5B**AxA•Ð
dot1x re-authentication	**A5B**AxAÄ
dot1x timeout quiet-period	**A5B**AxAX1Ê
dot1x timeout re-authperiod	**A5B**AxAÊÄ
dot1x timeout server-timeout	**A5B**AxAxfXCÊ
dot1x timeout supp-timeout	**A5B**AxAxfXCÊ
dot1x timeout tx-period	**A5B**AÊÄ

ĠÄÊ -

5 Web

5.1 dot1x redirect

ØG5B<,Xv0ÆÇ6ÃË> <G5BÇ **dot1x redirectÄÇ** **no 6È** GÍv
0ÃÇÑ
dot1x redirect
no dot1x redirect

ÐAÈ	–D	Ë Ä
	-	-

Ëß,Õ5BÐ -

ËÇ (Mã

ËSf -

ËG5B_Ð MI6A'5BÇ,Xv0ÆÇ6ÑX_$ Ö
5XLMLHFRQIXUHWHUPLQO
5XLMLHFRQIGRW[UHGLUHFW

ËÎGÇ

Ç	Ë Ä
http redirect	**G5B** HTTP GnåX IP
http redirect direct-site	**A5**ÆxA¸X5¼Cd8È
http redirect homepage	**A5B**GnåIÑXNI
http redirect port	**A5**ÇÎ(MÂ0Ã HTTP ,X WEB AË Ë> Gnå
http redirect session-limit	**A5**ÎxA¸XÎÔ HTTP ÂÐ
http redirect timeout	**A5**ÆÕGnÇXCÈ
show http redirect	**/** HTTP GnåXG5B

ËÄÈ -

5.2 http redirect

ØG5B HTTP GnåX IP s6ÃË> <G5BÇ **http redirectÄÇ** **no 6È** HTTP GnåX IP Ä
http redirect {*ip-address* | *ipv6-address*}
no http redirect

ÏÐAðð	–D	Ë Ä
	ip-address	HTTP GɲåX IPv4 Ä
	ipv6-address	HTTP GɲåX IPv6 Ä

Ï,Õ5BÐ 5,ÛÝ'5B HTTP GɲåX IPÏPv4 ê IPv6Å

Ïð <G5Bå

ÏÛ Ûähü Web AxAs6ÑOA'5B HTTP GɲåX IP ÈPv4 ` IPv6 ,X HTTP GɲåXÃ

ÏÕÐ | Web AxAÆÊÊ› Web AxAèÃ“KÂ%4Cd¢ÐÒ5%4Cd¢ÐxA•
ÐÃ“KÂoÇX5%4Cd¢È¢Ð%02bAxA•X5%4Cd¢Èwý
FÃ“KÂ5%0Ä
ÊÇG5B 50 þAxA•X5%4Cd¢È

ÏG5B_Ð _ 1ÊÏ5B IP 172.16.0.1 ,X5%0AxA•A“KÂX5%4Cd¢ÐÄ
5XLMLHFRQQHFWWSUHGLUHFWGLUHFWVLWH

ÏÎGÇ

Ç	ÆÄ
show http redirect	ß HTTP GnåXG5BÄ

ÏGÄè -

5.4 http redirect homepage

A’5BGnåIIM6,XNIÆÇX **no ÉÐAxA•NIÐX,XNIÄ**
http redirect homepage *url-string*
no http redirect homepage

ÐAè

–D	ÆÄ
url-string	**NIè** "http://" ê “https://”ÐG5BåÐS z 255 þ0Å

ï,Õ5BÐ 5,ÕÐAxA•NIM6,XNIÄ

ÇÐ <G5BåÄ

ÏÕÐ Ðäht Web AxAs6ÑÐG5BAxA•NIM6,XNIÄ

ÏG5B_Ð _ 1ÕÐAxA•NIM6,XNI http://www.web-auth.net/loginÄ
5XLMLHFRQQHFWWSUHGLUHFWKRPHSDJHHKWWSZEDXWKHQWORIQ

ÏÎGÇ

Ç	ÆÄ
show http redirect	ß HTTP GnåXG5BÄ
http redirect	**A5BxAáX** IP Ä

ÏGÄè -

5.5 http redirect port

HTTP ,X WEB A

ÏSÐ ÍZ6þAxA¢CK HTTP SÐÐÝ9A'ÎX TCP Eÿ5ÐÐÝ9A'ÎþAxA•
þXÔ HTTP ÂÆÄ
+bÞAxA¢ÐÔ HTTP ÂÆÞXÑÍG3ÕÑÚ HTTP ÂÆã
ÂA'5BþAxA¢XÔ HTTP ÂÆ 1Ä

ÏG5B_Ð _ 1Ø'5BþAxA¢XÔ HTTP ÂÆ 4Ä
5XLMLHFRQILJXUHGLUHFWVHVVLRQLPLW

ÏGÐ Ç	Ð Ä
show http redirect	þ HTTP GnåXG5BÄ

ÏGÄÐ s - /¦þ ! Á – Ð…ì “ E•,ì p¥ÿ ñýQN?X < 1Aa`< < Ð õ ãþ ”– E‡ Â ô 1Aa X_ðU0 c o n d s

5.7

5.8 show http redirect

/ HTTP GnåXG5BÄ

show http redirect

ÐAå	–D	Ä
	-	-

Ö,Ø5BÐ -

Ö -

ÖÐ -

Ö5B_Ð _ 1Ö HTTP GnåXG5BÄ

```
5XLMLHVKRZKWWSUHGLUHFW
+773UHGLUHFWLRQHWWLQ
VHUYHU
SRUW
KRPHSDJHKWWSH3RUWDOLQH[MVS
VHVVLRQLPLW
WLPHRXW

LUHFWVLWHV
6GUHVV0$3%LQLQ

2Q
2II
2II
2II
2II

LUHFWKRVWV
6GUHVV0DVN3RUW$3%LQLQ

)D2Q
```

```
+‰
```

homepage	GnåIIM6,XNIÄ
session-limit	HTTP
timeout	4
AxA5%4	

ÑORZODQLVW

ÏĈĢĐ

Ç	ÆÄ
web-auth allow-vlan	**A5Ê** VLAN ,X Web AxA‹s6ÃÆxA¡X VLAN ë<Ä

ĞĠÄê -

5.10 show web-auth direct-host

/! web AxA¡X8Ã

show web-auth direct-host

ÐAê

–D	ÆÄ
-	-

Ð,Õ5BÐ -

Ê (Mã

ÐÊÐ -

Ğ5B_Ð _ 1ÚÔxA¡XÄ

[redacted]

ÑGUHVV0DVN3RUW$3%LQLQ

)DÊ0

5.11 show web-auth port-control

/yÞXAxA•G5B¼ªAuÇÄ

show web-auth port-control

ËDAê

–D	ÉÄ
-	-

Ë,ÕG5BÐ -

Ëê -

ËGÕ5B_Ð _ 1ÇÝÞXAxA•G5B¼ªAuÇÄ

```
5XLMLHVKRZEDXWKSRUWFRQWURO
3RUWRXQWURO

)DVW(WKHUQW2Q
)DVW(WKHUQW2Q
)DVW(WKHUQW2II
```

+‰	Aê
Port	y9A’ÌX(=)ÓÃ
Control	A0Ð Web AxA•Ä

ÏÎGÇ

Ç	ÉÄ
web-auth port-control	0Ã Web AxA•Ä

ËGÄê -

5.12 show web-auth user

/ÊXä“Çê IP ÿÃ“ÉÈÇÄ

show web-auth user [*ip-address* | *ipv6-address*]

ËDAê

–D	ÉÄ
ip-address	IPv4 Ä
ipv6-address	IPv6 Ä

-

(Mã

-

_ 1Ö web AxA<G5B47AuÇÄ

```
5XLMLHVKRWEDXWKXVHU
&UHDWHQHZXVHUQDP

6GUHVV2QLQH7LPH/LPLW7LPH8VHG6WDWXV

2QG6WLYH
2QG6WLYH
2II&UHDWH
2IIGHVWUR\

5XLMLHVKRWEDXWKXVHU
6GUHVV
0DFGI
3RUW)D
2QLQH2Q
7LPH/LPLWG
7LPH8VHGG
7LPH6WDUW
6WDWXV6WLYH
```

+‰	AÈ
Address	X IP Ä
Mac	X MAC Ä
Port	y,Xy9A’X0Ã
Online	“Ä
Time Limit	XSL >< LÄ
Time Used	“
Time Start	AxA , X
Status	ctive >< “Create >< 5B estroy >< 8Ã 8A’5BÄ

Q	Ä
-	-

ÏGÄê -

5.13 web-auth allow-vlan

A'5Bîb VLAN ,X Web AxAs6ÑÆxA¡X VLAN ë<ÃÇX **no ÉÆ5Ë**

web-auth allow-vlan *list*

no web-auth allow-vlan [*list*]

ÐAê

–D	£Ä
list	**Õ** VLAN ,X web AxA¡X VLAN ë< *listÄ*

Ï,Õ5BÐ 5,ÛÛ VLAN ,X Web AxAs6ÑÚÝ'5BAÆxA¡X VLAN ë<Ä

Ï <G5BÄ

ÏÊ A'5BAÆxA¡X VLAN ë<Ïî VLAN ,XAxAs6ÑÛ8ÆxA¡X VLAN ë< Ä

ë<ÏE VLANÆÇKÃ VLAN ,XAxAs6Ñ

ÛSb VLAN ,XAxAs6ÑÈÔA'ÎX6(0Ð Web AxAs6Ñ6(0Ã

¡XÐÛ TRUNKÄ

Ï5B_Ð _ 1Ø'5BAÆxA¡X VLAN VLAN1Ã Ã Ã Ä

5XLMLHFRQIHEDXWKDOORZODQ

ÎÏÇÐ

Ç	£Ä
show web-auth allow-vlan	**Õ** VLAN ,X Web AxA¡X VLAN ë<µ CÄ

ÏÄê -

5.14 web-auth direct-host

A'5BLÔxAÚ IP 8ÑÇX **no ÉÔxAÄ**

web-auth direct-host { *ipv6-address* | *ipv6-prefix/prefix-length* | *ip-address* [*ip-mask*] [**arp**] } [**port** *interface-name*]

no web-auth direct-host { *ipv6-address* | *ipv6-prefix/prefix-length* | *ip-address* [*ip-mask*] }

ÐAê

–D	£Ä
ipv6-address	**ÔxA** IPv6 Ä
ipv6-prefix/prefix-length	*ú* IPv6 ¼ÊSÈ</A¹ IPv6 8È,XÉÑÔxAÄ
ip-address	**Ô** IPv4 Ä
ip-mask	**É** IPv4 }-Õ

port *interface-name*	IP
arp	ARP CHECK IP ARP **arp** IPv4

Web

Web

Web

50

Ø A’5Bd AxA•

ÐAÐ	–D

ÜÈ“Ç,XÊÈÈhÈ8Ê

ÏG5B_Đ _ 1Ê'5BÜ“Ç,XÊÈÈh 30 /Ä

5XLMLHFRQÜBEDXWKXSGDWHLÇVHUYDO

ÏÎGÇ	Ç	Ë:Ä
	-	-

ÏGÄÊ -

6 SSH

6.1 crypto key generate

á<0ÃXÈgÈG5BÈ Ç

crypto key generate {**rsa | dsa**}

–D	Ë
rsa	á RSA ÿ
dsa	á DSA ÿ

TAxÑ SSH Server ü

<G5Bã

LÔÔ SSH Server áÊE SSH á<0ÃXÈgÈ **enable service ssh-server** SSH Server s6Ñ SSH 1 Sü RSA ÿ SSH 2 Sü RSA DSA ÿ RSA ÿ SSH1 â SSH2 DSA ÿ SSH2

DSA RSA

DSA RSA

ÏÎGÇÇ

Ç	Ë Ä
show ssh	/ÁÊ,Ÿ SSH Eÿ²Ag¢
clear line vty *line-number*	ÇX VTY Eÿ²A±

ÏGÄÊê -

6.4 ip scp server enable

ï¤%4Ä'Ê SCP á<s6ÊÑ¤%4Ä'ÇX[Ê> Ê[ÇÊ

7Ç%4Ä'ÊfDBÇ6ÊÑ> ÊgÈÁxA}<Ì(MÄ

ip scp server enable

no ip scp server enable

Ï-DAÊê

–D	Ë Ä
-	-

Ï,Õ5BÐ 5,Ñ'5BÊ SCP á<s6Ñ

Ïê <G5Bã

ÏSÇ

ÏG5B_Ð Ô scp s6Ñ

```
5XLMLHFRQ[XUHWHUPLQO
5XLMLHFRQ1SVFSVHUYHUHQEOH
```

ÏÎGÇÇ

Ç	Aê Ë
show ip ssh	ß ssh-server ,X(Õ

ÏGÄÊê -

6.5 ip ssh authentication-retries

A'5B SSH Server ÄxA¸XGÁxA•ÐÊÄÇX no EÍMMÄxA¸XGÁxA•Ð6ê,Ñ'

5BÄ

ip ssh authentication-retries *retry times*

no ip ssh authentication-retries

ÏÐAÊê

–D	Ë Ä
retry times	G5BÄxA¸XGÁxA•Ð

Ï,Õ5BÐ 5,Ñ'5BGÁxA•Ð 3 Ä'5BGÁxA•ÐÊú **no ip ssh authentication-retries** ÇÃ

SA’5B6ÃAxÄ

<G5Bã

AQ5B SSH Server E> AxA;XGAxA•DÈYE› SSH Server G5B,XGAxA•DÉx
AÊxAAxABÊÃ **show ip ssh** SSH Server ,XG5BÄ

A’5BAxA;XGAxA•D 2Ö

```
5XLMLHFRQIXUHWHUPLQDO
5XLMLHFRQILSVVKDXWKHQWLFDWLRQHWULHV
```

Q	Ä
show ip ssh	SSH Server ,X(Õ

-

6.6 ip ssh time-out

A’5B SSH Server ,XAxA€YÊÃQX no EÍMÉxA€YÊÈ’5B6ã,Ñ’5BÄ

ip ssh time-out *time*

no ip ssh time-out

–D	Ä
time	

ã,Ñ5BÐ 5,Ñ’5BÈYÊÈ 120sÄ’5BCYÊÈÃ **no ip ssh time-out** 5BÃAx
Ä

<G5Bã

AQ5B SSH Server E> AxA•XCYÊÈÃ¿AÃuÊYE› 120s ÜÍx
AÊxAxA€YÊÃ **show ip ssh** SSH server ,XG5BÄ

G5B_Ð G5BCYÊÈ 100sÖ

```
5XLMLHFRQIXUHWHUPLQDO
5XLMLHFRQILSVVKWLPHRXW
```

Q	Ä
show ip ssh	ssh-server ,X(Õ

-

6.7 ip ssh peer

ip ssh peer *username* **public-key** {**rsa** | **dsa**} *filename*

no ip ssh peer *username* **public-key** {**rsa** | **dsa**} *filename*

	–D	
	username	
	filename	

-

<G5Ba

-

A’5B *test* RSA ` DSA

```
5XLMLHFRQIXUHWHUPLQO
5XLMLHFRQILSVVKSHHUWHVWSXEOLFNHUVDIODVKUVDSXE
5XLMLHFRQILSVVKSHHUWHVWSXEOLFNHGVDIODVKGVDSXE
```

show ip ssh	ssh-server

	2Ö
	5XLMLHFRQIXUHWHUPLQDO
	5XLMLHFRQIISVVKYHUVLRQ

	show ip ssh	SSH Server ,X(
	-	

6.9 show crypto key mypubkey

	/ SSH Server ,X
	show crypto key mypubkey {**rsa/dsa**}

/ SSH Server SSH Server

	SSH SSH

5XLMLHVKRVSVVK

ip ssh version {**1** | **2**}	**5B** SSH Server
ip ssh time-out *time*	**5B** SSH Server
ip ssh authentication-retries	**5B** SSH Server

-

6.11 show ssh

SSH

show ssh

–D	
-	-

-

(M

/ SSH VTY SSH (

1k

5XLMLHVKRVSVVK

-	-

-

7 GSN

7.1 security address-bind enable

AÇÇG5BA'ÛÃ#1*9Ä

security address-bind enable

no security address-bind enable

ÏÐÀÃ	–D	ÆÄ
	-	-

Ï5,Õ5BÐ -

Ï Ç yÃÊîXx6Ã AP ` AP äÃ

ÏÊ ;> AÇÃX4#GÊÎÃÇÇO ü GSN <ÛÊÕK0Ã

Ï5B_Ð G5B]<_ÃÈÆhÖ

5XLMLHFRQILVHFXULWDGGUHVVELQGHQEOH

ÏÎGÇ

Ç	ÆÄ
security gsn enable	GSN <Û

ÏÄÃ -

7.2 security community

AÇÇG5B` smp á<KÈÂƒX]<Á

security { [**v1 | v2**] **community** *community* | **v3 user** *username* }

no security { [**v1 | v2**] **community** *community* | **v3 user** *username* }

ÏÐÀÃ	–D	ÆÄ
	community	á<xf,X *community* ÛÁ
	username SÜX v3]<EÂÁ

Ï5,Õ5BÐ ÜÉ5B

Ï Ç <G5Bã

Ï v3

Ъ‚Õ5BÐ	GKÁ
ËÇ	<G5Bã
ЏЂÎ	'A'ÛØÕ GSN]<ÊÊG5B8ÇA'Õ GSN]<Ä
ËG5B_Ð	5XLMLHFRQJXUHWHUPLQO 5XLMLHFRQJVHFXULWYEQEOH

ÏÎGÇ

Ç	ÊÄ
-	-

ËGÄÈ

-

7.5 show security evnet interval

¦]<_ÈÈhÄ

show security evnet interval

ÐAÈ

–D	ÊÄ
-	-

Ï G Ä

A

Ï G ÄAÈ â Ð

Ï-DAèê

–D	ÆÄ
-	-

Ï,Õ5BÐ -

Ïê (Mã

ÏÊÔ / smp server ,X IP Ä

Ï5B_Ð 5XLMLHVKRWZPSVHUYHU
6036HUYHU,3Ö

ÎÎGÇ

Ç	ÆÄ
smp-server host	G5B smp server ip Ä

ÏÄèê -

7.7 smp-server host

AÇG5Bí,X smp-server ,X ip Ä

smp-server host *ip-address*

no smp-server host

ÐAèê

–D	ÆÄ
ip-address	smp server ,X ip

Ï,Õ5BÐ ùÉ5B smp server

Ïê <G5Bã

ÏÊÔ ;> AÇù **show smp-server G5B**

Ï5B_Ð 5XLMLHFRQVPSVHUYHUKRVW

ÎÎGÇ

Ç	ÆÄ
show smp-server	ß smp server ,XG5B

ÏÄèê -

8

8.1 nac-author-user maximum

L‡0ÃX IP y9DG£Ètů **no ÍÇÑÍÃ** IP DG£‡s6Ñ

nac-author-user maximum *value*

no nac-author-user maximum

ÐÃà	–D	£Ä
	value	IP DG£‡ÐÖ1024

ï‚,Õ5BÐ GKÁ IP DG£‡s6Ñ

ïÇ yã

ïŠÎ VpA'5B,X IP y9DG£ÈÆ,X IP ÇÐÃ'5BBù

ïG5B_Ð _ 1Ö‡0Ã 1 ,Xy9 IP Ç 100Ö

5XLMLHFRQILQXH

5XLMLHFRQILQFDXWKRUXVHUPD[LPXP

ÏÎGÇ

Ç	£Ä
show nac-author-user	ÇÃX IP y9DG£5BÆ,X IP Ç

ïGÄà

-

8.2 show nac-author-user

¡0Ã‡,X IP y9DG£5BÆ,X IP Ç

show nac-author-user

ÐÃà	–D	£Ä
	-	-

ï‚,Õ5BÐ 5,ÇÎÄ

ïÇ (Mã

Ï-DAèè

–D	Ë.Ä
interface-id	*y{è*

Ï5,Õ5BÐ 5,ÇÇ[ÇÏÄ

Ïè (Mã

ÏèÇ -

ÏGÏ5B_Ð 5XLMLHVKRZZWRUPFRQWURO1DELWHWKHUHQW
,QWHUIDFH%URDGFDVW&RQWURO0XOWLFDVW&RQWURO8QFDVW&RQWURO

ÇLVDEOHGLVDEOHGLVDEOHG

ÏÎGÇÐ

Ç	Ë.Ä
storm-control	A'5By¡XN¶[ÇÄ

ÏGÄèè -

8.5 strom-control

A'5By¡XN¶[ÇÇÄÄÇX **no** ÉÇÇÄÄ,XN¶[ÇÇs6ÃÑ

storm-control {**broadcast** | **multicast** | **unicast**} [{**level** *percent* | **pps** *packets* | *rate-bps*}]

no storm-control {**broadcast** | **multicast** | **unicast**} [{**level** *percent* | **pps** *packets* | *rate-bps*}]

ÐAèè

–D	Ë.Ä
broadcast	ÊÑN¶?X{s6ÃÑ
multicast	ÊÑN¶?X{s6ÃÑ
unicast	ÊÑN¶?X{s6ÃÑ
percent	[ÇX,RÉÈ> A'5B V 20 ></ 20%
packets	¹ pps)È> A'5B G packets per second
Rate-bps	AÇÇXÈÈÈÈ-[ÇÄ
64k-2M	¹ 64k)ÄÄ
2-100M	¹1M)ÄÄ
100M Þ	¹8M)ÄÄ

Ï5,Õ5BÐ -

ÏèÇ yG5BÄÄ

ÏèÇ ÊÑÊEG-ÇXSÄÄÊÑBÇÙXN¶[ÈÈÇÈ%46`
CYÈÄÄÇÙX;> ÄÄÑ%4ÊÑÄÑ5BFÄÄÊÑ?X{Ä
A'ÄÄÑÄÄDBÈ> N¶[ÇÄ,XSÄÄÊÑGÈ'Ü

VÊU6,h2O_,XÌXE@B67ÊÊXE@Â
Sŭ **show storm-control** **Q5Ë**

ÏG5B_Đ M6,X_ÂÊ)ÚÃ GigabitEthernet 1/1 ÌXÑsÔ5BAÕXEÉÉó)[4M Ä

```
5XLMLHFRQ1 XUHWHUPLQ O
5XLMLHFRQ1 WHUIDFH DELW(WKHUHW
5XLMLHFRQ1 IVWRUPFRQWUROPXOWLFDVW
5XLMLHFRQ1 IHQ
```

ÏĜGĐ

Q	ÈÄ
show storm-control	**/NĈĈÄ**

ÏGÄÊ -

8.6 switchport port-security

A'5B0ÃsÔÃ,XE±ÚÃÃX **no ÉÉÊÊÃA5ÈÈ** **_ÉÊÔ**

switchport port-security [**violation** {**protect** | **restrict** | **shutdown**}]

no switchport port-security [**violation**]

ĐAÊ

–D	ÈÄ
port-security	**y]Ĉ**
violation protect	**ÊÊXy[Ä**
violation restrict	**ÊÊXy[Ê** trapÄ
violation shutdown	**ÊÊ[Ê** Trap ĜKÁÄ

ÏĜ5BĐ y;X]<5,ĜKÁXÄ

Đ yG5Bã

ÏĈĐ ÊÃEÊMÊLÂEKÂ'ÊX MAC ž IP(ÊÝ9r)ü
ÁÿXEg9ÄÔÃs6X0ÃG5BÊ]<ÊÊ
Eo]<,XÊÊÊÊyÊÊÊÊXK]<
ĐÈpĐA'5B 1 ÀÔĜ5BĈÈÿEÈX00Ä
G5B,X]< M ÊÂ0ÃX<FÊ

ÏG5B_Đ M6,X_Ê Gigabitethernet 1/1 ĐÃsÔÂ'5BE±ÚÙ shutdownÖ

```
5XLMLHFRQ1 WHUIDFH DELWHWKHUHW
5XLMLHFRQ1 IVZWFKSRUWSRUWVHFXULW\
5XLMLHFRQ1 IVZWFKSRUWSRUWVHFXULW\YLRODWLRQVKXWGRZQ
```

ÏĜGĐ

Q	ÈÄ

show port-security	**/0ÃKA5B]Ä**

ÏGÄê -

8.7 switchport port-security aging

AÇÐX]<G5B5ÊÐ6ÑÎA'5B]<,XÐÈ

EÃA'ÎÃXrtÐ8yÞX]<ÄÇX no ÉM5Ê

7¼XÈÉÑ

switchport port-security aging {**static** | **time time** }

no switchport port-security aging {**static** | **time** }

ÐAê

–D	Ä
static	**5ÊÐG5]7¼XÈ** **7¼XÄ**
time *time*	**]5Ê** 0É440 ÄÄ VpA'5B 0ÑÑL>GKÄ

switchport port-security binding *mac-address* **vlan** *vlan_id ipv4-address* | *ipv6-address*
no switchport port-security binding *mac-address* **vlan** *vlan_id ipv4-address* | *ipv6-address*
switchport port-security binding *ipv4-address* | *ipv6-address*
no switchport port-security binding *ipv4-address* | *ipv6-address*

ÐAê

–D	Ë
mac-address	**4 X** MAC
vlan_id	*4* MAC ,X VID
ipv4-address	*4* Ipv4 ,X Ip
ipv6-address	*4* Ipv6 ,X Ip

Ь,Õ5BÐ -

ê yã

Ьê -

Ï5B_Ð _ 1 192.168.1.100 y· 10Ö

```
5XLMLHFRQILJVHUJ
5XLMLHFRQILJVHFXULWHLQWHUIDFH
```

_ 2 192.168.1.100 MAC 00d0.f800.5555, VID= 1 y· 10Ö

```
5XLMLHFRQILJVHUJ
5XLMLHFRQILJVHFXULWHLQWHUIDFHIYODQ
```

ÎÏGÐ

Ç	Ë
switchport port-security	**Ô**
switchport port-security binding interface	**(5 X**
Switchport port-security mac-address	**A5**
switchport port-security aging	**0**
show port-security	**/0**

ÏÄê -

8.9 switchport port-security binding interface

(M 5B]<4 E> IP+ MAC IP 4
NO0 ,X]<,Xy[9x ,Xy[**no**
4 X

interface-id	**4Ÿ¥Xy·** ID
mac-address	*4Ÿ¥Ø* MAC
Vlan_id	*4Ÿ¥Ø* MAC ,X VID
Ipv4-address	*4Ÿ¥* Ipv4 ,X Ip
Ipv6-address	*4Ÿ¥* Ipv6 ,X Ip

Ъ,ÕЪBÐ -

(Mã

ЪÐ -

ЪB_Ð _ 1Ø¥ 192.168.1.101lv/DB11D001D0>86f-0.0 10 Tc 2.[<0847216E>7<2C5818(i)1(d02 g/TT0 1 T8-0.0014 Tc 3.2(

Ï.X 6 à

ËÐ -

Ë5B_Đ _ 1Ø5B TRUNK y· 10 ,XM-Ç 00d0.f800.5555 VID=2Ö

5XLMLHFRQILJXUHV

5XLMLHFRQILJXUHVZWFKSRUWSRUWVHFXULWPDFDGGUHVVGIYODQ

ÏÎGÇ

Ç	ÉÄ
switchport port-security	**0Ç<**
switchport port-security binding	**G5Ç¼**
switchport port-security mac-address interface	**(Ø5Ç<**
switchport port-security aging	**0Ç5Ö**

@ **show port-security** **/5X dÇ@Ø0„88b88b88b88bÇ88gpH…a_SyÇ@{Q7A'l À'D**

ËGÄê -

8.12 switchport port-security maximum

A’5B0ÃÈÐÉšù **no ÍÑÑõÐ**

switchport port-security maximum *value*

no switchport port-security maximum

ËÐAê

–D	ÉÄ
value	*]Þ* 1-128

Ë,Õ5BÐ 128

ÈÑ yã

ÈÐ]<ÞÙ-Õ5B|Ã4,X]<Þ,XÈ,Õ 128 ÈpA’5B,X]<þ

DÈÚ]<ÞÈA’5BBù

Ë5B_Ð _ 1Ø’5B· 10 ,X0Ã<Þ 2Ö

```
5XLMLHFRQILJXUHJ
5XLMLHFRQILJXUHZFWKSRUWSRUWVHFXULWPD[LPXP
```

ÎËÇÐ

Ç	ÉÄ
switchport port-security	**ÔÃ<**
switchport port-security binding	**G5Þ¤¼**
Switchport port-security mac-address	**yÁ5Þ<**
switchport port-security aging	**0ÃõÖ**
show port-security	**/0Ã¢**

ËGÄê -

8.13 switchport port-security sticky mac-address

yÈ5B Stickk MAC]<È‰ù **no ÍÑG5Þ**

switchport port-security mac-address sticky *mac-address* [*vlan vlan-id*]

no switchport port-security mac-address sticky *mac-address* [*vlan vlan-id*]

áDÉ6Ñ Sticky MAC :4s6Ñ‰ù **no ÍÑ** Sticky MAC :4s6Ñ

switchport port-security mac-address sticky

no switchport port-security mac-address sticky

ËÐAê

–D	ÉÄ
mac-address	*M-Ã<*

9 CPU

9.1 cpu-protect type packet-type pps pps_value

A’5B CPU 0ÿÃû2O_y[,XÄ

cpu-protect type { **arp** | **bpdu** | **dhcp** | **ipv6mc** | **igmp** | **rip** | **ospf** | **vrrp** | **pim** | **ttl1** | **unknown-ipmc** | **dvmrp** | …} **pps** *pps_value*

Ï¨ÐÀ¨	–D	Ë¨Ä
	pps_value	**Ð¸ÿ[DÄ**

Ï¨Õ¸5BÐ CPU íÞ¿2O_y[,Xyí1X5,Õ 1000Ä

Ï¨Ò CG5BÃÄ

Ï¨ÊÐ -

Ï¨G5B_Ð ÑM6A’5B CPU y BPDU y[í1X_ÊÐ

5XLMLHFRQ¿FSXSUWSHESGXSSV

6HWSDFNHWWSHESGXSSV

ÏÎG¿Ò

Ò	Ë¨Ä
cpu-protect type packet-type pri *pri_num*	**A5B** CPU y,Xû2O_y[ĺ,X¼{Ä

Ï¨GÄÀ¨ S76 2Ë¨’[ÛXM2N6ÕÈZ 1X ` 6sfp ¼“50Ã cpp s6Ñ

9.2 cpu-protect type packet-type pri pri_num

A’5B CPU y,Xû2O_y[ĺ,X¼{Ä

cpu-protect type { **arp** | **bpdu** | **dhcp** | **ipv6mc** | **igmp** | **rip** | **ospf** | **vrrp** | **pim** | **ttl1** | **unknown-ipmc** | **dvmrp** | …} **pri** *pri_num*

Ï¨ÐÀ¨	–D	q02C5804EC071C347B01C4>18D1198 362.54 0.48 0.48 refD1198 362.54 0.48 0.48

ÜG5B_Đ ÑM6Ú BPDU y[ĥKő 7 ,X_Ŝ

```
5XLMLHFRQILJFSXSURWHFWWSHESGXSUL
6HWSDFNHWWSHESGXSUL
```

ÏÎGĘĐ

Ę	Ł:Ä
cpu-protect type packet-type pps *pps_value*	**A5ĥ2Oy[XĤ**

ÜGÄĝĥ -

9.3 show cpu-protect mboard

/1u)Ś CPU ±,XØOy[,X4ŦAuĻÄ

show cpu-protect mboard

ÐAĝĥ

–D	Ł:Ä
-	-

Ъ,Õ5BĐ -

ĝĘ (MĤ

ÜĝĐ AĘu)Ś CPU ¦yy[,X4ŦAuĻÄ

ÜG5B_Đ

S8600 CPU

```
5XLMLHVKRZSXSURWHFWPERDUG
SH3SV7RWDOURS

DUS
ESGX
GKFS
YUS
LSYPF
GYPUS
LPS
RVSI
SLP
ULS
YUUS
XQQZSPF
WWO
```


9.5 show cpu-protect type

/ÇÔO_y[,X4ªAuÖ

show cpu-protect type { **arp** | **bpdu** | **dhcp** | **ipv6mc** | **igmp** | **rip** | **ospf** | **vrrp** | **pim** | **ttl1** | **unknown-ipmc** | **dvmrp | …**} *dvmrp*

ÐAß

–D	Ë
slot_num	1-16Ä

Ï,Õ5BÐ -

Ç

(MÄ

ÏÊ

AÇÔ2O_y[,X4ªAuÇÄ

CPP ,XG5BÇ..”></ÞX CPP 2O_Ä

ÏG5B_Ð

show cpu-protect type bpdu BPDU y[,Xy4ªAuÖ

```
5XLMLHFRQVYKRESXSURWHFWVSHDUS
6ORW7SH3SV7RWDOURS

0DLQRDUGESGX
6ORWESGX
```

ÎÏGÇ

Ç	Ë
show cpu-protect type *packet-type*	**/** CPU ±²Oy[,X4ªAuÇÄ

ÏGÄß -

10 DoS

10.1 ip deny invalid-l4port

no

ip deny invalid-l4port

no ip deny invalid-l4port

–D	Ë
-	-

5,

<G5B

-

_ 1

5XLMLHFRQILSGHQ DOLGOSRUW

_ 2

5XLMLHFRQILSGHQ DOLGOSRUW

Ç	Ë
show ip deny invalid-l4port	

-

10.2 ip deny invalid-tcp

TCP y[**no** TCP y[

ÏG5B_Đ _ 1Đ'ÔM2'© TCP y[ï‹6Ñ
5XLMLHFRQ1LSGHQQDOLGWFS
_ 2Đ'ÔKÁM2'© TCP y[ï‹6Ñ
5XLMLHFRQ1LSGHQQDOLGWFS

ÎÏGÇ

Ç	Ł Ä
show ip deny invalid-tcp	**Þ** © TCP y[ÏX(Ñ

ÏGÄð -

10.3 ip deny land

Ô Land ï‹6ÑÄÇX **no ÉÚÚÉ** Land ï‹6Ñ
ip deny land
no ip deny land

ÐÄð

–D	Ł Ä
-	-

ï‚,Ñ5BÐ 5,Ñ‰ÇXL Land ï‹6ÑKÁ‹Ä

ïÇ <G5BÄ

ïÐ -

ÏG5B_Đ _ 1Đ'Ô Land ï‹6Ñ
5XLMLHFRQ1LSGHQDQ
_ 2Đ'ÔKÁ Land ï‹6Ñ
5XLMLHFRQ1LSGHQDQ

ÎÏGÇ

Ç	Ł Ä
show ip deny land	**ß** Land ÏX(Ñ

ÏGÄð Í S3760E A'ÔM2© TCP y[ï‹6ÑÇ[ÔÉ'5BÏ¡ÇX
TCP y[À'5BZ FIN ¤Ù‹É'5B ACK ¡ÇX TCP y[Ä

10.4 ip deny spoofing-source

Ô DOS ÐE$6ÑÄÇX **no ÉÚÚÉ** DOS ÐE$6Ñ
ip deny spoofing-source

R63URWHFWLRQRGH 6WDWH

SURWHFWDDLQWLQDOLGOSRUWDWWDFN2II

ÏĈĢĐ	
Ç	
-	-

ĬĠĜĂÈ â Ð p @ ` à 0 0

10.6 show ip deny invalid-tcp

/LM2© TCP y[ÏX(Ð

show ip deny invalid-tcp

ĐAĐ		
–D	ĿÄ	
-	-	

ÏÇ (MÆÁ

ÏÆÐ -

ÏÇ5B_Đ 5XLMLHVKRWZSGHQDQ
R63URWHFWLRQRGH6WDWH

SURWHFWDDLQWODQDWWDFN2Q

ÏÇÐ

Ç	ÆÄ
[**no**] **ip deny land**	ÊKÁ Land ¨6Ñ

ÏÄÆ -

11 DHCP Snooping

11.1 clear ip dhcp snooping binding

ºÍõ8 DHCP Snooping DBg,X|ÊÕ(Mã> 8ÇÒ

clear ip dhcp snooping binding [*mac* **| vlan** *vlan-id* **|** *ip* **| interface** *interface-id* **]**

ËÐÃâ

–D	£Ä	
mac	ûÍ68,Xt¥X	MAC ×
vlan-id	ûÍ68,Xt¥X	vlan id×
ip	ûÍ68,Xt¥X	IP ×
interface-id	*ûßØX*Ã	

Ëõ,Õ5BÐ -

Ëç (Mã

ËÕÍ ;> AÇ8 DHCP snooping DBg,X|Ê

ËG5B_Ð ¥Mºõ8 DHCP snooping DBg|ÊX_õ

5XLMLHFOHDULSGKFSVRQRSLÐLQLQ

5XLMLHVKRWSGKFSVRQRSLÐLQLQ

7RWDOXQPEHURIELQLW

0DFGUHVVTc 0 Tw 7.413 0 62.04 507.4403186.20 1Tc T* Tc 0.9542 Tv

ËÐ (Mã

ËSÊÐ ;> AÐß DHCP snooping s6ÑXAAÐÄ

ËG5B_Ð ÑM6Ô DHCP snooping AÁÊ,X_ÐÑ

```
5XLMLHGHEXJLSGKFSVRQRSLQHYHQW
5XLMLHGHEXJLSGKFSVRQRSLQDFNHW
```

ÏÊGÐ

Ç	ÉÄ
-	-

ËGÄÐ -

11.3 ip dhcp snooping

ÐÔ DHCP Snooping <s6ÑÔËGB5BÉ5BAÐ AÇX **no 6Ð**

GÍ DHCP Snooping s6Ñ

ip dhcp snooping

no ip dhcp snooping

ËÁÐ

–D	ÉÄ
-	-

```
,ÇVHUIDFH                    Ç                    Ç
```

ÏÎGÇ

Ç	ÉÄ
show ip dhcp snooping	ß DHCP snooping ,XG5BÇÄ

ÜGÄß -

11.4 ip dhcp snooping bootp-bind

ÇÏÔ DHCP Snooping Õ Bootp 4ĦsÑÔ¤G5BÉ5BAÇ AÇX **no 6**
ßÜK DHCP snooping Õ Bootp 4ĦsÑ
ip dhcp snooping bootp-bind
no ip dhcp snooping bootp-bind

ÜAß

–D	ÉÄ
-	-

Ü,Õ5BÐ AŝÑ,ÕKÄ

Çß <G5BÄ

ÜÐ 5,ßDHCP Snooping sÑ Bootp y[E> EßsÑDHCP Snooping sÑ
Bootp Ay[E> 0yvÄ Bootp vÄ+AÉ DHCP Snooping Ú Bootp ÜM-Õ
4ĦDBgÄ

GÜ5B_Ð ÑÔ DHCP Snooping Õ Bootp 4Ħ,X_Ü

```
5XLMLHFRQIXUHWHUPLQDO
5XLMLHFRQILJKFSVERRSLQRRWSELQ
5XLMLHFRQIHQ
5XLMLHVKRZSGKFSVERSLQ
6ZFK+&VERSLQWDWXV(1$%/(
9HULILFDWLRQIKZGGUILHOGVWDWXV(1$%/(
+&VERSLQDDWDEDVHZLWHGHOLPHVHFRQV
+&VERSLQSWLRQWDWXV(1$%/(
+&VERSLQXSSRUW%RRWSELQVWDWXV(1$%/(
,ÇVHUIDFH Ç Ç
```

ÏÎGÇ Ç

11.5 ip dhcp snooping database write-delay

ÒÐG5Bx6nÊ DHCP Snooping DBg|ÑÕm9 FLASH s6ÑÒ«G5Bõ
ß> 8ÇÐ AÇX **no 6ÑÒ«Ém9** FLASH s6Ñ

ip dhcp snooping database write-delay *time*

no ip dhcp snooping database write-delay

ÐAßÐ

–D	ÆÄ
time	ðÓ DHCP snooping DBgm9 FLASH ,XÊÈÈhÄ

Ö,Õ5BÐ Aš6Ñ,ÑÑKÉñ FLASH

ÖÐ <G5BÄ

ÖÊÐ EÆG5BAÑÐ DHCP Snooping DBgm9 FLASH [ÑÆA'ÛÖÆ
CÈÈÑOG9ª IP ÆÆ?Ä

ÖG5B_Ð ÑM6G5Bx6nÊñ flash ÊÈÈh 3600 ,X_Ö

```
5XLMLHFRQ;XUHWHUPLQO
5XLMLHFRQ1SGKFSVRSLQDWEDVHZLWHGHO\
5XLMLHFRQ;HQ
5XLMLHVKRZSGKFSVRSLQ
6ZFK+&VRSLQWXV(1%/(
9HULILFDWLRQIKZGGUILHGVWXV(1%/(
+&VRSLQDWEDVHZLWHGHOWLPHVFRQV
+&VRSLQSWLRQWXV(1%/(
+&VRSLQXSSRUW%RRWSELQVWXV(1%/(
,QVHUIDFH
```

ÎGÐ

Q	ÆÄ
show ip dhcp snooping	ß DHCP snooping ,XG5BÇ

ÖGÄßÐ -

11.6 ip dhcp snooping database write-to-flash

ÒÐG5Bx6rÊ DHCP Snooping DBg,X|ÑÕm9 FLASH [ÊÒ«G5Bß
;> 8ÇÐ

ip dhcp snooping database write-to-flash

ÐAßÐ

–D	ÆÄ
-	-

ï5,Õ5BÐ	-
ïÐ	<G5Bã
ïõÐ	EÉ›> 8ÇÐ DHCP Snooping DBg|Õm9 FLASH [Ê
ï5B_Ð	¥M6Ú DHCP 4¥DBg,X|Õrê9 flash ,X_õÐ 5XLMLHFRQX UHWHUPLQO 5XLMLHFRQ1SGKFSVRRSLQDWDEDVHØLWHWRIODVK 5XLMLHFRQ#Q

ÎGÇ	
Ç	ÉÄ
-	-

ïGÄõ
-

11.7 ip dhcp snooping information option

ØÛ DHCP AÿÇt9 option82 E¥MsõÕÐïG5BõG5BAÇõ AÇX

no õõÉs6Ñ

ip dhcp snooping information option [standard-format]

no ip dhcp snooping information option [standard-format]

ÐAõ	
–D	ÉÄ
standard-format	Option82 E¥MSõ

ï5,Õ5BÐ
As6ß,ÕKÄ

ïÐ
<G5Bã

ïõÐ	
EÉG5BAÇõ	DHCP AÿÇt#

,QWHUIDFH

Q	E
show ip dhcp snooping	DHCP snooping ,XG5BC

-

11.8 ip dhcp snooping information option format remote-id

5B option82 EM,XEM remote-id 7+0Xs6DiG5BB5BA

> A X **no 6s6**

ip dhcp snooping information option format remote-id [string *ascii-string* **| hostname]**

no ip dhcp snooping information option format remote-id [string *ascii-string* **| hostname]**

Hp7UA]vp88i88i.x

rate-value	A'ny[yEÿ[ÈPS[Packet Per Second]

Ï5,Õ5BÐ ùÉÝÿ[L$

Ïÿ yG5Bã

ÏÊÕ Aš6Ñ DHCP Snooping { VLAN Y,Xýÿ

CPP[CPU Protect Protocol] CPP DHCP CPP DHCP Snooping CPP

ÆE› **show ip dhcp snooping ÿyG5**

ÏG5B_Ð MI6A'5B0Ã 1 ,XEÿ[L$ 100ppsÖ

```
5XLMLHFRQIXUHWHUPLQDO
5XLMLHFRQIQRWHUIDFHIDVW(WKHUQHW
5XLMLHFRQIILSGKFSVQRSLQLPLWUDWH
5XLMLHFRQIIHQ
5XLMLHVKRZSGKFSVQRSLQ
6ZFK+&VQRSLQQWDWXVÖ1%/(
9HULILFDWLRQIKZGGUILHOGVWDWXVÖ%/(
+&VQRSLQDWDEDVHZLWHGHODWLPHVHFRQV
+&VQRSLQSWLRQWDWXV(1%/(
+&VQRSLQXSSRUW%RRWSELQVWDWXV(1%/(
,QWHUIDFH
```

ÏÎG5Ð

Q	Ë Ä
show ip dhcp snooping	¦ß DHCP snooping ,XG5BÇÄ

ÏGÄÈ Õ NFPP s6Ñ{ÈÇd;Ä

11.10 ip dhcp snooping suppression

ÐG5B0Ã suppression (ÈÐÿG5Bß Bß AÇX **no 6È0Ñ**

e5B no suppression (È

ip dhcp snooping suppression

no ip dhcp snooping suppression

ÐAÈ

–D	Ë Ä
-	-

ï¿Õ5BÐ A‹65Ï¿ÕKÄ

Ïþ yG5BÄ

ÏÐ EÊG5BAÏÞA0Ã DHCP AÏ[G/U6A0ÃXÉE› DHCP é

AÏ

ÏG5B_Ð ÑM6G5B0Ã fastethernet 0/2 suppression (ÕX_Ð

```
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJLQWHUIDFHIDVWHWKHUQHW
5XLMLHFRQILJLILSGKFSVQRRSLQXSSUHVVLRQ
5XLMLHFRQILJHQG
```

ÏGÞ

Ç	ÉÄ
-	-

ÏGÄÐ -

11.11 ip dhcp snooping trust

ÐG5B0Ã DHCP snooping ¡Õ TRUST ÉÐ¡G5BÐ 8Þ AÇ

,X **no** 6À0Ã UNTRUST Ä

ip dhcp snooping trust

no ip dhcp snooping trust

ÐAÐ

–D	ÉÄ
-	-

ï¿Õ5BÐ 5,Ã UNTRUST Ä

Ïþ yG5BÄ

ÏÐ EÊG5BAÉ¾ÝÜ DHCP á<,X0Ã5B TRUST Ä TRUST 0Ã DHCP h

y[>ÝÉÀNTRUST 0Ã DHCP hy[ÉÄ

ÏG5B_Ð ÑM6G5B0Ã **fastethernet** 0/1 TRUST ¡X_Ð

```
5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJLQWHUIDFHIDVW(WKHUQHW
5XLMLHFRQILJLILSGKFSVQRRSLQXUXVW
5XLMLHFRQILJHQG
5XLMLHVKRZSGKFSVQRRSLQ
6ZWFK+&VQRRSLQWDWXVÜ1%/(
```

show ip dhcp snooping	ß DHCP snooping ,XG5BÇÄ

Ï GÄâ -

11.13 ip dhcp snooping vlan

Ï ÔÎ VLAN ,X DHCP Snooping s6 ÕïG5BÆ5BA¸ÇAÇX **no 6È**

Ï ÓÍK VLAN ,X DHCP Snooping s6Ñ

ip dhcp snooping vlan {*vlan-rng* **|** {*vlan-min* [*vlan-max*]}}

no ip dhcp snooping vlan {*vlan-rng* **|** {*vlan-min* [*vlan-max*]}}

Ï ÐAâ

–D	Ë Ä
vlan-rng	dhcp snooping s6 X vlan 8
vlan-min	dhcp snooping s6 X vlan
vlan-max	dhcp snooping s6 X vlan

Ï ¿,Õ5BÐ 5,% DHCP Snooping s6 Ý VLANÄ

Ï Ç <G5BÄ

Ï ÐÎ EË<G5BA¸Ç,X VLAN YÔ DHCP Snooping s6 KÂ VLAN ,X DHCP Snooping s6Ñs6ÑOÛ DHCP Snooping <Ô,XÎ

Ï G5B_Ð M6ü VLAN1000 Ð DHCP Snooping s6 X_

```
5XLMLHFRQIXUHWHUPLQDO
5XLMLHFRQILSGKFSVQRSLQODQ
5XLMLHFRQIHQ
```

Ï ÎGÇ

Ç	Ë Ä
ip dhcp snooping	DHCP Snooping ,X<ÔÄ

Ï GÄâ -

11.14 ip dhcp snooping vlan *vlan-id* information option change-vlan-to vlan

Ô option82 EÍM,XÉÍM circuit-id circuit-id ,X VLAN Û VLAN G5BA¸Ç AÇX **no 6 s6Ñ**

ip dhcp snooping vlan *vlan-id* **information option change-vlan-to vlan** *vlan-id*

no ip dhcp snooping vlan *vlan-id* **information option change-vlan-to vlan** *vlan-id*

Ï ÐAâ

–D	Ë Ä

vlan-id	ûÐE> ó¸X VLAN

ÏÐ¸Õ5BÐ Aŝ6ðÑ¸ÕKÁ

Ïè¸Ø yG5Bã

ÏÐÑ¸Ø EÐG5BAÐè¸Ø DHCP AÐÐ# option82 EÑMMÈ option82 ,XÐÑM circuit-id ¸X VLAN Â¸X VLANÈDHCP á<B option82 EÑMµCE> ÓÄ

ÏG5B_Ð ÑM6G5Bü DHCP AÐÐ# option82 EÑMMÈ option82 ,XÐÑM circuit-id ,X VLAN4094 Â VLAN4093 ,X_ðÑ

```
5XLMLHFRQIXUHWHUPLQDO
5XLMLHFRQIILQWHUIDFHIDVW(WKHUQHW
5XLMLHFRQIILSGKFSVQRSLQQODQQRUPDWLRQSWLRQKDQYODQYRYODQ
5XLMLHFRQIIHQ
```

ÏGÐ¸		
	¸Ò	ÐÄ
	-	-

ÏGÄÐè - -

11.15 ip dhcp snooping vlan *vlan-id* information option format-type circuit-id string

ÐÏG5B option 82 EÑMM,XÐÑM circuit-id ðÑ¼XY¸Äã ASCIIÐÅ> EÑÐü

<G5BÐG5BAÐè AÐ¸X **no 6ðÑs6Ñ**

ip dhcp snooping vlan *vlan-id* **information option format-type circuit-id string** *ascii-string*

no ip dhcp snooping vlan *vlan-id* **information option format-type circuit-id string** *ascii-string*

ÏÐÄÐè		
	–Ð	ÐÄ
	vlan-id	DHCP AÐü VLAN
	ascii-string	Circuit ID Ð¸XðÑ¼XY•Ci.52ef119.46 260.6 0.48 15Ci.52ef119.46 260.6 0.48 15Ci.52ef1

5XLMLHFRQILJXUHUDFHIDVW(WKHUQHW

ËÐ -

ËÊÔ ;> 8ÇÃ DHCP Snooping ,XG5BÆ‰

ËG5B_Ð ÑM6¦ß DHCP Snooping G5B‰_Ë

```
5XLMLHVKRWZSGKFSVRQRSLQ
6WZFK+&VRQRSLQWDWXV(1‰/(
9HULILFDWLRQIKZGGUILHOGVWDWXV(‰/(
+&VRQRSLQDWDEDVHZLWHGHODWLPHVHFRQV
+&VRQRSLQSWLRQWDWXV(1‰/(
+&VRQRSLQXSSRUW%RRWSELQVWDWXV(1‰/(
,QWHUIDFH
```

ÏÇÐ

Ç	Ë
ip dhcp snooping	DHCP snooping <G5BÔÄ
ip dhcp snooping verify mac-address	DHCP snooping y[mac "ÔÄ
ip dhcp snooping write-delay	G5Bnê flash ,XÊÈÈhÄ
ip dhcp snooping information option	ü DHCP Aÿ[t9 option82 EÑMÄ
ip dhcp snooping bootp-bind	Ô DHCP Snooping Õ Bootp 4ís6Ñ
ip dhcp snooping trust	A’5B0Ã DHCP snooping trust Ä

ÐÄÊ -

11.18 show ip dhcp snooping binding

Ñ¦ß DHCP Snooping DBg,XÇÈMÊ> 8ÇÄ

show ip dhcp snooping binding

ÐÄÊ

–D	Ë
-	-

Ê,Õ5BÐ -

ÐÇ (Mã

ËÊÔ ;> 8ÇÃ DHCP Snooping DBgÝXÇÄ

ËG5B_Ð ÑM6/_Ë

```
5XLMLHVKRWZSGKFSVRQRSLÐLQLQ
7RWDOXQPEHURIELQLQ
0DF6GUHVV,S6GUHVV/HDVHVHF7SH9/$,QWHUIDFH

GKFSVRQRSLQDVW(WKHUÐW
```

ÏĈĢϙ

ϙ	Ɛ Ä
ip dhcp snooping binding	**G5B** DHCP snooping M-õ
clear ip dhcp snooping binding	**ø** DHCP snooping |õ

ĠÄø -

vlan-id	></ vlan 4Ë

ÏÕ,Õ5BÐ Ý VLAN ÐKÁ DAI y["s6Ñ

ÏÐ <G5BÃ

ÏÕÐ ÐS8ÐÇÐjLÔÐ DAI s6Ñ

ÏG5B_Ð ÐG5BÈ VLAN 1 Þ,X ARP y[Ä

```
5XLMLHFRQQLJSDUSLQVSHFWLRQ
5XLMLHFRQQLJSDUSLQVSHFWLRQODQ
```

ÏÎGÇÐ

Ç	È
show ip arp inspection vlan	/ VLAN Ô DAI y["s6Ñ

ÏGÄÃÐ -

12.3 DHCP Snooping

Ø VLAN ,Xh,X DAI s6Ñ,X ARP y[,XÒÃÐK(Õ ARP y[LÔEÇ,X

ÔÈXqB DHCP Snooping DBg,X,ÒÇ. VpüÑBgE> ÏG5BÈk"EEÄDHCP

Snooping ,ÒGG5BAË5ÐHCP Snooping Ç5Ã

13 IP Source Guard

13.1 ip source binding

ü IP

ip source binding *mac-address* **vlan** *vlan-id ip-address* **[interface** *interface-id* **| ip-mac | ip-only]**

no ip source binding *mac-address* **vlan** *vlan-id ip-address* **[interface** *interface-id* **| ip-mac | ip-only]**

–D	
mac-address	MAC ×
vlan-id	vlan id×
ip-address	IP ×
interface-id	
ip-mac	IP+MAC
ip-only	IP

5XLMLHFRQILJXUHWHUPLQDO
5XLMLHFRQILJXUHLQWHUIDFH)DVW(WKHUQHW
5XLMLHFRQILJHQG
5XLMLHVKRZVSRXUFHELQGLQJ
0DFGUHVV,SGUHVV/HDVHVHF7\SH9/$1,QWHUIDFH
LQWHUIDFH)DVW(WKHUQHW
7RWDOQXPEHURIELQGLQJ

Q	
show ip source binding	IP

-

13.2 ip verify source

IP Source Guard

ip verify source [**port-security**]

no ip verify source [**port-security**]

ÏDAê

–D	ÉÄ
port-security	G5B IP Source Guard s6ÑÌ> Îb IP+MAC ”Ä

Ï,Õ5BÐ GKÄ

Ïê yG5BäÄ

ÏÍÐ EÉAÇX IP Source Guard s6ÑÌ> Îb IP ,X”èÉÌ> Îb IP+MAC ,X”Ä

IP Source Guard s6ÑM DHCP Snooping ,XM2ÐAÉ Trust ¥M2 DHCP Snooping {,XÕ5B IP Source Guard s6ÑP Source Guard s6ÄÑ

Ï5B_Ð ÑM6G5By· 1 ÞX IP Source Guard s6Ñ

```
5XLMLHFRQXUHWHUPLQO
5XLMLHFRQIQHUIDFHIDVW(WKHUQW
5XLMLHFRQIILSYHULVRXFH
5XLMLHFRQIIHQ
```

ÏÍÇÐ

Ç	ÉÄ
show ip source binding	ß IP Source Guard É$<NM

ÏÄê -

13.3 show ip source binding

AÐ IP Ñ4¥DBg,XÇÄ

show ip source binding [*ip-address*] [*mac-address*] [**dhcp-snooping**] [**static**] [**vlan** *vlan-id*] [**interface** *interface-id*]

ÏDAê

–D	ÉÄ
ip-address	/h ip ,X¥ÇÇ×
mac-address	/h mac ,X¥ÇÇ×
dhcp-snooping	**/Ñ4¥ÇÇ×**
static	**/Ñ4¥ÇÇ×**
vlan-id	/h vlan ,X¥ÇÇ×
interface-id	/hy¡X¥ÇÇÄ

Ï,Õ5BÐ -

Ïê (Mã

ÏÊÐ -

ÏG5B_Ð ÑM6/_Ê

```
5XLMLHVKRWSVRXUFHELQGLQWDWLF
0DFGGUHVV,SGGUHVV/HDVHVHF7SH9/$,QWHUIDFH

LQQWHVWDWLF)DVW(WKHUQW
7RWDOXPEHURIELQLQ
```

ÏÎGÐ	Ç	ÉÄ
	ip source binding	A’5B IP ß4¥M-Ê

ÏGÄÊ -

13.4 show ip verify source

AÇÐ IP Source Guard ÉÇ<NM

show ip verify source [**interface** *interface-id*]

ÐAÊ

–D	ÉÄ
interface-id	/hy¡XÉÇ<NMÄ

Ï,ÕÎ5BÐ -

Ê

ÏÊÐ **interface Ðhy** IP Source Guard s6ÊVÇÖ

-

14 DHCPv6 snooping

14.1 ipv6 dhcp snooping

ÐSŠ dhcpv6 snooping s6ÑÔ<ÔÄÇX **no 6ÉÁ** dhcpv6 snooping s 6Ñ

ipv6 dhcp snooping

no ipv6 dhcp snooping

ÐAÈ	
–D	Ë Ä
-	-

5,ÕK,ÄÄ

<G5Bã

SÁÇ6,X dhcpv6 snooping s6Ñ **show ipv6 dhcp snooping** dhcpv6 snooping s6Ñ

_ 1Ô6,X dhcpv6 snooping s6Ñ

5XLMLHFRQ1SYGKFSVRSLQ

ÏÔÇ	
Ç	Ë Ä
show ipv6 dhcp snooping	**/** dhcpv6 snooping s6Ñ<G5BÇ

-

14.2 ipv6 dhcp snooping binding-delay

G5BÇ4#><NMÊ#Ê<,Xs6ÑÇX **no 6È s6Ñ**

ipv6 dhcp snooping binding-delay *seconds*

no ipv6 dhcp snooping binding-delay

ÐAÈ	
–D	Ë Ä
tim	*g1 1 1 0 0 ref1 3 1 1 ref2 1 1*

KÈ'ù'Ý# IPv6 ¶UÊ¼.Ê<Ä

Ï5B_Đ _ 1¶Ø¼><NMÊ³ 10 /µ¼Ê<Ä

5XLMLHFRQILSYGKFSVRRSLRLQLQHOD\

ÎGĐ	Ç	ÉÄ
	-	-

ÏGÄð -

ï5,Õ5BÐ -

ïÐ <G5Bã

ïêÐ ;> 8ëÐ dhcpv6 snooping 4¥DBg,XÇm9 flash [ÂÛÇ¾
|¢ flash Aë¡ flash ,XÇÄ

ïG5B_Ð _ 1Õ dhcpv6 snooping 4¥DBg,XÇrê9 flash
5XLMLHFRQILSYGKFSVRQRSLQGDWDEDVHZLWHWRIODVK

ïÏGÐ

Ç	Ë
-	-

ïGÄê -

14.5 ipv6 dhcp snooping filter-dhcp-pkt

G5B0ëX dhcpv6 AÇ[ÊÄÇX **no 6êÁs6Ñ**
ipv6 dhcp snooping filter-dhcp-pkt
no ipv6 dhcp snooping filter-dhcp-pkt

ÐAê

–D	Ë
-	-

ï5,Õ5BÐ 5,ÕKÁ

ïÐ yG5Bã

ïêÐ G5BAëÇÃXÝ dhcpv6 AÇ[ÊZU6A0ÃXÉE› dhcpv6
ãAË

ïG5B_Ð _ 1G5B0Ã fastethernet 0/1 ý dhcpv6 AÇ[
5XLMLHFRQILQWHUIDFHIDVWHWKHUQW
5XLMLHFRQILSYGKFSVRQRSLQOWHUGKFSSNW

ïÏGÐ

Ç	Ë
-	-

ïGÄê -

14.6 ipv6 dhcp snooping ignore dest-not-found

G5B¥9,ÂX0ÃRBiXÔÊÄÇX **no 6êá** DHCPv6 hy[,X0ÃÄ

ipv6 dhcp snooping ignore dest-not-found

no ipv6 dhcp snooping ignore dest-not-found

	–D	Ë÷Ä
	-	-

5,ÕKÁ

<G5Bã

DHCPv6 ,Xhy[Eè@qC* MAC ><,X2ÈZp DHCPv6 ,Xhy[ï6Rá

MAC ĥ,X0Ã5×%ÉÝ@y[Ä

MAC :4ÈÈ

DHCPV6_SNOOPING-5-DEST_NOT_FOUND:

Could not find destination port. Destination MAC [mac-address]ÈÃ}H5%,X DHCPv6 6Ñ

MAC ĥ0Ãxy[Ö6È VLAN

_ 1Õ5BÑ9,Ã0ÃBÞXÔÄ

5XLMLHFRQILSYGKFSVRRSLQRUHGHVWRWIRXQ

	Ç	Ë÷Ä
	show ipv6 dhcp snooping	/ dhcpv6 snooping s6ÑX<G5BÇ

-

14.7 ipv6 dhcp snooping information option

Ô DHCPv6 AÿÇt9 option18/37 EÍMs6ÑÔ¨G5BÉ5BAÉ AÇ

,X **no 6ÉÍs6Ñ**

ipv6 dhcp snooping information option [standard-format]

no ipv6 dhcp snooping information option [standard-format]

	–D	Ë÷Ä
	standard-format	Option18/37 EÍMSÉ

A¹s6Ñ,ÕKÁ

<G5Bã

EÈG5BAÉ DHCPv6 AÿÇt# option18/37 ÇÈDHCPv6 á<B option18/37

EÍMÇEÇÇEÉÇ}ÉÑÉÞ<G5BÉ3ÜÔÉNMSÉ

```
5XLMLHFRQ
5XLMLHFRQ
5XLMLHFRQ
5XLMLHVKRZ
6ZLWFK
6ZLWFK
6ZLWFK
```

ÏGÄÐ -

14.9 ipv6 dhcp snooping link-detection

G5B0Ã LINK DOWN ÐB8A0þÕ<NM,XÔÖÄÁQX **no 6ÐÁs6Ñ**

ipv6 dhcp snooping link-detection

no ipv6 dhcp snooping link-detection

ÏDAÐ	–D	ÆÄ
	-	-

Ï,Õ5BÐ 5,ÕKÁ

Ïþ <G5Bã

ÏÕÞ TAxÐÃ LINK DOWN ÐB0þÕ<NMÄs6ÐÃ LINK DOWN Ê

7þÐ8A0þÐX4¼<NMÄ

ÏG5B_Ð _ 1Ï5B0Ã LINK DOWN ÊþÐ8A0ÃX|Õ<NMÄ

5XLMLHFRQ11SYGKFSVQRSLQLQGHWHFWLRQ

ÏÎGÐ

Q	ÆÄ

@0.02 15.6 ref0603 T308 -0.0148 Tw1-0.09 0 01-0.09 125.1359050603 Tm[(sho)17(w)-25(i)8(pv)11(6)-1(d)-6(hcp snoo)6(ping)>]TJ

ǴƖƃB_Đ -

ÎǴĢǪ	Ǫ	ƐÄ

	–D	Ë Ä
	vlan-id	ûË > ó, X VLAN

Ï ,Õ5BÐ A‹s65Ñ,ÕKÁ

Ï yG5Bã

ÏÊ EË‹G5BAÊ DHCPv6 AÿÏ# option18 interface-idÊ VLAN Ê, X VLANÈDHCP á<B option18 EÝMÌ,Ë> ÓÏÄ

ÏG5B_Ð G5Bü DHCPv6 AÿÏt9 option18 interface-idÊÉÝM,X VLAN4094 Â VLAN4093 ,X _Ê

```
5XLMLHFRQIXUHWHUPLQDO
5XLMLHFRQIQWHUIDFHIDVW(WKHUQHW
5XLMLHFRQIILSYGKFSVRQRSLQODQ LQRUPDWLRQSWLRQKDQYODQRYODQ
5XLMLHFRQIIHQ
```

ÎÏGÊ	Ç	Ë Ä
	-	-

ÏGÄÊ -

14.13 ipv6 dhcp snooping vlan *vlan-id* information option format-type interface-id string

û DHCP AÿÏt9 option18 EÝMÌÈ Ú Option18 interface-id ??¼XY•

Á¸ã ASCIIÅ > EÝ@ ËÔ¨G5BÊG5BAÊ AÊX **no 6Ê**

GÉs6Ñ

ipv6 dhcp snooping vlan *vlan-id* **information option format-type interface-id string** *ascii-string*

no ipv6 dhcp snooping vlan *vlan-id* **information option format-type interface-id string** *ascii-string*

ÐAÊ	–D	Ë Ä
	vlan-id	DHCPv6 AÿÏü VLAN
	ascii-string	Interface-id Ø2X??¼XY•

Ï ,Õ5BÐ A‹s65Ñ,ÕKÁ

Ï yG5Bã

ÏÊ EË‹G5BAÊ DHCPv6 AÿÏ# option18 interface-id ??¼YÈDHCPv6 á u<B option18 EÝMÌ,Ë> ÓÏÄ

ĠБB_Đ GБBü DHCPv6

ÏGÄê -

14.15 ipv6 verify source

G5B0ÃÔÄ¼ÇÄ¼Ç **no 6ÈÉÃÔÄ¼ÇÄ**

ipv6 verify source [**port-security**]

no ipv6 verify source

ÐAê

–D	ÆÄ
port-security	MAC + IPV6 ÉÝÈÈ MAC È IPV6 FÑÜÜ><NMÆÆÆ8–DÊ IPV6 Eê ÐÝ[È IPV6 0ÜÜ><NMÈAÆÆ×

5,ÕGKÁ

0Ç5Bã

4¼ÔÆ5ßA' IPV6 ÆÆ› DHCPV6 xf9ª IPV6 ÈÜu

)Ú5BM-Ô¼,XÆÆ²Ä

_ 1Ö5B0Ã fastethernet 0/1 Ô MAC+IPV6 Eê¼ÔX4¼Ô

5XLMLHFRQILJYHUIDFHIDVWHWKHUQW

5XLMLHFRQILJILSYYHULIVRXUFHSRUWVHFXULW\

Ô	Ç	ÆÄ
	-	-

ÏGê -

14.16 renew ipv6 dhcp snooping database

Ô DHCPv6 snooping s6ÆLÔ¦' flash ,XÇÐ DHCPv6 Snoo/C2gri5(onC2gr-6(g)

flash

14.18 show ipv6 dhcp snooping binding

/ dhcpv6 snooping

Ï5,Õ5BÐ -

Ïê Ç (Mã

ÏÊ EÉ8ãß dhcpv6 snooping ¼Ê<,XÍÇÄ

ÏG5B_Ð _ 1Ö

```
5XLMLHVKRWSYGKFSVQRSLQUHIL[
7RWDOQPEHURISUHIL[
0DFGGUHVV,3Y3UHIL[/HVHV9/$,QVHUIDFH

GIID
```

ÏÎGÇ

Ç	ÉÄ
-	-

ÏGÄè -

14.20 show ipv6 dhcp snooping statistics

/ dhcpv6 snooping ÝÚ dhcpv6 y[,X4ÃuÇÄ

show ipv6 dhcp snooping statistics

ÐÄè

–D	ÉÄ
-	-

Ï5,Õ5BÐ -

Ïê Ç (Mã

ÏÊ EÉ8ãß dhcpv6 snooping ÝÚ dhcpv6 y[,X4ÃuÇÄ

ÏG5B_Ð _ 1ÇÐ dhcpv6 snooping ÝÚ dhcpv6 y[,X4ÃuÇ

```
5XLMLHVKRWSYGKFSVQRSLQWDWLVWLFV
3DFNHWV3URFHVVHGEÝ&Y6QRSLQ
3DFNHWVURSSHG%HFDXVH
5HFHLYHGRQUXVWHGSRUWV
5HODIRUZDUG
1RELQLÐQU\
%LQLQDLO
8QQQDFNHW
8QQQXWSXWLQWHUIDFH
1RHQXXPHRU\
SPLQOWHUGKFSYSNW
```

+‰	AÈ
Received on untrusted ports	ü untrust ø¥Xá<ĥy[
Relay forward	ø¥EÇÕ Relay ,Xy[
No binding entry	release/decline y[ĥ,X4¥><NMáøùÿÈ [>ø
Binding fail	><NM4¥₩BĞùø¥Xy[ĐÙÇ@ßø
Unknown packet	ø¥X DHCP #Ay[Ä
Unknown output interface	ø¥Xy[Đ MAC RÈ trust ü'Ý G5B
No enough memory	ü'Ćø¥XY,

Admin filter-dhcpv6-pkt

```
5XLMLHVKRZSYVRXUFHELQLQ
7RWDOXPEHURIELQLQ
0DFGUHVV,SYGUHVV/HDVHVWSH9ODQVHUIDFH

GIGPLFID
```

ÏĈĢĐ		
	Ç	ĒÄ
	-	-

ĊĢÄđ	-

14.22 clear ipv6 dhcp snooping binding

ĉ8	dhcpv6 snooping 4¥DBg,XĐĊÄ

clear ipv6 dhcp snooping binding [*ipv6-address*] [*mac-address*] [**vlan** *vlan_id*] [**interface** *interface_name*]

ĐAđ		
	–D	ĒÄ
	ipv6-address	đ¹ ipv6 ĥ,X4¥><NM
	mac-address	đ mac ĥ,X4¥><NM
	vlan *vlan_id*	đ VLAN ĥ,X4¥><NM
	interface *interface_name*	đ¹ýh,X4¥NM

ĊĵÕ5BĐ	-

Đ	(Mã

ĊĐ	EĒAđ	dhcpv6 snooping 4¥DBg4đXĐĊÄ

ĊĢ5B_Đ	_ 1đ8	dhcpv6 snooping 4¥DBg,XĐĊ

```
5XLMLHFOHDULSYGKFSVRRSLĐLQLQ
```

ÏĈĢĐ		
	Ç	ĒÄ
	-	-

ĊĢÄđ	-

14.23 clear ipv6 dhcp snooping prefix

ĉ8	dhcpv6 snooping 4Ê<,XĐĊÄ

clear ipv6 dhcp snooping prefix [*ipv6-prefix*] [*mac-address*] [**vlan** *vlan_id*] [**interface** *interface_name*]

14.25 debug ipv6 dhcp snooping

Ô dhcpv6 snooping ,XA^GÊÄ¸Q **no 6ÈÑXA^GÄ**

debug ipv6 dhcp snooping {event | packet}

no debug ipv6 dhcp snooping {event | packet}

ÐA

–D	Ë
event	_**ÊOA^pÈÈCþ** DHCPv6 SNP ,Xþ VLANÃ AP ,X<NMÃ8 1
packet	dhcpv6 y[2OA^pÈÈCþ DHCPv6 y[,XÐÃ> È sÃC

Ð,Õ5BÐ 5,ÕKÁ

Ð (Mã

ÐÑ EË^Ã 3 dhcpv6 snooping s6ÑX^GÄ

Ð5B_Ð _ 1Ô dhcpv6 snooping ,X_ÊO^GÄ
5XLMLHGHEX1SYGKFSVRSLYHV

Ï

Ç	Ë
-	-

Ð -

16 NFPP

16.1 arp-guard attack-threshold

G5B<Ï“Ès[EêYEÏ“,XÊx,ïø Ä

arp-guard attack-threshold {**per-src-ip** | **per-src-mac** | **per-port**} *pps*

ÐAÐ

ï5,Õ5BÐ TAx ARP kï56Ñ

ïÇ NFPP G5Bã

ïÐÊÐ -

ïG5B_Ð 5XLMLHFRQIQSS
5XLMLHFRQIQSSDUSXDUGHQEOH

ïÎGÇ

Ç	ÊÄ
nffp arp-guard enable	**0Ê** ARP kï6Ñ
show nfpp arp-guard summary	**Ç5B**

ïGÄè -

16.3 arp-guard isolate-period

AÇG5B<Lh/ÊÈ
arp-guard isolate-period {*seconds* | **permanent**}

ïÐAè

–D	ÊÄ
seconds	Lh/ÊÈ 0 ï[30, 86400] Ä
permanent	**Ê/•**

ï5,Õ5BÐ <Lh/ÊÈX5,Õ 0Ê/Ä

ïÇ NFPP G5Bã

ïÐÊÐ -

ïG5B_Ð 5XLMLHFRQIQSS
5XLMLHFRQIQSSDUSXDUGLVROODWHSHULRG

ïÎGÇ

Ç	ÊÄ
nfpp arp-guard isolate-period	**0Ê5B/Ê**
show nfpp arp-guard summary	**Ç5B**

ïGÄè -

16.4 arp-guard monitored-host-limit

AÇG5BÕXÐÄ
arp-guard monitored-host-limit *number*

show nfpp arp-guard summary	**G5B**
show nfpp arp-guard hosts	****
clear nfpp arp-guard hosts	****

ÏGÄð -

16.6 arp-guard rate-limit

G5B<L“
arp-guard rate-limit {per-src-ip | per-src-mac | per-port} *pps*

ÐAð

–D	Ä
per-src-ip	IP E> Ló
per-src-mac	MAC E> Ló
per-port	
pps	L“ [,9999] Ä

ï,Õ5BÐ IP MAC ,X5,Õ“ 4X5,Õ“ 100

ð NFPP G5Bã

ïð -

ïG5B_Ð 5XLMLHFRDG

ËÇ	NFPP G5Bã
ËSÊÐ	Vp 10 /§ 15 Þ ARP y[ÐÃ MAC Î5ã IP ÈÒÐÃ MAC ã IP Î5àÛ IP Ãxæ¥eÄ
ËG5B_Ð	5XLMLHFRQILJ 5XLMLHFRQILJSDUDPXDUGVFDQKUHVKROG

ÏÎGÇ

Ç	ÆÄ
nfpp arp-guard scan-threshold	**0Õ5B“**
show nfpp arp-guard summary	**G5B**
show nfpp arp-guard scan	ß ARP ²<
clear nfpp arp-guard scan	ã ARP ²<

ËGÄã

-

16.8 clear nfpp arp-guard hosts

È8‹¶ÆZp>Ł/ÈÔ‹28Lh/•

clear nfpp arp-guard hosts [**vlan** *vid*] [**interface** *interface-id*] [*ip-address* | *mac-address*]

ËÐAã

–D	ÆÄ
vid	<.5%Ë
interface-id	0ÃÄ
ip-address	IP
mac-address	MAC

Ëb‚Õ5BÐ

(Mã

Ëã

VpáDÈ</È8Ý•¥¶XÄ

ËSÊÐ

-

ËG5B_Ð

^ VLAN 1 0Ã g 0/1 ,X‹28Lh/Ä

5XLMLHFOHDUQSSDUSXDUGKRVWVYODQQHUIDFHJ

ÏÎGÇ

Ç	ÆÄ
arp-guard attack-threshold	**G5B“**

nfpp arp-guard policyk-threshold nfpp arp-guarhppsicsick-threshold

16.9 clear nfpp arp-guard scan

Ù8 ARP ¤<Ä

clear nfpp arp-guard scan

ÐA¤	–D	Ë Ä
	-	-

Ö,Õ5BÐ -

Ð (Mã

Ö Ð -

Ö5B_Ð 5XLMLHFOHDUQSSDUSXDUGVFDQ

ÎGÐ

Q	Ë Ä
arp-guard scan-threshold	**G5 “**
nfpp arp-guard scan-threshold	**G5 “**
show nfpp arp-guard scan	ß ARP ¤<

ÖÄ¤ -

16.10 clear nfpp define *name* hosts

Ù8;Z>Lh/ÈÔ28Lh/Ä

clear nfpp define *name* **hosts** [**vlan** *vid*] [ ] [*ip-addre*]ss[ ]

[ ]

ÐA¤	–D	Ë Ä
	name	7 ÏkÏ2_Ó Ä
	vid	<.5%Ë

ÏG5B_Đ tcp ,X VLAN 1 0Ãg 0/1 ,X
5XLMLHFOHDUQSSGHILQWFSKRVWVYODQQHUIDFHJ

ÎGĐ

Q	Ä
show nfpp define hosts	**/7 Xb/**

ÏGÄ -

16.11 clear nfpp dhcp-guard hosts

8Lh/Ä

clear nfpp dhcp-guard hosts [*vlan vid*] [**interface** *interface-id*] [*mac-address*]

ÐAÐ

–D	Ä
vid	<.5%Ë
interface-id	0Ä
mac-address	MAC

Ï,Ð5BÐ -

Ð

• Ä

ï,Õ5BÐ	-
ï	(Mã
ïî	VpáDè<ù8ýSïÇBA%Sð

16.14 clear nfpp ip-guard hosts

ÏĈĠĘ	Ç	Ɇ Ä
	show nfpp log	**/** NFPP Ġ5B₫ç

ĠÄȁ -

16.16 cpu-protect sub-interface {manage|protocol|route} percent

AĘĠ5BɆ2O_y[4ŧĿȝX,RÚ

cpu-protect sub-interface {*manage*|*protocol*|*route*} **percent** *percent_vaule*

ĐAȁ

–D	Ɇ Ä
percent_vaule	,RĞĿ 1 100

ĵ,Õ5BĐ 1u)ÚO(Manage) 4ŧdRÚ 30
E₫O(Route) 4ŧdRÚ 25
ŦA2O(Protocol) 4ŧdRÚ 45

Ę 0 <G5Bã

Ĵ Ĝ -

ĠĵB_Đ 5XLMLHFRQILJXUHSURWHFWVXEL0WHUIDFHPDQDJHSHUFHQW

ÏĈĠĘ

Ç	Ɇ Ä
cpu-protect sub-interface { *manage* | *protocol* | *route* } **pps**	A’5BɆ2O_y[,X4ŧĿȝX,RÚ !

ĠÄȁ -

16.17 cpu-protect sub-interface {manage|protocol|route} pps

AĘĠ5BɆ2O_y[,XĠ5Ä

cpu-protect sub-interface {***manage|protocol|route***} **pps** *pps_vaule*

ĐAȁ

–D	Ɇ Ä
pps_vaule	LĿĞ“ĞĿ 1-8192

ĵ,Õ5BĐ 1u)ÚO(Manage) ,X5,ÕĞ 3000
E₫O(Route) ,X5,ÕĞ 3000
ŦA2O(Protocol) ,X5,ÕĞ 3000

Ę 0 <G5Bã

ËßÐ	-
ËG5B_Đ	5XLMLHFRQLFSXSURWHFWVXELQWHUIDFHPDQQHSSV
ÌÎGĐ	Ç Ë:Ä

Ïê© NFPP G5Bã

ÏÊÐ -

ÏG5B_Đ 5XLMLHFRQILJ
5XLMLHFRQILJSGKFSXDUGDWWDFNWKUHVKROGSHUVUFPDF
5XLMLHFRQILJSGKFSXDUGDWWDFNWKUHVKROGSHUSRUW

ÏÎGÇ

Ç	Ë
nfpp dhcp-guard policy	**G5B**
show nfpp dhcp-guard summary	**G5B**
show nfpp dhcp-guard hosts	****
clear nfpp dhcp-guard hosts	****

ÏGÄê -

16.20 dhcp-guard enable

AÇÔ DHCP Lë6Ñ
dhcp-guard enable

ÐAê

–D	Ë
-	-

ï,Õ5BĐ 0ÃÍG5B DHCP kÒÈ¥ÔÄ

Ïê© NFPP G5Bã

ÏÊÐ -

ÏG5B_Đ 5XLMLHFRQILJ
5XLMLHFRQILJSGKFSXDUGHQEOH

ÏÎGÇ

Ç	Ë
nffp dhcp-guard enable	**0** DHCP kë6Ñ
show nfpp dhcp-guard summary	**G5B**

ÏGÄê -

16.21 dhcp-guard isolate-period

AÇG5B<Lh/ÈÈ
dhcp-guard isolate-period {*seconds* | **permanent**}

ÏÎGÇÇ

Ç	ÉÄ
show nfpp dhcp-guard summary	**ÇÇ5ßß**

ÜGÄßè -

16.23 dhcp-guard monitor-period

AßÇG5B,¥ÊÉÃ

dhcp-guard monitor- period *seconds*

ÜÄßè

–D	ÉÄ
seconds	,¶ÊÈßßÈ180, 86400] Ä

Ü,Õ5BÐ <,¥ÊÉX5,Õ 600 /Ä

Üè NFPP G5Bã

ÜÐ "ß,ÙXÇpLh/ÊÈ 0ÊÉ> ECß¥ÇYß¶ÊÊCß¥É/ß
Èh/ÊÉG5BM2LÊÐ¶ÉCß¶XÜÙ³Ê/ÈYÉ'5BLh/•
ÊÃÊÉh/ÊÈ 0 ,XÊ‰
VpLh/ÊÊM2LÊßÇÙG0ÃÜ5Ü8ÉÃ> ECß¶Ä

ÜG5B_Ð 5XLMLHFRQQGSS
5XLMLHFRQQGSSGKFSXDUGPRQWRUSHULRG

ÏÎGÇÇ

Ç	ÉÄ
show nfpp dhcp-guard summary	**ÇÇ5ßß**
show nfpp dhcp-guard hosts	**ß¶**
clear nfpp dhcp-guard hosts	**ßÊÉ•**

ÜGÄßè -

16.24 dhcp-guard rate-limit

G5B<LÉÜ“Ä

dhcp-guard rate-limit { **per-src-mac** | **per-port**} *pps*

ÜÄßè

–D	ÉÄ
per-src-mac	**ß** MAC E> LÉó
per-port	**ßÊ**
pps	LÉÜ“ßÈ1,9999] Ä

Ü,Õ5BÐ **ß** MAC ,X5,ÕÉÜ“Ç, 5 ßÃX5,ÕÉÜ“Ç, 150 ßÄ

16.26 dhcpv6-guard enable

AÇÇÔ DHCPv6 Lï6Ñ

dhcpv6-guard enable

ÐAå

–D	Ë
-	-

ï,Õ5BÐ 0ÃÁ5B DHCPv6 kÔÈ¥ÔÄ

Ç NFPP G5Bã

Ï -

G5B_Ð

```
5XLMLHFRQIGSS
5XLMLHFRQIGSSGKFSYXDUGHQEOH
```

ÎGÇ

Ç	Ë
nffp dhcpv6-guard enable	**0** DHCPv6 kï6Ñ
show nfpp dhcpv6-guard summary	**G5B**

GÄå

-

16.27 dhcpv6-guard isolate-period

AÇÇG5B<Lh/ÊÈ

dhcpv6-guard isolate-period {*seconds* | **permanent**}

ÐAå

–D	Ë
seconds	Lh/Ê 0 [30, 86400] È 0 ></ä/Ä
permanent	**/•**

ï,Õ5BÐ <Lh/ÊX5,Õ 0Èä/Ä

Ç NFPP G5Bã

Ï ÎXLh/ÊLh/Ê0ÃXLh/ÊFLh/Ê

püG5BÎ0ÃXLh/ÊwGLh/ÊÎ0ÃXLh/Ê

G5B_Ð

```
5XLMLHFRQIGSS
5XLMLHFRQIGSSGKFSYXDUGLVRODWHWLPHRXW
```

ÎGÇ

Ç	Ë

nfpp dhcpv6-guard isolate-period	**0Ñ5Bl/È**
show nfpp dhcpv6-guard summary	**G5B**

ÏGÄÈ -

16.28 dhcpv6-guard monitored-host-limit

AÇG5BÕXÇD

dhcpv6-guard monitored-host-limit *number*

ÏÐÄÈ

–D	ÆÄ	
number	ÕXÇDÈÈ	1 4294967295

Ï5ÕBÐ 5,ÕXÇD 1000 þ

ÏÇ NFPP G5Bã

ÏÑ Vp¿¢D4ÆE'TA-x,X 1000 þÆÊu)Ì¿¢XÐ,Â'5Bã 1000È
Ì8¿Æ¿¢ÈÐÇ%ERROR Ö The value that you configured is smaller than current monitored hosts 1000G5B,X¿¢DÅ þlease clear a part of monitored hosts. 9¤ Gf1u)ÌÇ5BÙ¤ÐÌ8FÆÆ•¿¢XÄ
¿¢<þ% NFPP_DHCP_GUARD-4-SESSION_LIMIT: Attempt to exceed limit of 1000G5B¿¢DÅmonitored hosts. Gf1u)ÌÄ

Ï5B_Ð 5XLMLHFRQILJ
5XLMLHFRQILJSGKFSXDUGPRQWRUHGKRVWOLPLW

ÎÇÐ

Ç	ÆÄ
show nfpp dhcpv6-guard summary	**G5B**

ÏGÄÈ -

16.29 dhcpv6-guard monitor-period

AÇG5B,¿ÆÈ

dhcpv6-guard monitor- period *seconds*

ÏÐÄÈ

–D	ÆÄ
seconds	,¿ÆÐÈÈ[180, 86400] Ä

Ï5ÕBÐ <,¿ÆÈX5,Õ 600 /Ä

ÏÇ NFPP G5Bã

	5XLMLHFRQILJ 5XLMLHFRQILJ SSGKFSYXDUGPRQWRUSHULRG

	show nfpp dhcpv6-guard summary	
	show nfpp dhcpv6-guard hosts	
	clear nfpp dhcpv6-guard hosts	

	-

16.30 dhcpv6-guard rate-limit

dhcpv6-guard rate-limit { **per-src-mac** | **per-port**} *pps*

	–D	

16.31 global-policy

AÇG5B7ñk2O_,XÎ5ÙÃ4“Ä

global-policy {per-src-mac | per-src-ip | per-port} *rate-limit-pps attack-threshold-pps*

ÐAê		
	–D	Ä
	per-src-ip	Î IP/VID/0Ãþ> Eý[4ªAu
	per-src-mac	Î MAC/VID/0Ãþ> Eý[4ªAu
	per-port	Îþ[yX(}0Ãþ4ªAu
	rate-limit-pps	
	attack-threshold-pps	

ï,Õ5BÐ -

ïÇ NFPP 7ñk2O_G5Bã

ïÊÐ ÕñkÏ2O_ÈMOA2O_ôEý[4ªAu,XÍ2OsÊÎ IP Aþ
MAC Aþ> bÇX7ñ[Eý[4ªAuêÎ0ÃXEý[4ªAuêÍ2O,XL$
E“Ï“Ä“ÄÏ“ãÑÏ“ÄÇ[CYEÏ“ÊÍ2O,X7ñk2O_y
[ÐÄÇ[CYEÏ“ÊÐ log trapÎÇÍXÍOÈ
EÐG5B,XLh/ÊÄÏ> Lh/ÇÄ

ïG5B_Ð 5XLMLHFRQILJ
5XLMLHFRQILJSROLF\SHUVUFLS
5XLMLHFRQILJSROLF\SHUSRUW

ÎÎGÇÐ

Ç	Ä
show nfpp define summary	**/7ñkÏ2OG5Bß**
nfpp define *name* **policy**	**G5BÃÄ“**

ïGÄê -

16.32 icmp-guard attack-threshold

G5B<Ï“ÈyÇ[EÍ2YEÏ“,XÊx,ïÄ

	IP **cmp-guard rate-limit**
	NFPP
	-
	5XLMLHFRQIGS 5XLMLHFRQIGSLFPSXDUGDWWDFNWKUHVKROGSHUVUFLS 5XLMLHFRQIGSLFPSXDUGDWWDFNWKUHVKROGSHUSRUW

16.34 icmp-guard isolate-period

AÇÇG5B<Lh/ÊÈÄ

icmp-guard isolate-period {*seconds* | **permanent**}

ÏDAÈÈ

–D	ÉÄ
seconds	Lh/ÊÈÈÈÉ 0 É[30, 86400] È 0 ></Éh/Ä
permanent	Ê/•

Ï,Õ5BÐ <Lh/ÊÈÈX5,Õ 0ÉÉh/Ä

ÏÇ NFPP G5Bã

ÏÉÐ ÊÇXLh/ÊÉLh/ÊÈÊ0ÃXLh/ÊÈÉFÉh/ÊÈÊÇÃ
pÙÚG5BÊ0ÃXLh/ÊÈwGÉLh/ÊÈÉÊ0ÃXLh/ÊÈÄ

ÏG5B_Ð 5XLMLHFRQQGS
5XLMLHFRQQGSLFPSXDUGLVRODWHSHULRG

ÏÎGÇ

Ç	ÉÄ
nfpp icmp-guard isolate-period	0ÃG5BFÉh/ÊÈ
show nfpp icmp-guard summary	G5BÊ

ÏGÄÈ -

16.35 icmp-guard monitored-host-limit

AÇÇG5BÇXÇD

icmp-guard monitored-host-limit *number*

ÏDAÈÈ

–D	ÉÄ
number	ÇXÇDÉÈ 1 4294967295

Ï,Õ5BÐ 5,ÇXÇD 1000 Ä

ÏÇ NFPP G5Bã

ÏÉÐ Vp¿¥D4E’TAx,X 1000 ÈÉu)Ú¿¥XÎ,Â’5Bã 1000È
Î8Ä¿¥ÉÈÇ%ERROR Ö The value that you configured is smaller than current monitored hosts 1000ÄG5B,X¿¥DÅ È please clear a part of monitored hosts. 9¤ Gf1u)ÚG5BÙÈÎ8F¿¥XÄ
¿¥È% NFPP_ICMP_GUARD-4-SESSION_LIMIT: Attempt to exceed limit of 1000ÄG5B,X¿¥DÅmonitored hosts. Gf1u)ÚÄ

ÏG5B_Ð 5XLMLHFRQIQG
5XLMLHFRQIQGSLFPSXDUGPRQWRUHGKRVWOLPLW

ÏÎGÇÐ

Ç	Ë Ä
show nfpp icmp-guard summary	**G5B**

ÏGÄÈ -

16.36 icmp-guard monitor-period

A G5B,¥ËÃ
icmp-guard monitor-period *seconds*

ÐAÈ

–D	Ë Ä
seconds	,¥ËÈ 80, 86400] Ä

Ï,Õ5BÐ <,¥ËÈX5,Õ 600 /Ä

Ç NFPP G5Bã

ÏÐ "È,ÙXÇpLh/ËÈ 0ÈÈ> ECÇ¥ËYÇ¥ËCÇ¥Ë/ß
Èh/ËÈG5BM2LÇÇCÇ¥XÏÙ³Çh/ÈYÇ'5BLh/•
ËÃ¥ËÈh/ËÈ 0 ,XÈ‰
VpLh/ËÈ2LÇÇ,ÏG0ÃXÏÙ85ã> ECÇÄ

Ï G5B_Ð 5XLMLHFRQIQG
5XLMLHFRQIQGSLFPSXDUGPRQWRUSHULRG

ÏÎGÇÐ

Ç	Ë Ä
show nfpp icmp-guard summary	**G5B**
show nfpp icmp-guard hosts	**Ç**
clear nfpp icmp-guard hosts	**È**

ÏGÄÈ -

16.37 icmp-guard rate-limit

G5B<LËÄ“Ä
icmp-guard rate-limit { **per-src-ip** | **per-port**} *pps*

ÐAÈ

–D	Ë Ä
per-src-ip	**Ç** IP E> LËó

per-port	þÿ
pps	L Ä

Ï,Õ5BÐ þ IP ,X5,Õ 4“ þ,X5,Õ 4“ ,þÿX5,Õ 4“ {5Ê KÖ

S26	200						
S2924G	200						
S3250E	250						
S3760	420						
S3760E	250						
S5750	130						
S5760	130						
S86			M8606-CM	M8610-CM		400	M8606-CM
II	M8610-CM II	M8614-CM II		2000			

Ï¿Õ5BÐ 5,ÕÝ'5BÌÃ

Ïº NFPP G5Bã

ÏÊÕ Vp1u)lÃ> ,¢ÁÞ></ÃEAÇ5BÄÃ
T CPU ,X ICMP y[ÞÀE CPUÃ,XLÊÄ:ÃEG5B}-ÕÝÕ
Ã5%‰ÝÕ> ,Ä
ÃÕ'5B 500 5Ã

ÏG5B_Ð 5XLMLHFRQILJ
5XLMLHFRQILJSLFPSXDUGWUXVWHGKRVW

ÏÇÐ	Ç	ÊÄ
	show nfpp icmp-guard trusted-host	**G5B**

ÏÄÃ -

16.39 ip-guard attack-threshold

G5B<Ì“Èy[EÈYEÌ“,XÊx,Ã Ä

ip-guard attack-threshold {**per-src-ip** | **per-port**} *pps*

ÐÃ

–D	ÊÄ	
per-src-ip	**G5B**	IP ,XÌ“Ä
per-port	**G5B**	ÃÌ“Ä
pps	Ì	,9999] Ä

Ï¿Õ5BÐ Ã IP ,X5,ÕÐ“Ì 20 ÃÀX5,ÕÐ“Ì 200 Ã

ckj/C2_0 1 TfNFP0 Tc 1.193 0 Td[<0D[(ckF07114>-7<2C5/TT0 1 C4>5E30C140E-0.0028 Tc 16.2 -45.233 -1.727 T.022T

show nfpp ip-guard summary	**ÍG5BÐ**
show nfpp ip-guard hosts	**Í**
clear nfpp ip-guard hosts	**ÌÍ•**

ÏGÄà IP L ÕÍ IP LÄ

16.40 ip-guard enable

AÍ<Ô IP L6Ñ
ip-guard enable

ÐAà

–D	ÆÄ
-	-

ï,Õ5BÐ TAx IP L6Ñ

Í NFPP G5Bã

ïÔ -

ïG5B_Ð 5XLMLHFRQIGSS
5XLMLHFRQIGSSLSXDUGHQEOH

ÏGÍ

Í	ÆÄ	
nffp ip-guard enable	**0**	IP L6Ñ
show nfpp ip-guard summary	**ÍG5BÐ**	

ÏGÄà -

16.41 ip-guard isolate-period

AÍG5B<Lh/ÆÄ
ip-guard isolate-period {*seconds* | **permanent**}

ÐAà

–D	ÆÄ
seconds	Lh/Æ 0 6[30, 86400] Ä
permanent	**/•**

ï,Õ5BÐ <Lh/ÆX5,Õ 0Éh/Ä

Í NFPP G5Bã

ïÔ -

	number		1	4294967295

	5,	1000	
	NFPP G5B		
	Vp	1000	1000
	current monitored hosts 1000		“The value that you configured is smaller than please clear a part of monitored hosts.”

106 55

show nfpp ip-guard summary	**G5B**

ÏGÄê -

16.45 ip-guard scan-threshold

G5B<2“Ä

ip-guard scan-threshold *pkt-cnt*

ÏDAê

–D	EÄ
pkt-cnt	2“ê[1,9999] Ä

Ï,Õ5BÐ 5,2Õ“ 10 /¦ 100 þÄ

Ïð NFPP G5Bã

ÏÐ -

ÏG5B_Ð

```
5XLMLHFRQIGSS
5XLMLHFRQIGSLSXDUGVFDQVKUHVKROG
```

ÏÎGÇ

Ç	EÄ
nfpp ip-guard scan-threshold	**0Õ5B2“**
show nfpp ip-guard summary	**G5B**

ÏGÄê -

16.46 ip-guard trusted-host

Vp1u)lÃ> ,¥GÁ></ÃEAÇ5BÄ

ip-guard trusted-host *ip mask*

no ip-guard trusted-host {**all** | *ip mask*}

ÏDAê

–D	EÄ
ip	IP
mask	IP ,X}-Õ
all	` **no Ô5B**

Ï,Õ5BÐ -

Ïð NFPP G5Bã

ÏÐ Vp1u)lÃ> ,¥GÁ></ÃEAÇ5BÄÃ

T CPU ,X IP y[ÚA¢E CPUß,XLÉÄ:ØÍ
ÊÕ5B 500 5ã

Ïõ5B_Ð ^ 1.1.1.0/24 5%‰Ïõ5Bã

```
5XLMLHFRQILJXUH
5XLMLHFRQILJXUHSLSXDUGWUXVWHGKRVW
```

ÎÕÇÐ

Ç	ÉÄ
show nfpp ip-guard trusted-hosts	ã

ÏÄÀè -

16.47 isolate-period

AÇÕ5BLh/ÊÈ
isolate-period {*seconds* | **permanent**}

ÐÀè

–D	ÉÄ
seconds	Lh/ÊÈ 0 ß[30, 86400] È 0 ></ÉÄ
permanent	ÞÀ•

ß,Õ5BÐ Lh/ÊÈX5,Õ 0ÈÉÄ

Ç NFPP 7‰2O_Õ5Bã

ßÐ Lh/ÊÈ 0 È‰2O_,Xy[EÞ[CYEÄ“,XÉÄLh/ÀÈÊÕÝ¾
n2O_,Xy[Ä

Ïõ5B_Ð

```
5XLMLHFRQILJXUH
5XLMLHFRQILJXUHSLSXDUGWUXVWHGKRVW
5XLMLHFRQILJXUHSLSXDUGWUXVWHGKRVWLVRODWHSHULRGSHUPDQHQW
```

ÎÕÇÐ

Ç	ÉÄ
show nfpp define summary	/7‰2O_Õ5BÇ

ÏÄÀè -

16.48 log-buffer entries

Õ5B NFPP ¼ã
log-buffer entries *number*

ÐÀè

–D	ÉÄ

number	4ßDBß[0,1024]

Ъ,Õ5BÐ TA-x4ã 256Ä

ãÐ NFPP G5Bã

ЪÐ -

log-buffer entries *number*	**G5B** NFPP ¼ä
show nfpp log summary	**/** NFPP G5B¢ä

ÏGÄê -

16.50 logging

G5B NFPP A)ø¼ VLAN ê,ÃXÄ

logging vlan *vlan-range*

logging interface *interface-id*

ÐAê

–D	E.Ä
vlan-range	LÔA)û VLAN 8È,XÇÈg9Ø1-3,5 Ä
interface-id	*ê0ê*

ï5,Õ5BÐ ¥ÑÃ)Ä

ïÐ NFPP G5Bã

ïÐ EEAÃÐ> E¾)û VLAN 8êû0Ã,XÇÄE¿G5B
êXG2È¾ÔÇÈAA)¼ä

ïG5B_Ð 1u)ÍD¾ VLAN 1Ã VLAN 2ÃLAN 3 ` VLAN 5 ,XÈ5BVÖ
5XLMLHFRQIG
5XLMLHFRQIGSORJEXIIHUVL]H
1u)ÍD¾0Ã G 0/1 ,XÈ5BVÖ
5XLMLHFRQIG
5XLMLHFRQIGSORJEXIIHUVL]H*

ÏÍGÐ

Ç	E.Ä
show nfpp log summary	**/** NFPP G5B¢ä

ÏGÄê -

16.51 match

A0ê7¾kÏG¦Xy[2O_Ä

match [etype *type***] [src-mac** *smac* **[src-mac-mask** *smac_mask***]] [dst-mac** *dmac* **[dst-mac-mask** *dst_mask***]] [protocol** *protocol***] [src-ip** *sip* **[src-ip-mask** *sip-mask***]] [src-ipv6** *sipv6* **[src-ipv6-masklen** *sipv6-masklen***]] [dst-ip** *dip* **[dst-ip-mask** *dip-mask***]] [dst-ipv6** *dipv6* **[dst-ipv6-masklen** *dipv6-masklen***]][src-port** *sport***] [dst-port** *dport***]**

ÐAê dport

type	*ÃPO*
smac	*6* mac
smac_mask	*6* mac }-Õ
dmac	*Â* mac
dmac_mask	*Â* mac }-Õ
protocol	IPv4/v6 y[ÆË
sip	*6* IPv4
sip_mask	*6* IPv4 }-Õ
sipv6	*6* IPv6
sipv6_masklen	*6* IPv6 }-ÕSz
dip	*Â* IPv4
dip_mask	*Â* IPv4 }-Õ
dipv6	*Â* IPv6
dipv6_masklen	*Â* IPv6 }-ÕSz
sport	*6ÕÃ*
dport	*ÂÃ*

Ï,Õ5BÐ -

Ï Q NFPP G5Bã

ÏÐ ÎX7ÞkÏO_ÂA2O_ÐG¦Xy[+Æ‰

ÏG5B_Ð 5XLMLHFRQIGSS
5XLMLHFRQIGSSQSSGHILQHWFS
5XLMLHFRQIGSSGHILQHPDWFKHWSH[SURWRFRO[

ÎÏGQ

Q	Ë.Ä
show nfpp define summary	**/7ÞkÏOG5B**

ÏGÄÐ -

16.52 monitored-host-limit

AQG5BÕXÐD
monitored-host-limit *number*

ÐAÐ

–D	Ë.Ä		
number	ÕXÐDÈ	1	4294967295

Ï,Õ5BÐ 5,ÕXÐD 1000 Ä

Ï Q NFPP 7Þ2O_G5Bã

		1000	1000
		The value that you configured is smaller than current monitored hosts 1000	please clear a part of monitored hosts.
name(	1000	NFPP_DEFINE-4-SESSION_LIMIT: Attempt to exceed limit of monitored hosts.	

```
5XLMLHFRQQHFW
5XLMLHFRQQHFWSSGHILQHWFS
5XLMLHFRQQHFWSSGHILQHPRQWRUHGKRVWOLPLW
```

16.54 nd-guard attack-threshold

nd-guard attack-threshold per-port {**ns-na** | **rs** | **ra-redirect**} *pps*

	–D	Ä
	ns-na	**@**
	rs	****
	ra-redirect	****
	pps	[1,9999] Ä

30 30

NFPP

-

16.55 nd-guard enable

nd-guard enable

	–D	Ä
	-	-

ND

NFPP

-

Ï5B_Đ

```
5XLMLHFRQILJ
5XLMLHFRQILJSQGXDUGHQEOH
```

ÎÎGÇ

Ç	Ë Ä
nffp nd-guard enable	**0Õ** ND k‡6Ñ
show nfpp nd-guard summary	**Ç5B**

ÏGÄå

-

16.56 nd-guard rate-limit

G5B<Lë“Ä

nd-guard rate-limit per-port {**ns-na** | **rs** | **ra-redirect**} *pps*

ÏÐAå

–D	Ë Ä
ns-na	**FAË@**
rs	**CÃAË**
ra-redirect	**CÃ@nå[**
pps	Lë“è[1,9999] Ä

ï,Õ5BÐ

ÞÃAË @X5,Õë“Ç 15 ÇÃ<AÞX5,Ð“Ç 15 ÇÃ<
/@ Gnå[,X5,Ð“Ç 15 Ä

Ïð

NFPP G5Bã

Ïê

-

Ï5B_Đ

```
5XLMLHFRQILJ
5XLMLHFRQILJSQGXDUGUDWHOLPLWSHUSRUWQQ
5XLMLHFRQILJSQGXDUGUDWHOLPLWSHUSRUWUV
5XLMLHFRQILJSQGXDUGUDWHOLPLWSHUSRUWUDUHGLUHFW
```

ÎÎGÇ

Ç	Ë Ä
nfpp nd-guard policy	**G5BXë“**

Ï-DAðð	–D	Ë.Ä
	-	-

Ï,Õ5BÐ 0ÃÁ5B ARP kÔÈ¥kÔÄ

ÐÇ yG5Bã

ÏÐ 0Ã¾ ARP kÔb< ARP kÔÄ

Ï5B_Ð 5XLMLHFRQILQHUIDFH*
5XLMLHFRQILQHSSDUSXDUGHQEOH

ÎÔÇÐ

Ç	Ë.Ä
arp-guard enable	ê ARP kï56Ñ

16.59 nfpp arp-guard policy

0Õ5BF¼XL64“Ä

ÏÊÔ -

ÏG5B_Đ
```
5XLMLHFRQILJXUHUIDFH*
5XLMLHFRQILJSDUDXDUGVFDQWKUHVKROG
```

ÏÎGÇ

Ç	ÉÄ
arp-guard scan-threshold	**G5B“**
show nfpp arp-guard summary	**¡G5Bß**
show nfpp arp-guard scan	ß ARP ²<
clear nfpp arp-guard scan	è ARP ²<

ÏGÄè -

16.61 nfpp define

AÇÔ7²¼k²O_Ä
nfpp define *name*

ÏÐAè

–D	ÉÄ
name	*7²¼k²O_á*

Ïõ,Õ5BÐ -

Ïè NFPP G5Bã

ÏÊÔ ¡X7²¼k²O_

ÏG5B_Đ
```
5XLMLHFRQGSS
5XLMLHFRQGSSQSSGHILQHWFS
5XLMLHFRQGSSGHILQH
```

ÏÎGÇ

Ç	ÉÄ
show nfpp define summary	**/7²¼k²O_G5Bß**

ÏGÄè -

16.62 nfpp define *name* enable

AÇÔÕX7²¼2O_kõ6Ñ
nfpp define *name* **enable**

ÏÐAè

–D	ÉÄ

name	*7ĩ№K2_ÓÄ*

Ï5,Õ¬5BÐ -

Ïĵ¤ yG5Bã

ÏÊÎ NÝO,Ä7ĩ№ÈÈ5BZ matchÃ rate-count Ã rate-limit ` attack-threshold Ê¢5B6Ñ Ê¢5BBÄ

ÏG5B_Ð 5XLMLHFRQILJHUHQDEOH*
5XLMLHFRQILJHUHQDEOHSSGHILQHWFSHQEOH

ÏÎG¤Ð

Ç	ÉÄ
show nfpp define summary	/7ĩ№k2O_G5BÇ

ÏGÄÊ -

16.63 nfpp define *name* isolate-period

Aĵ¤ÇÊ5BF¼h/ÉÄ

nfpp define *name* **isolate-period** {*seconds* | fi7 03Th0 13(n 03(nt-0.0049 0 0 9 62.04 5m<160005104B82AF220CF3

16.64 nfpp define *name* policy

0Õ5BF¼XLÉ4“Ä

nfpp define *name* **policy** {**per-src-ip | per-src-mac** | **per-port**} *rate-limit-pps attack-threshold-pps*

ÐAÈ

–D	ÉÄ		
per-src-ip	**G5Þ**	IP ,X¼“Ä	
per-port	**G5ÞÕ¼Ä**		
rate-limit-pps	**ÉÈ**	1	9999Ä
attack-threshold-pps	**¼È**	1	9999Ä

ÏÎGÇ

Ç	Ë Ä
dhcp-guard enable	**Ê** DHCP k s6Ñ
show nfpp dhcp-guard summary	**ç G5B**

ÜGÄè -

16.66 nfpp dhcp-guard isolate-period

Aç Õ5BF Lh/ÊÈ

nfpp dhcp-guard isolate-period {*seconds* | **permanent**}

Ü Aè

–D	Ë Ä
seconds	Lh/Ê È È 0 [30, 86400] È 0 ></ h/Ä
permanent	**L/•**

Ü ,Õ5BÐ 5, Õ5BF Lh/ÊÈ Lh/ÊÈ

ç yG5Bã

Ü Ê -

ÜG5B_Ð 5XLMLHFRQILJ QHUIDFH*

5XLMLHFRQILJ SSGKFSX DUGLVRODWHSHULRG

ÏÎGÇ

Ç	Ë Ä
dhcp-guard isolate-period	**G5B/Ê**
show nfpp dhcp-guard summary	**ç G5B**

ÜGÄè -

16.67 nfpp dhcp-guard policy

0Õ5BF XL Ä

nfpp dhcp-guard policy { **per-src-mac** | **per-port**} *rate-limit-pps attack-threshold-pps*

Ü Aè

–D	Ë Ä
per-src-mac	**G5B** MAC ,XL Ä
per-port	**G5B Ä**
rate-limit-pps	**È** 1 9999Ä
attack-threshold-pps	**È** 1 9999Ä

Ü ,Õ5BÐ 0 XL Ä XL Ä XL Ä

Ïð yG5Bã

ÏÎð ï“éõÑLÉï“Ä

ÏG5B_Ð 5XLMLHFRQILJXUHWHUIDFH*
5XLMLHFRQILJXUHWHUIDFHXDUGSROLFLHUVFPDF
5XLMLHFRQILJXUHWHUIDFHXDUGSROLFLHUSRUW

ÏÎGÐ

Ç	ÉÄ
dhcp-guard attack-threshold	**G5Bï“**
dhcp-guard rate-limit	**G5Bï“**

16.69 nfpp dhcpv6-guard isolate-period

nfpp dhcpv6-guard isolate-period {*seconds* | **permanent**}

	–D		
seconds		0 [30, 86400]	0

5XLMLHFRQILJ[SSGKFSYX'UGSROLF[SHUSRUW

ÏĈĢĘ

Ę	ĖÄ
dhcpv6-guard attack-threshold	**G5B“**
dhcpv6-guard rate-limit	**G5B“**
show nfpp dhcpv6-guard summary	**ĢG5Bß**
show nfpp dhcpv6-guard hosts	**ß**
clear nfpp dhcpv6-guard hosts	**ßÆ•**

ĔĠÄß -

16.71 nfpp icmp-guard enable

AĘĘ0Ð ICMP kï6Ñ

nfpp icmp-guard enable

ĐAß

–D	ĖÄ
-	-

ï,Õ5BĐ 0ÃÍG5B ICMP kÔÈ¥ÔÄ

ĐĘ yG5Bã

ïĐ 0Ã ICMP kÔb< ICMP kÔÄ

Ğ5B_Đ

```
5XLMLHFRQILJ[QVHUIDFH*
5XLMLHFRQILJ[SSLFPSX'UGHQEOH
```

ÏĈĢĘ

Ę	ĖÄ
icmp-guard enable	**ê** ICMP kï6Ñ
show nfpp icmp-guard summary	**ĢG5Bß**

ĔĠÄß -

16.72 nfpp icmp-guard isolate-period

AĘĘ0Ã5BF¼h/ÊĖ

nfpp icmp-guard isolate-period {*seconds* | **permanent**}

ĐAß

–D	ĖÄ
seconds	Lh/ÊĖ 0 ï[30, 86400] È 0 ></ïh/Ä
permanent	**ï/•**

̈5,Õ5BĐ	5,ØŸ5BF⁄h/ÉÈ¤Lh/ÉÃ
̈Ð	yG5Bã
̈Sθ	-

Ġ5B_Đ

```
5XLMLHFRQILJWHUIDFH*
5XLMLHFRQILJQISSLFPSJXDUGLVRODWHSHULRG
```

ÏĠĐ

Ç	ĒÄ
icmp-guard isolate-period	**G5B/Ê**
show nfpp icmp-guard summary	**ß5B**

ĠÄð -

16.73 nfpp icmp-guard policy

0Õ5BF¼XLĒö"Ï"Ä

nfpp icmp-guard policy { **per-src-ip** | **per-port**} *rate-limit-pps attack-threshold-pps*

ĐAð

–D	ĒÄ
per-src-ip	**G5B** IP ,XLĒö"Ï"Ä
per-port	**G5BÃÄÄ**
rate-limit-pps	**ÉÈ** 1 9999Ä
attack-threshold-pps	**ÏÈ** 1 9999Ä

̈5,Õ5BĐ	0ÃÝ¾XLĒö"Ï"È¤,XLĒö"ÌĒö"Ä
̈Ð	yG5Bã
̈Sθ	Ï"áÑLĒö"Ä

Ġ5B_Đ

```
5XLMLHFRQILJWHUIDFH*
5XLMLHFRQILJQISSLFPSJXDUGSROLF\SHUVUFLS
5XLMLHFRQILJQISSLFPSJXDUGSROLF\SHUSRUW
```

ÏĠĐ

Ç	ĒÄ
icmp-guard attack-threshold	**G5È"**
icmp-guard rate-limit	**G5É"**
show nfpp icmp-guard summary	**ß5B**
show nfpp icmp-guard hosts	**Ï**
clear nfpp icmp-guard hosts	**ÈÆ•**

ÏGÄÐ -

16.74 nfpp ip-guard enable

AÇ0Ð IP L86Ñ

nfpp ip-guard enable

ÐAÐ	–D	ÆÄ
	-	-

Ï,Õ5BÐ 0ÃÍ5B IP LÐÈ¥ÔÄ

Ïð yG5Bã

ÏÐ 0Ã IP LÔb<LÔÄ

Ï5B_Ð IP

ÏÎGϱ

ϱ	Ł Ä
ip-guard isolate-period	**G5B/Ł**
show nfpp ip-guard summary	**ϱ5β**

ËGÄð -

16.76 nfpp ip-guard policy

0ÕB5BF½XLŁÉ“Ï“Ä

nfpp ip-guard policy {**per-src-ip** | **per-port**} *rate-limit-pps attack-threshold-pps*

ËÐAð

–D	Ł Ä		
per-src-ip	**G5β**	IP ,X“Ä	
per-port	**G5βX“Ä**		
rate-limit-pps	****	1	9999Ä
attack-threshold-pps	****	1	9999Ä

ï,Õ5BÐ 0ÃÝXLŁÉ“Ï“È¤,XLŁÉ“Ï“Ä

ËÐ yG5Bã

ËÐ Ï“éÃLŁÉ“Ä

ËG5B_Ð

```
5XLMLHFRQILJXUHIDFH*
5XLMLHFRQILJXUHIDFHSLSXDUGSROLFLSHUVUFLS
5XLMLHFRQILJXUHIDFHSLSXDUGSROLFLSHUSRUW
```

ÏÎGϱ

ϱ	Ł Ä
ip-guard attack-threshold	**G5B“**
ip-guard rate-limit	**G5B“**
show nfpp ip-guard summary	**ϱ5β**
show nfpp ip-guard hosts	****
clear nfpp ip-guard hosts	****

ËGÄð -

16.77 nfpp ip-guard scan-threshold

0ÕB5BF“Ä

nfpp ip-guard scan-threshold *pkt-cnt*

ËÐAð

–D	Ł Ä	
pkt-cnt	“È[1,9999]	Ä

Ï5,Õ5BÐ ùG5BÎò0ÃX IP Ø“È¢ ARP Ø“Ä

Ëø yG5Bã

ÏÊÔ -

ÏG5B_Ð 5XLMLHFRQILJXUHUIDFH*
5XLMLHFRQILJSSLSXDUGVFDQKUHVKROG

ÎÏGÇ

Ç	Ë¢Ä
ip-guard scan-threshold	**G5B“**
show nfpp ip-guard summary	**ÇG5Bß**

ÏGÄÈ -

16.78 nfpp nd-guard enable

AÇ0ÃÉ ND kÏš6Ñ
nfpp nd-guard enable

ÐÄÈ

–D	Ë¢Ä
-	-

Ï5,Õ5BÐ 0ÃÍG5B ND kÏÒÈ¢ÔÄ

Ëø yG5Bã

ÏÊÔ 0Ã¥ ND kÏÒb<ÔÄ

ÏG5B_Ð 5XLMLHFRQILJXUHUIDFH*
5XLMLHFRQILJSSQXDUGHQEOH

ÎÏGÇ

Ç	Ë¢Ä
nd-guard enable	**Ô** ND kÏš6Ñ
show nfpp nd-guard summary	**ÇG5Bß**

ÏGÄÈ -

16.79 nfpp nd-guard policy

0Ã5BF½XLÉÚ“Ä
nfpp nd-guard policy per-port {**ns-na** | **rs** | **ra-redirect**} *rate-limit-pps attack-threshold-pps*

–D	E Ä
ns-na	**F A Ë @**
rs	**C Ã A Ë**
ra-redirect	**C Ã A A A A A C p p q E f 8 q E f 8 H n u 2 v k 2 y A l A A A 8 8 s 8 u Q u A 2 F A A 8 u P H v q E f V 2 V 2**

mac-address	MAC

ÜÞ,ÕΘ5BÐ -

Ïê(Mã

ÜÞÐ -

ÜG5B_Ð _ 1ÐÏ¢X4²AuÇÄ

```
5XLMLHVKRXSSDUSXDUGKRVWVVWDWLVWLFV
VXFFHVVIDLOWRWDO
```

Ý 120 Ä¸¢È 100 Ä¸ÊÐh/È 20 ÄÐm/ÐÐÈK,Xs

Ý,ÈÐÐÈÅ

_ 2ÐÏÈÈemain-time(seconds) Ù-,XLh/ÊÈ

```
5XLMLHVKRXSSDUSXDUGKRVWV
,IFROXPQKRZLWPHDQKDUGZUHGRWLVRODWHXVHU
9/$LQVHUIFH,3DGGUHVV0DGGUHVVUHPDLQWLPHV
t
t
t
t
7RWDOKRVWV
```

ÏÎGÐ

Ç	È
clear nfpp arp-guard hosts	Ê

ÜGÄÊÐ -

16.81 show nfpp arp-guard scan

¦ß ARP Ê<

show nfpp arp-guard scan [**statistics** | [[**vlan** *vid*] [**interface** *interface-id*] [*ip-address*] [*mac-address*]]]

ÜÞAÊÐ

–D	È
statistics	ß ARP Ê<,XA¸5D
vid	Ê
interface-id	0Ä
ip-address	IP
mac-address	MAC

ÏÔ,Õ5BÐ -

ÏÐ (Mã

ÏÔÐ -

ÏG5B_Ð 5XLMLHVKRZSSDUSXDUGVFDQWDWLVWLFV
$3VFDQDEOHKDVUHFRUGV
ÃARP ²<EÝ 4 5A)Ä

5XLMLHVKRZSSDUSXDUGVFDQ
9/$LQWHUIDFH,3DGGUHVV0RGGUHVVWLPHVWDPS

t1$
t
t1$
t1$
7RWDOÖHFRUGV
timestamp A),X"Î# ARP ²XÊÈ2008-01-23 16:23:10 ></ü 2008 H 1 Ü 23
¹ 16 & 23 Ú 10 /¡Î# ARP ²Ä

5XLMLHVKRZSSDUSXDUGVFDQQODQQWHUIDFH*
9/$LQWHUIDFH,3DGGUHVV0RGGUHVVWLPHVWDPS

t1$
7RWDOÖHFRUGV

ÏÎGÐ

Ç	Ë.Ä
arp-guard scan-threshold	**G5B“**
nfpp arp-guard scan-threshold	**G5B²“**
clear nfpp arp-guard scan	**è** ARP ²<

ÏGÄè -

16.82 show nfpp arp-guard summary

¡GÏ5BÇÄ

show nfpp arp-guard summary

ÏÐÄè

–D	Ë.Ä
-	-

ÏÔ,Õ5BÐ -

(Mã

EÊÃ5B

5XLMLHVKRG SSDUSXDUGVXPPDU\
RUPDWRIFROXPQDWHOLPLWDQWWDFNKUHVKROGLVSHUVUFLSSHUVUFPDFSHUSRUWÅ
,QWHUIDFH6WDWXV,VRODWHSHULRG5DWHOLPLWWWDFNKUHVKROG6FDQKUHVKROG
OREDO(QEOH
L(QEOH
LLVDEOH

0D[LPXPFRXQRIIPRQWRUHGKRVWV
0RQWRUSHULRGÖ

Interface Global

Status

Rate-limit IP / MAC /
Attack-threshold “ - ”

Q	Ä
arp-guard attack-threshold	**G5**
arp-guard enable	ARP k6Ñ
arp-guard isolate-period	**G5**
arp-guard monitor-period	**G5**
arp-guard monitored-host-limit	**G5**
arp-guard rate-limit	**G5**
arp-guard scan-threshold	**G5**
nfpp arp-guard enable	ARP k6Ñ
nfpp arp-guard isolate-period	**G5**
nfpp arp-guard policy	**G5**
nfpp arp-guard scan-threshold	**G5**

-

16.83 show nfpp define hosts

Ä

show nfpp define hosts *name*h

statistics	**Ø¥4ÃuÇ**
vid	<.5%Ë
interface-id	0ÆÄ
ip-address	IP
mac-address	MAC
ipv6-address	IPv6

Ö,ÕÖ5BÐ (Mã

Ïð -

ÖÐÐ ÆDE> EÆÄ

ÜÖ5B_Ð

```
5XLMLHVKRWSSGHILQHKRVWV  WFSWDWLVWLFV
HILQHWFSÖ
VXFFHVVIDLOWRWDO
```

ÐÝ 120 ÄLh/È 100 Äh/ÐÈ0 Äh/ÐÄ

```
5XLMLHVKRWSSGHILQHKRVWVWFS
HILQHWFSÖ
,IFROXPQKRWLWPHDQKDUGUHGQWLVRODWHKRVW
9/$LQWHUIFH,3DGGUHVV0RGGUHVVUHPDLQLPHV


t
t
7RWDOKRVWV
```

ÎÜGÇ

(Mã

name ></,X7ĸ2O_

5XLMLHVKRQSSGHILQVXPPDUWFS
HILQWFSVXPPDU\
PDWFKHWSH[SURWRFRO[
0D[LPXPFRXQWRIPRQWRUHGKRVWV
0RQWRUSHULRGÖ
ÄRUPDWRIFROXPQDWHOLPLWDQSWWDFNWKUHVKROGLVSHUVUFLSSHUVUFPDFSHUSRUWÅ
,QWHUIDFH6WDWXV,VRODWHSHULRG5DWHOLPLWSWWDFNWKUHVKROG
OREDO(QEOH
(QEOH
LVDEOH

Interface	Global
Status	

Q	E.Ä
match	**7ĸkG,Ky[2O**
policy	**7ĸkH“**
isolate-period	**7ĸkb/Ê**
monitor-period	**7ĸk¢Ê**
monitored-host-limit	**7ĸkp**

-

16.85 show nfpp define trusted-host

¼Ê¼XÃ
show nfpp define trusted-host *name*

–D	E.Ä
name	*7ĸ2O_é*

-

(Mã

-

¼Ê5BÄ
5XLMLHVKRQSSGHILQWUXVWHGKRVWWFS

HILĘWFS
,3DGGUHVVPDVN

7RWDOÖHFRUGV

ÏĞĢ

Ą	Ł Ä
trusted-host	**G5Ø¼kĪ**

-

16.86 show nfpp dhcp-guard hosts

¹ĢÄ

show nfpp dhcp-guard hosts [**statistics** | [[**vlan** *vid*] [**interface** *interface-id*] [*mac-address*]]]

ĐAĝ

–D	Ł Ä
statistics	**ĢX4ŻAuĢ**
vid	<.5%Ë
interface-id	0áBtlÊEeĞ'dBF·vĢdXT·v7ãĝĝĢĢĢ-DGFĝGBA”ĝGNĝGG Hnß8b–Hn9ĝĢĢË

Ì
7RWDOÖRVWV

ÎÎGĢ

Ç	Ë Ä
clear nfpp dhcp-guard hosts	**È**

ÏGÄâ -

16.87 show nfpp dhcp-guard summary

¦G5BÇÄ
show nfpp dhcp-guard summary

ÐAâ

–D	Ë Ä
-	-

Ï,Õ5BÐ -

â (Mã

ÏÎ EËAÇG5BÇÄ

ÏG5B_Ð

```
5XLMLHVKRÇSSGKFSXDUGVXPPDU\
ÆRUPDWRIFROXPÇDWHOLPLWDÇWWDFNWKUHVKROGLVSHUVUFLSSHUVUFPDFSHUSRUWÅ
,ÇWHUIDFH6WDWXV,VRODWHSHULRG5DWHOLPLWÇWWDFNWKUHVKROG
ÈOREDO(ÇEOH
È(ÇEOH
È LVDEOH

0D[LPXPFRXÇVRIPRÇWRUHGKRVWV
0RÇWRUSHULRGÖ
```

Interface	Global
Status	
Rate-limit	IP / MAC /
Attack-threshold	“ - ”

ÎÎGĢ

Ç	Ë Ä
dhcp-guard attack-threshold	**G5Ë“**
dhcp-guard enable	**Ê** DHCP kÏ6Ñ
dhcp-guard isolate-period	**G5Ë/Ê**
dhcp-guard monitor-period	**G5Ç**

dhcp-guard monitored-host-limit	**G5**
dhcp-guard rate-limit	**G5**
nfpp dhcp-guard enable	**0** DHCP k6Ñ
nfpp dhcp-guard isolate-period	**G5**
nfpp dhcp-guard policy	**G5**

nfpp dhcpv6-guard policy	**G5B**

-

16.90 show nfpp icmp-guard hosts

show nfpp icmp-guard hosts [**statistics** | [[**vlan** *vid*] [**interface** *interface-id*] [*ip-address*]]]

–D	E
statistics	**X4Au**
vid	<.5%Ë
interface-id	0
ip-address	IP

-

(M

–D	Ë Ä
-	-

Ï,Õ5BÐ -

Ï (Mã

Ï Ë Ë Ä Ç5BÇÄ

Ï5B_Ð

```
5XLMLHVKRZSSLFPSXDUGVXPPDU\
ÄRUPDWRIFROXPQDWHOLPLWDQWWDFNWKUHVKROGLVSHUVUFLSSHUVUFPDFSHUSRUWÅ
,QWHUIDFH6WDWXV,VRODWHPHULRG5DWHOLPLWWWDFNWKUHVKROG
ORREDO(QEOH
L(QEOH
LLVDEOH

0D[LPXPFRXQWRIPRQWRUHGKRVWV
0RQWRUSHULRGÖ
```

	Interface	Global			
	Status				
	Rate-limit	IP	/	MAC	/
	Attack-threshold		“ - ”		

ÏÎG Ç120 Td<058.94 358.52 mh5380057857 Tc 7 c 7Tc 7Tc 7Tc 7Tc 02 3Td0.902 g12519A345CD1B00640071>]TJ TT0 1

ËÐÀð	–D	Ë.Ä
	-	-

Ëõ,Ö5BÐ -

Ëð (Mã

ËõÐ -

ËG5B_Ð ¡Ð5BÄ

5XLMLHVKRQSLFPSXDUGWUXVWHGKRVW
,3DGGUHVVPDVN

7RWDOÖHFRUGV

ÏGÐ	Ç	Ë.Ä

5XLMLHVKRWSSLSXDUGKRVWV ,IFROXPQKRZLWPHDQKDUGZUHGQWLVRODWHKRVW 9/$1LQWHUIDFH,3DGGUHVV5HDVRQHPDLQLPHV t37& t6& 7RWDOKRVWV			

	" Reason "	" ATTACK "	IP
	" SCAN "		

	Status
	Rate-limit IP / MAC /
	Attack-threshold “ - ”

ÎĈĢę

Ç	ĖÄ
ip-guard attack-threshold	**G5ËË“**
ip-guard enable	**ê** IP Lë86Ñ
ip-guard isolate-period	**G5ËË/Ê**
ip-guard monitor-period	**G5Ëę̈Ê**
ip-guard monitored-host-limit	**G5Ëę̂D**
ip-guard rate-limit	**G5Ë“**
nfpp ip-guard enable	**0Ñ** IP Lë86Ñ
nfpp ip-guard isolate-period	**G5ËBl(Ê**
nfpp ip-guard policy	**G5ËBę̈“**

ĠÄâĕ -

16.95 show nfpp ip-guard trusted-host

¹ßĶXĄÃ

show nfpp ip-guard trusted-host

ĐAâĕ

–D	ĖÄ
-	-

ĥ,Õ5BĐ -

ĕę (Mã

ĠĐ -

ĠĜ5B_Đ ¹Ą5BÄ

```
5XLMLHVKRQSSLSXDUGWUXVWHGKRVW
,3DGGUHVVPDVN


7RWDOÖHFRUGV
```

ÎĈĢę

Ç	ĖÄ
ip-guard trusted-host	**G5ßXĄÃ**

```
$3      &
$       &
```

Protocol ®
ARPÄ ARP kÄ
IPÄ IP LÅ
ICMPÄ ICMP kÄ
DHCPÄ DHCP kÄ
DHCPv6Ä DHCPv6 kÄ
NS-NAÄ ND kÏXFÆÉ@
RSÄ ND kÏXCÃ<AÉ
RA-REDIRECTÄ ND kÏXCÃ<@nå[Å

Reason ></sÉ 5 /Ð
DoS ></"#áï
ISOLATED ></ïÌ»ê@h/•
ISOLATE_FAILED ></Lh/ïÐù
SCAN ></"Æ
PORT_ATTACKED ></0ÃÏ•

ÏÎGÐ		
	Ç	ÉÄ
	clear nfpp log	**N** NFPP ¼¢

ÜGÄê -

16.97 show nfpp nd-guard summary

¡G5BÇÄ
show nfpp nd-guard summary

ÐAê		
	–D	ÉÄ
	-	-

Ü,Õ5BÐ (Mã

Ü -

Üõ EÉÆÇ5BÇÄ

Ü5B_Ð
```
5XLMLHVKRQSQXDUGVXPPDU\
RUPDWRIFROXPQDWHOLPLWDQWWDFNUHVKROGLV1655(;5(&Å
QWHUIDFH6WDWXV5DWHOLPLWWDFNUHVKROG
OREDO(QEOH
```

ŧ(QEOH
ŧLVDEOH

Interface	Global
Status	
Rate-limit	/ / / / Attack-threshold " - "
	" -/5/30 " G 0/2 / 5 / 30

ÏĈĢĐ

Ç	ŧÄ
nd-guard attack-threshold	**G5Ëê“**
nd-guard enable	**ê** ND kŝ6Ñ
nd-guard rate-limit	**G5ê“**
nfpp nd-guard enable	**0ê** ND kŝ6Ñ
nfpp nd-guard policy	**G5Bêê“**

ËGÄê -

16.98 trusted-host

G5Bâ¾XÃ
trusted-host {*mac mac_mask* | *ip mask* | *IPv6/prefixlen*}
no trusted-host {**all |** *ip mask* | *IPv6/prefixlen* }

ÐAê

–D	ŧÄ
mac	mac
mac_mask	mac ,X}-Õ
ip	IP
mask	IP ,X}-Õ
IPv6/prefixlen	IPv6 }-ÕSz
all	` **no ÔêêG5B**

Ëƃ,Õ5BÐ 5,ÕÝ"5BÏÃ

ê NFPP 7ê2O_G5Bã

ËƑ Vp1u)Ïê> ,¥ÈÁ></êEAÇ5BÄê
T CPU ,X ICMP y[ÝAŒE CPUê,XLƑÄ:ÝêEG5B}-ÊÝÕ

17

17.1 security-mode compatible

5,ßx6]<s6Ñ RGOS Pß,ÈÊEÇ **security-mode compatible A5B**
PßÇA5B RGOS M2Pß,È**no ÇA5B**
security-mode compatible
no security-mode compatible

Ï-DAß	–D	ÊÄ
	-	-

ï5,Õ5BÐ 5,Õ5Bßx6]<s6Ñ RGOS Pß,

ïÇ <G5Bã

ïSÐ

ïG5B_Ð _ 1Ö5B]<s6Ñ2 RGOS Pß,Ö

,ÇOÇ

-ACL&QOS

ACL&QOS Q_5ÀGYBVÖ

1. ACL
2. IP QOS

1 ACL

1.1

qÊÊÊÊÊÊÊÊ

ÊÊú	ÿ
id	A“KÂ<DÊ8È IP ßÙ ACLÖ 1-99È 1300-1999 IP =) ACLÖ 100-199È 2000-2699 MAC =) ACLÖ00–799 ßÙ) ACLÖ700–2899
name	ACL á
sn	ACL ><NMcË ÊÖ(A5B{}
start-sn	cËKŸ
inc-sn	cËG£
deny	VpGÈÊA“KÂ
permit	VpGÈÊÆKÂ
port	Á4Ê IPv6 ,XA¹Ø‰ ipv6È icmpÈcp Èdp Ð 0-255Ê IPv4Ê eigrpÈ greÈ ipinipÈ igmpÈ nosÈ ospfÈ icmpÈ udpÈ tcpÈ ip ,X ßÑ< IP Á,X 0-255 4ÊGPÁV icmp/tcp/udp 1) (Ê> AÈ
interface idx	Eg9G¦Xy·
src	y[ÊÁ
src-wildcard	ÊÑ0ÃÁ Z 0.255.0.32
src-ipv6-pfix	Ê IPv6 5Á4
dst-ipv6-pfix	,ÂX IPv6 5Á4
pfix-len	PËK}-Õ
src-ipv6-addr	Ê IPv6
dst-ipv6-addr	,ÂX IPv6
dscp	Á-Ø, -ØÈ 8È 0-63

precedence	y[,X¼{Ø-7 Å
range	y[,X0ÃÈ
time-range tm-rng-name	y[E$XÊÈÄ tm-rng-name
tos	y[,Xá2O_Ø-15Å
cos	y[cos (0-7)
cos inner cos	y[YF¼ tag ,X cos
icmp-type	ICMP y[,XÈ2O_Ø-255 Å
icmp-code	ICMP y[,XÈ2O_-Õ-255 Å
icmp-message	ICMP y[,XÈ2O_áÄ
operator port[port]	Operator 0Ñ-ÈÈq- 1bÈt- 0ÈÈeq- 1bÈange- 8Å port 0ÃL0ÃÈX0ÈÔÃ
src-mac-addr	,X(=)Ú
dst-mac-addr	,X,X(=)Ú
VID vid	,X vlan id
VID inner vid	YF¼ tag ,X vid
ethernet-type	2O_Ãg9 0x D
match-all tcpf	G! tcp flag ,XÝ
text	
in	;Xy[E> E$
out	EgÎXy[E> E$
{rule mask offset}+	rule AE,XÈmask AE,X}-Õ offset “+”

y[VÖ

AA AA AA AA AA AA BB BB BB BB BB BB CC CC DD DD

DD DD EE FF GG HH HH HH II II JJ KK LL LL MM MM

NN NN OO PP QQ QQ RR RR RR RR SS SS SS SS TT TT

UU UU VV VV VV VV WW WW WW WW XY ZZ aa aa bb bb

<VÖ

+	ÿ

F	SSAP(ßéA“KÂ)+‰	19	T	TCP ß0Ã	46

TCP

destination-mac-address | **any**} [**precedence** *precedence*] [**tos** *tos*] [**fragment**] [**range** *lower upper*] [**time-range** *time-range-name*]

ôGPJ#,X Expert =)A“KÊ<Ö

Internet Control Message Protocol (ICMP)Ö

access-list *id* {**deny** | **permit**} **icmp** [**VID** [*out*][**inner** *in*]] {*source source-wildcard* | **host** *source* | **any**} {**host** *source-mac-address* | **any** } {*destination destination-wildcard* | **host** *destination* | **any**} {**host** *destination-mac-address* | **any**} [*icmp-type*] [[*icmp-type* [*icmp-code*]] | [*icmp-message*]] [**precedence** *precedence*] [**tos** *tos*] [**fragment**] [**time-range** *time-range-name*]

Transmission Control Protocol (TCP)Ö

access-list *id* {**deny** | **permit**} **tcp** [**VID** [*out*][**inner** *in*]]{*source source-wildcard* | **host** *Source* | **any**} {**host** *source-mac-address* | **any** } [**operator** port [*port*]] {*destination destination-wildcard* | **host** *destination* | **any**} {**host** *destination-mac-address* | **any**} [**operator port** [*port*]] [**precedence** *precedence*] [**tos** *tos*] [**fragment**] [**range** *lower upper*] [**time-range** *time-range-name*] [**match-all** *tcp-flag*]

User Datagram Protocol (UDP)Ö

access-list *id* {**deny** | **permit**} **udp**[**VID** [*out*][**inner** *in*]] {*source* | *source –wildcard* | **host** *source* | **any**} {**host** *source-mac-address* | **any** } [**operator port** [*port*]] {*destination destination-wildcard* | **host** *destination* | **any**}{**host** *destination-mac-address* | **any**} [**operator**

*port*Tf -0.0019 Tc 5.287 025

tos	**y[2O_**
tos	**y[2O Ä-15Å**
icmp-type	ICMP y[,X 2O_ Ä-255 Å
icmp-code	ICMP y[,X 2O_ -Ä-255 Å
icmp-message	ICMP y[,X 2O_ Ä
operator	00Ä-eq- 1bÈ gt-eq- 4be nge- 8Å
port [*port*]	0 nge
host *source-mac-address*	,X(=)Ä
host *destination-mac-address*	,X(=)Ä
VID *vid*	,X vid E> G!
ethernet-type	2O_
match-all	G! *tcp flag*
tcp-flag	tcp flag
text	

ACL

<G5B

ZS A“K <DBE> E N OEE Q¸ **access-list n**

IP A“K < Ä-99È 1300-1999 E> {Ä

IP A“K <Ä00-199 È 2000-2699 ,X E> {Ä

MAC =)A“K <Ä00-799 ,X MAC 2O_E> G! Expert =)A“K <Ä700-2899 6 ,X4 VLAN ID E> GE

precedence *precedence*/**tos** *tos*/**fragments**/**range** *lower upper*/**time-range** *time-range-name*Ä

TCP Flag

urg

ack

psh

rst

syn

fin

critical

flash

flash-override

immediate

internet

network

priority

routine

á2O_åXÖ

max-reliability

max-throughput

min-delay

min-monetary-cost

normal

ICMP y[Æ2O_åXÖ

administratively-prohibited

dod-host-prohibited

dod-net-prohibited

echo

echo-reply

fragment-time-exceeded

general-parameter-problem

host-isolated

host-precedence-unreachable

host-redirect

host-tos-redirect

host-tos-unreachable

host-unknown

host-unreachable

information-reply

information-request

mask-reply

mask-request

mobile-redirect

net-redirect

net-tos-redirect

net-tos-unreachable

net-unreachable

network-unknown

no-room-for-option

option-missing

packet-too-big

parameter-problem

port-unreachable

precedence-unreachable

protocol-unreachable

redirect

router-advertisement

router-solicitation

source-quench

source-route-failed

time-exceeded

timestamp-reply

timestamp-request

ttl-exceeded

unreachable

M6 TCP 0ÆCP ÃÕ0ÆÃÕ0K¦X0Ã

bgp

chargen

cmd

daytime

discard

domain

echo

exec

finger

ftp

ftp-data

gopher

hostname

ident

irc

klogin

kshell

login

nntp

pim-auto-rp

pop2

pop3

smtp

sunrpc

syslog

tacacs

talk

telnet

time

uucp

whois

www

M6 UDP 0ÆDP ÃÕ0ÆÃÕK¦X0Õ

biff

bootpc

bootps

discard

dnsix

domain

echo

isakmp

mobile-ip

nameserver

netbios-dgm

netbios-ns

netbios-ss

ntp

pim-auto-rp

rip

snmp

snmptrap

sunrpc

syslog

tacacs

talk

tftp

time

who

xdmcp

p¾2O_ Ethernet-type VÖ

aarp

arp

SHUPLWDQDQDQDQ\

ÏĈGQÞ

Q¸	Ë Ä
show access-lists	**Ý Ê**
mac access-group	**ÿ h ü** MAC =)A“KÊ<

ĞGÄÊ -

1.3 deny

+ÊX(deny) ,X5ÊHy[EÊÄ

1) IP ÊÍ“KÊ<

[*sn*] **deny** {*source source-wildcard* | **host** *source* | **any| interface** *idx* }[**time-range** *tm-range-name*]

2) IP =)A“KÊ<

[*sn*] **deny protocol** *source source-wildcard destination destination-wildcard* [**precedence** *precedence*] [**tos** *tos*] [**fragment**] [**range** *lower upper*] [**time-range** *time-range-name*]
ÔGÞØÆ,X IP =)A“KÊë<Ö

Internet Control Message Protocol (ICMP)

[*sn*] **deny icmp** {*source source-wildcard* | **host** *source* | **any**} {*destination destination-wildcard* | **host** *destination* | **any**} [*icmp-type*] [[*icmp-type* [*icmp-code*]] | [*icmp-message*]] [**precedence** *precedence*] [**tos** *tos*] [**fragment**] [**time-range** *time-range-name*]

Transmission Control Protocol (TCP)

[*sn*] **deny tcp** {*source source-wildcard* | **host** *Source* | **any**} [*operator* **port** [*port*]] {*destination destination-wildcard* | **host** *destination* | **any**} [*operator* **port**

E¥Ã¿Ø%O_ ethernet-type ê cos +Ê‰

[*sn*] **deny** {[*ethernet-type*}[**cos** [*out*] [**inner** *in*]]} [[**VID** [*out*][**inner** *in*]]] {*source source-wildcard* | **host** *source* | **any**} {**host** *source-mac-address* | **any** } {*destination destination-wildcard* | **host** *destination* | **any**} {**host** *destination-mac-address* | **any**} [**time-range** *time-range-name*]

E¾¾¸ protocol +Ê‰

[*sn*] **deny protocol** [[**VID** [*out*][**inner** *in*]]] {*source source-wildcard* | **host** *source* | **any**} {**host** *source-mac-address* | **any** } {*destinationdestination-wildcard* | **host** *destination* | **any**} {**host** *destination-mac-address* | **any**} [**precedence** *precedence*] [**tos** *tos*] [**fragment**] [**range** *lower upper*] [**time-range** *time-range-name*]

ôGPØÆ‚X expert =)A“KÂ<Ö

Internet Control Message Protocol (ICMP)

[*sn*] **deny icmp** [[**VID** [*out*][**inner** *in*]]] {*source source-wildcard* | **host** *source* | **any**} {**host** *source-mac-address* | **any**} {*destination destination-wildcard* | **host** *destination* | **any**} {**host** *destination-mac-address* | **any**} [*icmp-type*] [[*icmp-type* [*icmp-code*]] | [*icmp-message*]] [**precedence** *precedence*] [**tos** *tos*] [**fragment**] [**time-range** *time-range-name*]

Transmission Control Protocol (TCP)

[*sn*] **deny tcp** [[**VID** [*out*][**inner** *in*]]]{*source source-wildcard* | **host** *Source* | **any**} {**host** *source-mac-address* | **any** } [*operator* **port** [*port*]] {*destination destination-wildcard* | **host** *destination* | **any**} {**host** *destination-mac-address* | **any**} [*operator* **port** [*port*]] [**precedence** *precedence*] [**tos** *tos*] [**fragment**] [**range** *lower upper*] [**time-range** *time-range-name*] [**match-all** *tcp-flag*]

User Datagram Protocol (UDP)

[*sn*] **deny udp [[VID** [*out*][**inner** *in*]]]{*source source –wildcard* | **host** *source* | **any**} {**host** *source-mac-address* | **any** } [*operator* **port** [*port*]] {*destination destination-wildcard* | **host** *destination* | **any**}{**host** *destination-mac-address* | **any**} [*operator* **port** [*port*]] [**precedence** *precedence*] [**tos** *tos*] [**fragment**] [**range** *lower upper*] [**time-range** *time-range-name*]

Address Resolution Protocol (ARP)

[*sn*] **deny arp** {**vid** *vlan-id*}[*source-mac-address source-wildcard* **|host** *source-mac-address* | **any**] [**host** *destination –mac-address* | **any**] {*sender-ip sender-ip–wildcard* | **host** *sender-ip* | **any**} {*sender-mac sender-mac-wildcard* | **host** *sender-mac* | **any**} {*target-ip target-ip–wildcard* | **host** *target-ip* | **any**}

5) IPV6 =)A“KÂ<

[*sn*] **deny protocol**{*source-ipv6-prefix*/*prefix-length* | **any** | **host** *source-ipv6-address* } {*destination-ipv6-prefix / prefix-length* | **any**| *hostdestination-ipv6-address*} [**dscp** *dscp*] [**flow-label** *flow-label*] [**fragment**] [**range** *lower upper*] [**time-range** *time-range-name*]

ôGPØÆ‚X IPV6 =)A“K{ê<Ö

Internet Control Message Protocol (ICMP)

[*sn*]**deny icmp** {*source-ipv6-prefix / prefix-length* | *any source-ipv6-address* | **host**} {*destination-ipv6-prefix / prefix-length*| **host** *destination-ipv6-address* | **any**} [*icmp-type*] [[*icmp-type* [*icmp-code*]] | [*icmp-message*]] [**dscp** *dscp*] [**flow-label** *flow-label*] [**fragment**] [**time-range** *time-range-name*]

Transmission Control Protocol (TCP)

[*sn*] **deny tcp** {*source-ipv6-prefix / prefix-length* | **host***source-ipv6-address* | **any**}[*operator* **port**[*port*]] {*destination-ipv6-prefix /prefix-length* | **host** *destination-ipv6-address* | **any**} [*operator* **port** [*port*]] [**dscp** *dscp*] [**flow-label** *flow-label*] [**fragment**] [**range** *lower upper*] [**time-range** *time-range-name*] [**match-all** *tcp-flag*]

User Datagram Protocol (UDP)

[sn] **deny udp** {*source-ipv6-prefix/prefix-length* | **host** *source-ipv6-address* | **any**} [*operator* **port** [*port*]] {*destination-ipv6-prefix /prefix-length* | **host** *destination-ipv6-address* | **any**}[*operator* **port** [*port*]] [**dscp** *dscp*] [**flow-label** *flow-label*] [**fragment**] [**range** *lower upper*] [**time-range** *time-range-name*]

Ï–DAê

–D	Ë
Sn	ACL ><NMcË
source-ipv6-prefix	IPv6 5
destination-ipv6-prefix	IPv6 5
prefix-length	PE
source-ipv6-address	IPv6
destination-ipv6-address	IPv6
dscp	
dscp	8 0-63.
flow-label	
flow-label	0-1048575
protocol	IPV6 ,XA IPV6 | icmp | tcp | udp 0-255>
time-range	
time-range-name	y[E

ï5,Õ5BÐ ü><NMÄ

ÜÇ ACL G5BÐ

Ï Ü ACL G5BÐ5B ACL ,XE <NMÄ

G5B_Ð _ Expert Extended ACL ACL IP 192.168.4.12 J MAC 001300498272 ,XÝ TCP y[Ä

```
5XLMLHFRQILJH[SHUWDFFHVVOLVWH[WHQGHG
5XLMLHFRQILJH[SQDFOGHQWFSKRVW
KRVWDQDQ\
5XLMLHFRQILJH[SQDFOSHUPLWDQDQDQDQ\
5XLMLHFRQILJH[SQDFOVKRZDFFHVVOLVWV
H[SHUWDFFHVVOLVWH[WHQGHG
GHQWFSKRVWKRVWDQDQ\
SHUPLWDQDQDQDQ\
5XLMLHFRQILJH[SQDFO
```

_ 2 IP =) ACL S IP 192.168.4.12 ,X TCP 0Ã 100 ,X á gigabitethernet 1/1

5XLMLHFRQILJLSDFFHVVOLVWH[WHQGHGLSH[WDFO
5XLMLHFRQILJH[WQDFOGHQWFSKRVWHTDQ\

mac access-group	MAC =) ACL ,Xyhŭ
ip access-list	IP ACL ,Xn
mac access-list	MAC =) ACL ,Xn
expert access-list	ß ACL ,Xn
ipv6 access-list	IPV6 =) ACL n
permit	**ÄÆnQ¸**

ĞÄß -

1.4 expert access-group

ßh,X EXPERT ACL hŭ,XyÄÆQ¸X no EÍMMhÄ

expert access-group {*id* | *name*} {**in** | **out**}

no expert access-group {*id* | *name*} {**in** | **out**}

ÐAß

–D	ÆÄ
id	Expert A“KÅ<,X4Æ700-2899 Å
name	Expert A“KÅ<,Xá
in	É9Aу¸Xy[E> E$
out	ÁуEgÎXy[E> E$

Ъ,Õ5BÐ yŭhŕŭExpert ACL Ä

ÒÇß yG5Bã

ÐÐ ŭ,X ACL hŭAуßý¸XEg9EgÎDBÆ> {ÄŭX

	+<ÁÆ¢E¯9YF5¼Å
reflect	¶¡¼ ACL

Ï¿,Õ5BÐ yÙÍ¶ÙACL Ä

ÙQ¸Ð yG5Bã

ÙÉÐ Sº **ip access-group Q¸ÚÁÊÙyÈ8ÚÙ**

ÙG5B_Ð ¶M6,X/_ü fastEthernet0/0 ÞÆA“KÊ< 120 É¯9,Xy[E> E¸Ð

```
5XLMLHFRQILJLQWHUIDFHIDVW(WKHUQHW
5XLMLHFRQILJLILSDFFHVVJURXSLQ
```

ÏÎGQ¸Ð

Q¸	ÆÄ
access-list	**nAÊ**
show access-lists	**¸ÁÊ**

ÙGÄÈð -

1.7 ip access-list

AÐQ¸Ñ IP ACL ê) IP ACLÈÆ9AÐG5BÈÚÆQ¸X no E¶M8A¹ ACLÄ

ip access-list {**extended** | **standard**} {*id* | *name*}

no ip access-list {**extended** | **standard**} {*id* | *name*}

ÐÄÈð

–D	ÆÄ
id	IP A“KÊ<,X4Ê-99È300-1999 Ê)È00-199 È000-2699 Å
name	IP A“KÊ<,Xá

Ï¿,Õ5BÐ ù¸Ý ACL

ÙQ¸Ð <G5Bã

ÙÉÐ ¸Ñ ACL G5Bã)G5Bã¸<ÈÊã ACL ,XA5BÈ43Ê× **deny ` permit**

Q¸ÊÚÁÊù **show access-lists Q¸** ACL A5BÄ

ÙG5B_Ð _ 1Ñ ACLÖ

```
5XLMLHFRQILJLSDFFHVVOLVWVWDQGDUGVWGDFO
5XLMLHFRQILJVWGQDFOVKRZDFFHVVOLVWV
LSDFFHVVOLVWVWDQGDUGVWGDFO
5XLMLHFRQILJVWGQDFO
```

_ 2 Ñ) ACLÖ

```
5XLMLHFRQILJLSDFFHVVOLVWH[WHQGHG
5XLMLHFRQILJH[WQDFOVKRZDFFHVVOLVWV
```

LSDFFHVVOLVWH[WHQGHG

ÏĬGQÐ

1.9 ipv6 access-list

AŒQÎ IPV6 =) ACL ÐÈ9AG5BÐÐ¼Q¸X no E¼MM08A¹ ACL

ipv6 access-list *name*

no ipv6 access-list *name*

Ï-DAÐ	–D	Ð£Ä ipv6 access-list

no mac access-group {*id* | *name*} {**in** | **out**}

Ï-DAÈ

–D	Ë.Ä
id	MAC A“KÂ<,X4È00-799 Å
name	MAC A“KÂ<,Xá

in }

in

B8580745BB[602 g1194 723.32 41915.1 ref1194 691.58 0.48 75{

PDFDFFHVVOLVWH[WHQGHGPDFDFO

_ 2Õ MAC =) ACLÖ

5XLMLHFRQILJPDFDFFHVVOLVWH[WHQGHG
5XLMLHFRQILJPDFQDFOVKRZDFFHVVOLVWV
PDFDFFHVVOLVWH[WHQGHG

ÏÎGQÞ

Q¸	Ł Ä
show access-lists	ß mac =)2OA“KÂ<

ĠÄÂ

-

1.14 no sn

ô8 ACL ,Xþ<NM

no *sn*

Ï-DAÂ

–D	Ł Ä
sn	ACL ,Xþ<NM,XcË

Ď,Õ5BÐ

-

ĎÇÞ

ACL G5B

ĎÞ

ü ACL G5B8 ACL ><NM

ĠĎ5B_Ð

5XLMLHFRQILJLSYDFFHVVOLVWH[WHQGHGYDFO
5XLMLHFRQILJLSYQDFOSHUPLWLSYKRVWDQ\
5XLMLHFRQILJLSYQDFOGHQLSYKRVWDQDQ\
5XLMLHFRQILJLSYQDFOVKRZDFFHVVOLVWV
LSYDFFHVVOLVWH[WHQGHGYDFO
SHUPLWLSYKRVWDQ\
GHQLSYDQDQ\
5XLMLHFRQILJLSYQDFOQR
5XLMLHFRQILJLSYQDFOVKRZDFFHVVOLVWV
LSYDFFHVVOLVWH[WHQGHGYDFO
SHUPLWLSYKRVWDQ\
5XLMLHFRQILJLSYQDFO

ÏÎGQÞ

Q¸	Ł Ä
show access-lists	
ip access-list	ip ACL ,Xn
ipv6 access-list	IPV6 =) ACL n
deny	ACL ><NM

destination-mac-address | **any**} [**precedence** *precedence*] [**tos** *tos*] [**fragment**] [**range** *lower upper*] [**time-range** *time-range-name*]

0ÔGP/#A,X Expert =)A“KÂ<Ö

Internet Control Message Protocol (ICMP)

[*sn*] **permit icmp** [**VID** [*out*][**inner** *in*]] {*source source-wildcard* | **host** *source* | **any**} {**host** *source-mac-address* | **any** } {*destination destination-wildcard* | **host** *destination* | **any**} {**host** *destination-mac-address* | **any**}[*icmp-type*] [[*icmp-type* [*icmp-code*]] | [*icmp-message*]] [**precedence** *precedence*] [**tos** *tos*] [**fragment**] [**time-range** *time-range-name*]

Transmission Control Protocol (TCP)

[*sn*] **permit tcp** [**VID** [*out*][**inner** *in*]]{*source source-wildcard* | **host** *Source* | **any**} {**host** *source-mac-address* | **any** } [*operator* **port** [*port*]] {*destination destination-wildcard* | **host** *destination* | **any**} {**host** *destination-mac-address* | **any**} [*operator* **port** [*port*]] [**precedence** *precedence*] [**tos** *tos*] [**fragment**] [**range** *lower upper*] [**time-range** *time-range-name*] [**match-all**

gramd[(ontro)-ProtoUDP0 Td(TCP)

[ ] [**VID** *f r*]a[*g m e n t in* |

perator **p o r t** [*port*]] [**precedence** *prec*r*edence*] [**tos** *tos* **y**

per] [**time-range** *time-range-name*

Ï-DAÐ	–D	Ł.Ä
	-	-

Ï5,Õ5BÐ ü}Ý><NM

ÜQ Ð ACL G5BÐ

ÜSÐ ü ACL G5BÐG5B ACL ,XAÐÊ<NM

ÜG5B_Ð _ 1ÐV)Ð Expert Extended ACL ÆÊ ACL AÐE IP 192.168.4.12 JÐ MAC 001300498272 ,XÝ TCP y[Ä

```
5XLMLHFRQILJH[SHUWDFFHVVOLVWH[WHQGHGH[SDFO
5XLMLHFRQILJH[SQDFOSHUPLWWFSKRVWKRVWDQDQ\
5XLMLHFRQILJH[SQDFOGHQDQDQDQDQ\
5XLMLHFRQILJH[SQDFOVKRZDFFHVVOLVWV
H[SHUWDFFHVVOLVWH[WHQGHGH[SDFO
SHUPLWWFSKRVWKRVWDQDQ\
GHQDQDQDQDQ\
5XLMLHFRQILJH[SQDFO
```

_ 2ÐV6 IP =) ACL SÐ_ÊXÐÆ IP 192.168.4.12 ,XÐu TCP 0Ã 100 ,X áÈÐý· gigabitethernet 1/1Ð5BÐ

```
5XLMLHFRQILJLSDFFHVVOLVWH[WHQGHG
5XLMLHFRQILJH[WQDFOSHUPLWWFSKRVWHTDQ\
5XLMLHFRQILJH[WQDFOVKRZDFFHVVOLVWV
LSDFFHVVOLVWH[WHQGHG
SHUPLWWFSKRVWHTDQ\
5XLMLHFRQILJH[WQDFOH[LW
5XLMLHFRQILJLQWHUIDFHJLJDELWHWKHUQHW
5XLMLHFRQILJLILSDFFHVVJURXSLQ
5XLMLHFRQILJLI
```

_ 3ÐV6 MAC =) ACL SÐ_ÊXÐÆ MAC 0013.0049.8272 ,XÐÆÊÕO 100

OOT

ÏQþÐ yG5Bã

ÏSfÐ G5By]<EF'

ÏG5B_Ð 5XLMLHFRQILJLIVHFXULWDFFHVVJURXS

ÏÎGQÞÐ

Q¸	EÄ
show secu-acl	**þB**

ÏGÄð -

1.17 security global access-group

G5B<]<EF'

security global access-group {*id*|*name*}

no security global access-group

Ï-DAð

–D	EÄ
id	ACL id
name	ACL á

Ï5,Õ5BÐ -

ÏQþÐ <G5Bã

ÏSfÐ G5B<]<EF'

ÏG5B_Ð 5XLMLHFRQILJVHFXULWJOREDODFFHVVJURXS

ÏÎGQÞÐ

Q¸	EÄ
show secu-acl	**þB**

ÏGÄð -

1.18 security uplink enable

G5By]<EF',X_ê

security uplink enable

no security uplink enable

Ï-DAð

–D	EÄ
-	-

ï5,Õ5BÐ -

ÏQÇÐ yG5Bã

ÏSÐ G5B]<EF¦X_ê·

ÏG5B_Ð 5XLMLHFRQILJLIVHFXULWXSOLQNHQDEOH

ÏÎGQÇÐ

Q¸	Ë.Ä
show secu-acl	**ÍÆB**

ÏGÄÐð -

1.19 show access-group

/yÐ¼¸X ACL G5B

show access-group [**interface** *interface*]

Ï-DAÐð

–D	Ë.Ä
interface	ûÍ¸Xy·

ï5,Õ5BÐ -

ÏQÇÐ (Mã

ÏSÐ /yÞ¦X ACLÐÑ<Fy¼Þ¦X ACL

ÏG5B_Ð

```
5XLMLHVKRZDFFHVVJURXS
LSDFFHVVOLVWVWDQGDUGLSVWG
$SOLHG2QLQWHUIDFHtJDELW(WKHUQHW
LSDFFHVVOLVWVWDQGDUGLSVWG
$SOLHG2QLQWHUIDFHtJDELW(WKHUQHW
LSDFFHVVOLVWH[WHQGHG
$SOLHG2QLQWHUIDFHtJDELW(WKHUQHW
LSDFFHVVOLVWH[WHQGHG
$SOLHG2QLQWHUIDFHtJDELW(WKHUQHW
```

ÏÎGQÇÐ

Q¸	Ë.Ä
ip access-group	**Ú** ip A“KÂ<hÙy·
mac access-group	**Ú** mac A“KÂ<hÙy·
expert access-group	**Ú** expert A“KÂ<hÙy·
ipv6 traffic-filter	**Ú** ipv6 A“KÂ<hÙy·

ÏGÄÐ -

1.20 show access-lists

/Ý ACL G5BÐ¼,X ACL

interface	û,Xy·

ï5,Õ5BÐ -

ÜQþÐ (Mã

ÜSfÐ /yG5B,X Expert ACLÈtûyßÝG6(Expert ACLÄ

ÜG5B_Ð

```
5XLMLHVKRZH[SHUWDFFHVVJURXSLQWHUIDFHJLJDELWHWKHUQHW
H[SHUWDFFHVVJURXSHHLQ
$SOLHG2QLQWHUIDFHtJDELW(WKHUQHW
```

ÏÎGQÞÐ

Q¸	Ä
expert access-list	Expert =) ACL n

ÜGÄð -

1.22 show ip access-group

/yG5B,X IP ACL

show ip access-group[**interface** *interface*]

Ï-DAð

–D	Ä
interface	û,Xy·

ï5,Õ5BÐ -

ÜQþÐ (Mã

ÜSfÐ /yG5B,X IP ACLÈtûyßÝG6(,X IP ACLÄ

ÜG5B_Ð

```
5XLMLHVKRZLSDFFHVVJURXSLQWHUIDFHJLJDELWHWKHUQHW
LSDFFHVVJURXSDDDLQ
$SOLHG2QLQWHUIDFHtJDELW(WKHUQHW
```

1.23 show ipv6 traffic-filter

/yG5B,X IPV6 A“KâÊ<

show ipv6 traffic-filter [**interface** *interface*]

ï-DAèð

–D	ÆÄ
interface	û,Xy·

ï5,Õ5BÐ -

ÜQ¸Ð (Mã

ïSÐ /yG6(,X IPv6 ACLÈtûyÐÝ;X IPv6 ACLÄ

ÜG5B_Ð

```
5XLMLHVKRZLSYWUDIILFILOWHULQWHUIDFHJLJDELWHWKHUQHW
LSYWUDIILFILOWHUYLQ
$SSOLHG2QLQWHUIDFHtJDELW(WKHUQHW
```

ÏÎGQÐ

Q¸	ÆÄ
ipv6 access-list	IPV6 2O_ ACL n

ÜGÄèð -

1.24 show mac access-group

/0Õ5B,X MAC A“KâÊ<

show mac access-group[**interface** *interface*]

ï-DAèð

–D	ÆÄ
interface	û,Xy·

ï5,Õ5BÐ -

ÜQ¸Ð (Mã

ïSÐ /yG6(,X MAC ACLÈtûyÐÝG6(,X MAC ACLÄ

ÜG5B_Ð

```
5XLMLHVKRZPDFDFFHVVJURXSLQWHUIDFHJLJDELWHWKHUQHW
PDFDFFHVVJURXSPPLQ
$SSOLHG2QLQWHUIDFHtJDELW(WKHUQHW
```

ÏÎGQÐ

Q¸	ÆÄ
mac access-list	MAC =) ACL n

ÏGÄê -

1.25 svi router-acls enable

Ô svi router-acls s6Ñ SVI ACL ÉÊ»CÃyÞQ¸X no EÝMG KÁs6Ñ

svi router-acls enable

[**no**] **svi router-acls enable**

Ï-DAê

–D	ÉÄ
no	svi router-acls s6Ñ

Ï¸Õ5BÐ SVI Router ACLs TAxGKÁ

ÏQþ <G5Bã

ÏSÐ -

ÏG5B_Ð 5XLMLHFRQILJVYLURXWHUDFOVHQDEOH

ÏÎGQÞ

Q¸	ÉÄ
-	-

ÏGÄê -

2 IP QOS

2.1

ß QoS G5BÈÔÙ QoS Ý,X&µÖ

þÔG6(1 þ policy-map×

þ policy-map þ class-map×

þ class-map ÔG6(1 þ ACLÈ¹ ACL ,XÝ ACE ¾OK,È6×

þD6(,X ACE ,XÞ4G5B]< ACL"08V,XLÄ

5,ßoS s6ÑKÁxÖAÑXy[¹)ÞÔ Policy Map G6(þÈ’

5BZy¡XÞy¡X QoS s6Ñ>ØGKÁy¡X QoS s6ÞEÄy¡X Policy Map A’

5BÞÝ¡XÞ’ Off GÄ QOS ,X5,Ñ5BÖ

5,Ñ5B	5,Ñ CoS	0
	Kþ	8
	KßBEQ®	WRR
	QueueWeight	1:1:1:1:1:1:1:1
	WRR Weight Range	1:15
	DRR Weight Range	1:15
	ß	No Trust

Cos KßXTAxØ<

Cos Kß	CoS	Kß
	0	1
	1	2
	2	3
	3	4
	4	5
	5	6
	6	7
	7	8

CoS to DSCP TAxØ<

CoS to DSCP	CoS	DSCP
	0	0
	1	8
	2	16
	3	24
	4	32

	5	40
	6	48
	7	56

IP-Precedence to DSCP TÀxØ<

	IP-Precedence	DSCP
IP-Precedenc e to DSCP	0	0
	1	8
	2	16
	3	24
	4	32
	5	40
	6	48
	7	56

DSCP to CoS ,XTÀxØ<

	DSCP	CoS
DSCP to CoS	0	0
	8	1
	16	2
	24	3
	32	4
	40	5
	48	6
	56	7

SØ	S2900 DRR Weight Range

2.2 class maps

Î ACLÖ

ip access-list {**extended** | **standard**} { *acl-id* | *acl-name* }

ê **mac access-list extended** {*acl-id* | *acl-name*}

ê **expert access-list extended** {*acl-id* | *acl-name*}

ê **ipv6 access-list extended** *acl-name*

ê **access-list acl-id 2ÖÇÅ** ACL ,Ġ08VÅ

Î class mapÈÉ9 class map G5BØ

[**no**] **class-map** *class-map-name*

Â¹ class map ,XGØ

[**no**] **match access-group** *acl-name*| *acl-id*

[**no**] **match ip dscp** *dscp-value1* [*dscp-value2* [*dscp-valueN*]]

[**no**] **match ip precedence** *ip-pre-value1* [*ip-pre-value2* [*ip-pre-valueN*]]

Ï–DAèð

–D	Ë.Ä
acl-name	Á¶Ê¥X ACL ,Xá¤
acl-id	Á¶Ê¥X ACL ,X id
class-map-name	Ø0Î¥X class map ,Xá¤
dscp-vlaueN	Ø0G¦X ip dscp
ip-pre-valueN	Ø0G¦X ip precedence
no class-map *class-map-name*	ô08Á¶Ê¥X class map
no match access-group *acl-name*| *acl-id*	ô08AG!
no match ip dscp *dscp-value1* [*dscp-value2* [*dscp-valueN*]]	ô08G¦X ip dscp
no match ip precedence *ip-pre-value1* [*ip-pre-value2* [*ip-pre-valueN*]]	ô08¦G ip precedence

Ï5,Õ5BÐ -

ÏQ¸è <G5Bã

ÏSÊÐ -

ÏG5B_Ð _ 1ÕÐ MAC ACL,Qá me

5XLMLHFRQILJPDFDFFHVVOLVWH[WHQGHGPH

_ 2Ø5B ACL Ï?

5XLMLHFRQILJH[WPDFOSHUPLWKRVWDQ\

_ 3ÈÕÐ ACL A5B

5XLMLHFRQILJH[WPDFOH[LW

_ 4ÕÐ class-map,Qá cm

5XLMLHFRQILJFODVVPDSFP

_ 5Ø6(ACL

5XLMLHFRQILJFPDSPDWFKDFFHVVJURXSPH

_ 6ÈÕÐ class-map A5B

5XLMLHFRQILJFPDSH[LW

_ 7ÕÐ class-mapèQá cm-dscpè! DSCP 8È 16è24èÊÐ5B

5XLMLHFRQILJFODVVPDSFPGVFS

5XLMLHFRQILJFPDSPDWFKLSGVFS

5XLMLHFRQILJFPDSH[LW

ÏÏGQÐ

Q¸	Ë.Ä
show mac access-lists	-
show ip access-lists	-
show class-map	-

ÏGÄèð õÐ none-tos s6Ñ

2.3 drr-queue bandwidth

A5B DRR AzøXKGÄ

drr-queue bandwidth *weight1...weight8*

no drr-queue bandwidth

Ï-DAè

–D	ÆÄ
weight1...weight8	8È 9,Õ5B
no	65Õ

Ï5,Õ5BÐ

9,Õ5B

ÜQè

<G5Bã

ÏÕ

-

Ï5B_Ð

5XLMLHFRQILJGUUTXHXHEDQGZLGWK

ÌÎGQÐ

Q¸	ÆÄ
show mls qos queueing	-

ÏGÄè

-

2.4 interface rate-limit

0ÆÝ[L$XA5BÄ

rate-limit {**input** | **output**} *bps burst-size*

no rate-limit

ÏÐAè

–D	ÆÄ
input	Eg9L5ó
output	gÎL
bps	¾K
burst-size	(Kbyte)dscp-list 8{5å
no	65Õ

Ï5,Õ5BÐ

-

ÜQè

yG5Bã

ÏÕ

-

Ï5B_Ð

5XLMLHFRQILJLQWHUIDFHIDVW(WKHUQHW

5XLMLHFRQILJLIUDWHOLPLWLQSXW

ÏĈGQÞ	Q¸	ÐÄ
	show mls qos interface	-

ĠÄâê -

2.5 mls qos cos

G5By¡X CoS Ä

mls qos cos *default-cos*

no mls qos cos

Ï–DAâê	–D	ÐÄ
	default-cos	07
	no	*6ãÕ*

ĕ¸ÕĠ5BÐ CoS 0

ĊQÞê yG5Bã

ĕŠÞê -

ĠĕB_Ð 5XLMLHFRQILJLQWHUIDFHJLJDELWHWKHUQHW
5XLMLHFRQILJLIPOVTRVFRV

ÏĈGQÞ	Q¸	ÐÄ

show mls qos interface *interface-id*

ÏQþÐ <G5Bã

ÏÉÐ -

ÏG5B_Đ 5XLMLHFRQILJPOVTRPDSFRVGVFS

ÏÎGQÞÐ

Q¸	ÆÄ
show mls qos maps	**/** dscp-cos maps,dscp-cos maps ` ip-prec-dscp maps

ÏGÄÐ -

2.7 mls qos map dscp-cos

A5By[,XYF¼ DSCP Ø CoS Ä

mls qos map dscp-cos *dscp-list* to *cos*

no mls qos map dscp-cos

ÐAÐ

–D	ÆÄ
dscp-list	

no	**6ãÕ**

ï5,Õ5BÐ 9,Õ5B

ÏQþÐ <G5Bã

ÏSêÐ -

ÏG5B_Ð 5XLMLHFRQILJPOVTRPDSLSSUHFGVFS

ÏÎGQÞÐ

Q¸	ÆÄ
show mls qos maps	**/** dscp-cos maps,dscp-cos maps ` ip-prec-dscp maps

ÏGÄâÐ -

2.9 mls qos scheduler

A5BEgÎKáz1kÄ

mls qos scheduler [**sp** | **rr** | **wrr** | **drr**]

no mls qos scheduler

ÐAâÐ

–D	ÆÄ
sp	**4ÉÆAz**
rr	**@z**
wrr	**Ô@z**
drr	**3@z**
no	**6ãÕ**

ï5,Õ5BÐ 5,Õ wrr Az

ÏQþÐ <G5Bã

ÏSêÐ -

ÏG5B_Ð 5XLMLHFRQILJPOVTRVVFKHGXOHUVS

ÏÎGQÞÐ

Q¸	ÆÄ
show mls qos scheduler	-

ÏGÄâÐ -

policy-map-name	ØÎK policymap ,Xá
no policy-map *policy-map-name*	ßÁÐ policy map
class-map-name	ÁÐ class map ,Xá
no class *class-map-name*	ûßADÉÒ
new-dscp	„ DSCP ßè{ßå
new-cos	„ CoS ßè 0-7
rate-bps	ßÍÀß kbps
burst-byte	ßè kbyte
drop	ßÚÝ
dscp-value	mÝ DSCP ßè{ßå
cos-value	mÝ CoS ßè 0-7

ï¿Õ5BÐ -

ÏQÞÐ <G5Bã

ÏßÐ -

ÏG5B_Ð _ 1ÕÐ policy map,Qá po

```
5XLMLHFRQILJSROLFLPDSSR
```

_ 2Ö6(class-map cm

```
5XLMLHFRQILJSPDSFODVVFP
```

_ 3ÐÖ5B# dscp 10

```
5XLMLHFRQILJSPDSFVHWLSGVFS
```

_ 4ÐÖ5Bß 1M, (ß£ 4096k,CYLßDC„ dscp 16

```
5XLMLHFRQILJSPDSFSROLFHH[FHHGDFWLRQGVFS
```

ÌÎGQÞ

Q¸	£Ä
show policy-map	-

ÏGÄß -

2.12 priority-queue

A5BEgÎKåx1kÖ

[**no**] **priority-queue**

ÐAß

–D	£Ä
priority-queue	gÎ© SP (S2900 2Ä,S8600 2Ä)Ù
no priority-queue	gÎ© WRR

ï¿Õ5BÐ EgÎKßBE©Ù WRR

ÜQþÐ <G5Bã

ÜSÐ -

ÜG5B_Đ 5XLMLHFRQILJQRSULRULWTXHXH

ÏÎGQÞ

Q¸	Ë Ä
show mls qos queueing	-

ÜGÄÀð -

2.13 priority-queue cos-map

G5BEgÎK6(,X CoS Ä

priority-queue cos-map *qid cos0* [*cos1* [*cos2* [*cos3* [*cos4* [*cos5* [*cos6* [*cos7*]]]]]]]

no priority-queue cos-map

ÐÀð

–D	Ë Ä
qid	ô X id
cos7	*cos0 ...* 6X CoS
no	6 Õ

Ü,Õ5BÐ 9,Õ5BàVÄ

ÜQþÐ <G5Bã

ÜSÐ -

ÜG5B_Đ 5XLMLHFRQILJSULRULWTXHXHFRVPDS

ÏÎGQÞ

Q¸	Ë Ä

ÐAð	–D	

2.18 show mls qos queueing

/ QoS K¢(cos-to-queue map,wrr weight,drr weight) Ä

show mls qos queueing

ÐAð	–D	£Ä

2.20 show mls qos scheduler

/0Ã{KázÄ

show mls qos scheduler

ÐAð	–D	Ł Ä
	-	-

ï,Õ5BÐ -

ÏQþ (Mã

ÏÐ -

Ï5B_Ð 5XLMLHVKRZPOVTRVVFKHGXOHU

	Ł Ä	

2.22 show policy-map

/ QoS policy me0iþp r]p

ÏGÄê -

2.24 wfq-queue bandwidth

Äz1kSŭ wfq ,XÈQÇG5B,ĥ,XþØÁ

wfq-queue *queue-id* **bandwidth** *min max*

no wfq-queue *queue-id* **bandwidth**

ÏÐAê

–D	ÆÄ
queue-id	ë
min	ê
max	Ø

Ï,Õ5BÐ min êÁ kbpsÄ

max ÛÁ kbpsÄ

ÏÇê yG5Bã

ÏSÛ kŭ wfq 1kÄzÎÈÄQÃ5B0ÊÛÆ

ÏG5B_Ð KŭÄ wfq 1kÄzÖ

```
5XLMLHFRQILJPOVTRVVFKHGXOHUZIT
5XLMLHFRQILJVKRZPOVTRVVFKHGXOHU
```

G5BÊÛÆ

```
5XLMLHFRQILJLIZITTXHXHEDQGZLGWK
5XLMLHFRQILJLIZITTXHXHEDQGZLGWK
5XLMLHFRQILJLIVKRZUXQQLQJ
```

ÎÏGQÐ

Q¸	ÆÄ
show mls qos scheduler	ß QOS Azã

ÏGÄê -

2.25 wfq-queue sp

Äz1kSŭ wfq ,XÈQÇG5B,ĥ,XþØ{(sp) Ä

wfq-queue *queue-id* **sp**

no wfq-queue *queue-id* **sp**

ÏÐAê

–D	ÆÄ
queue-id	ë
sp	ÀÁ1K©

Ъ¸ÇÕ5BÐ
ŝŭ
sp

ÜÇþÐ
<G5Bã

ÜÊÜ±G5BÇÇµÀ
Ï !5B Ô S/pÜ
< G!5B õ ¿0~µ2¯À

2.27 virtual-group

[illegible] Aggregate Port [illegible] no [illegible]

virtual-group *virtual-group-number*

no virtual-group *virtual-group-number*

[illegible]	–D	[illegible]
	virtual-group-number	[illegible] 128

[illegible]

[illegible]

[illegible] Aggregate Port [illegible]

[illegible]

[illegible] 1/3 [illegible] 3

```
5XLMLHFRQILJLQWHUIDFHJLJDELWHWKHUHQHW
5XLMLHFRQILJLIYLUWXDOJURXS
```

[illegible]

Q¸	[illegible]
show virtual-group	[illegible]

[illegible]

-

-

ÍÑM4Q¸–5¸GB8VÖ

1. VRRP
2. VRRP Plus
3. BFD
4. RLDP
5. TPP
6. GRTD
7. SEM

1 VRRP

1.1 debug vrrp

QẹÔ VRRP ÎJfÃ VRRP _ÆRRP y[ÆÃÂCJÄ **no 6ÆÁ6Ñ**

debug [**ipv6**] **vrrp**

no debug [**ipv6**] **vrrp**

ÐÀ –D]

Ï–DAðð

–D	ÆÄ
ipv6	h*ü IPv6ßÄ,Õ IPv4Ä

ß,Õ!5BÐ GKÁªAÂG

ÜÇÞ (M*ã

ß*Ð -

Ü!5B_Ð Ô VRRP ÎÍÆAÂGÄ

```
5XLMLHGHEXJ8USHUURUV
5XLMLHGHEXJLSV8USHUURUV
9553,39Y553*USGM8UWLVHPHQWIURPKDVZRQJFKHFNVXP
9553,39Y553*USGM8UWLVHPHQWIURPKDVZRQJFKHFNVXP
9553,39Y553*USGM8UWLVHPHQWIURPKDVZRQJFKHFNVXP
```

M6,X/Ç><ĵ97¾ 192.168.1.1 JÍ IPv4 VRRP 4˜ 1 ,X VRRP EÐJÄÃ

ÏGQÞ

Q¸	ÆÄ
-	-

ÜÄðð -

1.3 debug vrrp events

QÇÔ VRRP _ÊÆAÂGÄ **no 6ðÉÂÄ**

debug [**ipv6**] **vrrp events**

no debug [**ipv6**] **vrrp events**

Ðð

–D	ÆÄ
ipv6	h*ü IPv6ßÄ,Õ IPv4Ä

ß,Õ!5BÐ GKÁªAÂG

ÜÇÞ (M*ã

ß*Ð -

Ü!5B_Ð Ô VRRP _ÊÆAÂGÄ

```
5XLMLHGHEXJ8USHMQWV
5XLMLHGHEXJLSV8USHMQWV
9553,39Y553*US(MQWGM8UWKLJKHURUHTXDOSULRULW\
9553,39Y553*US(MQWGM8UWKLJKHURUHTXDOSULRULW\
9553,39Y553*US(MQWGM8UWKLJKHURUHTXDOSULRULW\
```

ÏĈGQÐ	Q¸	Ł Ä
	-	-

ĠÄ₴ -

1.4 debug vrrp packets

QỌ VRRP DB₩ÀĈÄ **no 6₴ÓÔÄ**

debug [**ipv6**]

1.5 debug vrrp state

QÇÔ VRRP (ÕXAAÊÔÄ **no 6ÉÊÄ**

debug [**ipv6**] **vrrp state**

no debug [**ipv6**] **vrrp state**

Ð

–D	Ë
ipv6	h*ü IPv6Ä¸Õ IPv4Ä

Ü¸Õ!5BÐ GKÁ¤AÊÔ

ÜÇÞ (M*ã

Ü*Ð -

Ü!5B_Ð Ô VRRP (ÕXAAÊÔÄ

```
5XLMLHGHEXJ9USVWDWH
5XLMLHGHEXJLSV9USVWDWH
9553,39¥9553*USDGGSULPDU¥UWXDO,3VWDWUXS
5XLMLHGHEXJLSV9USVWDWH
9553,39¥9553*USDGGSULPDU¥UWXDO,3VWDWUXS
```

M6,X/Ù><â Fastethernet 0/0 ÞX IPv4 VRRP 4˜ IPv6 VRRP 4Ü!5BZ IP È VRRP ÃÙÄ

ÎÜGQÞ

Q¸	Ë
-	-

ÜÄÐ -

1.6 show vrrp

Q¿ IPv4 VRRP ÕÙ IPv6 VRRP ,XV‰ÃVÄ

show [**ipv6**] **vrrp** [**brief** | *grou*p]

Ð

–D	Ë
ipv6	h*ü IPv6Ä¸Õ IPv4Ä
brief	/ VRRP ,XV‰
group	ÝX VRRP 4Ë

Ü¸Õ!5BÐ -

ÜÇÞ (M*ã

Ï*Ð Vpš*ÊÝDÐX VRRP 4¸XŸ‰

Ï!5B_Ð _ 1ŒX VRRP 4‰

```
5XLMLHVKRØUS
)DVW(WKHUQHW*URXS
6WDWHLV%DFNXS
9LUWXDO,3DGGUHVVLVFRQILJXUHG
9LUWXDO0$GGUHVVLVH
$GMUWLVHPHQWLQWHUØOLVVHF
3UHHPSWLRQLVHQDEOHG
PLQGHOLVVHF
3ULRULWLV
0DVWHU5RXWHULVPULRULWLV
0DVWHU$GMUWLVHPHQWLQWHUØOLVVHF
0DVWHURQLQWHUØOLVVHF
)DVW(WKHUQHW*URXS
6WDWHLV0DVWHU
9LUWXDO,3DGGUHVVLVFRQILJXUHG
9LUWXDO0$GGUHVVLVH
$GMUWLVHPHQWLQWHUØOLVVHF
3UHHPSWLRQLVHQDEOHG
PLQGHOLVVHF
3ULRULWLV
0DVWHU5RXWHULVORFDOSULRULWLV
0DVWHU$GMUWLVHPHQWLQWHUØOLVVHF
0DVWHURQLQWHUØOLVVHF
5XLMLHVKRZSVØUS
*LJDELW(WKHUQHW*URXS
6WDWHLV0DVWHU
9LUWXDO,3ØGGUHVVLVDVIROORZ
)(

9LUWXDO0$GGUHVVLVH
$GMUWLVHPHQWLQWHUØOLVVHF
$FFHSWB0RGHLVHQDEOHG
3UHHPSWLRQLVHQDEOHG
PLQGHOLVVHF
3ULRULWLV
0DVWHU5RXWHULV)(ORFDOSULRULWLV
0DVWHU$GMUWLVHPHQWLQWHUØOLVVHF
0DVWHURQLQWHUØOLVVHF
5XLMLH
```

_ 2Ö VRRP 4¸XV‰

```
5XLMLHVKRZUSEULHI
,QWHUIDFH*US3UL7LPH2QQ3UH6WDWH0DVWHUDGGU*URXSDGGU
)D3%DFNXS
)D30DVWHU
5XLMLHVKRZSWUSEULHI
,QWHUIDFH*US3ULWLPHU2QQ3UH6WDWH0DVWHUDGGU*URXSDGGU
*L30DVWHU)()(
5XLMLH
```

ÏĜGQÞ Q¸ EÄ/480.199 0.-27-54-f9 -1-5(V-480.(0485.199 9n20-7.79 35(0.4B-0(V-42030

```
0DVWHURQLQWHUIDFH
)DVW(WKHUQHW*URXS
6WDWHLV0DVWHU
9LUWXDO,3DGGUHVVLVFRQILJXUHG
9LUWXDO0DGGUHVVLVH
6HFRQGDU\LQWHUIDFH
3UHHPSWLRQLVHQDEOHG
PLQGHODLVVHF
3ULRULWLV
0DVWHU5RXWHULVORFDOSULRULWLV
0DVWHUSHFRQGDU\LQWHUIDFH
0DVWHURQLQWHUIDFH
```

_ 2Ø5%· gigabitEthernet 0/13 ÞX IPv6 VRRP %‰

```
5XLMLHVKRZSVUSLQWHUIDFHJLJDELW(WKHUQHW
*LJDELW(WKHUQHW*URXS
6WDWHLV0DVWHU
9LUWXDO,3DGGUHVVLVDVIROORZ
)(

9LUWXDO0DGGUHVVLVH
6HFRQGDU\LQWHUIDFH
$FFHSWB0RGHLVHQDEOHG
3UHHPSWLRQLVHQDEOHG
PLQGHODLVVHF
3ULRULWLV
0DVWHU5RXWHULV)(ORFDOSULRULWLV
0DVWHUSHFRQGDU\LQWHUIDFH
0DVWHURQLQWHUIDFH
```

ÏĪGQÞ

Q¸	Ë Ä
vrrp ip	*ü VRRP s6ÕA5B<.³AĮX IP
vrrp ipv6	*ü VRRP s6ÕA5B<.³AĮX IPv6

ĪGÄß

-

1.8 show vrrp packet statistics

AÐQ¸*0¡ß VRRP y[¥X4³AuĮÄ

show vrrp packet statistics [*interface-type interface-number*]

Ïß

–D	Ë Ä
interface-type *interface-number*	y2O_ù4Ë

Ï5‚Õ!5BÐ -

ÜQþÐ (M*ã

Ü5*ôÐ -

ÜG!5B_Ð _ 1ÐÑX VRRP y[4ªAuÇÄ

```
Ruijie#show vrrp packet statistics

Total
  InReceives: 1000 packets, InOctets: 250, InErrors: 50
  OutTransmits: 900, OutOctets: 230
VLAN 1
  InReceives: 300 packets, InOctets: 100, InErrors: 6
  OutTransmits: 275, OutOctets: 75
VLAN 2
  InReceives: 500 packets, InOctets: 150, InErrors: 24
  OutTransmits: 450, OutOctets: 125
```

_ 2ÐÐ· VLAN 2 ,X VRRP y[4ªAuÇÄ

```
Ruijie#show vrrp packet statistics vlan 2

VLAN 2
  InReceives: 500 packets, InOctets: 150, InErrors: 24
  OutTransmits: 450, OutOctets: 125
```

ÏÎGQÞÐ

Q¸	Ë.Ä
-	-

ÜGÄèÐ -

1.9 vrrp accept_mode

Q¸*ü IPv6 VRRP <.ÇÃ<,Xy[ys6ÐÑ **no 6ÐÝÓ6ÑÑ**

vrrp ipv6 *group* **accept_mode**

no vrrp ipv6 *group* **accept_mode**

ÐÐÐ

–D	Ë.Ä
group	VRRP 4Ë

Ï5‚Õ!5BÐ Master (ÐÑX IPv6 VRRP ÁyÇÂX IPv6 <.ÇÃ<,X IPv6 ,Xy[Ä NA ` NS y[ÁuÇ!5B Accept_Mode FÑÓÐÊÄ Owner (ÐÑX IPv6 VRRP Master (ÐÑ.ÇÃ<È ÁuÝÓ!5B Accept_Mode èÑÓÐÊÄ IPv6 <.ÇÃ<,X IPv6 ,Xy[Ä

ÜQþÐ yG!5Bã

Ü5*ôÐ 5%4ÿG!5BÊ!5B,XØ Master (ÐÑX<.ÇÃ<*Á

Ý¼ IPv6 VRRP !ÍÐG!5Bã

Ğ!5B_Đ VRRP 4˜ 1 *ü IPv6 VRRP <.ĈÃ<,Xy[ys6Ñ

no vrrp delay

–D	Ë Ä
minimum *min-seconds*	2Ï‡ÊXÊÊÈ
reload *reload-seconds*	y(ÊXÊÊÈ

0~60 /Ä

yG!5B

G!5BQ VRRP VRRP M2v4G!5B VRRP

VRRP IPv4 VRRP

IPv6 VRRP

VRRP

5XLMLHFRQILJLIVUSGHODPLQLPXPUHORDG

Q¸	Ë Ä
vrrp ip	*ü IPv4 VRRP s6ÕA5B<.ÀÛX IP
vrrp ipv6	*ü IPv6 VRRP s6ÕA5B<.ÀÛX IPv6

-

1.12 vrrp description

Q¸ IPv4 VRRP IPv6 VRRP **no 6**

vrrp [**ipv6**] *group* **description** *text*

no vrrp [**ipv6**] *group* **description**

Building B – Marketing and AdministrationÄ

5XLMLHFRQILJLQWHUIDFH)DVW(WKHUQHW
5XLMLHFRQILJLILSDGGUHVV
5XLMLHFRQILJLIYUSLS
5XLMLHFRQILJLIYUSGHVFULSWLRQ“ ■V
■Q
■V ■V

ÏĈGQÐ	Q¸	Ł:Ä
	vrrp ip	*ü VRRP s6ÕA5B<.ÀÅ¸X IP
	vrrp ipv6	*ü VRRP s6ÕA5B<.ÀÅ¸X IPv6

ĬGÄÐ -

1.13 vrrp ip

Qÿ¿Pü IPv4 VRRP s6ÕA5BAÕs6ÕÑ6Õ18ÀÀ2ÀPv6smDv5BÀ3mDÐ

ÏÎGQÞ

Q¸	Ë.Ä
show vrrp	/!,X VRRP A5B

ËGÄß

-

1.14 vrrp ipv6

Qüµ¹ü IPv6 VRRP s6ÑA5Bí,X<.³ IPv6 Ä **no 6É6¼Ñ** IPv6 VRRP s6Ñ¼.³ IPv6 ,XA5BÄ

vrrp *group* **ipv6** *ipv6-address*

no vrrp *group* **ipv6** *ipv6-address*

Ëß

–D	Ë.Ä
group	<.ÆÂ¦Ù¼ VRRP 4Ë
ipv6-address	<.ÆÂ¦Ù¼ IPv6

Ë5,Õ!5BÐ

y¼½ú IPv6 ,X VRRP s6Ñ

ËQ§Þ

yG!5Bã

Ë5*Ô

IPv6 ,X VRRP â IPv4 ,X VRRP E*ü 1255 ,X4¼Ñ¼X VRRP 4Ë5Cü

b IPv4 VRRP ` IPv6 VRRPÄÔ!5B,XÑ¼OJÒÃÒÑ¼OJW<.³

ü8ó6Ñ8Ä

ËG!5B_Ð

µ· Fa0/0 ¹ü IPv6 ,X VRRP s6Ñ¹ VRRP 4Ë 1È.³ IPv6 FE80::1 ` 2001::1Ä

```
5XLMLHFRQILJLQWHUIDFH)DVW(WKHUQHW
‘ ¼ ¼
¼
¼
¼
¼
¼
```

ÏÎGQÞ

Q¸	Ë.Ä Ë7 1 0r&s0 Uð

Ï Ð à

–D	Ë Ä
ipv6	h*ü IPv6 Ë Ä, Õ IPv4 Ä
group	VRRP 4 Ë
delay *seconds*	ê ü 7 Ä Master D Ñ , X Ê Ë Ä , Õ 0 / Ä

Ï Ð , Õ ! 5 B Ð y Þ ý ü VRRP s 6 Ñ
Ê ü VRRP s 6 Ñ VRRP 4 T A x ð ü 4 Ë Ä

Ï Ð Ò ã y G ! 5 B ã

Ï * ê ð Vp VRRP 4 Ð ü 4 Ê Ñ ¥ ¿ Ä ì 4 { P Þ ! Master , X ì 4 { Ê ü Ú 4 Ä ¹
VRRP 4 ¸ X A Ê ð p VRRP 4 Ð ü M 2 v 4 Ê Ñ W ¥ ¿ Ä ì 4 { P Þ ! Master , X
ì 4 { Ê W 3 ã ü 4 Ä ¹ VRRP 4 ¸ X A Ê ð VRRP 4 Ï * ã 5 % y · IP Ê Ñ ã
A T B ã ê { 4 Ð ã s e E e A s e R Ä 4 1 A 2 ' 4 R 3 4 Q [F 3 P 4 [P W P P 3 E E Å 1 0 4 E H M 7 Ä @ 3 4 ' 1 Ô Ä Ó 0 E 4 0 8 9 > Ð y Q N 0 e

level	VRRP 4¸˜Xï4{

ï5¸Õ!5BÐ yb*ý VRRP s6Ñ
ê0ü VRRP s6ÑVRRP 4TAxJï4{ 100Ä

ÜQ5Ð yG!5Bã

Ï*ê0 AÐQ¸A5B VRRP 4¸˜Xï4{Ä

Ü!5B_Ð _ 1Ø5B IPv4 VRRP 4˜ 1 ,Xï4{ 254Ä
5XLMLHFRQILJLIVUSSULRULW\

_ 2Ø5B IPv6 VRRP 4˜ 1 ,Xï4{ 254Ä
5XLMLHFRQILJLIVUSLSSULRULW\

ÏÜGQÐ

Q¸	Ð:Ä
vrrp ip	*ü VRRP s6ÑA5B<.ªA¸ÛX IP
vrrp ipv6	*ü VRRP s6ÑA5B<.ªA¸ÛX IPv6

ÜÄÃð -

1.17 vrrp timers advertise

QA5B IPv4 VRRP 4ÕÙ IPv6 VRRP 4ÀÆÕ VRRP EîXKÈhÄ **no 6ÕÄ4T¬ xÃBÄ**

vrrp [**ipv6**] *group* **timers advertise** *interval*

no vrrp [**ipv6**] *group* **timers advertise**

Ðð

–D	Ð:Ä
ipv6	h*ü IPv6Ä¸Õ IPv4Ä
group	VRRP 4Ë
interval	VRRP EÆÕÈh(ª¸!)

ï5¸Õ!5BÐ yb*ý VRRP s6Ñ
ê0ü VRRP s6Ñ4TAxA¸ÛXEÆÕÈh 1 /ª¸Ä

ÜQ5Ð yG!5Bã

Ï*ê0 Vp!Aê VRRP 4¸˜XAÐÚh,XKÈhÆÕ VRRP EÐE7å¾ VRRP ¸(Ñ
4{ªWC¸Ä

Ü!5B_Ð _ 1Ø5B IPv4 VRRP EÆÕÈh 4 /ª¸Ä
5XLMLHFRQILJLIVUSWLPHUVDGYUWLVH

1.19 vrrp track

Q*ü VRRP ,XyC€Cþs6Ñ **no 6ÉÉs6Ñ**

vrrp *group* **track** { *interface-type interface-number* | **bfd** *interface-type interface-number ipv4-addess* }

[*priority*]

vrrp ipv6 *group* **track** *interface-type numbe* [*priority*]

no vrrp [**ipv6**] *group* **track** *interface-type number*

Q*ü VRRP ,X IP/IPv6 C€Cþs6Ñ no 6ÉKÁs6Ñ

vrrp *group* **track** *ipv4-address* [**interval** *interval-value*] [**timeout** *timeout-value*] [**retry** *retry-value*]

[*priority*]

vrrp ipv6 *group* **track** { *ipv6-global-address* | *ipv6-linkmtcal-address* } *interface-type interface-number* [[*priority*]

Vp VRRP 4Ä*ü (Own)Ø%yrL IP!ÈÊ¹ VRRP 4˜Xä{ 255ÈÊ!5B,¥ IP
6ÌÝÄ

Ë!5B_Ð _ 1Ö VRRP 4˜ 1 Í Routed Port Fa1/1 E> ,¥p Fa1/1 JÒÊ VRRP 4˜Xä{ 30×
ü Fa1/1 ,XJÒÊRRP 4˜ 1 ,Xä{6Á

```
5XLMLHFRQILJLIVUSWUDFN)DVW(WKHUQHW
```

_ 2Ö€Cþ 1000::1 ÊÁ

```
5XLMLHFRQILJLIVUSLSVWUDFN
```

_ 3Ö€Cþ5%4ÿ· VLAN 1 þ FE80::1 ÊÝÞ

```
5XLMLHFRQILJLIVUSLSVWUDFN)(VDQ
```

_ 4Ë!5Bû VRRP 4ÈÈ› BFD C€Cþ,XF• 192.168.1.3

```
5XLMLHFRQILJXUHWHUPLQDO
```

Ï‹Ð‰	–D	Ë‡Ä
	2	**Sˆ‰** VRRPv2 y[¥Ë‡Õ
	3	**Sˆ‰** VRRPv3 y[¥Ë‡Õ

Ï‚‚Õ!5BÐ yG!5B IPv4 VRRP ‚Xy[¥Ë‡Õ VRRPv2Ä

ÏQ¸Ð yG!5Bã

Ï*Ð‰ Ì IPv4 VRRP 5×% VRRPv2 ` VRRPv3 ‚XP¥ÂÎ¹ÐÃ5%4ŕL)ÿWE½² VRRP y [‚X¥Ë‡ÕRRPv2 Ì RFC3768È VRRPv3 Ì RFC 5798. !8Q¸Ë‡Ì IPv4 VRRPÄ

Ï!5B_Ð ÿÏ!5B IPv4 VRRP y[‚X¥Ë‡Õ
5XLMLHFRQILJLIVUSMUVLRQ

ÎÏQ¸Ð	Q¸	Ë‡Ä
	vrrp ip	*ü VRRP s6ÕA5B<.ÀÎX IP
	vrrp timers advertise	A5B VRRP E¥ËÕÈh

Ï‚Äã -

2 VRRP Plus

2.1 debug vrrp balance

ÐÀÇÈ¥ VRRP Plus ¢Ä

debug vrrp balance [**errors | messages | packets | state | timer | event**]

Ð¼	–D	¤fVÀQ%JHÀÀKÞH*H3Ú)%ÀQú)%ÀQú)%&1àERÎÐ{Ä

Ï*Ô VpsS*ÃÝDÐX VRRP Plus 4¸XA¼Ø‰

ÏG!5B_Ð _ 1ÐX VRRP Plus 4¸XA¼Ø‰

```
5XLMLHVKRØUSEDODQFH
9/$*URXS
6WDWHLV%9*
9LUWXDO,3DGGUHVVLV
+HOORWLPHVHFKROGWLPHVHF
/RGEDODQFLQJKRVWGHSHQGHQW
5HGLUHFWWLPHVHFIRUØUGHUWLPHRXWVHF
:HLJKWLQJFRQILJXUHGWKUHVKROGVORØUXSSHU
7UDFNREMHFWVWDWHGRØGHFUHPHQWØLJKW
7KHUHDUHIRUØUGHUV
)RUØUGHUORFDO
0Ø GGUHVV
H
2ØHU,LVGIDE
)RUØUGHU
0Ø GGUHVV
DD
2ØHU,LVGI
```

_ 2Ö VRRP Plus 4¸XV‰

```
5XLMLHVKRØUSEDODQFHEULHI
,QWHUIDFH*US6WDWH*URXSÑGU0Ø GGU
9/$%9*H
```

ÏÎGQÐ

Q¸	Ë Ä
vrrp balance	*ü VRRP Plus s6Ñ
vrrp load-balancing	A5B VRRP Plus ,XBÉQ>51*+9
show vrrp balance interface	/ûy¡X VRRP Plus E¤ (Ñ

ÏGÄÐ -

2.3 show vrrp balance interface

/ûyÞX VRRP Plus 4¸X|0Ø‰

show vrrp balance interface *type number* [**brief**]

Ï Ð

ï5,Õ!5BÐ -

ÏQþÐ (Mã

ïS*Ð -

ÏG!5B_Ð /þ5%· FastEthernet 0/0 þX VRRP Plus |0

5XD¢XKPPÞUU6PEPDÐ4X¢W4XUÐ4XÞPDW4(W4E¢W488(8ã

6P0esD¢X¢%ã

6P9¢¢6PDttU¸8JP¢PP¢P¢Ð@

ï5,Õ!5BÐ yÞ*ú VRRP Plus s6Ñ

ïQ¸Ð yG!5Bã

ï5*ÐÎ NVOG!5B VRRP s6ßÑú VRRP Plus s6Ñ

ïG!5B_Ð ý· interface FastEthernet 0/0 Þú VRRP Plus s6Ñ

```
5XLMLHFRQILJLQWHUIDFH)DVW(WKHUQHW
5XLMLHFRQILJLIVUSLS
5XLMLHFRQILJLIVUSEDODQFH
```

ïÎGQÐ

Q¸	Ë.Ä
vrrp load-balancing	A5B VRRP Plus ,XBËQ>51*+9
show vrrp balance	/ VRRP Plus ,XE¤ (Õ
show vrrp balance interface	/ûy¡X VRRP Plus E¤ (Õ

ïGÄÐ -

2.5 vrrp forwarder preempt

AQ¸*ûA5B VRRP Plus ÕÇXE¥4s6Ñ **no 6ßGÉ6Ñ**

vrrp *group* **forwarder preempt**

no vrrp *group* **forwarder preempt**

ïÐà

–D	Ë.Ä
group	û4Ïx VRRP Plus ÕÇXE¥4s6Ñ

ï5,Õ!5BÐ AE¥4

ïQ¸Ð yG!5Bã

ï5*ÐÎ NVOG!5B VRRP Plus s6ßÕE¥4s6Ñ

ïG!5B_Ð ý· interface FastEthernet 0/0 Þ4 VRRP Plus ÕÇXE¥4s6Ñ

```
5XLMLHFRQILJLQWHUIDFH)DVW(WKHUQHW
5XLMLHFRQILJLIVUSLS
5XLMLHFRQILJLIVUSEDODQFH
5XLMLHFRQILJLIVUSIRUZDUGHUSUHHPSW
```

ïÎGQÐ

Q¸	Ë.Ä

vrrp balance

```
5XLMLHFRQILJLIVUSEDODQFH
5XLMLHFRQILJLIVUSEDLJKWLQJOREUXSSHU
```

ÏĈGQÞ

Q¸	Ë:Ä
vrrp balance	*ü VRRP Plus s6Ñ
show vrrp balance	/ VRRP Plus ,XE¤ (Õ
show vrrp balance interface	/ûy¡X VRRP Plus E¤ (Õ

ĠÄß

-

3 BFD

3.1 bfd

G!5BBFD Â¸¥X–DÆÃE› no QÉ> ûß BFD Â±DÄ

bfd interval *milliseconds* **min_rx** *milliseconds* **multiplier** *multiplier-value*

no bfd interval

Ï Ð

–D	E Ä
Interval milliseconds	G!5BÆÕ BFD ÂE•X BFD {y[KÈh<Ê milliseconds Ã G!5B,X8È 50ms 10000msÄ¹–DrL3 echo y[,XKÈh –DÄ
min_rx milliseconds	G!5B BFD Â¿F•X BFD {y[KÈh<ÊD milliseconds Ã G!5B,X8È 50ms 10000msÄ
multiplier multiplier-value	G!5BÆXKÈh<ÍÑÃX BFD {y[,XD,ÊD multiplier-value Ã G!5B,X8È 3 50Ä

ï ,Õ!5BÐ Â±Dü5,Þ BFD Â±ÑOG!5BEo–D

ÏQÞ yG!5Bã

ï *Ô AÐÇÆ L3 AP yÈ> G!5BÄ

CÃ<Þü BFD s6ÑÔO*È@Ñ

Ï G!5B_Ð ü Routed Port y· FastEthernet 0/2 Ð G!5B BFD Â±DÄ

```
5XLMLHFRQILJLQWHUIDFHIDVW(WKHUQHW
5XLMLHFRQILJLIQRVZWFKSRUWCÃ<ÞQÞÑ9
5XLMLHFRQILJLIEIGLQWHUZOPLQBU[PXOWLSOLHU
```

ÎGQÞ

Q¸	E Ä
bfd all-interfaces	**S6ÞÑ** BFD 6(|Ä
clear bfd	**û8** BFD Â±ÆuDBÄ
ip ospf bfd	**S6ÃE** OSPF â BFD 6(|Ä
ip rip bfd	**S6ÃE** RIP â BFD 6(|

ï GÄÃÐ -

3.2 bfd all-interfaces

S6ÞÑX OSPFÅ RIPÅ BFD 6(|Ä*ü **no QÉ6ÑÑ**

bfd all-interfaces

no bfd all-interfaces

–D	EÄ
-	-

GKýÝX OSPFÅ RIPÅ BFD 6(|

CÃG!5Bã

ÁÃ6ÕÙKýAŒ OSPFÄ RIPÅ BFD 6(|Ö

ùÈ OSPFÄ RIPÃÃÃE¦ **no**] **bfd all-interfaces** OSPFÄ RIPÅ BFD 6(|Ä

ýÈE› **ip ospf bfd** [**disable**]ê **ip rip bfd** [**disable**]Q¸S6ÕKÛyAŒ OSPF Å RIPÅ BFD 6(|Ä

ü OSPF CÃG!5BÃ6ÝAŒ OSPF â BFD 6(|Ä

```
5XLMLHFRQILJURXWHURVSI
5XLMLHFRQILJURXWHUEIGDOOLQWHUIDFHV
```

Ï¨G!5B_Ð G!5Bü routed port ¤E› BFD ÍÐÃ 1.1.1.2 Ê¢*ý¸X BFD (Õ

```
5XLMLHFRQILJLQWHUIDFH)DVW(WKHUQHW
5XLMLHFRQILJLIQRVZÃ<t8QÇÑ9
5XLMLHFRQILJLILSDGGUHVV
5XLMLHFRQILJLIEIGELQGSHHULSVRXUFHLSSURFHVVSVW
```

ÏÎGQÇÐ

Q¸	Ë.Ä
-	-

¨GÄÊð -

3.4 bfd cpp

ü BFD ±1+9Ë*ü **no ÇQÍ** BFD ±1*+9Ä

bfd cpp

no bfd cpp

Ðð

–D	Ë.Ä
-	-

¨Ê¸Õ!5BÐ 5,Ñ BFD ±1*+9*ü

¨Çð <G!5Bã

¨S*Ô BFD M2ÐXÄÈp*ü BFD s6ÑXÄÊ*ü BFD ±1*+9E> ±Ä

Vp*ü BFD s6ÑXÊ1*+9ÈÐÇ¸X BFD y[4ËÄÄÊÄÛ

Ú BFD y[ÊÈÐÇÊÄÈX BFD ÎÊÄs6ÊÑ6*Ä

¨G!5B_Ð *ü BFD ±1*+9Ä

```
5XLMLHFRQILJEIGFSS
```

ÏÎGQÇÐ

Q¸	Ë.Ä
-	-

¨GÄÊð -

3.5 bfd echo

Ô echo Ë*ü **no ÇQÍ** echo Ä

bfd echo

no bfd echo

Ï-DAèð

–D	£Ä
-	-

Ï5,Õ!5BÐ 5,ßW BFD ?A±S6Ñ echo ã

ÏQ¸Þ yG!5Bã

Ï5*ÐÞ AÐQ¸ÁŒE L3 AP yG!5BÄ

5,ßW5BZ BFD ?A±D,XÆÜ+?¦S6Ñ echo ã echo y[,XÆÕÕEhÞ

KÈhG*?A±G!5B,X Interval milliseconds ` min_rx milliseconds –DÄ

ü BFD *ü echo ã LÔü BFD ?A¸XF¬Aþ **no ip redirects** Q¸ÉÕ ICMP Gɲ

ÿ[,Xs6Ñ **no ip deny land** Q¸Ý DDOS s6Ñ (L!6 Land-based)ÄÄ

Echo ßW BFD ?A¸X0ZÜ+F5Ñ6Ñ6ÑÄ

ÏG!5B_Ð ü Routed Port y· FastEthernet 0/2 ÐG!5B echo ãÄ

```
5XLMLHFRQILJLQWHUIDFHIDVW(WKHUQHW
5XLMLHFRQILJQRVZWFKSRUWCÃ<ÞQ¸Ñ9
5XLMLHFRQILJLIEIGHFKR
```

ÏÏGQÞ

Q¸	£Ä
bfd	**G5B** BFD ?A±DÄ
ip redirects	**S6Ñ** ICMP Gɲÿ[s6Ñ
bfd slow-timer	**G5B6EóêÊÈ**

ÏGÄèð -

3.6 bfd slow-timer

G!5BBFD ü ECHO s6ßEóÊXÊÃÊÈÐ BFD ÜÞÆÕ BFD {y[Ä›

*ü **no** ÉÞÐ

bfd slow-timer *milliseconds*

no bfd slow-timer

Ï-DAèð

–D	£Ä
milliseconds	BFD ,X6EóÊÈÐÆÃ!5B8È 1000 30000, Ð!5B 5,Õ 1000Ä

Ï5,Õ!5BÐ 5,Õ 1000ms

ÏQ¸Þ <G!5Bã

Ï5*ÐÞ -

ÏG!5B_Ð G!5Bslow-timer 14000 !¿Ä

5XLMLHFRQILJEIGVORZLPHU

ÏQþÐ yG!5Bã

Ï*ÐÐ ÆÃ6ßÕÏGKýÁÆŒ OSPF â BFD 6(|Ö
1ÈÈ OSPF CÃÆEÈ¦ **no**] **bfd all-interfaces** Ş6ßÕÝÆ OSPF â BFD 6(|Ä
2ÿÆE› **ip ospf bfd** [**disable**]QŞ6ßÕKÂyÞX OSPF â BFD 6(|Ä

ÏG!5B_Ð ü Routed Port y· FastEthernet 0/2 ÐKÁ OSPF Æâ BFD 6(|Ä

```
5XLMLHFRQILJQWHUIDFH)DVW(WKHUQHW
5XLMLHFRQILJLQRVZWFKSRUWCÃ<!8QÑ9
5XLMLHFRQILJLILSRVSIEIGGLVDEOH
```

ÎÏGQÞÐ

Q¸	Ë Ä
bfd	**G5B** BFD Ã±DÄ
bfd all-interfaces	**S6ÿÆ** BFD 6(|

ÏGÄÆÐ -

3.9 ip rip bfd

S6ÿÞX RIP â BFD 6(|Æü **disable GÆÝÆ** RIP Æâ BFD 6(|ÆE› **no Q**
ô8ÆG5BÄ
ip rip bfd [**disable**]
nM[r-6þ)6(r1)6þ)6

ĬGÄâê -

3.10 ip route static bfd

G!5BIPv4 M-ÕÃâ BFD 6(|ËE› **no Ò8G5BÄ**

ip route static bfd [**vrf** *vrf-name*] *interface-type interface-number gateway* [**source** *ip-address*]

no ip route static bfd [**vrf** *vrf-name*] *interface-type interface-number gateway* [**source** *ip-address*]

Ï-DAâê

–D	ËÄ
vrf *vrf-name*	G!5BM-ÕÃ<2,X VRF áÄ
interface-type *interface-number*	*á2Oy4Ä*
gateway	*á* IPÈ BFD ,XF• IPÄ-ÕÃG!5BÔÇF¸XÉE› BFD E> ÄEÁÃ,XÃÄ
source *ip-address*	*á* BFD ÂÆ*¡Xá IP , VpF• IP ÎCÇXÄG!5BA¹ –DÄ

Ï5,Õ!5BÐ ú¥!5BM-õ BFD 6(|

ÏQê <G!5Bã

Ï5*Ð G!5BÊj.BÆ¼¸X BFD ÂÆDÄÆG!5B

Ï!5B_Ð S6Ñ-ÕÃG6(BFD h*ÈE› BFD á 172.16.0.2 FKÈXEÁÃÄ

```
5XLMLHFRQILJLQWHUIDFH)DVW(WKHUQHW
5XLMLHFRQILJLIQRVZWFKSRUWCÃ<!8QÇÑ9
5XLMLHFRQILJLILSDGGUHVV
5XLMLHFRQILJLIEIGLQWHUZOPLQBU[PXOWLSOLHU
5XLMLHFRQILJLSURXWHVWDWLFIEIG)DVW(WKHUQHW
5XLMLHFRQILJLSURXWH)DVW(WKHUQHW
```

ÎĬGQÐ

Q¸	ËÄ
bfd	**G5B** BFD ÂÆDÄ

ĬGÄâê -

3.11 set ip next-hop verify-availability

G!5B1*+9CÃâ BFD 6(|È*ü BFD ê TRACK ÊÇËE› **no QÉ6Ñ**

set ip next-hop verify-availability *next-hop-address* { **track** number **| bfd** [**vrf** *vrf-name*] *interface-type interface-number gateway* }

no set ip next-hop verify-availability *next-hop-address* { **track** *number* | **bfd** [**vrf** *vrf-name*]

interface-type interface-number gateway }

Ï–DAèð

–D	Ë.Ä
vrf *vrf-name*	VRF æÄ
next-hop-address	Ô Ç IP
track	Ë.Ë› Track ßÔÇ
Number	track Ê54Ë.
bfd	Ë.Ë› BFD ß> F#
interface-type *interface-number*	*ß2Ô4Ë.*
gateway	ß IPÈ BFD ,XF• IPÄ-ÕÃG!5BÔÇF•XÉË› BFD E> ÄË@Ã,XÆÄ

ï5,Õ!5BÐ 5,Ð*+9CÃG6(BFD s6Ñ

ÏQæ CÃÒ!5Bã

Ï5*Ô G!5BÊj.BË• IP Ĥ,Xy¡X BFD ÎA±DÄG!5B

Ï!5B_Ð S6Ñ*+9CÃG6(BFD h*ÈË› BFD ß 172.16.0.2 FKÞXE@Ã

```
5XLMLHFRQILJXUHWHUPLQDO
(QWHUFRQILJXUDWLRQFRPPDQGVRQHSHUOLQH(QGZKW7/=
5XLMLHFRQILJURXWHPDS([DPSOHSHUPLW
5XLMLHFRQILJURXWHPDSPDWFKLSDGGUHVV
5XLMLHFRQILJURXWHPDSVHWLSSUHFHGHQFHSULRULW\
5XLMLHFRQILJURXWHPDSVHWLSQH[WKRSMULIDMLODELOLWEIG)DVW(WKHUQHW

5XLMLHFRQILJURXWHPDSHQG
```

ÏÎGQÞÐ

Q¸	Ë.Ä
bfd	**G!5B** BFD ÎA±DÄ

ÏGÄèð -

3.12 show bfd neighbors

/ BFD ÎAÞ

show bfd neighbors [**vrf** *vrf-name*] [**client** { **ospf | rip | vrrp | static-route | vrrp-balance | pst** }] [**ipv4** *ip-addess* | **ipv6** *ip-addess*] [**details**]

Ï–DAèð

–D	Ë.Ä
vrf *vrf-name*	**F2X** VRF æÄ
client	**ôhÞ**

ospf	ô/	OSPF 6(|,X BFD ?Ą€
rip	ô/	RIP 6(|,X BFD ?Ą€
vrrp	ô/	VRRP 6(|,X BFD ?Ą€
static-route	ô/	StaticRoute 6(|,X BFD ?Ą€
pbr	ô/	PBR 6(|,X BFD ?Ą€
vrrp-balance	ô/	VRRP Plus 6(|,X BFD ,X?Ą€
pst	ôýÕ	BFD 6(|,X?Ą€
ipv4 *ip-addess*	ô/	IPv4 (Mn?Ą±X?Ą€
ipv6 *ip-addess*	ô/	IPv6 (MnF•X?Ą€
details	?Ąš	

ï5,Õ!5BÐ -

ÜQþ (Mã

Ï5*Ð ü **show bfd neighbors** ÈurAddr ></?Ą±X6ÎÊ</þ

NeighAddr	²ÁÉ•X IP
LD/RD	²ÁÉ0Ãš
RH/RS	²Á‰ÝÃ(Õ
Holdown(mult)	²Á½ hello y[,XÊÈÀÉCÊÐ
State	²Á¼(Õ
Int	²Á½XyË
Session state is UP and using echo function with 50 ms interval	²ÁG*ü echoõá echo ,XÊÈÀÉh (Á¢Ú¼ ü Echo ¼
Local Diag	²Á±XÁÊ¢
Demand mode	²ÁÁ¼‰#
Poll bit	²Á±XG!5BÂv
MinTxInt	²ÁG!5B,XÊÕÈh
MinRxInt	²ÁG!5B,XÊKÈh
Multiplier	²ÁG!5B,XCÊÐ
Received MinRxInt	²ÁÉ0ÃG!5B,XÊÕÈh
Received Multiplier	²ÁÉ0ÃG!5B,XCÊÐ
Holdown (hits)	²ÁÊÈÀÉ±X Ð
Hello (hits)	²Á½ hello Ê±XyÊÈh
Rx Count	²Á¥ BFD y[,XÊÐ
Rx Interval (ms) min/max/avg	²Á¥,XÊÈhÊÉhÈKÈh
Tx Count	²ÁÉÕ BFD y[,XÊÐ
Tx Interval (ms) min/max/avg	²ÁÉÕXÊÈhÊÉhÈKÈh
Registered protocols	²Á±Xh*Á2O_
Uptime	²ÁÉÐ UP ,XÊÈ
Last packet	²Á±XÊÐ BFD y[Ê¢

ÏÎGQÐ		
	Q¸	ÉÄ
	-	-

ÏGÄÊ -

3.13 vrrp bfd

S6ÿÝX VRRP â BFD 6(|É master CÃ<ÊÉÄ› **no** ÊÉ6Ñ

vrrp *group-number* **bfd** *ip-addess*

no vrrp *group-number* **bfd** *ip-addess*

Ï-DAÊ		
	–Ð	ÉÄ
	group-number	*ÐÍ* VRRP 4Ê ü BFD # master CÃÊÉÄ
	ip-addess	*ÐÊ* IP

Ï5,Ð!5BÐ 5,Ê VRRP G*ü BFD Ê master ÉÑÃÊ<ÉÄ

ÏQþ yG!5Bã

Ï*Ô G!5BÊj.B‡• IP Ĥ,Xy¡X BFD Â±DÄG!5BÄ
Vp VRRP 4¡Ţ‹Ã<, LØEE¬AQG!5BÃÕÃ<,XF• IPÄ

ÏG!5B_Ð G!5BS6ÑVRRP G6(BFD h*ÈE› BFD ÐÃ<KÞXEÆÃÄ

```
5XLMLHFRQILJXUHWHUPLQDO
(QWHUFRQILJXUDWLRQFRPPDQGVRQHSHUOLQH(QGZKHQ7/=
5XLMLHFRQILJLQWHUIDFH)DVW(WKHUQHW
[illegible]
```

ÏÎGQÞ

Q¸	E Ä
bfd	**G5B** BFD Â±DÄ

ÏGÄÈ -

4 DLDP

4.1 clear dldp

Ì8 dldp Ø b up/down Ð,X4ªAuÇÈGÐ> 4ªAuÄ

clear dldp [**interface** *interface-name* [*ip-address*]]

Ï–DAè

–D	Ë.Ä
interface-name	ýÿÄ
ip-address	Ø IP

Ï5,Õ!5BÐ -

ÏQÿÐ (Mã

ÏS*Ô DLDP Ø,JÒÃ up/down Ð,X4ªAuÇÈ>Qÿ8Ô,Ø up/down 4ªAu ÐÈ JÇÿØAuÈÈôýÂÛ IP Ø8ôýØ
Ø up/down 4ªAu ÐÔýÂÛ IP È</Ì8,Ø up/down 4ªAu õ DÄ

Ï!5B_Ð _ 1Ø8,Ø up/down 4ªAu ÐÖ

```
5XLMLHFOHDUGOGS
```

_ 2Ø8 interface vlan 1 yØ up/down 4ªAu ÐÖ

```
5XLMLHFOHDUGOGSLQWHUIDFHVDQ
```

_ 3Ø8 interface vlan 1 yÇbÛÃÛ 10.83.132.1 ,X up/down 4ªAu ÐÖ

```
5XLMLHFOHDUGOGSLQWHUIDFHVDQ
```

ÏÎGQÐ

Q¸	Ë.Ä
-	-

ÏGÄè -

4.2 dldp

Ô DLDP ¥6ÑQ¸X **no 66Ë** IP ,X DLDP ¥6Ñ

dldp *ip-address* [**next-hop** *ip-address*] [**interval** *tick* | **retry** *retry-num* | **resume** *resume-num*]

no dldp *ip-address*

Ï-DAèð

–D	ÆÄ
ip-address	ó÷ IP Ä
next-hop *ip-address*	IP Ä
interval *tick*	5~6000Ê tickÈO 5 ,XHDick= 10msÅ
retry *retry-num*	1~3600Ä
resume *resume-num*	DOWN (Õ UP !ÈÔE4,Á DLDP ¥[DÆ¹–D8È 1~200Ä

Ö,Õ!5BÐ tick 100tickÆs Æetry-num 3 Èesume-num 3 Þ

ÜQþ yG!5BÆ

Ö*ÐÔ EÆG!5BQ¦ DLDP ¥6ÆÞ%JÒÆp,XÇÆ

Ü!5B_Ð _ 1ÕÛ 10.83.132.10 ,X DLDP ¥6Ñ

```
5XLMLHFRQILJ
5XLMLHFRQILJLQWHUIDFH0DQ
5XLMLHFRQILJLI9/$LSDGGUHVV
5XLMLHFRQILJLI9/$GOGS
```

_ 2Õ5%!‰Û 10.83.131.10 ,X DLDP ¥6Ñ

```
5XLMLHFRQILJ
5XLMLHFRQILJLQWHUIDFH0DQ
5XLMLHFRQILJLI9/$LSDGGUHVV
5XLMLHFRQILJLI9/$GOGSQH[WKRS
```

_ 3ÜKÁÛ 10.83.132.10 ,X DLDP ¥6Ñ

```
5XLMLHFRQILJ
5XLMLHFRQILJLQWHUIDFH0DQ
5XLMLHFRQILJLI9/$QRGOGS
```

ÏÜGQÞ

Q¸	ÆÄ
-	-

ÜÄèð -

4.3 dldp passive

A5B dldp Æ¼ÄÆQ¸X **no 6Æ5Þ**

dldp passive

no dldp passive

Ï-DAèê

–D	Ë-Ä
-	-

Ï5,Õ!5BÐ |ã

ÏQ¸ê yG!5Bã

Ï5*ê rL5%4È¿pØÃÊÐÑ DLDPÈÈEøÑ¥ ICMP Echo 9r)Ë¸ÏCÊêu
-GêXy[ÄÏ¥ØÃÊ5*ü ICMP Echo ØÑêX#D9.BAxy[,Xž
ÊÑ¸AÊÒÊÏC¸Xpè38V,ÐÐ¿AÛ CPU Cê,XÊÄ
!8ê¥ ICMP Echo ,XAÛ!5B|êáy ICMP Echo ,XAÛ!5Bä¦õ
ä

ÏG!5B_Ð G!5BDLDP ,Xê¦Ñ

```
5XLMLHFRQILJ
5XLMLHFRQILJLQWHUIDFHØDQ
5XLMLHFRQILJLI9/$LSDGGUHVVA5BØDQ ,X ,3
5XLMLHFRQILJLI9/$GOGSSDVVLM
```

ÏÛGQ¸Ð

Q¸	Ë-Ä
-	-

ÏGÄêê -

4.4 show dldp

/ DLDP ¦ê¥KG!5Bé¿4ªAuÇÄ

show dldp [**interface** *interface-name*] [**statistic**]

Ï-DAèê

–D	Ë-Ä
interface-name	ýêÄ
statistic	*4ªÇ*

Ï5,Õ!5BÐ -

ÏQ¸ê (Mã

Ï5*ê EËÊÛ statistic GK+9/¸ê¥ýêX4ªAuÇÂýá
/ÊÊ(MnýêKG!5B4ªAuÇÄ

ÏG!5B_Ð _ 1Ñê¥KG!5BÇÖ

```
5XLMLHVKRZOGS
,QWHUIDFH7ŠH,S1H[WKRS,QWHUØO5HWU5HVXPH6WDWH
```

```
9O3DVVLM8S
9O3DVVLM8S
9O3DVVLM8S
```

_ 2Ó· vlan 2 XG!5BÖ

```
5XLMLHVKRZGOGSLQWIDFHDQ
,QWHUIDFH7SH,S1H[WKRS,QWHUO5HWU5HVXPH6WDWH

9O3DVVLM8S
```

_ 3ÓX43uÖ

```
5XLMLHVKRZGOGSVWDWLVWLF
,QWHUIDFH7SH,SUHFRUGWLPH8SFRXQWRQFRXQW

9O3DVVLMKPV
9O3DVVLMGKPV
```

_ 4Ó· vlan 2 X43uÖ

```
5XLMLHVKRZGOGSVWDWLVWLFLQWHUIDFHDQ
,QWHUIDFH7SH,SUHFRUGWLPH8SFRXQWRQFRXQW

9O3DVVLMKPV
```

+!‰	A
	A1Ö></*0432Au up/down 0,X S z m S,X / ã
record-time	*y***d**h**m**sEG,X y ></HÈ d ></ h ></ m ></Ús

5 REUP

5.1 link state track

*ıÒ{ÃÕ¢Cµ¿Ä*ÆQ¸X **no EÍGÃÄ**

link state track [*num*]

no link state track [*num*]

Ï¤Ã	–D	Ë¤Ä
	num	JÒÃ.Ü[X ID

Ï5,Õ!5BÐ -

ÏQÃÐ <G!5Bã

Ï5*Ð NVÎÒÃ¢Cµ¿Ã5ÕÜ¹ıXC¢Cµ¿Ä

Ï!5B_Ð ÎÒ{ÃÕ¢Cµ˜

5XLMLHFRQILJOLQNVWDWHWUDFN

ÏÎGQÐ

Q¸	Ë¤Ä
link state group	**ÜÃ¹ıÃ**

Ï!ÄÃÐ -

5.2 link state group

ÜÃ¹ıXJÒ{ÃÕ¢Cµ¿Ä*ÆQ¸X **no EÍÜÃ¿Ä**

Ġ!5B_Đ

-	-

Ï5,Õ!5BÐ ý

ÏQÞÐ <G!5BÄ

ÏS*ÐÐ JÒÑÊÐ1Ò6,X MAC ><ÚÞÈ DBÄ
ÊDB#XÈÔÐ6E> MAC ><ÞXÞÊÔÐ1Ò6Ô
y MAC È,XÔÄ

ÏG!5B_Ð y MAC È
5XLMLHFRQILJPDFDGGUHVVWDEOHPRMXSGDWHUHFHLM

ÏÎGQÞÐ

Q¸	È.Ä
mac-address-table move update transit	**Ô6È.Õ** MAC È,XÞÊ

ÏGÄÊÐ -

5.5 mac-address-table move update receive vlan

G!5BÞÚ MAC È,X VLANÄ

mac-address-table move update receive vlan *vlan-range*

no mac-address-table move update receive vlan *vlan-range*

ÏÐÊÐ

–D	È.Ä
vlan-range	ÞÚ MAC È,X VLAN 8Ê

Ï5,Õ!5BÐ TAxý VLAN ÞÚ MAC ÈÄ

ÏQÞÐ <G!5BÄ

ÏS*ÐÐ E!8Q¸GKÄ VLAN ÞXÞÚ MAC ÈsÕÑKÞÚ MAC È,X VLAN ¡
ÊE› MAC ÞÈ[96ÄÔÔX3ÊgÈÒÊp,X/ÔÑÄ

ÏG!5B_Ð G!5BÞÚ MAC È,X VLAN
5XLMLHFRQILJQRPDFDGGUHVVWDEOHPRMXSGDWHUHFHLMÝDQ

ÏÎGQÞÐ

Q¸	È.Ä
mac-address-table move update receive	**Ô** REUP y MAC È,XÔÄ

ÏGÄÊÐ -

5.6 mac-address-table move update transit

ÊÕ MAC È£,XÔÄ

mac-address-table move update transit

no mac-address-table move update transit

Ï Ð à

–D	£Ä
-	-

Ï5,Õ!5BÐ 5,ÐÑÄ

ÏQÞÐ <G!5BÄ

Ï5*Ð ÄÒÑÊDB#ÝÈÒÝÐ,Xx6ÊÕ MAC È£,Xs

6Ñ

ÏG!5B_Ð Ô MAC È£

5XLMLHFRQILJPDFDGGUHVVWDEOHPRGHXSGDWHWUDQVLW

ÏÎGQÞ

Q¸	£Ä
mac-address-table move update transit	ÔÕ6£ÕÊÕ MAC È£,XÔÄ

ÏGÄÐ -

5.7 mac-address-table move update transit vlan

A5B0ÑÊÕ MAC È£,X VLANÄ

mac-address-table move update transit vlan *vid*

no mac-address-table move update transit vlan

Ï Ð à

–D	£Ä
vid	ÊÕ MAC È£,X VLAN IDÄ

Ï5,Õ!5BÐ TAx0ÑXTAx VLAN £ÕÊÕ MAC È£Ä

ÏQÞÐ yÐ5BÄ

Ï5*Ð JÒÐÊÕÊÕ MAC È£,Xs6ÐÒÝ MAC È£Ä

ÏG!5B_Ð G!5B0ÑÊÕ MAC È£,X VLAN

5XLMLHFRQILJLIPDFDGGUHVVWDEOHPRGHXSGDWHWUDQVLWÝDQ

ÏÎGQÞ

Q¸	£Ä

mac-address-table move update transit	**Ô** REUP ¥£Õ MAC È£,XÔÄ

ÏGÄà¤ -

5.8 mac-address-table update group

A5Bx6,X MAC È£ÄÄ

mac-address-table update group [*group-num*]

no mac-address-table update group

Ï¤à¤

–D	£ÄÄ
group-num	MAC È£,X ID

Ï5,Õ!5BÐ TÄx,X¤£¯ ID 1Ä

ù¡Ý¡,X MAC È£ÄÄ

ÏQ¸¤ yÄ5BÄ

Ï5*Ð¤ Ä MAC È£ÄÄXGÈ£x6,X!7DB£gÄ¤Ð MAC

È£,XA5BÄÕCÄ¡X0ÄÄ¸Ð MAC È£ÑÈ£6Ä

> DB£g,Xs6ÄÑ

ÏG!5B_Ð 0ÄÄ MAC È£¯

5XLMLHFRQILJLIPDFDGGUHVVWDEOHXSGDWHJURXS

ÏÎGQ¸Ð

Q¸	£ÄÄ
show mac-address-table update group	**k6¤¥** MAC È£ÇÄÄ

ÏGÄà¤ -

5.9 switchport backup interface

G!5BREUP ,XJÒÑ

switchport backup interface *interface-id*

no switchport backup

Ï¤à¤

–D	£ÄÄ
interface *interface-id*	ÑÒÃ¡X0Ã IDÄ

Ï5,Õ!5BÐ ù¡ÝJÒÑ

ÏQ¸¤ yG!5BÄÄ

Ï*Ð ê X0ÕÃD,X interface-id Í,X0ÃÒÑÃÒ×ÓpÈ
E6ÃÒ¸ÃXEgÄ

ÏG!5B_Ð A5BÞÒÃ5B fa 0/1 0Ã a 0/2 ÑÃ
5XLMLHFRQILJLQWHUIDFHID
5XLMLHFRQILJLIVZWFKSRUWEDFNXSLQWHUIDFHID

ÏÎGQÞ

Q¸	EÄ
show interface switchport backup	***k6ÞBÄ***

ÏGÄÃê -

5.10 switchport backup interface preemption

G!5BREUP ,XJÒÃ4s6Ñ

switchport backup interface *interface-id* **preemption mode** { **forced** | **bandwidth** | **off** }

switchport backup interface *interface-id* **preemption delay** *delay-time*

no switchport backup interface *interface-id* **preemption delay**

Ðê

–D	EÄ
interface *interface-id*	ÑÒÃX0Ã IDÄ
mode { **forced** | **bandwidth** | **off** }	***B4Õ*** **forced** ß **bandwidth** ß **off** ßÁ
delay *delay-time*	A5Bv4,XÊÊÃ

Ï,Õ!5BÐ v4s6ÑÃxGK(Ã
v4ÊTAx 35 /Ä

ÏGÄð -

5.11 switchport backup interface prefer

G!5BREUP ,XJÒÃ VLAN BéQ>5Ä*ÀQ¸X **no EÍÎ8G5BX** vlan BéQ1*+9Ä

switchport backup interface *interface-id* **prefer instance** *instance-range*

no switchport backup interface *interface-id* **prefer**

Ïð

Ï!5B_Đ /JÒÕ

```
5XLMLHVKRWQWHUIDFHVVWFKSRUWEDFNXSGHWDLO
6WFK%DFNXS,QWHUIDFH3DLUV
WFWLM,QWHUIDFH%DFNXS,QWHUIDFH6WDWH

*L*LWFWLM8S%DFNXS6WDQGE\
,QWHUIDFH3DLU*L*L
3UHHPSWLRQ0RGH2II
3UHHPSWLRQHODVHFRQGV
%DQGWGWK*L0ELWV*L0ELWV
```

ÏÎGQÐ

Q¸	Ë Ä
-	-

ÏGÄÕ -

5.13 show link state group

/JÒÕ ÕÏ‚ÐŸXÇÄ

show link state group *num*

ÏÕÕ

–D	Ë Ä
num	JÒÕÏ‚Ð˜ ID

Ï,Õ!5BÐ -

ÏÇÕ (M EXEC G!5BÕ

Ï*ÕÐ -

Ï!5B_Đ /JÒÕÏ‚Ð˜

```
5XLMLHVKRWLQNVWDWHJURXS
/LQN6WDWH*URXS6WDWXV(QDEOHG83
8SVWUHDP,QWHUIDFHV*L8S
RWVWUHDP,QWHUIDFHV*LW*LW
/LQN6WDWH*URXS6WDWXVLVDEOHGRW
8SVWUHDP,QWHUIDFHV
RWVWUHDP,QWHUIDFHV
8S,QWHUIDFHXSW,QWHUIDFHRWLV,QWHUIDFHGLVDEOHG
```

ÏÎGQÐ

Q¸	Ë Ä
-	-

ÏGÄÕ -

5.14 show mac-address-table update group

/È£XÇÄ

show mac-address-table update group [**detail**]

Ð	–D	£Ä

6 RLDP

6.1 debug rldp

Ô rldp áAʌĈÄQ¸X no 6ĒKÁʌĈÄ

debug rldp [**packet | event | error**]

undebug rldp [**packet | event | error**]

–D	Ē£Ä
packet	¥ rldp y[,XAʌąĈÄ
event	0(ĝXAʌąĈÄ
error	Ē/ĝ0Ą¸XAʌąĈÄ

-

(M EXEC G!5Bã

-

-

Q¸	Ē£Ä
-	-

-

6.2 rldp detect-interval

S*ʌQ¸G!5B RLDP 0ĝĈ¥[,XKÈhÄ

rldp detect-interval *interval*

no rldp detect-interval

–D	Ē£Ä

Ğ!5B_Đ	G!5BvѢÈh 5s	
	5XLMLHFRQILJUOGSGHWHFWLQWHUƁO	
ÏĜGQÞ	Q¸	ĿÄ

ÏQþÐ <G!5BÄÅ

Ï*ûÐ ¥¼ RLDP ÐÃ RLDP !6Ñ» Ä

Ï!5B_Ð 5XLMLHFRQILJUOGSHQDEOH

ÏÎGQÞÐ

Q¸	Ä
rldp port	**G5B0Ã** RLDP s6Ñ

ÏÄÅÐ -

6.5 rldp port

AÐQG!5B0Ã rldp ÐÐZO_LpÐÐ

rldp port { **unidirection-detect | bidirection-detect | loop-detect** } { **warning | shutdown-svi | shutdown-port | block** }

no rldp port { **unidirection-detect | bidirection-detect | loop-detect** }

ÏÐÅÐ

–D	Ä
unidirection-detect	)åÒÃO_
bidirection-detect	ÃO_
loop-detect	ÃO_
warning	Ð
shutdown-svi	shutdown 0Ã svi
shutdown-port	shutdown 0Ã
block	GKÁÃ:4E¥Ð

ï,Õ!5BÐ -

ÏQþÐ yG!5BÄÅ

Ï*ûÐ ¥¼ RLDP ÐÐÃ RLDP !6ÑK0*Ä

Ï!5B_Ð ü fas 0/1 Ð!5BZ rldp ÐÐZO_)ÇÃpÐÐKÁÃ4E¥Ð

5XLMLHFRQILJLQWHUIDFHIDV

5XLMLHFRQILJLIUOGSSRUWORRSGHWHFWEORFN

ÏÎGQÞÐ

Q¸	Ä
rldp enable	**<** rldp G!5BQ¸

ÏÄÅÐ -

6.6 rldp reset

AŒQS¥• **rldp shutdown ê disable** þ**ÃGÉ¯9** rldp Ä

rldp reset

Ïèâà

–D	ÉÄ
-	-

Ï5,Ã!5BÐ -

ÏQþ (MÄ

ÏŠ*Ô -

Ï!5B_Ð 5XLMLHUOGSUHVHW

ÏÎGQÞ

Q¸	ÉÄ
rldp enable	Rldp <G!5BQ¸

ÏGÄâ -

6.7 show rldp

/ rldp ,X0ÃÄ

show rldp [**interface** *interface-id*]

Ïèâà

–D	ÉÄ
interface *Interface-id*	û0Ã

Ï5,Ã!5BÐ -

ÏQþ (M EXEC G!5Bã

ÏŠ*Ô -

Ï!5B_Ð -

ÏÎGQÞ

Q¸	ÉÄ
-	-

ÏGÄâ -

7 TPP

7.1 show tpp

Ï!5B_Đ ÔKÁ%Lxs6Ñ

8 GRTD

8.1 diagnostic bootup level

A5B bootup Å© (CKÅ)¸X14{Ä

diagnostic bootup level { **bypass | minimal | complete** }

Ï Ð	–D	Ł Ä
	GK+ **bypass**	ß > bootup Å©
	GK+ **minimal**	

Ï¨Qþ <G!5Bã

Ï¨S*Ð AÆQ¸3¼lu)ÓÆ5ÞXÁ¼ÉÑ¼lu)ÓÄ

Ï¨G!5B_Ð _ 1ÐÄ©Ê¸5DA5B 1000 5Ö

UXLMLHFRQILJGLDJQRVWLFHMQWORJVL]H

_ 2ÐÄ©Ê¸5D6ã¸Õ

UXLMLHFRQILJQRGLDJQRVWLFHMQWORJVL]H

ÏÎGQÞ

Q¸	Ë¨Ä
show diagnostic events	**Ê**

Ï¨GÄÞ -

8.3 diagnostic loopback-test

A5B0ÃÊX0Ã ID Ð)ÑÞÄ

diagnostic loopback-test [**slot** *slot_id* [**sub_sysytem** *subsys_id*]] **port** { **all | range** *potr_range* | *port_id* } **loopback** { **mac | phy | none** }

Ï-DAÞ

–D	Ë¨Ä			
range_value	0Ñ	1/1-24þ4!,X	1 Ñ	IDÄ

slot

ÏĈGQÐ	Q¸	ÆÄ
	-	-

-

ĞGÄĐ -

8.4 diagnostic monitor active

úu)Ê45ÔÑM,X9¸ŧ^(Ð5B%ŧÐ*Q¸X no 6Ã5B/U!6(Š

Ã

bˆ

ЬЗ¸Õ!5BÐ	)Ø¥ABÊÕ¼Ê{*Á
ÜQþÐ	<G!5Bã
Ь*ÐÐ	-
Ü!5B_Ð	_ 1Ø5B)Ø¥ABÊÕ¼Ê{ÄÄ ¶
	_ 2Ø5B)Ø¥ABÊÕ¼Ê{ UXLMLHFRQILJQRGLDJQRVWLFPRQLWRUVVORJ

ÏÜGQÐ		
	Q¸	ÊÄ
	-	-

ÜÄÄÐ	-

8.7 diagnostic monitor threshold

A5B¶u)Ø¥5¤ABM9¸¥¥AÊ4ÁBÜXÐÐÄ

diagnostic monitor threshold [**slot** *slot_id* [**sub_sysytem** *subsys_id*]] *slot_s_id*

Ï¨G!5B_Ð _ 1ÔÕ5 2 ,XÁÑM,X9¸¢ÆÉ4ÁÉ¸XÂÐÔA5B 50Ä

```
UXLMLHFRQILJGLDJQRVWLFPRQLWRUWKUHVKROGVORWWHVWDOOIDLOXUHFRXQW
UXLMLHFRQILJ
7KHWHVWFDQQRWEHXVHGDVKHDOWKPRQLWRULQJWHVW
7KHWHVWFDQQRWEHXVHGDVKHDOWKPRQLWRULQJWHVW
```

_ 2Ô BOX A¸ÙXÁÑM,X9¸¢ÆÉ4ÁÉ¸XÂÐÔ65¸Õ

```
UXLMLHFRQILJQRGLDJQRVWLFPRQLWRUWKUHVKROGWHVWDOO
```

ÏÎGQÐ

Q¸	Ë¨Ä
show diagnostic content	Ø

Ï¨GÄÃè -

8.8 diagnostic packet

A5BÃèÊÇXKSzÃÉÐÃQ1ÇÊÃ

diagnostic packet [**slot** *slot_id* [**sub_sysytem** *subsys_id*]] [**length** *lengtn_size*] [**num** *num_count*] [**time_out** *tick_count*]

Ï-DAÃè

–D	Ë¨Ä
slot *slot_id*	ÑÕÄ
sub_sysytem *subsys_id*	ÄÉ 0-1Ä ÿÐ **show version** Ø cpu idÄ
length	ÄÄ
num	ØÄ
time_out	ØÕ tickÄ

Ï¨Õ,Õ!5BÐ -

Ï¨QÐ (Mã

Ï¨Ð **diagnostic packet** Õ

Ï¨G!5B_Ð _ 1Ô5BÑ 1 ÄÄDÄ

```
UXLMLHGLDJQRVWLFSDFNHWVORWOHQJWKQXPWLPHRXW
```

ÏÎGQÐ

Q¸	Ë¨Ä
-	-

Ï¨GÄÃè -

8.9 diagnostic schedule

A5BÐu)Ê45»ÆNMAuæ¢XÊÈ<Ä

diagnostic schedule [**slot** *slot_id* [**sub_sysytem** *subsys_id*]] **test** { **all |** *test-id* | **range** *test-range* } { **daily** *hh:mm* | **on** *year month day_of_month hh:mm* | **weekly** *day_of_week hh:mm* }

no diagnostic schedule [**slot** *slot_id* [**sub_sysytem** *subsys_id*]] **test** { **all |** *test-id* | **range** *test-range* } { **daily** *hh:mm* | **on** *year month day_of_month hh:mm* | **weekly** *day_of_week hh:mm* }

Ï–DAè

–D	Ë
slot *slot_id*	Ñ
sub_sysytem *subsys_id*	0-1 **show version** cpu id
daily	h:mm
weekly	ay_of_week <h:mm
on	

ï5,Õ!5BÐ ÆNM,XAuæÊÈ<5,ÑÑNÄ

ÏQ¸ <G!5BÆ

ÏÓ*Ð ÃÃ5B¸,X¸ÊÈ> ÆÄ
ÃÃ5B¸X¸ÊÈ> ÆÄ
ÃÃ5B¸£,X¸ÊÈ> ÆÄ
ÓÆNMÊÃÑUèÊÈ> AuæÄ
ÆG!5BÊÈXÆAuèÊÈG!5BÊÈWÃXÆAuÆe

ÏG!5B_Ð _ 1 5 2 ,XÆNM 1Ã 2 A5B! 10 & 10 É> Æ©
UXLMLHFRQILJGLDJQRVWLFVFKHGXOHVORWWHVWUDQJHGDLO\

_ 2 5 2 ,XÆNM 1 A5B 2010 H 9 Ü 10 Ë10:10 E> Æ©
UXLMLHFRQILJGLDJQRVWLFVFKHGXOHVWRQVHSWHPEHU

_ 3 5 2 ,XÆNM 1 A5B!£,X 10:10 E> Æ©
UXLMLHFRQILJGLDJQRVWLFVFKHGXOHVWÆHNOÆGQHVGD\

_ 4 5 2 ,XÆNM 1 ,X Æ<Ë,X 10:10 E> Æ©
UXLMLHFRQILJQRGLDJQRVWLFVFKHGXOHVORWWHVWÆHNOÆGQHVGD\

ÏÎGQÐ

Q¸	Ë
show diagnostic schedule	

ÏGÄè -

8.10 diagnostic start

Ø¸> ÆÄ

diagnostic start [**slot** *slot_id* [**sub_sysytem** *subsys_id*

ÏQþÐ (Mã

ÏS*ÐÐ -

ÏG!5B_Ð _ 10Ï645 5 ,XQ¸> A¥©
UXLMLHGLDJQRVWLFVWRSVORW

ÏÎGQÞÐ

Q¸	ÆÄ
-	-

ÏGÄÐÐ -

8.12 show diagnostic bootup

/ bootup Æ1©4{Ä
show diagnostic bootup level

Ï–DAÐÐ

–D	ÆÄ
level	bootup Æ1©4{

Ïõ,Õ!5BÐ -

ÏQþÐ (Mã

ÏS*ÐÐ -

ÏG!5B_Ð UXLMLHVKRZGLDJQRVWLFERRWXSOHYO
&UUHQWERRWXSGLDJQRVWLFOHYHO&RPSOHWH

ÏÎGQÞÐ

Q¸	ÆÄ
-	-

ÏGÄÐÐ -

8.13 show diagnostic content

/1u)Śe5,XA¥ÇÈ1u)Śe5,X¥ÑMÃÑM2ÃÑM,XG!
5B1ÇÄ
show diagnostic content [**slot** *slot_id* [**sub_sysytem** *subsys_id*]]

Ï–DAÐÐ

–D	ÆÄ
sub_sysytem *subsys_id*	¥Æ 0-1þ **show version** Æ cpu idÄ

```
393HUSRUWWHVW3HUGHLFHWHVW1$
'1LVUXSWLMWHVW1RQGLVUXSWLMWHVW1$
,1RWDKHDOWKPRQLWRULQJWHVW1$
))L[HGPRQLWRULQJLQWHUYDOWHVW1$
(6DVHQDEOHGPRQLWRULQJWHVW1$
$0RQLWRULQJLQDFWLM0RQLWRULQJLQLQDFWLM1$
<2.HWHVW1RQNHWHVW1$
53RZUGRZQOLQHFDUGVDQGHHGUHORDGPDLQERUG1$
.5HTXLUHUHVHWWLQJWKHOLQHFDUGDIWHUWKHWHVWFRPSOHWHG1$

WHVWLQWHUYDO7KUH
,7HVW1DPH$WWULEXWHVGDKKPPVVVKROG

3RUW/RRSEDFN7HVW!03QRWFRQILJ1$
,QEDQG6HOI7HVW!QRWFRQILJ1$
0DF6HOI7HVW!QRWFRQILJ1$
7HVW&OG!;QRWFRQILJ1$
7HVW3&;
7HVW1DQG)ODVK!QRWFRQILJ1$
7HVW1RU)ODVK!QRWFRQILJ1$
7HVW,&QRWFRQILJ1$
7HVWGU!QRWFRQILJ1$
00&,,

LDJQRVWLFWHVWVXLWHDWWULEXWHV
0&LQLPDOERRWXSOHMOWHVW&RPSOHWHERRWXSOHMOWHVW1$
393HUSRUWWHVW3HUGHLFHWHVW1$
'1LVUXSWLMWHVW1RQGLVUXSWLMWHVW1$
,1RWDKHDOWKPRQLWRULQJWHVW1$
))L[HGPRQLWRULQJLQWHUYDOWHVW1$
(6DVHQDEOHGPRQLWRULQJWHVW1$
$0RQLWRULQJLQDFWLM0RQLWRULQJLQLQDFWLM1$
<2.HWHVW1RQNHWHVW1$
53RZUGRZQOLQHFDUGVDQGHHGUHORDGPDLQERUG1$
.5HTXLUHUHVHWWLQJWKHOLQHFDUGDIWHUWKHWHVWFRPSOHWHG1$

WHVWLQWHUYDO7KUH
,7HVW1DPH$WWULEXWHVGDKKPPVVVKROG

2XWEDQG6HOI7HVW!0QRWFRQILJ1$
,QEDQG6HOI7HVW!&QRWFRQILJ1$
0DF6HOI7HVW!QRWFRQILJ1$
7HVW&OG!&QRWFRQILJ1$
7HVW3&&QRWFRQILJ1$
```

```
7HVW1DQG)ODVK!3ĢQRWFRQILJ1$
7HVW1RU)ODVK!3ĢQRWFRQILJ1$
7HVW,Ķ&QRWFRQILJ1$
7HVWGU!ĢQRWFRQILJ1$
,Q%DQG&DQQHO7HVW!1
2XW%DQG&DQQHO7HVW!1
```

+!‰	AĚ
ID	ÆÑM id
Test Name	ÆÑMÆÄ
Attributes	ÆÑM2Ê4ÀÈË5<!5BÛÄ
test interval	ÆÊÈÈhÈb2Ï9¸¼Æ©
threshold	¸¼ÆÑMÊÙD

ÏĴGQĢÐ

Q¸	ĖÄ
diagnostic monitor interval	A5B,¼ÊÈÈh
diagnostic monitor threshold	**ÆBĢÛ**

ĬGÄÈ -

8.14 show diagnostic description

/ÆÑM,XA4ÀÈ

show diagnostic description [

ÏĈGQÞ	Q¸	Ł.Ä
	diagnostic event-log size	A5B_Ê¸Þ

ĬGÄß -

8.16 show diagnostic result

8.17 show diagnostic schedule

/Ø¿u)Ó¼5A5BQ,XAuæÊÈ<Ä

show diagnostic schedule [**slot** *slot_id* [**sub_sysytem** *subsys_id*]]

Ï–DAèð

–D	ÆÄ
slot *slot_id*	¶
sub_sysytem *subsys_id*	¾ÜÕÈ 0-1þ **show version** ¶ cpu idÄ

Ï5,Õ!5BÐ -

ÜQþð (Mã

Ü5*Ðð -

Ü!5B_Ð

```
UXLMLHVKRØLDJQRVWLFVFKHGXOHVORWDOO
XUUHQW7LPH 87XL2FW
LDJQRVWLFIRU0RGXOH
6FKHGXOH
7REHUXQRQ-DQXDU\
7HVW,VWREHH[HFXWHG
6FKHGXOH
7REHUXQRQ6HSWHPEHU
7HVW,VWREHH[HFXWHG
LDJQRVWLFIRU0RGXOHLVQRWVFKHGXOHG
LDJQRVWLFIRU0RGXOHLVQRWVFKHGXOHG
LDJQRVWLFIRU0RGXOHLVQRWVFKHGXOHG
```

ÏÎGQÐ

Q¸	ÆÄ
diagnostic schedule	A5B1u)Ó¼5,XAuæÊÈ

ÜÄèð -

8.18 show diagnostic status

/!ÝÆÆ(Õ

show diagnostic status

Ï–DAèð

–D	ÆÄ
status	!Æ(Õ

Ï5,Õ!5BÐ -

ÏQþÐ (Mã

Ï*ÐÐ -

Ï!5B_Ð UXLMLHVKRZGLDJQRVWLFVWDWXV
%8%RRWXSLDJQRVWLFV+0+HDOWK0RQLWRULQJLDJQRVWLFV
22QHPDQGLDJQRVWLFV6&6FKHGXOHGLDJQRVWLFV

6ORWHVFULSWLRQXUUHQW5XQQLQJ7HVW5XQE\

0*76)31$$$
0*76)31$$$
00&,7HVW1DQG)ODVK2'

+!‰	Aè
Slot	Ñ
Description	45tu)Ó,Xä
Current Running Test	!7E¤ ,X#Ñ
Run by	2b#Aã

ÎÏGQÐ

Q¸	E
-	-

ÏGÄè -

9 IP Event Dampening

9.1 dampening

pQX ip event dampeningÄ_ Ê6ÑÄQ¸X **no EÍGjX** ip event dampening s6Ñ

dampening [*half-life-period* [*reuse-threshold suppress-threshold max-suppress* [**restart** [*restart-penalty*]]]]

no dampening

Ï-DAÐ

–D	EÄ
half-life-period	Ð1-30> ÈAx 5sÄ
reuse-threshold	ÐÐ1-20000>ÈAx 1000Ä
suppress-threshold	eÐ1-20000> ÈAx 2000Ä
max-suppress	óÑ1-255> ÈAx half-life-period ,X 4 Ä
restart *restart-penalty*	È1-20000> ÈAx 2000Ä

Ъ,Õ!5BÐ

5,Ð¤=ÐÐpÐ¤ÐK9N=

show interface dampening	**ý**es6Ñ

Ï*Ð 8ÊZ interface-idÐÊy¡X dampening ÇÄ

ÏG!5B_Ð /ý¡X dampening A4ÇÄ

```
5XLMLHVKRWQWHUIDFHGDPSHQLQJ
(WKHUQHW
)ODSV3HQDOW6XSS5HXVH7P+DOI/5HXVH96XSS90D[67P0D[35HVWDUW
)6(
```

+!‰	Aè
Flaps	y5ÈØ
Penalty	y!5‰ã
Supp	!ú¤e
ReuseTm	NXAuÞ8eEÞÐ(s)
HalfL	>DÓ(s)
ReuseV	Þ8eKÞ¼$
SuppV	ÐKÞ¼$

10.2 action counter

ü SEM G!5BßG!5B1*+9|0Ê SEM QÁuD<ÄQ¸X no 6ãû8ûÛR,X> |Ä

action *label* **counter name** *counter-name* **value** *counter-value* **op** { **dec** | **inc** | **nop** | **set** }

no action ***label***

Ï-DAßà

–D	ÆÄ
label	>|ÛR
name *counter-name*	0ÁADÁ
value *counter-value*	0SÞ
op { **dec**	**inc**	**nop**	**set** }	0SÞ

ï5,Õ!5BÐ 5,ß!5B> |

ÜQþ SEM G!5Bã

Ï5*ûÐ –D **name** *counter-name* û¸XAuD<ÈÔÈÞ¸S*GÃ

Ü!5B_Ð ¸ÞÁogin faile ÆAuD< Authenticate_Faile t 1Ä

```
5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB
5XLMLHFRQILJDSSOHWHHMQWWDJPRQLWRUBORJVVORJSDWWHUQORJLQIDLOH
5XLMLHFRQILJDSSOHWDFWLRQFRXQWHUQDPHXWKHQWLFDWHB)DLOHRSLQFHOXH
5XLMLHFRQILJDSSOHWFRPPLW
5XLMLHFRQILJDSSOHWH[LW
```

ÏÎGQÞ

Q¸	ÆÄ
smart manager applet	**nÔÞ** SEM 1*+9

ÜÄßà -

10.3 action exit

ü SEM G!5BßG!5B1*+9|0ÆÈ1*+96ÈÃ5BE(ÕÞQ¸X no 6ãû8ûÛ

1R,X> |Ä

action *label* **exit** [*result*]

no action *label*

Ð

–D	ÆÄ
label	> |,XÛR
result	Exit ,XEÈÆAx 1

ï5,Õ!5BÐ TAxÞ1*+9Ê² 1Ä

ÏQ¸Ð SEM G!5Bã

Ï5*Ð ê Ð È*+9,XÇ1Y*+9Ç ÄB1*+9,XE³ 1 4Á ÏXpE¨
² 0 Ç!6E¤ Ä 4Á E¤ Ä
1*+9,XE³ action exit ÇÈEAxÐ‰ 1Ä

ÏG!5B_Ð _ 1ê Ð ÐÑ Q¸ È Eg9 write memoryÈJ!6*ÇJ/*ü

```
5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB
5XLMLHFRQILJDSSOHWHMQWWDJPRQLWRUBFOLFOLSDWWHUQØLWHPHPRUVQFHV
5XLMLHFRQILJDSSOHWDFWLRQSXWVFDQQRWGRWKLV
5XLMLHFRQILJDSSOHWDFWLRQH[LW
5XLMLHFRQILJDSSOHWFRPPLW
5XLMLHFRQILJDSSOHWH[LW
```

_ 2ê Ð ÐÑ Q¸ È Eg9line ÈQ¡¸ aaa new-model È

```
> *ÇÄ
5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB
5XLMLHFRQILJDSSOHWHMQWWDJPRQLWRUBFOLFOLSDWWHUQOLQHVQFHV
5XLMLHFRQILJDSSOHWDFWLRQFOLFRPPDQGHQDEOH
5XLMLHFRQILJDSSOHWDFWLRQFOLFRPPDQGDDDQHØRGHO
5XLMLHFRQILJDSSOHWFRPPLW
5XLMLHFRQILJDSSOHWH[LW
```

ÏÎGQ¸Ð

Q¸	E Ä
smart manager applet	nÎQ¸ ,X SEM 1*+9

ÏGÄê Ð -

10.4 action publish-event

ü SEM G!5Bê G!5B1*+9|0È Application Event È ÇÕÄQ¸X no 6ãÜ 8ÛÛ
1R,X> |Ä

action *label* **publish-event** **subset** *subset-id* **type** *event-type* [**arg1** *argument-data*] [**arg2** *argument-data*] [**arg3** *argument-data*] [**arg4** *argument-data*]
no action *label*

ÏDAê Ð

–D	E Ä
label	>Ø
subset *subset-id*	¥ Ø
type *event-type*	¥ Ø
arg1 *argument-data*	_Ø 1
arg2 *argument-data*	_Ø 2
arg3 *argument-data*	_Ø 3

arg4 *argument-data*	_ 4

ï5,Õ!5BÐ 5,ê!5B> |

ïQ¸ SEM G!5Bã

ïS*Ô !8G!5Bâ event application G!S*Ê> action publish-event ,X1*+9{*Ê J subset ` type ,ÏÈX event application Ê

ïG!5B_Ð ,¢ action publish-event ¥X_ÊS š ID 100È O_ ID 50Ê ¸)«

```
5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB
5XLMLHFRQILJDSSOHWHHMQWWDJPRQLWRUBHHMQWQRQH
5XLMLHFRQILJDSSOHWDFWLRQSXEOLVKHMQWVXEVHWWSHDUJSDUDB
5XLMLHFRQILJDSSOHWFRPPLW
5XLMLHFRQILJDSSOHWH[LW
```

ïÎGQ¸Ð

Q¸	E Ä
smart manager applet	**nÎ¸ X** SEM 1*+9
event application	

ïGÄÊ -

10.5 action reload

ü SEM G!5BÊ G!5B1*+9|0È AÛ0ÄÊQ¸X no 6Ê ûÛ8ûÛR,X> |Ä

action *label* **reload**

no action *label*

ïÐÊ

–D	E Ä
label	>

ï5,Õ!5BÐ 5,ê!5B> |

ïQ¸ SEM G!5Bã

ïS*Ô -

ïG!5B_Ð H¥ C‡ 20M ÊÛ¸AÛ

```
5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB
```

ÏĜQĢÐ	Q¸	ĿÄ

smart manager applet

Ï–DAê

–D	Ë Ä
label	> |
priority *priority-level*	
msg *msg-text*	
facility *string*	

ï,Õ!5BÐ 5,ê!5B> |

ÜQê SEM G!5Bã

Ü*ê -

Ü!5B_Ð H cpu ÿ)[CË› 95%È),Ä

```
5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB
5XLMLHFRQILJDSSOHWHMQWWDJPRQLWRUBFSXVVPRQFSXVFRSHVVWHPHQWURSJWHQWUVO
5XLMLHFRQILJDSSOHWDFWLRQVVORJPVJVVWHPEXV\
5XLMLHFRQILJDSSOHWFRPPLW
5XLMLHFRQILJDSSOHWH[LW
```

4 32 Action syslog l

ÎÜGQÞ

Q¸	Ë Ä
smart manager applet	**nbê** SEM 1*+9

Ü!ÄÃê -

10.8 action wait

ü SEM G!5Bê!5B1*+9|0È1*+96V0ÐÄQ¸X no 6ê8ûR,X> |Ä

action *label* **wait** *wait-seconds*

no action *label* **wait**

Ï–DAê

–D	Ë Ä
label	> |
wait-seconds	

ï,Õ!5BÐ 5,ê!5B> |

ÜQê SEM G!5Bã

Ü*ê -

Ġǃ5B_Đ ≥ **show arp** ₨ **clear arp-cache** 1**Y** 5 /ƔsÄ

```
5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB
5XLMLHFRQILJDSSOHWHMQWWDJPRQLWRUBFOLFOLSDWWHUQVKRØUSVQFHV
5XLMLHFRQILJDSSOHWDFWLRQFOLFRPPDQGHQDEOH
5XLMLHFRQILJDSSOHWDFWLRQØLW
5XLMLHFRQILJDSSOHWDFWLRQH[LW
5XLMLHFRQILJDSSOHWFRPPLW
5XLMLHFRQILJDSSOHWH[LW
```

ÏĜGQÞ

10.10 description

ü SEM G!5BB!5B SEM 1*+9,XE[ÄQ¸X no 6ÈU8 SEM 1*+9,XE[Ä

description *string*

no description

Ï-DAÈ	–D	E[Ä
	string	È SEM 1*+9,X[[

Ï,Õ!5BÐ 5,È!5B SEM 1*+9,XE[

ÏQÈ SEM G!5Bã

Ï*È

, ¨

Ï!5B_Ð _ 1Ö!5B! SEM 1*+9 E[Descrption_For_SEM_Applet

5XLMLHFRQILJDSSOHWGHVFULSWLRQHVFUSWLRQB)RUB6(0B$SOHW

_ 2È8! SEM 1*+9E[

5XLMLHFRQILJDSSOHWQRGHVFULSWLRQ

ÏGQÐ	Q¸	E[Ä
	smart manager applet	**nÎ** SEM 1*+9

ÏÄÈ -

10.11 event application

ü SEM G!5BB!5B,¥<,¥ **action publish-event** no 6È8Û

È X_E

event tag *event-name* [**correlate** { **andnot** | **and** | **or** }] **application subset** *subset-id* **type** *event-type*

no event tag *event-name*

Ï-DAÈ	–D	E[Ä
	event-name	_È
	correlate { **andnot** | **and** | **or** }	></È2Ïand ></È2Ïor ></È2Ïandnot ></J2Ï
	subset *subset-id*	È ID
	type *event-type*	È ID

Ï,Õ!5BÐ 5,È!5B_Ê

ÜQþÐ SEM G!5Bã

Ü*ÐÔ event application ¢¸¼ action publish-event ¥X_ÊÐ*+9PE|Ô*+9,X,ÂXÄ *subset-id ` event-type* *ùÐX ¥Ê *subset-id ` event-type* PolicyÄ ÃÕ*¡X event GÊÐ

GÊ	*Ê
_application_subset	¥Mn_ÊX1š
_application_type	¥Mn_ÊX2O_
_application_data1	¥ÊX–D 1
_application_data2	¥ÊX–D 2
_application_data3	¥ÊX–D 3
_application_data4	¥ÊX–D 4

Ü!5B_Ð ,¥ action publish-event ¥X_Ê1š ID 100È2O_ ID 50È¸¼

```
5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB
5XLMLHFRQILJDSSOHWHMQWWDJPRQLWRUBHMQWDSSOLFDWLRQVXEVVWHPWSH
5XLMLHFRQILJDSSOHWDFWLRQVVORJPVJ+DMHMQWVXEVHWBDSSOLFDWLRQBVXEVHWWSH
BDSSOLFDWLRQBWSH
5XLMLHFRQILJDSSOHWFRPPLW
5XLMLHFRQILJDSSOHWH[LW
```

ÏÎGQÞÐ

Q¸	Ê.Ä
smart manager applet	**nôbÞX** SEM 1*+9
action publish-event	**¥** application event ,X action

ÜGÄÃè -

10.12 event cli

ü SEM G!5BÈ!5B,¥<,¥Q¸> ÄÐQ¸X no 6ãüô8hÛÞX_Ê

event tag *event-name* [**correlate** { **andnot** | **and** |**or** }] **cli pattern** *regular-expression* [**sync** { **yes** [**default** *wait-time*] | **no skip** { **yes** | **no** } }] [**mode** *variable*] [**occurs** *num-occurrences*] [**period** *period-value*]

no event tag *event-name*

Ï–DAè

–D	Ê.Ä
event-name	_Ê
correlate { **andnot**	**and**	**or** }	þ_Ê-ÝÊÜÐX5Ê2Ïand ></È2Ïor ></È2Ïandnot ></JÈ2Ï
pattern *regular-expression*	Ê
sync { **yes**	**no** }	ÞÊ ¸Ä

skip { **yes** | **no** }	no
default *wait-time*	30 /¦
mode *variable*	
occurs *num-occurrences*	Event LØ,XG! ÐÄA x 1
period *period-value*	occurs <ÊE› period-value ,X occurs 0 CÊccurs 1 ÊB–DÄ

mode EMÚQ¿pEg9ÊEMÈ>GÄ

default EMÚQ¿Y9E=4ÊEMÈ¿¼ **sync** EM **yes** Ê

Ä

occurs EM_Ê9LÔ¿ÚXpôÜÊ' *num-occurrences* È

Ê

period EM **occurs** EMÚÊ

SEM SEM Action cli ž Ò ž Ò , ž Ò **pattern** ± ÷ ž Ò , ÷ ž Ò ,

enable

configure terminal

[no] smart manager applet

Exit

SEM ÉKQÄ

ÃS*¡X event GÉÐ

GÊ	*Èè
_cli_msg	*Èg9,XQ¿ Ý
_cli_msg_count	*Èg9,XQ¿ KSz
_cli_mode	*¡XQõ

Ò!5B_Ð _ 1ÜQ¿ Eg9ÈEg9 **show ip route** Ê

5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB

5XLMLHFRQILJDSSOHWHMQWWDJPRQLWRUBLQSXWFOLSDWWHUQVKRZSURXWHVQFQRVNLSQR

5XLMLHFRQILJDSSOHWDFWLRQVVORJPVJVKRZSURXWHUXQQLQJ

5XLMLHFRQILJDSSOHWDFWLRQ[LW

5XLMLHFRQILJDSSOHWFRPPLW

5XLMLHFRQILJDSSOHWH[LW

_ 2ÜQ¿ Eg9ÈEg9 **shutdown** Ê6ÄÄ

5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB

5XLMLHFRQILJDSSOHWHMQWWDJPRQLWRUBLQSXWFOLSDWWHUQVKXWGRZQPRGHLQWHUIDFH

5XLMLHFRQILJDSSOHWDFWLRQSXWVFDQQRWGRWKLV

5XLMLHFRQILJDSSOHWDFWLRQ[LW

5XLMLHFRQILJDSSOHWFRPPLW

5XLMLHFRQILJDSSOHWH[LW

ÎÒGQÐ

Q¸	ÊÄ
smart manager applet	**nÒÜ** SEM 1*+9

ÒÄÈ -

10.13 event counter

ü SEM G!5B6!5B,¥<,¥ SEM AuD<ÄQ¸X no 6 0 8 X_

event tag *event-name* [**correlate** { **andnot** | **and** | **or** }] **counter name** *counter-name* **entry-op** *operator* **entry-val** *entry-value* **exit-op** *operator* **exit-val** *exit-value*

no event tag *event-name*

Ï-DA

–D	E
event-name	
correlate { **andnot** | **and** | **or** }	nd r andnot J
name *counter-name*	
entry-op *operator*	eq 1b ge 1b gt le 1b lt ne 1b

ËG!5B_Ð G!5B1*+9,¥AuD< Test_CounterÈ Test_Counter ,Xõ1b 10 ¥*+9A),¥
Test_Counter 5B0È Test_Counter ,Xõ 5 Ê6¡¥Ä

```
5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB
5XLMLHFRQILJDSSOHWHHMQWWDJPRQLWRUBFRXQWHUFRXQWHUQDPH7HVWBRXQWHUHQWUSJH
HQWUÐOH[LWRSJWH[LWÐO
5XLMLHFRQILJDSSOHWDFWLRQFRXQWHUQDPH7HVWBRXQWHURSVHWÐOXH
5XLMLHFRQILJDSSOHWFRPPLW
5XLMLHFRQILJDSSOHWH[LW
```

ÏÎGQÐ

Q¸	Ë Ä
smart manager applet	**nÎ¸** SEM 1*+9
action counter	

ËGÄ¥ -

10.14 event cpp

ü SEM G!5B¥G!5BÎ CPP ,X_ÊQ¸X no 6¥ü8Î¥Ä X_Ê

event tag *event-name* [**correlate** { **andnot** | **and** | **or** }] **cpp parameter** { *counter-name* | **any** } **type** { **pps** | **total** | **drop** } **op** *operator* **value** *value* [**slot** { *slotid* | **mboard** }] **poll-interval** *poll-int-value*
no event tag *event-name*

Ï–DA¥

Ï*Ð
Ã*¡X event G£Ð

G£	*Ee
_cpp_slot	#XS!5B
_cpp_parameter	y[2O_
_cpp_type	y[AuD2O_
_cpp_value	rL,X

Ï!5B_Ð

```
5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB
5XLMLHFRQILJDSSOHWHMQWWDJHMQWBFSSSDUDPHWHUDQWSHGURSRSJHØOXH
SROOLQWHUØO
5XLMLHFRQILJDSSOHWDFWLRQDFWLRQBFOLFRPPDQGHQDEOH
5XLMLHFRQILJDSSOHWDFWLRQDFWLRQBFOLFRPPDQGFRQILJXUHWHUPLQDO
5XLMLHFRQILJDSSOHWDFWLRQDFWLRQBFOLFRPPDQGFSXSURWHFWWSHBWSHSUL
5XLMLHFRQILJDSSOHWFRPPLW
5XLMLHFRQILJDSSOHWH[LW
```

ÏGQÐ

```
Q¸3¥VÆAÐPSVQP6VÐQPiocQ¸
```

parameter *counter-name*	ÿXÄÂD
entry-op *operator*	ÿ/ eq 1b ge õ1b gt õ le ã1b lt ã ne á1b
entry-val *entry-value*	ÿ/
entry-type { **value** | **increment** | **rate** }	ÈÃÿ6ã
poll-interval *poll-int-value*	ÈÂhÈA 5 /¦
exit-comb { **or** | **and** }	exit-op âexit-time ,XJdG2Ï
exit-op *operator*	6ÈÃÿ eq 1b ge õ1b gt õ le ã1b lt ã ne á1b
exit-val *exit-value*	6ÈÃÿ
exit-type { **value** | **increment** | **rate** }	6ÈÃÿ6ã
exit-time *exit-time-value*	¢9Þ,S6ÿ
average-factor *average-factor-value*	➢ **rate SÈ** poll-int-value ,Ì4Au<ó

Ë,Õ!5BÐ 5,ê!5B_Ê

ÏQ¸Ð SEM G!5Bã

Ë*ÊÐ **event interface parameter** øÞÕ

–Dá	Aê
input_errors	Number of damaged packets received
input_errors_crc	Number of packets received with CRC errors
input_errors_frame	Number of framing ERR packets received
input_errors_overrun	Number of overruns and resource errors
input_packets_dropped	Number of packets dropped from input Q
interface_resets	Number of times an interface has been reset
output_buffer_failures	Number of failed buffers
output_buffer_swappedout	Number of packets swapped to DRAM
output_errors	Number of packets errored on output
output_errors_underrun	Number of underruns on output
output_packets_dropped	Number of packets dropped from output Q
receive_broadcasts	Number of broadcast packets received
receive_giants	Number of too large packets received

receive_rate_bps	Interface receive rate in bits/sec
receive_rate_pps	Interface receive rate in pkts/sec
receive_runts	Number of too small packets received
receive_throttle	Number of times the receiver was disabled
reliability	Interface reliability as a fraction of 255
rxload	Receive rate as a fraction of 255
transmit_rate_bps	Interface transmit rate in bits/sec
transmit_rate_pps	Interface transmit rate in pkts/sec
txload	Transmit rate as a fraction of 255

EÈG!5B **exit-op ` exit-val** Á\_ **p** **9** **áE** **y4** **ADÆ** **exit-op ` exit-val 4** **exit-op ` entry-val 4** **exit-comb ` exit-time** G5BZ **exit-op ` exit-val** **exit-comb ¤ exit-op ` exit-val â exit-time** **exit-time** **exit-comb and** **C exit-op ` exit-val** E **exit-time** **exit-comb or** **exit-op** E**W exit-val ` 4** **exit-time** **6** Ã

Ã*¡X event G

G	*E

event tag *event-name* [**correlate** { **andnot** | **and** | **or** }] **none** [**sync** { **yes** [**default** *wait-time*] | **no** }]
no event tag *event-name*

10.18 event snmp

ü SEM G!5BG!5B,¥<,¥ snmp Ð5ÄQ¸X no 6ïûî8ûéX_Ê

event tag *event-name* [**correlate** { **andnot** | **and** | **or** }] **snmp oid** *oid-value* **get-type** { **exact** | **next** } **entry-op** *operator* **entry-val** *entry-value* **entry-type** { **value** | **increment** | **rate** } **poll-interval** *poll-int-value* [**exit-op** *operator* **exit-val** *exit-value* **exit-type** { **value** | **increment** | **rate** } [**exit-comb** { **or** | **and** } **exit-time** *exit-time-value*]] [**average-factor** *average-factor-value*]

no event tag *event-name*

Ï–DAêè

–D	ÆÄ
event-name	_Á
correlate { **andnot** | **and** | **or** }	Ä and ><ê or ><è andnot ><Ú
oid *oid-value*	¥ snmp oid
get-type { **exact** | **next** }	snmp ÐÑ¥Ð¬ get next Ð
entry-op *operator*	eq 1b ge ð1b gt ð le ñ1b lt ñ ne á1b
entry-val *entry-value*	
entry-type { **value** | **increment** | **rate** }	¥EWS*¡XD6ã
exit-comb { **or** | **and** }	exit-op â exit-time ,XJÆ2Ï
exit-op *operator*	eq 1b ge ð1b gt ð le ñ1b lt ñ ne á1b
exit-val *exit-value*	
exit-type { **value** | **increment** | **rate** }	6ã
exit-time *exit-time-value*	¢ Policy >¥G¸S6¡XÐÈ
average-factor *average-factor-value*	▸ rate S*è poll-int-value ,¡ê?Au<ó
poll-interval *poll-int-value*	Eèh 5 /¦

ï5,Õ!5BÐ 5,ê!5B_Ê

ïQ¸ê SEM G!5Bã

ïS*ô EÆG!5B **exit-op** ` **exit-val** á_ê4èÊp_èÉ9Ê

áE> „X¥ SNMP OID ,Xâ **exit-op ` exit-val 4**

6è entry-op ` entry-val 4

exit-comb ` exit-time G5BZ exit-op ` exit-val **exit-comb ¤ exit-op ` exit-val**

â exit-time 2È exit-time exit-comb and

exit-op ` exit-val E exit-time exit-comb or

exit-op E exit-val 4 exit-time

event G

G	*Eè
_snmp_oid	SNMP OID
_snmp_oid_delta_val	SNMP OID ,X
_snmp_oid_val	SNMP OID ,X

G!5B_Đ G!5B,¥ snmp oid `1.3.6.1.2.1.2.2.1.10.1` 10000

```
```

ÏGQÞ Q¸ 4 456.144129.4 0.48 ref538.38 456.14 0.48 0.48 ref538.38

ÏQþ SEM G!5Bã

ÏS*ð Ã*¡X event GÐ

G¤	*Ð
_snmp_notif_oid	Trap OID
_snmp_notif_oid_val	Trap OID ,X

ÏG!5B_Ð ,¥Aþ¥X oid 1.3.6.1.2.1.52.2.1 ,X trap ¥È oid ,Xð 1000 ¥*+9Ä

```
5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB
5XLMLHFRQILJDSSOHWHMQWWDJPRQLWRUBWUDSVQPSQRWLILFDWLRQRLGRSJW
RLGØO
5XLMLHFRQILJDSSOHWDFWLRQVVORJPVJKDMWUDSBVQPSBQRWLIBRLGØOXH
BVQPSBQRWLIBRLGBØO
5XLMLHFRQILJDSSOHWDFWLRQH[LW
5XLMLHFRQILJDSSOHWFRPPLW
5XLMLHFRQILJDSSOHWH[LW
```

ÏÎGQÞ

Q¸	Ð
smart manager applet	**nðþ¥** SEM 1*+9

ÏGÄð -

10.20 event snmp-object

ü SEM G!5Bð!5B,¥<,¥ snmp Í snmp Ð5,X get set getnext ÞÄÐQ¸X no 6ðÞ

ð8ÛÞÄX_Ð

event tag *event-name* [**correlate** { **andnot** | **and** | **or** }] **snmp-object** [**operate** { **get** | **getnext** | **set** }]

oid *oid-value* **type** *value* **istable** { **yes** | **no** } **skip** { **yes** | **no** }

no event tag *event-name*

Ï-DAð

ÜQþÐ SEM G!5Bã

Ü5*ÐÔ Ã*¡X event GÐ

G	*Ð
_snmp_oid	SNMP OID
_snmp_request_type	SNMP AÆO_
_snmp_value	SNMP AË

ÜG!5B_Ð ,¼ snmp oid 1.3.6.1.2.1.1.4 ,X

```
5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB
5XLMLHFRQILJDSSOHWHHMQWWDJPRQLWRUVQPSREMVQPSREMHFWRLGWSHRFWHW
5XLMLHFRQILJDSSOHWDFWLRQVVORJPVJBVQPSBRLGBVQPSBRLGBVQPSBUHTXHVWBWSH
BVQPSBUHTXHVWBWSHBVQPSBBOXHBVQPSBBOXH
5XLMLHFRQILJDSSOHWDFWLRQH[LW
5XLMLHFRQILJDSSOHWFRPPLW
5XLMLHFRQILJDSSOHWH[LW
```

ÏÎGQÞÐ

Q¸	Ð
smart manager applet	**nbþ** SEM 1*+9

ÜGÄÐ -

10.21 event syslog

ü SEM G!5B G!5B,¼ logÄQ¸X no 6

event tag *event-name* [**correlate** { **andnot** | **and** | **or** }] **syslog pattern** *regular-expression* [**priority** *priority-level*] [**occurs** *num-occurrences*] [**period** *period-value*] [**skip** { **yes** | **no** }]

no event tag *event-name*

Ï–DAÐ

–D	Ð
event-name	_
correlate { **andnot**	**and**	**or** }	nd ></ r ></ andnot ></J
pattern *regular-expression*	
priority *priority-level*	
occurs *num-occurrences*	
period *period-value*	*period-value* **occurs** **occurs**
skip { **yes**	**no** }	Syslog G!5B! yes , G!, Ax no

Ü5,Õ!5BÐ 5,Õ!5B_Ê

ÏQþÐ SEM G!5Bã

Ï*ÐÔ L!6 SEM ¥óÊ÷}È SEM s6ÃÕXÈ SEM Az<ÖK,XÃÑ Action Syslog
È¸ÕXÈÑ• Syslog #Ñ9È> Ä
+bQ¸ LÈ **pattern** Ð7ÈÃg9ÊÔSÈ4ÃØÈG0È
s0ÃÃÈÄ
Ã*¡X event GÈÐ

GÃ	*È
_syslog_msg	Syslog È
_syslog_priority	Syslog ,X4{ÿ

ÏG!5B_Ð ,¥pÎ,memory fail ÊÃÄ

```
5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB
5XLMLHFRQILJDSSOHWHM QWWDJPRQLWRUBORJVVORJSDWWHUQPHPRUIDLO
5XLMLHFRQILJDSSOHWDFWLRQVZWFKRM U
5XLMLHFRQILJDSSOHWFRPPLW
5XLMLHFRQILJDSSOHWH[LW
```

ÎÏGQÞÐ

Q¸	È Ä
smart manager applet	**nÎ¸X** SEM 1*+9

ÏGÄÃÐ -

10.22 event sysmon

` SEM G!5BÃ!5B,¥<,¥2ÏÈCÃÄÈQ¸X no 6ÃÏ68ÎÃÄX_Ê

event tag *event-name* [**correlate** { **andnot** | **and** | **or** }] **sysmon type** { **cpu** { **system** | **task** task-name } | **memory** { **system-use** | **system-free** | **task** task-name } { **percent** | **absolute** } } **entry-op** *operator* **entry-val** *entry-value* **poll-interval** *poll-int-value* [**exit-op** *operator* **exit-val** *exit-value*] [**slot** { *slot-num* | **slave** [**subsystem** *subsystem-id*] }]

no event

Ã*¡X event G÷Ë

G÷å	*Ëè
_timer_type	nÞ
_timer_time	nÞ
_timer_remain	nÞon 2O_nÊÃ÷GÅ

Ï!5B_Ð _ 1Önix ÊÈ 1257831095 G¦AÛ

```
5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB
5XLMLHFRQILJDSSOHWHMQWWDJPRQLWRUBWLPHUWLPHUDEVROXWHWLPH
5XLMLHFRQILJDSSOHWDFWLRQUHORDG
5XLMLHFRQILJDSSOHWFRPPLW
5XLMLHFRQILJDSSOHWH[LW
```

_ 2Ö600 /Ê600 second arrival

```
5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB
5XLMLHFRQILJDSSOHWHMQWWDJPRQLWRUBWLPHUWLPHUFRXQWGRZQWLPH
5XLMLHFRQILJDSSOHWDFWLRQVVORJPVJVHFRQGDUULØO
5XLMLHFRQILJDSSOHWFRPPLW
5XLMLHFRQILJDSSOHWH[LW
```

_ 3Ö 7200 ÈNÕ arp 4ç

```
5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB
5XLMLHFRQILJDSSOHWHMQWWDJPRQLWRUBWLPHUWLPHUHZWFKGRJWLPH
5XLMLHFRQILJDSSOHWDFWLRQFOLFRPPDQGHQDEOH
5XLMLHFRQILJDSSOHWDFWLRQFOLFRPPDQGFOHDUDUSFDFKH
5XLMLHFRQILJDSSOHWFRPPLW
5XLMLHFRQILJDSSOHWH[LW
```

_ 4Ö 0 ÈNCÃ

```
5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB
5XLMLHFRQILJDSSOHWHMQWWDJPRQLWRUBWLPHUWLPHUFRQFURQHQWU\
5XLMLHFRQILJDSSOHWDFWLRQFOLFRPPDQGHQDEOH
5XLMLHFRQILJDSSOHWDFWLRQFOLFRPPDQGFOHDULSURXWH
5XLMLHFRQILJDSSOHWFRPPLW
5XLMLHFRQILJDSSOHWH[LW
```

ÏÎGQÐ

Q¸	Ë:Ä
smart manager applet	**nÞ** SEM 1*+9

ÏGÄÈ -

10.24 list-config

ü SEM G!5BÈ1*+9,XG!5BÄ

list-config

Ï–DAèð

–D	ÆÄ
-	-

Ï5,Õ!5BÐ 5,Õ!5B

ÏQþÐ SEM G!5Bã

ÏS*ûÐ -

ÏG!5B_Ð -

ÏÎGQÞÐ

Q¸	ÆÄ
commit	**x19G5B**
rollback	**ÆÔ9G5B**

ÏGÄèð -

10.25 policy record

ü SEM G!5BÆ!5B4~) CLI > |,XEgÎG!5B CLI > |EgÎXGÄ

policy record [**per-instance** *record-size-per-policy*] [**per-policy** *record-size-per-policy*]

no policy record

Ï–DAèð

–D	ÆÄ
per-instance *record-size-per-policy*	**æX** CLI 4~)GÈ K +8VÈAx 50
per-policy *record-size-per-policy*	**19É¤** CLI 4~)kGÈ K +8VÈAx 1000

Ï5,Õ!5BÐ 5,ê~) CLI > |,XEgÎ

ÏQþÐ SEM G!5Bã

ÏS*ûÐ TAxÈEM 1*+9¸ CLI > |,XEgêA)È!5B **policy record É** CLI > |>¸•
> , X Êí ÈCLI > | , X E g Î Ú› •A „) A ’ Û[Ê2 Ï4 ³ ÄA „) [Ê¸X C ÃX ãV ßÖ
/sem_record/policy_name/yyyy-mm-dd_hh-mm-ss_mspolicytriggerid.txt È /sem_record/
Ý CLI > |,XEgÎA),X,ÆÈ[Ê¼³X,ÆÄpolicy_name 1*+9,XáèÈ
/sem_record/ ,ÆÈ*+9FÑÛÀX,ÆÄ
yyyy-mm-dd_hh-mm-ss_mspolicytriggerid.txtA),[ÊXá[ÊXá+A){*ôXÊÈ
!/ò1*+9ÆÆÄ
S*ü **more** ÆÆ
1*+9E¤ {*ôX CLI > |NMEgÊÈ›D per-instance record-size-per-policy È),[Ê

(Mn1*+9E¤ {*ôX CLI > |NMEgÂ¸[ÊKCÆ¥-D per-policy record-size-per-policy

ÆEQ¸ **smart manager policy record clean** CLI > |NMEgÂ¸[Ê

5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB
5XLMLHFRQILJDSSOHWHHMQWWDJQRQHHMQWQRQH
5XLMLHFRQILJDSSOHWDFWLRQFOLFRPPDQGHQDEOH
5XLMLHFRQILJDSSOHWDFWLRQFOLFRPPDQGVKRZUS
5XLMLHFRQILJDSSOHWSROLFUHFRUG
5XLMLHFRQILJDSSOHWFRPPLW
5XLMLHFRQILJDSSOHWH[LW
5XLMLHFRQILJH[LW
5XLMLHPRUHVHPBUHFRUG7HVWBBBW[W
6(0&5(25),/(
6(0SROLFQDPH7HVWB
6(0SROLFWULJJHULG
6(0SROLFFOLUHFRUGWLPH)UL-DQ

5XLMLHHQDEOH
5XLMLHVKRZUS
3URWRFROGGUHVV3HPLQ+DGZUH7SH,QWHUIDFH
P€000H000€000004P€000000@00<<70@E000@P€09Ä000@000000000

ÜQþð SEM G!5Bã

Ü5*Ûð -

ÜG!5B_Ð ÊÛ*+9G!5B_Ä

```
5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB
5XLMLHFRQILJDSSOHWHHMQWWDJQRQHHMQWQRQH
5XLMLHFRQILJDSSOHWDFWLRQVHWÐUBIRUBWHVW7HVWBUXQQLQJ
5XLMLHFRQILJDSSOHWUROOEDFN
5XLMLHFRQILJDSSOHWH[LW
```

ÏÜGQÞ

Q¸	ÊÄ
commit	**x19G5B**

ÜGÄãð -

10.27 show smart manager detector

(MßÝ<Ü

show smart manager detector [**all** | *detector-name*] [**detailed | statistics**]

Ï–DAãð

–D	ÊÄ
all | *detector-name*	(Mn,X,Ý<Ü
detailed	
statistics	

Ü5,Õ!5BÐ -

ÜQþð (Mã

Ü5*Ûð -

ÜG!5B_Ð _ 1Ö

VQPSQRWLILFDWLRQ
WLPHU
VQPSREMHFW

_ 2ȩ **show smart manager detector cli**

ъ‚Õ!5BÐ -

ÜQþ (Mã

Ъ*Ô AÐQ}¼GŁ

ÜG!5B_Ð _ 1þÖ **show smart manager environment** ÐQß

```
5XLMLHVKRZPDUWPDQDJHUHQYURQPHQW
1R1DPH9DOXH
ÐUBDÐOXHBD
ÐUBEÐOXHBE
```

_ 2þÖ **show smart manager environment all** ÐQß

```
5XLMLHVKRZPDUWPDQDJHUHQYURQPHQWDOO
1R1DPH9DOXH
ÐUBDÐOXHBD
ÐUBEÐOXHBE
```

_ 3þÖ **show smart manager environment** *var_a* ÐÀß

Ðß

```
5XLMLHVKRZPDUWPDQDJHUHQYURQPHQWÐUBD
ÐOXHBD
```

_ 4þÖ **show smart manager environment** *var_none*Ðß

```
5XLMLHVKRZPDUWPDQDJHUHQYURQPHQWÐUBQRQH
1RVXFKHQYURQPHQWÐULDEOHGHILQHG
```

ÏÎGQÞ

Q¸	Ł.Ä
smart manager environment	-

ÜGÄß -

10.29 show smart manager history events

(Mß SEM event ÐÆÄ

show smart manager history events [**detailed**] [**maximum** *number*]

Ï-DAß

–D	Ł.Ä
detailed	Ð€
maximum *number*	ÐÔG£

ъ‚Õ!5BÐ -

ÜQþ (Mã

Ï*Ð -

Ï!5B_Ð _ 1Ð **show smart manager history events ÑÑ**

Ï*Ð AÐQ¸É> EG!5B,X1*CÃ

ÜG!5B_Ð > **show smart manager policy all** ÐQß J State ></1*+9,XæÐß Policy Name ><
/1*+9,XáÄ

```
5XLMLHVKRWZPDUWPDQDJHUSROLFDOO
1R6WDWXV3ROLF1DPH
FRPPLW7HVWB
QRWFRPPLW7HVWB
```

ÏGQÐ

Q¸	EÄ
-	-

ÜGÄß -

10.31 show smart manager policy active

(MÐ¼#X1*+9r_Ä

show smart manager policy active [**class** *class-options*] [**detailed**]

Ï–DAß

–D	EÄ
class *class-options*	ß
detailed	ÐG

Ï,ÕG!5BÐ -

ÜQß (Mã

Ï*Ð AÐQ¸!7E¤ ,X1*+9r_Ä

Ü G!5B_Ð _ 1ÐÐ **show smart manager policy active** ÐQß

```
5XLMLHVKRWZPDUWPDQDJHUSROLFDFWLM
.HS3ULRULW1/RZ+LJK11RUPDO
66FKHGXOLQJPRGH6WLM33HQGLQJ

1R-RE,G366WDWXV7LPH2I(MQW(MQW7SH3ROLF1DPH
```

13SHQG:HG1RQRQH7HVWB

á È Class 1*+9,X2O ÿ Type 1*+9,X2O_È Event Type 1*+9,XOjbÊX2O_È Time Registered
1*+9¦¾ÊÄ

```
5XLMLHVKRWZPDUWPDQDJHUSROLFUHJLVWHUHG
1R1DPHQDVV7SH(HQW7SH7LPH5HJLVWHUHG
7HVWB$SSOHWWLPHU7KX2FW
HHQWBWLPHUZWFKGRJWLPH
DFWLRQVORJPVJ$WLRQB
DFWLRQZLW
DFWLRQVORJPVJ$WLRQB
```

ÏGQÞ

Q¸	Ä
smart manager applet	**nbX** SEM 1*+9

GÄ

-

10.34 show smart manager scheduler

(M¦¾)¦ß SEM Az<,XE¤ (

show smart manager scheduler thread

FDOVV%Ö

ÏÎGQÞ	Q¸	ÆÄ
	smart manager applet	**nÎbş¢X** SEM 1*+9

ÏGÄß -

10.35 show smart manager version

(Mß SEM ,X(Ä
show smart manager version

Ï–DAß	–D	ÆÄ
	-	-

Ï5,Ö!5BÐ -

ÏQÞ (Mã

ÏS*Ð -

ÏG!5B_Ð ¸ **show smart manager version** SEM Þ(È.Bn(
ø,Xs6Ñ

```
5XLMLHVKRZPDUWPDQDJHUHUVLRQ
6PDUW(PEHGGHG0DQDJHU9HUVLRQ
(HQWHWHFWRUV
QDPHHUVLRQ
DSSOLFDWLRQ
VVORJ
FOL
FRXQWHU
FSS
JUWG
LQWHUIDFH
QRQH
RLU
VQPS
VQPSREMHFW
VQPSQRWLILFDWLRQ
VVPRQ
WLPHU
```

ÏÎGQÞ	Q¸	ÆÄ
	-	-

ﯿ ، ﯿ ﺋ ،

، ﯿ ⁴ ﯿ SEM ﯿ ﭺ **commit** ﭽ Շ ﯿ

، ، ، ﯿ ﭢ ،

ﭢ ﯿ ، ،

ﭢ ﯿ ، ɀ ، ٩ ┬
∂

، ﯿ ɀ **rollback** ﭽ Շ ، ﯿ

SEM ، ⁴ SEM ، ╝ ﯿ ╋ ɀ
╟ ﯿ **smart manager policy bootup-delay**

، ﯿ SEM SEM tag ﮬ ﻕ ﻕ `
`

` ، ﯿ ` ک and

Ý Policy ŠǠ*¡X event ƓĐ

Ɠâ	*Ɇè
_event_id	ĺ⁹*+9_ẼX_ẺŶ ID
_event_type	ĺ⁹*+9,X_ẺŸ2O_ ID
_event_type_string	ĺ⁹*+9,X_ẺŸẺẼâ
_event_pub_time	_ẼX¥ẺŸÈ
_event_pub_sec	_ẼX¥ẺŸẼnix ẺẤ
_event_pub_msec	_ẼẺ

ƓG!5B_Đ _ 1ĚẼĐ Test_A ,XÎQ¸> ,X1*+9

```
5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB$
5XLMLHFRQILJDSSOHW
```

_ 2ĚẼĐ Test_B ,X1*+9ĚÚ*+9&O2OÿD Ä

```
5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB%FODVV'
5XLMLHFRQILJDSSOHW
```

ǐĨGQĐ

Q¸	ẼÄ
show smart manager policy registered	ẼẼ
smart manager policy bootup-delay	ẼB SEM 1*+9Êħ*¡XẺẤ

ƓÄĐ -

10.37 smart manager environment

ƂG!5BĐ SEM <ƓĄQ¸X no 6ẫŭ8û,X SEM <ƓĄ

smart manager environment *variable-name string*

no smart manager environment *variable-name*

Ï-DAê

–D	Ë Ä
variable-name	*n*
string	*n*

Ï,Õ!5BÐ 5,ê SEM <G£

Ù Ò <G!5Bã

Ï*Ð 6 X2O_F 0 ú G XKÞS*C.BnÄ
<G X1*+9S* 3 *+9nX FG *+9<
G ÐF G *Ä

Ù!5B_Ð _ 1è Ò variable_name variable_value ,X<G Ä
5XLMLHFRQILJVPDUWPDQDJHUHQWURQHQWULDEOHBQDPHULDEOHBOXH

ÎGQÞ

Q¸	Ë Ä
show smart manager environment	**Þ Ë**

Ù Äê -

10.38 smart manager history

ú G!5B !5B SEM Ø EXÔDG Ä Q¸X no 6 ü6 Ø EXÔ
DG Ä TAxÄ

smart manager history size events *size*

no smart manager history size events

Ï-DAê

–D	Ë Ä
events	Event Ø EXÔDG£
size	Ô 50 TAx 50

Ï,Õ!5BÐ TAx Event ÔDG£ 50

Ù Ò <G!5Bã

Ï*Ð

ˇ Ŋ 0 SEM ų Ŋ

Ù!5B_Ð G!5BSEM Event Ø DG£ 30
5XLMLHFRQILJVPDUWPDQDJHUKLVWRUVL]HHM QWV

ÏĈGQ¸Ð		
	Q¸	ÆÄ
	show smart manager history events	***/ ¸Ê***

ĞGÄ₿	-

10.39 smart manager policy bootup-delay

Ğ!5B₿!5BA5B SEM 1*+9Ê³ħ*¡ĶÊÃ

smart manager policy bootup-delay *dealy-time*

Ï-DA₿			
	–D	ÆÄ	ÂÅ>•€ @

Ï*Ð -

Ï!5B_Đ _ 1Đ8<F¼ +9,X CLI Egî~)Ï>±-,XÆ8,X1*+9,X CLI Egî~)Ä

```
5XLMLHVPDUWPDQDJHUSROLFUHFRUGFOHDQQRUHJLVWHG
```

_ 2Đ8<F¼ SEM 1*+9E¤ {*ðX CLI Egî~)

```
5XLMLHVPDUWPDQDJHUSROLFUHFRUGFOHDQDOO
```

ÎGQÐ

Q¸	Ë Ä
action cli	**x**
policy record	**G5B4)** CLI > |,XEgî~)

ÏGÄð -

10.41 smart manager run

(Mð¤ KÝ none 2O_,X_ÊX1*+9Ä

smart manager run *policy-name* [*parameter*]

Ï-DAð

–D	Ë Ä
policy-name	none 2O_,X_ÊX1*+9,Xá
parameter	ð 5 þ

Ï,Ï!5BÐ 5,Ð¤

ÒÇð (Mã

Ï*Ð -

Ï!5B_Đ G!5Bnone 2O_,X eventÊÄ Test_1ð¸Ä

```
5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB
5XLMLHFRQILJDSSOHWHHMQWWDJPRQLWRUBFPGQRQH
5XLMLHFRQILJDSSOHWDFWLRQVVORJPVJQRQHHMQWWULJJHUHGZWKBQRQHBDUJFDUJF
5XLMLHFRQILJDSSOHWFRPPLW
5XLMLHFRQILJDSSOHWH[LW
```

ÎGQÐ

Q¸	Ë Ä
smart manager applet	**nb** SEM 1*+9

ÏGÄð -

10.42 smart manager scheduler

ëG!5B6!5B SEM 1*+92Oÿ X4ƒ‚A5B4ƒ‚,XÄ¢Q¸X no 6‚Ò6á SEM 1*+94ƒ‚TAxÄ

smart manager scheduler thread class *class-options* **number** *thread-number*

no smart manager scheduler thread class *class-options*

Ï–DAß

ẗQ₫Đ (Mã

ẗ5*ĐĐ -

ẗG!5B_Đ _ 1ĐNỷOý

5XLMLHVPDUWPDQDJHUVFKHGXOHUFOHDUDOO

_ 2ĐNÝ class BÈ

10.45 smart manager scheduler modify

(MB‹{Ä

smart manager scheduler modify class *class-options* **queue-priority** { **high** | **low** | **normal** }

Ï-DAß	–D	E Ä
	class *class-options*	*b*

	smart manager applet	**nbş**	SEM 1*+9

ÜGÄß -

10.47 smart manager scheduler suspend

ü¢G!5Bß SEM AzÖKÄQ¸X no 6ßü6á SEM AzÄ

smart manager scheduler suspend

no smart manager scheduler suspend

Ï-DAß

correlate-start *period-start-value*	Cron
correlate-period *correlate-period-value*	60
delay *delay-value*	0
maxrun *maxruntime-number*	20

ъ‚Õ!5BÐ 5,ê!5B trigger

ÜÇþ SEM G!5Bã

Ъ*ê -

Ü!5B_Ð ûï1*+9 Test_1 >ê³ 10 /Ę¤

```
5XLMLHFRQILJVPDUWPDQDJHUDSSOHW7HVWB
5XLMLHFRQILJDSSOHWHMQWWDJQRQHHMQWQRQH
5XLMLHFRQILJDSSOHWWULJJHUGHOD\
5XLMLHFRQILJDSSOHWFRPPLW
5XLMLHFRQILJDSSOHWH[LW
```

ÏÎGQÞ

Q¸	Ę
smart manager applet	**nbş** SEM 1*+9

ÜÄê -