

Profile

752 MAP 1

OFF

SATA

Bypass

RG-MAP752(T)

III

Ч Ч Ч

Ч Ч Ч III



III

III

Ч III Ч III
III III
III III
III III
III III

III

¶

¶

III

III

III

<http://www.ruijie.com.cn/>

<http://webchat.ruijie.com.cn>

<http://www.ruijie.com.cn/service.aspx>

7 × 24

4008-111-000

<http://bbs.ruijie.com.cn/portal.php>

1

1.1

RG-MAP752(T)		+1.0	AP		ч				
		III	802.11ac			AM		24	
Radio	24	2.4G	5G		600M	+			
14.4G				III	RG-MAP752(T)			ч	
ч	ч	ч			ч	III			

1.2

1.2.1 RG-MAP752(T)

RG-MAP752(T)										
	802.11b/g/n 802.11a/n/ac									
	802.11b/g/n 2.4G ~ 2.4835GHz 802.11a/n/ac 5G 5.150 5.350GHz 5.47 5.725 5.725 5.850GHz (									
	2.4G ч 5G									
	2.4G 450Mbps 5G 867Mbps III 1.317Gbps III									
	OFDM BPSK@6/9Mbps QPSK@12/18Mbps 16-QAM@24Mbps 64-QAM@48/54Mbps DSSS DBPSK@1Mbps DQPSK@2Mbps and CCK@5.5/11Mbps MIMO-OFDM BPSK QPSK 16QAM 64QAM and 256QAM									
	23dBm III									
	1dBm									
	SPI Flash 256Mbit DDR2 1Gb									
	86*160*29.88mm × ×									
	250g()									
	1	10/100/1000Base-T		4	10/100/1000Base-T		1	10/100Base-T		
			4W	1	Micro usb console					
	AP AP									
	IP41									
	-10 ° C 45 ° C -40 ° C 70 ° C 5 95 5 95									
	8W									
	GB4943 ч EN60950-1 ч IEC60950-1									

EMC	GB9254 Ч GB17618 Ч EN301 489-1 Ч EN301 489-17 Ч EN55022 Ч EN55024
Health	EN 62311
	Ч EN300 328 Ч EN301 893



1.2.1.1 RG-MAP752(T)

RG-MAP752(T) 1 Ч 4 Ч 1 24V III



1.	—LAN	2.	—
3.	LAN 2	4.	LAN 3
5.	LAN 4	6.	LAN 5
7. Micro Usb Console			

1 RG-MAP752(T)



AM

WAN

AM

1.3RG-MAP752(T)

RG-MAP752(T)

USB

III

AP

Led

III

1 LED

		AP III
	0.4s 0.4s (45s)	AP 45s AP 45s III 5 III III
	90s	AP 90s III 90sIII
	2s 2s	AP AP III

2

2.1

RG-MAP752(T) III

RG-MAP752(T) III



£


2.2

		ч	ч		III	
III		ч	ч	ч		RG-MAP752 T
	2-2III					
2-2						

3



3.1



:

,

15

3.2


AP

4


4

3.3

86




WAN





RG-MAP752(T)

86



MAP752(T)





4

4.1

AM RG-MAP752(T) III

4.2

4.2.1

AM RG-MAP752(T)III

4.2.2

AP

III

5

5.1

AP

III

45s 0.4s 0.4s (45s) AP 45s III
 AP III 5 III AP
 III AP 90s AP 90s III 90s
 III (2s 2s) AP AP
 4 (3.8s 0.2s) AP AP III
 0.4s 0.4s LED ON APIII

5.2

RG-MAP752(T)

AP

AC

III

5.3

RG-MAP752(T)

1)

III




œ



œ

6

6.1



6.2

1

2


LED

RG-MAP752(T)					
AP		AP			
3		AP			
	III				
AP	III				
		AP	III		
	RG-MAP752(T)	æ	æ	£	

A

1000BASE-T/100BASE-TX/10BASE-T

1000BASE-T/100BASE-TX/10BASE-T			MDI/MDIX Crossover		
III1000BASE-T	IEEE 802.3ab		100-ohm	5	UTP
STP	STP	100	III1000BASE-T	4	
4	III1000BASE-T		A-1		
A- 1 1000BASE-T					



100BASE-TX/10BASE-T		10Mbps	100-ohm	3,4,5	100Mbps
100-ohm	5	100	III	100BASE-TX/10BASE-T	
A-2:					
A- 2100BASE-TX/10BASE-T					



100BASE-TX/10BASE-T , A-3

A- 3 100BASE-TX/10BASE-T

非总线	总线	总线	总线	总线
1	2	3	4	5
1 IRD+	1 IRD+	1 OTD+	1 IRD+	
2 IRD-	2 IRD-	2 OTD-	2 IRD-	
3 IRD+	3 IRD+	3 OTD+	3 IRD+	
4 IRD-	4 IRD-	4 OTD-	4 IRD-	

B —RG-MAP752(T)

1	RG-MAP752(T)	1	
2		1	
3	M4*40	2	
4		1	