

RG-S5750-S Ƨ̃ ρ 'O ū ǿ W ʎ é j ù

Contents

V
V
V
V
V
V

v t „ Q 1 9 σ

1 α Η β ß È ä | ∫ ∩ 1

Ruijie# write

Building configuration...

Write to boot config file: [/config.text]

Contents

V
V
V
V
V
V
V

```
Ctrl Version: RGOS 10.4(3b16) Release(146430)
MTD_DRIVER-5-MTD_NAND_FOUND: 1 NAND chips(chip size : 134217728) detected
1 nand chip(s) found on the target.
Press Ctrl+C to enter Ctrl ...
```

```
//ǎ, ъ ȳ log"Y ^ 'Q ε ̈n ȳ3sЛ 'l i ctrl+c ε p'O ū и ч dCTRL ↑
```

Hot Commands:

Ctrl>^C

Ctrl>^C

```
Ctrl>rename config.text config.bak
```

```
Ctrl>load // ! p'O ū
```

Β τ 1 η Τ ε ε ∫ ! n ο n e γ λ σ

```
Ruijie#copy flash:config.bak flash:config.text
```

Ruijie#copy

Contents

V
V
V
V
V
V

$$\tau' \vee \underline{u}_9 \quad \sigma$$

RGOS

Ruijie#copy

Contents

V
V
V
V
V
V



v j l i σ

'

,

'

,

,

Ruijie#show tempr

Device-1:

Current Tempr: 29.0 C

Ã £ ĩ ŵ ʌ Æ ʌ ĭ

Ruijie

v ∫ ~ T ° σ

		指示灯灭	端口未 Link
1000M Link Up			绿色常亮
1000M 数据收发	1000Mbps RJ-45 接口指示	1-24	绿色闪烁
100/10M Link Up			黄灯常亮
100/10M 数据收发			黄灯闪烁

Ruijie#show fans

Device-1:

Item	Status	Serial Number		Ver	Speed
1	Normal	-	-	1	//normal
2	Normal	-	-	1	

Ã £ ĩ ŵ ㄣÆㄣ

Ruijie



v CPU • v V à Ì Û ä 2 Â K 3 °) T ¿ ! € \$ ñ † A ' 0 L

• b °

,

,



ν $\mathcal{L}$ $\tilde{E}_\nu$ ν Ψ τ σ

,

v ð Å ° ÿ σ

```
Ruijie#show interfaces counters
```

```
Interface : GigabitEthernet 0/1
```

```
5 minutes input rate :1034 bits/sec, 1 packets/sec
```

```
5 minutes output rate :65 bits/sec, 0 packets/sec
```

```
InOctets      : 8918550
```

```
InUcastPkts   : 4
```

```
InMulticastPkts : 103298
```

```
InBroadcastPkts : 0
```

```
OutOctets     : 524352
```

```
OutUcastPkts  : 4
```

```
OutMulticastPkts : 2298
```

```
OutBroadcastPkts : 0
```

```
Undersize packets : 0
```

```
Oversize packets : 0
```

```
collisions      : 0
```

```
Fragments       : 0
```

```
Jabbers         : 0
```

```
CRC alignment errors : 0
```

```
AlignmentErrors  : 0
```

```
FCSErrors        : 0
```

```
dropped packet events (due to lack of resources): 0
```

```
packets received of length (in octets):
```



v Ѡ ѡ ı σ

‘

’

’

Ǻ £ ı ǫ ı æ ı

Ruile

Contents

V
V
V
V
V
V

ℳ σ

U σ

· $\tau \leftarrow \sigma$

♪ σ

U $\vdash$ σ

• $\top \leftarrow \sigma$

ℳ σ

U ⊢ σ

· $\tau \leftarrow \sigma$

♪ σ

U † σ

• $\top \leftarrow \sigma$

ℳ σ

U ⊢ σ

• $\top \leftarrow \sigma$





6

,

,

,

,

,

Ruile



၇ ၊ ဘီဗီ

†

†

†

†

†
